

TEST DATA OF MGFS402412

Regulated DC Power Supply

December 3, 2018

Approved by : Junichi Hatagishi Design Manager

Prepared by : Shohei Mukaide
Shohei Mukaide Design Engineer



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Overvoltage Protection	18
19.Switching frequency (by Load Current)	19
20.Figure of Testing Circuitry	20

(Final Page 20)

COSEL

Model	MGFS402412																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	—	—	—																																																																															
1.Graph			2.Values																																																																															
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>7.6</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>7.8</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>8.0</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>8.2</td><td>0.054</td><td>2.785</td><td>-※</td></tr> <tr><td>8.4</td><td>0.053</td><td>2.718</td><td>-※</td></tr> <tr><td>8.6</td><td>0.052</td><td>2.717</td><td>-※</td></tr> <tr><td>8.8</td><td>0.051</td><td>2.646</td><td>-※</td></tr> <tr><td>9.0</td><td>0.050</td><td>2.580</td><td>-※</td></tr> <tr><td>12.0</td><td>0.041</td><td>1.879</td><td>-※</td></tr> <tr><td>18.0</td><td>0.032</td><td>1.238</td><td>2.508</td></tr> <tr><td>24.0</td><td>0.020</td><td>0.940</td><td>1.854</td></tr> <tr><td>36.0</td><td>0.015</td><td>0.632</td><td>1.232</td></tr> <tr><td>40.0</td><td>0.014</td><td>0.572</td><td>1.115</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	7.6	0.004	0.004	-※	7.8	0.004	0.004	-※	8.0	0.004	0.004	-※	8.2	0.054	2.785	-※	8.4	0.053	2.718	-※	8.6	0.052	2.717	-※	8.8	0.051	2.646	-※	9.0	0.050	2.580	-※	12.0	0.041	1.879	-※	18.0	0.032	1.238	2.508	24.0	0.020	0.940	1.854	36.0	0.015	0.632	1.232	40.0	0.014	0.572	1.115	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
7.6	0.004	0.004	-※																																																																															
7.8	0.004	0.004	-※																																																																															
8.0	0.004	0.004	-※																																																																															
8.2	0.054	2.785	-※																																																																															
8.4	0.053	2.718	-※																																																																															
8.6	0.052	2.717	-※																																																																															
8.8	0.051	2.646	-※																																																																															
9.0	0.050	2.580	-※																																																																															
12.0	0.041	1.879	-※																																																																															
18.0	0.032	1.238	2.508																																																																															
24.0	0.020	0.940	1.854																																																																															
36.0	0.015	0.632	1.232																																																																															
40.0	0.014	0.572	1.115																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>			<p>※During this area, overcurrent protection activates and power supply operates in hiccup mode.</p>																																																																															

COSEL

Model	MGFS402412																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.050</td><td>0.041</td><td>0.032</td><td>0.020</td><td>0.015</td></tr> <tr><td>0.68</td><td>1.023</td><td>0.773</td><td>0.518</td><td>0.394</td><td>0.271</td></tr> <tr><td>1.36</td><td>2.007</td><td>1.499</td><td>1.001</td><td>0.755</td><td>0.513</td></tr> <tr><td>1.70</td><td>2.580</td><td>1.879</td><td>1.238</td><td>0.940</td><td>0.632</td></tr> <tr><td>2.04</td><td>3.004</td><td>2.230</td><td>1.483</td><td>1.116</td><td>0.751</td></tr> <tr><td>2.38</td><td>3.546</td><td>2.627</td><td>1.735</td><td>1.300</td><td>0.872</td></tr> <tr><td>2.72</td><td>-※1</td><td>3.009</td><td>1.980</td><td>1.482</td><td>0.995</td></tr> <tr><td>3.40</td><td>-※1</td><td>-※2</td><td>2.508</td><td>1.854</td><td>1.232</td></tr> <tr><td>3.74</td><td>-※1</td><td>-※2</td><td>2.757</td><td>2.050</td><td>1.369</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.050	0.041	0.032	0.020	0.015	0.68	1.023	0.773	0.518	0.394	0.271	1.36	2.007	1.499	1.001	0.755	0.513	1.70	2.580	1.879	1.238	0.940	0.632	2.04	3.004	2.230	1.483	1.116	0.751	2.38	3.546	2.627	1.735	1.300	0.872	2.72	-※1	3.009	1.980	1.482	0.995	3.40	-※1	-※2	2.508	1.854	1.232	3.74	-※1	-※2	2.757	2.050	1.369	--	-	-	-	-	-	--	-	-	-	-	-					
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	0.050	0.041	0.032	0.020	0.015																																																																													
0.68	1.023	0.773	0.518	0.394	0.271																																																																													
1.36	2.007	1.499	1.001	0.755	0.513																																																																													
1.70	2.580	1.879	1.238	0.940	0.632																																																																													
2.04	3.004	2.230	1.483	1.116	0.751																																																																													
2.38	3.546	2.627	1.735	1.300	0.872																																																																													
2.72	-※1	3.009	1.980	1.482	0.995																																																																													
3.40	-※1	-※2	2.508	1.854	1.232																																																																													
3.74	-※1	-※2	2.757	2.050	1.369																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.050</td><td>0.041</td><td>0.032</td><td>0.020</td><td>0.015</td></tr> <tr><td>0.68</td><td>1.023</td><td>0.773</td><td>0.518</td><td>0.394</td><td>0.271</td></tr> <tr><td>1.36</td><td>2.007</td><td>1.499</td><td>1.001</td><td>0.755</td><td>0.513</td></tr> <tr><td>1.70</td><td>2.580</td><td>1.879</td><td>1.238</td><td>0.940</td><td>0.632</td></tr> <tr><td>2.04</td><td>3.004</td><td>2.230</td><td>1.483</td><td>1.116</td><td>0.751</td></tr> <tr><td>2.38</td><td>3.546</td><td>2.627</td><td>1.735</td><td>1.300</td><td>0.872</td></tr> <tr><td>2.72</td><td>-※1</td><td>3.009</td><td>1.980</td><td>1.482</td><td>0.995</td></tr> <tr><td>3.40</td><td>-※1</td><td>-※2</td><td>2.508</td><td>1.854</td><td>1.232</td></tr> <tr><td>3.74</td><td>-※1</td><td>-※2</td><td>2.757</td><td>2.050</td><td>1.369</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.050	0.041	0.032	0.020	0.015	0.68	1.023	0.773	0.518	0.394	0.271	1.36	2.007	1.499	1.001	0.755	0.513	1.70	2.580	1.879	1.238	0.940	0.632	2.04	3.004	2.230	1.483	1.116	0.751	2.38	3.546	2.627	1.735	1.300	0.872	2.72	-※1	3.009	1.980	1.482	0.995	3.40	-※1	-※2	2.508	1.854	1.232	3.74	-※1	-※2	2.757	2.050	1.369	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	0.050	0.041	0.032	0.020	0.015																																																																													
0.68	1.023	0.773	0.518	0.394	0.271																																																																													
1.36	2.007	1.499	1.001	0.755	0.513																																																																													
1.70	2.580	1.879	1.238	0.940	0.632																																																																													
2.04	3.004	2.230	1.483	1.116	0.751																																																																													
2.38	3.546	2.627	1.735	1.300	0.872																																																																													
2.72	-※1	3.009	1.980	1.482	0.995																																																																													
3.40	-※1	-※2	2.508	1.854	1.232																																																																													
3.74	-※1	-※2	2.757	2.050	1.369																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note: Slanted line shows the range of the rated load current.	<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current. ※2 Maximum output current at 12V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																	

COSEL


Model	MGFS402412																																																																																	
Item	Input Power (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.46</td><td>0.49</td><td>0.58</td><td>0.48</td><td>0.52</td></tr> <tr><td>0.68</td><td>9.29</td><td>9.31</td><td>9.34</td><td>9.48</td><td>9.78</td></tr> <tr><td>1.36</td><td>18.09</td><td>18.04</td><td>18.10</td><td>18.19</td><td>18.51</td></tr> <tr><td>1.70</td><td>22.60</td><td>22.45</td><td>22.41</td><td>22.49</td><td>22.79</td></tr> <tr><td>2.04</td><td>27.23</td><td>26.95</td><td>26.80</td><td>26.84</td><td>27.10</td></tr> <tr><td>2.38</td><td>31.97</td><td>31.54</td><td>31.26</td><td>31.24</td><td>31.44</td></tr> <tr><td>2.72</td><td>-※1</td><td>36.19</td><td>35.77</td><td>35.68</td><td>35.84</td></tr> <tr><td>3.40</td><td>-※1</td><td>-※2</td><td>44.96</td><td>44.74</td><td>44.77</td></tr> <tr><td>3.74</td><td>-※1</td><td>-※2</td><td>49.66</td><td>49.33</td><td>49.28</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.46	0.49	0.58	0.48	0.52	0.68	9.29	9.31	9.34	9.48	9.78	1.36	18.09	18.04	18.10	18.19	18.51	1.70	22.60	22.45	22.41	22.49	22.79	2.04	27.23	26.95	26.80	26.84	27.10	2.38	31.97	31.54	31.26	31.24	31.44	2.72	-※1	36.19	35.77	35.68	35.84	3.40	-※1	-※2	44.96	44.74	44.77	3.74	-※1	-※2	49.66	49.33	49.28	--	-	-	-	-	-	--	-	-	-	-	-					
Load Current [A]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	0.46	0.49	0.58	0.48	0.52																																																																													
0.68	9.29	9.31	9.34	9.48	9.78																																																																													
1.36	18.09	18.04	18.10	18.19	18.51																																																																													
1.70	22.60	22.45	22.41	22.49	22.79																																																																													
2.04	27.23	26.95	26.80	26.84	27.10																																																																													
2.38	31.97	31.54	31.26	31.24	31.44																																																																													
2.72	-※1	36.19	35.77	35.68	35.84																																																																													
3.40	-※1	-※2	44.96	44.74	44.77																																																																													
3.74	-※1	-※2	49.66	49.33	49.28																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.46</td><td>0.49</td><td>0.58</td><td>0.48</td><td>0.52</td></tr> <tr><td>0.68</td><td>9.29</td><td>9.31</td><td>9.34</td><td>9.48</td><td>9.78</td></tr> <tr><td>1.36</td><td>18.09</td><td>18.04</td><td>18.10</td><td>18.19</td><td>18.51</td></tr> <tr><td>1.70</td><td>22.60</td><td>22.45</td><td>22.41</td><td>22.49</td><td>22.79</td></tr> <tr><td>2.04</td><td>27.23</td><td>26.95</td><td>26.80</td><td>26.84</td><td>27.10</td></tr> <tr><td>2.38</td><td>31.97</td><td>31.54</td><td>31.26</td><td>31.24</td><td>31.44</td></tr> <tr><td>2.72</td><td>-※1</td><td>36.19</td><td>35.77</td><td>35.68</td><td>35.84</td></tr> <tr><td>3.40</td><td>-※1</td><td>-※2</td><td>44.96</td><td>44.74</td><td>44.77</td></tr> <tr><td>3.74</td><td>-※1</td><td>-※2</td><td>49.66</td><td>49.33</td><td>49.28</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Input Power [W]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	0.46	0.49	0.58	0.48	0.52	0.68	9.29	9.31	9.34	9.48	9.78	1.36	18.09	18.04	18.10	18.19	18.51	1.70	22.60	22.45	22.41	22.49	22.79	2.04	27.23	26.95	26.80	26.84	27.10	2.38	31.97	31.54	31.26	31.24	31.44	2.72	-※1	36.19	35.77	35.68	35.84	3.40	-※1	-※2	44.96	44.74	44.77	3.74	-※1	-※2	49.66	49.33	49.28	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Power [W]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	0.46	0.49	0.58	0.48	0.52																																																																													
0.68	9.29	9.31	9.34	9.48	9.78																																																																													
1.36	18.09	18.04	18.10	18.19	18.51																																																																													
1.70	22.60	22.45	22.41	22.49	22.79																																																																													
2.04	27.23	26.95	26.80	26.84	27.10																																																																													
2.38	31.97	31.54	31.26	31.24	31.44																																																																													
2.72	-※1	36.19	35.77	35.68	35.84																																																																													
3.40	-※1	-※2	44.96	44.74	44.77																																																																													
3.74	-※1	-※2	49.66	49.33	49.28																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※1 Maximum output current at minimum input Voltage is 70% of rated load current. ※2 Maximum output current at 12V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFS402412
Item	Efficiency (by Input Voltage)
Object	—

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8.5	90.5	89.2
9.0	90.8	89.8
12.0	91.4	90.7
15.0	91.5	91.4
18.0	91.5	91.9
24.0	91.2	92.0
30.0	90.5	91.9
36.0	89.8	91.7
40.0	89.3	91.5

※1: Load 70%

※2: Load 80%

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	MGFS402412																																																																																	
Item	Efficiency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object	<hr/>																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 9V - - □ - - Input Volt. 12V - - * - - Input Volt. 18V - - ○ - - Input Volt. 24V - - ◇ - - Input Volt. 36V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.68</td><td>88.3</td><td>88.1</td><td>87.7</td><td>86.4</td><td>83.5</td></tr> <tr> <td>1.36</td><td>90.7</td><td>90.9</td><td>90.6</td><td>90.1</td><td>88.4</td></tr> <tr> <td>1.70</td><td>90.8</td><td>91.4</td><td>91.5</td><td>91.2</td><td>89.8</td></tr> <tr> <td>2.04</td><td>90.4</td><td>91.3</td><td>91.8</td><td>91.6</td><td>90.7</td></tr> <tr> <td>2.38</td><td>89.8</td><td>91.0</td><td>91.8</td><td>91.9</td><td>91.2</td></tr> <tr> <td>2.72</td><td>-※1</td><td>90.7</td><td>91.7</td><td>91.9</td><td>91.5</td></tr> <tr> <td>3.40</td><td>-※1</td><td>-※2</td><td>91.9</td><td>92.0</td><td>91.7</td></tr> <tr> <td>3.74</td><td>-※1</td><td>-※2</td><td>90.9</td><td>91.6</td><td>91.5</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.00	-	-	-	-	-	0.68	88.3	88.1	87.7	86.4	83.5	1.36	90.7	90.9	90.6	90.1	88.4	1.70	90.8	91.4	91.5	91.2	89.8	2.04	90.4	91.3	91.8	91.6	90.7	2.38	89.8	91.0	91.8	91.9	91.2	2.72	-※1	90.7	91.7	91.9	91.5	3.40	-※1	-※2	91.9	92.0	91.7	3.74	-※1	-※2	90.9	91.6	91.5	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.68	88.3	88.1	87.7	86.4	83.5																																																																													
1.36	90.7	90.9	90.6	90.1	88.4																																																																													
1.70	90.8	91.4	91.5	91.2	89.8																																																																													
2.04	90.4	91.3	91.8	91.6	90.7																																																																													
2.38	89.8	91.0	91.8	91.9	91.2																																																																													
2.72	-※1	90.7	91.7	91.9	91.5																																																																													
3.40	-※1	-※2	91.9	92.0	91.7																																																																													
3.74	-※1	-※2	90.9	91.6	91.5																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	※1 Maximum output current at minimum input Voltage is 70% of rated load current. ※2 Maximum output current at 12V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFS402412
Item	Line Regulation
Object	+12V3.4A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.5	12.079	- ※1
9.0	12.078	- ※1
12.0	12.076	- ※2
15.0	12.073	12.075
18.0	12.073	12.075
24.0	12.069	12.072
30.0	12.064	12.071
36.0	12.061	12.066
40.0	12.057	12.066

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 12V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS402412																																																																																	
Item	Load Regulation																																																																																	
Object	+12V3.4A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																	
Temperature Testing Circuitry	25°C Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.080</td><td>12.075</td><td>12.071</td><td>12.076</td><td>12.081</td></tr> <tr><td>0.68</td><td>12.079</td><td>12.075</td><td>12.071</td><td>12.067</td><td>12.061</td></tr> <tr><td>1.36</td><td>12.078</td><td>12.076</td><td>12.072</td><td>12.069</td><td>12.059</td></tr> <tr><td>1.70</td><td>12.078</td><td>12.076</td><td>12.073</td><td>12.069</td><td>12.061</td></tr> <tr><td>2.04</td><td>12.077</td><td>12.076</td><td>12.073</td><td>12.070</td><td>12.063</td></tr> <tr><td>2.38</td><td>12.077</td><td>12.075</td><td>12.073</td><td>12.071</td><td>12.064</td></tr> <tr><td>2.72</td><td>-※1</td><td>12.075</td><td>12.074</td><td>12.071</td><td>12.065</td></tr> <tr><td>3.40</td><td>-※1</td><td>-※2</td><td>12.075</td><td>12.072</td><td>12.066</td></tr> <tr><td>3.74</td><td>-※1</td><td>-※2</td><td>12.074</td><td>12.072</td><td>12.067</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	12.080	12.075	12.071	12.076	12.081	0.68	12.079	12.075	12.071	12.067	12.061	1.36	12.078	12.076	12.072	12.069	12.059	1.70	12.078	12.076	12.073	12.069	12.061	2.04	12.077	12.076	12.073	12.070	12.063	2.38	12.077	12.075	12.073	12.071	12.064	2.72	-※1	12.075	12.074	12.071	12.065	3.40	-※1	-※2	12.075	12.072	12.066	3.74	-※1	-※2	12.074	12.072	12.067	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	12.080	12.075	12.071	12.076	12.081																																																																													
0.68	12.079	12.075	12.071	12.067	12.061																																																																													
1.36	12.078	12.076	12.072	12.069	12.059																																																																													
1.70	12.078	12.076	12.073	12.069	12.061																																																																													
2.04	12.077	12.076	12.073	12.070	12.063																																																																													
2.38	12.077	12.075	12.073	12.071	12.064																																																																													
2.72	-※1	12.075	12.074	12.071	12.065																																																																													
3.40	-※1	-※2	12.075	12.072	12.066																																																																													
3.74	-※1	-※2	12.074	12.072	12.067																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 12V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																	



COSEL

Model	MGFS402412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V3.4A		



Input Volt. 24 V
 Cycle 100 ms





Min.Load (0A)↔
 Load 100% (3.4A)



Min.Load (0A)↔
 Load 50% (1.7A)



Load 50% (1.7A)↔
 Load 100% (3.4A)



COSEL


Model	MGFS402412																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+12V3.4A																																							
1.Graph																																								
<p>Input Volt. 9V Input Volt. 36V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 9 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>15</td><td>15</td></tr> <tr> <td>0.68</td><td>5</td><td>5</td></tr> <tr> <td>1.36</td><td>5</td><td>5</td></tr> <tr> <td>2.04</td><td>20</td><td>10</td></tr> <tr> <td>2.38</td><td>25</td><td>10</td></tr> <tr> <td>2.72</td><td>- *</td><td>10</td></tr> <tr> <td>3.40</td><td>- *</td><td>5</td></tr> <tr> <td>3.74</td><td>- *</td><td>10</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 9 [V]	Input Volt. 36 [V]	0.00	15	15	0.68	5	5	1.36	5	5	2.04	20	10	2.38	25	10	2.72	- *	10	3.40	- *	5	3.74	- *	10	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 9 [V]	Input Volt. 36 [V]																																						
0.00	15	15																																						
0.68	5	5																																						
1.36	5	5																																						
2.04	20	10																																						
2.38	25	10																																						
2.72	- *	10																																						
3.40	- *	5																																						
3.74	- *	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								
<p>* Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																								

COSEL

Model	MGFS402412
Item	Ripple-Noise
Object	+12V3.4A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.
 Ripple-Noise is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.00	15	20
0.68	10	10
1.36	20	15
2.04	25	15
2.38	35	20
2.72	-	20
3.40	-	25
3.74	-	35
--	-	-
--	-	-
--	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGFS402412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V3.4A

Testing Circuitry Figure B

1. Graph



2. Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	20
-40	10	20
-20	10	15
25	10	10
60	10	10
85	5	10
--	--	--
--	--	--
--	--	--
--	--	--
--	--	--

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGFS402412
Item	Ambient Temperature Drift
Object	+12V3.4A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-60	11.977	11.980	11.981	11.981	11.976
-40	12.009	12.011	12.012	12.012	12.007
-20	12.034	12.035	12.037	12.036	12.031
0	12.054	12.055	12.056	12.055	12.049
25	12.071	12.072	12.075	12.072	12.066
65	12.082	12.082	12.080	12.078	12.073
75	12.084	12.084	12.081	12.079	12.074
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of input Volt.9V, Load 70%.
12V, Load 80%.
Other case Load 100%.



Model	MGFS402412	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V3.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 65°C

Input Voltage : 9 - 36V

Load Current : 0 - 3.4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	65	36	0	12.089	± 45	± 0.4
Minimum Voltage	-40	18	0	12.000		


COSEL

Model	MGFS402412	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V3.4A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.072</td></tr> <tr><td>0.5</td><td>12.078</td></tr> <tr><td>1.0</td><td>12.078</td></tr> <tr><td>2.0</td><td>12.078</td></tr> <tr><td>3.0</td><td>12.078</td></tr> <tr><td>4.0</td><td>12.078</td></tr> <tr><td>5.0</td><td>12.078</td></tr> <tr><td>6.0</td><td>12.078</td></tr> <tr><td>7.0</td><td>12.078</td></tr> <tr><td>8.0</td><td>12.078</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.072	0.5	12.078	1.0	12.078	2.0	12.078	3.0	12.078	4.0	12.078	5.0	12.078	6.0	12.078	7.0	12.078	8.0	12.078
Time since start [H]	Output Voltage [V]																								
0.0	12.072																								
0.5	12.078																								
1.0	12.078																								
2.0	12.078																								
3.0	12.078																								
4.0	12.078																								
5.0	12.078																								
6.0	12.078																								
7.0	12.078																								
8.0	12.078																								

COSEL


Model	MGFS402412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V3.4A		

1.Graph



2.Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.7	4.0	10.7	0.5	3.1	
100 %		6.7	5.5	12.2	0.4	1.0	




COSEL

Model	MGFS402412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V3.4A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	7.5	7.6
-40	7.5	7.6
-20	7.5	7.5
0	7.5	7.5
25	7.5	7.5
65	7.5	7.5
75	7.5	7.5
--	-	-
--	-	-
--	-	-
--	-	-



Model	MGFS402412	Temperature Testing Circuitry	25°C Figure A																																																																																			
Item	Overcurrent Protection																																																																																					
Object	+12V3.4A																																																																																					
1.Graph		<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V (triangle) Input Volt. 12V (square) Input Volt. 18V (asterisk) Input Volt. 24V (circle) Input Volt. 36V (diamond) 																																																																																				
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation activates when overcurrent protection is activated.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>12.000</td><td>2.915</td><td>3.535</td><td>4.089</td><td>4.015</td><td>4.012</td></tr> <tr><td>11.400</td><td>-</td><td>※1</td><td>※2</td><td>-</td><td>-</td></tr> <tr><td>10.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.200</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.800</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.600</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.400</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.200</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.000</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	12.000	2.915	3.535	4.089	4.015	4.012	11.400	-	※1	※2	-	-	10.800	-	-	-	-	-	9.600	-	-	-	-	-	8.400	-	-	-	-	-	7.200	-	-	-	-	-	6.000	-	-	-	-	-	4.800	-	-	-	-	-	3.600	-	-	-	-	-	2.400	-	-	-	-	-	1.200	-	-	-	-	-	0.000	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																																	
12.000	2.915	3.535	4.089	4.015	4.012																																																																																	
11.400	-	※1	※2	-	-																																																																																	
10.800	-	-	-	-	-																																																																																	
9.600	-	-	-	-	-																																																																																	
8.400	-	-	-	-	-																																																																																	
7.200	-	-	-	-	-																																																																																	
6.000	-	-	-	-	-																																																																																	
4.800	-	-	-	-	-																																																																																	
3.600	-	-	-	-	-																																																																																	
2.400	-	-	-	-	-																																																																																	
1.200	-	-	-	-	-																																																																																	
0.000	-	-	-	-	-																																																																																	


※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 12V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS402412
Item	Overvoltage Protection
Object	+12V3.4A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Ratio [%]	Operating Point [%]		
	Input Volt. 9[V]	Input Volt. 24[V]	Input Volt. 36[V]
0	135	135	135
10	129	128	128
20	129	129	129
30	129	129	129
40	129	128	128
50	129	127	127
60	129	128	127
70	130	128	127
80	-	128	127
90	-	128	127
100	-	128	127





※During this area, overcurrent protection activates.

COSEL

Model	MGFS402412
Item	Switching frequency (by Load Current)
Object	+12V3.4A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)