

# TEST DATA OF MGFS404805

# Regulated DC Power Supply

## December 6, 2018

Approved by : Junichi Hatagishi Junichi Hatagishi Design Manager

Prepared by : Shohei Mukaide  
Shohei Mukaide Design Engineer

# **COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	9
10.Ripple-Noise . . . . .	10
11.Ripple Voltage (by Ambient Temperature) . . . . .	11
12.Ambient Temperature Drift . . . . .	12
13.Output Voltage Accuracy . . . . .	13
14.Time Lapse Drift . . . . .	14
15.Rise and Fall Time . . . . .	15
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	16
17.Overcurrent Protection . . . . .	17
18.Overvoltage Protection . . . . .	18
19.Switching frequency (by Load Current) . . . . .	19
20.Figure of Testing Circuitry . . . . .	20


(Final Page 20)

**COSEL**

Model	MGFS404805																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	_____																																																																																	
1.Graph			2.Values																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>15.2</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>15.6</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>16.0</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>16.4</td><td>0.035</td><td>1.353</td><td>-※</td></tr> <tr><td>16.8</td><td>0.034</td><td>1.320</td><td>-※</td></tr> <tr><td>17.2</td><td>0.034</td><td>1.288</td><td>-※</td></tr> <tr><td>17.6</td><td>0.033</td><td>1.257</td><td>-※</td></tr> <tr><td>18.0</td><td>0.033</td><td>1.229</td><td>-※</td></tr> <tr><td>24.0</td><td>0.027</td><td>0.919</td><td>-※</td></tr> <tr><td>36.0</td><td>0.023</td><td>0.616</td><td>1.227</td></tr> <tr><td>48.0</td><td>0.023</td><td>0.464</td><td>0.919</td></tr> <tr><td>76.0</td><td>0.018</td><td>0.302</td><td>0.586</td></tr> <tr><td>80.0</td><td>0.010</td><td>0.288</td><td>0.558</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	15.2	0.004	0.004	-※	15.6	0.004	0.004	-※	16.0	0.004	0.004	-※	16.4	0.035	1.353	-※	16.8	0.034	1.320	-※	17.2	0.034	1.288	-※	17.6	0.033	1.257	-※	18.0	0.033	1.229	-※	24.0	0.027	0.919	-※	36.0	0.023	0.616	1.227	48.0	0.023	0.464	0.919	76.0	0.018	0.302	0.586	80.0	0.010	0.288	0.558	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
15.2	0.004	0.004	-※																																																																															
15.6	0.004	0.004	-※																																																																															
16.0	0.004	0.004	-※																																																																															
16.4	0.035	1.353	-※																																																																															
16.8	0.034	1.320	-※																																																																															
17.2	0.034	1.288	-※																																																																															
17.6	0.033	1.257	-※																																																																															
18.0	0.033	1.229	-※																																																																															
24.0	0.027	0.919	-※																																																																															
36.0	0.023	0.616	1.227																																																																															
48.0	0.023	0.464	0.919																																																																															
76.0	0.018	0.302	0.586																																																																															
80.0	0.010	0.288	0.558																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

※During this area, overcurrent protection activates and power supply operates in hiccup mode.

COSEL

Model	MGFS404805	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Current (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 18V - - -□--- Input Volt. 24V - - -*--- Input Volt. 36V - - -○--- Input Volt. 48V - - -◇--- Input Volt. 76V																																																																														
			2.Values																																																																													
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>0.033</td> <td>0.027</td> <td>0.023</td> <td>0.023</td> <td>0.018</td> </tr> <tr> <td>1.6</td> <td>0.502</td> <td>0.379</td> <td>0.256</td> <td>0.195</td> <td>0.131</td> </tr> <tr> <td>3.2</td> <td>0.987</td> <td>0.738</td> <td>0.495</td> <td>0.375</td> <td>0.246</td> </tr> <tr> <td>4.0</td> <td>1.229</td> <td>0.919</td> <td>0.616</td> <td>0.464</td> <td>0.302</td> </tr> <tr> <td>4.8</td> <td>1.480</td> <td>1.107</td> <td>0.736</td> <td>0.555</td> <td>0.358</td> </tr> <tr> <td>5.6</td> <td>1.740</td> <td>1.290</td> <td>0.857</td> <td>0.645</td> <td>0.414</td> </tr> <tr> <td>6.4</td> <td>-※1</td> <td>1.482</td> <td>0.981</td> <td>0.737</td> <td>0.472</td> </tr> <tr> <td>8.0</td> <td>-※1</td> <td>-※2</td> <td>1.227</td> <td>0.919</td> <td>0.586</td> </tr> <tr> <td>8.8</td> <td>-※1</td> <td>-※2</td> <td>1.360</td> <td>1.018</td> <td>0.647</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	0.033	0.027	0.023	0.023	0.018	1.6	0.502	0.379	0.256	0.195	0.131	3.2	0.987	0.738	0.495	0.375	0.246	4.0	1.229	0.919	0.616	0.464	0.302	4.8	1.480	1.107	0.736	0.555	0.358	5.6	1.740	1.290	0.857	0.645	0.414	6.4	-※1	1.482	0.981	0.737	0.472	8.0	-※1	-※2	1.227	0.919	0.586	8.8	-※1	-※2	1.360	1.018	0.647	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.0	0.033	0.027	0.023	0.023	0.018																																																																											
1.6	0.502	0.379	0.256	0.195	0.131																																																																											
3.2	0.987	0.738	0.495	0.375	0.246																																																																											
4.0	1.229	0.919	0.616	0.464	0.302																																																																											
4.8	1.480	1.107	0.736	0.555	0.358																																																																											
5.6	1.740	1.290	0.857	0.645	0.414																																																																											
6.4	-※1	1.482	0.981	0.737	0.472																																																																											
8.0	-※1	-※2	1.227	0.919	0.586																																																																											
8.8	-※1	-※2	1.360	1.018	0.647																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											

Note: Slanted line shows the range of the rated load current.

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

**COSEL**


Model	MGFS404805																																																																																																																																																											
Item	Input Power (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																																																																																																							
Object	<hr/>																																																																																																																																																											
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.59</td><td>0.66</td><td>0.80</td><td>1.08</td><td>1.45</td></tr> <tr><td>1.6</td><td>9.08</td><td>9.12</td><td>9.23</td><td>9.37</td><td>9.94</td></tr> <tr><td>3.2</td><td>17.77</td><td>17.76</td><td>17.83</td><td>18.00</td><td>18.70</td></tr> <tr><td>4.0</td><td>22.22</td><td>22.14</td><td>22.17</td><td>22.30</td><td>22.95</td></tr> <tr><td>4.8</td><td>26.74</td><td>26.57</td><td>26.52</td><td>26.64</td><td>27.24</td></tr> <tr><td>5.6</td><td>31.32</td><td>31.06</td><td>30.93</td><td>30.99</td><td>31.52</td></tr> <tr><td>6.4</td><td>-※1</td><td>35.62</td><td>35.37</td><td>35.40</td><td>35.88</td></tr> <tr><td>8.0</td><td>-※1</td><td>-※2</td><td>44.44</td><td>44.36</td><td>44.70</td></tr> <tr><td>8.8</td><td>-※1</td><td>-※2</td><td>49.03</td><td>48.91</td><td>49.18</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]	0.0	0.59	0.66	0.80	1.08	1.45	1.6	9.08	9.12	9.23	9.37	9.94	3.2	17.77	17.76	17.83	18.00	18.70	4.0	22.22	22.14	22.17	22.30	22.95	4.8	26.74	26.57	26.52	26.64	27.24	5.6	31.32	31.06	30.93	30.99	31.52	6.4	-※1	35.62	35.37	35.40	35.88	8.0	-※1	-※2	44.44	44.36	44.70	8.8	-※1	-※2	49.03	48.91	49.18	--	-	-	-	-	-	--	-	-	-	-	-	<hr/> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.59</td><td>0.66</td><td>0.80</td><td>1.08</td><td>1.45</td></tr> <tr><td>1.6</td><td>9.08</td><td>9.12</td><td>9.23</td><td>9.37</td><td>9.94</td></tr> <tr><td>3.2</td><td>17.77</td><td>17.76</td><td>17.83</td><td>18.00</td><td>18.70</td></tr> <tr><td>4.0</td><td>22.22</td><td>22.14</td><td>22.17</td><td>22.30</td><td>22.95</td></tr> <tr><td>4.8</td><td>26.74</td><td>26.57</td><td>26.52</td><td>26.64</td><td>27.24</td></tr> <tr><td>5.6</td><td>31.32</td><td>31.06</td><td>30.93</td><td>30.99</td><td>31.52</td></tr> <tr><td>6.4</td><td>-※1</td><td>35.62</td><td>35.37</td><td>35.40</td><td>35.88</td></tr> <tr><td>8.0</td><td>-※1</td><td>-※2</td><td>44.44</td><td>44.36</td><td>44.70</td></tr> <tr><td>8.8</td><td>-※1</td><td>-※2</td><td>49.03</td><td>48.91</td><td>49.18</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	0.59	0.66	0.80	1.08	1.45	1.6	9.08	9.12	9.23	9.37	9.94	3.2	17.77	17.76	17.83	18.00	18.70	4.0	22.22	22.14	22.17	22.30	22.95	4.8	26.74	26.57	26.52	26.64	27.24	5.6	31.32	31.06	30.93	30.99	31.52	6.4	-※1	35.62	35.37	35.40	35.88	8.0	-※1	-※2	44.44	44.36	44.70	8.8	-※1	-※2	49.03	48.91	49.18	--	-	-	-	-	-	--	-	-	-	-	-	<hr/>				
Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																																																																																							
0.0	0.59	0.66	0.80	1.08	1.45																																																																																																																																																							
1.6	9.08	9.12	9.23	9.37	9.94																																																																																																																																																							
3.2	17.77	17.76	17.83	18.00	18.70																																																																																																																																																							
4.0	22.22	22.14	22.17	22.30	22.95																																																																																																																																																							
4.8	26.74	26.57	26.52	26.64	27.24																																																																																																																																																							
5.6	31.32	31.06	30.93	30.99	31.52																																																																																																																																																							
6.4	-※1	35.62	35.37	35.40	35.88																																																																																																																																																							
8.0	-※1	-※2	44.44	44.36	44.70																																																																																																																																																							
8.8	-※1	-※2	49.03	48.91	49.18																																																																																																																																																							
--	-	-	-	-	-																																																																																																																																																							
--	-	-	-	-	-																																																																																																																																																							
Load Current [A]	Input Power [W]																																																																																																																																																											
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																																																																																							
0.0	0.59	0.66	0.80	1.08	1.45																																																																																																																																																							
1.6	9.08	9.12	9.23	9.37	9.94																																																																																																																																																							
3.2	17.77	17.76	17.83	18.00	18.70																																																																																																																																																							
4.0	22.22	22.14	22.17	22.30	22.95																																																																																																																																																							
4.8	26.74	26.57	26.52	26.64	27.24																																																																																																																																																							
5.6	31.32	31.06	30.93	30.99	31.52																																																																																																																																																							
6.4	-※1	35.62	35.37	35.40	35.88																																																																																																																																																							
8.0	-※1	-※2	44.44	44.36	44.70																																																																																																																																																							
8.8	-※1	-※2	49.03	48.91	49.18																																																																																																																																																							
--	-	-	-	-	-																																																																																																																																																							
--	-	-	-	-	-																																																																																																																																																							
Note:	Slanted line shows the range of the rated load current.																																																																																																																																																											
	※1 Maximum output current at minimum input Voltage is 70% of rated load current. ※2 Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																																																																																											

**COSEL**

Model	MGFS404805
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	90.5	89.9 ※1
18	90.7	90.1 ※1
24	91.0	90.5 ※2
30	90.9	90.4
36	90.8	90.6
48	90.1	91.0
60	89.2	90.5
76	87.3	89.7
80	86.9	89.5

※1: Load 70%

※2: Load 80%

Note: Slanted line shows the range of the rated input voltage.

**COSEL**


Model	MGFS404805																																																																																	
Item	Efficiency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object	<hr/>																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <p>Efficiency [%]</p> <p>Load Current [A]</p>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>1.6</td> <td>88.7</td> <td>88.2</td> <td>87.1</td> <td>86.0</td> <td>80.4</td> </tr> <tr> <td>3.2</td> <td>90.6</td> <td>90.7</td> <td>90.2</td> <td>89.3</td> <td>85.6</td> </tr> <tr> <td>4.0</td> <td>90.7</td> <td>91.0</td> <td>90.8</td> <td>90.1</td> <td>87.3</td> </tr> <tr> <td>4.8</td> <td>90.5</td> <td>91.0</td> <td>91.0</td> <td>90.5</td> <td>88.4</td> </tr> <tr> <td>5.6</td> <td>90.1</td> <td>90.8</td> <td>91.1</td> <td>90.9</td> <td>89.1</td> </tr> <tr> <td>6.4</td> <td>-※1</td> <td>90.5</td> <td>91.1</td> <td>90.9</td> <td>89.5</td> </tr> <tr> <td>8.0</td> <td>-※1</td> <td>-※2</td> <td>90.6</td> <td>91.0</td> <td>89.7</td> </tr> <tr> <td>8.8</td> <td>-※1</td> <td>-※2</td> <td>90.4</td> <td>90.8</td> <td>89.7</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Efficiency [%]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	-	-	-	-	-	1.6	88.7	88.2	87.1	86.0	80.4	3.2	90.6	90.7	90.2	89.3	85.6	4.0	90.7	91.0	90.8	90.1	87.3	4.8	90.5	91.0	91.0	90.5	88.4	5.6	90.1	90.8	91.1	90.9	89.1	6.4	-※1	90.5	91.1	90.9	89.5	8.0	-※1	-※2	90.6	91.0	89.7	8.8	-※1	-※2	90.4	90.8	89.7	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.0	-	-	-	-	-																																																																													
1.6	88.7	88.2	87.1	86.0	80.4																																																																													
3.2	90.6	90.7	90.2	89.3	85.6																																																																													
4.0	90.7	91.0	90.8	90.1	87.3																																																																													
4.8	90.5	91.0	91.0	90.5	88.4																																																																													
5.6	90.1	90.8	91.1	90.9	89.1																																																																													
6.4	-※1	90.5	91.1	90.9	89.5																																																																													
8.0	-※1	-※2	90.6	91.0	89.7																																																																													
8.8	-※1	-※2	90.4	90.8	89.7																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 24V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																	

**COSEL**

Model	MGFS404805
Item	Line Regulation
Object	+5V8A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1. Graph



Note: Slanted line shows the range of the rated input voltage.

## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	5.050	-
18	5.050	-
24	5.050	-
30	5.050	5.050
36	5.050	5.050
48	5.050	5.051
60	5.051	5.050
76	5.052	5.052
80	5.051	5.051

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFS404805																																																																																	
Item	Load Regulation																																																																																	
Object	+5V8A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>5.052</td> <td>5.051</td> <td>5.051</td> <td>5.053</td> <td>5.053</td> </tr> <tr> <td>1.6</td> <td>5.051</td> <td>5.051</td> <td>5.051</td> <td>5.052</td> <td>5.052</td> </tr> <tr> <td>3.2</td> <td>5.051</td> <td>5.050</td> <td>5.050</td> <td>5.051</td> <td>5.052</td> </tr> <tr> <td>4.0</td> <td>5.050</td> <td>5.050</td> <td>5.050</td> <td>5.051</td> <td>5.052</td> </tr> <tr> <td>4.8</td> <td>5.050</td> <td>5.050</td> <td>5.050</td> <td>5.051</td> <td>5.052</td> </tr> <tr> <td>5.6</td> <td>5.050</td> <td>5.050</td> <td>5.050</td> <td>5.051</td> <td>5.052</td> </tr> <tr> <td>6.4</td> <td>-※1</td> <td>5.050</td> <td>5.050</td> <td>5.051</td> <td>5.052</td> </tr> <tr> <td>8.0</td> <td>-※1</td> <td>-※2</td> <td>5.050</td> <td>5.051</td> <td>5.052</td> </tr> <tr> <td>8.8</td> <td>-※1</td> <td>-※2</td> <td>5.050</td> <td>5.051</td> <td>5.052</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	5.052	5.051	5.051	5.053	5.053	1.6	5.051	5.051	5.051	5.052	5.052	3.2	5.051	5.050	5.050	5.051	5.052	4.0	5.050	5.050	5.050	5.051	5.052	4.8	5.050	5.050	5.050	5.051	5.052	5.6	5.050	5.050	5.050	5.051	5.052	6.4	-※1	5.050	5.050	5.051	5.052	8.0	-※1	-※2	5.050	5.051	5.052	8.8	-※1	-※2	5.050	5.051	5.052	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.0	5.052	5.051	5.051	5.053	5.053																																																																													
1.6	5.051	5.051	5.051	5.052	5.052																																																																													
3.2	5.051	5.050	5.050	5.051	5.052																																																																													
4.0	5.050	5.050	5.050	5.051	5.052																																																																													
4.8	5.050	5.050	5.050	5.051	5.052																																																																													
5.6	5.050	5.050	5.050	5.051	5.052																																																																													
6.4	-※1	5.050	5.050	5.051	5.052																																																																													
8.0	-※1	-※2	5.050	5.051	5.052																																																																													
8.8	-※1	-※2	5.050	5.051	5.052																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																																	
※2	Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

**COSEL**

Model	MGFS404805	Temperature Testing Circuitry Figure A	25°C
Item	Dynamic Load Response		Figure A
Object	+5V8A		

Input Volt. 48 V  
 Cycle 100 ms





Min.Load (0A)↔  
 Load 100% (8A)

100 mV/div



100  $\mu$ s/div

1 ms/div

100  $\mu$ s/div

Min.Load (0A)↔  
 Load 50% (4A)

100 mV/div

100  $\mu$ s/div

Load 50% (4A)↔  
 Load 100% (8A)

100 mV/div

100  $\mu$ s/div


1 ms/div

**COSEL**

Model	MGFS404805
Item	Ripple Voltage (by Load Current)
Object	+5V8A

 Temperature 25°C  
 Testing Circuitry Figure B

## 1.Graph



Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	10	15
1.6	5	10
3.2	5	10
4.8	20	10
5.6	30	10
6.4	-	10
8.0	-	10
8.8	-	10
--	-	-
--	-	-
--	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

**COSEL**

Model	MGFS404805
Item	Ripple-Noise
Object	+5V8A

Temperature 25°C  
Testing Circuitry Figure B

## 1.Graph



Measured by 100 MHz Oscilloscope.  
Ripple-Noise is shown as p-p in the figure below.  
Note: Slanted line shows the range of the rated load current.

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	15	20
1.6	10	15
3.2	15	15
4.8	20	20
5.6	40	25
6.4	-	25
8.0	-	35
8.8	-	35
--	-	-
--	-	-
--	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

**COSEL**

Model	MGFS404805
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V8A

## 1. Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure B

## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	25
-40	10	20
-20	10	15
25	10	10
60	5	10
85	5	10
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**

Model	MGFS404805
Item	Ambient Temperature Drift
Object	+5V8A



Note: Slanted line shows the range of the rated ambient temperature.

### Testing Circuitry Figure A

#### 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	5.005	5.006	5.004	5.006	5.008
-40	5.019	5.020	5.019	5.020	5.022
-20	5.031	5.032	5.030	5.032	5.033
0	5.041	5.041	5.040	5.041	5.042
25	5.050	5.050	5.050	5.051	5.052
60	5.056	5.056	5.055	5.056	5.056
70	5.056	5.056	5.055	5.056	5.056
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of input Volt. 18V, Load 70%.  
24V, Load 80%.  
Other case Load 100%.



Model	MGFS404805	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V8A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 18 - 76V

Load Current : 0 - 8A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	60	18	0	5.058	±20	±0.4
Minimum Voltage	-40	36	8	5.019		


**COSEL**

Model	MGFS404805	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+5V8A																								
1. Graph			2. Values																						
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.050</td></tr> <tr><td>0.5</td><td>5.055</td></tr> <tr><td>1.0</td><td>5.055</td></tr> <tr><td>2.0</td><td>5.055</td></tr> <tr><td>3.0</td><td>5.055</td></tr> <tr><td>4.0</td><td>5.055</td></tr> <tr><td>5.0</td><td>5.055</td></tr> <tr><td>6.0</td><td>5.055</td></tr> <tr><td>7.0</td><td>5.055</td></tr> <tr><td>8.0</td><td>5.055</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.050	0.5	5.055	1.0	5.055	2.0	5.055	3.0	5.055	4.0	5.055	5.0	5.055	6.0	5.055	7.0	5.055	8.0	5.055
Time since start [H]	Output Voltage [V]																								
0.0	5.050																								
0.5	5.055																								
1.0	5.055																								
2.0	5.055																								
3.0	5.055																								
4.0	5.055																								
5.0	5.055																								
6.0	5.055																								
7.0	5.055																								
8.0	5.055																								

**COSEL**


Model	MGFS404805	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V8A		

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.6	3.6	10.2	1.5	1.7	
100 %		6.6	5.3	11.9	1.1	0.7	




**COSEL**

Model	MGFS404805
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V8A

Testing Circuitry Figure A

## 1. Graph



## 2. Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	15.2	15.3
-40	15.2	15.1
-20	15.2	15.1
0	15.2	15.1
25	15.2	15.1
60	15.0	15.1
70	15.0	15.1
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFS404805	Temperature Testing Circuitry	25°C Figure A																																																																																			
Item	Overcurrent Protection																																																																																					
Object	+5V8A																																																																																					
1.Graph		2.Values																																																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation activates when overcurrent protection is activated.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>6.311</td><td>7.703</td><td>9.645</td><td>9.825</td><td>9.795</td></tr> <tr><td>4.75</td><td>-</td><td>※1</td><td>※2</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.      ※2 Maximum output current at 24V input Voltage is 80% of rated load current.      Refer to instruction manuals for details of input derating.</p>		Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	5.00	6.311	7.703	9.645	9.825	9.795	4.75	-	※1	※2	-	-	4.50	-	-	-	-	-	4.00	-	-	-	-	-	3.50	-	-	-	-	-	3.00	-	-	-	-	-	2.50	-	-	-	-	-	2.00	-	-	-	-	-	1.50	-	-	-	-	-	1.00	-	-	-	-	-	0.50	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																	
5.00	6.311	7.703	9.645	9.825	9.795																																																																																	
4.75	-	※1	※2	-	-																																																																																	
4.50	-	-	-	-	-																																																																																	
4.00	-	-	-	-	-																																																																																	
3.50	-	-	-	-	-																																																																																	
3.00	-	-	-	-	-																																																																																	
2.50	-	-	-	-	-																																																																																	
2.00	-	-	-	-	-																																																																																	
1.50	-	-	-	-	-																																																																																	
1.00	-	-	-	-	-																																																																																	
0.50	-	-	-	-	-																																																																																	
0.00	-	-	-	-	-																																																																																	

**COSEL**


Model	MGFS404805																																																				
Item	Overvoltage Protection	Temperature 25°C Testing Circuitry Figure A																																																			
Object	+5V8A																																																				
1.Graph																																																					
<p style="text-align: center;"> <span style="display: inline-block; width: 15px; height: 15px; background-color: white; border: 1px solid black;"></span> Input Volt. 18V  <span style="display: inline-block; width: 15px; height: 15px; border: 1px dashed black;"></span> Input Volt. 48V  <span style="display: inline-block; width: 15px; height: 15px; border: 1px dashed black;">*</span> Input Volt. 76V     </p> 																																																					
2.Values																																																					
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Operating Point [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>130</td> <td>129</td> <td>128</td> </tr> <tr> <td>10</td> <td>128</td> <td>128</td> <td>128</td> </tr> <tr> <td>20</td> <td>129</td> <td>128</td> <td>127</td> </tr> <tr> <td>30</td> <td>128</td> <td>127</td> <td>127</td> </tr> <tr> <td>40</td> <td>129</td> <td>126</td> <td>126</td> </tr> <tr> <td>50</td> <td>129</td> <td>126</td> <td>125</td> </tr> <tr> <td>60</td> <td>129</td> <td>126</td> <td>125</td> </tr> <tr> <td>70</td> <td>- ※</td> <td>126</td> <td>125</td> </tr> <tr> <td>80</td> <td>- ※</td> <td>126</td> <td>126</td> </tr> <tr> <td>90</td> <td>- ※</td> <td>126</td> <td>126</td> </tr> <tr> <td>100</td> <td>- ※</td> <td>125</td> <td>125</td> </tr> </tbody> </table>			Load Ratio [%]	Operating Point [%]			Input Volt. 18[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	130	129	128	10	128	128	128	20	129	128	127	30	128	127	127	40	129	126	126	50	129	126	125	60	129	126	125	70	- ※	126	125	80	- ※	126	126	90	- ※	126	126	100	- ※	125	125
Load Ratio [%]	Operating Point [%]																																																				
	Input Volt. 18[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																		
0	130	129	128																																																		
10	128	128	128																																																		
20	129	128	127																																																		
30	128	127	127																																																		
40	129	126	126																																																		
50	129	126	125																																																		
60	129	126	125																																																		
70	- ※	126	125																																																		
80	- ※	126	126																																																		
90	- ※	126	126																																																		
100	- ※	125	125																																																		
<small>※During this area, overcurrent protection activates.</small>																																																					

# COSEL

Model	MGFS404805
Item	Switching frequency (by Load Current)
Object	+5V8A

Temperature 25°C  
Testing Circuitry Figure A

### 1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.




Figure A




Figure B (Ripple and Ripple noise Characteristic)