

TEST DATA OF MGFS404812

Regulated DC Power Supply
December 7, 2018

Approved by : Junichi Hatagishi
Junichi Hatagishi Design Manager

Prepared by : Shohei Mukaide
Shohei Mukaide Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	9
10.Ripple-Noise · · · · ·	10
11.Ripple Voltage (by Ambient Temperature) · · · · ·	11
12.Ambient Temperature Drift · · · · ·	12
13.Output Voltage Accuracy · · · · ·	13
14.Time Lapse Drift · · · · ·	14
15.Rise and Fall Time · · · · ·	15
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	16
17.Overcurrent Protection · · · · ·	17
18.Overvoltage Protection · · · · ·	18
19.Switching frequency (by Load Current) · · · · ·	19
20.Figure of Testing Circuitry · · · · ·	20


(Final Page 20)

COSEL

Model	MGFS404812																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	_____																																																																																	
1.Graph			2.Values																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>15.2</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>15.6</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>16.0</td><td>0.004</td><td>0.004</td><td>-※</td></tr> <tr><td>16.4</td><td>0.028</td><td>1.371</td><td>-※</td></tr> <tr><td>16.8</td><td>0.028</td><td>1.338</td><td>-※</td></tr> <tr><td>17.2</td><td>0.027</td><td>1.303</td><td>-※</td></tr> <tr><td>17.6</td><td>0.027</td><td>1.271</td><td>-※</td></tr> <tr><td>18.0</td><td>0.026</td><td>1.245</td><td>-※</td></tr> <tr><td>24.0</td><td>0.022</td><td>0.933</td><td>-※</td></tr> <tr><td>36.0</td><td>0.017</td><td>0.622</td><td>1.241</td></tr> <tr><td>48.0</td><td>0.011</td><td>0.468</td><td>0.934</td></tr> <tr><td>76.0</td><td>0.011</td><td>0.302</td><td>0.594</td></tr> <tr><td>80.0</td><td>0.011</td><td>0.287</td><td>0.557</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	15.2	0.004	0.004	-※	15.6	0.004	0.004	-※	16.0	0.004	0.004	-※	16.4	0.028	1.371	-※	16.8	0.028	1.338	-※	17.2	0.027	1.303	-※	17.6	0.027	1.271	-※	18.0	0.026	1.245	-※	24.0	0.022	0.933	-※	36.0	0.017	0.622	1.241	48.0	0.011	0.468	0.934	76.0	0.011	0.302	0.594	80.0	0.011	0.287	0.557	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
15.2	0.004	0.004	-※																																																																															
15.6	0.004	0.004	-※																																																																															
16.0	0.004	0.004	-※																																																																															
16.4	0.028	1.371	-※																																																																															
16.8	0.028	1.338	-※																																																																															
17.2	0.027	1.303	-※																																																																															
17.6	0.027	1.271	-※																																																																															
18.0	0.026	1.245	-※																																																																															
24.0	0.022	0.933	-※																																																																															
36.0	0.017	0.622	1.241																																																																															
48.0	0.011	0.468	0.934																																																																															
76.0	0.011	0.302	0.594																																																																															
80.0	0.011	0.287	0.557																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

※During this area, overcurrent protection activates and power supply operates in hiccup mode.

COSEL

Model	MGFS404812	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Current (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 18V - -□--- Input Volt. 24V - -*--- Input Volt. 36V - -○--- Input Volt. 48V - -◇--- Input Volt. 76V																																																																														
																																																																																
Note: Slanted line shows the range of the rated load current.			2.Values																																																																													
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.026</td> <td>0.022</td> <td>0.017</td> <td>0.011</td> <td>0.011</td> </tr> <tr> <td>0.68</td> <td>0.512</td> <td>0.384</td> <td>0.258</td> <td>0.196</td> <td>0.130</td> </tr> <tr> <td>1.36</td> <td>0.996</td> <td>0.746</td> <td>0.500</td> <td>0.377</td> <td>0.246</td> </tr> <tr> <td>1.70</td> <td>1.245</td> <td>0.933</td> <td>0.622</td> <td>0.468</td> <td>0.302</td> </tr> <tr> <td>2.04</td> <td>1.492</td> <td>1.118</td> <td>0.744</td> <td>0.560</td> <td>0.359</td> </tr> <tr> <td>2.38</td> <td>1.752</td> <td>1.303</td> <td>0.869</td> <td>0.653</td> <td>0.418</td> </tr> <tr> <td>2.72</td> <td>-※1</td> <td>1.495</td> <td>0.995</td> <td>0.745</td> <td>0.476</td> </tr> <tr> <td>3.40</td> <td>-※1</td> <td>-※2</td> <td>1.241</td> <td>0.934</td> <td>0.594</td> </tr> <tr> <td>3.74</td> <td>-※1</td> <td>-※2</td> <td>1.370</td> <td>1.026</td> <td>0.653</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.026	0.022	0.017	0.011	0.011	0.68	0.512	0.384	0.258	0.196	0.130	1.36	0.996	0.746	0.500	0.377	0.246	1.70	1.245	0.933	0.622	0.468	0.302	2.04	1.492	1.118	0.744	0.560	0.359	2.38	1.752	1.303	0.869	0.653	0.418	2.72	-※1	1.495	0.995	0.745	0.476	3.40	-※1	-※2	1.241	0.934	0.594	3.74	-※1	-※2	1.370	1.026	0.653	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																											
0.00	0.026	0.022	0.017	0.011	0.011																																																																											
0.68	0.512	0.384	0.258	0.196	0.130																																																																											
1.36	0.996	0.746	0.500	0.377	0.246																																																																											
1.70	1.245	0.933	0.622	0.468	0.302																																																																											
2.04	1.492	1.118	0.744	0.560	0.359																																																																											
2.38	1.752	1.303	0.869	0.653	0.418																																																																											
2.72	-※1	1.495	0.995	0.745	0.476																																																																											
3.40	-※1	-※2	1.241	0.934	0.594																																																																											
3.74	-※1	-※2	1.370	1.026	0.653																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
			<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current. ※2 Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																													

COSEL

Model	MGFS404812																																																																																		
Item	Input Power (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																														
Object	<hr/>																																																																																		
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.47</td><td>0.52</td><td>0.62</td><td>0.51</td><td>0.81</td></tr> <tr><td>0.68</td><td>9.23</td><td>9.22</td><td>9.31</td><td>9.42</td><td>9.92</td></tr> <tr><td>1.36</td><td>17.96</td><td>17.97</td><td>18.01</td><td>18.10</td><td>18.69</td></tr> <tr><td>1.70</td><td>22.46</td><td>22.42</td><td>22.40</td><td>22.50</td><td>22.98</td></tr> <tr><td>2.04</td><td>26.98</td><td>26.85</td><td>26.84</td><td>26.91</td><td>27.32</td></tr> <tr><td>2.38</td><td>31.59</td><td>31.35</td><td>31.33</td><td>31.36</td><td>31.79</td></tr> <tr><td>2.72</td><td>-※1</td><td>35.91</td><td>35.81</td><td>35.85</td><td>36.22</td></tr> <tr><td>3.40</td><td>-※1</td><td>-※2</td><td>44.78</td><td>44.84</td><td>45.14</td></tr> <tr><td>3.74</td><td>-※1</td><td>-※2</td><td>49.39</td><td>49.28</td><td>49.65</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.47	0.52	0.62	0.51	0.81	0.68	9.23	9.22	9.31	9.42	9.92	1.36	17.96	17.97	18.01	18.10	18.69	1.70	22.46	22.42	22.40	22.50	22.98	2.04	26.98	26.85	26.84	26.91	27.32	2.38	31.59	31.35	31.33	31.36	31.79	2.72	-※1	35.91	35.81	35.85	36.22	3.40	-※1	-※2	44.78	44.84	45.14	3.74	-※1	-※2	49.39	49.28	49.65	--	-	-	-	-	-	--	-	-	-	-	-	<hr/>									
Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																														
0.00	0.47	0.52	0.62	0.51	0.81																																																																														
0.68	9.23	9.22	9.31	9.42	9.92																																																																														
1.36	17.96	17.97	18.01	18.10	18.69																																																																														
1.70	22.46	22.42	22.40	22.50	22.98																																																																														
2.04	26.98	26.85	26.84	26.91	27.32																																																																														
2.38	31.59	31.35	31.33	31.36	31.79																																																																														
2.72	-※1	35.91	35.81	35.85	36.22																																																																														
3.40	-※1	-※2	44.78	44.84	45.14																																																																														
3.74	-※1	-※2	49.39	49.28	49.65																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.47</td><td>0.52</td><td>0.62</td><td>0.51</td><td>0.81</td></tr> <tr><td>0.68</td><td>9.23</td><td>9.22</td><td>9.31</td><td>9.42</td><td>9.92</td></tr> <tr><td>1.36</td><td>17.96</td><td>17.97</td><td>18.01</td><td>18.10</td><td>18.69</td></tr> <tr><td>1.70</td><td>22.46</td><td>22.42</td><td>22.40</td><td>22.50</td><td>22.98</td></tr> <tr><td>2.04</td><td>26.98</td><td>26.85</td><td>26.84</td><td>26.91</td><td>27.32</td></tr> <tr><td>2.38</td><td>31.59</td><td>31.35</td><td>31.33</td><td>31.36</td><td>31.79</td></tr> <tr><td>2.72</td><td>-※1</td><td>35.91</td><td>35.81</td><td>35.85</td><td>36.22</td></tr> <tr><td>3.40</td><td>-※1</td><td>-※2</td><td>44.78</td><td>44.84</td><td>45.14</td></tr> <tr><td>3.74</td><td>-※1</td><td>-※2</td><td>49.39</td><td>49.28</td><td>49.65</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	0.47	0.52	0.62	0.51	0.81	0.68	9.23	9.22	9.31	9.42	9.92	1.36	17.96	17.97	18.01	18.10	18.69	1.70	22.46	22.42	22.40	22.50	22.98	2.04	26.98	26.85	26.84	26.91	27.32	2.38	31.59	31.35	31.33	31.36	31.79	2.72	-※1	35.91	35.81	35.85	36.22	3.40	-※1	-※2	44.78	44.84	45.14	3.74	-※1	-※2	49.39	49.28	49.65	--	-	-	-	-	-	--	-	-	-	-	-	<hr/>				
Load Current [A]	Input Power [W]																																																																																		
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																														
0.00	0.47	0.52	0.62	0.51	0.81																																																																														
0.68	9.23	9.22	9.31	9.42	9.92																																																																														
1.36	17.96	17.97	18.01	18.10	18.69																																																																														
1.70	22.46	22.42	22.40	22.50	22.98																																																																														
2.04	26.98	26.85	26.84	26.91	27.32																																																																														
2.38	31.59	31.35	31.33	31.36	31.79																																																																														
2.72	-※1	35.91	35.81	35.85	36.22																																																																														
3.40	-※1	-※2	44.78	44.84	45.14																																																																														
3.74	-※1	-※2	49.39	49.28	49.65																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
Note: Slanted line shows the range of the rated load current.	<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current. ※2 Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>	<hr/>																																																																																	

COSEL

Model	MGFS404812																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (Dashed line with squares) Load 100% (Solid line with triangles) 																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td> <td>91.1</td> <td>91.4 ※1</td> </tr> <tr> <td>18</td> <td>91.3</td> <td>91.5 ※1</td> </tr> <tr> <td>24</td> <td>91.5</td> <td>92.0 ※2</td> </tr> <tr> <td>30</td> <td>91.5</td> <td>91.9</td> </tr> <tr> <td>36</td> <td>91.5</td> <td>92.1</td> </tr> <tr> <td>48</td> <td>91.2</td> <td>92.0</td> </tr> <tr> <td>60</td> <td>90.5</td> <td>91.8</td> </tr> <tr> <td>76</td> <td>89.2</td> <td>91.4</td> </tr> <tr> <td>80</td> <td>88.8</td> <td>91.2</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	91.1	91.4 ※1	18	91.3	91.5 ※1	24	91.5	92.0 ※2	30	91.5	91.9	36	91.5	92.1	48	91.2	92.0	60	90.5	91.8	76	89.2	91.4	80	88.8	91.2
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	91.1	91.4 ※1																																
18	91.3	91.5 ※1																																
24	91.5	92.0 ※2																																
30	91.5	91.9																																
36	91.5	92.1																																
48	91.2	92.0																																
60	90.5	91.8																																
76	89.2	91.4																																
80	88.8	91.2																																
※1: Load 70% ※2: Load 80%																																		
Note: Slanted line shows the range of the rated input voltage.																																		

COSEL


Model	MGFS404812																																																																																	
Item	Efficiency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object	<hr/>																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.68</td> <td>89.0</td> <td>89.1</td> <td>88.2</td> <td>87.0</td> <td>82.6</td> </tr> <tr> <td>1.36</td> <td>91.3</td> <td>91.3</td> <td>91.1</td> <td>90.5</td> <td>87.7</td> </tr> <tr> <td>1.70</td> <td>91.3</td> <td>91.5</td> <td>91.5</td> <td>91.2</td> <td>89.2</td> </tr> <tr> <td>2.04</td> <td>91.2</td> <td>91.6</td> <td>91.6</td> <td>91.4</td> <td>90.0</td> </tr> <tr> <td>2.38</td> <td>91.5</td> <td>92.0</td> <td>92.0</td> <td>91.9</td> <td>90.6</td> </tr> <tr> <td>2.72</td> <td>-※1</td> <td>92.0</td> <td>92.0</td> <td>91.9</td> <td>90.9</td> </tr> <tr> <td>3.40</td> <td>-※1</td> <td>-※2</td> <td>92.1</td> <td>92.0</td> <td>91.4</td> </tr> <tr> <td>3.74</td> <td>-※1</td> <td>-※2</td> <td>91.3</td> <td>91.5</td> <td>90.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Efficiency [%]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	-	-	-	-	-	0.68	89.0	89.1	88.2	87.0	82.6	1.36	91.3	91.3	91.1	90.5	87.7	1.70	91.3	91.5	91.5	91.2	89.2	2.04	91.2	91.6	91.6	91.4	90.0	2.38	91.5	92.0	92.0	91.9	90.6	2.72	-※1	92.0	92.0	91.9	90.9	3.40	-※1	-※2	92.1	92.0	91.4	3.74	-※1	-※2	91.3	91.5	90.8	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	-	-	-	-	-																																																																													
0.68	89.0	89.1	88.2	87.0	82.6																																																																													
1.36	91.3	91.3	91.1	90.5	87.7																																																																													
1.70	91.3	91.5	91.5	91.2	89.2																																																																													
2.04	91.2	91.6	91.6	91.4	90.0																																																																													
2.38	91.5	92.0	92.0	91.9	90.6																																																																													
2.72	-※1	92.0	92.0	91.9	90.9																																																																													
3.40	-※1	-※2	92.1	92.0	91.4																																																																													
3.74	-※1	-※2	91.3	91.5	90.8																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 24V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																	

COSEL

Model	MGFS404812
Item	Line Regulation
Object	+12V3.4A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	12.066	- ※1
18	12.070	- ※1
24	12.067	- ※2
30	12.067	12.065
36	12.066	12.066
48	12.064	12.065
60	12.061	12.064
76	12.057	12.062
80	12.057	12.061

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.


COSEL

Model	MGFS404812																																																																																	
Item	Load Regulation																																																																																	
Object	+12V3.4A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> 18V 24V 36V 48V 76V 																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.073</td><td>12.066</td><td>12.061</td><td>12.066</td><td>12.069</td></tr> <tr><td>0.68</td><td>12.072</td><td>12.066</td><td>12.062</td><td>12.060</td><td>12.048</td></tr> <tr><td>1.36</td><td>12.071</td><td>12.067</td><td>12.063</td><td>12.060</td><td>12.047</td></tr> <tr><td>1.70</td><td>12.070</td><td>12.067</td><td>12.066</td><td>12.064</td><td>12.057</td></tr> <tr><td>2.04</td><td>12.070</td><td>12.067</td><td>12.064</td><td>12.061</td><td>12.049</td></tr> <tr><td>2.38</td><td>12.069</td><td>12.066</td><td>12.065</td><td>12.062</td><td>12.051</td></tr> <tr><td>2.72</td><td>-※1</td><td>12.066</td><td>12.065</td><td>12.062</td><td>12.053</td></tr> <tr><td>3.40</td><td>-※1</td><td>-※2</td><td>12.066</td><td>12.065</td><td>12.062</td></tr> <tr><td>3.74</td><td>-※1</td><td>-※2</td><td>12.065</td><td>12.063</td><td>12.054</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	12.073	12.066	12.061	12.066	12.069	0.68	12.072	12.066	12.062	12.060	12.048	1.36	12.071	12.067	12.063	12.060	12.047	1.70	12.070	12.067	12.066	12.064	12.057	2.04	12.070	12.067	12.064	12.061	12.049	2.38	12.069	12.066	12.065	12.062	12.051	2.72	-※1	12.066	12.065	12.062	12.053	3.40	-※1	-※2	12.066	12.065	12.062	3.74	-※1	-※2	12.065	12.063	12.054	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.00	12.073	12.066	12.061	12.066	12.069																																																																													
0.68	12.072	12.066	12.062	12.060	12.048																																																																													
1.36	12.071	12.067	12.063	12.060	12.047																																																																													
1.70	12.070	12.067	12.066	12.064	12.057																																																																													
2.04	12.070	12.067	12.064	12.061	12.049																																																																													
2.38	12.069	12.066	12.065	12.062	12.051																																																																													
2.72	-※1	12.066	12.065	12.062	12.053																																																																													
3.40	-※1	-※2	12.066	12.065	12.062																																																																													
3.74	-※1	-※2	12.065	12.063	12.054																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																																	
※2	Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL

Model	MGFS404812	Temperature Testing Circuitry Figure A	25°C
Item	Dynamic Load Response		Figure A
Object	+12V3.4A		

Input Volt. 48 V
 Cycle 100 ms





Min.Load (0A)↔
 Load 100% (3.4A)

200 mV/div

1 ms/div

2 ms/div





Min.Load (0A)↔
 Load 50% (1.7A)

200 mV/div

1 ms/div

2 ms/div



Load 50% (1.7A)↔
 Load 100% (3.4A)

200 mV/div

1 ms/div


2 ms/div

COSEL

Model	MGFS404812
Item	Ripple Voltage (by Load Current)
Object	+12V3.4A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.
 Ripple Voltage is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.00	30	15
0.68	5	10
1.36	10	10
2.04	25	10
2.38	40	10
2.72	-	10
3.40	-	10
3.74	-	15
--	-	-
--	-	-
--	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

COSEL

Model	MGFS404812
Item	Ripple-Noise
Object	+12V3.4A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.00	35	20
0.68	30	30
1.36	30	30
2.04	40	35
2.38	45	35
2.72	-	40
3.40	-	45
3.74	-	45
--	-	-
--	-	-
--	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGFS404812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V3.4A

1.Graph




Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	30
-40	10	25
-20	10	20
25	5	15
60	5	15
85	5	20
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL


Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	11.976	11.983	11.978	11.985	11.981
-40	12.004	12.008	12.003	12.005	12.002
-20	12.030	12.031	12.030	12.031	12.027
0	12.049	12.050	12.049	12.049	12.045
25	12.069	12.066	12.066	12.065	12.062
70	12.072	12.073	12.071	12.070	12.066
80	12.072	12.073	12.071	12.070	12.066
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of input Volt.18V, Load 70%.
 24V, Load 80%.
 Other case Load 100%.



Model	MGFS404812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V3.4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 70°C

Input Voltage : 18 - 76V

Load Current : 0 - 3.4A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	70	76	0	12.081	±40	±0.3
Minimum Voltage	-40	36	0	12.001		


COSEL

Model	MGFS404812	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V3.4A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th><th>Output Voltage [V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>12.064</td></tr> <tr><td>0.5</td><td>12.070</td></tr> <tr><td>1.0</td><td>12.070</td></tr> <tr><td>2.0</td><td>12.070</td></tr> <tr><td>3.0</td><td>12.070</td></tr> <tr><td>4.0</td><td>12.070</td></tr> <tr><td>5.0</td><td>12.070</td></tr> <tr><td>6.0</td><td>12.070</td></tr> <tr><td>7.0</td><td>12.070</td></tr> <tr><td>8.0</td><td>12.070</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.064	0.5	12.070	1.0	12.070	2.0	12.070	3.0	12.070	4.0	12.070	5.0	12.070	6.0	12.070	7.0	12.070	8.0	12.070
Time since start [H]	Output Voltage [V]																								
0.0	12.064																								
0.5	12.070																								
1.0	12.070																								
2.0	12.070																								
3.0	12.070																								
4.0	12.070																								
5.0	12.070																								
6.0	12.070																								
7.0	12.070																								
8.0	12.070																								

COSEL


Model	MGFS404812	Temperature Testing Circuitry Figure A
Item	Rise and Fall Time	
Object	+12V3.4A	

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.6	4.3	10.9	0.4	3.2	
100 %		6.6	5.7	12.3	0.3	1.1	




COSEL

Model	MGFS404812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V3.4A

Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	15.4	17.1
-40	15.2	16.1
-20	15.3	15.9
0	15.2	15.8
25	15.3	15.6
70	15.3	15.2
80	15.2	15.3
--	-	-
--	-	-
--	-	-
--	-	-



Model	MGFS404812	Temperature Testing Circuitry	25°C Figure A																																																																																			
Item	Overcurrent Protection																																																																																					
Object	+12V3.4A																																																																																					
1.Graph		<p>—△— Input Volt. 18V —□— Input Volt. 24V —*— Input Volt. 36V —○— Input Volt. 48V —◇— Input Volt. 76V</p>																																																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation activates when overcurrent protection is activated.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>2.580</td><td>3.338</td><td>4.066</td><td>4.135</td><td>4.154</td></tr> <tr><td>11.4</td><td>- ※1</td><td>- ※2</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.8</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.6</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.4</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.2</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.8</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.6</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.4</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.2</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	12.0	2.580	3.338	4.066	4.135	4.154	11.4	- ※1	- ※2	-	-	-	10.8	-	-	-	-	-	9.6	-	-	-	-	-	8.4	-	-	-	-	-	7.2	-	-	-	-	-	6.0	-	-	-	-	-	4.8	-	-	-	-	-	3.6	-	-	-	-	-	2.4	-	-	-	-	-	1.2	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																	
12.0	2.580	3.338	4.066	4.135	4.154																																																																																	
11.4	- ※1	- ※2	-	-	-																																																																																	
10.8	-	-	-	-	-																																																																																	
9.6	-	-	-	-	-																																																																																	
8.4	-	-	-	-	-																																																																																	
7.2	-	-	-	-	-																																																																																	
6.0	-	-	-	-	-																																																																																	
4.8	-	-	-	-	-																																																																																	
3.6	-	-	-	-	-																																																																																	
2.4	-	-	-	-	-																																																																																	
1.2	-	-	-	-	-																																																																																	
0.0	-	-	-	-	-																																																																																	


※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL

Model	MGFS404812
Item	Overvoltage Protection
Object	+12V3.4A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Ratio [%]	Operating Point [%]		
	18[V]	48[V]	76[V]
0	135	135	135
10	129	128	128
20	129	129	128
30	129	128	128
40	130	128	128
50	129	128	127
60	129	128	128
70	- ✕	128	128
80	- ✕	128	128
90	- ✕	128	128
100	- ✕	127	127


※During this area, overcurrent protection activates.

COSEL

Model	MGFS404812
Item	Switching frequency (by Load Current)
Object	12V3.4A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)