

# TEST DATA OF MGFS804805

Regulated DC Power Supply  
April 17, 2019

Approved by : Junichi Hatagishi  
Junichi Hatagishi Design Manager

Prepared by : Satoshi Kinoshita  
Satoshi Kinoshita Design Engineer

**COSEL CO.,LTD.**




## CONTENTS

1.Input Current (by Input Voltage) · · · · ·	1
2.Input Current (by Load Current) · · · · ·	2
3.Input Power (by Load Current) · · · · ·	3
4.Efficiency (by Input Voltage) · · · · ·	4
5.Efficiency (by Load Current) · · · · ·	5
6.Line Regulation · · · · ·	6
7.Load Regulation · · · · ·	7
8.Dynamic Load Response · · · · ·	8
9.Ripple Voltage (by Load Current) · · · · ·	9
10.Ripple-Noise · · · · ·	10
11.Ripple Voltage (by Ambient Temperature) · · · · ·	11
12.Ambient Temperature Drift · · · · ·	12
13.Output Voltage Accuracy · · · · ·	13
14.Time Lapse Drift · · · · ·	14
15.Rise and Fall Time · · · · ·	15
16.Minimum Input Voltage for Regulated Output Voltage · · · · ·	16
17.Overcurrent Protection · · · · ·	17
18.Overvoltage Protection · · · · ·	18
19.Switching frequency (by Load Current) · · · · ·	19
20.Figure of Testing Circuitry · · · · ·	20

(Final Page 20)

**COSEL**

Model	MGFS804805
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
15.2	0.004	0.004	- ✕
15.6	0.004	0.004	- ✕
16.0	0.004	0.004	- ✕
16.4	0.004	0.004	- ✕
16.8	0.041	2.575	- ✕
17.2	0.040	2.511	- ✕
17.6	0.040	2.452	- ✕
18.0	0.039	2.394	- ✕
24.0	0.032	1.796	- ✕
36.0	0.025	1.200	2.404
48.0	0.024	0.902	1.803
76.0	0.011	0.584	1.146
80.0	0.011	0.556	1.084
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

※During this area, overcurrent protection activates and power supply operates in hiccup mode.

COSEL

Model	MGFS804805																																																																													
Item	Input Current (by Load Current)																																																																													
Object	_____																																																																													
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.039</td><td>0.032</td><td>0.025</td><td>0.024</td><td>0.011</td></tr> <tr><td>3.2</td><td>0.971</td><td>0.729</td><td>0.492</td><td>0.376</td><td>0.247</td></tr> <tr><td>6.4</td><td>1.921</td><td>1.442</td><td>0.965</td><td>0.726</td><td>0.469</td></tr> <tr><td>9.6</td><td>2.899</td><td>2.160</td><td>1.439</td><td>1.082</td><td>0.694</td></tr> <tr><td>11.2</td><td>3.379</td><td>2.522</td><td>1.677</td><td>1.259</td><td>0.806</td></tr> <tr><td>12.8</td><td>-※1</td><td>2.889</td><td>1.921</td><td>1.440</td><td>0.919</td></tr> <tr><td>16.0</td><td>-※1</td><td>-※2</td><td>2.404</td><td>1.803</td><td>1.146</td></tr> <tr><td>17.6</td><td>-※1</td><td>-※2</td><td>2.656</td><td>1.984</td><td>1.260</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]	0.0	0.039	0.032	0.025	0.024	0.011	3.2	0.971	0.729	0.492	0.376	0.247	6.4	1.921	1.442	0.965	0.726	0.469	9.6	2.899	2.160	1.439	1.082	0.694	11.2	3.379	2.522	1.677	1.259	0.806	12.8	-※1	2.889	1.921	1.440	0.919	16.0	-※1	-※2	2.404	1.803	1.146	17.6	-※1	-※2	2.656	1.984	1.260	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																									
0.0	0.039	0.032	0.025	0.024	0.011																																																																									
3.2	0.971	0.729	0.492	0.376	0.247																																																																									
6.4	1.921	1.442	0.965	0.726	0.469																																																																									
9.6	2.899	2.160	1.439	1.082	0.694																																																																									
11.2	3.379	2.522	1.677	1.259	0.806																																																																									
12.8	-※1	2.889	1.921	1.440	0.919																																																																									
16.0	-※1	-※2	2.404	1.803	1.146																																																																									
17.6	-※1	-※2	2.656	1.984	1.260																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.039</td><td>0.032</td><td>0.025</td><td>0.024</td><td>0.011</td></tr> <tr><td>3.2</td><td>0.971</td><td>0.729</td><td>0.492</td><td>0.376</td><td>0.247</td></tr> <tr><td>6.4</td><td>1.921</td><td>1.442</td><td>0.965</td><td>0.726</td><td>0.469</td></tr> <tr><td>9.6</td><td>2.899</td><td>2.160</td><td>1.439</td><td>1.082</td><td>0.694</td></tr> <tr><td>11.2</td><td>3.379</td><td>2.522</td><td>1.677</td><td>1.259</td><td>0.806</td></tr> <tr><td>12.8</td><td>-※1</td><td>2.889</td><td>1.921</td><td>1.440</td><td>0.919</td></tr> <tr><td>16.0</td><td>-※1</td><td>-※2</td><td>2.404</td><td>1.803</td><td>1.146</td></tr> <tr><td>17.6</td><td>-※1</td><td>-※2</td><td>2.656</td><td>1.984</td><td>1.260</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	0.039	0.032	0.025	0.024	0.011	3.2	0.971	0.729	0.492	0.376	0.247	6.4	1.921	1.442	0.965	0.726	0.469	9.6	2.899	2.160	1.439	1.082	0.694	11.2	3.379	2.522	1.677	1.259	0.806	12.8	-※1	2.889	1.921	1.440	0.919	16.0	-※1	-※2	2.404	1.803	1.146	17.6	-※1	-※2	2.656	1.984	1.260	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																													
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																									
0.0	0.039	0.032	0.025	0.024	0.011																																																																									
3.2	0.971	0.729	0.492	0.376	0.247																																																																									
6.4	1.921	1.442	0.965	0.726	0.469																																																																									
9.6	2.899	2.160	1.439	1.082	0.694																																																																									
11.2	3.379	2.522	1.677	1.259	0.806																																																																									
12.8	-※1	2.889	1.921	1.440	0.919																																																																									
16.0	-※1	-※2	2.404	1.803	1.146																																																																									
17.6	-※1	-※2	2.656	1.984	1.260																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
Note: Slanted line shows the range of the rated load current.	<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.      ※2 Maximum output current at 24V input Voltage is 80% of rated load current.      Refer to instruction manuals for details of input derating.</p>																																																																													


**COSEL**

Model	MGFS804805																																																																								
Item	Input Power (by Load Current)																																																																								
Object	_____																																																																								
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.71</td><td>0.78</td><td>0.38</td><td>0.51</td><td>0.84</td></tr> <tr><td>3.2</td><td>17.55</td><td>17.57</td><td>17.74</td><td>18.07</td><td>18.77</td></tr> <tr><td>6.4</td><td>34.70</td><td>34.65</td><td>34.75</td><td>34.90</td><td>35.70</td></tr> <tr><td>9.6</td><td>52.20</td><td>51.96</td><td>51.85</td><td>51.95</td><td>52.83</td></tr> <tr><td>11.2</td><td>61.12</td><td>60.69</td><td>60.48</td><td>60.55</td><td>61.31</td></tr> <tr><td>12.8</td><td>-※1</td><td>69.51</td><td>69.16</td><td>69.19</td><td>69.86</td></tr> <tr><td>16.0</td><td>-※1</td><td>-※2</td><td>86.75</td><td>86.60</td><td>87.11</td></tr> <tr><td>17.6</td><td>-※1</td><td>-※2</td><td>95.68</td><td>95.45</td><td>95.83</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]	0.0	0.71	0.78	0.38	0.51	0.84	3.2	17.55	17.57	17.74	18.07	18.77	6.4	34.70	34.65	34.75	34.90	35.70	9.6	52.20	51.96	51.85	51.95	52.83	11.2	61.12	60.69	60.48	60.55	61.31	12.8	-※1	69.51	69.16	69.19	69.86	16.0	-※1	-※2	86.75	86.60	87.11	17.6	-※1	-※2	95.68	95.45	95.83	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																				
0.0	0.71	0.78	0.38	0.51	0.84																																																																				
3.2	17.55	17.57	17.74	18.07	18.77																																																																				
6.4	34.70	34.65	34.75	34.90	35.70																																																																				
9.6	52.20	51.96	51.85	51.95	52.83																																																																				
11.2	61.12	60.69	60.48	60.55	61.31																																																																				
12.8	-※1	69.51	69.16	69.19	69.86																																																																				
16.0	-※1	-※2	86.75	86.60	87.11																																																																				
17.6	-※1	-※2	95.68	95.45	95.83																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
--	-	-	-	-	-																																																																				
2.Values																																																																									
Note:	Slanted line shows the range of the rated load current.																																																																								
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																								
※2	Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																								

**COSEL**

Model	MGFS804805	Temperature	25°C
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A
Object	_____		

## 1.Graph



## 2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	92.8	92.5 ※1
18	92.9	92.6 ※1
24	93.3	93.0 ※2
30	93.3	92.7
36	93.3	92.9
48	92.8	93.1
60	91.8	92.9
76	90.2	92.4
80	90.0	92.2

※1: Load 70%

※2: Load 80%

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	MGFS804805																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul>																																																																																	
	<p>Temperature 25°C Testing Circuitry Figure A</p> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>3.2</td> <td>92.0</td> <td>91.9</td> <td>90.7</td> <td>89.1</td> <td>84.5</td> </tr> <tr> <td>6.4</td> <td>93.2</td> <td>93.2</td> <td>92.9</td> <td>92.3</td> <td>90.0</td> </tr> <tr> <td>9.6</td> <td>92.9</td> <td>93.3</td> <td>93.4</td> <td>93.2</td> <td>91.4</td> </tr> <tr> <td>11.2</td> <td>92.6</td> <td>93.2</td> <td>93.5</td> <td>93.3</td> <td>91.7</td> </tr> <tr> <td>12.8</td> <td>-※1</td> <td>93.0</td> <td>93.4</td> <td>93.3</td> <td>92.2</td> </tr> <tr> <td>16.0</td> <td>-※1</td> <td>-※2</td> <td>92.9</td> <td>93.1</td> <td>92.4</td> </tr> <tr> <td>17.6</td> <td>-※1</td> <td>-※2</td> <td>92.9</td> <td>93.1</td> <td>92.5</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Efficiency [%]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	-	-	-	-	-	3.2	92.0	91.9	90.7	89.1	84.5	6.4	93.2	93.2	92.9	92.3	90.0	9.6	92.9	93.3	93.4	93.2	91.4	11.2	92.6	93.2	93.5	93.3	91.7	12.8	-※1	93.0	93.4	93.3	92.2	16.0	-※1	-※2	92.9	93.1	92.4	17.6	-※1	-※2	92.9	93.1	92.5	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.0	-	-	-	-	-																																																																													
3.2	92.0	91.9	90.7	89.1	84.5																																																																													
6.4	93.2	93.2	92.9	92.3	90.0																																																																													
9.6	92.9	93.3	93.4	93.2	91.4																																																																													
11.2	92.6	93.2	93.5	93.3	91.7																																																																													
12.8	-※1	93.0	93.4	93.3	92.2																																																																													
16.0	-※1	-※2	92.9	93.1	92.4																																																																													
17.6	-※1	-※2	92.9	93.1	92.5																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

Note: Slanted line shows the range of the rated load current.

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.


Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFS804805
Item	Line Regulation
Object	+5V16A

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	5.057	- ※1
18	5.057	- ※1
24	5.057	- ※2
30	5.058	5.057
36	5.058	5.058
48	5.058	5.058
60	5.058	5.057
76	5.058	5.057
80	5.058	5.057

Note: Slanted line shows the range of the rated input voltage.

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFS804805																																																																																	
Item	Load Regulation																																																																																	
Object	+5V16A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> <li>18V</li> <li>24V</li> <li>36V</li> <li>48V</li> <li>76V</li> </ul>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>5.064</td> <td>5.063</td> <td>5.063</td> <td>5.064</td> <td>5.064</td> </tr> <tr> <td>3.2</td> <td>5.063</td> <td>5.062</td> <td>5.062</td> <td>5.062</td> <td>5.061</td> </tr> <tr> <td>6.4</td> <td>5.062</td> <td>5.061</td> <td>5.060</td> <td>5.060</td> <td>5.060</td> </tr> <tr> <td>9.6</td> <td>5.060</td> <td>5.060</td> <td>5.059</td> <td>5.059</td> <td>5.059</td> </tr> <tr> <td>11.2</td> <td>5.060</td> <td>5.059</td> <td>5.059</td> <td>5.059</td> <td>5.058</td> </tr> <tr> <td>12.8</td> <td>-※1</td> <td>5.059</td> <td>5.058</td> <td>5.058</td> <td>5.058</td> </tr> <tr> <td>16.0</td> <td>-※1</td> <td>-※2</td> <td>5.058</td> <td>5.058</td> <td>5.057</td> </tr> <tr> <td>17.6</td> <td>-※1</td> <td>-※2</td> <td>5.057</td> <td>5.057</td> <td>5.057</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.0	5.064	5.063	5.063	5.064	5.064	3.2	5.063	5.062	5.062	5.062	5.061	6.4	5.062	5.061	5.060	5.060	5.060	9.6	5.060	5.060	5.059	5.059	5.059	11.2	5.060	5.059	5.059	5.059	5.058	12.8	-※1	5.059	5.058	5.058	5.058	16.0	-※1	-※2	5.058	5.058	5.057	17.6	-※1	-※2	5.057	5.057	5.057	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0.0	5.064	5.063	5.063	5.064	5.064																																																																													
3.2	5.063	5.062	5.062	5.062	5.061																																																																													
6.4	5.062	5.061	5.060	5.060	5.060																																																																													
9.6	5.060	5.060	5.059	5.059	5.059																																																																													
11.2	5.060	5.059	5.059	5.059	5.058																																																																													
12.8	-※1	5.059	5.058	5.058	5.058																																																																													
16.0	-※1	-※2	5.058	5.058	5.057																																																																													
17.6	-※1	-※2	5.057	5.057	5.057																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																																	
※2	Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

**COSEL**

Model	MGFS804805	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+5V16A	

Input Volt. 48 V  
 Cycle 100 ms





Min.Load (0A)↔  
 Load 100% (16A)

200 mV/div

1 ms/div

4 ms/div



Min.Load (0A)↔  
 Load 50% (8A)

200 mV/div

1 ms/div

4 ms/div

Load 50% (8A)↔  
 Load 100% (16A)

200 mV/div

1 ms/div


4 ms/div

**COSEL**

Model	MGFS804805
Item	Ripple Voltage (by Load Current)
Object	+5V16A

Temperature 25°C  
Testing Circuitry Figure B

## 1.Graph



Measured by 100 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

## 2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	15	30
3.2	5	10
6.4	5	10
9.6	10	5
11.2	15	5
12.8	-	10
16.0	-	5
17.6	-	10
--	-	-
--	-	-
--	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple [mVp-p]





Fig.Complex Ripple Wave Form

**COSEL**

Model	MGFS804805
Item	Ripple-Noise
Object	+5V16A

Temperature 25°C  
Testing Circuitry Figure B

## 1.Graph



Measured by 100 MHz Oscilloscope.  
Ripple-Noise is shown as p-p in the figure below.  
Note: Slanted line shows the range of the rated load current.

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.0	15	30
3.2	10	10
6.4	10	10
9.6	10	10
11.2	20	10
12.8	-	10
16.0	-	10
17.6	-	15
--	-	-
--	-	-
--	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

**COSEL**

Model	MGFS804805
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V16A

Testing Circuitry Figure B

## 1. Graph



## 2. Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	10
-40	5	10
-20	5	10
25	5	5
60	5	10
75	5	10
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	MGFS804805
Item	Ambient Temperature Drift
Object	+5V16A



Note: Slanted line shows the range of the rated ambient temperature.

### Testing Circuitry Figure A

#### 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	5.015	5.017	5.018	5.020	5.021
-40	5.029	5.031	5.032	5.033	5.034
-20	5.041	5.042	5.042	5.043	5.043
0	5.049	5.050	5.050	5.050	5.050
25	5.056	5.057	5.058	5.058	5.057
55	5.059	5.060	5.058	5.058	5.057
65	5.060	5.060	5.058	5.058	5.057
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

Note: In case of input Volt.18V, Load 70%.  
24V, Load 80%.  
Other case Load 100%.



Model	MGFS804805	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V16A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 55°C

Input Voltage : 18 - 76V

Load Current : 0 - 16A


\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	55	48	0	5.064	±18	±0.4
Minimum Voltage	-40	18	11.2	5.029		


**COSEL**

Model	MGFS804805	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+5V16A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.052</td></tr> <tr><td>0.5</td><td>5.059</td></tr> <tr><td>1.0</td><td>5.059</td></tr> <tr><td>2.0</td><td>5.059</td></tr> <tr><td>3.0</td><td>5.059</td></tr> <tr><td>4.0</td><td>5.059</td></tr> <tr><td>5.0</td><td>5.059</td></tr> <tr><td>6.0</td><td>5.059</td></tr> <tr><td>7.0</td><td>5.059</td></tr> <tr><td>8.0</td><td>5.059</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.052	0.5	5.059	1.0	5.059	2.0	5.059	3.0	5.059	4.0	5.059	5.0	5.059	6.0	5.059	7.0	5.059	8.0	5.059
Time since start [H]	Output Voltage [V]																								
0.0	5.052																								
0.5	5.059																								
1.0	5.059																								
2.0	5.059																								
3.0	5.059																								
4.0	5.059																								
5.0	5.059																								
6.0	5.059																								
7.0	5.059																								
8.0	5.059																								

**COSEL**


Model	MGFS804805	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V16A		

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.5	3.2	9.7	0.5	0.6	
100 %		6.5	4.8	11.3	0.2	0.2	




**COSEL**

Model	MGFS804805
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V16A

Testing Circuitry Figure A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	15.3	15.2
-40	15.2	15.2
-20	15.1	15.3
0	15.1	15.3
25	15.3	15.2
55	15.2	15.1
65	15.2	15.2
--	-	-
--	-	-
--	-	-
--	-	-



Model	MGFS804805	Temperature Testing Circuitry	25°C Figure A																																																																																			
Item	Overcurrent Protection																																																																																					
Object	+5V16A																																																																																					
1.Graph		<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 18V Input Volt. 24V Input Volt. 36V Input Volt. 48V Input Volt. 76V</p>																																																																																				
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>12.932</td><td>15.683</td><td>18.797</td><td>19.288</td><td>19.765</td></tr> <tr><td>4.75</td><td>-※1</td><td>-※2</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.50</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	5.00	12.932	15.683	18.797	19.288	19.765	4.75	-※1	-※2	-	-	-	4.50	-	-	-	-	-	4.00	-	-	-	-	-	3.50	-	-	-	-	-	3.00	-	-	-	-	-	2.50	-	-	-	-	-	2.00	-	-	-	-	-	1.50	-	-	-	-	-	1.00	-	-	-	-	-	0.50	-	-	-	-	-	0.00	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																																	
5.00	12.932	15.683	18.797	19.288	19.765																																																																																	
4.75	-※1	-※2	-	-	-																																																																																	
4.50	-	-	-	-	-																																																																																	
4.00	-	-	-	-	-																																																																																	
3.50	-	-	-	-	-																																																																																	
3.00	-	-	-	-	-																																																																																	
2.50	-	-	-	-	-																																																																																	
2.00	-	-	-	-	-																																																																																	
1.50	-	-	-	-	-																																																																																	
1.00	-	-	-	-	-																																																																																	
0.50	-	-	-	-	-																																																																																	
0.00	-	-	-	-	-																																																																																	


※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFS804805
Item	Overvoltage Protection
Object	+5V16A



Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Operating Point [%]				
	18[V]	24[V]	36[V]	48[V]	76[V]
-60	125	125	125	125	125
-40	125	125	125	125	125
-20	126	126	126	126	125
0	126	126	126	126	126
25	126	126	126	126	126
55	126	126	126	126	126
65	126	126	126	126	126
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-


Note: Slanted line shows the range of the rated ambient temperature.

# COSEL

Model	MGFS804805
Item	Switching frequency (by Load Current)
Object	+5V16A

Temperature 25°C  
Testing Circuitry Figure A

### 1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG80 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG80 operates intermittently, so switching frequency would not become constant.

\* Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL

