

TEST DATA OF MGFW102412

Regulated DC Power Supply
December 16, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Ratio)	2
3.Input Power (by Load Ratio)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Ratio)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Switching frequency (by Load Current)	22
19.Figure of Testing Circuitry	23

(Final Page 23)



Model		MGFW102412		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph			—△— Load 100% - - - □ - - Load 50% - · - ○ - · - Load 0%																																																																																	
			2.Values																																																																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>6.0</td><td>0.002</td><td>0.003</td><td>0.003</td></tr> <tr><td>8.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>8.2</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>8.4</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>8.6</td><td>0.033</td><td>0.701</td><td>1.442</td></tr> <tr><td>8.8</td><td>0.031</td><td>0.682</td><td>1.405</td></tr> <tr><td>9.0</td><td>0.031</td><td>0.666</td><td>1.368</td></tr> <tr><td>12.0</td><td>0.025</td><td>0.493</td><td>0.977</td></tr> <tr><td>18.0</td><td>0.019</td><td>0.329</td><td>0.647</td></tr> <tr><td>24.0</td><td>0.009</td><td>0.247</td><td>0.484</td></tr> <tr><td>30.0</td><td>0.006</td><td>0.199</td><td>0.394</td></tr> <tr><td>36.0</td><td>0.005</td><td>0.167</td><td>0.326</td></tr> <tr><td>40.0</td><td>0.005</td><td>0.153</td><td>0.297</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	6.0	0.002	0.003	0.003	8.0	0.003	0.003	0.003	8.2	0.003	0.003	0.003	8.4	0.003	0.003	0.003	8.6	0.033	0.701	1.442	8.8	0.031	0.682	1.405	9.0	0.031	0.666	1.368	12.0	0.025	0.493	0.977	18.0	0.019	0.329	0.647	24.0	0.009	0.247	0.484	30.0	0.006	0.199	0.394	36.0	0.005	0.167	0.326	40.0	0.005	0.153	0.297	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
6.0	0.002	0.003	0.003																																																																																	
8.0	0.003	0.003	0.003																																																																																	
8.2	0.003	0.003	0.003																																																																																	
8.4	0.003	0.003	0.003																																																																																	
8.6	0.033	0.701	1.442																																																																																	
8.8	0.031	0.682	1.405																																																																																	
9.0	0.031	0.666	1.368																																																																																	
12.0	0.025	0.493	0.977																																																																																	
18.0	0.019	0.329	0.647																																																																																	
24.0	0.009	0.247	0.484																																																																																	
30.0	0.006	0.199	0.394																																																																																	
36.0	0.005	0.167	0.326																																																																																	
40.0	0.005	0.153	0.297																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
Note: Slanted line shows the range of the rated input voltage.																																																																																				



Model		MGFW102412		Temperature 25°C																																																																														
Item		Input Current (by Load Ratio)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>-·-·*·-·-·- Input Volt. 18V</p> <p>-·-·○-·-·- Input Volt. 24V</p> <p>-·-·◇-·-·- Input Volt. 36V</p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.031</td><td>0.025</td><td>0.019</td><td>0.009</td><td>0.005</td></tr> <tr><td>20</td><td>0.278</td><td>0.209</td><td>0.142</td><td>0.108</td><td>0.075</td></tr> <tr><td>40</td><td>0.524</td><td>0.399</td><td>0.266</td><td>0.200</td><td>0.136</td></tr> <tr><td>60</td><td>0.809</td><td>0.583</td><td>0.389</td><td>0.295</td><td>0.198</td></tr> <tr><td>80</td><td>1.051</td><td>0.794</td><td>0.521</td><td>0.388</td><td>0.262</td></tr> <tr><td>90</td><td>1.225</td><td>0.886</td><td>0.584</td><td>0.436</td><td>0.294</td></tr> <tr><td>100</td><td>- ※</td><td>0.977</td><td>0.647</td><td>0.484</td><td>0.326</td></tr> <tr><td>110</td><td>- ※</td><td>1.111</td><td>0.722</td><td>0.535</td><td>0.357</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ratio [%]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.031	0.025	0.019	0.009	0.005	20	0.278	0.209	0.142	0.108	0.075	40	0.524	0.399	0.266	0.200	0.136	60	0.809	0.583	0.389	0.295	0.198	80	1.051	0.794	0.521	0.388	0.262	90	1.225	0.886	0.584	0.436	0.294	100	- ※	0.977	0.647	0.484	0.326	110	- ※	1.111	0.722	0.535	0.357	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Ratio [%]	Input Current [A]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0	0.031	0.025	0.019	0.009	0.005																																																																													
20	0.278	0.209	0.142	0.108	0.075																																																																													
40	0.524	0.399	0.266	0.200	0.136																																																																													
60	0.809	0.583	0.389	0.295	0.198																																																																													
80	1.051	0.794	0.521	0.388	0.262																																																																													
90	1.225	0.886	0.584	0.436	0.294																																																																													
100	- ※	0.977	0.647	0.484	0.326																																																																													
110	- ※	1.111	0.722	0.535	0.357																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
				<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																														



Model		MGFW102412		Temperature 25°C																																																																														
Item		Input Power (by Load Ratio)		Testing Circuitry Figure A																																																																														
Object		_____																																																																																
1.Graph		<p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>-··*·-·- Input Volt. 18V</p> <p>-··○-·- Input Volt. 24V</p> <p>--◇-- Input Volt. 36V</p>		2.Values																																																																														
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.28</td><td>0.31</td><td>0.35</td><td>0.22</td><td>0.17</td></tr> <tr><td>20</td><td>2.48</td><td>2.50</td><td>2.54</td><td>2.58</td><td>2.69</td></tr> <tr><td>40</td><td>4.75</td><td>4.75</td><td>4.76</td><td>4.80</td><td>4.91</td></tr> <tr><td>60</td><td>7.11</td><td>7.03</td><td>7.02</td><td>7.06</td><td>7.14</td></tr> <tr><td>80</td><td>9.54</td><td>9.38</td><td>9.30</td><td>9.33</td><td>9.41</td></tr> <tr><td>90</td><td>10.86</td><td>10.60</td><td>10.47</td><td>10.47</td><td>10.56</td></tr> <tr><td>100</td><td>- ※</td><td>11.82</td><td>11.65</td><td>11.61</td><td>11.71</td></tr> <tr><td>110</td><td>- ※</td><td>13.09</td><td>12.84</td><td>12.79</td><td>12.84</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ratio [%]	Input Power [W]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.28	0.31	0.35	0.22	0.17	20	2.48	2.50	2.54	2.58	2.69	40	4.75	4.75	4.76	4.80	4.91	60	7.11	7.03	7.02	7.06	7.14	80	9.54	9.38	9.30	9.33	9.41	90	10.86	10.60	10.47	10.47	10.56	100	- ※	11.82	11.65	11.61	11.71	110	- ※	13.09	12.84	12.79	12.84	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-		
Load Ratio [%]	Input Power [W]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0	0.28	0.31	0.35	0.22	0.17																																																																													
20	2.48	2.50	2.54	2.58	2.69																																																																													
40	4.75	4.75	4.76	4.80	4.91																																																																													
60	7.11	7.03	7.02	7.06	7.14																																																																													
80	9.54	9.38	9.30	9.33	9.41																																																																													
90	10.86	10.60	10.47	10.47	10.56																																																																													
100	- ※	11.82	11.65	11.61	11.71																																																																													
110	- ※	13.09	12.84	12.79	12.84																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
				<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																														




Model		MGFW102412																																	
Item		Efficiency (by Input Voltage)																																	
Object		_____																																	
1.Graph		Temperature 25°C Testing Circuitry Figure A																																	
<p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		2.Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>8.6</td> <td>85.8</td> <td>84.6 ※1</td> </tr> <tr> <td>9.0</td> <td>85.8</td> <td>85.0 ※1</td> </tr> <tr> <td>12.0</td> <td>86.3</td> <td>85.8</td> </tr> <tr> <td>15.0</td> <td>86.2</td> <td>86.6</td> </tr> <tr> <td>18.0</td> <td>86.0</td> <td>87.1</td> </tr> <tr> <td>24.0</td> <td>85.3</td> <td>87.3</td> </tr> <tr> <td>30.0</td> <td>84.9</td> <td>87.1</td> </tr> <tr> <td>36.0</td> <td>84.2</td> <td>86.8</td> </tr> <tr> <td>40.0</td> <td>83.4</td> <td>86.4</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.6	85.8	84.6 ※1	9.0	85.8	85.0 ※1	12.0	86.3	85.8	15.0	86.2	86.6	18.0	86.0	87.1	24.0	85.3	87.3	30.0	84.9	87.1	36.0	84.2	86.8	40.0	83.4	86.4
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
8.6	85.8	84.6 ※1																																	
9.0	85.8	85.0 ※1																																	
12.0	86.3	85.8																																	
15.0	86.2	86.6																																	
18.0	86.0	87.1																																	
24.0	85.3	87.3																																	
30.0	84.9	87.1																																	
36.0	84.2	86.8																																	
40.0	83.4	86.4																																	
		※1: Load 80%																																	



Model	MGFW102412
Item	Efficiency (by Load Ratio)
Object	_____

Temperature 25°C
Testing Circuitry Figure A



2.Values


Load Ratio [%]	Efficiency [%]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0	-	-	-	-	-
20	81.2	80.9	79.5	78.1	75.1
40	85.4	85.4	85.2	84.5	82.6
60	85.7	86.6	86.8	86.3	85.3
80	85.0	86.4	87.2	87.0	86.3
90	84.0	86.1	87.1	87.2	86.4
100	- ※	85.8	87.1	87.3	86.8
110	- ※	85.2	86.9	87.3	86.9
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.



Model	MGFW102412
Item	Line Regulation
Object	+12V0.42A

Temperature 25°C
Testing Circuitry Figure A




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	12.173	- ※
9.0	12.172	- ※
12.0	12.166	12.065
15.0	12.162	12.067
18.0	12.159	12.068
24.0	12.155	12.068
30.0	12.152	12.068
36.0	12.150	12.067
40.0	12.149	12.068

-12V: Rated Load Current

Object	-12V0.42A
--------	-----------




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	-12.213	- ※
9.0	-12.211	- ※
12.0	-12.201	-12.097
15.0	-12.194	-12.096
18.0	-12.190	-12.095
24.0	-12.186	-12.094
30.0	-12.185	-12.094
36.0	-12.183	-12.094
40.0	-12.182	-12.094

+12V: Rated Load Current

Note: Slanted line shows the range of the rated input voltage.

※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.




Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	12.406	12.376	12.349	12.338	12.321
0.084	12.265	12.252	12.239	12.233	12.224
0.168	12.200	12.193	12.184	12.180	12.174
0.252	12.151	12.147	12.142	12.138	12.135
0.336	12.105	12.105	12.103	12.102	12.100
0.378	12.081	12.085	12.086	12.085	12.083
0.420	- ※	12.065	12.068	12.068	12.067
0.462	- ※	12.044	12.050	12.051	12.051
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

-12V: Rated Load Current



2.Values

Load Current [A]	Output Voltage [V]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	-12.457	-12.419	-12.393	-12.382	-12.360
0.084	-12.309	-12.291	-12.274	-12.268	-12.260
0.168	-12.237	-12.226	-12.213	-12.209	-12.205
0.252	-12.186	-12.177	-12.168	-12.165	-12.162
0.336	-12.140	-12.135	-12.129	-12.127	-12.126
0.378	-12.117	-12.116	-12.112	-12.111	-12.110
0.420	- ※	-12.097	-12.095	-12.094	-12.094
0.462	- ※	-12.076	-12.077	-12.076	-12.077
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-


+12V: Rated Load Current

※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.




Model		MGFW102412	
Item		Dynamic Load Response	
Object		+12V0.42A	
Input Volt.		24 V	
-12V:rated load current.		Temperature 25°C	
Cycle 100 ms		Testing Circuitry Figure A	

Input Volt. 24 V
 -12V:rated load current.
 Cycle 100 ms




Min.Load (0A) ←→
 Load 100% (0.42A)

200 mV/div




4 ms/div




4 ms/div

Min.Load (0A) ←→
 Load 50% (0.21A)

200 mV/div




4 ms/div




4 ms/div

Load 50% (0.21A) ←→
 Load 100% (0.42A)

200 mV/div



4 ms/div



4 ms/div



Model	MGFW102412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V0.42A		


Input Volt. 24 V
 +12V:rated load current.
 Cycle 100 ms

t1,t2 = 100 μs




Min.Load (0A) ←→
 Load 100% (0.42A)

200 mV/div




4 ms/div




4 ms/div

Min.Load (0A) ←→
 Load 50% (0.21A)

200 mV/div




4 ms/div




4 ms/div

Load 50% (0.21A) ←→
 Load 100% (0.42A)

200 mV/div



4 ms/div



4 ms/div



<p>Model MGFW102412</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple Voltage (by Load Current)</p>																																								
<p>Object +12V0.42A</p>																																								
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>—△— Input Volt. 12V</p> <p>-·-○-·- Input Volt. 36V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.084</td><td>5</td><td>5</td></tr> <tr><td>0.168</td><td>5</td><td>5</td></tr> <tr><td>0.252</td><td>10</td><td>5</td></tr> <tr><td>0.336</td><td>15</td><td>5</td></tr> <tr><td>0.378</td><td>15</td><td>5</td></tr> <tr><td>0.420</td><td>20</td><td>5</td></tr> <tr><td>0.462</td><td>25</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated Load Current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.000	5	5	0.084	5	5	0.168	5	5	0.252	10	5	0.336	15	5	0.378	15	5	0.420	20	5	0.462	25	5	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 12 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.084	5	5																																						
0.168	5	5																																						
0.252	10	5																																						
0.336	15	5																																						
0.378	15	5																																						
0.420	20	5																																						
0.462	25	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								



<p>Model MGFW102412</p> <p>Item Ripple Voltage (by Load Current)</p> <p>Object -12V0.42A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <div style="display: flex; align-items: center;"> <div style="margin-right: 20px;"> <p>—△— Input Volt. 12V</p> <p>-·-○-·- Input Volt. 36V</p> </div> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.084</td><td>5</td><td>5</td></tr> <tr><td>0.168</td><td>5</td><td>5</td></tr> <tr><td>0.252</td><td>10</td><td>5</td></tr> <tr><td>0.336</td><td>15</td><td>5</td></tr> <tr><td>0.378</td><td>15</td><td>5</td></tr> <tr><td>0.420</td><td>20</td><td>5</td></tr> <tr><td>0.462</td><td>25</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.000	5	5	0.084	5	5	0.168	5	5	0.252	10	5	0.336	15	5	0.378	15	5	0.420	20	5	0.462	25	5	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 12 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.084	5	5																																						
0.168	5	5																																						
0.252	10	5																																						
0.336	15	5																																						
0.378	15	5																																						
0.420	20	5																																						
0.462	25	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope.</p> <p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								



<p>Model MGFW102412</p> <p>Item Ripple-Noise</p> <p>Object +12V0.42A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.084</td><td>10</td><td>5</td></tr> <tr><td>0.168</td><td>10</td><td>5</td></tr> <tr><td>0.252</td><td>10</td><td>5</td></tr> <tr><td>0.336</td><td>15</td><td>10</td></tr> <tr><td>0.420</td><td>20</td><td>10</td></tr> <tr><td>0.462</td><td>25</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.000	5	5	0.084	10	5	0.168	10	5	0.252	10	5	0.336	15	10	0.420	20	10	0.462	25	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 12 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.084	10	5																																						
0.168	10	5																																						
0.252	10	5																																						
0.336	15	10																																						
0.420	20	10																																						
0.462	25	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								




<p>Model MGFW102412</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object -12V0.42A</p>																																								
<p>1.Graph</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.084</td><td>10</td><td>5</td></tr> <tr><td>0.168</td><td>10</td><td>5</td></tr> <tr><td>0.252</td><td>10</td><td>5</td></tr> <tr><td>0.336</td><td>15</td><td>10</td></tr> <tr><td>0.420</td><td>20</td><td>10</td></tr> <tr><td>0.462</td><td>25</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.000	5	5	0.084	10	5	0.168	10	5	0.252	10	5	0.336	15	10	0.420	20	10	0.462	25	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 12 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.084	10	5																																						
0.168	10	5																																						
0.252	10	5																																						
0.336	15	10																																						
0.420	20	10																																						
0.462	25	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								



COSEL	
Model	MGFW102412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.42A

Testing Circuitry Figure B

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	5
-40	5	5
-20	5	5
0	5	5
25	5	5
50	5	5
60	5	5
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

Object	-12V0.42A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	5
-40	5	5
-20	5	5
0	5	5
25	5	5
50	5	5
60	5	5
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.



COSEL																																																																															
Model	MGFW102412																																																																														
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																																													
Object	+12V0.42A																																																																														
1.Graph	<p> —△— Input Volt. 9V - - - □ - - - Input Volt. 12V - · · * · · - · - Input Volt. 18V - · · ○ · · - · - Input Volt. 24V - - ◇ - - Input Volt. 36V </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p>	2.Values																																																																													
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.006</td><td>12.011</td><td>12.013</td><td>12.014</td><td>12.012</td></tr> <tr><td>-40</td><td>12.027</td><td>12.032</td><td>12.035</td><td>12.035</td><td>12.034</td></tr> <tr><td>-20</td><td>12.043</td><td>12.048</td><td>12.051</td><td>12.051</td><td>12.050</td></tr> <tr><td>0</td><td>12.054</td><td>12.058</td><td>12.061</td><td>12.061</td><td>12.060</td></tr> <tr><td>25</td><td>12.060</td><td>12.065</td><td>12.068</td><td>12.068</td><td>12.067</td></tr> <tr><td>50</td><td>12.060</td><td>12.065</td><td>12.069</td><td>12.069</td><td>12.068</td></tr> <tr><td>60</td><td>12.058</td><td>12.064</td><td>12.068</td><td>12.068</td><td>12.068</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated Load Current</p>	Ambient Temperature [°C]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	12.006	12.011	12.013	12.014	12.012	-40	12.027	12.032	12.035	12.035	12.034	-20	12.043	12.048	12.051	12.051	12.050	0	12.054	12.058	12.061	12.061	12.060	25	12.060	12.065	12.068	12.068	12.067	50	12.060	12.065	12.069	12.069	12.068	60	12.058	12.064	12.068	12.068	12.068	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																														
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																										
-60	12.006	12.011	12.013	12.014	12.012																																																																										
-40	12.027	12.032	12.035	12.035	12.034																																																																										
-20	12.043	12.048	12.051	12.051	12.050																																																																										
0	12.054	12.058	12.061	12.061	12.060																																																																										
25	12.060	12.065	12.068	12.068	12.067																																																																										
50	12.060	12.065	12.069	12.069	12.068																																																																										
60	12.058	12.064	12.068	12.068	12.068																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
Object	-12V0.42A																																																																														
1.Graph	<p> —△— Input Volt. 9V - - - □ - - - Input Volt. 12V - · · * · · - · - Input Volt. 18V - · · ○ · · - · - Input Volt. 24V - - ◇ - - Input Volt. 36V </p> <p style="text-align: center;">Output Voltage [V]</p> <p style="text-align: center;">Ambient Temperature [°C]</p>	2.Values																																																																													
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.030</td><td>-12.031</td><td>-12.031</td><td>-12.031</td><td>-12.032</td></tr> <tr><td>-40</td><td>-12.053</td><td>-12.055</td><td>-12.054</td><td>-12.055</td><td>-12.056</td></tr> <tr><td>-20</td><td>-12.072</td><td>-12.073</td><td>-12.072</td><td>-12.072</td><td>-12.073</td></tr> <tr><td>0</td><td>-12.084</td><td>-12.085</td><td>-12.084</td><td>-12.084</td><td>-12.085</td></tr> <tr><td>25</td><td>-12.094</td><td>-12.097</td><td>-12.095</td><td>-12.094</td><td>-12.094</td></tr> <tr><td>50</td><td>-12.097</td><td>-12.097</td><td>-12.096</td><td>-12.095</td><td>-12.095</td></tr> <tr><td>60</td><td>-12.096</td><td>-12.097</td><td>-12.095</td><td>-12.095</td><td>-12.094</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated Load Current</p>	Ambient Temperature [°C]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	-12.030	-12.031	-12.031	-12.031	-12.032	-40	-12.053	-12.055	-12.054	-12.055	-12.056	-20	-12.072	-12.073	-12.072	-12.072	-12.073	0	-12.084	-12.085	-12.084	-12.084	-12.085	25	-12.094	-12.097	-12.095	-12.094	-12.094	50	-12.097	-12.097	-12.096	-12.095	-12.095	60	-12.096	-12.097	-12.095	-12.095	-12.094	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																														
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																										
-60	-12.030	-12.031	-12.031	-12.031	-12.032																																																																										
-40	-12.053	-12.055	-12.054	-12.055	-12.056																																																																										
-20	-12.072	-12.073	-12.072	-12.072	-12.073																																																																										
0	-12.084	-12.085	-12.084	-12.084	-12.085																																																																										
25	-12.094	-12.097	-12.095	-12.094	-12.094																																																																										
50	-12.097	-12.097	-12.096	-12.095	-12.095																																																																										
60	-12.096	-12.097	-12.095	-12.095	-12.094																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
--	-	-	-	-	-																																																																										
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>Note: In case of Input Volt. 9V, Load 80%. Other case Load 100%.</p>																																																																													



COSEL		Testing Circuitry Figure A
Model	MGFW102412	
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 50°C

Input Voltage : 12 - 36V

Load Current (AVR 1) : 0 - 0.42A (AVR 2) : 0 - 0.42A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.42A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	12	0	12.388	±321	±2.7
Minimum Voltage	50	12	0.42	11.746		

Object		-12V0.42A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	12	0	-12.428	±321	±2.7
Minimum Voltage	50	12	0.42	-11.786		




COSEL																									
Model	MGFW102412	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.42A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.060</td></tr> <tr><td>0.5</td><td>12.065</td></tr> <tr><td>1.0</td><td>12.065</td></tr> <tr><td>2.0</td><td>12.065</td></tr> <tr><td>3.0</td><td>12.065</td></tr> <tr><td>4.0</td><td>12.065</td></tr> <tr><td>5.0</td><td>12.065</td></tr> <tr><td>6.0</td><td>12.065</td></tr> <tr><td>7.0</td><td>12.065</td></tr> <tr><td>8.0</td><td>12.065</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated Load Current</p>		Time since start [H]	Output Voltage [V]	0.0	12.060	0.5	12.065	1.0	12.065	2.0	12.065	3.0	12.065	4.0	12.065	5.0	12.065	6.0	12.065	7.0	12.065	8.0	12.065
Time since start [H]	Output Voltage [V]																								
0.0	12.060																								
0.5	12.065																								
1.0	12.065																								
2.0	12.065																								
3.0	12.065																								
4.0	12.065																								
5.0	12.065																								
6.0	12.065																								
7.0	12.065																								
8.0	12.065																								
Object	-12V0.42A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.090</td></tr> <tr><td>0.5</td><td>-12.097</td></tr> <tr><td>1.0</td><td>-12.097</td></tr> <tr><td>2.0</td><td>-12.097</td></tr> <tr><td>3.0</td><td>-12.097</td></tr> <tr><td>4.0</td><td>-12.097</td></tr> <tr><td>5.0</td><td>-12.097</td></tr> <tr><td>6.0</td><td>-12.097</td></tr> <tr><td>7.0</td><td>-12.097</td></tr> <tr><td>8.0</td><td>-12.097</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated Load Current</p>		Time since start [H]	Output Voltage [V]	0.0	-12.090	0.5	-12.097	1.0	-12.097	2.0	-12.097	3.0	-12.097	4.0	-12.097	5.0	-12.097	6.0	-12.097	7.0	-12.097	8.0	-12.097
Time since start [H]	Output Voltage [V]																								
0.0	-12.090																								
0.5	-12.097																								
1.0	-12.097																								
2.0	-12.097																								
3.0	-12.097																								
4.0	-12.097																								
5.0	-12.097																								
6.0	-12.097																								
7.0	-12.097																								
8.0	-12.097																								




Model	MGFW102412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.42A		

1.Graph



2.Values


		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.4	1.8	3.2	0.2	2.4
100 %		1.5	2.3	3.8	0.2	1.1






Model	MGFW102412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V0.42A		

1. Graph



2. Values


Load \ Time	Td	Tr	Ts	Th	Tf
50 %	1.4	1.7	3.1	0.2	2.7
100 %	1.5	2.0	3.5	0.2	1.3





Model	MGFW102412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.42A


Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	7.6	7.6
-40	7.6	7.6
-20	7.6	7.6
0	7.6	7.6
25	7.6	7.6
50	7.5	7.6
60	7.5	7.5
--	-	-
--	-	-
--	-	-
--	-	-


Object	-12V0.42A
--------	-----------



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	7.6	7.6
-40	7.6	7.6
-20	7.6	7.6
0	7.6	7.6
25	7.6	7.6
50	7.5	7.6
60	7.5	7.5
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.




Temperature 25°C
Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
11.4	0.509	0.642	0.710	0.689	0.692
10.8	0.562	0.691	0.761	0.735	0.731
9.6	0.673	0.800	0.874	0.832	0.815
8.4	0.794	0.922	0.988	0.929	0.894
7.2	0.931	1.056	1.097	1.027	0.980
6.0	1.076	1.197	1.215	1.129	1.070
4.8	1.230	1.342	1.333	1.235	1.165
3.6	1.335	1.492	1.459	1.346	1.259
2.4	1.494	1.623	1.602	1.460	1.354
1.2	1.681	1.770	1.729	1.566	1.435
0.0	1.778	1.759	1.593	1.379	1.222
--	-	-	-	-	-

-12V: Rated Load Current



2.Values

Output Voltage [V]	Load Current [A]				
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-11.4	0.511	0.640	0.711	0.693	0.696
-10.8	0.564	0.692	0.766	0.740	0.736
-9.6	0.676	0.801	0.877	0.838	0.817
-8.4	0.804	0.928	0.990	0.935	0.897
-7.2	0.939	1.062	1.104	1.034	0.987
-6.0	1.090	1.205	1.218	1.136	1.077
-4.8	1.241	1.352	1.343	1.247	1.172
-3.6	1.347	1.507	1.475	1.358	1.269
-2.4	1.521	1.646	1.621	1.475	1.364
-1.2	1.733	1.810	1.752	1.587	1.452
0.0	1.829	1.832	1.668	1.455	1.290
--	-	-	-	-	-

+12V: Rated Load Current

Maximum output current at minimum input Voltage is 80% of rated load current.
Refer to instruction manuals for details of input derating.



COSEL																																																																																		
Model	MGFW102412	Temperature 25°C																																																																																
Item	Switching frequency (by Load Current)	Testing Circuitry Figure A																																																																																
Object	+/-12V0.42A																																																																																	
1.Graph	<p>—△— Input Volt. 9V</p> <p>---□--- Input Volt. 12V</p> <p>-··*·-·- Input Volt. 18V</p> <p>-··○-·- Input Volt. 24V</p> <p>--◇-- Input Volt. 36V</p>	2.Values																																																																																
<p>Switching Frequency [kHz]</p> <p>Load Current [A]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>785</td><td>910</td><td>1040</td><td>1100</td><td>1250</td></tr> <tr><td>0.084</td><td>419</td><td>527</td><td>674</td><td>766</td><td>865</td></tr> <tr><td>0.168</td><td>283</td><td>371</td><td>497</td><td>583</td><td>679</td></tr> <tr><td>0.252</td><td>211</td><td>286</td><td>394</td><td>470</td><td>558</td></tr> <tr><td>0.336</td><td>167</td><td>231</td><td>325</td><td>393</td><td>475</td></tr> <tr><td>0.378</td><td>153</td><td>212</td><td>300</td><td>365</td><td>443</td></tr> <tr><td>0.420</td><td>- ※</td><td>193</td><td>276</td><td>338</td><td>412</td></tr> <tr><td>0.462</td><td>- ※</td><td>178</td><td>257</td><td>315</td><td>387</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Current [A]	Input Current [A]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	785	910	1040	1100	1250	0.084	419	527	674	766	865	0.168	283	371	497	583	679	0.252	211	286	394	470	558	0.336	167	231	325	393	475	0.378	153	212	300	365	443	0.420	- ※	193	276	338	412	0.462	- ※	178	257	315	387	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
	Load Current [A]	Input Current [A]																																																																																
		Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																												
	0.000	785	910	1040	1100	1250																																																																												
	0.084	419	527	674	766	865																																																																												
	0.168	283	371	497	583	679																																																																												
	0.252	211	286	394	470	558																																																																												
	0.336	167	231	325	393	475																																																																												
	0.378	153	212	300	365	443																																																																												
	0.420	- ※	193	276	338	412																																																																												
0.462	- ※	178	257	315	387																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p> <p>When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>		<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)