

# TEST DATA OF MGFW32415

Regulated DC Power Supply  
January 6, 2017

Approved by : Takayuki Fukuda  
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi  
Takaaki Sekiguchi Design Engineer

**COSEL CO.,LTD.**




## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Ratio) . . . . .	2
3.Input Power (by Load Ratio) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Ratio) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Switching frequency (by Load Current) . . . . .	22
19.Figure of Testing Circuitry . . . . .	23

(Final Page 23)

**COSEL**

Model	MGFW32415
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C  
Testing Circuitry Figure A

## 2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
6.0	0.003	0.003	0.003
8.0	0.003	0.003	0.003
8.2	0.003	0.003	0.003
8.4	0.026	0.233	0.457
8.6	0.025	0.227	0.452
8.8	0.025	0.221	0.447
9.0	0.024	0.216	0.441
12.0	0.020	0.160	0.316
18.0	0.015	0.108	0.203
24.0	0.012	0.082	0.153
30.0	0.010	0.066	0.125
36.0	0.007	0.056	0.103
40.0	0.007	0.051	0.095
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

**COSEL**

Model	MGFW32415																																																																																
Item	Input Current (by Load Ratio)																																																																																
Object	_____																																																																																
1.Graph	—△— Input Volt. 9V - - -□--- Input Volt. 12V - - -*--- Input Volt. 18V - - -○--- Input Volt. 24V - - -◇--- Input Volt. 36V																																																																																
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.024</td> <td>0.020</td> <td>0.015</td> <td>0.012</td> <td>0.007</td> </tr> <tr> <td>20</td> <td>0.098</td> <td>0.074</td> <td>0.052</td> <td>0.040</td> <td>0.028</td> </tr> <tr> <td>40</td> <td>0.176</td> <td>0.131</td> <td>0.089</td> <td>0.067</td> <td>0.047</td> </tr> <tr> <td>60</td> <td>0.253</td> <td>0.190</td> <td>0.126</td> <td>0.095</td> <td>0.065</td> </tr> <tr> <td>80</td> <td>0.348</td> <td>0.247</td> <td>0.165</td> <td>0.124</td> <td>0.084</td> </tr> <tr> <td>90</td> <td>0.388</td> <td>0.282</td> <td>0.184</td> <td>0.138</td> <td>0.093</td> </tr> <tr> <td>100</td> <td>- ⋆</td> <td>0.316</td> <td>0.203</td> <td>0.153</td> <td>0.103</td> </tr> <tr> <td>110</td> <td>- ⋆</td> <td>0.344</td> <td>0.226</td> <td>0.168</td> <td>0.112</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Ratio [%]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0	0.024	0.020	0.015	0.012	0.007	20	0.098	0.074	0.052	0.040	0.028	40	0.176	0.131	0.089	0.067	0.047	60	0.253	0.190	0.126	0.095	0.065	80	0.348	0.247	0.165	0.124	0.084	90	0.388	0.282	0.184	0.138	0.093	100	- ⋆	0.316	0.203	0.153	0.103	110	- ⋆	0.344	0.226	0.168	0.112	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Current [A]																																																																																
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																												
0	0.024	0.020	0.015	0.012	0.007																																																																												
20	0.098	0.074	0.052	0.040	0.028																																																																												
40	0.176	0.131	0.089	0.067	0.047																																																																												
60	0.253	0.190	0.126	0.095	0.065																																																																												
80	0.348	0.247	0.165	0.124	0.084																																																																												
90	0.388	0.282	0.184	0.138	0.093																																																																												
100	- ⋆	0.316	0.203	0.153	0.103																																																																												
110	- ⋆	0.344	0.226	0.168	0.112																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
	⋆ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																

**COSEL**


Model	MGFW32415																																																																																	
Item	Input Power (by Load Ratio)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 9V</li> <li>Input Volt. 12V</li> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> </ul> <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.22</td><td>0.24</td><td>0.27</td><td>0.30</td><td>0.25</td></tr> <tr><td>20</td><td>0.87</td><td>0.89</td><td>0.93</td><td>0.95</td><td>1.02</td></tr> <tr><td>40</td><td>1.56</td><td>1.56</td><td>1.59</td><td>1.61</td><td>1.68</td></tr> <tr><td>60</td><td>2.29</td><td>2.26</td><td>2.27</td><td>2.29</td><td>2.36</td></tr> <tr><td>80</td><td>3.07</td><td>2.99</td><td>2.96</td><td>2.97</td><td>3.02</td></tr> <tr><td>90</td><td>3.47</td><td>3.37</td><td>3.31</td><td>3.32</td><td>3.36</td></tr> <tr><td>100</td><td>-</td><td>3.75</td><td>3.67</td><td>3.66</td><td>3.69</td></tr> <tr><td>110</td><td>-</td><td>4.14</td><td>4.04</td><td>4.02</td><td>4.05</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	9[V]	12[V]	18[V]	24[V]	36[V]	0	0.22	0.24	0.27	0.30	0.25	20	0.87	0.89	0.93	0.95	1.02	40	1.56	1.56	1.59	1.61	1.68	60	2.29	2.26	2.27	2.29	2.36	80	3.07	2.99	2.96	2.97	3.02	90	3.47	3.37	3.31	3.32	3.36	100	-	3.75	3.67	3.66	3.69	110	-	4.14	4.04	4.02	4.05	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Ratio [%]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	0.22	0.24	0.27	0.30	0.25																																																																													
20	0.87	0.89	0.93	0.95	1.02																																																																													
40	1.56	1.56	1.59	1.61	1.68																																																																													
60	2.29	2.26	2.27	2.29	2.36																																																																													
80	3.07	2.99	2.96	2.97	3.02																																																																													
90	3.47	3.37	3.31	3.32	3.36																																																																													
100	-	3.75	3.67	3.66	3.69																																																																													
110	-	4.14	4.04	4.02	4.05																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.22</td><td>0.24</td><td>0.27</td><td>0.30</td><td>0.25</td></tr> <tr><td>20</td><td>0.87</td><td>0.89</td><td>0.93</td><td>0.95</td><td>1.02</td></tr> <tr><td>40</td><td>1.56</td><td>1.56</td><td>1.59</td><td>1.61</td><td>1.68</td></tr> <tr><td>60</td><td>2.29</td><td>2.26</td><td>2.27</td><td>2.29</td><td>2.36</td></tr> <tr><td>80</td><td>3.07</td><td>2.99</td><td>2.96</td><td>2.97</td><td>3.02</td></tr> <tr><td>90</td><td>3.47</td><td>3.37</td><td>3.31</td><td>3.32</td><td>3.36</td></tr> <tr><td>100</td><td>-</td><td>3.75</td><td>3.67</td><td>3.66</td><td>3.69</td></tr> <tr><td>110</td><td>-</td><td>4.14</td><td>4.04</td><td>4.02</td><td>4.05</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Input Power [W]					9[V]	12[V]	18[V]	24[V]	36[V]	0	0.22	0.24	0.27	0.30	0.25	20	0.87	0.89	0.93	0.95	1.02	40	1.56	1.56	1.59	1.61	1.68	60	2.29	2.26	2.27	2.29	2.36	80	3.07	2.99	2.96	2.97	3.02	90	3.47	3.37	3.31	3.32	3.36	100	-	3.75	3.67	3.66	3.69	110	-	4.14	4.04	4.02	4.05	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Power [W]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	0.22	0.24	0.27	0.30	0.25																																																																													
20	0.87	0.89	0.93	0.95	1.02																																																																													
40	1.56	1.56	1.59	1.61	1.68																																																																													
60	2.29	2.26	2.27	2.29	2.36																																																																													
80	3.07	2.99	2.96	2.97	3.02																																																																													
90	3.47	3.37	3.31	3.32	3.36																																																																													
100	-	3.75	3.67	3.66	3.69																																																																													
110	-	4.14	4.04	4.02	4.05																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
	<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																	

**COSEL**

Model	MGFW32415
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
8.6	77.9	77.8
9.0	78.0	78.4
12.0	78.5	80.0
15.0	78.8	81.3
18.0	78.1	82.0
24.0	77.1	81.9
30.0	76.0	81.8
36.0	74.6	81.4
40.0	74.0	80.4

※1: Load 80%

Note: Slanted line shows the range of the rated input voltage.

**COSEL**


Model	MGFW32415																																																																																	
Item	Efficiency (by Load Ratio)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Efficiency [%]</p> <p>Load Ratio [%]</p> <ul style="list-style-type: none"> <li>—△— Input Volt. 9V</li> <li>- -□--- Input Volt. 12V</li> <li>- ·*·— Input Volt. 18V</li> <li>- ·○·— Input Volt. 24V</li> <li>- ·◇·— Input Volt. 36V</li> </ul>																																																																																	
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>67.0</td><td>68.1</td><td>64.1</td><td>63.0</td><td>58.6</td></tr> <tr> <td>40</td><td>76.0</td><td>77.0</td><td>75.7</td><td>74.2</td><td>71.7</td></tr> <tr> <td>60</td><td>78.7</td><td>79.3</td><td>79.3</td><td>78.3</td><td>76.6</td></tr> <tr> <td>80</td><td>78.4</td><td>80.2</td><td>81.3</td><td>80.7</td><td>79.3</td></tr> <tr> <td>90</td><td>77.9</td><td>80.1</td><td>81.7</td><td>81.4</td><td>80.4</td></tr> <tr> <td>100</td><td>-</td><td>※</td><td>80.0</td><td>82.0</td><td>81.9</td></tr> <tr> <td>110</td><td>-</td><td>※</td><td>80.0</td><td>81.7</td><td>82.2</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Efficiency [%]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	-	-	20	67.0	68.1	64.1	63.0	58.6	40	76.0	77.0	75.7	74.2	71.7	60	78.7	79.3	79.3	78.3	76.6	80	78.4	80.2	81.3	80.7	79.3	90	77.9	80.1	81.7	81.4	80.4	100	-	※	80.0	82.0	81.9	110	-	※	80.0	81.7	82.2	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Efficiency [%]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0	-	-	-	-	-																																																																													
20	67.0	68.1	64.1	63.0	58.6																																																																													
40	76.0	77.0	75.7	74.2	71.7																																																																													
60	78.7	79.3	79.3	78.3	76.6																																																																													
80	78.4	80.2	81.3	80.7	79.3																																																																													
90	77.9	80.1	81.7	81.4	80.4																																																																													
100	-	※	80.0	82.0	81.9																																																																													
110	-	※	80.0	81.7	82.2																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																		

**COSEL**

Model	MGFW32415
Item	Line Regulation
Object	+15V0.1A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	15.172	- *
9.0	15.169	- *
12.0	15.154	15.017
15.0	15.146	15.022
18.0	15.139	15.024
24.0	15.133	15.027
30.0	15.129	15.028
36.0	15.126	15.029
40.0	15.125	15.029

-15V: Rated Load Current

## Object -15V0.1A

## 1.Graph



## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
8.6	-15.226	- *
9.0	-15.220	- *
12.0	-15.194	-15.067
15.0	-15.177	-15.063
18.0	-15.166	-15.059
24.0	-15.152	-15.053
30.0	-15.144	-15.050
36.0	-15.138	-15.047
40.0	-15.136	-15.046

+15V: Rated Load Current


Note: Slanted line shows the range of the rated input voltage.

※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFW32415	Temperature Testing Circuitry	25°C Figure A																																																																														
Item	Load Regulation																																																																																
Object	+15V0.1A																																																																																
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>—△— Input Volt. 9V</li> <li>- - □ - - Input Volt. 12V</li> <li>- - * - - Input Volt. 18V</li> <li>- - ○ - - Input Volt. 24V</li> <li>- - ◆ - - Input Volt. 36V</li> </ul>																																																																																
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.383</td><td>15.337</td><td>15.297</td><td>15.279</td><td>15.264</td></tr> <tr><td>0.02</td><td>15.278</td><td>15.247</td><td>15.218</td><td>15.206</td><td>15.194</td></tr> <tr><td>0.04</td><td>15.204</td><td>15.184</td><td>15.165</td><td>15.156</td><td>15.148</td></tr> <tr><td>0.06</td><td>15.136</td><td>15.126</td><td>15.116</td><td>15.111</td><td>15.106</td></tr> <tr><td>0.08</td><td>15.070</td><td>15.070</td><td>15.069</td><td>15.068</td><td>15.067</td></tr> <tr><td>0.09</td><td>15.036</td><td>15.044</td><td>15.047</td><td>15.048</td><td>15.048</td></tr> <tr><td>0.10</td><td>-</td><td>15.017</td><td>15.024</td><td>15.027</td><td>15.029</td></tr> <tr><td>0.11</td><td>-</td><td>14.989</td><td>15.001</td><td>15.006</td><td>15.010</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>			Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	15.383	15.337	15.297	15.279	15.264	0.02	15.278	15.247	15.218	15.206	15.194	0.04	15.204	15.184	15.165	15.156	15.148	0.06	15.136	15.126	15.116	15.111	15.106	0.08	15.070	15.070	15.069	15.068	15.067	0.09	15.036	15.044	15.047	15.048	15.048	0.10	-	15.017	15.024	15.027	15.029	0.11	-	14.989	15.001	15.006	15.010	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	
Load Current [A]	Output Voltage [V]																																																																																
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																												
0.00	15.383	15.337	15.297	15.279	15.264																																																																												
0.02	15.278	15.247	15.218	15.206	15.194																																																																												
0.04	15.204	15.184	15.165	15.156	15.148																																																																												
0.06	15.136	15.126	15.116	15.111	15.106																																																																												
0.08	15.070	15.070	15.069	15.068	15.067																																																																												
0.09	15.036	15.044	15.047	15.048	15.048																																																																												
0.10	-	15.017	15.024	15.027	15.029																																																																												
0.11	-	14.989	15.001	15.006	15.010																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
Object	-15V0.1A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.422</td><td>-15.365</td><td>-15.314</td><td>-15.290</td><td>-15.270</td></tr> <tr><td>0.02</td><td>-15.322</td><td>-15.279</td><td>-15.238</td><td>-15.219</td><td>-15.202</td></tr> <tr><td>0.04</td><td>-15.253</td><td>-15.221</td><td>-15.189</td><td>-15.173</td><td>-15.159</td></tr> <tr><td>0.06</td><td>-15.190</td><td>-15.168</td><td>-15.144</td><td>-15.132</td><td>-15.120</td></tr> <tr><td>0.08</td><td>-15.130</td><td>-15.117</td><td>-15.101</td><td>-15.091</td><td>-15.083</td></tr> <tr><td>0.09</td><td>-15.099</td><td>-15.092</td><td>-15.080</td><td>-15.072</td><td>-15.065</td></tr> <tr><td>0.10</td><td>-</td><td>15.067</td><td>-15.059</td><td>-15.053</td><td>-15.047</td></tr> <tr><td>0.11</td><td>-</td><td>15.043</td><td>-15.038</td><td>-15.034</td><td>-15.030</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p> <p>* Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>			Load Current [A]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	-15.422	-15.365	-15.314	-15.290	-15.270	0.02	-15.322	-15.279	-15.238	-15.219	-15.202	0.04	-15.253	-15.221	-15.189	-15.173	-15.159	0.06	-15.190	-15.168	-15.144	-15.132	-15.120	0.08	-15.130	-15.117	-15.101	-15.091	-15.083	0.09	-15.099	-15.092	-15.080	-15.072	-15.065	0.10	-	15.067	-15.059	-15.053	-15.047	0.11	-	15.043	-15.038	-15.034	-15.030	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																												
0.00	-15.422	-15.365	-15.314	-15.290	-15.270																																																																												
0.02	-15.322	-15.279	-15.238	-15.219	-15.202																																																																												
0.04	-15.253	-15.221	-15.189	-15.173	-15.159																																																																												
0.06	-15.190	-15.168	-15.144	-15.132	-15.120																																																																												
0.08	-15.130	-15.117	-15.101	-15.091	-15.083																																																																												
0.09	-15.099	-15.092	-15.080	-15.072	-15.065																																																																												
0.10	-	15.067	-15.059	-15.053	-15.047																																																																												
0.11	-	15.043	-15.038	-15.034	-15.030																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												
--	-	-	-	-	-																																																																												

Note: Slanted line shows the range of the rated load current.

**COSEL**


**COSEL**

Model	MGFW32415	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-15V0.1A		

Input Volt. 24 V

+15V:rated load current.


Cycle 100 ms

t1,t2 = 100  $\mu$  s

Min.Load (0A)↔  
Load 100% (0.1A)

200 mV/div

4 ms/div




4 ms/div

Min.Load (0A)↔  
Load 50% (0.05A)

200 mV/div

4 ms/div




4 ms/div

Load 50% (0.05A)↔  
Load 100% (0.1A)

200 mV/div

4 ms/div



4 ms/div

**COSEL**

Model	MGFW32415																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V0.1A																																							
1.Graph																																								
		2.Values																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>5</td></tr> <tr><td>0.02</td><td>10</td><td>10</td></tr> <tr><td>0.04</td><td>25</td><td>15</td></tr> <tr><td>0.06</td><td>40</td><td>20</td></tr> <tr><td>0.08</td><td>55</td><td>25</td></tr> <tr><td>0.09</td><td>60</td><td>30</td></tr> <tr><td>0.10</td><td>70</td><td>35</td></tr> <tr><td>0.11</td><td>75</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.00	10	5	0.02	10	10	0.04	25	15	0.06	40	20	0.08	55	25	0.09	60	30	0.10	70	35	0.11	75	35	--	-	-	--	-	-	--	-	-	-15V: Rated Load Current
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 12 [V]	Input Volt. 36 [V]																																						
0.00	10	5																																						
0.02	10	10																																						
0.04	25	15																																						
0.06	40	20																																						
0.08	55	25																																						
0.09	60	30																																						
0.10	70	35																																						
0.11	75	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope.      Ripple Voltage is shown as p-p in the figure below.      Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								

**COSEL**


Model	MGFW32415																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-15V0.1A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0.00 to 0.12 A. Two curves are plotted: one for Input Volt. 12V (solid line with triangle markers) and one for Input Volt. 36V (dashed line with circle markers). Both curves show an increase in ripple voltage as load current increases. A slanted line on the graph indicates the rated load current range.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 12 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>5</td></tr> <tr><td>0.02</td><td>10</td><td>10</td></tr> <tr><td>0.04</td><td>25</td><td>15</td></tr> <tr><td>0.06</td><td>40</td><td>20</td></tr> <tr><td>0.08</td><td>55</td><td>25</td></tr> <tr><td>0.09</td><td>60</td><td>30</td></tr> <tr><td>0.10</td><td>70</td><td>35</td></tr> <tr><td>0.11</td><td>75</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 12 [V]	Input Volt. 36 [V]	0.00	10	5	0.02	10	10	0.04	25	15	0.06	40	20	0.08	55	25	0.09	60	30	0.10	70	35	0.11	75	35	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 12 [V]	Input Volt. 36 [V]																																						
0.00	10	5																																						
0.02	10	10																																						
0.04	25	15																																						
0.06	40	20																																						
0.08	55	25																																						
0.09	60	30																																						
0.10	70	35																																						
0.11	75	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

**COSEL**

Model	MGFW32415
Item	Ripple-Noise
Object	+15V0.1A

 Temperature 25°C  
 Testing Circuitry Figure B

## 1.Graph



## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 12 [V]	Input Volt. 36 [V]
0.00	10	10
0.02	15	15
0.04	35	25
0.06	45	30
0.08	65	35
0.09	70	40
0.10	75	45
0.11	85	45
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current

Measured by 100 MHz Oscilloscope.  
 Ripple-Noise is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form


**COSEL**

Model MGFW32415

Item Ripple-Noise

Object -15V0.1A

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

Temperature 25°C  
Testing Circuitry Figure B

## 2. Values


Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 12 [V]	Input Volt. 36 [V]
0.00	10	10
0.02	15	15
0.04	35	25
0.06	45	30
0.08	65	35
0.09	70	40
0.10	75	45
0.11	85	45
--	-	-
--	-	-
--	-	-

+15V: Rated Load Current

**COSEL**

Model	MGFW32415
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V0.1A

## 1.Graph




Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	25	40
-40	25	35
-20	20	35
0	20	35
25	20	35
80	20	35
90	20	40
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current



## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	25	40
-40	25	35
-20	20	35
0	20	35
25	20	35
80	20	35
90	20	40
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	MGFW32415	Testing Circuitry Figure A																																																																																	
Item	Ambient Temperature Drift																																																																																		
Object	+15V0.1A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 9V</li> <li>Input Volt. 12V</li> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> </ul>	2.Values																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>14.980</td><td>14.978</td><td>14.983</td><td>14.985</td><td>14.988</td></tr> <tr><td>-40</td><td>14.995</td><td>14.993</td><td>14.998</td><td>15.001</td><td>15.003</td></tr> <tr><td>-20</td><td>15.008</td><td>15.005</td><td>15.011</td><td>15.014</td><td>15.016</td></tr> <tr><td>0</td><td>15.015</td><td>15.012</td><td>15.018</td><td>15.021</td><td>15.023</td></tr> <tr><td>25</td><td>15.021</td><td>15.017</td><td>15.024</td><td>15.027</td><td>15.029</td></tr> <tr><td>80</td><td>15.006</td><td>15.002</td><td>15.010</td><td>15.014</td><td>15.016</td></tr> <tr><td>90</td><td>15.004</td><td>14.999</td><td>15.008</td><td>15.011</td><td>15.014</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	-60	14.980	14.978	14.983	14.985	14.988	-40	14.995	14.993	14.998	15.001	15.003	-20	15.008	15.005	15.011	15.014	15.016	0	15.015	15.012	15.018	15.021	15.023	25	15.021	15.017	15.024	15.027	15.029	80	15.006	15.002	15.010	15.014	15.016	90	15.004	14.999	15.008	15.011	15.014	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
-60	14.980	14.978	14.983	14.985	14.988																																																																														
-40	14.995	14.993	14.998	15.001	15.003																																																																														
-20	15.008	15.005	15.011	15.014	15.016																																																																														
0	15.015	15.012	15.018	15.021	15.023																																																																														
25	15.021	15.017	15.024	15.027	15.029																																																																														
80	15.006	15.002	15.010	15.014	15.016																																																																														
90	15.004	14.999	15.008	15.011	15.014																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
		-15V: Rated Load Current																																																																																	
Object	-15V0.1A																																																																																		
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 9V</li> <li>Input Volt. 12V</li> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> </ul>	2.Values																																																																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-15.027</td><td>-15.030</td><td>-15.024</td><td>-15.018</td><td>-15.008</td></tr> <tr><td>-40</td><td>-15.040</td><td>-15.044</td><td>-15.037</td><td>-15.031</td><td>-15.023</td></tr> <tr><td>-20</td><td>-15.051</td><td>-15.055</td><td>-15.047</td><td>-15.041</td><td>-15.034</td></tr> <tr><td>0</td><td>-15.056</td><td>-15.060</td><td>-15.052</td><td>-15.047</td><td>-15.040</td></tr> <tr><td>25</td><td>-15.063</td><td>-15.067</td><td>-15.059</td><td>-15.053</td><td>-15.047</td></tr> <tr><td>80</td><td>-15.046</td><td>-15.050</td><td>-15.042</td><td>-15.037</td><td>-15.032</td></tr> <tr><td>90</td><td>-15.044</td><td>-15.048</td><td>-15.039</td><td>-15.035</td><td>-15.030</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Ambient Temperature [°C]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	-60	-15.027	-15.030	-15.024	-15.018	-15.008	-40	-15.040	-15.044	-15.037	-15.031	-15.023	-20	-15.051	-15.055	-15.047	-15.041	-15.034	0	-15.056	-15.060	-15.052	-15.047	-15.040	25	-15.063	-15.067	-15.059	-15.053	-15.047	80	-15.046	-15.050	-15.042	-15.037	-15.032	90	-15.044	-15.048	-15.039	-15.035	-15.030	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																		
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																														
-60	-15.027	-15.030	-15.024	-15.018	-15.008																																																																														
-40	-15.040	-15.044	-15.037	-15.031	-15.023																																																																														
-20	-15.051	-15.055	-15.047	-15.041	-15.034																																																																														
0	-15.056	-15.060	-15.052	-15.047	-15.040																																																																														
25	-15.063	-15.067	-15.059	-15.053	-15.047																																																																														
80	-15.046	-15.050	-15.042	-15.037	-15.032																																																																														
90	-15.044	-15.048	-15.039	-15.035	-15.030																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
--	-	-	-	-	-																																																																														
		+15V: Rated Load Current																																																																																	
Note: Slanted line shows the range of the rated ambient temperature.			Note: In case of Input Volt. 9V, Load 80%. Other case Load 100%.																																																																																



Model	MGFW32415	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 80°C

Input Voltage : 12 - 36V

Load Current (AVR 1) : 0 - 0.1A (AVR 2) : 0 - 0.1A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object	+15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	80	12	0	15.339	±312	±2.1
Minimum Voltage	80	12	0.1	14.715		


Object	-15V0.1A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	80	12	0	-15.364	±312	±2.1
Minimum Voltage	80	12	0.1	-14.741		

**COSEL**

Model	MGFW32415
Item	Time Lapse Drift
Object	+15V0.1A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Time since start [H]	Output Voltage [V]
0.0	15.023
0.5	15.022
1.0	15.022
2.0	15.022
3.0	15.022
4.0	15.022
5.0	15.021
6.0	15.022
7.0	15.022
8.0	15.022

-15V: Rated Load Current

## 1.Graph



## 2.Values

Time since start [H]	Output Voltage [V]
0.0	-15.055
0.5	-15.054
1.0	-15.055
2.0	-15.055
3.0	-15.055
4.0	-15.055
5.0	-15.055
6.0	-15.055
7.0	-15.055
8.0	-15.055

+15V: Rated Load Current


Input Volt. 24V  
Load 100%

**COSEL**

Model	MGFW32415
Item	Rise and Fall Time
Object	+15V0.1A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	$T_d$	$T_r$	$T_s$	$T_h$	$T_f$
50 %		1.3	0.9	2.2	0.3	6.7
100 %		1.3	1.2	2.5	0.2	3.3




**COSEL**

Model	MGFW32415
Item	Rise and Fall Time
Object	-15V0.1A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		1.3	0.9	2.2	0.4	7.6	
100 %		1.3	1.2	2.5	0.3	3.8	




**COSEL**

Model	MGFW32415
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V0.1A

Testing Circuitry Figure A

## 1.Graph




## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	7.4	7.5
-40	7.4	7.4
-20	7.4	7.4
0	7.4	7.4
25	7.3	7.4
80	7.3	7.4
90	7.3	7.4
--	-	-
--	-	-
--	-	-
--	-	-

Object	-15V0.1A
--------	----------

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 80%
-60	7.4	7.5
-40	7.4	7.4
-20	7.4	7.4
0	7.4	7.4
25	7.3	7.4
80	7.3	7.4
90	7.3	7.4
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

**COSEL**

Model	MGFW32415	Temperature	25°C																																																																																			
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																																			
Object	+15V0.1A																																																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																																					
	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>																																																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>14.3</td><td>0.114</td><td>0.146</td><td>0.151</td><td>0.147</td><td>0.149</td></tr> <tr><td>13.5</td><td>0.126</td><td>0.159</td><td>0.165</td><td>0.159</td><td>0.160</td></tr> <tr><td>12.0</td><td>0.151</td><td>0.188</td><td>0.193</td><td>0.184</td><td>0.184</td></tr> <tr><td>10.5</td><td>0.181</td><td>0.218</td><td>0.221</td><td>0.211</td><td>0.208</td></tr> <tr><td>9.0</td><td>0.212</td><td>0.252</td><td>0.252</td><td>0.238</td><td>0.234</td></tr> <tr><td>7.5</td><td>0.248</td><td>0.287</td><td>0.283</td><td>0.267</td><td>0.261</td></tr> <tr><td>6.0</td><td>0.288</td><td>0.326</td><td>0.316</td><td>0.297</td><td>0.288</td></tr> <tr><td>4.5</td><td>0.330</td><td>0.367</td><td>0.351</td><td>0.328</td><td>0.316</td></tr> <tr><td>3.0</td><td>0.377</td><td>0.410</td><td>0.386</td><td>0.359</td><td>0.343</td></tr> <tr><td>1.5</td><td>0.424</td><td>0.448</td><td>0.415</td><td>0.384</td><td>0.363</td></tr> <tr><td>0.0</td><td>0.399</td><td>0.409</td><td>0.356</td><td>0.324</td><td>0.301</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	14.3	0.114	0.146	0.151	0.147	0.149	13.5	0.126	0.159	0.165	0.159	0.160	12.0	0.151	0.188	0.193	0.184	0.184	10.5	0.181	0.218	0.221	0.211	0.208	9.0	0.212	0.252	0.252	0.238	0.234	7.5	0.248	0.287	0.283	0.267	0.261	6.0	0.288	0.326	0.316	0.297	0.288	4.5	0.330	0.367	0.351	0.328	0.316	3.0	0.377	0.410	0.386	0.359	0.343	1.5	0.424	0.448	0.415	0.384	0.363	0.0	0.399	0.409	0.356	0.324	0.301	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																																	
14.3	0.114	0.146	0.151	0.147	0.149																																																																																	
13.5	0.126	0.159	0.165	0.159	0.160																																																																																	
12.0	0.151	0.188	0.193	0.184	0.184																																																																																	
10.5	0.181	0.218	0.221	0.211	0.208																																																																																	
9.0	0.212	0.252	0.252	0.238	0.234																																																																																	
7.5	0.248	0.287	0.283	0.267	0.261																																																																																	
6.0	0.288	0.326	0.316	0.297	0.288																																																																																	
4.5	0.330	0.367	0.351	0.328	0.316																																																																																	
3.0	0.377	0.410	0.386	0.359	0.343																																																																																	
1.5	0.424	0.448	0.415	0.384	0.363																																																																																	
0.0	0.399	0.409	0.356	0.324	0.301																																																																																	
--	-	-	-	-	-																																																																																	
	<p>-15V: Rated Load Current</p>																																																																																					
Object	-15V0.1A																																																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																																					
	<p>Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V</p>																																																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-14.3</td><td>0.114</td><td>0.147</td><td>0.152</td><td>0.147</td><td>0.150</td></tr> <tr><td>-13.5</td><td>0.127</td><td>0.160</td><td>0.165</td><td>0.159</td><td>0.161</td></tr> <tr><td>-12.0</td><td>0.152</td><td>0.189</td><td>0.193</td><td>0.184</td><td>0.184</td></tr> <tr><td>-10.5</td><td>0.181</td><td>0.220</td><td>0.222</td><td>0.210</td><td>0.209</td></tr> <tr><td>-9.0</td><td>0.213</td><td>0.253</td><td>0.252</td><td>0.238</td><td>0.234</td></tr> <tr><td>-7.5</td><td>0.249</td><td>0.289</td><td>0.283</td><td>0.266</td><td>0.262</td></tr> <tr><td>-6.0</td><td>0.289</td><td>0.327</td><td>0.315</td><td>0.296</td><td>0.288</td></tr> <tr><td>-4.5</td><td>0.332</td><td>0.367</td><td>0.351</td><td>0.328</td><td>0.316</td></tr> <tr><td>-3.0</td><td>0.380</td><td>0.411</td><td>0.387</td><td>0.360</td><td>0.344</td></tr> <tr><td>-1.5</td><td>0.425</td><td>0.449</td><td>0.417</td><td>0.385</td><td>0.364</td></tr> <tr><td>0.0</td><td>0.416</td><td>0.415</td><td>0.358</td><td>0.324</td><td>0.301</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	-14.3	0.114	0.147	0.152	0.147	0.150	-13.5	0.127	0.160	0.165	0.159	0.161	-12.0	0.152	0.189	0.193	0.184	0.184	-10.5	0.181	0.220	0.222	0.210	0.209	-9.0	0.213	0.253	0.252	0.238	0.234	-7.5	0.249	0.289	0.283	0.266	0.262	-6.0	0.289	0.327	0.315	0.296	0.288	-4.5	0.332	0.367	0.351	0.328	0.316	-3.0	0.380	0.411	0.387	0.360	0.344	-1.5	0.425	0.449	0.417	0.385	0.364	0.0	0.416	0.415	0.358	0.324	0.301	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																																	
-14.3	0.114	0.147	0.152	0.147	0.150																																																																																	
-13.5	0.127	0.160	0.165	0.159	0.161																																																																																	
-12.0	0.152	0.189	0.193	0.184	0.184																																																																																	
-10.5	0.181	0.220	0.222	0.210	0.209																																																																																	
-9.0	0.213	0.253	0.252	0.238	0.234																																																																																	
-7.5	0.249	0.289	0.283	0.266	0.262																																																																																	
-6.0	0.289	0.327	0.315	0.296	0.288																																																																																	
-4.5	0.332	0.367	0.351	0.328	0.316																																																																																	
-3.0	0.380	0.411	0.387	0.360	0.344																																																																																	
-1.5	0.425	0.449	0.417	0.385	0.364																																																																																	
0.0	0.416	0.415	0.358	0.324	0.301																																																																																	
--	-	-	-	-	-																																																																																	
	<p>+15V: Rated Load Current</p>																																																																																					
Note: Slanted line shows the range of the rated load current.																																																																																						
Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																						

**COSEL**

Model	MGFW32415																																																																																	
Item	Switching frequency (by Load Current)				Temperature 25°C Testing Circuitry Figure A																																																																													
Object	+/-15V0.1A																																																																																	
1.Graph																																																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>644</td> <td>740</td> <td>860</td> <td>930</td> <td>1020</td> </tr> <tr> <td>0.02</td> <td>397</td> <td>496</td> <td>630</td> <td>710</td> <td>795</td> </tr> <tr> <td>0.04</td> <td>286</td> <td>372</td> <td>493</td> <td>573</td> <td>660</td> </tr> <tr> <td>0.06</td> <td>222</td> <td>298</td> <td>406</td> <td>480</td> <td>564</td> </tr> <tr> <td>0.08</td> <td>179</td> <td>246</td> <td>344</td> <td>413</td> <td>492</td> </tr> <tr> <td>0.09</td> <td>164</td> <td>227</td> <td>321</td> <td>387</td> <td>465</td> </tr> <tr> <td>0.10</td> <td>-</td> <td>209</td> <td>297</td> <td>361</td> <td>437</td> </tr> <tr> <td>0.11</td> <td>-</td> <td>194</td> <td>279</td> <td>339</td> <td>414</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0.00	644	740	860	930	1020	0.02	397	496	630	710	795	0.04	286	372	493	573	660	0.06	222	298	406	480	564	0.08	179	246	344	413	492	0.09	164	227	321	387	465	0.10	-	209	297	361	437	0.11	-	194	279	339	414	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0.00	644	740	860	930	1020																																																																													
0.02	397	496	630	710	795																																																																													
0.04	286	372	493	573	660																																																																													
0.06	222	298	406	480	564																																																																													
0.08	179	246	344	413	492																																																																													
0.09	164	227	321	387	465																																																																													
0.10	-	209	297	361	437																																																																													
0.11	-	194	279	339	414																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Note:	Slanted line shows the range of the rated load current.																																																																																	
	When load current is low, MG operates intermittently, so switching frequency would not become constant.																																																																																	
	※ Maximum output current at minimum input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)