

# TEST DATA OF MGFW404815

Regulated DC Power Supply

Approved by : Junichi Hatagishi  
Junichi Hatagishi                                  Design Manager

Prepared by : Shohei Mukaide  
Shohei Mukaide                                  Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Overvoltage Protection . . . . .	22
19.Switching frequency (by Load Current) . . . . .	23
20.Figure of Testing Circuitry . . . . .	24

(Final Page 24)

**COSEL**

Model	MGFW404815																																																																																		
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																																
Object	_____																																																																																		
1.Graph	<p style="text-align: center;">—△— Load 100%        - - -□- - Load 50%        - - -○- - Load 0%</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>15.2</td><td>0.004</td><td>0.004</td><td>- ✕</td></tr> <tr><td>15.6</td><td>0.004</td><td>0.004</td><td>- ✕</td></tr> <tr><td>16.0</td><td>0.004</td><td>0.004</td><td>- ✕</td></tr> <tr><td>16.4</td><td>0.004</td><td>0.004</td><td>- ✕</td></tr> <tr><td>16.8</td><td>0.041</td><td>1.376</td><td>- ✕</td></tr> <tr><td>17.2</td><td>0.040</td><td>1.342</td><td>- ✕</td></tr> <tr><td>17.6</td><td>0.039</td><td>1.310</td><td>- ✕</td></tr> <tr><td>18.0</td><td>0.038</td><td>1.280</td><td>- ✕</td></tr> <tr><td>24.0</td><td>0.031</td><td>0.956</td><td>- ✕</td></tr> <tr><td>36.0</td><td>0.023</td><td>0.635</td><td>1.273</td></tr> <tr><td>48.0</td><td>0.020</td><td>0.480</td><td>0.953</td></tr> <tr><td>76.0</td><td>0.010</td><td>0.311</td><td>0.605</td></tr> <tr><td>80.0</td><td>0.010</td><td>0.297</td><td>0.576</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	15.2	0.004	0.004	- ✕	15.6	0.004	0.004	- ✕	16.0	0.004	0.004	- ✕	16.4	0.004	0.004	- ✕	16.8	0.041	1.376	- ✕	17.2	0.040	1.342	- ✕	17.6	0.039	1.310	- ✕	18.0	0.038	1.280	- ✕	24.0	0.031	0.956	- ✕	36.0	0.023	0.635	1.273	48.0	0.020	0.480	0.953	76.0	0.010	0.311	0.605	80.0	0.010	0.297	0.576	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																		
	Load 0%	Load 50%	Load 100%																																																																																
0.0	0.000	0.000	0.000																																																																																
15.2	0.004	0.004	- ✕																																																																																
15.6	0.004	0.004	- ✕																																																																																
16.0	0.004	0.004	- ✕																																																																																
16.4	0.004	0.004	- ✕																																																																																
16.8	0.041	1.376	- ✕																																																																																
17.2	0.040	1.342	- ✕																																																																																
17.6	0.039	1.310	- ✕																																																																																
18.0	0.038	1.280	- ✕																																																																																
24.0	0.031	0.956	- ✕																																																																																
36.0	0.023	0.635	1.273																																																																																
48.0	0.020	0.480	0.953																																																																																
76.0	0.010	0.311	0.605																																																																																
80.0	0.010	0.297	0.576																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
--	-	-	-																																																																																
Note:	Slanted line shows the range of the rated input voltage.																																																																																		

※During this area, overcurrent protection activates and power supply operates in hiccup mode.

**COSEL**

Model	MGFW404815																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.038</td><td>0.031</td><td>0.023</td><td>0.020</td><td>0.010</td></tr> <tr><td>20</td><td>0.537</td><td>0.406</td><td>0.271</td><td>0.206</td><td>0.137</td></tr> <tr><td>40</td><td>1.042</td><td>0.782</td><td>0.523</td><td>0.395</td><td>0.258</td></tr> <tr><td>60</td><td>1.554</td><td>1.159</td><td>0.773</td><td>0.582</td><td>0.375</td></tr> <tr><td>80</td><td>-※1</td><td>1.543</td><td>1.025</td><td>0.770</td><td>0.492</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>1.273</td><td>0.953</td><td>0.605</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>1.412</td><td>1.057</td><td>0.671</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	18[V]	24[V]	36[V]	48[V]	76[V]	0	0.038	0.031	0.023	0.020	0.010	20	0.537	0.406	0.271	0.206	0.137	40	1.042	0.782	0.523	0.395	0.258	60	1.554	1.159	0.773	0.582	0.375	80	-※1	1.543	1.025	0.770	0.492	100	-※1	-※2	1.273	0.953	0.605	110	-※1	-※2	1.412	1.057	0.671	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Ratio [%]	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	0.038	0.031	0.023	0.020	0.010																																																																													
20	0.537	0.406	0.271	0.206	0.137																																																																													
40	1.042	0.782	0.523	0.395	0.258																																																																													
60	1.554	1.159	0.773	0.582	0.375																																																																													
80	-※1	1.543	1.025	0.770	0.492																																																																													
100	-※1	-※2	1.273	0.953	0.605																																																																													
110	-※1	-※2	1.412	1.057	0.671																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.038</td><td>0.031</td><td>0.023</td><td>0.020</td><td>0.010</td></tr> <tr><td>20</td><td>0.537</td><td>0.406</td><td>0.271</td><td>0.206</td><td>0.137</td></tr> <tr><td>40</td><td>1.042</td><td>0.782</td><td>0.523</td><td>0.395</td><td>0.258</td></tr> <tr><td>60</td><td>1.554</td><td>1.159</td><td>0.773</td><td>0.582</td><td>0.375</td></tr> <tr><td>80</td><td>-※1</td><td>1.543</td><td>1.025</td><td>0.770</td><td>0.492</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>1.273</td><td>0.953</td><td>0.605</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>1.412</td><td>1.057</td><td>0.671</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Input Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.038	0.031	0.023	0.020	0.010	20	0.537	0.406	0.271	0.206	0.137	40	1.042	0.782	0.523	0.395	0.258	60	1.554	1.159	0.773	0.582	0.375	80	-※1	1.543	1.025	0.770	0.492	100	-※1	-※2	1.273	0.953	0.605	110	-※1	-※2	1.412	1.057	0.671	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Current [A]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	0.038	0.031	0.023	0.020	0.010																																																																													
20	0.537	0.406	0.271	0.206	0.137																																																																													
40	1.042	0.782	0.523	0.395	0.258																																																																													
60	1.554	1.159	0.773	0.582	0.375																																																																													
80	-※1	1.543	1.025	0.770	0.492																																																																													
100	-※1	-※2	1.273	0.953	0.605																																																																													
110	-※1	-※2	1.412	1.057	0.671																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 24V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																		

COSEL


Model	MGFW404815																																																																																	
Item	Input Power (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 18V</li> <li>Input Volt. 24V</li> <li>Input Volt. 36V</li> <li>Input Volt. 48V</li> <li>Input Volt. 76V</li> </ul> <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>18V</th> <th>24V</th> <th>36V</th> <th>48V</th> <th>76V</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.70</td><td>0.74</td><td>0.84</td><td>0.97</td><td>0.74</td></tr> <tr><td>20</td><td>9.68</td><td>9.75</td><td>9.77</td><td>9.89</td><td>10.40</td></tr> <tr><td>40</td><td>18.86</td><td>18.82</td><td>18.85</td><td>19.00</td><td>19.63</td></tr> <tr><td>60</td><td>28.04</td><td>27.92</td><td>27.87</td><td>27.94</td><td>28.50</td></tr> <tr><td>80</td><td>-※1</td><td>37.15</td><td>36.95</td><td>37.00</td><td>37.43</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>46.18</td><td>46.14</td><td>46.49</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>50.87</td><td>50.76</td><td>51.05</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	18V	24V	36V	48V	76V	0	0.70	0.74	0.84	0.97	0.74	20	9.68	9.75	9.77	9.89	10.40	40	18.86	18.82	18.85	19.00	19.63	60	28.04	27.92	27.87	27.94	28.50	80	-※1	37.15	36.95	37.00	37.43	100	-※1	-※2	46.18	46.14	46.49	110	-※1	-※2	50.87	50.76	51.05	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Ratio [%]	18V	24V	36V	48V	76V																																																																													
0	0.70	0.74	0.84	0.97	0.74																																																																													
20	9.68	9.75	9.77	9.89	10.40																																																																													
40	18.86	18.82	18.85	19.00	19.63																																																																													
60	28.04	27.92	27.87	27.94	28.50																																																																													
80	-※1	37.15	36.95	37.00	37.43																																																																													
100	-※1	-※2	46.18	46.14	46.49																																																																													
110	-※1	-※2	50.87	50.76	51.05																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.70</td><td>0.74</td><td>0.84</td><td>0.97</td><td>0.74</td></tr> <tr><td>20</td><td>9.68</td><td>9.75</td><td>9.77</td><td>9.89</td><td>10.40</td></tr> <tr><td>40</td><td>18.86</td><td>18.82</td><td>18.85</td><td>19.00</td><td>19.63</td></tr> <tr><td>60</td><td>28.04</td><td>27.92</td><td>27.87</td><td>27.94</td><td>28.50</td></tr> <tr><td>80</td><td>-※1</td><td>37.15</td><td>36.95</td><td>37.00</td><td>37.43</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>46.18</td><td>46.14</td><td>46.49</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>50.87</td><td>50.76</td><td>51.05</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Input Power [W]					18[V]	24[V]	36[V]	48[V]	76[V]	0	0.70	0.74	0.84	0.97	0.74	20	9.68	9.75	9.77	9.89	10.40	40	18.86	18.82	18.85	19.00	19.63	60	28.04	27.92	27.87	27.94	28.50	80	-※1	37.15	36.95	37.00	37.43	100	-※1	-※2	46.18	46.14	46.49	110	-※1	-※2	50.87	50.76	51.05	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Power [W]																																																																																	
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																													
0	0.70	0.74	0.84	0.97	0.74																																																																													
20	9.68	9.75	9.77	9.89	10.40																																																																													
40	18.86	18.82	18.85	19.00	19.63																																																																													
60	28.04	27.92	27.87	27.94	28.50																																																																													
80	-※1	37.15	36.95	37.00	37.43																																																																													
100	-※1	-※2	46.18	46.14	46.49																																																																													
110	-※1	-※2	50.87	50.76	51.05																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 24V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																		

**COSEL**

Model	MGFW404815
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C  
 Testing Circuitry Figure A

## 1.Graph



## 2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
17	90.7	89.8
18	90.8	90.8
24	91.0	91.2
30	91.1	91.2
36	91.1	91.6
48	90.7	91.6
60	89.8	91.3
76	88.5	90.9
80	88.0	90.7

※1: Load 70%

※2: Load 80%

Note: Slanted line shows the range of the rated input voltage.

**COSEL**

Model	MGFW404815																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph																																																																																		
Temperature	25°C																																																																																	
Testing Circuitry	Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr> <td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>20</td><td>88.0</td><td>87.4</td><td>87.2</td><td>86.0</td><td>82.0</td></tr> <tr> <td>40</td><td>90.5</td><td>90.7</td><td>90.6</td><td>89.8</td><td>86.9</td></tr> <tr> <td>60</td><td>90.8</td><td>91.3</td><td>91.3</td><td>91.2</td><td>89.3</td></tr> <tr> <td>80</td><td>-※1</td><td>91.2</td><td>91.7</td><td>91.6</td><td>90.4</td></tr> <tr> <td>100</td><td>-※1</td><td>-※2</td><td>91.6</td><td>91.6</td><td>90.9</td></tr> <tr> <td>110</td><td>-※1</td><td>-※2</td><td>91.3</td><td>91.5</td><td>90.9</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Efficiency [%]					Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	-	-	20	88.0	87.4	87.2	86.0	82.0	40	90.5	90.7	90.6	89.8	86.9	60	90.8	91.3	91.3	91.2	89.3	80	-※1	91.2	91.7	91.6	90.4	100	-※1	-※2	91.6	91.6	90.9	110	-※1	-※2	91.3	91.5	90.9	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Efficiency [%]																																																																																	
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																																													
0	-	-	-	-	-																																																																													
20	88.0	87.4	87.2	86.0	82.0																																																																													
40	90.5	90.7	90.6	89.8	86.9																																																																													
60	90.8	91.3	91.3	91.2	89.3																																																																													
80	-※1	91.2	91.7	91.6	90.4																																																																													
100	-※1	-※2	91.6	91.6	90.9																																																																													
110	-※1	-※2	91.3	91.5	90.9																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																																	
※2	Maximum output current at 24V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSEL


Model MGFW404815

Temperature 25°C  
Testing Circuitry Figure A

Item Line Regulation

Object +15V1.4A

## 1. Graph




## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	15.114	- ⋆1
18	15.117	- ⋆1
24	15.094	- ⋆2
30	15.085	15.024
36	15.082	15.024
48	15.079	15.024
60	15.073	15.023
76	15.073	15.023
80	15.071	15.023

-15V: Rated Load Current

Object -15V1.4A

## 1. Graph



## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	-15.126	- ⋆1
18	-15.124	- ⋆1
24	-15.100	- ⋆2
30	-15.093	-15.020
36	-15.088	-15.020
48	-15.085	-15.020
60	-15.081	-15.020
76	-15.081	-15.020
80	-15.081	-15.019

+15V: Rated Load Current

Note: Slanted line shows the range of the rated input voltage.

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at 24V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL

Model	MGFW404815	Temperature 25°C Testing Circuitry Figure A																																																																																		
Item	Load Regulation																																																																																			
Object	+15V1.4A																																																																																			
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt.</p> <ul style="list-style-type: none"> <li>18V</li> <li>24V</li> <li>36V</li> <li>48V</li> <li>76V</li> </ul>																																																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15.366</td><td>15.338</td><td>15.326</td><td>15.309</td><td>15.300</td></tr> <tr><td>0.28</td><td>15.143</td><td>15.121</td><td>15.124</td><td>15.125</td><td>15.119</td></tr> <tr><td>0.56</td><td>15.136</td><td>15.107</td><td>15.094</td><td>15.090</td><td>15.087</td></tr> <tr><td>0.70</td><td>15.117</td><td>15.094</td><td>15.082</td><td>15.079</td><td>15.073</td></tr> <tr><td>0.84</td><td>15.101</td><td>15.080</td><td>15.070</td><td>15.067</td><td>15.062</td></tr> <tr><td>0.98</td><td>15.077</td><td>15.064</td><td>15.056</td><td>15.054</td><td>15.051</td></tr> <tr><td>1.12</td><td>-※1</td><td>15.050</td><td>15.046</td><td>15.042</td><td>15.040</td></tr> <tr><td>1.40</td><td>-※1</td><td>-※2</td><td>15.024</td><td>15.024</td><td>15.023</td></tr> <tr><td>1.54</td><td>-※1</td><td>-※2</td><td>15.009</td><td>15.010</td><td>15.012</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	15.366	15.338	15.326	15.309	15.300	0.28	15.143	15.121	15.124	15.125	15.119	0.56	15.136	15.107	15.094	15.090	15.087	0.70	15.117	15.094	15.082	15.079	15.073	0.84	15.101	15.080	15.070	15.067	15.062	0.98	15.077	15.064	15.056	15.054	15.051	1.12	-※1	15.050	15.046	15.042	15.040	1.40	-※1	-※2	15.024	15.024	15.023	1.54	-※1	-※2	15.009	15.010	15.012	--	-	-	-	-	-	--	-	-	-	-	-	
Load Current [A]	Output Voltage [V]																																																																																			
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																															
0.00	15.366	15.338	15.326	15.309	15.300																																																																															
0.28	15.143	15.121	15.124	15.125	15.119																																																																															
0.56	15.136	15.107	15.094	15.090	15.087																																																																															
0.70	15.117	15.094	15.082	15.079	15.073																																																																															
0.84	15.101	15.080	15.070	15.067	15.062																																																																															
0.98	15.077	15.064	15.056	15.054	15.051																																																																															
1.12	-※1	15.050	15.046	15.042	15.040																																																																															
1.40	-※1	-※2	15.024	15.024	15.023																																																																															
1.54	-※1	-※2	15.009	15.010	15.012																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
Object	-15V1.4A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-15.393</td><td>-15.361</td><td>-15.340</td><td>-15.329</td><td>-15.304</td></tr> <tr><td>0.28</td><td>-15.141</td><td>-15.145</td><td>-15.134</td><td>-15.137</td><td>-15.136</td></tr> <tr><td>0.56</td><td>-15.139</td><td>-15.112</td><td>-15.099</td><td>-15.096</td><td>-15.088</td></tr> <tr><td>0.70</td><td>-15.124</td><td>-15.100</td><td>-15.088</td><td>-15.085</td><td>-15.081</td></tr> <tr><td>0.84</td><td>-15.115</td><td>-15.082</td><td>-15.073</td><td>-15.071</td><td>-15.065</td></tr> <tr><td>0.98</td><td>-15.110</td><td>-15.069</td><td>-15.061</td><td>-15.057</td><td>-15.055</td></tr> <tr><td>1.12</td><td>-※1</td><td>-15.053</td><td>-15.047</td><td>-15.046</td><td>-15.042</td></tr> <tr><td>1.40</td><td>-※1</td><td>-※2</td><td>-15.020</td><td>-15.020</td><td>-15.020</td></tr> <tr><td>1.54</td><td>-※1</td><td>-※2</td><td>-15.006</td><td>-15.007</td><td>-15.009</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>						Load Current [A]	Output Voltage [V]					18[V]	24[V]	36[V]	48[V]	76[V]	0.00	-15.393	-15.361	-15.340	-15.329	-15.304	0.28	-15.141	-15.145	-15.134	-15.137	-15.136	0.56	-15.139	-15.112	-15.099	-15.096	-15.088	0.70	-15.124	-15.100	-15.088	-15.085	-15.081	0.84	-15.115	-15.082	-15.073	-15.071	-15.065	0.98	-15.110	-15.069	-15.061	-15.057	-15.055	1.12	-※1	-15.053	-15.047	-15.046	-15.042	1.40	-※1	-※2	-15.020	-15.020	-15.020	1.54	-※1	-※2	-15.006	-15.007	-15.009	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																			
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																															
0.00	-15.393	-15.361	-15.340	-15.329	-15.304																																																																															
0.28	-15.141	-15.145	-15.134	-15.137	-15.136																																																																															
0.56	-15.139	-15.112	-15.099	-15.096	-15.088																																																																															
0.70	-15.124	-15.100	-15.088	-15.085	-15.081																																																																															
0.84	-15.115	-15.082	-15.073	-15.071	-15.065																																																																															
0.98	-15.110	-15.069	-15.061	-15.057	-15.055																																																																															
1.12	-※1	-15.053	-15.047	-15.046	-15.042																																																																															
1.40	-※1	-※2	-15.020	-15.020	-15.020																																																																															
1.54	-※1	-※2	-15.006	-15.007	-15.009																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>*1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>*2 Maximum output current at 24V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																				


**COSEL**

Model	MGFW404815	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+15V1.4A	

Input Volt. 48 V

-15V:rated load current.


Cycle 100 ms

t1,t2 = 100  $\mu$  s

Min.Load (0A)↔  
Load 100% (1.4A)

200 mV/div


2 ms/div



Min.Load (0A)↔  
Load 50% (0.7A)

200 mV/div


2 ms/div



Load 50% (0.7A)↔  
Load 100% (1.4A)

200 mV/div

2 ms/div



**COSEL**


Model	MGFW404815	Temperature Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	-15V1.4A	

Input Volt. 48 V

+15V:rated load current.

Cycle 100 ms


t1,t2 = 100  $\mu$  s

Load Current  


Min.Load (0A)↔  
 Load 100% (1.4A)

200 mV/div

2 ms/div




2 ms/div

Min.Load (0A)↔  
 Load 50% (0.7A)

200 mV/div

2 ms/div




2 ms/div

Load 50% (0.7A)↔  
 Load 100% (1.4A)

200 mV/div

2 ms/div



2 ms/div

**COSEL**

Model	MGFW404815																																																																										
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																																																									
Object	+15V1.4A																																																																										
1.Graph																																																																											
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two sets of data points: Input Volt. 18V (solid line with triangle markers) and Input Volt. 76V (dashed line with circle markers). The x-axis represents Load Current [A] from 0.0 to 2.0. The y-axis represents Ripple Voltage [mV] from 0 to 200. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (18V)</th> <th>Ripple Voltage [mV] (76V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>30</td><td>50</td></tr> <tr><td>0.28</td><td>15</td><td>20</td></tr> <tr><td>0.56</td><td>15</td><td>25</td></tr> <tr><td>0.84</td><td>15</td><td>25</td></tr> <tr><td>0.98</td><td>20</td><td>30</td></tr> <tr><td>1.12</td><td>-</td><td>25</td></tr> <tr><td>1.40</td><td>-</td><td>25</td></tr> <tr><td>1.54</td><td>-</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV] (18V)	Ripple Voltage [mV] (76V)	0.00	30	50	0.28	15	20	0.56	15	25	0.84	15	25	0.98	20	30	1.12	-	25	1.40	-	25	1.54	-	35	--	-	-	--	-	-	--	-	-	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>30</td><td>50</td></tr> <tr><td>0.28</td><td>15</td><td>20</td></tr> <tr><td>0.56</td><td>15</td><td>25</td></tr> <tr><td>0.84</td><td>15</td><td>25</td></tr> <tr><td>0.98</td><td>20</td><td>30</td></tr> <tr><td>1.12</td><td>-</td><td>25</td></tr> <tr><td>1.40</td><td>-</td><td>25</td></tr> <tr><td>1.54</td><td>-</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	30	50	0.28	15	20	0.56	15	25	0.84	15	25	0.98	20	30	1.12	-	25	1.40	-	25	1.54	-	35	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV] (18V)	Ripple Voltage [mV] (76V)																																																																									
0.00	30	50																																																																									
0.28	15	20																																																																									
0.56	15	25																																																																									
0.84	15	25																																																																									
0.98	20	30																																																																									
1.12	-	25																																																																									
1.40	-	25																																																																									
1.54	-	35																																																																									
--	-	-																																																																									
--	-	-																																																																									
--	-	-																																																																									
Load Current [A]	Ripple Voltage [mV]																																																																										
	Input Volt. 18 [V]	Input Volt. 76 [V]																																																																									
0.00	30	50																																																																									
0.28	15	20																																																																									
0.56	15	25																																																																									
0.84	15	25																																																																									
0.98	20	30																																																																									
1.12	-	25																																																																									
1.40	-	25																																																																									
1.54	-	35																																																																									
--	-	-																																																																									
--	-	-																																																																									
--	-	-																																																																									
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																																																											

# COSEL

Model	MGFW404815																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	-15V1.4A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from 0.0 to 2.0 A. Two sets of data points are plotted: Input Volt. 18V (solid line with triangle markers) and Input Volt. 76V (dashed line with circle markers). A slanted line indicates the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (18V)</th> <th>Ripple Voltage [mV] (76V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>30</td><td>50</td></tr> <tr><td>0.28</td><td>15</td><td>20</td></tr> <tr><td>0.56</td><td>15</td><td>25</td></tr> <tr><td>0.84</td><td>15</td><td>25</td></tr> <tr><td>0.98</td><td>20</td><td>30</td></tr> <tr><td>1.12</td><td>-</td><td>25</td></tr> <tr><td>1.40</td><td>-</td><td>25</td></tr> <tr><td>1.54</td><td>-</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (18V)	Ripple Voltage [mV] (76V)	0.00	30	50	0.28	15	20	0.56	15	25	0.84	15	25	0.98	20	30	1.12	-	25	1.40	-	25	1.54	-	35	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (18V)	Ripple Voltage [mV] (76V)																																						
0.00	30	50																																						
0.28	15	20																																						
0.56	15	25																																						
0.84	15	25																																						
0.98	20	30																																						
1.12	-	25																																						
1.40	-	25																																						
1.54	-	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>30</td><td>50</td></tr> <tr><td>0.28</td><td>15</td><td>20</td></tr> <tr><td>0.56</td><td>15</td><td>25</td></tr> <tr><td>0.84</td><td>15</td><td>25</td></tr> <tr><td>0.98</td><td>20</td><td>30</td></tr> <tr><td>1.12</td><td>-</td><td>25</td></tr> <tr><td>1.40</td><td>-</td><td>25</td></tr> <tr><td>1.54</td><td>-</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 76 [V]	0.00	30	50	0.28	15	20	0.56	15	25	0.84	15	25	0.98	20	30	1.12	-	25	1.40	-	25	1.54	-	35	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 76 [V]																																						
0.00	30	50																																						
0.28	15	20																																						
0.56	15	25																																						
0.84	15	25																																						
0.98	20	30																																						
1.12	-	25																																						
1.40	-	25																																						
1.54	-	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
+15V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								


**COSEL**

Model MGFW404815

Item Ripple-Noise

Object +15V1.4A

## 1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

Temperature 25°C  
Testing Circuitry Figure B

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.00	35	60
0.28	25	35
0.56	25	40
0.84	25	40
0.98	25	40
1.12	- *	50
1.40	- *	50
1.54	- *	55
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current


\* Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

**COSEL**

Model	MGFW404815
Item	Ripple-Noise
Object	-15V1.4A

 Temperature 25°C  
 Testing Circuitry Figure B

## 1.Graph



Measured by 100 MHz Oscilloscope.  
 Ripple-Noise is shown as p-p in the figure below.  
 Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

## 2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 18 [V]	Input Volt. 76 [V]
0.00	35	60
0.28	25	35
0.56	25	40
0.84	25	40
0.98	30	40
1.12	- *	50
1.40	- *	50
1.54	- *	55
--	-	-
--	-	-
--	-	-


+15V: Rated Load Current

\* Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.



Model	MGFW404815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V1.4A

## 1.Graph




Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	20	25
-40	20	25
-20	20	25
25	20	25
60	25	25
85	30	30
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Rated Load Current



## 2.Values



Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	20	25
-40	20	25
-20	20	25
25	20	25
60	25	25
85	30	30
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

# COSEL

Model	MGFW404815
Item	Ambient Temperature Drift
Object	+15V1.4A
1.Graph	<p>—△— Input Volt. 18V            - - - □ - - Input Volt. 24V            - - * - - Input Volt. 36V            - - ○ - - Input Volt. 48V            - - ◆ - - Input Volt. 76V</p>  <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>
Object	-15V1.4A
1.Graph	<p>—△— Input Volt. 18V            - - - □ - - Input Volt. 24V            - - * - - Input Volt. 36V            - - ○ - - Input Volt. 48V            - - ◆ - - Input Volt. 76V</p>  <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>
Note: Slanted line shows the range of the rated ambient temperature.	

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	14.972	14.977	14.969	14.972	14.972
-40	14.993	14.994	14.991	14.992	14.993
-20	15.008	15.009	15.006	15.007	15.008
0	15.018	15.020	15.017	15.018	15.018
25	15.023	15.025	15.024	15.024	15.023
65	15.018	15.020	15.019	15.019	15.019
75	15.017	15.019	15.016	15.017	15.016
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

-15V: Rated Load Current

## 2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	-14.927	-14.926	-14.931	-14.934	-14.937
-40	-14.962	-14.964	-14.964	-14.968	-14.970
-20	-14.986	-14.989	-14.990	-14.992	-14.993
0	-15.004	-15.005	-15.007	-15.008	-15.009
25	-15.011	-15.053	-15.020	-15.020	-15.020
65	-15.019	-15.021	-15.021	-15.020	-15.020
75	-15.019	-15.021	-15.020	-15.019	-15.018
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

+15V: Rated Load Current

Note: In case of input Volt.18V, Load 70%.

24V, Load 80%.

Other case Load 100%.



Model	MGFW404815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 65°C

Input Voltage : 18 - 76V

Load Current (AVR 1) : 0 - 1.4A (AVR 2) : 0 - 1.4A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Object	+15V1.4A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	65	18	0	15.379	±352	±2.3
Minimum Voltage	-40	48	1.4	14.675		

Object	-15V1.4A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	65	36	0	-15.357	±374	±2.5
Minimum Voltage	-40	18	1.4	-14.610		


**COSEL**

Model	MGFW404815	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V1.4A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.024</td></tr> <tr><td>0.5</td><td>15.019</td></tr> <tr><td>1.0</td><td>15.019</td></tr> <tr><td>2.0</td><td>15.019</td></tr> <tr><td>3.0</td><td>15.019</td></tr> <tr><td>4.0</td><td>15.019</td></tr> <tr><td>5.0</td><td>15.019</td></tr> <tr><td>6.0</td><td>15.019</td></tr> <tr><td>7.0</td><td>15.019</td></tr> <tr><td>8.0</td><td>15.019</td></tr> </tbody> </table> <p>-15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	15.024	0.5	15.019	1.0	15.019	2.0	15.019	3.0	15.019	4.0	15.019	5.0	15.019	6.0	15.019	7.0	15.019	8.0	15.019
Time since start [H]	Output Voltage [V]																								
0.0	15.024																								
0.5	15.019																								
1.0	15.019																								
2.0	15.019																								
3.0	15.019																								
4.0	15.019																								
5.0	15.019																								
6.0	15.019																								
7.0	15.019																								
8.0	15.019																								
Object -15V1.4A			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 48V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-15.019</td></tr> <tr><td>0.5</td><td>-15.020</td></tr> <tr><td>1.0</td><td>-15.020</td></tr> <tr><td>2.0</td><td>-15.020</td></tr> <tr><td>3.0</td><td>-15.020</td></tr> <tr><td>4.0</td><td>-15.020</td></tr> <tr><td>5.0</td><td>-15.020</td></tr> <tr><td>6.0</td><td>-15.020</td></tr> <tr><td>7.0</td><td>-15.020</td></tr> <tr><td>8.0</td><td>-15.020</td></tr> </tbody> </table> <p>+15V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-15.019	0.5	-15.020	1.0	-15.020	2.0	-15.020	3.0	-15.020	4.0	-15.020	5.0	-15.020	6.0	-15.020	7.0	-15.020	8.0	-15.020
Time since start [H]	Output Voltage [V]																								
0.0	-15.019																								
0.5	-15.020																								
1.0	-15.020																								
2.0	-15.020																								
3.0	-15.020																								
4.0	-15.020																								
5.0	-15.020																								
6.0	-15.020																								
7.0	-15.020																								
8.0	-15.020																								

**COSEL**


Model	MGFW404815	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+15V1.4A		

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.8	4.1	10.9	1.5	3.1	
100 %		6.9	5.5	12.4	1.1	1.1	



**COSEL**


Model	MGFW404815	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-15V1.4A		

## 1. Graph



## 2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.8	4.2	11.0	1.5	3.2	
100 %		6.8	5.7	12.5	1.1	1.2	




**COSEL**

Model	MGFW404815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V1.4A

Testing Circuitry Figure A

## 1.Graph




## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	15.4	16.0
-40	15.4	15.8
-20	15.3	15.8
0	15.3	15.8
25	15.3	15.5
65	15.3	15.3
75	15.2	15.2
--	-	-
--	-	-
--	-	-
--	-	-

-15V: Load Current is same as well as +15V

## Object -15V1.4A

## 1.Graph



## 2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	15.4	16.0
-40	15.4	15.8
-20	15.3	15.8
0	15.3	15.8
25	15.3	15.5
65	15.3	15.3
75	15.2	15.2
--	-	-
--	-	-
--	-	-
--	-	-

+15V: Load Current is same as well as -15V

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGFW404815	Temperature	25°C																																																																								
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																																								
Object	+15V1.4A																																																																										
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																																										
	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>15.0</td><td>1.293</td><td>1.633</td><td>1.938</td><td>1.938</td><td>2.031</td></tr> <tr><td>14.3</td><td>-※1</td><td>-※2</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>13.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>12.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>9.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>7.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>4.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: right;">-15V: Rated Load Current</p>			Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	15.0	1.293	1.633	1.938	1.938	2.031	14.3	-※1	-※2	-	-	-	13.5	-	-	-	-	-	12.0	-	-	-	-	-	10.5	-	-	-	-	-	9.0	-	-	-	-	-	7.5	-	-	-	-	-	6.0	-	-	-	-	-	4.5	-	-	-	-	-	0.0	-	-	-	-	-	
Output Voltage [V]	Load Current [A]																																																																										
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																						
15.0	1.293	1.633	1.938	1.938	2.031																																																																						
14.3	-※1	-※2	-	-	-																																																																						
13.5	-	-	-	-	-																																																																						
12.0	-	-	-	-	-																																																																						
10.5	-	-	-	-	-																																																																						
9.0	-	-	-	-	-																																																																						
7.5	-	-	-	-	-																																																																						
6.0	-	-	-	-	-																																																																						
4.5	-	-	-	-	-																																																																						
0.0	-	-	-	-	-																																																																						
Object	-15V1.4A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> <th>48[V]</th> <th>76[V]</th> </tr> </thead> <tbody> <tr><td>-15.0</td><td>1.269</td><td>1.620</td><td>1.938</td><td>1.938</td><td>2.031</td></tr> <tr><td>-14.3</td><td>-※1</td><td>-※2</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-13.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-12.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-10.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-9.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-7.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-6.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-4.5</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: right;">+15V: Rated Load Current</p> <p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.      ※2 Maximum output current at 24V input Voltage is 80% of rated load current.      Refer to instruction manuals for details of input derating.</p>			Output Voltage [V]	Load Current [A]					18[V]	24[V]	36[V]	48[V]	76[V]	-15.0	1.269	1.620	1.938	1.938	2.031	-14.3	-※1	-※2	-	-	-	-13.5	-	-	-	-	-	-12.0	-	-	-	-	-	-10.5	-	-	-	-	-	-9.0	-	-	-	-	-	-7.5	-	-	-	-	-	-6.0	-	-	-	-	-	-4.5	-	-	-	-	-	0.0	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																										
	18[V]	24[V]	36[V]	48[V]	76[V]																																																																						
-15.0	1.269	1.620	1.938	1.938	2.031																																																																						
-14.3	-※1	-※2	-	-	-																																																																						
-13.5	-	-	-	-	-																																																																						
-12.0	-	-	-	-	-																																																																						
-10.5	-	-	-	-	-																																																																						
-9.0	-	-	-	-	-																																																																						
-7.5	-	-	-	-	-																																																																						
-6.0	-	-	-	-	-																																																																						
-4.5	-	-	-	-	-																																																																						
0.0	-	-	-	-	-																																																																						
<p>Note: Slanted line shows the range of the rated load current.      Intermittent operation activates when overcurrent protection is activated.</p>		<p>BC-11326</p>																																																																									

**COSEL**


Model	MGFW404815																																																					
Item	Overvoltage Protection																																																					
Object	+30V1.4A																																																					
1.Graph	—△— Input Volt. 18V ---□--- Input Volt. 48V -·-*-- Input Volt. 76V	Operating Point [%]	Temperature 25°C Testing Circuitry Figure A																																																			
		Load Ratio [%]	2.Values																																																			
			<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th><th colspan="3">Operating Point [%]</th></tr> <tr> <th>Input Volt. 18[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr> </thead> <tbody> <tr><td>0</td><td>131</td><td>131</td><td>133</td></tr> <tr><td>10</td><td>126</td><td>126</td><td>126</td></tr> <tr><td>20</td><td>126</td><td>126</td><td>126</td></tr> <tr><td>30</td><td>126</td><td>125</td><td>126</td></tr> <tr><td>40</td><td>126</td><td>125</td><td>125</td></tr> <tr><td>50</td><td>127</td><td>126</td><td>125</td></tr> <tr><td>60</td><td>127</td><td>126</td><td>125</td></tr> <tr><td>70</td><td>- ✕</td><td>126</td><td>125</td></tr> <tr><td>80</td><td>- ✕</td><td>126</td><td>125</td></tr> <tr><td>90</td><td>- ✕</td><td>126</td><td>125</td></tr> <tr><td>100</td><td>- ✕</td><td>126</td><td>125</td></tr> </tbody> </table>	Load Ratio [%]	Operating Point [%]			Input Volt. 18[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	131	131	133	10	126	126	126	20	126	126	126	30	126	125	126	40	126	125	125	50	127	126	125	60	127	126	125	70	- ✕	126	125	80	- ✕	126	125	90	- ✕	126	125	100	- ✕	126	125
Load Ratio [%]	Operating Point [%]																																																					
	Input Volt. 18[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	131	131	133																																																			
10	126	126	126																																																			
20	126	126	126																																																			
30	126	125	126																																																			
40	126	125	125																																																			
50	127	126	125																																																			
60	127	126	125																																																			
70	- ✕	126	125																																																			
80	- ✕	126	125																																																			
90	- ✕	126	125																																																			
100	- ✕	126	125																																																			
			※During this area, overcurrent protection activates.																																																			
			Measured as a single output(+30V).																																																			

# COSEL

Model	MGFW404815
Item	Switching frequency (by Load Current)
Object	+/-15V1.4A

Temperature 25°C  
Testing Circuitry Figure A

### 1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG40 changes depending on load current and input voltage.

When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG40 operates intermittently, so switching frequency can not be stable.

\* Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)