

TEST DATA OF MGFW802412

Regulated DC Power Supply

April 10, 2019

Approved by : Junichi Hatagishi Junichi Hatagishi Design Manager

Prepared by : Satoshi Kinoshita
Satoshi Kinoshita Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Overvoltage Protection	22
19.Switching frequency (by Load Current)	23
20.Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	MGFW802412	Temperature	25°C																																																																															
Item	Input Current (by Input Voltage)	Testing Circuitry	Figure A																																																																															
Object	_____																																																																																	
1.Graph		2.Values																																																																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>7.6</td><td>0.001</td><td>0.001</td><td>- ✕</td></tr> <tr><td>7.8</td><td>0.001</td><td>0.001</td><td>- ✕</td></tr> <tr><td>8.0</td><td>0.001</td><td>0.001</td><td>- ✕</td></tr> <tr><td>8.2</td><td>0.001</td><td>0.001</td><td>- ✕</td></tr> <tr><td>8.4</td><td>0.132</td><td>5.253</td><td>- ✕</td></tr> <tr><td>8.6</td><td>0.130</td><td>5.117</td><td>- ✕</td></tr> <tr><td>8.8</td><td>0.127</td><td>5.015</td><td>- ✕</td></tr> <tr><td>9.0</td><td>0.125</td><td>4.887</td><td>- ✕</td></tr> <tr><td>12.0</td><td>0.099</td><td>3.667</td><td>- ✕</td></tr> <tr><td>18.0</td><td>0.074</td><td>2.438</td><td>4.852</td></tr> <tr><td>24.0</td><td>0.062</td><td>1.837</td><td>3.640</td></tr> <tr><td>36.0</td><td>0.014</td><td>1.239</td><td>2.435</td></tr> <tr><td>40.0</td><td>0.014</td><td>1.115</td><td>2.202</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	7.6	0.001	0.001	- ✕	7.8	0.001	0.001	- ✕	8.0	0.001	0.001	- ✕	8.2	0.001	0.001	- ✕	8.4	0.132	5.253	- ✕	8.6	0.130	5.117	- ✕	8.8	0.127	5.015	- ✕	9.0	0.125	4.887	- ✕	12.0	0.099	3.667	- ✕	18.0	0.074	2.438	4.852	24.0	0.062	1.837	3.640	36.0	0.014	1.239	2.435	40.0	0.014	1.115	2.202	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
7.6	0.001	0.001	- ✕																																																																															
7.8	0.001	0.001	- ✕																																																																															
8.0	0.001	0.001	- ✕																																																																															
8.2	0.001	0.001	- ✕																																																																															
8.4	0.132	5.253	- ✕																																																																															
8.6	0.130	5.117	- ✕																																																																															
8.8	0.127	5.015	- ✕																																																																															
9.0	0.125	4.887	- ✕																																																																															
12.0	0.099	3.667	- ✕																																																																															
18.0	0.074	2.438	4.852																																																																															
24.0	0.062	1.837	3.640																																																																															
36.0	0.014	1.239	2.435																																																																															
40.0	0.014	1.115	2.202																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
<p>※During this area, overcurrent protection activates and power supply operates in hiccup mode.</p>																																																																																		

COSEL

Model	MGFW802412																																																																													
Item	Input Current (by Load Current)																																																																													
Object	_____																																																																													
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 9V - -□-- Input Volt. 12V - ·*·- Input Volt. 18V - ·○·- Input Volt. 24V - ·◇·- Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.125</td><td>0.099</td><td>0.074</td><td>0.062</td><td>0.014</td></tr> <tr><td>20</td><td>1.992</td><td>1.499</td><td>1.010</td><td>0.766</td><td>0.522</td></tr> <tr><td>40</td><td>3.912</td><td>2.938</td><td>1.974</td><td>1.482</td><td>1.001</td></tr> <tr><td>60</td><td>5.875</td><td>4.377</td><td>2.920</td><td>2.198</td><td>1.478</td></tr> <tr><td>80</td><td>-※1</td><td>5.873</td><td>3.891</td><td>2.914</td><td>1.956</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>4.852</td><td>3.640</td><td>2.435</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>5.352</td><td>4.016</td><td>2.680</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ratio [%]	9[V]	12[V]	18[V]	24[V]	36[V]	0	0.125	0.099	0.074	0.062	0.014	20	1.992	1.499	1.010	0.766	0.522	40	3.912	2.938	1.974	1.482	1.001	60	5.875	4.377	2.920	2.198	1.478	80	-※1	5.873	3.891	2.914	1.956	100	-※1	-※2	4.852	3.640	2.435	110	-※1	-※2	5.352	4.016	2.680	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-					
Load Ratio [%]	9[V]	12[V]	18[V]	24[V]	36[V]																																																																									
0	0.125	0.099	0.074	0.062	0.014																																																																									
20	1.992	1.499	1.010	0.766	0.522																																																																									
40	3.912	2.938	1.974	1.482	1.001																																																																									
60	5.875	4.377	2.920	2.198	1.478																																																																									
80	-※1	5.873	3.891	2.914	1.956																																																																									
100	-※1	-※2	4.852	3.640	2.435																																																																									
110	-※1	-※2	5.352	4.016	2.680																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.125</td><td>0.099</td><td>0.074</td><td>0.062</td><td>0.014</td></tr> <tr><td>20</td><td>1.992</td><td>1.499</td><td>1.010</td><td>0.766</td><td>0.522</td></tr> <tr><td>40</td><td>3.912</td><td>2.938</td><td>1.974</td><td>1.482</td><td>1.001</td></tr> <tr><td>60</td><td>5.875</td><td>4.377</td><td>2.920</td><td>2.198</td><td>1.478</td></tr> <tr><td>80</td><td>-※1</td><td>5.873</td><td>3.891</td><td>2.914</td><td>1.956</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>4.852</td><td>3.640</td><td>2.435</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>5.352</td><td>4.016</td><td>2.680</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ratio [%]	Input Current [A]					9[V]	12[V]	18[V]	24[V]	36[V]	0	0.125	0.099	0.074	0.062	0.014	20	1.992	1.499	1.010	0.766	0.522	40	3.912	2.938	1.974	1.482	1.001	60	5.875	4.377	2.920	2.198	1.478	80	-※1	5.873	3.891	2.914	1.956	100	-※1	-※2	4.852	3.640	2.435	110	-※1	-※2	5.352	4.016	2.680	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Current [A]																																																																													
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																									
0	0.125	0.099	0.074	0.062	0.014																																																																									
20	1.992	1.499	1.010	0.766	0.522																																																																									
40	3.912	2.938	1.974	1.482	1.001																																																																									
60	5.875	4.377	2.920	2.198	1.478																																																																									
80	-※1	5.873	3.891	2.914	1.956																																																																									
100	-※1	-※2	4.852	3.640	2.435																																																																									
110	-※1	-※2	5.352	4.016	2.680																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
--	-	-	-	-	-																																																																									
<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 12V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																														

COSEL

Model	MGFW802412																																																																																	
Item	Input Power (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																	
Temperature Testing Circuitry	25°C Figure A																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Power [W]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>1.14</td> <td>1.20</td> <td>1.33</td> <td>1.49</td> <td>0.52</td> </tr> <tr> <td>20</td> <td>18.07</td> <td>18.11</td> <td>18.22</td> <td>18.42</td> <td>18.80</td> </tr> <tr> <td>40</td> <td>35.46</td> <td>35.45</td> <td>35.54</td> <td>35.69</td> <td>36.07</td> </tr> <tr> <td>60</td> <td>53.11</td> <td>52.82</td> <td>52.76</td> <td>52.92</td> <td>53.34</td> </tr> <tr> <td>80</td> <td>-※1</td> <td>70.57</td> <td>70.14</td> <td>70.15</td> <td>70.46</td> </tr> <tr> <td>100</td> <td>-※1</td> <td>-※2</td> <td>87.79</td> <td>87.61</td> <td>87.76</td> </tr> <tr> <td>110</td> <td>-※1</td> <td>-※2</td> <td>96.78</td> <td>96.45</td> <td>96.50</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Ratio [%]	Input Power [W]					9[V]	12[V]	18[V]	24[V]	36[V]	0	1.14	1.20	1.33	1.49	0.52	20	18.07	18.11	18.22	18.42	18.80	40	35.46	35.45	35.54	35.69	36.07	60	53.11	52.82	52.76	52.92	53.34	80	-※1	70.57	70.14	70.15	70.46	100	-※1	-※2	87.79	87.61	87.76	110	-※1	-※2	96.78	96.45	96.50	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Power [W]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	1.14	1.20	1.33	1.49	0.52																																																																													
20	18.07	18.11	18.22	18.42	18.80																																																																													
40	35.46	35.45	35.54	35.69	36.07																																																																													
60	53.11	52.82	52.76	52.92	53.34																																																																													
80	-※1	70.57	70.14	70.15	70.46																																																																													
100	-※1	-※2	87.79	87.61	87.76																																																																													
110	-※1	-※2	96.78	96.45	96.50																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
※1	Maximum output current at minimum input Voltage is 70% of rated load current.																																																																																	
※2	Maximum output current at 12V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																	

COSSEL

Model	MGFW802412																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—																																	
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>92.8</td><td>92.5 ※1</td></tr> <tr><td>9.0</td><td>93.0</td><td>92.8 ※1</td></tr> <tr><td>12.0</td><td>93.2</td><td>93.2 ※2</td></tr> <tr><td>15.0</td><td>93.2</td><td>93.2</td></tr> <tr><td>18.0</td><td>93.0</td><td>93.6</td></tr> <tr><td>24.0</td><td>92.7</td><td>93.8</td></tr> <tr><td>30.0</td><td>92.3</td><td>93.8</td></tr> <tr><td>36.0</td><td>91.7</td><td>93.7</td></tr> <tr><td>40.0</td><td>91.7</td><td>93.5</td></tr> </tbody> </table> <p>※1: Load 70% ※2: Load 80%</p>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	8.5	92.8	92.5 ※1	9.0	93.0	92.8 ※1	12.0	93.2	93.2 ※2	15.0	93.2	93.2	18.0	93.0	93.6	24.0	92.7	93.8	30.0	92.3	93.8	36.0	91.7	93.7	40.0	91.7	93.5
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
8.5	92.8	92.5 ※1																																
9.0	93.0	92.8 ※1																																
12.0	93.2	93.2 ※2																																
15.0	93.2	93.2																																
18.0	93.0	93.6																																
24.0	92.7	93.8																																
30.0	92.3	93.8																																
36.0	91.7	93.7																																
40.0	91.7	93.5																																
Note: Slanted line shows the range of the rated input voltage.																																		

COSEL

Model	MGFW802412																																																																																	
Item	Efficiency (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V <table border="1"> <thead> <tr> <th>Load Ratio [%]</th> <th>9V</th> <th>12V</th> <th>18V</th> <th>24V</th> <th>36V</th> </tr> </thead> <tbody> <tr><td>20</td><td>91.1</td><td>90.9</td><td>90.3</td><td>89.3</td><td>87.5</td></tr> <tr><td>40</td><td>92.8</td><td>92.8</td><td>92.6</td><td>92.2</td><td>91.2</td></tr> <tr><td>60</td><td>92.9</td><td>93.4</td><td>93.5</td><td>93.2</td><td>92.5</td></tr> <tr><td>80</td><td>-※1</td><td>93.2</td><td>93.8</td><td>93.7</td><td>93.3</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>93.6</td><td>93.8</td><td>93.7</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>93.4</td><td>93.8</td><td>93.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	9V	12V	18V	24V	36V	20	91.1	90.9	90.3	89.3	87.5	40	92.8	92.8	92.6	92.2	91.2	60	92.9	93.4	93.5	93.2	92.5	80	-※1	93.2	93.8	93.7	93.3	100	-※1	-※2	93.6	93.8	93.7	110	-※1	-※2	93.4	93.8	93.7	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-											
Load Ratio [%]	9V	12V	18V	24V	36V																																																																													
20	91.1	90.9	90.3	89.3	87.5																																																																													
40	92.8	92.8	92.6	92.2	91.2																																																																													
60	92.9	93.4	93.5	93.2	92.5																																																																													
80	-※1	93.2	93.8	93.7	93.3																																																																													
100	-※1	-※2	93.6	93.8	93.7																																																																													
110	-※1	-※2	93.4	93.8	93.7																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>91.1</td><td>90.9</td><td>90.3</td><td>89.3</td><td>87.5</td></tr> <tr><td>40</td><td>92.8</td><td>92.8</td><td>92.6</td><td>92.2</td><td>91.2</td></tr> <tr><td>60</td><td>92.9</td><td>93.4</td><td>93.5</td><td>93.2</td><td>92.5</td></tr> <tr><td>80</td><td>-※1</td><td>93.2</td><td>93.8</td><td>93.7</td><td>93.3</td></tr> <tr><td>100</td><td>-※1</td><td>-※2</td><td>93.6</td><td>93.8</td><td>93.7</td></tr> <tr><td>110</td><td>-※1</td><td>-※2</td><td>93.4</td><td>93.8</td><td>93.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>					Load Ratio [%]	Efficiency [%]					9[V]	12[V]	18[V]	24[V]	36[V]	0	-	-	-	-	-	20	91.1	90.9	90.3	89.3	87.5	40	92.8	92.8	92.6	92.2	91.2	60	92.9	93.4	93.5	93.2	92.5	80	-※1	93.2	93.8	93.7	93.3	100	-※1	-※2	93.6	93.8	93.7	110	-※1	-※2	93.4	93.8	93.7	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Efficiency [%]																																																																																	
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																													
0	-	-	-	-	-																																																																													
20	91.1	90.9	90.3	89.3	87.5																																																																													
40	92.8	92.8	92.6	92.2	91.2																																																																													
60	92.9	93.4	93.5	93.2	92.5																																																																													
80	-※1	93.2	93.8	93.7	93.3																																																																													
100	-※1	-※2	93.6	93.8	93.7																																																																													
110	-※1	-※2	93.4	93.8	93.7																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>※1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>※2 Maximum output current at 12V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																		



Model	MGFW802412	Temperature 25°C Testing Circuitry Figure A																																
Item	Line Regulation																																	
Object	+12V3.4A																																	
1.Graph		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>12.154</td><td>- ≈1</td></tr> <tr><td>9.0</td><td>12.151</td><td>- ≈1</td></tr> <tr><td>12.0</td><td>12.139</td><td>- ≈2</td></tr> <tr><td>15.0</td><td>12.130</td><td>12.084</td></tr> <tr><td>18.0</td><td>12.127</td><td>12.088</td></tr> <tr><td>24.0</td><td>12.124</td><td>12.090</td></tr> <tr><td>30.0</td><td>12.123</td><td>12.090</td></tr> <tr><td>36.0</td><td>12.122</td><td>12.091</td></tr> <tr><td>40.0</td><td>12.122</td><td>12.091</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	12.154	- ≈1	9.0	12.151	- ≈1	12.0	12.139	- ≈2	15.0	12.130	12.084	18.0	12.127	12.088	24.0	12.124	12.090	30.0	12.123	12.090	36.0	12.122	12.091	40.0	12.122	12.091
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
8.5	12.154	- ≈1																																
9.0	12.151	- ≈1																																
12.0	12.139	- ≈2																																
15.0	12.130	12.084																																
18.0	12.127	12.088																																
24.0	12.124	12.090																																
30.0	12.123	12.090																																
36.0	12.122	12.091																																
40.0	12.122	12.091																																
Object -12V3.4A		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>8.5</td><td>-12.196</td><td>- ≈1</td></tr> <tr><td>9.0</td><td>-12.190</td><td>- ≈1</td></tr> <tr><td>12.0</td><td>-12.161</td><td>- ≈2</td></tr> <tr><td>15.0</td><td>-12.149</td><td>-12.106</td></tr> <tr><td>18.0</td><td>-12.142</td><td>-12.103</td></tr> <tr><td>24.0</td><td>-12.136</td><td>-12.101</td></tr> <tr><td>30.0</td><td>-12.133</td><td>-12.100</td></tr> <tr><td>36.0</td><td>-12.132</td><td>-12.100</td></tr> <tr><td>40.0</td><td>-12.132</td><td>-12.100</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	8.5	-12.196	- ≈1	9.0	-12.190	- ≈1	12.0	-12.161	- ≈2	15.0	-12.149	-12.106	18.0	-12.142	-12.103	24.0	-12.136	-12.101	30.0	-12.133	-12.100	36.0	-12.132	-12.100	40.0	-12.132	-12.100
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
8.5	-12.196	- ≈1																																
9.0	-12.190	- ≈1																																
12.0	-12.161	- ≈2																																
15.0	-12.149	-12.106																																
18.0	-12.142	-12.103																																
24.0	-12.136	-12.101																																
30.0	-12.133	-12.100																																
36.0	-12.132	-12.100																																
40.0	-12.132	-12.100																																
Note: Slanted line shows the range of the rated input voltage.		<p>≈1 Maximum output current at minimum input Voltage is 70% of rated load current.</p> <p>≈2 Maximum output current at V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																



Model	MGFW802412																																																																																	
Item	Load Regulation				Temperature 25°C Testing Circuitry Figure A																																																																													
Object	+12V3.4A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 9V - - □ - - Input Volt. 12V - - * - - Input Volt. 18V - - ○ - - Input Volt. 24V - - ◆ - - Input Volt. 36V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>12.189</td> <td>12.193</td> <td>12.203</td> <td>12.195</td> <td>12.193</td> </tr> <tr> <td>0.7</td> <td>12.141</td> <td>12.141</td> <td>12.151</td> <td>12.155</td> <td>12.153</td> </tr> <tr> <td>1.4</td> <td>12.125</td> <td>12.127</td> <td>12.135</td> <td>12.133</td> <td>12.131</td> </tr> <tr> <td>2.0</td> <td>12.100</td> <td>12.109</td> <td>12.122</td> <td>12.120</td> <td>12.119</td> </tr> <tr> <td>2.4</td> <td>12.085</td> <td>12.099</td> <td>12.112</td> <td>12.111</td> <td>12.111</td> </tr> <tr> <td>2.7</td> <td>-※1</td> <td>12.086</td> <td>12.107</td> <td>12.105</td> <td>12.104</td> </tr> <tr> <td>3.4</td> <td>-※1</td> <td>-※2</td> <td>12.088</td> <td>12.090</td> <td>12.091</td> </tr> <tr> <td>3.7</td> <td>-※1</td> <td>-※2</td> <td>12.078</td> <td>12.081</td> <td>12.083</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>-12V: Rated Load Current</p>					Load Current [A]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	12.189	12.193	12.203	12.195	12.193	0.7	12.141	12.141	12.151	12.155	12.153	1.4	12.125	12.127	12.135	12.133	12.131	2.0	12.100	12.109	12.122	12.120	12.119	2.4	12.085	12.099	12.112	12.111	12.111	2.7	-※1	12.086	12.107	12.105	12.104	3.4	-※1	-※2	12.088	12.090	12.091	3.7	-※1	-※2	12.078	12.081	12.083	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.0	12.189	12.193	12.203	12.195	12.193																																																																													
0.7	12.141	12.141	12.151	12.155	12.153																																																																													
1.4	12.125	12.127	12.135	12.133	12.131																																																																													
2.0	12.100	12.109	12.122	12.120	12.119																																																																													
2.4	12.085	12.099	12.112	12.111	12.111																																																																													
2.7	-※1	12.086	12.107	12.105	12.104																																																																													
3.4	-※1	-※2	12.088	12.090	12.091																																																																													
3.7	-※1	-※2	12.078	12.081	12.083																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
Object	-12V3.4A																																																																																	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 9V - - □ - - Input Volt. 12V - - * - - Input Volt. 18V - - ○ - - Input Volt. 24V - - ◆ - - Input Volt. 36V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-12.199</td> <td>-12.205</td> <td>-12.215</td> <td>-12.211</td> <td>-12.221</td> </tr> <tr> <td>0.7</td> <td>-12.147</td> <td>-12.147</td> <td>-12.159</td> <td>-12.157</td> <td>-12.166</td> </tr> <tr> <td>1.4</td> <td>-12.140</td> <td>-12.138</td> <td>-12.145</td> <td>-12.141</td> <td>-12.137</td> </tr> <tr> <td>2.0</td> <td>-12.117</td> <td>-12.122</td> <td>-12.134</td> <td>-12.129</td> <td>-12.125</td> </tr> <tr> <td>2.4</td> <td>-12.105</td> <td>-12.113</td> <td>-12.126</td> <td>-12.122</td> <td>-12.118</td> </tr> <tr> <td>2.7</td> <td>-※1</td> <td>-12.104</td> <td>-12.121</td> <td>-12.116</td> <td>-12.113</td> </tr> <tr> <td>3.4</td> <td>-※1</td> <td>-※2</td> <td>-12.103</td> <td>-12.101</td> <td>-12.100</td> </tr> <tr> <td>3.7</td> <td>-※1</td> <td>-※2</td> <td>-12.095</td> <td>-12.095</td> <td>-12.094</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>+12V: Rated Load Current</p>					Load Current [A]	Output Voltage [V]					Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	-12.199	-12.205	-12.215	-12.211	-12.221	0.7	-12.147	-12.147	-12.159	-12.157	-12.166	1.4	-12.140	-12.138	-12.145	-12.141	-12.137	2.0	-12.117	-12.122	-12.134	-12.129	-12.125	2.4	-12.105	-12.113	-12.126	-12.122	-12.118	2.7	-※1	-12.104	-12.121	-12.116	-12.113	3.4	-※1	-※2	-12.103	-12.101	-12.100	3.7	-※1	-※2	-12.095	-12.095	-12.094	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																	
	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																																													
0.0	-12.199	-12.205	-12.215	-12.211	-12.221																																																																													
0.7	-12.147	-12.147	-12.159	-12.157	-12.166																																																																													
1.4	-12.140	-12.138	-12.145	-12.141	-12.137																																																																													
2.0	-12.117	-12.122	-12.134	-12.129	-12.125																																																																													
2.4	-12.105	-12.113	-12.126	-12.122	-12.118																																																																													
2.7	-※1	-12.104	-12.121	-12.116	-12.113																																																																													
3.4	-※1	-※2	-12.103	-12.101	-12.100																																																																													
3.7	-※1	-※2	-12.095	-12.095	-12.094																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
<p>Note: Slanted line shows the range of the rated load current.</p> <p>*1 Maximum output current at minimum input Voltage is 70% of rated load current. *2 Maximum output current at 12V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																		

COSEL

Model	MGFW802412
Item	Dynamic Load Response
Object	+12V3.4A


Temperature 25°C
Testing Circuitry Figure A

Input Volt. 24 V

-12V:rated load current.


Cycle 100 ms

t1,t2 = 100 μ s

Min.Load (0A)↔
Load 100% (3.4A)

200 mV/div

2 ms/div




2 ms/div

Min.Load (0A)↔
Load 50% (1.7A)

200 mV/div

2 ms/div




2 ms/div

Load 50% (1.7A)↔
Load 100% (3.4A)

200 mV/div

2 ms/div



2 ms/div

COSEL

Model	MGFW802412
Item	Dynamic Load Response
Object	-12V3.4A


Temperature 25°C
Testing Circuitry Figure A

Input Volt. 24 V

+12V:rated load current.


Cycle 100 ms

t1,t2 = 100 μ s

Min.Load (0A)↔
Load 100% (3.4A)

200 mV/div

2 ms/div




2 ms/div

Min.Load (0A)↔
Load 50% (1.7A)

200 mV/div

2 ms/div




2 ms/div

Load 50% (1.7A)↔
Load 100% (3.4A)

200 mV/div

2 ms/div




2 ms/div

COSEL

Model	MGFW802412
Item	Ripple Voltage (by Load Current)
Object	+12V3.4A

 Temperature 25°C
 Testing Circuitry Figure B

1. Graph



Measured by 100 MHz Oscilloscope.
 Ripple Voltage is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.0	15	30
0.7	5	5
1.4	5	5
2.0	10	5
2.4	10	5
2.7	-	5
3.4	-	5
3.7	-	10
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.





Fig.Complex Ripple Wave Form

COSEL

Model	MGFW802412
Item	Ripple Voltage (by Load Current)
Object	-12V3.4A

 Temperature 25°C
 Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.
 Ripple Voltage is shown as p-p in the figure below.
 Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.0	15	30
0.7	5	5
1.4	5	5
2.0	10	5
2.4	10	5
2.7	-	5
3.4	-	5
3.7	-	10
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.




Fig.Complex Ripple Wave Form


COSEL

Model MGF802412

Item Ripple-Noise

Object +12V3.4A

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.0	15	30
0.7	10	10
1.4	10	10
2.0	15	10
2.4	15	15
2.7	-	15
3.4	-	20
3.7	-	25
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.


COSEL

Model MGF802412

Item Ripple-Noise

Object -12V3.4A

1. Graph



Measured by 100 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Ripple Noise[mVp-p]




Fig.Complex Ripple Noise Wave Form

Temperature 25°C
Testing Circuitry Figure B

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 9 [V]	Input Volt. 36 [V]
0.0	15	30
0.7	10	10
1.4	10	10
2.0	15	10
2.4	15	15
2.7	-	15
3.4	-	20
3.7	-	25
--	-	-
--	-	-
--	-	-


+12V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.

COSEL

Model	MGFW802412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V3.4A

1.Graph




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	10
-20	5	10
25	5	10
60	5	10
70	5	10
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	10
-20	5	10
25	5	10
60	5	10
70	5	10
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current

Measured by 100 MHz Oscilloscope.
Note: Slanted line shows the range of the rated ambient temperature.



Model	MGFW802412	Testing Circuitry Figure A																																																																																		
Item	Ambient Temperature Drift																																																																																			
Object	+12V3.4A																																																																																			
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 9V Input Volt. 12V Input Volt. 18V Input Volt. 24V Input Volt. 36V 																																																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>11.993</td><td>11.998</td><td>12.007</td><td>12.011</td><td>12.014</td></tr> <tr><td>-40</td><td>12.025</td><td>12.026</td><td>12.035</td><td>12.038</td><td>12.041</td></tr> <tr><td>-20</td><td>12.048</td><td>12.050</td><td>12.054</td><td>12.057</td><td>12.059</td></tr> <tr><td>0</td><td>12.066</td><td>12.071</td><td>12.072</td><td>12.074</td><td>12.076</td></tr> <tr><td>25</td><td>12.081</td><td>12.087</td><td>12.088</td><td>12.090</td><td>12.091</td></tr> <tr><td>60</td><td>12.093</td><td>12.099</td><td>12.097</td><td>12.099</td><td>12.100</td></tr> <tr><td>70</td><td>12.095</td><td>12.102</td><td>12.098</td><td>12.100</td><td>12.101</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>						Ambient Temperature [°C]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	-60	11.993	11.998	12.007	12.011	12.014	-40	12.025	12.026	12.035	12.038	12.041	-20	12.048	12.050	12.054	12.057	12.059	0	12.066	12.071	12.072	12.074	12.076	25	12.081	12.087	12.088	12.090	12.091	60	12.093	12.099	12.097	12.099	12.100	70	12.095	12.102	12.098	12.100	12.101	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	
Ambient Temperature [°C]	Output Voltage [V]																																																																																			
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																															
-60	11.993	11.998	12.007	12.011	12.014																																																																															
-40	12.025	12.026	12.035	12.038	12.041																																																																															
-20	12.048	12.050	12.054	12.057	12.059																																																																															
0	12.066	12.071	12.072	12.074	12.076																																																																															
25	12.081	12.087	12.088	12.090	12.091																																																																															
60	12.093	12.099	12.097	12.099	12.100																																																																															
70	12.095	12.102	12.098	12.100	12.101																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
Object	-12V3.4A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> <th>24[V]</th> <th>36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.028</td><td>-12.025</td><td>-12.022</td><td>-12.021</td><td>-12.019</td></tr> <tr><td>-40</td><td>-12.052</td><td>-12.053</td><td>-12.050</td><td>-12.049</td><td>-12.047</td></tr> <tr><td>-20</td><td>-12.073</td><td>-12.073</td><td>-12.068</td><td>-12.067</td><td>-12.066</td></tr> <tr><td>0</td><td>-12.089</td><td>-12.086</td><td>-12.086</td><td>-12.084</td><td>-12.083</td></tr> <tr><td>25</td><td>-12.104</td><td>-12.101</td><td>-12.103</td><td>-12.101</td><td>-12.100</td></tr> <tr><td>60</td><td>-12.116</td><td>-12.113</td><td>-12.113</td><td>-12.111</td><td>-12.109</td></tr> <tr><td>70</td><td>-12.118</td><td>-12.115</td><td>-12.114</td><td>-12.112</td><td>-12.111</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>						Ambient Temperature [°C]	Output Voltage [V]					9[V]	12[V]	18[V]	24[V]	36[V]	-60	-12.028	-12.025	-12.022	-12.021	-12.019	-40	-12.052	-12.053	-12.050	-12.049	-12.047	-20	-12.073	-12.073	-12.068	-12.067	-12.066	0	-12.089	-12.086	-12.086	-12.084	-12.083	25	-12.104	-12.101	-12.103	-12.101	-12.100	60	-12.116	-12.113	-12.113	-12.111	-12.109	70	-12.118	-12.115	-12.114	-12.112	-12.111	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																																																			
	9[V]	12[V]	18[V]	24[V]	36[V]																																																																															
-60	-12.028	-12.025	-12.022	-12.021	-12.019																																																																															
-40	-12.052	-12.053	-12.050	-12.049	-12.047																																																																															
-20	-12.073	-12.073	-12.068	-12.067	-12.066																																																																															
0	-12.089	-12.086	-12.086	-12.084	-12.083																																																																															
25	-12.104	-12.101	-12.103	-12.101	-12.100																																																																															
60	-12.116	-12.113	-12.113	-12.111	-12.109																																																																															
70	-12.118	-12.115	-12.114	-12.112	-12.111																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
Note: Slanted line shows the range of the rated ambient temperature.		<p>Note: In case of input Volt.9V, Load 70%. 12V, Load 80%. Other case Load 100%.</p>																																																																																		



Model	MGFW802412	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 9 - 36V

Load Current (AVR 1) : 0 - 3.4A (AVR 2) : 0 - 3.4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+12V3.4A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	60	9	0	12.228	± 102	± 0.9
Minimum Voltage	-40	9	2.4	12.025		

Object	-12V3.4A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	60	36	0	-12.245	± 99	± 0.8
Minimum Voltage	-40	36	3.4	-12.047		

COSEL


Model	MGFW802412	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V3.4A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.078</td></tr> <tr><td>0.5</td><td>12.090</td></tr> <tr><td>1.0</td><td>12.090</td></tr> <tr><td>2.0</td><td>12.090</td></tr> <tr><td>3.0</td><td>12.090</td></tr> <tr><td>4.0</td><td>12.090</td></tr> <tr><td>5.0</td><td>12.090</td></tr> <tr><td>6.0</td><td>12.090</td></tr> <tr><td>7.0</td><td>12.090</td></tr> <tr><td>8.0</td><td>12.090</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	12.078	0.5	12.090	1.0	12.090	2.0	12.090	3.0	12.090	4.0	12.090	5.0	12.090	6.0	12.090	7.0	12.090	8.0	12.090
Time since start [H]	Output Voltage [V]																								
0.0	12.078																								
0.5	12.090																								
1.0	12.090																								
2.0	12.090																								
3.0	12.090																								
4.0	12.090																								
5.0	12.090																								
6.0	12.090																								
7.0	12.090																								
8.0	12.090																								
Object			2.Values																						
1.Graph			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.091</td></tr> <tr><td>0.5</td><td>-12.104</td></tr> <tr><td>1.0</td><td>-12.104</td></tr> <tr><td>2.0</td><td>-12.104</td></tr> <tr><td>3.0</td><td>-12.104</td></tr> <tr><td>4.0</td><td>-12.104</td></tr> <tr><td>5.0</td><td>-12.104</td></tr> <tr><td>6.0</td><td>-12.104</td></tr> <tr><td>7.0</td><td>-12.104</td></tr> <tr><td>8.0</td><td>-12.104</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-12.091	0.5	-12.104	1.0	-12.104	2.0	-12.104	3.0	-12.104	4.0	-12.104	5.0	-12.104	6.0	-12.104	7.0	-12.104	8.0	-12.104
Time since start [H]	Output Voltage [V]																								
0.0	-12.091																								
0.5	-12.104																								
1.0	-12.104																								
2.0	-12.104																								
3.0	-12.104																								
4.0	-12.104																								
5.0	-12.104																								
6.0	-12.104																								
7.0	-12.104																								
8.0	-12.104																								
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>																									

COSEL

Model	MGFW802412
Item	Rise and Fall Time
Object	+12V3.4A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		6.6	3.6	10.2	0.3	2.0	
100 %		6.6	5.1	11.7	0.2	0.7	




COSEL

Model	MGFW802412
Item	Rise and Fall Time
Object	-12V3.4A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		6.6	3.6	10.2	0.3	2.3
100 %		6.6	5.1	11.7	0.2	0.8



COSEL

Model	MGFW802412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V3.4A

1.Graph



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	7.5	7.7
-40	7.4	7.7
-20	7.5	7.5
0	7.5	7.5
25	7.5	7.4
60	7.4	7.5
70	7.4	7.5
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Load Current is same as well as +12V

Object	-12V3.4A
--------	----------

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	7.5	7.7
-40	7.4	7.7
-20	7.5	7.5
0	7.5	7.5
25	7.5	7.4
60	7.4	7.5
70	7.4	7.5
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Load Current is same as well as -12V

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]				
	9[V]	12[V]	18[V]	24[V]	36[V]
12.0	3.495	4.373	4.701	4.719	4.797
11.4	-※1	-※2	-	-	-
10.8	-	-	-	-	-
9.6	-	-	-	-	-
8.4	-	-	-	-	-
7.2	-	-	-	-	-
6.0	-	-	-	-	-
4.8	-	-	-	-	-
3.6	-	-	-	-	-
0.0	-	-	-	-	-

-12V: Rated Load Current

2.Values


Output Voltage [V]	Load Current [A]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-12.0	3.495	4.373	4.688	4.699	4.834
-11.4	-※1	-※2	-	-	-
-10.8	-	-	-	-	-
-9.6	-	-	-	-	-
-8.4	-	-	-	-	-
-7.2	-	-	-	-	-
-6.0	-	-	-	-	-
-4.8	-	-	-	-	-
-3.6	-	-	-	-	-
0.0	-	-	-	-	-

+12V: Rated Load Current

※1 Maximum output current at minimum input Voltage is 70% of rated load current.

※2 Maximum output current at V input Voltage is 80% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL


Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [%]				
	9[V]	12[V]	18[V]	24[V]	36[V]
-60	125	125	125	125	125
-40	126	126	126	126	126
-20	128	128	128	128	128
0	129	129	129	129	129
25	131	131	131	131	131
60	134	134	134	134	134
70	135	135	135	135	135
0	-	-	-	-	-
0	-	-	-	-	-
0	-	-	-	-	-
0	-	-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.


Measured as a single output (+24V).

COSEL

Model	MGFW802412
Item	Switching frequency (by Load Current)
Object	+/-12V3.4A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

-switching frequency of MG80 changes depending on load current and input voltage.


When load current is low, switching frequency becomes high and step down to low frequency at certain point. There is hysteresis, so characteristic is different between load increase (sweep from 0% to 100%) and load decrease (sweep from 100% to 0%).

-When load current is low, MG80 operates intermittently, so switching frequency would not become constant.

※ Maximum output current at minimum input Voltage is 70% of rated load current.

Refer to instruction manuals for details of input derating.

COSEL



Data Acquisition/Control Unit

Figure A




Figure B (Ripple and Ripple noise Characteristic)