

TEST DATA OF MGS15243R3

Regulated DC Power Supply
September 9, 2010

Approved by : Kazunari Asano
Kazunari Asano

Design Manager

Prepared by : Junki Nakayama
Junki Nakayama


Design Engineer

COSEL CO.,LTD.


CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	9
10. Ripple-Noise	10
11. Ripple Voltage (by Ambient Temperature)	11
12. Ambient Temperature Drift	12
13. Output Voltage Accuracy	13
14. Time Lapse Drift	14
15. Rise and Fall Time	15
16. Minimum Input Voltage for Regulated Output Voltage	16
17. Overcurrent Protection	17
18. Figure of Testing Circuitry	18


(Final Page 18)

Model	MGS15243R3																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	_____																																																																																	
1.Graph	<p style="text-align: center;">—△— Load 100% - - -□--- Load 50% - - -○--- Load 0%</p>  <p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>4</td><td>0.001</td><td>0.002</td><td>0.001</td></tr> <tr><td>8</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>16</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>17</td><td>0.041</td><td>0.467</td><td>0.940</td></tr> <tr><td>18</td><td>0.040</td><td>0.433</td><td>0.864</td></tr> <tr><td>20</td><td>0.038</td><td>0.390</td><td>0.777</td></tr> <tr><td>22</td><td>0.035</td><td>0.355</td><td>0.704</td></tr> <tr><td>24</td><td>0.033</td><td>0.326</td><td>0.644</td></tr> <tr><td>28</td><td>0.030</td><td>0.280</td><td>0.550</td></tr> <tr><td>30</td><td>0.029</td><td>0.262</td><td>0.515</td></tr> <tr><td>32</td><td>0.028</td><td>0.247</td><td>0.481</td></tr> <tr><td>36</td><td>0.026</td><td>0.220</td><td>0.429</td></tr> <tr><td>40</td><td>0.025</td><td>0.199</td><td>0.387</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0	0.000	0.000	0.000	4	0.001	0.002	0.001	8	0.002	0.002	0.002	16	0.003	0.003	0.003	17	0.041	0.467	0.940	18	0.040	0.433	0.864	20	0.038	0.390	0.777	22	0.035	0.355	0.704	24	0.033	0.326	0.644	28	0.030	0.280	0.550	30	0.029	0.262	0.515	32	0.028	0.247	0.481	36	0.026	0.220	0.429	40	0.025	0.199	0.387	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0	0.000	0.000	0.000																																																																															
4	0.001	0.002	0.001																																																																															
8	0.002	0.002	0.002																																																																															
16	0.003	0.003	0.003																																																																															
17	0.041	0.467	0.940																																																																															
18	0.040	0.433	0.864																																																																															
20	0.038	0.390	0.777																																																																															
22	0.035	0.355	0.704																																																																															
24	0.033	0.326	0.644																																																																															
28	0.030	0.280	0.550																																																																															
30	0.029	0.262	0.515																																																																															
32	0.028	0.247	0.481																																																																															
36	0.026	0.220	0.429																																																																															
40	0.025	0.199	0.387																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

Model	MGS15243R3																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - ○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 18V [A]</th> <th>Input Volt. 24V [A]</th> <th>Input Volt. 36V [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.040</td><td>0.034</td><td>0.026</td></tr> <tr><td>0.8</td><td>0.194</td><td>0.148</td><td>0.103</td></tr> <tr><td>1.6</td><td>0.354</td><td>0.267</td><td>0.181</td></tr> <tr><td>2.4</td><td>0.517</td><td>0.390</td><td>0.263</td></tr> <tr><td>3.2</td><td>0.693</td><td>0.516</td><td>0.344</td></tr> <tr><td>4.0</td><td>0.866</td><td>0.642</td><td>0.429</td></tr> <tr><td>4.4</td><td>0.954</td><td>0.715</td><td>0.473</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 18V [A]	Input Volt. 24V [A]	Input Volt. 36V [A]	0.0	0.040	0.034	0.026	0.8	0.194	0.148	0.103	1.6	0.354	0.267	0.181	2.4	0.517	0.390	0.263	3.2	0.693	0.516	0.344	4.0	0.866	0.642	0.429	4.4	0.954	0.715	0.473																			
Load Current [A]	Input Volt. 18V [A]	Input Volt. 24V [A]	Input Volt. 36V [A]																																																			
0.0	0.040	0.034	0.026																																																			
0.8	0.194	0.148	0.103																																																			
1.6	0.354	0.267	0.181																																																			
2.4	0.517	0.390	0.263																																																			
3.2	0.693	0.516	0.344																																																			
4.0	0.866	0.642	0.429																																																			
4.4	0.954	0.715	0.473																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.040</td><td>0.034</td><td>0.026</td></tr> <tr><td>0.8</td><td>0.194</td><td>0.148</td><td>0.103</td></tr> <tr><td>1.6</td><td>0.354</td><td>0.267</td><td>0.181</td></tr> <tr><td>2.4</td><td>0.517</td><td>0.390</td><td>0.263</td></tr> <tr><td>3.2</td><td>0.693</td><td>0.516</td><td>0.344</td></tr> <tr><td>4.0</td><td>0.866</td><td>0.642</td><td>0.429</td></tr> <tr><td>4.4</td><td>0.954</td><td>0.715</td><td>0.473</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	0.040	0.034	0.026	0.8	0.194	0.148	0.103	1.6	0.354	0.267	0.181	2.4	0.517	0.390	0.263	3.2	0.693	0.516	0.344	4.0	0.866	0.642	0.429	4.4	0.954	0.715	0.473	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0.0	0.040	0.034	0.026																																																			
0.8	0.194	0.148	0.103																																																			
1.6	0.354	0.267	0.181																																																			
2.4	0.517	0.390	0.263																																																			
3.2	0.693	0.516	0.344																																																			
4.0	0.866	0.642	0.429																																																			
4.4	0.954	0.715	0.473																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	MGS15243R3																																																						
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - · -○--- Input Volt. 36V</p>  <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (18V)</th> <th>Input Power [W] (24V)</th> <th>Input Power [W] (36V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.72</td><td>0.81</td><td>0.95</td></tr> <tr><td>0.8</td><td>3.47</td><td>3.55</td><td>3.69</td></tr> <tr><td>1.6</td><td>6.35</td><td>6.39</td><td>6.52</td></tr> <tr><td>2.4</td><td>9.33</td><td>9.34</td><td>9.44</td></tr> <tr><td>3.2</td><td>12.34</td><td>12.31</td><td>12.35</td></tr> <tr><td>4.0</td><td>15.55</td><td>15.44</td><td>15.41</td></tr> <tr><td>4.4</td><td>17.22</td><td>17.03</td><td>16.97</td></tr> </tbody> </table>	Load Current [A]	Input Power [W] (18V)	Input Power [W] (24V)	Input Power [W] (36V)	0.0	0.72	0.81	0.95	0.8	3.47	3.55	3.69	1.6	6.35	6.39	6.52	2.4	9.33	9.34	9.44	3.2	12.34	12.31	12.35	4.0	15.55	15.44	15.41	4.4	17.22	17.03	16.97																						
Load Current [A]	Input Power [W] (18V)	Input Power [W] (24V)	Input Power [W] (36V)																																																				
0.0	0.72	0.81	0.95																																																				
0.8	3.47	3.55	3.69																																																				
1.6	6.35	6.39	6.52																																																				
2.4	9.33	9.34	9.44																																																				
3.2	12.34	12.31	12.35																																																				
4.0	15.55	15.44	15.41																																																				
4.4	17.22	17.03	16.97																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.72</td><td>0.81</td><td>0.95</td></tr> <tr><td>0.8</td><td>3.47</td><td>3.55</td><td>3.69</td></tr> <tr><td>1.6</td><td>6.35</td><td>6.39</td><td>6.52</td></tr> <tr><td>2.4</td><td>9.33</td><td>9.34</td><td>9.44</td></tr> <tr><td>3.2</td><td>12.34</td><td>12.31</td><td>12.35</td></tr> <tr><td>4.0</td><td>15.55</td><td>15.44</td><td>15.41</td></tr> <tr><td>4.4</td><td>17.22</td><td>17.03</td><td>16.97</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	0.72	0.81	0.95	0.8	3.47	3.55	3.69	1.6	6.35	6.39	6.52	2.4	9.33	9.34	9.44	3.2	12.34	12.31	12.35	4.0	15.55	15.44	15.41	4.4	17.22	17.03	16.97	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Input Power [W]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
0.0	0.72	0.81	0.95																																																				
0.8	3.47	3.55	3.69																																																				
1.6	6.35	6.39	6.52																																																				
2.4	9.33	9.34	9.44																																																				
3.2	12.34	12.31	12.35																																																				
4.0	15.55	15.44	15.41																																																				
4.4	17.22	17.03	16.97																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

Model	MGS15243R3																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td> <td>85.3</td> <td>85.3</td> </tr> <tr> <td>18</td> <td>85.4</td> <td>85.4</td> </tr> <tr> <td>20</td> <td>85.3</td> <td>85.8</td> </tr> <tr> <td>24</td> <td>85.1</td> <td>86.3</td> </tr> <tr> <td>30</td> <td>84.8</td> <td>86.5</td> </tr> <tr> <td>36</td> <td>84.3</td> <td>86.4</td> </tr> <tr> <td>40</td> <td>83.8</td> <td>86.2</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	85.3	85.3	18	85.4	85.4	20	85.3	85.8	24	85.1	86.3	30	84.8	86.5	36	84.3	86.4	40	83.8	86.2	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	85.3	85.3																																
18	85.4	85.4																																
20	85.3	85.8																																
24	85.1	86.3																																
30	84.8	86.5																																
36	84.3	86.4																																
40	83.8	86.2																																
--	-	-																																
--	-	-																																


Model	MGS15243R3	Temperature Testing Circuitry 25°C Figure A																																																		
Item	Efficiency (by Load Current)																																																			
Object	_____																																																			
1.Graph		2.Values																																																		
<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - - ○ - - Input Volt. 36V</p>  <p>The graph plots Efficiency [%] on the y-axis (50 to 90) against Load Current [A] on the x-axis (0.0 to 4.0). Three data series are shown: 18V (solid line with triangle markers), 24V (dashed line with square markers), and 36V (dash-dot line with circle markers). All curves show efficiency increasing with load current. A slanted line on the right side of the graph indicates the rated load current range.</p>																																																				
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>0.8</td> <td>77.1</td> <td>75.4</td> <td>72.5</td> </tr> <tr> <td>1.6</td> <td>84.4</td> <td>83.8</td> <td>82.2</td> </tr> <tr> <td>2.4</td> <td>86.2</td> <td>86.1</td> <td>85.2</td> </tr> <tr> <td>3.2</td> <td>86.4</td> <td>86.7</td> <td>86.3</td> </tr> <tr> <td>4.0</td> <td>85.6</td> <td>86.4</td> <td>86.6</td> </tr> <tr> <td>4.4</td> <td>85.2</td> <td>86.2</td> <td>86.5</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	-	-	-	0.8	77.1	75.4	72.5	1.6	84.4	83.8	82.2	2.4	86.2	86.1	85.2	3.2	86.4	86.7	86.3	4.0	85.6	86.4	86.6	4.4	85.2	86.2	86.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																			
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																	
0.0	-	-	-																																																	
0.8	77.1	75.4	72.5																																																	
1.6	84.4	83.8	82.2																																																	
2.4	86.2	86.1	85.2																																																	
3.2	86.4	86.7	86.3																																																	
4.0	85.6	86.4	86.6																																																	
4.4	85.2	86.2	86.5																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
<p>Note: Slanted line shows the range of the rated load current.</p>																																																				

Model	MGS15243R3																																	
Item	Line Regulation	Temperature Testing Circuitry 25°C Figure A																																
Object	+3.3V4A																																	
1. Graph																																		
<p>The graph plots Output Voltage [V] on the y-axis (3.28 to 3.42) against Input Voltage [V] on the x-axis (10 to 40). Two horizontal dashed lines represent Load 50% and Load 100%, both centered at approximately 3.34 V. A slanted line shows the range of the rated input voltage, from about 17 V to 40 V.</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td> <td>3.343</td> <td>3.341</td> </tr> <tr> <td>18</td> <td>3.343</td> <td>3.342</td> </tr> <tr> <td>20</td> <td>3.343</td> <td>3.342</td> </tr> <tr> <td>24</td> <td>3.343</td> <td>3.342</td> </tr> <tr> <td>30</td> <td>3.343</td> <td>3.342</td> </tr> <tr> <td>36</td> <td>3.343</td> <td>3.342</td> </tr> <tr> <td>40</td> <td>3.343</td> <td>3.342</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	17	3.343	3.341	18	3.343	3.342	20	3.343	3.342	24	3.343	3.342	30	3.343	3.342	36	3.343	3.342	40	3.343	3.342	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
17	3.343	3.341																																
18	3.343	3.342																																
20	3.343	3.342																																
24	3.343	3.342																																
30	3.343	3.342																																
36	3.343	3.342																																
40	3.343	3.342																																
--	-	-																																
--	-	-																																
Note: Slanted line shows the range of the rated input voltage.																																		

Model	MGS15243R3	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Load Regulation																																																						
Object	+3.3V4A																																																						
1.Graph	<p style="text-align: center;"> Input Volt. 18V Input Volt. 24V Input Volt. 36V </p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>3.344</td> <td>3.344</td> <td>3.344</td> </tr> <tr> <td>0.8</td> <td>3.344</td> <td>3.344</td> <td>3.343</td> </tr> <tr> <td>1.6</td> <td>3.343</td> <td>3.343</td> <td>3.343</td> </tr> <tr> <td>2.4</td> <td>3.343</td> <td>3.343</td> <td>3.343</td> </tr> <tr> <td>3.2</td> <td>3.342</td> <td>3.342</td> <td>3.342</td> </tr> <tr> <td>4.0</td> <td>3.342</td> <td>3.342</td> <td>3.342</td> </tr> <tr> <td>4.4</td> <td>3.341</td> <td>3.341</td> <td>3.342</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.0	3.344	3.344	3.344	0.8	3.344	3.344	3.343	1.6	3.343	3.343	3.343	2.4	3.343	3.343	3.343	3.2	3.342	3.342	3.342	4.0	3.342	3.342	3.342	4.4	3.341	3.341	3.342	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
0.0	3.344	3.344	3.344																																																				
0.8	3.344	3.344	3.343																																																				
1.6	3.343	3.343	3.343																																																				
2.4	3.343	3.343	3.343																																																				
3.2	3.342	3.342	3.342																																																				
4.0	3.342	3.342	3.342																																																				
4.4	3.341	3.341	3.342																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.

COSEL




Model	MGS15243R3																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+3.3V4A																																							
1.Graph																																								
<p>Input Volt. 18V Input Volt. 36V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>5</td><td>6</td></tr> <tr> <td>0.8</td><td>5</td><td>7</td></tr> <tr> <td>1.6</td><td>5</td><td>7</td></tr> <tr> <td>2.4</td><td>7</td><td>8</td></tr> <tr> <td>3.2</td><td>8</td><td>9</td></tr> <tr> <td>4.0</td><td>10</td><td>10</td></tr> <tr> <td>4.4</td><td>11</td><td>10</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	5	6	0.8	5	7	1.6	5	7	2.4	7	8	3.2	8	9	4.0	10	10	4.4	11	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.0	5	6																																						
0.8	5	7																																						
1.6	5	7																																						
2.4	7	8																																						
3.2	8	9																																						
4.0	10	10																																						
4.4	11	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

Model	MGS15243R3	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure B																																						
Object	+3.3V4A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>7</td><td>9</td></tr> <tr><td>0.8</td><td>6</td><td>8</td></tr> <tr><td>1.6</td><td>6</td><td>8</td></tr> <tr><td>2.4</td><td>7</td><td>8</td></tr> <tr><td>3.2</td><td>9</td><td>9</td></tr> <tr><td>4.0</td><td>10</td><td>10</td></tr> <tr><td>4.4</td><td>11</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.0	7	9	0.8	6	8	1.6	6	8	2.4	7	8	3.2	9	9	4.0	10	10	4.4	11	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 18 [V]	Input Volt. 36 [V]																																							
0.0	7	9																																							
0.8	6	8																																							
1.6	6	8																																							
2.4	7	8																																							
3.2	9	9																																							
4.0	10	10																																							
4.4	11	10																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Noise Wave Form</p>			-																																						
			BC-10443																																						

Model	MGS15243R3
Item	Ripple Voltage (by Ambient Temp.)
Object	+3.3V4A

Testing Circuitry Figure B

1. Graph




2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	10	14
-40	10	13
-20	8	12
0	7	10
25	8	10
60	7	10
65	7	10
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGS15243R3
Item	Ambient Temperature Drift
Object	+3.3V4A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
-60	3.346	3.346	3.346
-40	3.347	3.347	3.347
-20	3.345	3.346	3.346
0	3.343	3.343	3.343
25	3.342	3.342	3.342
60	3.339	3.339	3.339
65	3.338	3.338	3.338
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGS15243R3	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+3.3V4A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 18 - 36V

Load Current : 0 - 4A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	18	0	3.350	±6	±0.2
Minimum Voltage	60	18	4	3.339		

COSEL

Model	MGS15243R3
Item	Time Lapse Drift
Object	+3.3V4A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Time since start [H]	Output Voltage [V]
0.0	3.342
0.5	3.341
1.0	3.341
2.0	3.341
3.0	3.341
4.0	3.341
5.0	3.341
6.0	3.341
7.0	3.341
8.0	3.341

COSEL

Model	MGS15243R3
Item	Rise and Fall Time
Object	+3.3V4A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.2	1.0	2.2	0.2	2.5
100 %		1.2	1.0	2.2	0.2	1.2



Model	MGS15243R3
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+3.3V4A

Testing Circuitry Figure A


1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	16.0	15.9
-40	15.9	15.9
-20	15.9	16.0
0	15.9	15.9
25	15.9	15.8
60	15.8	15.8
65	15.8	15.8
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGS15243R3	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Overcurrent Protection																																																								
Object	+3.3V4A																																																								
1.Graph	<p>—△— Input Volt. 18V —□— Input Volt. 24V —○— Input Volt. 36V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																							
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Intermittent operation occurs when overcurrent protection is activated.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>3.30</td><td>5.64</td><td>5.99</td><td>5.75</td></tr> <tr><td>3.14</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.97</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.64</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.31</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.98</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.65</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.32</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.99</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.66</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.33</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	3.30	5.64	5.99	5.75	3.14	-	-	-	2.97	-	-	-	2.64	-	-	-	2.31	-	-	-	1.98	-	-	-	1.65	-	-	-	1.32	-	-	-	0.99	-	-	-	0.66	-	-	-	0.33	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																						
3.30	5.64	5.99	5.75																																																						
3.14	-	-	-																																																						
2.97	-	-	-																																																						
2.64	-	-	-																																																						
2.31	-	-	-																																																						
1.98	-	-	-																																																						
1.65	-	-	-																																																						
1.32	-	-	-																																																						
0.99	-	-	-																																																						
0.66	-	-	-																																																						
0.33	-	-	-																																																						
0.00	-	-	-																																																						

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)