



TEST DATA OF MGS1R50515

Regulated DC Power Supply
March 31, 2016

Approved by : Takayuki Fukuda Design Manager
Takayuki Fukuda

Prepared by : Shohei Mukaiide Design Engineer
Shohei Mukaiide

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching Frequency (by Load Current)	18
19.Figure of Testing Circuitry	19


(Final Page 19)

COSEL

Model	MGS1R50515																																																																																	
Item	Input Current (by Input Voltage)	Temperature Testing Circuitry	25°C Figure A																																																																															
Object	_____	_____	_____																																																																															
1.Graph	Load 100% Load 50% Load 0%	Input Current [A]	2.Values																																																																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>3.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>3.7</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>3.8</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>3.9</td><td>0.031</td><td>0.245</td><td>0.464</td></tr> <tr><td>4.0</td><td>0.030</td><td>0.233</td><td>0.450</td></tr> <tr><td>4.2</td><td>0.029</td><td>0.227</td><td>0.427</td></tr> <tr><td>4.5</td><td>0.028</td><td>0.212</td><td>0.398</td></tr> <tr><td>5.0</td><td>0.026</td><td>0.192</td><td>0.358</td></tr> <tr><td>6.0</td><td>0.024</td><td>0.161</td><td>0.298</td></tr> <tr><td>7.0</td><td>0.019</td><td>0.140</td><td>0.257</td></tr> <tr><td>8.0</td><td>0.017</td><td>0.126</td><td>0.227</td></tr> <tr><td>9.0</td><td>0.015</td><td>0.115</td><td>0.206</td></tr> <tr><td>10.0</td><td>0.014</td><td>0.107</td><td>0.188</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	3.0	0.002	0.002	0.002	3.7	0.003	0.003	0.003	3.8	0.003	0.003	0.003	3.9	0.031	0.245	0.464	4.0	0.030	0.233	0.450	4.2	0.029	0.227	0.427	4.5	0.028	0.212	0.398	5.0	0.026	0.192	0.358	6.0	0.024	0.161	0.298	7.0	0.019	0.140	0.257	8.0	0.017	0.126	0.227	9.0	0.015	0.115	0.206	10.0	0.014	0.107	0.188	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
3.0	0.002	0.002	0.002																																																																															
3.7	0.003	0.003	0.003																																																																															
3.8	0.003	0.003	0.003																																																																															
3.9	0.031	0.245	0.464																																																																															
4.0	0.030	0.233	0.450																																																																															
4.2	0.029	0.227	0.427																																																																															
4.5	0.028	0.212	0.398																																																																															
5.0	0.026	0.192	0.358																																																																															
6.0	0.024	0.161	0.298																																																																															
7.0	0.019	0.140	0.257																																																																															
8.0	0.017	0.126	0.227																																																																															
9.0	0.015	0.115	0.206																																																																															
10.0	0.014	0.107	0.188																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															

COSEL

Model	MGS1R50515
Item	Input Current (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Current [A]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.00	0.028	0.026	0.015
0.02	0.099	0.090	0.061
0.04	0.171	0.155	0.096
0.06	0.246	0.222	0.132
0.08	0.322	0.290	0.168
0.10	0.398	0.358	0.206
0.11	0.441	0.396	0.224
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	MGS1R50515	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 4.5V - - □ - - Input Volt. 5V - - ○ - - Input Volt. 9V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.13</td><td>0.13</td><td>0.14</td></tr> <tr><td>0.02</td><td>0.45</td><td>0.46</td><td>0.56</td></tr> <tr><td>0.04</td><td>0.78</td><td>0.79</td><td>0.87</td></tr> <tr><td>0.06</td><td>1.12</td><td>1.12</td><td>1.19</td></tr> <tr><td>0.08</td><td>1.46</td><td>1.46</td><td>1.53</td></tr> <tr><td>0.10</td><td>1.81</td><td>1.81</td><td>1.86</td></tr> <tr><td>0.11</td><td>1.99</td><td>1.98</td><td>2.02</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	0.13	0.13	0.14	0.02	0.45	0.46	0.56	0.04	0.78	0.79	0.87	0.06	1.12	1.12	1.19	0.08	1.46	1.46	1.53	0.10	1.81	1.81	1.86	0.11	1.99	1.98	2.02	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.00	0.13	0.13	0.14																																																			
0.02	0.45	0.46	0.56																																																			
0.04	0.78	0.79	0.87																																																			
0.06	1.12	1.12	1.19																																																			
0.08	1.46	1.46	1.53																																																			
0.10	1.81	1.81	1.86																																																			
0.11	1.99	1.98	2.02																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	MGS1R50515																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1.Graph																																		
<p>The graph plots Efficiency [%] on the y-axis (50 to 90) against Input Voltage [V] on the x-axis (3 to 11). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a general downward trend as input voltage increases. Vertical dashed lines are drawn at approximately 4.4V, 5.0V, 7.0V, 9.0V, and 10.0V to indicate the rated input voltage range for each load level.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>4.4</td><td>80.4</td><td>84.4</td></tr> <tr><td>4.5</td><td>80.3</td><td>84.4</td></tr> <tr><td>4.8</td><td>80.2</td><td>84.4</td></tr> <tr><td>5.0</td><td>80.1</td><td>84.3</td></tr> <tr><td>7.0</td><td>77.1</td><td>83.8</td></tr> <tr><td>9.0</td><td>73.4</td><td>81.9</td></tr> <tr><td>10.0</td><td>70.6</td><td>80.9</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	4.4	80.4	84.4	4.5	80.3	84.4	4.8	80.2	84.4	5.0	80.1	84.3	7.0	77.1	83.8	9.0	73.4	81.9	10.0	70.6	80.9								
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																
4.4	80.4	84.4																																
4.5	80.3	84.4																																
4.8	80.2	84.4																																
5.0	80.1	84.3																																
7.0	77.1	83.8																																
9.0	73.4	81.9																																
10.0	70.6	80.9																																
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.4</td><td>80.4</td><td>84.4</td></tr> <tr><td>4.5</td><td>80.3</td><td>84.4</td></tr> <tr><td>4.8</td><td>80.2</td><td>84.4</td></tr> <tr><td>5.0</td><td>80.1</td><td>84.3</td></tr> <tr><td>7.0</td><td>77.1</td><td>83.8</td></tr> <tr><td>9.0</td><td>73.4</td><td>81.9</td></tr> <tr><td>10.0</td><td>70.6</td><td>80.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.4	80.4	84.4	4.5	80.3	84.4	4.8	80.2	84.4	5.0	80.1	84.3	7.0	77.1	83.8	9.0	73.4	81.9	10.0	70.6	80.9	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
4.4	80.4	84.4																																
4.5	80.3	84.4																																
4.8	80.2	84.4																																
5.0	80.1	84.3																																
7.0	77.1	83.8																																
9.0	73.4	81.9																																
10.0	70.6	80.9																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	MGS1R50515	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>Graph showing Efficiency (%) vs Load Current (A) for MGS1R50515 at 25°C. The graph plots Efficiency [%] on the Y-axis (50 to 90) against Load Current [A] on the X-axis (0.00 to 0.12). Three curves are shown for different input voltages: 4.5V (solid line with open triangle markers), 5V (dashed line with open square markers), and 9V (dash-dot line with open circle markers). A slanted line indicates the rated load current range.</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [4.5V] [%]</th> <th>Efficiency [5V] [%]</th> <th>Efficiency [9V] [%]</th> </tr> </thead> <tbody> <tr><td>0.02</td><td>66.9</td><td>-</td><td>-</td></tr> <tr><td>0.03</td><td>77.8</td><td>67.0</td><td>-</td></tr> <tr><td>0.04</td><td>81.4</td><td>77.2</td><td>69.6</td></tr> <tr><td>0.06</td><td>82.9</td><td>81.1</td><td>76.4</td></tr> <tr><td>0.08</td><td>84.1</td><td>84.4</td><td>81.9</td></tr> <tr><td>0.10</td><td>84.2</td><td>84.5</td><td>82.4</td></tr> <tr><td>0.11</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>0.12</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>			Load Current [A]	Efficiency [4.5V] [%]	Efficiency [5V] [%]	Efficiency [9V] [%]	0.02	66.9	-	-	0.03	77.8	67.0	-	0.04	81.4	77.2	69.6	0.06	82.9	81.1	76.4	0.08	84.1	84.4	81.9	0.10	84.2	84.5	82.4	0.11	--	--	--	0.12	--	--	--															
Load Current [A]	Efficiency [4.5V] [%]	Efficiency [5V] [%]	Efficiency [9V] [%]																																																			
0.02	66.9	-	-																																																			
0.03	77.8	67.0	-																																																			
0.04	81.4	77.2	69.6																																																			
0.06	82.9	81.1	76.4																																																			
0.08	84.1	84.4	81.9																																																			
0.10	84.2	84.5	82.4																																																			
0.11	--	--	--																																																			
0.12	--	--	--																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.02</td><td>66.9</td><td>67.0</td><td>54.5</td></tr> <tr><td>0.04</td><td>77.8</td><td>77.2</td><td>69.6</td></tr> <tr><td>0.06</td><td>81.4</td><td>81.1</td><td>76.4</td></tr> <tr><td>0.08</td><td>82.9</td><td>83.5</td><td>79.4</td></tr> <tr><td>0.10</td><td>84.1</td><td>84.4</td><td>81.9</td></tr> <tr><td>0.11</td><td>84.2</td><td>84.5</td><td>82.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.00	-	-	-	0.02	66.9	67.0	54.5	0.04	77.8	77.2	69.6	0.06	81.4	81.1	76.4	0.08	82.9	83.5	79.4	0.10	84.1	84.4	81.9	0.11	84.2	84.5	82.4	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																			
0.00	-	-	-																																																			
0.02	66.9	67.0	54.5																																																			
0.04	77.8	77.2	69.6																																																			
0.06	81.4	81.1	76.4																																																			
0.08	82.9	83.5	79.4																																																			
0.10	84.1	84.4	81.9																																																			
0.11	84.2	84.5	82.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL


Model MGS1R50515

Item Line Regulation

Object +15V0.1A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.4	15.042	15.040
4.5	15.042	15.040
4.8	15.042	15.040
5.0	15.042	15.040
7.0	15.042	15.040
9.0	15.042	15.039
10.0	15.042	15.039
--	-	-
--	-	-


Note: Slanted line shows the range of the rated input voltage.

COSEL

Model MGS1R50515

Item Load Regulation

Object +15V0.1A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values


Load Current [A]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.00	15.048	15.048	15.049
0.02	15.046	15.046	15.045
0.04	15.044	15.044	15.043
0.06	15.043	15.043	15.042
0.08	15.041	15.041	15.040
0.10	15.040	15.040	15.039
0.11	15.039	15.039	15.038
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	MGS1R50515	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.1A		

Input Volt. 5 V
Cycle 1000 ms



Min.Load (0A)↔
Load 100% (0.1A)

100 mV/div

4 ms/div

4 ms/div

Min.Load (0A)↔
Load 50% (0.05A)

100 mV/div

4 ms/div

4 ms/div

Load 50% (0.05A)↔
Load 100% (0.1A)

100 mV/div

4 ms/div

4 ms/div

COSEL

Model	MGS1R50515																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V0.1A																																							
1.Graph																																								
<p>—△— Input Volt. 4.5V ---○--- Input Volt. 9V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>20</td></tr> <tr><td>0.02</td><td>15</td><td>20</td></tr> <tr><td>0.04</td><td>20</td><td>20</td></tr> <tr><td>0.06</td><td>40</td><td>30</td></tr> <tr><td>0.08</td><td>50</td><td>35</td></tr> <tr><td>0.10</td><td>65</td><td>50</td></tr> <tr><td>0.11</td><td>75</td><td>55</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.00	5	20	0.02	15	20	0.04	20	20	0.06	40	30	0.08	50	35	0.10	65	50	0.11	75	55	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.00	5	20																																						
0.02	15	20																																						
0.04	20	20																																						
0.06	40	30																																						
0.08	50	35																																						
0.10	65	50																																						
0.11	75	55																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	MGS1R50515																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+15V0.1A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>25</td></tr> <tr><td>0.02</td><td>20</td><td>25</td></tr> <tr><td>0.04</td><td>25</td><td>25</td></tr> <tr><td>0.06</td><td>45</td><td>35</td></tr> <tr><td>0.08</td><td>55</td><td>40</td></tr> <tr><td>0.10</td><td>70</td><td>55</td></tr> <tr><td>0.11</td><td>80</td><td>60</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.00	10	25	0.02	20	25	0.04	25	25	0.06	45	35	0.08	55	40	0.10	70	55	0.11	80	60	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.00	10	25																																						
0.02	20	25																																						
0.04	25	25																																						
0.06	45	35																																						
0.08	55	40																																						
0.10	70	55																																						
0.11	80	60																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								


COSEL

Model MGS1R50515

Item Ripple Voltage (by Ambient Temp.)

Object +15V0.1A

1.Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	50	80
-40	45	75
-20	40	70
0	25	60
25	25	60
75	30	60
85	30	60
90	30	60
--	-	-
--	-	-
--	-	-

COSEL


Model MGS1R50515

Item Ambient Temperature Drift

Object +15V0.1A

1.Graph

—△— Input Volt. 4.5V
 - - -□--- Input Volt. 5V
 - - ○ - - Input Volt. 9V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
-60	14.920	14.921	14.921
-40	14.948	14.949	14.948
-20	14.983	14.984	14.983
0	15.010	15.010	15.010
25	15.040	15.040	15.039
75	15.054	15.054	15.054
85	15.056	15.056	15.056
90	15.057	15.057	15.057
--	-	-	-
--	-	-	-
--	-	-	-



Model	MGS1R50515	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V0.1A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 4.5 - 9V

Load Current : 0 - 0.1A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	85	9	0	15.068	± 60	± 0.4
Minimum Voltage	-40	4.5	0.1	14.948		

COSEL


Model MGS1R50515

Item Time Lapse Drift

Object +15V0.1A

Temperature 25°C
Testing Circuitry Figure A

1.Graph

Input Volt. 5V
Load 100%

2.Values

Time since start [H]	Output Voltage [V]
0.0	15.036
0.5	15.039
1.0	15.038
2.0	15.038
3.0	15.038
4.0	15.038
5.0	15.038
6.0	15.037
7.0	15.037
8.0	15.037

COSEL


Model MGS1R50515

Item Rise and Fall Time

Object +15V0.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.7	0.6	1.3	0.3	5.8	
100 %		0.7	0.7	1.4	0.2	2.8	




COSEL

Model MGS1R50515

Item Minimum Input Voltage
for Regulated Output Voltage

Object +15V0.1A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.7	3.7
-40	3.6	3.7
-20	3.6	3.6
0	3.6	3.6
25	3.6	3.6
75	3.5	3.6
85	3.5	3.6
90	3.5	3.6
--	-	-
--	-	-
--	-	-


COSEL

Model MGS1R50515

Item Overcurrent Protection

Object +15V0.1A

1.Graph



Note: Slanted line shows the range of the rated load current.


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
15.0	0.10	0.10	0.10
14.3	0.14	0.14	0.14
13.5	0.14	0.14	0.14
12.0	0.15	0.15	0.15
10.5	0.16	0.16	0.16
9.0	0.17	0.17	0.17
7.5	0.18	0.18	0.18
6.0	0.20	0.19	0.19
4.5	0.21	0.21	0.20
3.0	0.23	0.22	0.21
1.5	0.25	0.24	0.22
0.0	0.24	0.23	0.20

COSEL

Model	MGS1R50515
Item	Switching Frequency (by Load Current)
Object	+15V0.1A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Frequency [kHz]		
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]
0.00	980	1000	1150
0.02	658	689	830
0.04	491	522	670
0.06	389	420	560
0.08	329	353	482
0.10	279	303	422
0.11	261	288	410
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

When load current is low, MG operates intermittently, so switching frequency would not become constant.





Figure B (Ripple and Ripple noise Characteristic)