



TEST DATA OF MGS1R54812

Regulated DC Power Supply
August 9, 2016

Approved by : Takayuki Fukuda _____
Takayuki Fukuda Design Manager

Prepared by : Shohei Mukaide _____
Shohei Mukaide Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Current)	2
3.Input Power (by Load Current)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Current)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	9
10.Ripple-Noise	10
11.Ripple Voltage (by Ambient Temperature)	11
12.Ambient Temperature Drift	12
13.Output Voltage Accuracy	13
14.Time Lapse Drift	14
15.Rise and Fall Time	15
16.Minimum Input Voltage for Regulated Output Voltage	16
17.Overcurrent Protection	17
18.Switching Frequency (by Load Current)	18
19.Figure of Testing Circuitry	19

(Final Page 19)

COSEL


Model MGS1R54812

Item Input Current (by Input Voltage)

Object _____

1.Graph

—△— Load 100%
 - - -□--- Load 50%
 - - -○--- Load 0%



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
24.0	0.003	0.003	0.003
30.0	0.003	0.003	0.003
33.0	0.003	0.003	0.003
33.2	0.003	0.003	0.003
33.4	0.004	0.030	0.055
33.6	0.004	0.030	0.055
33.8	0.004	0.030	0.055
36.0	0.004	0.028	0.052
48.0	0.004	0.021	0.039
60.0	0.003	0.018	0.032
70.0	0.003	0.016	0.028
76.0	0.003	0.015	0.026
80.0	0.002	0.014	0.025
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGS1R54812																																																					
Item	Input Current (by Load Current)	Temperature	25°C																																																			
Object		Testing Circuitry	Figure A																																																			
1.Graph	<p>—△— Input Volt. 36V - -□--- Input Volt. 48V - ·○--- Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Current [A] (36V)</th> <th>Input Current [A] (48V)</th> <th>Input Current [A] (76V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.004</td><td>0.004</td><td>0.003</td></tr> <tr><td>0.026</td><td>0.013</td><td>0.011</td><td>0.008</td></tr> <tr><td>0.052</td><td>0.023</td><td>0.018</td><td>0.012</td></tr> <tr><td>0.078</td><td>0.032</td><td>0.025</td><td>0.017</td></tr> <tr><td>0.104</td><td>0.042</td><td>0.032</td><td>0.021</td></tr> <tr><td>0.130</td><td>0.052</td><td>0.039</td><td>0.026</td></tr> <tr><td>0.143</td><td>0.057</td><td>0.043</td><td>0.028</td></tr> </tbody> </table>	Load Current [A]	Input Current [A] (36V)	Input Current [A] (48V)	Input Current [A] (76V)	0.00	0.004	0.004	0.003	0.026	0.013	0.011	0.008	0.052	0.023	0.018	0.012	0.078	0.032	0.025	0.017	0.104	0.042	0.032	0.021	0.130	0.052	0.039	0.026	0.143	0.057	0.043	0.028																					
Load Current [A]	Input Current [A] (36V)	Input Current [A] (48V)	Input Current [A] (76V)																																																			
0.00	0.004	0.004	0.003																																																			
0.026	0.013	0.011	0.008																																																			
0.052	0.023	0.018	0.012																																																			
0.078	0.032	0.025	0.017																																																			
0.104	0.042	0.032	0.021																																																			
0.130	0.052	0.039	0.026																																																			
0.143	0.057	0.043	0.028																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.004</td><td>0.004</td><td>0.003</td></tr> <tr><td>0.026</td><td>0.013</td><td>0.011</td><td>0.008</td></tr> <tr><td>0.052</td><td>0.023</td><td>0.018</td><td>0.012</td></tr> <tr><td>0.078</td><td>0.032</td><td>0.025</td><td>0.017</td></tr> <tr><td>0.104</td><td>0.042</td><td>0.032</td><td>0.021</td></tr> <tr><td>0.130</td><td>0.052</td><td>0.039</td><td>0.026</td></tr> <tr><td>0.143</td><td>0.057</td><td>0.043</td><td>0.028</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	0.004	0.004	0.003	0.026	0.013	0.011	0.008	0.052	0.023	0.018	0.012	0.078	0.032	0.025	0.017	0.104	0.042	0.032	0.021	0.130	0.052	0.039	0.026	0.143	0.057	0.043	0.028	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	0.004	0.004	0.003																																																			
0.026	0.013	0.011	0.008																																																			
0.052	0.023	0.018	0.012																																																			
0.078	0.032	0.025	0.017																																																			
0.104	0.042	0.032	0.021																																																			
0.130	0.052	0.039	0.026																																																			
0.143	0.057	0.043	0.028																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL


Model	MGS1R54812																																																					
Item	Input Power (by Load Current)	Temperature	25°C																																																			
Object		Testing Circuitry	Figure A																																																			
1.Graph	—△— Input Volt. 36V - - -□- - Input Volt. 48V - · -○- - Input Volt. 76V	2.Values																																																				
<p>The graph shows a linear increase of input power with load current for all three input voltages. The 36V curve starts at approximately (0.00, 0.15) and ends at (0.14, 2.0). The 48V curve starts at approximately (0.00, 0.17) and ends at (0.14, 1.8). The 76V curve starts at approximately (0.00, 0.19) and ends at (0.14, 1.6). A slanted line is drawn through the origin, representing the rated load current range.</p>																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>0.15</td><td>0.17</td><td>0.19</td></tr> <tr><td>0.026</td><td>0.49</td><td>0.51</td><td>0.60</td></tr> <tr><td>0.052</td><td>0.83</td><td>0.85</td><td>0.94</td></tr> <tr><td>0.078</td><td>1.17</td><td>1.20</td><td>1.27</td></tr> <tr><td>0.104</td><td>1.51</td><td>1.54</td><td>1.63</td></tr> <tr><td>0.130</td><td>1.87</td><td>1.88</td><td>1.97</td></tr> <tr><td>0.143</td><td>2.04</td><td>2.06</td><td>2.14</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	0.15	0.17	0.19	0.026	0.49	0.51	0.60	0.052	0.83	0.85	0.94	0.078	1.17	1.20	1.27	0.104	1.51	1.54	1.63	0.130	1.87	1.88	1.97	0.143	2.04	2.06	2.14	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	0.15	0.17	0.19																																																			
0.026	0.49	0.51	0.60																																																			
0.052	0.83	0.85	0.94																																																			
0.078	1.17	1.20	1.27																																																			
0.104	1.51	1.54	1.63																																																			
0.130	1.87	1.88	1.97																																																			
0.143	2.04	2.06	2.14																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	MGS1R54812																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1.Graph																																		
		2.Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>34</td><td>78.6</td><td>83.6</td> </tr> <tr> <td>36</td><td>78.0</td><td>83.8</td> </tr> <tr> <td>40</td><td>77.2</td><td>83.2</td> </tr> <tr> <td>48</td><td>76.2</td><td>82.8</td> </tr> <tr> <td>55</td><td>74.7</td><td>82.2</td> </tr> <tr> <td>60</td><td>74.1</td><td>81.8</td> </tr> <tr> <td>70</td><td>72.0</td><td>80.0</td> </tr> <tr> <td>76</td><td>69.6</td><td>79.3</td> </tr> <tr> <td>80</td><td>69.0</td><td>78.7</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	34	78.6	83.6	36	78.0	83.8	40	77.2	83.2	48	76.2	82.8	55	74.7	82.2	60	74.1	81.8	70	72.0	80.0	76	69.6	79.3	80	69.0	78.7
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
34	78.6	83.6																																
36	78.0	83.8																																
40	77.2	83.2																																
48	76.2	82.8																																
55	74.7	82.2																																
60	74.1	81.8																																
70	72.0	80.0																																
76	69.6	79.3																																
80	69.0	78.7																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	MGS1R54812
Item	Efficiency (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Efficiency [%]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.000	-	-	-
0.026	64.7	62.0	52.6
0.052	75.1	73.1	66.3
0.078	80.0	78.0	73.5
0.104	82.4	80.8	76.8
0.130	83.8	82.8	79.3
0.143	84.0	83.2	80.3
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL




Model	MGS1R54812																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+12V0.13A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>34</td><td>11.971</td><td>11.969</td></tr> <tr><td>36</td><td>11.971</td><td>11.969</td></tr> <tr><td>40</td><td>11.971</td><td>11.969</td></tr> <tr><td>48</td><td>11.971</td><td>11.969</td></tr> <tr><td>55</td><td>11.971</td><td>11.969</td></tr> <tr><td>60</td><td>11.971</td><td>11.969</td></tr> <tr><td>70</td><td>11.971</td><td>11.969</td></tr> <tr><td>76</td><td>11.971</td><td>11.969</td></tr> <tr><td>80</td><td>11.971</td><td>11.969</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	34	11.971	11.969	36	11.971	11.969	40	11.971	11.969	48	11.971	11.969	55	11.971	11.969	60	11.971	11.969	70	11.971	11.969	76	11.971	11.969	80	11.971	11.969
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
34	11.971	11.969																																
36	11.971	11.969																																
40	11.971	11.969																																
48	11.971	11.969																																
55	11.971	11.969																																
60	11.971	11.969																																
70	11.971	11.969																																
76	11.971	11.969																																
80	11.971	11.969																																

COSEL

Model	MGS1R54812	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V0.13A																																																					
1.Graph		2.Values																																																				
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 36V Input Volt. 48V Input Volt. 76V 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>11.974</td><td>11.974</td><td>11.975</td></tr> <tr><td>0.026</td><td>11.973</td><td>11.973</td><td>11.973</td></tr> <tr><td>0.052</td><td>11.972</td><td>11.972</td><td>11.972</td></tr> <tr><td>0.078</td><td>11.971</td><td>11.971</td><td>11.971</td></tr> <tr><td>0.104</td><td>11.970</td><td>11.970</td><td>11.970</td></tr> <tr><td>0.130</td><td>11.969</td><td>11.969</td><td>11.969</td></tr> <tr><td>0.143</td><td>11.968</td><td>11.969</td><td>11.968</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	11.974	11.974	11.975	0.026	11.973	11.973	11.973	0.052	11.972	11.972	11.972	0.078	11.971	11.971	11.971	0.104	11.970	11.970	11.970	0.130	11.969	11.969	11.969	0.143	11.968	11.969	11.968	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.000	11.974	11.974	11.975																																																			
0.026	11.973	11.973	11.973																																																			
0.052	11.972	11.972	11.972																																																			
0.078	11.971	11.971	11.971																																																			
0.104	11.970	11.970	11.970																																																			
0.130	11.969	11.969	11.969																																																			
0.143	11.968	11.969	11.968																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	MGS1R54812
Item	Dynamic Load Response
Object	+12V0.13A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 48 V
Cycle 100 ms

COSEL

Model	MGS1R54812																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure B																																						
Object	+12V0.13A																																							
1.Graph																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td><td>10</td><td>20</td></tr> <tr> <td>0.026</td><td>20</td><td>20</td></tr> <tr> <td>0.052</td><td>35</td><td>35</td></tr> <tr> <td>0.078</td><td>55</td><td>40</td></tr> <tr> <td>0.104</td><td>65</td><td>50</td></tr> <tr> <td>0.130</td><td>80</td><td>60</td></tr> <tr> <td>0.143</td><td>95</td><td>70</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.000	10	20	0.026	20	20	0.052	35	35	0.078	55	40	0.104	65	50	0.130	80	60	0.143	95	70	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.000	10	20																																						
0.026	20	20																																						
0.052	35	35																																						
0.078	55	40																																						
0.104	65	50																																						
0.130	80	60																																						
0.143	95	70																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								

COSEL


Model	MGS1R54812																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure B																																						
Object	+12V0.13A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0.00 to 0.15 A. Two curves are plotted: one for 36V (solid line with open triangle markers) and one for 76V (dashed line with open circle markers). Both curves show an increase in ripple voltage as load current increases, with the 76V curve generally higher than the 36V curve. A slanted line indicates the rated load current range.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>10</td> <td>20</td> </tr> <tr> <td>0.026</td> <td>25</td> <td>25</td> </tr> <tr> <td>0.052</td> <td>35</td> <td>35</td> </tr> <tr> <td>0.078</td> <td>55</td> <td>45</td> </tr> <tr> <td>0.104</td> <td>65</td> <td>55</td> </tr> <tr> <td>0.130</td> <td>85</td> <td>65</td> </tr> <tr> <td>0.143</td> <td>100</td> <td>75</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.000	10	20	0.026	25	25	0.052	35	35	0.078	55	45	0.104	65	55	0.130	85	65	0.143	100	75	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.000	10	20																																						
0.026	25	25																																						
0.052	35	35																																						
0.078	55	45																																						
0.104	65	55																																						
0.130	85	65																																						
0.143	100	75																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>																																								

COSEL

Model	MGS1R54812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.13A

Testing Circuitry Figure B

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	45	80
-40	40	75
-20	40	75
0	40	70
25	35	70
75	35	70
85	35	70
90	35	70
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL


Model MGS1R54812

Item Ambient Temperature Drift

Object +12V0.13A

1.Graph

—△— Input Volt. 36V
 - - -□--- Input Volt. 48V
 - ·○--- Input Volt. 76V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	11.899	11.900	11.901
-40	11.920	11.920	11.921
-20	11.940	11.941	11.941
0	11.954	11.955	11.954
25	11.969	11.969	11.969
75	11.967	11.968	11.967
85	11.966	11.966	11.966
90	11.965	11.965	11.965
--	-	-	-
--	-	-	-
--	-	-	-



Model	MGS1R54812	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V0.13A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 36 - 76V

Load Current : 0 - 0.13A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	70	76	0	11.976	± 28	± 0.2
Minimum Voltage	-40	36	0.13	11.920		

COSEL

Model	MGS1R54812	Temperature	25°C
Item	Time Lapse Drift	Testing Circuitry	Figure A
Object	+12V0.13A		

1.Graph



Input Volt. 48V
Load 100%


2.Values

Time since start [H]	Output Voltage [V]
0.0	11.971
0.5	11.972
1.0	11.972
2.0	11.972
3.0	11.972
4.0	11.972
5.0	11.972
6.0	11.972
7.0	11.972
8.0	11.972

COSEL


Model	MGS1R54812	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.13A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		2.5	0.4	2.9	0.1	3.8
100 %		2.5	0.5	3.0	0.1	1.8




COSEL

Model	MGS1R54812
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.13A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	30.9	30.9
-40	30.7	30.9
-20	30.8	30.8
0	30.4	30.8
25	30.2	30.6
75	30.0	30.1
85	29.8	30.1
90	29.7	30.1
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.


COSEL

Model MGS1R54812

Item Overcurrent Protection

Object +12V0.13A

1. Graph



Note: Slanted line shows the range of the rated load current.


 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
12.0	0.13	0.13	0.13
11.4	0.22	0.24	0.23
10.8	0.23	0.24	0.24
9.6	0.25	0.26	0.25
8.4	0.27	0.28	0.27
7.2	0.29	0.30	0.29
6.0	0.31	0.32	0.31
4.8	0.34	0.35	0.33
3.6	0.37	0.38	0.35
2.4	0.40	0.41	0.37
1.2	0.43	0.43	0.39
0.0	0.57	0.56	0.56

COSEL

Model	MGS1R54812
Item	Switching Frequency (by Load Current)
Object	+12V0.13A


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Current [A]	Frequency [kHz]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
0.000	465	497	516
0.026	388	428	471
0.052	334	375	421
0.078	292	331	380
0.104	259	297	345
0.130	232	270	317
0.143	222	258	305
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

-When load current is low, MG operates intermittently, so switching frequency would not become constant.

