

# TEST DATA OF MGS304815

Regulated DC Power Supply  
December 7, 2010

Approved by : Kazunari Asano  
Kazunari Asano Design Manager

Prepared by : Sho Saito  
Sho Saito Design Engineer


**COSEL CO.,LTD.**

## CONTENTS

1. Input Current (by Input Voltage) · · · · ·	1
2. Input Current (by Load Current) · · · · ·	2
3. Input Power (by Load Current) · · · · ·	3
4. Efficiency (by Input Voltage) · · · · ·	4
5. Efficiency (by Load Current) · · · · ·	5
6. Line Regulation · · · · ·	6
7. Load Regulation · · · · ·	7
8. Dynamic Load Response · · · · ·	8
9. Ripple Voltage (by Load Current) · · · · ·	9
10. Ripple-Noise · · · · ·	10
11. Ripple Voltage (by Ambient Temperature) · · · · ·	11
12. Ambient Temperature Drift · · · · ·	12
13. Output Voltage Accuracy · · · · ·	13
14. Time Lapse Drift · · · · ·	14
15. Rise and Fall Time · · · · ·	15
16. Minimum Input Voltage for Regulated Output Voltage · · · · ·	16
17. Overcurrent Protection · · · · ·	17
18. Overvoltage Protection · · · · ·	18
19. Figure of Testing Circuitry · · · · ·	19

(Final Page 19)


Model	MGS304815	Temperature Testing Circuitry 25°C Figure A																																																																										
Item	Input Current (by Input Voltage)																																																																											
Object	_____																																																																											
1. Graph		2. Values																																																																										
<p>—△— Load 100%</p> <p>- - -□- - Load 50%</p> <p>- - ○- - Load 0%</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Load 0% [A]</th> <th>Load 50% [A]</th> <th>Load 100% [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>8.0</td><td>0.002</td><td>0.000</td><td>0.002</td></tr> <tr><td>16.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>24.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>28.0</td><td>0.002</td><td>0.002</td><td>0.002</td></tr> <tr><td>32.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr> <tr><td>32.8</td><td>0.034</td><td>0.513</td><td>1.015</td></tr> <tr><td>34.0</td><td>0.031</td><td>0.492</td><td>0.974</td></tr> <tr><td>36.0</td><td>0.028</td><td>0.461</td><td>0.914</td></tr> <tr><td>40.0</td><td>0.025</td><td>0.414</td><td>0.821</td></tr> <tr><td>48.0</td><td>0.025</td><td>0.348</td><td>0.684</td></tr> <tr><td>60.0</td><td>0.025</td><td>0.284</td><td>0.551</td></tr> <tr><td>70.0</td><td>0.025</td><td>0.248</td><td>0.477</td></tr> <tr><td>76.0</td><td>0.025</td><td>0.231</td><td>0.442</td></tr> <tr><td>80.0</td><td>0.025</td><td>0.221</td><td>0.422</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]	0	0.000	0.000	0.000	8.0	0.002	0.000	0.002	16.0	0.002	0.002	0.002	24.0	0.002	0.002	0.002	28.0	0.002	0.002	0.002	32.0	0.003	0.003	0.003	32.8	0.034	0.513	1.015	34.0	0.031	0.492	0.974	36.0	0.028	0.461	0.914	40.0	0.025	0.414	0.821	48.0	0.025	0.348	0.684	60.0	0.025	0.284	0.551	70.0	0.025	0.248	0.477	76.0	0.025	0.231	0.442	80.0	0.025	0.221	0.422	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Load 0% [A]	Load 50% [A]	Load 100% [A]																																																																									
0	0.000	0.000	0.000																																																																									
8.0	0.002	0.000	0.002																																																																									
16.0	0.002	0.002	0.002																																																																									
24.0	0.002	0.002	0.002																																																																									
28.0	0.002	0.002	0.002																																																																									
32.0	0.003	0.003	0.003																																																																									
32.8	0.034	0.513	1.015																																																																									
34.0	0.031	0.492	0.974																																																																									
36.0	0.028	0.461	0.914																																																																									
40.0	0.025	0.414	0.821																																																																									
48.0	0.025	0.348	0.684																																																																									
60.0	0.025	0.284	0.551																																																																									
70.0	0.025	0.248	0.477																																																																									
76.0	0.025	0.231	0.442																																																																									
80.0	0.025	0.221	0.422																																																																									
--	-	-	-																																																																									
--	-	-	-																																																																									
--	-	-	-																																																																									
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																																																												

Model	MGS304815																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 36V        - - -□- - Input Volt. 48V        - - ○ - - Input Volt. 76V</p> 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.027</td><td>0.025</td><td>0.025</td></tr> <tr><td>0.4</td><td>0.199</td><td>0.153</td><td>0.107</td></tr> <tr><td>0.8</td><td>0.374</td><td>0.283</td><td>0.189</td></tr> <tr><td>1.2</td><td>0.552</td><td>0.416</td><td>0.272</td></tr> <tr><td>1.6</td><td>0.735</td><td>0.550</td><td>0.357</td></tr> <tr><td>2.0</td><td>0.919</td><td>0.688</td><td>0.443</td></tr> <tr><td>2.2</td><td>1.015</td><td>0.758</td><td>0.486</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	0.027	0.025	0.025	0.4	0.199	0.153	0.107	0.8	0.374	0.283	0.189	1.2	0.552	0.416	0.272	1.6	0.735	0.550	0.357	2.0	0.919	0.688	0.443	2.2	1.015	0.758	0.486	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	0.027	0.025	0.025																																																			
0.4	0.199	0.153	0.107																																																			
0.8	0.374	0.283	0.189																																																			
1.2	0.552	0.416	0.272																																																			
1.6	0.735	0.550	0.357																																																			
2.0	0.919	0.688	0.443																																																			
2.2	1.015	0.758	0.486																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	MGS304815																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 36V        - - -□- - Input Volt. 48V        - - ○ - - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (36V)</th> <th>Input Power [W] (48V)</th> <th>Input Power [W] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.00</td><td>1.20</td><td>1.94</td></tr> <tr><td>0.4</td><td>7.15</td><td>7.35</td><td>8.13</td></tr> <tr><td>0.8</td><td>13.43</td><td>13.60</td><td>14.40</td></tr> <tr><td>1.2</td><td>19.85</td><td>19.93</td><td>20.73</td></tr> <tr><td>1.6</td><td>26.36</td><td>26.38</td><td>27.15</td></tr> <tr><td>2.0</td><td>33.02</td><td>32.93</td><td>33.65</td></tr> <tr><td>2.2</td><td>36.50</td><td>36.29</td><td>37.00</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)	0.0	1.00	1.20	1.94	0.4	7.15	7.35	8.13	0.8	13.43	13.60	14.40	1.2	19.85	19.93	20.73	1.6	26.36	26.38	27.15	2.0	33.02	32.93	33.65	2.2	36.50	36.29	37.00																			
Load Current [A]	Input Power [W] (36V)	Input Power [W] (48V)	Input Power [W] (76V)																																																			
0.0	1.00	1.20	1.94																																																			
0.4	7.15	7.35	8.13																																																			
0.8	13.43	13.60	14.40																																																			
1.2	19.85	19.93	20.73																																																			
1.6	26.36	26.38	27.15																																																			
2.0	33.02	32.93	33.65																																																			
2.2	36.50	36.29	37.00																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>1.00</td><td>1.20</td><td>1.94</td></tr> <tr><td>0.4</td><td>7.15</td><td>7.35</td><td>8.13</td></tr> <tr><td>0.8</td><td>13.43</td><td>13.60</td><td>14.40</td></tr> <tr><td>1.2</td><td>19.85</td><td>19.93</td><td>20.73</td></tr> <tr><td>1.6</td><td>26.36</td><td>26.38</td><td>27.15</td></tr> <tr><td>2.0</td><td>33.02</td><td>32.93</td><td>33.65</td></tr> <tr><td>2.2</td><td>36.50</td><td>36.29</td><td>37.00</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	1.00	1.20	1.94	0.4	7.15	7.35	8.13	0.8	13.43	13.60	14.40	1.2	19.85	19.93	20.73	1.6	26.36	26.38	27.15	2.0	33.02	32.93	33.65	2.2	36.50	36.29	37.00	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	1.00	1.20	1.94																																																			
0.4	7.15	7.35	8.13																																																			
0.8	13.43	13.60	14.40																																																			
1.2	19.85	19.93	20.73																																																			
1.6	26.36	26.38	27.15																																																			
2.0	33.02	32.93	33.65																																																			
2.2	36.50	36.29	37.00																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	MGS304815	Temperature Testing Circuitry 25°C Figure A																															
Item	Efficiency (by Input Voltage)																																
Object	—																																
1.Graph		2.Values																															
<p>The graph plots Efficiency [%] on the y-axis (50 to 100) against Input Voltage [V] on the x-axis (20 to 80). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show a slight decrease in efficiency as input voltage increases. Two vertical hatched lines indicate the rated input voltage range between approximately 38V and 75V.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>35</td><td>90.5</td><td>91.0</td></tr> <tr><td>40</td><td>90.8</td><td>91.2</td></tr> <tr><td>45</td><td>90.5</td><td>91.0</td></tr> <tr><td>50</td><td>89.5</td><td>90.5</td></tr> <tr><td>60</td><td>88.5</td><td>89.5</td></tr> <tr><td>70</td><td>86.5</td><td>87.5</td></tr> <tr><td>80</td><td>85.5</td><td>86.5</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	35	90.5	91.0	40	90.8	91.2	45	90.5	91.0	50	89.5	90.5	60	88.5	89.5	70	86.5	87.5	80	85.5	86.5								
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																															
35	90.5	91.0																															
40	90.8	91.2																															
45	90.5	91.0																															
50	89.5	90.5																															
60	88.5	89.5																															
70	86.5	87.5																															
80	85.5	86.5																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>34</td><td>90.1</td><td>90.6</td></tr> <tr><td>36</td><td>91.0</td><td>91.2</td></tr> <tr><td>40</td><td>91.0</td><td>91.6</td></tr> <tr><td>48</td><td>90.0</td><td>91.5</td></tr> <tr><td>60</td><td>88.4</td><td>90.9</td></tr> <tr><td>76</td><td>86.0</td><td>89.6</td></tr> <tr><td>80</td><td>85.3</td><td>89.3</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	34	90.1	90.6	36	91.0	91.2	40	91.0	91.6	48	90.0	91.5	60	88.4	90.9	76	86.0	89.6	80	85.3	89.3	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																
	Load 50%	Load 100%																															
34	90.1	90.6																															
36	91.0	91.2																															
40	91.0	91.6																															
48	90.0	91.5																															
60	88.4	90.9																															
76	86.0	89.6																															
80	85.3	89.3																															
--	-	-																															
--	-	-																															


Note: Slanted line shows the range of the rated input voltage.

Model	MGS304815																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 36V        - - -□- - Input Volt. 48V        - - ○- - Input Volt. 76V</p> 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.4</td><td>84.3</td><td>82.0</td><td>74.1</td></tr> <tr><td>0.8</td><td>89.8</td><td>88.7</td><td>83.7</td></tr> <tr><td>1.2</td><td>91.2</td><td>90.8</td><td>87.3</td></tr> <tr><td>1.6</td><td>91.5</td><td>91.5</td><td>88.9</td></tr> <tr><td>2.0</td><td>91.3</td><td>91.6</td><td>89.6</td></tr> <tr><td>2.2</td><td>90.9</td><td>91.4</td><td>89.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	-	-	-	0.4	84.3	82.0	74.1	0.8	89.8	88.7	83.7	1.2	91.2	90.8	87.3	1.6	91.5	91.5	88.9	2.0	91.3	91.6	89.6	2.2	90.9	91.4	89.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0.0	-	-	-																																																			
0.4	84.3	82.0	74.1																																																			
0.8	89.8	88.7	83.7																																																			
1.2	91.2	90.8	87.3																																																			
1.6	91.5	91.5	88.9																																																			
2.0	91.3	91.6	89.6																																																			
2.2	90.9	91.4	89.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

Model	MGS304815
Item	Line Regulation
Object	+15V2A

Temperature 25°C  
Testing Circuitry Figure A

## 1.Graph




## 2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
34	15.089	15.088
36	15.089	15.088
40	15.089	15.088
48	15.089	15.088
60	15.088	15.087
76	15.088	15.087
80	15.088	15.087
--	-	-
--	-	-

Note: Slanted line shows the range of the rated input voltage.

Model	MGS304815	Temperature Testing Circuitry      25°C Figure A																																																		
Item	Load Regulation																																																			
Object	+15V2A																																																			
1.Graph	<p>—△— Input Volt. 36V      - - -□- - Input Volt. 48V      - - -○- - Input Volt. 76V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (36V)</th> <th>Output Voltage [V] (48V)</th> <th>Output Voltage [V] (76V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.094</td><td>15.093</td><td>15.092</td></tr> <tr><td>0.4</td><td>15.093</td><td>15.092</td><td>15.091</td></tr> <tr><td>0.8</td><td>15.092</td><td>15.091</td><td>15.090</td></tr> <tr><td>1.2</td><td>15.091</td><td>15.090</td><td>15.089</td></tr> <tr><td>1.6</td><td>15.090</td><td>15.089</td><td>15.088</td></tr> <tr><td>2.0</td><td>15.089</td><td>15.089</td><td>15.087</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)	0.0	15.094	15.093	15.092	0.4	15.093	15.092	15.091	0.8	15.092	15.091	15.090	1.2	15.091	15.090	15.089	1.6	15.090	15.089	15.088	2.0	15.089	15.089	15.087																							
Load Current [A]	Output Voltage [V] (36V)	Output Voltage [V] (48V)	Output Voltage [V] (76V)																																																	
0.0	15.094	15.093	15.092																																																	
0.4	15.093	15.092	15.091																																																	
0.8	15.092	15.091	15.090																																																	
1.2	15.091	15.090	15.089																																																	
1.6	15.090	15.089	15.088																																																	
2.0	15.089	15.089	15.087																																																	
2.Values																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 36[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 76[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.094</td><td>15.093</td><td>15.092</td></tr> <tr><td>0.4</td><td>15.093</td><td>15.092</td><td>15.091</td></tr> <tr><td>0.8</td><td>15.092</td><td>15.091</td><td>15.090</td></tr> <tr><td>1.2</td><td>15.091</td><td>15.090</td><td>15.089</td></tr> <tr><td>1.6</td><td>15.090</td><td>15.089</td><td>15.088</td></tr> <tr><td>2.0</td><td>15.089</td><td>15.089</td><td>15.087</td></tr> <tr><td>2.2</td><td>15.089</td><td>15.088</td><td>15.087</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.0	15.094	15.093	15.092	0.4	15.093	15.092	15.091	0.8	15.092	15.091	15.090	1.2	15.091	15.090	15.089	1.6	15.090	15.089	15.088	2.0	15.089	15.089	15.087	2.2	15.089	15.088	15.087	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																			
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																	
0.0	15.094	15.093	15.092																																																	
0.4	15.093	15.092	15.091																																																	
0.8	15.092	15.091	15.090																																																	
1.2	15.091	15.090	15.089																																																	
1.6	15.090	15.089	15.088																																																	
2.0	15.089	15.089	15.087																																																	
2.2	15.089	15.088	15.087																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Note: Slanted line shows the range of the rated load current.



**COSSEL**


Model	MGS304815	Temperature Testing Circuitry 25°C Figure B																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+15V2A																																							
1.Graph		2.Values																																						
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 120 mV, and the X-axis ranges from 0.0 to 2.0 A. Two curves are shown: a solid line for 36V and a dashed line for 76V. Both curves show a slight increase in ripple voltage as load current increases, with the 76V curve being higher than the 36V curve. A horizontal line at approximately 15 mV indicates the rated output voltage.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>29</td></tr> <tr><td>0.4</td><td>15</td><td>29</td></tr> <tr><td>0.8</td><td>15</td><td>29</td></tr> <tr><td>1.2</td><td>15</td><td>29</td></tr> <tr><td>1.6</td><td>15</td><td>29</td></tr> <tr><td>2.0</td><td>15</td><td>29</td></tr> <tr><td>2.2</td><td>15</td><td>29</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.0	15	29	0.4	15	29	0.8	15	29	1.2	15	29	1.6	15	29	2.0	15	29	2.2	15	29	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.0	15	29																																						
0.4	15	29																																						
0.8	15	29																																						
1.2	15	29																																						
1.6	15	29																																						
2.0	15	29																																						
2.2	15	29																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

Model	MGS304815	Temperature Testing Circuitry 25°C Figure B																																						
Item	Ripple-Noise																																							
Object	+15V2A																																							
1.Graph	<p>Input Volt. 36V</p> <p>Input Volt. 76V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>	2.Values																																						
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 36 [V]</th> <th>Input Volt. 76 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>40</td></tr> <tr><td>0.4</td><td>20</td><td>40</td></tr> <tr><td>0.8</td><td>20</td><td>40</td></tr> <tr><td>1.2</td><td>20</td><td>40</td></tr> <tr><td>1.6</td><td>20</td><td>40</td></tr> <tr><td>2.0</td><td>20</td><td>40</td></tr> <tr><td>2.2</td><td>20</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.0	20	40	0.4	20	40	0.8	20	40	1.2	20	40	1.6	20	40	2.0	20	40	2.2	20	40	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 36 [V]	Input Volt. 76 [V]																																						
0.0	20	40																																						
0.4	20	40																																						
0.8	20	40																																						
1.2	20	40																																						
1.6	20	40																																						
2.0	20	40																																						
2.2	20	40																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>Ripple Noise[mVp-p]</p>																																						
<p>Fig.Complex Ripple Noise Wave Form</p>																																								

# COSEL

Model	MGS304815
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V2A

## 1. Graph



Testing Circuitry Figure B


## 2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	35	35
-40	27	27
-20	25	25
0	24	24
25	23	23
60	21	21
65	21	21
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGS304815
Item	Ambient Temperature Drift
Object	+15V2A



Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
-60	14.966	14.965	14.965
-40	15.000	15.000	15.000
-20	15.030	15.029	15.029
0	15.054	15.054	15.053
25	15.089	15.089	15.088
60	15.098	15.098	15.098
65	15.103	15.103	15.102
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGS304815	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V2A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 36 - 76V

Load Current : 0 - 2A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	60	48	0	15.103	±52	±0.3
Minimum Voltage	-40	76	0	14.999		

**COSEL**

Model	MGS304815
Item	Time Lapse Drift
Object	+15V2A

Temperature 25°C  
Testing Circuitry Figure A

1.Graph



Input Volt. 48V  
Load 100%

2.Values


Time since start [H]	Output Voltage [V]
0.0	15.089
0.5	15.091
1.0	15.091
2.0	15.091
3.0	15.091
4.0	15.091
5.0	15.090
6.0	15.090
7.0	15.090
8.0	15.090

**COSEL**

Model	MGS304815
Item	Rise and Fall Time
Object	+15V2A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph



## 2. Values


Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.8	2.2	4.0	2.1	1.6
100 %		1.9	3.3	5.2	1.1	0.8



Model	MGS304815
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V2A

Testing Circuitry Figure A

## 1. Graph



## 2. Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	30.9	31.0
-40	30.9	31.0
-20	30.9	30.7
0	30.7	30.8
25	30.7	30.6
60	30.4	30.6
65	30.5	30.5
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Model	MGS304815		
Item	Overcurrent Protection		
Object	+15V2A		
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 36V</p> <p>Input Volt. 48V</p> <p>Input Volt. 76V</p>		
Note:	Slanted line shows the range of the rated load current.		
	Intermittent operation occurs when overcurrent protection is activated.		
Temperature	25°C		
Testing Circuitry	Figure A		
2.Values			
Output Voltage [V]	Load Current [A]		
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]
15.0	2.56	2.64	2.68
14.3	-	-	-
13.5	-	-	-
12.0	-	-	-
10.5	-	-	-
9.0	-	-	-
7.5	-	-	-
6.0	-	-	-
4.5	-	-	-
3.0	-	-	-
1.5	-	-	-
0.0	-	-	-

Model	MGS304815
Item	Oversupply Protection
Object	+15V2A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 48[V]	Input Volt. 76[V]
-60	20.35	20.36
-40	20.51	20.56
-20	20.77	20.80
0	21.01	21.08
25	21.40	21.45
60	21.92	21.97
65	22.00	22.05
--	-	-
--	-	-
--	-	-
--	-	-

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)