

# TEST DATA OF MGW100512

Regulated DC Power Supply  
November 4, 2016

Approved by : Takayuki Fukuda  
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi  
Takaaki Sekiguchi Design Engineer

**COSEL CO.,LTD.**

CONTENTS

1.Input Current (by Input Voltage) . . . . . 1

2.Input Ratio (by Load Ratio) . . . . . 2

3.Input Power (by Load Ratio) . . . . . 3

4.Efficiency (by Input Voltage) . . . . . 4

5.Efficiency (by Load Ratio) . . . . . 5

6.Line Regulation . . . . . 6

7.Load Regulation . . . . . 7

8.Dynamic Load Response . . . . . 8

9.Ripple Voltage (by Load Current) . . . . . 10

10.Ripple-Noise . . . . . 12

11.Ripple Voltage (by Ambient Temperature) . . . . . 14

12.Ambient Temperature Drift . . . . . 15

13.Output Voltage Accuracy . . . . . 16

14.Time Lapse Drift . . . . . 17

15.Rise and Fall Time . . . . . 18

16.Minimum Input Voltage for Regulated Output Voltage . . . . . 20

17.Overcurrent Protection . . . . . 21

18.Switching Frequency (by Load Current) . . . . . 22

19.Figure of Testing Circuitry . . . . . 23

(Final Page 23)



Model		MGW100512		Temperature	25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry	Figure A																																																																																
Object		_____																																																																																			
1.Graph			—△— Load 100% - - - □ - - Load 50% - · - ○ - · - Load 0%	2.Values																																																																																	
Input Current [A]				<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>3.0</td><td>0.004</td><td>0.001</td><td>0.000</td></tr> <tr><td>3.8</td><td>0.003</td><td>0.001</td><td>0.004</td></tr> <tr><td>3.9</td><td>0.002</td><td>0.002</td><td>0.003</td></tr> <tr><td>4.0</td><td>0.035</td><td>1.500</td><td>0.004</td></tr> <tr><td>4.1</td><td>0.033</td><td>1.459</td><td>2.990</td></tr> <tr><td>4.2</td><td>0.033</td><td>1.421</td><td>2.982</td></tr> <tr><td>4.4</td><td>0.031</td><td>1.352</td><td>2.825</td></tr> <tr><td>4.5</td><td>0.030</td><td>1.319</td><td>2.730</td></tr> <tr><td>5.0</td><td>0.026</td><td>1.178</td><td>2.482</td></tr> <tr><td>6.0</td><td>0.022</td><td>1.005</td><td>2.013</td></tr> <tr><td>7.0</td><td>0.019</td><td>0.854</td><td>1.728</td></tr> <tr><td>8.0</td><td>0.016</td><td>0.750</td><td>1.501</td></tr> <tr><td>9.0</td><td>0.015</td><td>0.673</td><td>1.333</td></tr> <tr><td>10.0</td><td>0.015</td><td>0.606</td><td>1.198</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	3.0	0.004	0.001	0.000	3.8	0.003	0.001	0.004	3.9	0.002	0.002	0.003	4.0	0.035	1.500	0.004	4.1	0.033	1.459	2.990	4.2	0.033	1.421	2.982	4.4	0.031	1.352	2.825	4.5	0.030	1.319	2.730	5.0	0.026	1.178	2.482	6.0	0.022	1.005	2.013	7.0	0.019	0.854	1.728	8.0	0.016	0.750	1.501	9.0	0.015	0.673	1.333	10.0	0.015	0.606	1.198	--	-	-	-	--	-	-	-	--	-	-	-
	Input Voltage [V]	Input Current [A]																																																																																			
		Load 0%	Load 50%	Load 100%																																																																																	
	0.0	0.000	0.000	0.000																																																																																	
	3.0	0.004	0.001	0.000																																																																																	
	3.8	0.003	0.001	0.004																																																																																	
	3.9	0.002	0.002	0.003																																																																																	
	4.0	0.035	1.500	0.004																																																																																	
	4.1	0.033	1.459	2.990																																																																																	
	4.2	0.033	1.421	2.982																																																																																	
	4.4	0.031	1.352	2.825																																																																																	
	4.5	0.030	1.319	2.730																																																																																	
	5.0	0.026	1.178	2.482																																																																																	
6.0	0.022	1.005	2.013																																																																																		
7.0	0.019	0.854	1.728																																																																																		
8.0	0.016	0.750	1.501																																																																																		
9.0	0.015	0.673	1.333																																																																																		
10.0	0.015	0.606	1.198																																																																																		
--	-	-	-																																																																																		
--	-	-	-																																																																																		
--	-	-	-																																																																																		
Note: Slanted line shows the range of the rated input voltage.																																																																																					



Model		MGW100512		Temperature 25°C																																																				
Item		Input Current (by Load Ratio)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 4.5V</p> <p>- - - □ - - Input Volt. 5V</p> <p>- · - ○ - · - Input Volt. 9V</p>		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.030</td><td>0.026</td><td>0.015</td></tr> <tr><td>20</td><td>0.558</td><td>0.502</td><td>0.300</td></tr> <tr><td>40</td><td>1.081</td><td>0.977</td><td>0.547</td></tr> <tr><td>60</td><td>1.617</td><td>1.434</td><td>0.803</td></tr> <tr><td>80</td><td>2.171</td><td>1.952</td><td>1.062</td></tr> <tr><td>100</td><td>2.730</td><td>2.482</td><td>1.333</td></tr> <tr><td>110</td><td>3.059</td><td>2.681</td><td>1.473</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Ratio [%]	Input Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.030	0.026	0.015	20	0.558	0.502	0.300	40	1.081	0.977	0.547	60	1.617	1.434	0.803	80	2.171	1.952	1.062	100	2.730	2.482	1.333	110	3.059	2.681	1.473	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Input Current [A]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0	0.030	0.026	0.015																																																					
20	0.558	0.502	0.300																																																					
40	1.081	0.977	0.547																																																					
60	1.617	1.434	0.803																																																					
80	2.171	1.952	1.062																																																					
100	2.730	2.482	1.333																																																					
110	3.059	2.681	1.473																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model		MGW100512		Temperature	25°C																																																			
Item		Input Power (by Load Ratio)		Testing Circuitry	Figure A																																																			
Object		_____																																																						
1.Graph			—△— Input Volt. 4.5V	2.Values																																																				
			- - -□- - - Input Volt. 5V																																																					
			- · - ○ - · - - Input Volt. 9V																																																					
<p>Input Power [W]</p> <p>Load Ratio [%]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.13</td><td>0.12</td><td>0.14</td></tr> <tr><td>20</td><td>2.46</td><td>2.47</td><td>2.68</td></tr> <tr><td>40</td><td>4.71</td><td>4.70</td><td>4.88</td></tr> <tr><td>60</td><td>7.06</td><td>7.04</td><td>7.12</td></tr> <tr><td>80</td><td>9.47</td><td>9.41</td><td>9.41</td></tr> <tr><td>100</td><td>11.97</td><td>11.90</td><td>11.75</td></tr> <tr><td>110</td><td>13.30</td><td>13.15</td><td>12.96</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ratio [%]	Input Power [W]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	0.13	0.12	0.14	20	2.46	2.47	2.68	40	4.71	4.70	4.88	60	7.06	7.04	7.12	80	9.47	9.41	9.41	100	11.97	11.90	11.75	110	13.30	13.15	12.96	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Input Power [W]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0	0.13	0.12	0.14																																																					
20	2.46	2.47	2.68																																																					
40	4.71	4.70	4.88																																																					
60	7.06	7.04	7.12																																																					
80	9.47	9.41	9.41																																																					
100	11.97	11.90	11.75																																																					
110	13.30	13.15	12.96																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model		MGW100512		Temperature	25°C																																
Item		Efficiency (by Input Voltage)		Testing Circuitry	Figure A																																
Object		_____																																			
1.Graph			2.Values																																		
<p>---□--- Load 50% —△— Load 100%</p> <p>Efficiency [%]</p> <p>Input Voltage [V]</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.4</td><td>86.3</td><td>84.1</td></tr> <tr><td>4.5</td><td>86.5</td><td>84.7</td></tr> <tr><td>4.8</td><td>86.6</td><td>84.9</td></tr> <tr><td>5.0</td><td>86.7</td><td>85.2</td></tr> <tr><td>7.0</td><td>85.9</td><td>86.2</td></tr> <tr><td>9.0</td><td>84.6</td><td>86.3</td></tr> <tr><td>10.0</td><td>84.1</td><td>86.1</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	4.4	86.3	84.1	4.5	86.5	84.7	4.8	86.6	84.9	5.0	86.7	85.2	7.0	85.9	86.2	9.0	84.6	86.3	10.0	84.1	86.1	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																				
	Load 50%	Load 100%																																			
4.4	86.3	84.1																																			
4.5	86.5	84.7																																			
4.8	86.6	84.9																																			
5.0	86.7	85.2																																			
7.0	85.9	86.2																																			
9.0	84.6	86.3																																			
10.0	84.1	86.1																																			
--	-	-																																			
--	-	-																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																					



Model		MGW100512		Temperature	25°C																																																			
Item		Efficiency (by Load Ratio)		Testing Circuitry	Figure A																																																			
Object		_____																																																						
1.Graph			—△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - · - ○ - · - - Input Volt. 9V	2.Values																																																				
			<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>82.5</td><td>82.4</td><td>75.4</td></tr> <tr><td>40</td><td>86.2</td><td>86.1</td><td>83.0</td></tr> <tr><td>60</td><td>86.1</td><td>86.5</td><td>85.4</td></tr> <tr><td>80</td><td>85.6</td><td>86.2</td><td>86.1</td></tr> <tr><td>100</td><td>84.7</td><td>85.2</td><td>86.3</td></tr> <tr><td>110</td><td>83.9</td><td>84.8</td><td>86.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ratio [%]	Efficiency [%]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0	-	-	-	20	82.5	82.4	75.4	40	86.2	86.1	83.0	60	86.1	86.5	85.4	80	85.6	86.2	86.1	100	84.7	85.2	86.3	110	83.9	84.8	86.0	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Efficiency [%]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0	-	-	-																																																					
20	82.5	82.4	75.4																																																					
40	86.2	86.1	83.0																																																					
60	86.1	86.5	85.4																																																					
80	85.6	86.2	86.1																																																					
100	84.7	85.2	86.3																																																					
110	83.9	84.8	86.0																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



<p>Model MGW100512</p> <p>Item Line Regulation</p> <p>Object +12V0.42A</p> <p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.4</td><td>12.143</td><td>12.059</td></tr> <tr><td>4.5</td><td>12.143</td><td>12.059</td></tr> <tr><td>4.8</td><td>12.142</td><td>12.059</td></tr> <tr><td>5.0</td><td>12.142</td><td>12.059</td></tr> <tr><td>7.0</td><td>12.138</td><td>12.060</td></tr> <tr><td>9.0</td><td>12.136</td><td>12.061</td></tr> <tr><td>10.0</td><td>12.136</td><td>12.061</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.4	12.143	12.059	4.5	12.143	12.059	4.8	12.142	12.059	5.0	12.142	12.059	7.0	12.138	12.060	9.0	12.136	12.061	10.0	12.136	12.061	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
4.4	12.143	12.059																																
4.5	12.143	12.059																																
4.8	12.142	12.059																																
5.0	12.142	12.059																																
7.0	12.138	12.060																																
9.0	12.136	12.061																																
10.0	12.136	12.061																																
--	-	-																																
--	-	-																																
<p>Object -12V0.42A</p> <p>1.Graph</p> <p>---□--- Load 50% —△— Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>4.4</td><td>-12.161</td><td>-12.071</td></tr> <tr><td>4.5</td><td>-12.160</td><td>-12.071</td></tr> <tr><td>4.8</td><td>-12.159</td><td>-12.071</td></tr> <tr><td>5.0</td><td>-12.158</td><td>-12.071</td></tr> <tr><td>7.0</td><td>-12.153</td><td>-12.070</td></tr> <tr><td>9.0</td><td>-12.151</td><td>-12.070</td></tr> <tr><td>10.0</td><td>-12.150</td><td>-12.070</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	4.4	-12.161	-12.071	4.5	-12.160	-12.071	4.8	-12.159	-12.071	5.0	-12.158	-12.071	7.0	-12.153	-12.070	9.0	-12.151	-12.070	10.0	-12.150	-12.070	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
4.4	-12.161	-12.071																																
4.5	-12.160	-12.071																																
4.8	-12.159	-12.071																																
5.0	-12.158	-12.071																																
7.0	-12.153	-12.070																																
9.0	-12.151	-12.070																																
10.0	-12.150	-12.070																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		




Model		MGW100512		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+12V0.42A																																																						
1.Graph		—△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - · - ○ - · - - Input Volt. 9V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.327</td><td>12.325</td><td>12.305</td></tr> <tr><td>0.084</td><td>12.212</td><td>12.211</td><td>12.200</td></tr> <tr><td>0.168</td><td>12.165</td><td>12.164</td><td>12.157</td></tr> <tr><td>0.252</td><td>12.127</td><td>12.126</td><td>12.122</td></tr> <tr><td>0.336</td><td>12.092</td><td>12.092</td><td>12.091</td></tr> <tr><td>0.420</td><td>12.059</td><td>12.059</td><td>12.061</td></tr> <tr><td>0.462</td><td>12.041</td><td>12.042</td><td>12.046</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	12.327	12.325	12.305	0.084	12.212	12.211	12.200	0.168	12.165	12.164	12.157	0.252	12.127	12.126	12.122	0.336	12.092	12.092	12.091	0.420	12.059	12.059	12.061	0.462	12.041	12.042	12.046	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	-12V: Rated Load Current	
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0.000	12.327	12.325	12.305																																																					
0.084	12.212	12.211	12.200																																																					
0.168	12.165	12.164	12.157																																																					
0.252	12.127	12.126	12.122																																																					
0.336	12.092	12.092	12.091																																																					
0.420	12.059	12.059	12.061																																																					
0.462	12.041	12.042	12.046																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Object		-12V0.42A																																																						
1.Graph		—△— Input Volt. 4.5V - - - □ - - - Input Volt. 5V - · - ○ - · - - Input Volt. 9V		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.387</td><td>-12.382</td><td>-12.353</td></tr> <tr><td>0.084</td><td>-12.234</td><td>-12.232</td><td>-12.219</td></tr> <tr><td>0.168</td><td>-12.181</td><td>-12.179</td><td>-12.171</td></tr> <tr><td>0.252</td><td>-12.141</td><td>-12.139</td><td>-12.133</td></tr> <tr><td>0.336</td><td>-12.105</td><td>-12.104</td><td>-12.101</td></tr> <tr><td>0.420</td><td>-12.071</td><td>-12.071</td><td>-12.070</td></tr> <tr><td>0.462</td><td>-12.054</td><td>-12.054</td><td>-12.055</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	-12.387	-12.382	-12.353	0.084	-12.234	-12.232	-12.219	0.168	-12.181	-12.179	-12.171	0.252	-12.141	-12.139	-12.133	0.336	-12.105	-12.104	-12.101	0.420	-12.071	-12.071	-12.070	0.462	-12.054	-12.054	-12.055	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-	+12V: Rated Load Current	
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0.000	-12.387	-12.382	-12.353																																																					
0.084	-12.234	-12.232	-12.219																																																					
0.168	-12.181	-12.179	-12.171																																																					
0.252	-12.141	-12.139	-12.133																																																					
0.336	-12.105	-12.104	-12.101																																																					
0.420	-12.071	-12.071	-12.070																																																					
0.462	-12.054	-12.054	-12.055																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								



Model	MGW100512	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.42A		


Input Volt. 5 V  
 -12V:rated load current.  
 Cycle 100 ms

t1,t2 = 100 μs



Min.Load (0A) ←→  
 Load 100% (0.42A)

200 mV/div




4 ms/div




4 ms/div

Min.Load (0A) ←→  
 Load 50% (0.21A)

200 mV/div




4 ms/div




4 ms/div

Load 50% (0.21A) ←→  
 Load 100% (0.42A)

200 mV/div



4 ms/div




4 ms/div



Model	MGW100512	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V0.42A		


Input Volt. 5 V  
 +12V:rated load current.  
 Cycle 100 ms

t1,t2 = 100 μs




Min.Load (0A) ←→  
 Load 100% (0.42A)

200 mV/div




4 ms/div




4 ms/div

Min.Load (0A) ←→  
 Load 50% (0.21A)

200 mV/div




4 ms/div




4 ms/div

Load 50% (0.21A) ←→  
 Load 100% (0.42A)

200 mV/div



4 ms/div



4 ms/div



<p>Model MGW100512</p> <p>Item Ripple Voltage (by Load Current)</p> <p>Object +12V0.42A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>                 —△— Input Volt. 4.5V                  - - ○ - - - Input Volt. 9V             </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.084</td><td>5</td><td>5</td></tr> <tr><td>0.168</td><td>5</td><td>5</td></tr> <tr><td>0.252</td><td>5</td><td>5</td></tr> <tr><td>0.336</td><td>5</td><td>5</td></tr> <tr><td>0.420</td><td>10</td><td>5</td></tr> <tr><td>0.462</td><td>10</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	5	5	0.084	5	5	0.168	5	5	0.252	5	5	0.336	5	5	0.420	10	5	0.462	10	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	5	5																																						
0.084	5	5																																						
0.168	5	5																																						
0.252	5	5																																						
0.336	5	5																																						
0.420	10	5																																						
0.462	10	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope.                  Ripple Voltage is shown as p-p in the figure below.                  Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								




<p>Model MGW100512</p> <p>Item Ripple Voltage (by Load Current)</p> <p>Object -12V0.42A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.084</td><td>5</td><td>5</td></tr> <tr><td>0.168</td><td>5</td><td>5</td></tr> <tr><td>0.252</td><td>5</td><td>5</td></tr> <tr><td>0.336</td><td>5</td><td>5</td></tr> <tr><td>0.420</td><td>10</td><td>5</td></tr> <tr><td>0.462</td><td>10</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	5	5	0.084	5	5	0.168	5	5	0.252	5	5	0.336	5	5	0.420	10	5	0.462	10	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	5	5																																						
0.084	5	5																																						
0.168	5	5																																						
0.252	5	5																																						
0.336	5	5																																						
0.420	10	5																																						
0.462	10	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						



<p>Model MGW100512</p> <p>Item Ripple-Noise</p> <p>Object +12V0.42A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>—△— Input Volt. 4.5V</p> <p>- -○- - Input Volt. 9V</p> </div> </div> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.084</td><td>5</td><td>5</td></tr> <tr><td>0.168</td><td>5</td><td>5</td></tr> <tr><td>0.252</td><td>5</td><td>5</td></tr> <tr><td>0.336</td><td>10</td><td>5</td></tr> <tr><td>0.420</td><td>10</td><td>5</td></tr> <tr><td>0.462</td><td>10</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated Load Current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	5	5	0.084	5	5	0.168	5	5	0.252	5	5	0.336	10	5	0.420	10	5	0.462	10	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	5	5																																						
0.084	5	5																																						
0.168	5	5																																						
0.252	5	5																																						
0.336	10	5																																						
0.420	10	5																																						
0.462	10	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						



<p>Model MGW100512</p> <p>Item Ripple-Noise</p> <p>Object -12V0.42A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure B</p>																																						
<p>1.Graph</p> <p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Ripple Noise[mVp-p]</p> <p>Fig.Complex Ripple Noise Wave Form</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 4.5 [V]</th> <th>Input Volt. 9 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.084</td><td>5</td><td>5</td></tr> <tr><td>0.168</td><td>5</td><td>5</td></tr> <tr><td>0.252</td><td>5</td><td>5</td></tr> <tr><td>0.336</td><td>10</td><td>5</td></tr> <tr><td>0.420</td><td>10</td><td>5</td></tr> <tr><td>0.462</td><td>10</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 4.5 [V]	Input Volt. 9 [V]	0.000	5	5	0.084	5	5	0.168	5	5	0.252	5	5	0.336	10	5	0.420	10	5	0.462	10	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 4.5 [V]	Input Volt. 9 [V]																																						
0.000	5	5																																						
0.084	5	5																																						
0.168	5	5																																						
0.252	5	5																																						
0.336	10	5																																						
0.420	10	5																																						
0.462	10	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						




Testing Circuitry Figure B

2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	5
-20	5	5
0	5	5
25	5	5
50	5	5
60	5	5
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	5	10
-40	5	5
-20	5	5
0	5	5
25	5	5
50	5	5
60	5	5
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current



Model		MGW100512		Testing Circuitry Figure A																																																				
Item		Ambient Temperature Drift																																																						
Object		+12V0.42A		2.Values																																																				
1.Graph		<p>—△— Input Volt. 4.5V</p> <p>---□--- Input Volt. 5V</p> <p>---○--- Input Volt. 9V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.013</td><td>12.014</td><td>12.015</td></tr> <tr><td>-40</td><td>12.032</td><td>12.033</td><td>12.035</td></tr> <tr><td>-20</td><td>12.046</td><td>12.047</td><td>12.048</td></tr> <tr><td>0</td><td>12.055</td><td>12.055</td><td>12.057</td></tr> <tr><td>25</td><td>12.059</td><td>12.059</td><td>12.061</td></tr> <tr><td>50</td><td>12.057</td><td>12.057</td><td>12.059</td></tr> <tr><td>60</td><td>12.055</td><td>12.055</td><td>12.057</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	12.013	12.014	12.015	-40	12.032	12.033	12.035	-20	12.046	12.047	12.048	0	12.055	12.055	12.057	25	12.059	12.059	12.061	50	12.057	12.057	12.059	60	12.055	12.055	12.057	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
-60	12.013	12.014	12.015																																																					
-40	12.032	12.033	12.035																																																					
-20	12.046	12.047	12.048																																																					
0	12.055	12.055	12.057																																																					
25	12.059	12.059	12.061																																																					
50	12.057	12.057	12.059																																																					
60	12.055	12.055	12.057																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Ambient Temperature [°C]</p> <p>Load 100%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.013</td><td>12.014</td><td>12.015</td></tr> <tr><td>-40</td><td>12.032</td><td>12.033</td><td>12.035</td></tr> <tr><td>-20</td><td>12.046</td><td>12.047</td><td>12.048</td></tr> <tr><td>0</td><td>12.055</td><td>12.055</td><td>12.057</td></tr> <tr><td>25</td><td>12.059</td><td>12.059</td><td>12.061</td></tr> <tr><td>50</td><td>12.057</td><td>12.057</td><td>12.059</td></tr> <tr><td>60</td><td>12.055</td><td>12.055</td><td>12.057</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	12.013	12.014	12.015	-40	12.032	12.033	12.035	-20	12.046	12.047	12.048	0	12.055	12.055	12.057	25	12.059	12.059	12.061	50	12.057	12.057	12.059	60	12.055	12.055	12.057	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
-60	12.013	12.014	12.015																																																					
-40	12.032	12.033	12.035																																																					
-20	12.046	12.047	12.048																																																					
0	12.055	12.055	12.057																																																					
25	12.059	12.059	12.061																																																					
50	12.057	12.057	12.059																																																					
60	12.055	12.055	12.057																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Object		-12V0.42A		2.Values																																																				
1.Graph		<p>—△— Input Volt. 4.5V</p> <p>---□--- Input Volt. 5V</p> <p>---○--- Input Volt. 9V</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.019</td><td>-12.021</td><td>-12.021</td></tr> <tr><td>-40</td><td>-12.041</td><td>-12.041</td><td>-12.042</td></tr> <tr><td>-20</td><td>-12.056</td><td>-12.056</td><td>-12.056</td></tr> <tr><td>0</td><td>-12.065</td><td>-12.065</td><td>-12.065</td></tr> <tr><td>25</td><td>-12.071</td><td>-12.071</td><td>-12.070</td></tr> <tr><td>50</td><td>-12.070</td><td>-12.069</td><td>-12.069</td></tr> <tr><td>60</td><td>-12.068</td><td>-12.068</td><td>-12.068</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	-12.019	-12.021	-12.021	-40	-12.041	-12.041	-12.042	-20	-12.056	-12.056	-12.056	0	-12.065	-12.065	-12.065	25	-12.071	-12.071	-12.070	50	-12.070	-12.069	-12.069	60	-12.068	-12.068	-12.068	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
-60	-12.019	-12.021	-12.021																																																					
-40	-12.041	-12.041	-12.042																																																					
-20	-12.056	-12.056	-12.056																																																					
0	-12.065	-12.065	-12.065																																																					
25	-12.071	-12.071	-12.070																																																					
50	-12.070	-12.069	-12.069																																																					
60	-12.068	-12.068	-12.068																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Ambient Temperature [°C]</p> <p>Load 100%</p>				<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-12.019</td><td>-12.021</td><td>-12.021</td></tr> <tr><td>-40</td><td>-12.041</td><td>-12.041</td><td>-12.042</td></tr> <tr><td>-20</td><td>-12.056</td><td>-12.056</td><td>-12.056</td></tr> <tr><td>0</td><td>-12.065</td><td>-12.065</td><td>-12.065</td></tr> <tr><td>25</td><td>-12.071</td><td>-12.071</td><td>-12.070</td></tr> <tr><td>50</td><td>-12.070</td><td>-12.069</td><td>-12.069</td></tr> <tr><td>60</td><td>-12.068</td><td>-12.068</td><td>-12.068</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-60	-12.019	-12.021	-12.021	-40	-12.041	-12.041	-12.042	-20	-12.056	-12.056	-12.056	0	-12.065	-12.065	-12.065	25	-12.071	-12.071	-12.070	50	-12.070	-12.069	-12.069	60	-12.068	-12.068	-12.068	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
-60	-12.019	-12.021	-12.021																																																					
-40	-12.041	-12.041	-12.042																																																					
-20	-12.056	-12.056	-12.056																																																					
0	-12.065	-12.065	-12.065																																																					
25	-12.071	-12.071	-12.070																																																					
50	-12.070	-12.069	-12.069																																																					
60	-12.068	-12.068	-12.068																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																								



<b>COSEL</b>		Testing Circuitry Figure A
Model	MGW100512	
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 50°C

Input Voltage : 4.5 - 9V

Load Current (AVR 1) : 0 - 0.42A (AVR 2) : 0 - 0.42A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

\* Output Voltage Accuracy (Ratio) = 
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.42A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	4.5	0	12.343	±302	±2.5
Minimum Voltage	50	4.5	0.42	11.739		

Object		-12V0.42A				
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	4.5	0	-12.398	±302	±2.5
Minimum Voltage	50	4.5	0.42	-11.794		




<b>COSEL</b>																									
Model	MGW100512	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.42A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt.     5V Load             100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.054</td></tr> <tr><td>0.5</td><td>12.055</td></tr> <tr><td>1.0</td><td>12.055</td></tr> <tr><td>2.0</td><td>12.055</td></tr> <tr><td>3.0</td><td>12.055</td></tr> <tr><td>4.0</td><td>12.055</td></tr> <tr><td>5.0</td><td>12.055</td></tr> <tr><td>6.0</td><td>12.055</td></tr> <tr><td>7.0</td><td>12.055</td></tr> <tr><td>8.0</td><td>12.055</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated Load Current</p>		Time since start [H]	Output Voltage [V]	0.0	12.054	0.5	12.055	1.0	12.055	2.0	12.055	3.0	12.055	4.0	12.055	5.0	12.055	6.0	12.055	7.0	12.055	8.0	12.055
Time since start [H]	Output Voltage [V]																								
0.0	12.054																								
0.5	12.055																								
1.0	12.055																								
2.0	12.055																								
3.0	12.055																								
4.0	12.055																								
5.0	12.055																								
6.0	12.055																								
7.0	12.055																								
8.0	12.055																								
Object	-12V0.42A																								
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt.     5V Load             100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.072</td></tr> <tr><td>0.5</td><td>-12.075</td></tr> <tr><td>1.0</td><td>-12.075</td></tr> <tr><td>2.0</td><td>-12.074</td></tr> <tr><td>3.0</td><td>-12.074</td></tr> <tr><td>4.0</td><td>-12.074</td></tr> <tr><td>5.0</td><td>-12.074</td></tr> <tr><td>6.0</td><td>-12.074</td></tr> <tr><td>7.0</td><td>-12.074</td></tr> <tr><td>8.0</td><td>-12.075</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated Load Current</p>		Time since start [H]	Output Voltage [V]	0.0	-12.072	0.5	-12.075	1.0	-12.075	2.0	-12.074	3.0	-12.074	4.0	-12.074	5.0	-12.074	6.0	-12.074	7.0	-12.074	8.0	-12.075
Time since start [H]	Output Voltage [V]																								
0.0	-12.072																								
0.5	-12.075																								
1.0	-12.075																								
2.0	-12.074																								
3.0	-12.074																								
4.0	-12.074																								
5.0	-12.074																								
6.0	-12.074																								
7.0	-12.074																								
8.0	-12.075																								




Model		MGW100512	Temperature 25°C	
Item		Rise and Fall Time	Testing Circuitry Figure A	
Object		+12V0.42A		

1. Graph



2. Values


Load \ Time	Td	Tr	Ts	Th	Tf
50 %	1.3	1.6	2.9	0.2	2.3
100 %	1.2	2.3	3.5	0.1	1.1






Model	MGW100512	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V0.42A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.3	2.0	3.3	0.2	2.7
100 %		1.2	2.5	3.7	0.1	1.3






Model	MGW100512
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.42A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.8	3.8
-40	3.7	3.8
-20	3.7	3.8
0	3.7	3.8
25	3.7	3.8
50	3.7	3.8
60	3.7	3.8
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.42A
--------	-----------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	3.8	3.8
-40	3.7	3.8
-20	3.7	3.8
0	3.7	3.8
25	3.7	3.8
50	3.7	3.8
60	3.7	3.8
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



<p>Model MGW100512</p> <p>Item Overcurrent Protection</p> <p>Object +12V0.42A</p>		<p>Temperature 25°C</p> <p>Testing Circuitry Figure A</p>																																																							
<p>1.Graph</p> <p>— Input Volt. 4.5V</p> <p>— Input Volt. 5V</p> <p>— Input Volt. 9V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.63</td><td>0.64</td><td>0.73</td></tr> <tr><td>10.8</td><td>0.67</td><td>0.68</td><td>0.77</td></tr> <tr><td>9.6</td><td>0.76</td><td>0.76</td><td>0.84</td></tr> <tr><td>8.4</td><td>0.85</td><td>0.85</td><td>0.92</td></tr> <tr><td>7.2</td><td>0.94</td><td>0.95</td><td>1.00</td></tr> <tr><td>6.0</td><td>1.04</td><td>1.04</td><td>1.09</td></tr> <tr><td>4.8</td><td>1.14</td><td>1.14</td><td>1.17</td></tr> <tr><td>3.6</td><td>1.24</td><td>1.24</td><td>1.25</td></tr> <tr><td>2.4</td><td>1.36</td><td>1.35</td><td>1.33</td></tr> <tr><td>1.2</td><td>1.48</td><td>1.45</td><td>1.40</td></tr> <tr><td>0.0</td><td>1.42</td><td>1.39</td><td>1.28</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	11.4	0.63	0.64	0.73	10.8	0.67	0.68	0.77	9.6	0.76	0.76	0.84	8.4	0.85	0.85	0.92	7.2	0.94	0.95	1.00	6.0	1.04	1.04	1.09	4.8	1.14	1.14	1.17	3.6	1.24	1.24	1.25	2.4	1.36	1.35	1.33	1.2	1.48	1.45	1.40	0.0	1.42	1.39	1.28	--	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																						
11.4	0.63	0.64	0.73																																																						
10.8	0.67	0.68	0.77																																																						
9.6	0.76	0.76	0.84																																																						
8.4	0.85	0.85	0.92																																																						
7.2	0.94	0.95	1.00																																																						
6.0	1.04	1.04	1.09																																																						
4.8	1.14	1.14	1.17																																																						
3.6	1.24	1.24	1.25																																																						
2.4	1.36	1.35	1.33																																																						
1.2	1.48	1.45	1.40																																																						
0.0	1.42	1.39	1.28																																																						
--	-	-	-																																																						
<p>Object -12V0.42A</p> <p>1.Graph</p> <p>— Input Volt. 4.5V</p> <p>— Input Volt. 5V</p> <p>— Input Volt. 9V</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>-11.4</td><td>0.63</td><td>0.64</td><td>0.73</td></tr> <tr><td>-10.8</td><td>0.67</td><td>0.68</td><td>0.77</td></tr> <tr><td>-9.6</td><td>0.76</td><td>0.77</td><td>0.85</td></tr> <tr><td>-8.4</td><td>0.85</td><td>0.86</td><td>0.92</td></tr> <tr><td>-7.2</td><td>0.95</td><td>0.95</td><td>1.01</td></tr> <tr><td>-6.0</td><td>1.04</td><td>1.04</td><td>1.09</td></tr> <tr><td>-4.8</td><td>1.14</td><td>1.15</td><td>1.18</td></tr> <tr><td>-3.6</td><td>1.26</td><td>1.25</td><td>1.26</td></tr> <tr><td>-2.4</td><td>1.37</td><td>1.36</td><td>1.34</td></tr> <tr><td>-1.2</td><td>1.50</td><td>1.47</td><td>1.41</td></tr> <tr><td>0.0</td><td>1.40</td><td>1.36</td><td>1.24</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Output Voltage [V]	Load Current [A]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	-11.4	0.63	0.64	0.73	-10.8	0.67	0.68	0.77	-9.6	0.76	0.77	0.85	-8.4	0.85	0.86	0.92	-7.2	0.95	0.95	1.01	-6.0	1.04	1.04	1.09	-4.8	1.14	1.15	1.18	-3.6	1.26	1.25	1.26	-2.4	1.37	1.36	1.34	-1.2	1.50	1.47	1.41	0.0	1.40	1.36	1.24	--	-	-	-
Output Voltage [V]	Load Current [A]																																																								
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																						
-11.4	0.63	0.64	0.73																																																						
-10.8	0.67	0.68	0.77																																																						
-9.6	0.76	0.77	0.85																																																						
-8.4	0.85	0.86	0.92																																																						
-7.2	0.95	0.95	1.01																																																						
-6.0	1.04	1.04	1.09																																																						
-4.8	1.14	1.15	1.18																																																						
-3.6	1.26	1.25	1.26																																																						
-2.4	1.37	1.36	1.34																																																						
-1.2	1.50	1.47	1.41																																																						
0.0	1.40	1.36	1.24																																																						
--	-	-	-																																																						



Model		MGW100512		Temperature 25°C																																																				
Item		Switching Frequency (by Load Current)		Testing Circuitry Figure A																																																				
Object		+/-12V0.42A																																																						
1.Graph		<p>—△— Input Volt. 4.5V</p> <p>- - - □ - - Input Volt. 5V</p> <p>- · - ○ - · - Input Volt. 9V</p>		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Frequency [kHz]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>1510</td><td>1708</td><td>1359</td></tr> <tr><td>0.080</td><td>821</td><td>874</td><td>1082</td></tr> <tr><td>0.170</td><td>528</td><td>568</td><td>758</td></tr> <tr><td>0.250</td><td>385</td><td>419</td><td>585</td></tr> <tr><td>0.340</td><td>299</td><td>328</td><td>473</td></tr> <tr><td>0.420</td><td>242</td><td>268</td><td>398</td></tr> <tr><td>0.462</td><td>219</td><td>245</td><td>368</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Frequency [kHz]			Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	0.000	1510	1708	1359	0.080	821	874	1082	0.170	528	568	758	0.250	385	419	585	0.340	299	328	473	0.420	242	268	398	0.462	219	245	368	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Frequency [kHz]																																																							
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]																																																					
0.000	1510	1708	1359																																																					
0.080	821	874	1082																																																					
0.170	528	568	758																																																					
0.250	385	419	585																																																					
0.340	299	328	473																																																					
0.420	242	268	398																																																					
0.462	219	245	368																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
<p>Note: Slanted line shows the range of the rated load current.</p> <p>When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>																																																								




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)