

# TEST DATA OF MGW154812

Regulated DC Power Supply  
September 11, 2010

Approved by : Kazunari Asano  
Kazunari Asano Design Manager

Prepared by : Hidetaka Kobayashi  
Hidetaka Kobayashi Design Engineer

**COSEL CO.,LTD.**

## CONTENTS

1.Input Current (by Input Voltage) . . . . .	1
2.Input Current (by Load Current) . . . . .	2
3.Input Power (by Load Current) . . . . .	3
4.Efficiency (by Input Voltage) . . . . .	4
5.Efficiency (by Load Current) . . . . .	5
6.Line Regulation . . . . .	6
7.Load Regulation . . . . .	7
8.Dynamic Load Response . . . . .	8
9.Ripple Voltage (by Load Current) . . . . .	10
10.Ripple-Noise . . . . .	12
11.Ripple Voltage (by Ambient Temperature) . . . . .	14
12.Ambient Temperature Drift . . . . .	15
13.Output Voltage Accuracy . . . . .	16
14.Time Lapse Drift . . . . .	17
15.Rise and Fall Time . . . . .	18
16.Minimum Input Voltage for Regulated Output Voltage . . . . .	20
17.Overcurrent Protection . . . . .	21
18.Figure of Testing Circuitry . . . . .	22

(Final Page 22)




Model	MGW154812																																																																																	
Item	Input Current (by Input Voltage)	Temperature	25°C																																																																															
Object		Testing Circuitry	Figure A																																																																															
1.Graph		2.Values																																																																																
<div><div><div></div><div></div><div></div></div><div><div></div><div></div><div></div></div><div><div></div><div></div><div></div></div></div> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="3">Input Current [A]</th></tr><tr><th>Load 0%</th><th>Load 50%</th><th>Load 100%</th></tr><tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr><tr><td>8.0</td><td>0.002</td><td>0.003</td><td>0.003</td></tr><tr><td>16.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr><tr><td>24.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr><tr><td>28.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr><tr><td>32.0</td><td>0.003</td><td>0.003</td><td>0.003</td></tr><tr><td>32.8</td><td>0.017</td><td>0.274</td><td>0.558</td></tr><tr><td>34.0</td><td>0.017</td><td>0.263</td><td>0.538</td></tr><tr><td>36.0</td><td>0.017</td><td>0.252</td><td>0.508</td></tr><tr><td>40.0</td><td>0.016</td><td>0.230</td><td>0.456</td></tr><tr><td>48.0</td><td>0.013</td><td>0.190</td><td>0.379</td></tr><tr><td>60.0</td><td>0.011</td><td>0.154</td><td>0.301</td></tr><tr><td>70.0</td><td>0.010</td><td>0.135</td><td>0.260</td></tr><tr><td>76.0</td><td>0.009</td><td>0.124</td><td>0.242</td></tr><tr><td>80.0</td><td>0.009</td><td>0.118</td><td>0.231</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	8.0	0.002	0.003	0.003	16.0	0.003	0.003	0.003	24.0	0.003	0.003	0.003	28.0	0.003	0.003	0.003	32.0	0.003	0.003	0.003	32.8	0.017	0.274	0.558	34.0	0.017	0.263	0.538	36.0	0.017	0.252	0.508	40.0	0.016	0.230	0.456	48.0	0.013	0.190	0.379	60.0	0.011	0.154	0.301	70.0	0.010	0.135	0.260	76.0	0.009	0.124	0.242	80.0	0.009	0.118	0.231	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																	
	Load 0%	Load 50%	Load 100%																																																																															
0.0	0.000	0.000	0.000																																																																															
8.0	0.002	0.003	0.003																																																																															
16.0	0.003	0.003	0.003																																																																															
24.0	0.003	0.003	0.003																																																																															
28.0	0.003	0.003	0.003																																																																															
32.0	0.003	0.003	0.003																																																																															
32.8	0.017	0.274	0.558																																																																															
34.0	0.017	0.263	0.538																																																																															
36.0	0.017	0.252	0.508																																																																															
40.0	0.016	0.230	0.456																																																																															
48.0	0.013	0.190	0.379																																																																															
60.0	0.011	0.154	0.301																																																																															
70.0	0.010	0.135	0.260																																																																															
76.0	0.009	0.124	0.242																																																																															
80.0	0.009	0.118	0.231																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															
--	-	-	-																																																																															



Model	MGW154812																																																		
Item	Input Current (by Load Current)	Temperature	25°C																																																
		Testing Circuitry	Figure A																																																
Object																																																			
1.Graph		2.Values																																																	
<div><div><div>—△—</div><div>Input Volt.</div><div>36V</div></div><div><div>---□---</div><div>Input Volt.</div><div>48V</div></div><div><div>---○---</div><div>Input Volt.</div><div>76V</div></div></div> <table><thead><tr><th>Load Ration [%]</th><th>Input Current 36[V] [A]</th><th>Input Current 48[V] [A]</th><th>Input Current 76[V] [A]</th></tr></thead><tbody><tr><td>0</td><td>0.017</td><td>0.013</td><td>0.009</td></tr><tr><td>20</td><td>0.113</td><td>0.083</td><td>0.056</td></tr><tr><td>40</td><td>0.208</td><td>0.155</td><td>0.099</td></tr><tr><td>60</td><td>0.301</td><td>0.229</td><td>0.147</td></tr><tr><td>80</td><td>0.401</td><td>0.296</td><td>0.190</td></tr><tr><td>100</td><td>0.500</td><td>0.373</td><td>0.238</td></tr><tr><td>110</td><td>0.550</td><td>0.410</td><td>0.258</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Ration [%]	Input Current 36[V] [A]	Input Current 48[V] [A]	Input Current 76[V] [A]	0	0.017	0.013	0.009	20	0.113	0.083	0.056	40	0.208	0.155	0.099	60	0.301	0.229	0.147	80	0.401	0.296	0.190	100	0.500	0.373	0.238	110	0.550	0.410	0.258	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Ration [%]	Input Current 36[V] [A]	Input Current 48[V] [A]	Input Current 76[V] [A]																																																
0	0.017	0.013	0.009																																																
20	0.113	0.083	0.056																																																
40	0.208	0.155	0.099																																																
60	0.301	0.229	0.147																																																
80	0.401	0.296	0.190																																																
100	0.500	0.373	0.238																																																
110	0.550	0.410	0.258																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																



Model	MGW154812																																																		
Item	Input Power (by Load Current)	Temperature	25°C																																																
Object		Testing Circuitry	Figure A																																																
1.Graph		2.Values																																																	
<div><div>—△—</div><div>Input Volt.</div><div>36V</div></div> <div><div>---□---</div><div>Input Volt.</div><div>48V</div></div> <div><div>-·-○-·-</div><div>Input Volt.</div><div>76V</div></div>  <table><thead><tr><th>Load Ration [%]</th><th>Input Power [W] 36[V]</th><th>Input Power [W] 48[V]</th><th>Input Power [W] 76[V]</th></tr></thead><tbody><tr><td>0</td><td>0.61</td><td>0.65</td><td>0.74</td></tr><tr><td>20</td><td>4.07</td><td>4.00</td><td>4.29</td></tr><tr><td>40</td><td>7.49</td><td>7.46</td><td>7.53</td></tr><tr><td>60</td><td>10.85</td><td>11.00</td><td>11.21</td></tr><tr><td>80</td><td>14.41</td><td>14.22</td><td>14.45</td></tr><tr><td>100</td><td>17.98</td><td>17.90</td><td>18.12</td></tr><tr><td>110</td><td>19.77</td><td>19.66</td><td>19.68</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></tbody></table>		Load Ration [%]	Input Power [W] 36[V]	Input Power [W] 48[V]	Input Power [W] 76[V]	0	0.61	0.65	0.74	20	4.07	4.00	4.29	40	7.49	7.46	7.53	60	10.85	11.00	11.21	80	14.41	14.22	14.45	100	17.98	17.90	18.12	110	19.77	19.66	19.68	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-		
Load Ration [%]	Input Power [W] 36[V]	Input Power [W] 48[V]	Input Power [W] 76[V]																																																
0	0.61	0.65	0.74																																																
20	4.07	4.00	4.29																																																
40	7.49	7.46	7.53																																																
60	10.85	11.00	11.21																																																
80	14.41	14.22	14.45																																																
100	17.98	17.90	18.12																																																
110	19.77	19.66	19.68																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																
--	-	-	-																																																





Model	MGW154812																																																																
Item	Efficiency (by Input Voltage)	Temperature	25°C																																																														
		Testing Circuitry	Figure A																																																														
Object																																																																	
1.Graph		2.Values																																																															
<div><div><div>---</div><div>□</div><div>---</div></div><div>Load 50%</div></div> <div><div>—</div><div>△</div><div>—</div></div> <div>Load 100%</div> <table border="1"><thead><tr><th>Input Voltage [V]</th><th>Load 50% Efficiency [%]</th><th>Load 100% Efficiency [%]</th></tr></thead><tbody><tr><td>34</td><td>87.2</td><td>87.3</td></tr><tr><td>36</td><td>86.2</td><td>87.4</td></tr><tr><td>40</td><td>85.0</td><td>87.6</td></tr><tr><td>48</td><td>85.7</td><td>87.7</td></tr><tr><td>60</td><td>84.6</td><td>88.8</td></tr><tr><td>76</td><td>82.8</td><td>86.7</td></tr><tr><td>80</td><td>83.0</td><td>86.4</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]	34	87.2	87.3	36	86.2	87.4	40	85.0	87.6	48	85.7	87.7	60	84.6	88.8	76	82.8	86.7	80	83.0	86.4	--	-	-	--	-	-	<table><tr><th rowspan="2">Input Voltage [V]</th><th colspan="2">Efficiency [%]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr><tr><td>34</td><td>87.2</td><td>87.3</td></tr><tr><td>36</td><td>86.2</td><td>87.4</td></tr><tr><td>40</td><td>85.0</td><td>87.6</td></tr><tr><td>48</td><td>85.7</td><td>87.7</td></tr><tr><td>60</td><td>84.6</td><td>88.8</td></tr><tr><td>76</td><td>82.8</td><td>86.7</td></tr><tr><td>80</td><td>83.0</td><td>86.4</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	34	87.2	87.3	36	86.2	87.4	40	85.0	87.6	48	85.7	87.7	60	84.6	88.8	76	82.8	86.7	80	83.0	86.4	--	-	-	--	-	-
Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]																																																															
34	87.2	87.3																																																															
36	86.2	87.4																																																															
40	85.0	87.6																																																															
48	85.7	87.7																																																															
60	84.6	88.8																																																															
76	82.8	86.7																																																															
80	83.0	86.4																																																															
--	-	-																																																															
--	-	-																																																															
Input Voltage [V]	Efficiency [%]																																																																
	Load 50%	Load 100%																																																															
34	87.2	87.3																																																															
36	86.2	87.4																																																															
40	85.0	87.6																																																															
48	85.7	87.7																																																															
60	84.6	88.8																																																															
76	82.8	86.7																																																															
80	83.0	86.4																																																															
--	-	-																																																															
--	-	-																																																															
Note: Slanted line shows the range of the rated input voltage.																																																																	

Model	MGW154812																																																					
Item	Efficiency (by Load Current)	Temperature	25°C																																																			
		Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<div><div>—△— Input Volt. 36V</div><div>---□--- Input Volt. 48V</div><div>-·-○-·- Input Volt. 76V</div></div> <p>Efficiency [%]</p> <p>Load Ration [%]</p>		<table><tr><th rowspan="2">Load Ration [%]</th><th colspan="3">Efficiency [%]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>0</td><td>-</td><td>-</td><td>-</td></tr><tr><td>20</td><td>77.1</td><td>78.4</td><td>73.1</td></tr><tr><td>40</td><td>83.8</td><td>84.2</td><td>83.4</td></tr><tr><td>60</td><td>86.8</td><td>85.6</td><td>84.0</td></tr><tr><td>80</td><td>87.2</td><td>88.3</td><td>86.9</td></tr><tr><td>100</td><td>87.3</td><td>87.7</td><td>86.7</td></tr><tr><td>110</td><td>87.4</td><td>87.9</td><td>87.8</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>		Load Ration [%]	Efficiency [%]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0	-	-	-	20	77.1	78.4	73.1	40	83.8	84.2	83.4	60	86.8	85.6	84.0	80	87.2	88.3	86.9	100	87.3	87.7	86.7	110	87.4	87.9	87.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																			
0	-	-	-																																																			
20	77.1	78.4	73.1																																																			
40	83.8	84.2	83.4																																																			
60	86.8	85.6	84.0																																																			
80	87.2	88.3	86.9																																																			
100	87.3	87.7	86.7																																																			
110	87.4	87.9	87.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	MGW154812	Temperature 25°C Testing Circuitry Figure A	
Item	Line Regulation		
Object	+12V0.65A		
1.Graph		2.Values	
<div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div><div></div><div></div></div><div>&lt;</div></div>			



Model		MGW154812		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+12V0.65A																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>36V</div></div><div><div>---□---</div><div>Input Volt.</div><div>48V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>76V</div></div></div> 		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>0.000</td><td>12.561</td><td>12.568</td><td>12.587</td></tr><tr><td>0.130</td><td>12.196</td><td>12.196</td><td>12.197</td></tr><tr><td>0.260</td><td>12.146</td><td>12.146</td><td>12.146</td></tr><tr><td>0.390</td><td>12.117</td><td>12.116</td><td>12.116</td></tr><tr><td>0.520</td><td>12.093</td><td>12.092</td><td>12.092</td></tr><tr><td>0.650</td><td>12.072</td><td>12.071</td><td>12.072</td></tr><tr><td>0.715</td><td>12.061</td><td>12.062</td><td>12.063</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	12.561	12.568	12.587	0.130	12.196	12.196	12.197	0.260	12.146	12.146	12.146	0.390	12.117	12.116	12.116	0.520	12.093	12.092	12.092	0.650	12.072	12.071	12.072	0.715	12.061	12.062	12.063	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.000	12.561	12.568	12.587																																																					
0.130	12.196	12.196	12.197																																																					
0.260	12.146	12.146	12.146																																																					
0.390	12.117	12.116	12.116																																																					
0.520	12.093	12.092	12.092																																																					
0.650	12.072	12.071	12.072																																																					
0.715	12.061	12.062	12.063																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
		-12V: Rated output current																																																						

Object		-12V0.65A																																																						
1.Graph		<div><div><div>—△—</div><div>Input Volt.</div><div>36V</div></div><div><div>---□---</div><div>Input Volt.</div><div>48V</div></div><div><div>-·-○-·-</div><div>Input Volt.</div><div>76V</div></div></div> 		2.Values																																																				
		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>0.000</td><td>-12.519</td><td>-12.524</td><td>-12.536</td></tr><tr><td>0.130</td><td>-12.191</td><td>-12.191</td><td>-12.191</td></tr><tr><td>0.260</td><td>-12.143</td><td>-12.144</td><td>-12.144</td></tr><tr><td>0.390</td><td>-12.115</td><td>-12.114</td><td>-12.114</td></tr><tr><td>0.520</td><td>-12.092</td><td>-12.090</td><td>-12.090</td></tr><tr><td>0.650</td><td>-12.070</td><td>-12.070</td><td>-12.070</td></tr><tr><td>0.715</td><td>-12.059</td><td>-12.061</td><td>-12.061</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>				Load Current [A]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	0.000	-12.519	-12.524	-12.536	0.130	-12.191	-12.191	-12.191	0.260	-12.143	-12.144	-12.144	0.390	-12.115	-12.114	-12.114	0.520	-12.092	-12.090	-12.090	0.650	-12.070	-12.070	-12.070	0.715	-12.059	-12.061	-12.061	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																					
0.000	-12.519	-12.524	-12.536																																																					
0.130	-12.191	-12.191	-12.191																																																					
0.260	-12.143	-12.144	-12.144																																																					
0.390	-12.115	-12.114	-12.114																																																					
0.520	-12.092	-12.090	-12.090																																																					
0.650	-12.070	-12.070	-12.070																																																					
0.715	-12.059	-12.061	-12.061																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
		+12V: Rated output current																																																						

Note: Slanted line shows the range of the rated load current.



Model	MGW154812	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	+12V0.65A	

Input Volt. 48 V

Other output current rated

Cycle 1000 ms

$t_1, t_2 = 50\mu\text{s}$




Min. Load (0A)  $\longleftrightarrow$

Load 100% (0.65A)

200mV/div



200 $\mu\text{s}$ /div



200 $\mu\text{s}$ /div


Min. Load (0A)  $\longleftrightarrow$

Load 50% (0.325A)

200mV/div



200 $\mu\text{s}$ /div




200 $\mu\text{s}$ /div


Load 50% (0.325A)  $\longleftrightarrow$

Load 100% (0.65A)

200mV/div



200 $\mu\text{s}$ /div



200 $\mu\text{s}$ /div



Model	MGW154812	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response	
Object	-12V0.65A	

Input Volt. 48 V

Other output current rated

Cycle 1000 ms


$t_1, t_2 = 50\mu\text{s}$




Min. Load (0A)  $\longleftrightarrow$

Load 100% (0.65A)

200mV/div



200 $\mu\text{s}$ /div



200 $\mu\text{s}$ /div


Min. Load (0A)  $\longleftrightarrow$

Load 50% (0.325A)

200mV/div



200 $\mu\text{s}$ /div




200 $\mu\text{s}$ /div


Load 50% (0.325A)  $\longleftrightarrow$

Load 100% (0.65A)

200mV/div



200 $\mu\text{s}$ /div



200 $\mu\text{s}$ /div

Model		MGW154812																																							
Item		Ripple Voltage (by Load Current)																																							
Object		+12V0.65A																																							
1.Graph		2.Values																																							
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>Input Volt.</div><div>36V</div></div><div><div>Input Volt.</div><div>76V</div></div></div><div><p>Ripple Voltage [mV]</p><p>Load Current [A]</p></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 36 [V]</th><th>Input Volt. 76 [V]</th></tr><tr><td>0.000</td><td>5</td><td>5</td></tr><tr><td>0.130</td><td>5</td><td>6</td></tr><tr><td>0.260</td><td>6</td><td>7</td></tr><tr><td>0.390</td><td>7</td><td>8</td></tr><tr><td>0.520</td><td>8</td><td>9</td></tr><tr><td>0.650</td><td>9</td><td>10</td></tr><tr><td>0.715</td><td>10</td><td>10</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table> <p>-12V: Rated output current</p>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.000	5	5	0.130	5	6	0.260	6	7	0.390	7	8	0.520	8	9	0.650	9	10	0.715	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 36 [V]	Input Volt. 76 [V]																																							
0.000	5	5																																							
0.130	5	6																																							
0.260	6	7																																							
0.390	7	8																																							
0.520	8	9																																							
0.650	9	10																																							
0.715	10	10																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><p>Ripple [mVp-p]</p><p>Fig.Complex Ripple Wave Form</p></div></div>																																									


Model		MGW154812		Temperature 25°C																																							
Item		Ripple Voltage (by Load Current)		Testing Circuitry Figure B																																							
Object		-12V0.65A																																									
1.Graph				2.Values																																							
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>Input Volt.</div><div>36V</div></div><div><div>Input Volt.</div><div>76V</div></div></div><div><p>Ripple Voltage [mV]</p><p>Load Current [A]</p></div></div>				<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple Voltage [mV]</th></tr><tr><th>Input Volt. 36 [V]</th><th>Input Volt. 76 [V]</th></tr><tr><td>0.000</td><td>5</td><td>5</td></tr><tr><td>0.130</td><td>5</td><td>7</td></tr><tr><td>0.260</td><td>7</td><td>8</td></tr><tr><td>0.390</td><td>9</td><td>9</td></tr><tr><td>0.520</td><td>10</td><td>11</td></tr><tr><td>0.650</td><td>11</td><td>12</td></tr><tr><td>0.715</td><td>12</td><td>12</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table> <p>+12V: Rated output current</p>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.000	5	5	0.130	5	7	0.260	7	8	0.390	9	9	0.520	10	11	0.650	11	12	0.715	12	12	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																										
	Input Volt. 36 [V]	Input Volt. 76 [V]																																									
0.000	5	5																																									
0.130	5	7																																									
0.260	7	8																																									
0.390	9	9																																									
0.520	10	11																																									
0.650	11	12																																									
0.715	12	12																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
<p>Measured by 100 MHz Oscilloscope.</p> <p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																											
<div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><p>Ripple [mVp-p]</p><p>Fig.Complex Ripple Wave Form</p></div></div>																																											

- 11 -


BC-10466

Model		MGW154812																																							
Item		Ripple-Noise																																							
Object		+12V0.65A																																							
1.Graph		2.Values																																							
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>Input Volt.</div><div>36V</div></div><div><div>Input Volt.</div><div>76V</div></div></div><div><p>Ripple Voltage [mV]</p><p>Load Current [A]</p></div><div><p>Measured by 100 MHz Oscilloscope.</p><p>Ripple-Noise is shown as p-p in the figure below.</p><p>Note: Slanted line shows the range of the rated load current.</p><div><div><div></div><div></div></div><div><div></div><div></div></div></div><p>Ripple Noise[mVp-p]</p><p>Fig.Complex Ripple Noise Wave Form</p></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr><tr><th>Input Volt. 36 [V]</th><th>Input Volt. 76 [V]</th></tr><tr><td>0.000</td><td>5</td><td>5</td></tr><tr><td>0.130</td><td>7</td><td>7</td></tr><tr><td>0.260</td><td>8</td><td>8</td></tr><tr><td>0.390</td><td>9</td><td>8</td></tr><tr><td>0.520</td><td>10</td><td>10</td></tr><tr><td>0.650</td><td>11</td><td>11</td></tr><tr><td>0.715</td><td>11</td><td>11</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table> <p>-12V: Rated output current</p>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.000	5	5	0.130	7	7	0.260	8	8	0.390	9	8	0.520	10	10	0.650	11	11	0.715	11	11	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 36 [V]	Input Volt. 76 [V]																																							
0.000	5	5																																							
0.130	7	7																																							
0.260	8	8																																							
0.390	9	8																																							
0.520	10	10																																							
0.650	11	11																																							
0.715	11	11																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							

Model		MGW154812																																							
Item		Ripple-Noise																																							
Object		-12V0.65A																																							
1.Graph		2.Values																																							
<div><div><div><div><div></div><div></div></div><div><div></div><div></div></div></div><div><div>Input Volt.</div><div>36V</div></div><div><div>Input Volt.</div><div>76V</div></div></div><div><p>Ripple Voltage [mV]</p><p>Load Current [A]</p></div><div><p>Measured by 100 MHz Oscilloscope.</p><p>Ripple-Noise is shown as p-p in the figure below.</p><p>Note: Slanted line shows the range of the rated load current.</p><div><p>Ripple Noise[mVp-p]</p></div><p>Fig.Complex Ripple Noise Wave Form</p></div></div>		<table><tr><th rowspan="2">Load Current [A]</th><th colspan="2">Ripple-Noise [mV]</th></tr><tr><th>Input Volt. 36 [V]</th><th>Input Volt. 76 [V]</th></tr><tr><td>0.000</td><td>5</td><td>6</td></tr><tr><td>0.130</td><td>7</td><td>7</td></tr><tr><td>0.260</td><td>10</td><td>8</td></tr><tr><td>0.390</td><td>11</td><td>9</td></tr><tr><td>0.520</td><td>12</td><td>12</td></tr><tr><td>0.650</td><td>13</td><td>13</td></tr><tr><td>0.715</td><td>14</td><td>13</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></table> <p>+12V: Rated output current</p>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 36 [V]	Input Volt. 76 [V]	0.000	5	6	0.130	7	7	0.260	10	8	0.390	11	9	0.520	12	12	0.650	13	13	0.715	14	13	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 36 [V]	Input Volt. 76 [V]																																							
0.000	5	6																																							
0.130	7	7																																							
0.260	10	8																																							
0.390	11	9																																							
0.520	12	12																																							
0.650	13	13																																							
0.715	14	13																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							


	
Model	MGW154812
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.65A

## 1.Graph



Object	-12V0.65A
--------	-----------

## 1.Graph



Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure B

## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	25	31
-40	26	32
-20	27	33
0	20	27
25	15	19
60	11	15
65	10	14
--	-	-
--	-	-
--	-	-
--	-	-

-12V: Rated output current



## 2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	18	24
-40	19	22
-20	15	21
0	12	19
25	9	14
60	8	14
65	8	13
--	-	-
--	-	-
--	-	-
--	-	-

+12V: Rated output current

Model	MGW154812																																																						
Item	Ambient Temperature Drift	Testing Circuitry    Figure A																																																					
Object	+12V0.65A																																																						
1.Graph		2.Values																																																					
<div><div><div>—△—</div><div>Input Volt.</div><div>36V</div></div><div><div>---□---</div><div>Input Volt.</div><div>48V</div></div><div><div>---○---</div><div>Input Volt.</div><div>76V</div></div></div> <div>Output Voltage [V]</div> <div>Ambient Temperature [°C]</div> <div>Load 100%</div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>-60</td><td>12.004</td><td>12.005</td><td>12.006</td></tr><tr><td>-40</td><td>12.028</td><td>12.029</td><td>12.030</td></tr><tr><td>-20</td><td>12.047</td><td>12.047</td><td>12.048</td></tr><tr><td>0</td><td>12.060</td><td>12.061</td><td>12.061</td></tr><tr><td>25</td><td>12.071</td><td>12.071</td><td>12.072</td></tr><tr><td>60</td><td>12.077</td><td>12.077</td><td>12.077</td></tr><tr><td>65</td><td>12.077</td><td>12.077</td><td>12.077</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-60	12.004	12.005	12.006	-40	12.028	12.029	12.030	-20	12.047	12.047	12.048	0	12.060	12.061	12.061	25	12.071	12.071	12.072	60	12.077	12.077	12.077	65	12.077	12.077	12.077	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
-60	12.004	12.005	12.006																																																				
-40	12.028	12.029	12.030																																																				
-20	12.047	12.047	12.048																																																				
0	12.060	12.061	12.061																																																				
25	12.071	12.071	12.072																																																				
60	12.077	12.077	12.077																																																				
65	12.077	12.077	12.077																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Object	-12V0.65A																																																						
1.Graph		2.Values																																																					
<div><div><div>—△—</div><div>Input Volt.</div><div>36V</div></div><div><div>---□---</div><div>Input Volt.</div><div>48V</div></div><div><div>---○---</div><div>Input Volt.</div><div>76V</div></div></div> <div>Output Voltage [V]</div> <div>Ambient Temperature [°C]</div> <div>Load 100%</div>		<table><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="3">Output Voltage [V]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>-60</td><td>-12.000</td><td>-12.002</td><td>-12.003</td></tr><tr><td>-40</td><td>-12.025</td><td>-12.027</td><td>-12.027</td></tr><tr><td>-20</td><td>-12.044</td><td>-12.045</td><td>-12.046</td></tr><tr><td>0</td><td>-12.058</td><td>-12.059</td><td>-12.060</td></tr><tr><td>25</td><td>-12.069</td><td>-12.070</td><td>-12.070</td></tr><tr><td>60</td><td>-12.076</td><td>-12.076</td><td>-12.076</td></tr><tr><td>65</td><td>-12.076</td><td>-12.076</td><td>-12.077</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td><td>-</td></tr></table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-60	-12.000	-12.002	-12.003	-40	-12.025	-12.027	-12.027	-20	-12.044	-12.045	-12.046	0	-12.058	-12.059	-12.060	25	-12.069	-12.070	-12.070	60	-12.076	-12.076	-12.076	65	-12.076	-12.076	-12.077	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																				
-60	-12.000	-12.002	-12.003																																																				
-40	-12.025	-12.027	-12.027																																																				
-20	-12.044	-12.045	-12.046																																																				
0	-12.058	-12.059	-12.060																																																				
25	-12.069	-12.070	-12.070																																																				
60	-12.076	-12.076	-12.076																																																				
65	-12.076	-12.076	-12.077																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note: Slanted line shows the range of the rated ambient temperature.																																																							




Model	MGW154812																								
Item	Time Lapse Drift	Temperature	25°C																						
		Testing Circuitry	Figure A																						
Object	+12V0.65A																								
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 48V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>12.063</td></tr><tr><td>0.5</td><td>12.063</td></tr><tr><td>1.0</td><td>12.063</td></tr><tr><td>2.0</td><td>12.063</td></tr><tr><td>3.0</td><td>12.063</td></tr><tr><td>4.0</td><td>12.064</td></tr><tr><td>5.0</td><td>12.064</td></tr><tr><td>6.0</td><td>12.064</td></tr><tr><td>7.0</td><td>12.064</td></tr><tr><td>8.0</td><td>12.064</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	12.063	0.5	12.063	1.0	12.063	2.0	12.063	3.0	12.063	4.0	12.064	5.0	12.064	6.0	12.064	7.0	12.064	8.0	12.064
Time since start [H]	Output Voltage [V]																								
0.0	12.063																								
0.5	12.063																								
1.0	12.063																								
2.0	12.063																								
3.0	12.063																								
4.0	12.064																								
5.0	12.064																								
6.0	12.064																								
7.0	12.064																								
8.0	12.064																								
Object	-12V0.65A																								
1.Graph		2.Values																							
<div><p>Output Voltage [V]</p><p>Time [H]</p><p>Input Volt. 48V</p><p>Load 100%</p></div>		<table><tr><th>Time since start [H]</th><th>Output Voltage [V]</th></tr><tr><td>0.0</td><td>-12.073</td></tr><tr><td>0.5</td><td>-12.073</td></tr><tr><td>1.0</td><td>-12.073</td></tr><tr><td>2.0</td><td>-12.073</td></tr><tr><td>3.0</td><td>-12.073</td></tr><tr><td>4.0</td><td>-12.073</td></tr><tr><td>5.0</td><td>-12.073</td></tr><tr><td>6.0</td><td>-12.073</td></tr><tr><td>7.0</td><td>-12.073</td></tr><tr><td>8.0</td><td>-12.073</td></tr></table>		Time since start [H]	Output Voltage [V]	0.0	-12.073	0.5	-12.073	1.0	-12.073	2.0	-12.073	3.0	-12.073	4.0	-12.073	5.0	-12.073	6.0	-12.073	7.0	-12.073	8.0	-12.073
Time since start [H]	Output Voltage [V]																								
0.0	-12.073																								
0.5	-12.073																								
1.0	-12.073																								
2.0	-12.073																								
3.0	-12.073																								
4.0	-12.073																								
5.0	-12.073																								
6.0	-12.073																								
7.0	-12.073																								
8.0	-12.073																								




Model	MGW154812		
Item	Rise and Fall Time	Temperature	25°C
Object	+12V0.65A	Testing Circuitry	Figure A

## 1.Graph



## 2.Values


		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.1	4.8	5.9	3.9	11.3
100 %		1.1	4.8	5.9	2.0	5.5






Model	MGW154812		
Item	Rise and Fall Time	Temperature	25°C
Object	-12V0.65A	Testing Circuitry	Figure A

## 1.Graph



## 2.Values

		[ms]				
Load	Time	Td	Tr	Ts	Th	Tf
50 %		1.1	5.0	6.1	3.9	11.3
100 %		1.1	5.0	6.1	1.9	5.7







Model	MGW154812	Testing Circuitry    Figure A																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																								
Object	+12V0.65A																																								
1.Graph		2.Values																																							
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-60</td><td>30.9</td><td>30.9</td></tr><tr><td>-40</td><td>31.0</td><td>30.9</td></tr><tr><td>-20</td><td>31.0</td><td>30.9</td></tr><tr><td>0</td><td>30.9</td><td>30.9</td></tr><tr><td>25</td><td>31.0</td><td>30.9</td></tr><tr><td>60</td><td>31.0</td><td>30.9</td></tr><tr><td>65</td><td>31.0</td><td>30.9</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	30.9	30.9	-40	31.0	30.9	-20	31.0	30.9	0	30.9	30.9	25	31.0	30.9	60	31.0	30.9	65	31.0	30.9	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	30.9	30.9																																							
-40	31.0	30.9																																							
-20	31.0	30.9																																							
0	30.9	30.9																																							
25	31.0	30.9																																							
60	31.0	30.9																																							
65	31.0	30.9																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
Object	-12V0.65A																																								
1.Graph		2.Values																																							
<div><div><div>---□---</div><div>Load 50%</div></div><div><div>—△—</div><div>Load 100%</div></div></div> <table><thead><tr><th rowspan="2">Ambient Temperature [°C]</th><th colspan="2">Input Voltage [V]</th></tr><tr><th>Load 50%</th><th>Load 100%</th></tr></thead><tbody><tr><td>-60</td><td>30.8</td><td>30.8</td></tr><tr><td>-40</td><td>30.8</td><td>30.7</td></tr><tr><td>-20</td><td>30.8</td><td>30.7</td></tr><tr><td>0</td><td>30.8</td><td>30.8</td></tr><tr><td>25</td><td>30.8</td><td>30.7</td></tr><tr><td>60</td><td>30.7</td><td>30.7</td></tr><tr><td>65</td><td>30.8</td><td>30.7</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr><tr><td>--</td><td>-</td><td>-</td></tr></tbody></table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-60	30.8	30.8	-40	30.8	30.7	-20	30.8	30.7	0	30.8	30.8	25	30.8	30.7	60	30.7	30.7	65	30.8	30.7	--	-	-	--	-	-	--	-	-	--	-	-		
Ambient Temperature [°C]	Input Voltage [V]																																								
	Load 50%	Load 100%																																							
-60	30.8	30.8																																							
-40	30.8	30.7																																							
-20	30.8	30.7																																							
0	30.8	30.8																																							
25	30.8	30.7																																							
60	30.7	30.7																																							
65	30.8	30.7																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
Note: Slanted line shows the range of the rated ambient temperature.																																									

- 20 -

BC-10466



Model	MGW154812																																																									
Item	Overcurrent Protection	Temperature	25°C																																																							
Object	+12V0.65A	Testing Circuitry	Figure A																																																							
1.Graph		2.Values																																																								
<div><div><div>—△ Input Volt. 36V</div><div>—□ Input Volt. 48V</div><div>—○ Input Volt. 76V</div></div></div>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>12.00</td><td>1.16</td><td>1.25</td><td>1.19</td></tr><tr><td>11.40</td><td>-</td><td>-</td><td>-</td></tr><tr><td>10.80</td><td>-</td><td>-</td><td>-</td></tr><tr><td>9.60</td><td>-</td><td>-</td><td>-</td></tr><tr><td>8.40</td><td>-</td><td>-</td><td>-</td></tr><tr><td>7.20</td><td>-</td><td>-</td><td>-</td></tr><tr><td>6.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>4.80</td><td>-</td><td>-</td><td>-</td></tr><tr><td>3.60</td><td>-</td><td>-</td><td>-</td></tr><tr><td>2.40</td><td>-</td><td>-</td><td>-</td></tr><tr><td>1.20</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	12.00	1.16	1.25	1.19	11.40	-	-	-	10.80	-	-	-	9.60	-	-	-	8.40	-	-	-	7.20	-	-	-	6.00	-	-	-	4.80	-	-	-	3.60	-	-	-	2.40	-	-	-	1.20	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
12.00	1.16	1.25	1.19																																																							
11.40	-	-	-																																																							
10.80	-	-	-																																																							
9.60	-	-	-																																																							
8.40	-	-	-																																																							
7.20	-	-	-																																																							
6.00	-	-	-																																																							
4.80	-	-	-																																																							
3.60	-	-	-																																																							
2.40	-	-	-																																																							
1.20	-	-	-																																																							
0.00	-	-	-																																																							
		-12V: Rated output current																																																								
Object	-12V0.65A																																																									
1.Graph		2.Values																																																								
<div><div><div>—△ Input Volt. 36V</div><div>—□ Input Volt. 48V</div><div>—○ Input Volt. 76V</div></div></div>		<table><tr><th rowspan="2">Output Voltage [V]</th><th colspan="3">Load Current [A]</th></tr><tr><th>Input Volt. 36[V]</th><th>Input Volt. 48[V]</th><th>Input Volt. 76[V]</th></tr><tr><td>-12.00</td><td>1.16</td><td>1.25</td><td>1.19</td></tr><tr><td>-11.40</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-10.80</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-9.60</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-8.40</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-7.20</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-6.00</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-4.80</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-3.60</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-2.40</td><td>-</td><td>-</td><td>-</td></tr><tr><td>-1.20</td><td>-</td><td>-</td><td>-</td></tr><tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr></table>		Output Voltage [V]	Load Current [A]			Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]	-12.00	1.16	1.25	1.19	-11.40	-	-	-	-10.80	-	-	-	-9.60	-	-	-	-8.40	-	-	-	-7.20	-	-	-	-6.00	-	-	-	-4.80	-	-	-	-3.60	-	-	-	-2.40	-	-	-	-1.20	-	-	-	0.00	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 36[V]	Input Volt. 48[V]	Input Volt. 76[V]																																																							
-12.00	1.16	1.25	1.19																																																							
-11.40	-	-	-																																																							
-10.80	-	-	-																																																							
-9.60	-	-	-																																																							
-8.40	-	-	-																																																							
-7.20	-	-	-																																																							
-6.00	-	-	-																																																							
-4.80	-	-	-																																																							
-3.60	-	-	-																																																							
-2.40	-	-	-																																																							
-1.20	-	-	-																																																							
0.00	-	-	-																																																							
		+12V: Rated output current																																																								
Note: Slanted line shows the range of the rated load current.																																																										
Intermittent operation occurs when overcurrent protection is activated.																																																										




Figure A




Figure B (Ripple and Ripple noise Characteristic)