

TEST DATA OF MGW302405

Regulated DC Power Supply
December 7, 2010

Approved by : Kazunari Asano
Kazunari Asano Design Manager

Prepared by : Sho Saito
Sho Saito Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Input Voltage)	1
2. Input Current (by Load Current)	2
3. Input Power (by Load Current)	3
4. Efficiency (by Input Voltage)	4
5. Efficiency (by Load Current)	5
6. Line Regulation	6
7. Load Regulation	7
8. Dynamic Load Response	8
9. Ripple Voltage (by Load Current)	10
10. Ripple-Noise	12
11. Ripple Voltage (by Ambient Temperature)	14
12. Ambient Temperature Drift	15
13. Output Voltage Accuracy	16
14. Time Lapse Drift	17
15. Rise and Fall Time	18
16. Minimum Input Voltage for Regulated Output Voltage	20
17. Overcurrent Protection	21
18. Overvoltage Protection	22
19. Figure of Testing Circuitry	23

(Final Page 23)

Model	MGW302405	Temperature Testing Circuitry	25°C
Item	Input Current (by Input Voltage)		Figure A
Object			
1. Graph		<p>—△— Load 100%</p> <p>- - - □ - - Load 50%</p> <p>- - ○ - - Load 0%</p>	
		2. Values	
Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
4.0	0.001	0.001	0.001
8.0	0.002	0.002	0.002
16.0	0.002	0.002	0.002
16.6	0.027	0.885	1.897
17.0	0.027	0.853	1.833
18.0	0.025	0.801	1.720
20.0	0.023	0.720	1.552
22.0	0.022	0.655	1.406
24.0	0.021	0.604	1.289
28.0	0.017	0.521	1.107
30.0	0.017	0.488	1.034
32.0	0.016	0.458	0.969
36.0	0.015	0.411	0.866
40.0	0.015	0.373	0.780
--	-	-	-
--	-	-	-
--	-	-	-

Model	MGW302405																																																						
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	_____																																																						
1.Graph	<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - - ○ - - Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Current [A] (18V)</th> <th>Input Current [A] (24V)</th> <th>Input Current [A] (36V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.025</td><td>0.021</td><td>0.016</td></tr> <tr><td>20</td><td>0.339</td><td>0.260</td><td>0.181</td></tr> <tr><td>40</td><td>0.651</td><td>0.492</td><td>0.337</td></tr> <tr><td>60</td><td>0.967</td><td>0.727</td><td>0.493</td></tr> <tr><td>80</td><td>1.293</td><td>0.967</td><td>0.651</td></tr> <tr><td>100</td><td>1.619</td><td>1.214</td><td>0.818</td></tr> <tr><td>110</td><td>1.790</td><td>1.339</td><td>0.896</td></tr> </tbody> </table>	Load Ration [%]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)	0	0.025	0.021	0.016	20	0.339	0.260	0.181	40	0.651	0.492	0.337	60	0.967	0.727	0.493	80	1.293	0.967	0.651	100	1.619	1.214	0.818	110	1.790	1.339	0.896																						
Load Ration [%]	Input Current [A] (18V)	Input Current [A] (24V)	Input Current [A] (36V)																																																				
0	0.025	0.021	0.016																																																				
20	0.339	0.260	0.181																																																				
40	0.651	0.492	0.337																																																				
60	0.967	0.727	0.493																																																				
80	1.293	0.967	0.651																																																				
100	1.619	1.214	0.818																																																				
110	1.790	1.339	0.896																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.025</td><td>0.021</td><td>0.016</td></tr> <tr><td>20</td><td>0.339</td><td>0.260</td><td>0.181</td></tr> <tr><td>40</td><td>0.651</td><td>0.492</td><td>0.337</td></tr> <tr><td>60</td><td>0.967</td><td>0.727</td><td>0.493</td></tr> <tr><td>80</td><td>1.293</td><td>0.967</td><td>0.651</td></tr> <tr><td>100</td><td>1.619</td><td>1.214</td><td>0.818</td></tr> <tr><td>110</td><td>1.790</td><td>1.339</td><td>0.896</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ration [%]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.025	0.021	0.016	20	0.339	0.260	0.181	40	0.651	0.492	0.337	60	0.967	0.727	0.493	80	1.293	0.967	0.651	100	1.619	1.214	0.818	110	1.790	1.339	0.896	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Ration [%]	Input Current [A]																																																						
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																				
0	0.025	0.021	0.016																																																				
20	0.339	0.260	0.181																																																				
40	0.651	0.492	0.337																																																				
60	0.967	0.727	0.493																																																				
80	1.293	0.967	0.651																																																				
100	1.619	1.214	0.818																																																				
110	1.790	1.339	0.896																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Model	MGW302405																																																					
Item	Input Power (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - -○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Ration [%]</th> <th>Input Power [W] (18V)</th> <th>Input Power [W] (24V)</th> <th>Input Power [W] (36V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.45</td><td>0.49</td><td>0.56</td></tr> <tr><td>20</td><td>6.12</td><td>6.22</td><td>6.51</td></tr> <tr><td>40</td><td>11.71</td><td>11.78</td><td>12.08</td></tr> <tr><td>60</td><td>17.41</td><td>17.45</td><td>17.73</td></tr> <tr><td>80</td><td>23.24</td><td>23.22</td><td>23.45</td></tr> <tr><td>100</td><td>29.18</td><td>29.13</td><td>29.29</td></tr> <tr><td>110</td><td>32.20</td><td>32.12</td><td>32.24</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W] (18V)	Input Power [W] (24V)	Input Power [W] (36V)	0	0.45	0.49	0.56	20	6.12	6.22	6.51	40	11.71	11.78	12.08	60	17.41	17.45	17.73	80	23.24	23.22	23.45	100	29.18	29.13	29.29	110	32.20	32.12	32.24																			
Load Ration [%]	Input Power [W] (18V)	Input Power [W] (24V)	Input Power [W] (36V)																																																			
0	0.45	0.49	0.56																																																			
20	6.12	6.22	6.51																																																			
40	11.71	11.78	12.08																																																			
60	17.41	17.45	17.73																																																			
80	23.24	23.22	23.45																																																			
100	29.18	29.13	29.29																																																			
110	32.20	32.12	32.24																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.45</td><td>0.49</td><td>0.56</td></tr> <tr><td>20</td><td>6.12</td><td>6.22</td><td>6.51</td></tr> <tr><td>40</td><td>11.71</td><td>11.78</td><td>12.08</td></tr> <tr><td>60</td><td>17.41</td><td>17.45</td><td>17.73</td></tr> <tr><td>80</td><td>23.24</td><td>23.22</td><td>23.45</td></tr> <tr><td>100</td><td>29.18</td><td>29.13</td><td>29.29</td></tr> <tr><td>110</td><td>32.20</td><td>32.12</td><td>32.24</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.45	0.49	0.56	20	6.12	6.22	6.51	40	11.71	11.78	12.08	60	17.41	17.45	17.73	80	23.24	23.22	23.45	100	29.18	29.13	29.29	110	32.20	32.12	32.24	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Input Power [W]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0	0.45	0.49	0.56																																																			
20	6.12	6.22	6.51																																																			
40	11.71	11.78	12.08																																																			
60	17.41	17.45	17.73																																																			
80	23.24	23.22	23.45																																																			
100	29.18	29.13	29.29																																																			
110	32.20	32.12	32.24																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Model	MGW302405																																	
Item	Efficiency (by Input Voltage)	Temperature Testing Circuitry 25°C Figure A																																
Object	—	—																																
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>17</td><td>87.1</td><td>86.5</td> </tr> <tr> <td>18</td><td>87.5</td><td>87.0</td> </tr> <tr> <td>20</td><td>87.7</td><td>87.1</td> </tr> <tr> <td>24</td><td>87.1</td><td>87.1</td> </tr> <tr> <td>30</td><td>86.3</td><td>87.1</td> </tr> <tr> <td>36</td><td>85.3</td><td>86.7</td> </tr> <tr> <td>40</td><td>84.6</td><td>86.4</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	87.1	86.5	18	87.5	87.0	20	87.7	87.1	24	87.1	87.1	30	86.3	87.1	36	85.3	86.7	40	84.6	86.4	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	87.1	86.5																																
18	87.5	87.0																																
20	87.7	87.1																																
24	87.1	87.1																																
30	86.3	87.1																																
36	85.3	86.7																																
40	84.6	86.4																																
--	-	-																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	MGW302405																																																					
Item	Efficiency (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 18V - - -□--- Input Volt. 24V - - ○--- Input Volt. 36V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Ration [%]</th> <th>18V [Efficiency %]</th> <th>24V [Efficiency %]</th> <th>36V [Efficiency %]</th> </tr> </thead> <tbody> <tr><td>20</td><td>82.0</td><td>80.0</td><td>78.0</td></tr> <tr><td>40</td><td>84.0</td><td>83.0</td><td>82.0</td></tr> <tr><td>60</td><td>86.0</td><td>85.0</td><td>84.0</td></tr> <tr><td>80</td><td>87.0</td><td>86.0</td><td>85.0</td></tr> <tr><td>100</td><td>87.0</td><td>87.0</td><td>87.0</td></tr> <tr><td>120</td><td>87.0</td><td>87.0</td><td>87.0</td></tr> </tbody> </table>			Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]	20	82.0	80.0	78.0	40	84.0	83.0	82.0	60	86.0	85.0	84.0	80	87.0	86.0	85.0	100	87.0	87.0	87.0	120	87.0	87.0	87.0																							
Load Ration [%]	18V [Efficiency %]	24V [Efficiency %]	36V [Efficiency %]																																																			
20	82.0	80.0	78.0																																																			
40	84.0	83.0	82.0																																																			
60	86.0	85.0	84.0																																																			
80	87.0	86.0	85.0																																																			
100	87.0	87.0	87.0																																																			
120	87.0	87.0	87.0																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ration [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>82.7</td><td>81.5</td><td>77.9</td></tr> <tr><td>40</td><td>86.6</td><td>86.1</td><td>84.0</td></tr> <tr><td>60</td><td>87.5</td><td>87.3</td><td>85.9</td></tr> <tr><td>80</td><td>87.3</td><td>87.4</td><td>86.6</td></tr> <tr><td>100</td><td>87.0</td><td>87.1</td><td>86.7</td></tr> <tr><td>110</td><td>86.7</td><td>86.9</td><td>86.6</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Ration [%]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	20	82.7	81.5	77.9	40	86.6	86.1	84.0	60	87.5	87.3	85.9	80	87.3	87.4	86.6	100	87.0	87.1	86.7	110	86.7	86.9	86.6	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ration [%]	Efficiency [%]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
0	-	-	-																																																			
20	82.7	81.5	77.9																																																			
40	86.6	86.1	84.0																																																			
60	87.5	87.3	85.9																																																			
80	87.3	87.4	86.6																																																			
100	87.0	87.1	86.7																																																			
110	86.7	86.9	86.6																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Model	MGW302405
Item	Line Regulation
Object	+5V2.5A

Temperature 25°C
Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	5.132	5.072
18	5.131	5.073
20	5.129	5.073
24	5.126	5.073
30	5.124	5.073
36	5.122	5.073
40	5.122	5.072
--	-	-
--	-	-

-5V: Rated output current

Object	-5V2.5A
--------	---------

1.Graph




2.Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	-5.139	-5.075
18	-5.137	-5.075
20	-5.134	-5.075
24	-5.131	-5.076
30	-5.129	-5.076
36	-5.128	-5.076
40	-5.127	-5.076
--	-	-
--	-	-

+5V: Rated output current

Note: Slanted line shows the range of the rated input voltage.

Model	MGW302405	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Load Regulation																																																				
Object	+5V2.5A																																																				
1.Graph	<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - · -○- - Input Volt. 36V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5.638</td><td>5.671</td><td>5.724</td></tr> <tr><td>0.125</td><td>5.209</td><td>5.206</td><td>5.218</td></tr> <tr><td>0.500</td><td>5.180</td><td>5.176</td><td>5.173</td></tr> <tr><td>1.000</td><td>5.146</td><td>5.142</td><td>5.139</td></tr> <tr><td>1.500</td><td>5.120</td><td>5.117</td><td>5.114</td></tr> <tr><td>2.000</td><td>5.096</td><td>5.095</td><td>5.093</td></tr> <tr><td>2.500</td><td>5.073</td><td>5.073</td><td>5.072</td></tr> <tr><td>2.750</td><td>5.061</td><td>5.062</td><td>5.062</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	5.638	5.671	5.724	0.125	5.209	5.206	5.218	0.500	5.180	5.176	5.173	1.000	5.146	5.142	5.139	1.500	5.120	5.117	5.114	2.000	5.096	5.095	5.093	2.500	5.073	5.073	5.072	2.750	5.061	5.062	5.062	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.000	5.638	5.671	5.724																																																		
0.125	5.209	5.206	5.218																																																		
0.500	5.180	5.176	5.173																																																		
1.000	5.146	5.142	5.139																																																		
1.500	5.120	5.117	5.114																																																		
2.000	5.096	5.095	5.093																																																		
2.500	5.073	5.073	5.072																																																		
2.750	5.061	5.062	5.062																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
		-5V: Rated output current																																																			
Object	-5V2.5A	2.Values																																																			
1.Graph	<p>—△— Input Volt. 18V - - -□- - Input Volt. 24V - · -○- - Input Volt. 36V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-5.598</td><td>-5.627</td><td>-5.662</td></tr> <tr><td>0.125</td><td>-5.210</td><td>-5.206</td><td>-5.217</td></tr> <tr><td>0.500</td><td>-5.185</td><td>-5.178</td><td>-5.174</td></tr> <tr><td>1.000</td><td>-5.151</td><td>-5.146</td><td>-5.142</td></tr> <tr><td>1.500</td><td>-5.124</td><td>-5.120</td><td>-5.118</td></tr> <tr><td>2.000</td><td>-5.099</td><td>-5.098</td><td>-5.096</td></tr> <tr><td>2.500</td><td>-5.075</td><td>-5.075</td><td>-5.076</td></tr> <tr><td>2.750</td><td>-5.063</td><td>-5.065</td><td>-5.066</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	-5.598	-5.627	-5.662	0.125	-5.210	-5.206	-5.217	0.500	-5.185	-5.178	-5.174	1.000	-5.151	-5.146	-5.142	1.500	-5.124	-5.120	-5.118	2.000	-5.099	-5.098	-5.096	2.500	-5.075	-5.075	-5.076	2.750	-5.063	-5.065	-5.066	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.000	-5.598	-5.627	-5.662																																																		
0.125	-5.210	-5.206	-5.217																																																		
0.500	-5.185	-5.178	-5.174																																																		
1.000	-5.151	-5.146	-5.142																																																		
1.500	-5.124	-5.120	-5.118																																																		
2.000	-5.099	-5.098	-5.096																																																		
2.500	-5.075	-5.075	-5.076																																																		
2.750	-5.063	-5.065	-5.066																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
		+5V: Rated output current																																																			
Note: Slanted line shows the range of the rated load current.																																																					





COSSEL

Model	MGW302405	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																						
Object	+5V2.5A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>2</td></tr> <tr><td>0.50</td><td>4</td><td>6</td></tr> <tr><td>1.00</td><td>4</td><td>6</td></tr> <tr><td>1.50</td><td>4</td><td>6</td></tr> <tr><td>2.00</td><td>5</td><td>6</td></tr> <tr><td>2.50</td><td>5</td><td>6</td></tr> <tr><td>2.75</td><td>5</td><td>6</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-5V: Rated output current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.00	2	2	0.50	4	6	1.00	4	6	1.50	4	6	2.00	5	6	2.50	5	6	2.75	5	6	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 18 [V]	Input Volt. 36 [V]																																							
0.00	2	2																																							
0.50	4	6																																							
1.00	4	6																																							
1.50	4	6																																							
2.00	5	6																																							
2.50	5	6																																							
2.75	5	6																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Wave Form</p>																																									

Model	MGW302405	Temperature	25°C																																					
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure B																																					
Object	-5V2.5A																																							
1.Graph			2.Values																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>2</td><td>3</td></tr> <tr><td>0.50</td><td>2</td><td>4</td></tr> <tr><td>1.00</td><td>2</td><td>4</td></tr> <tr><td>1.50</td><td>2</td><td>4</td></tr> <tr><td>2.00</td><td>3</td><td>4</td></tr> <tr><td>2.50</td><td>3</td><td>4</td></tr> <tr><td>2.75</td><td>3</td><td>4</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.00	2	3	0.50	2	4	1.00	2	4	1.50	2	4	2.00	3	4	2.50	3	4	2.75	3	4	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.00	2	3																																						
0.50	2	4																																						
1.00	2	4																																						
1.50	2	4																																						
2.00	3	4																																						
2.50	3	4																																						
2.75	3	4																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>+5V: Rated output current</p> <p>Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Fig.Complex Ripple Wave Form</p>																																								


Model	MGW302405	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure B																																						
Object	+5V2.5A																																								
1.Graph			2.Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.50</td><td>10</td><td>10</td></tr> <tr><td>1.00</td><td>10</td><td>10</td></tr> <tr><td>1.50</td><td>10</td><td>10</td></tr> <tr><td>2.00</td><td>10</td><td>10</td></tr> <tr><td>2.50</td><td>10</td><td>10</td></tr> <tr><td>2.75</td><td>10</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-5V: Rated output current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.00	5	5	0.50	10	10	1.00	10	10	1.50	10	10	2.00	10	10	2.50	10	10	2.75	10	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 18 [V]	Input Volt. 36 [V]																																							
0.00	5	5																																							
0.50	10	10																																							
1.00	10	10																																							
1.50	10	10																																							
2.00	10	10																																							
2.50	10	10																																							
2.75	10	10																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
--	-	-																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig.Complex Ripple Noise Wave Form</p>																																									

Model	MGW302405	Temperature	25°C																																								
Item	Ripple-Noise	Testing Circuitry	Figure B																																								
Object	-5V2.5A	2. Values																																									
1. Graph																																											
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.50</td><td>5</td><td>10</td></tr> <tr><td>1.00</td><td>5</td><td>10</td></tr> <tr><td>1.50</td><td>5</td><td>10</td></tr> <tr><td>2.00</td><td>5</td><td>10</td></tr> <tr><td>2.50</td><td>5</td><td>10</td></tr> <tr><td>2.75</td><td>5</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.00	5	5	0.50	5	10	1.00	5	10	1.50	5	10	2.00	5	10	2.50	5	10	2.75	5	10	--	-	-	--	-	-	--	-	-	--	-	-	+5V: Rated output current		
Load Current [A]	Ripple-Noise [mV]																																										
	Input Volt. 18 [V]	Input Volt. 36 [V]																																									
0.00	5	5																																									
0.50	5	10																																									
1.00	5	10																																									
1.50	5	10																																									
2.00	5	10																																									
2.50	5	10																																									
2.75	5	10																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
--	-	-																																									
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																											
<p>Fig.Complex Ripple Noise Wave Form</p>																																											

Model	MGW302405
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V2.5A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	19	20
-40	13	13
-20	9	10
0	8	9
25	6	7
60	5	5
65	5	5
--	-	-
--	-	-
--	-	-
--	-	-

-5V: Rated output current

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	11	11
-40	7	8
-20	6	6
0	5	5
25	4	4
60	3	4
65	3	4
--	-	-
--	-	-
--	-	-
--	-	-


+5V: Rated output current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Model	MGW302405
Item	Ambient Temperature Drift
Object	+5V2.5A

Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt.	Input Volt.	Input Volt.
18[V]	24[V]	36[V]	
-60	5.050	5.051	5.052
-40	5.059	5.059	5.060
-20	5.065	5.065	5.066
0	5.070	5.070	5.070
25	5.073	5.073	5.072
60	5.075	5.075	5.074
65	5.075	5.074	5.073
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt.	Input Volt.	Input Volt.
18[V]	24[V]	36[V]	
-60	-5.047	-5.050	-5.052
-40	-5.057	-5.058	-5.060
-20	-5.063	-5.065	-5.066
0	-5.069	-5.070	-5.071
25	-5.075	-5.075	-5.076
60	-5.076	-5.077	-5.077
65	-5.076	-5.076	-5.077
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGW302405	Testing Circuitry Figure A
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 60°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 2.5A (AVR 2) : 0 - 2.5A

* Other Output : Rated Load

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$



$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object	+5V2.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-40	36		0	5.757	
Minimum Voltage	-40	18	2.5	5.059	±349	±7.0

Object	-5V2.5A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	36		0	-5.687	
Minimum Voltage	-40	18	2.5	-5.057	±315	±6.3

COSEL


Model	MGW302405	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+5V2.5A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.073</td></tr> <tr><td>0.5</td><td>5.086</td></tr> <tr><td>1.0</td><td>5.085</td></tr> <tr><td>2.0</td><td>5.085</td></tr> <tr><td>3.0</td><td>5.085</td></tr> <tr><td>4.0</td><td>5.084</td></tr> <tr><td>5.0</td><td>5.083</td></tr> <tr><td>6.0</td><td>5.083</td></tr> <tr><td>7.0</td><td>5.083</td></tr> <tr><td>8.0</td><td>5.083</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.073	0.5	5.086	1.0	5.085	2.0	5.085	3.0	5.085	4.0	5.084	5.0	5.083	6.0	5.083	7.0	5.083	8.0	5.083
Time since start [H]	Output Voltage [V]																								
0.0	5.073																								
0.5	5.086																								
1.0	5.085																								
2.0	5.085																								
3.0	5.085																								
4.0	5.084																								
5.0	5.083																								
6.0	5.083																								
7.0	5.083																								
8.0	5.083																								
Object			2.Values																						
1.Graph			 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V Load 100%</p>																						
<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-5.075</td></tr> <tr><td>0.5</td><td>-5.093</td></tr> <tr><td>1.0</td><td>-5.094</td></tr> <tr><td>2.0</td><td>-5.094</td></tr> <tr><td>3.0</td><td>-5.094</td></tr> <tr><td>4.0</td><td>-5.094</td></tr> <tr><td>5.0</td><td>-5.096</td></tr> <tr><td>6.0</td><td>-5.095</td></tr> <tr><td>7.0</td><td>-5.096</td></tr> <tr><td>8.0</td><td>-5.095</td></tr> </tbody> </table>			Time since start [H]	Output Voltage [V]	0.0	-5.075	0.5	-5.093	1.0	-5.094	2.0	-5.094	3.0	-5.094	4.0	-5.094	5.0	-5.096	6.0	-5.095	7.0	-5.096	8.0	-5.095	
Time since start [H]	Output Voltage [V]																								
0.0	-5.075																								
0.5	-5.093																								
1.0	-5.094																								
2.0	-5.094																								
3.0	-5.094																								
4.0	-5.094																								
5.0	-5.096																								
6.0	-5.095																								
7.0	-5.096																								
8.0	-5.095																								

COSEL

Model	MGW302405
Item	Rise and Fall Time
Object	+5V2.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.3	8.2	10.5	0.1	0.6	
100 %		2.3	8.0	10.3	0.1	0.4	




COSEL

Model	MGW302405
Item	Rise and Fall Time
Object	-5V2.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		2.3	7.9	10.2	0.1	0.8	
100 %		2.3	7.8	10.1	0.1	0.5	



Model	MGW302405
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V2.5A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.7	15.8
-40	15.7	15.8
-20	15.7	15.8
0	15.7	15.8
25	15.7	15.8
60	15.7	15.8
65	15.7	15.7
--	-	-
--	-	-
--	-	-
--	-	-

Object	-5V2.5A
--------	---------

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.6	15.7
-40	15.6	15.7
-20	15.6	15.6
0	15.6	15.7
25	15.6	15.7
60	15.6	15.6
65	15.6	15.6
--	-	-
--	-	-
--	-	-
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

Model	MGW302405	Temperature Testing Circuitry 25°C Figure A
Item	Overcurrent Protection	
Object	+5V2.5A	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values
Object	-5V2.5A	
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p>	2.Values
Note: Slanted line shows the range of the rated load current.		
Intermittent operation occurs when overcurrent protection is activated.		

Model	MGW302405
Item	Oversupply Protection
Object	+10V2.5A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 24[V]	Input Volt. 36[V]
-60	13.26	13.26
-40	13.33	13.33
-20	13.48	13.48
0	13.62	13.62
25	13.83	13.83
60	14.05	14.12
65	14.12	14.12
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

Measured as a single output(+10V).

COSEL




Figure A




Figure B (Ripple and Ripple noise Characteristic)