

TEST DATA OF MGW62412

Regulated DC Power Supply
October 27, 2016

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Takaaki Sekiguchi
Takaaki Sekiguchi Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Ratio (by Load Ratio)	2
3.Input Power (by Load Ratio)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Ratio)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Switching Frequency (by Load Current)	22
19.Figure of Testing Circuitry	23

(Final Page 23)



Model		MGW62412		Temperature 25°C																																																																																
Item		Input Current (by Input Voltage)		Testing Circuitry Figure A																																																																																
Object		_____																																																																																		
1.Graph			—△— Load 100% - - - □ - - Load 50% · · · ○ · · · Load 0%																																																																																	
			2.Values																																																																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Load 0%</th> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.000</td><td>0.000</td><td>0.000</td></tr> <tr><td>16.0</td><td>0.004</td><td>0.004</td><td>0.003</td></tr> <tr><td>16.2</td><td>0.003</td><td>0.003</td><td>0.004</td></tr> <tr><td>16.4</td><td>0.004</td><td>0.003</td><td>0.003</td></tr> <tr><td>16.5</td><td>0.017</td><td>0.213</td><td>0.419</td></tr> <tr><td>16.6</td><td>0.016</td><td>0.211</td><td>0.417</td></tr> <tr><td>17.0</td><td>0.016</td><td>0.206</td><td>0.407</td></tr> <tr><td>18.0</td><td>0.016</td><td>0.195</td><td>0.384</td></tr> <tr><td>22.0</td><td>0.013</td><td>0.161</td><td>0.314</td></tr> <tr><td>24.0</td><td>0.012</td><td>0.147</td><td>0.288</td></tr> <tr><td>28.0</td><td>0.010</td><td>0.127</td><td>0.247</td></tr> <tr><td>32.0</td><td>0.007</td><td>0.113</td><td>0.217</td></tr> <tr><td>36.0</td><td>0.006</td><td>0.101</td><td>0.193</td></tr> <tr><td>40.0</td><td>0.005</td><td>0.092</td><td>0.176</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Input Current [A]			Load 0%	Load 50%	Load 100%	0.0	0.000	0.000	0.000	16.0	0.004	0.004	0.003	16.2	0.003	0.003	0.004	16.4	0.004	0.003	0.003	16.5	0.017	0.213	0.419	16.6	0.016	0.211	0.417	17.0	0.016	0.206	0.407	18.0	0.016	0.195	0.384	22.0	0.013	0.161	0.314	24.0	0.012	0.147	0.288	28.0	0.010	0.127	0.247	32.0	0.007	0.113	0.217	36.0	0.006	0.101	0.193	40.0	0.005	0.092	0.176	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Input Voltage [V]	Input Current [A]																																																																																			
	Load 0%	Load 50%	Load 100%																																																																																	
0.0	0.000	0.000	0.000																																																																																	
16.0	0.004	0.004	0.003																																																																																	
16.2	0.003	0.003	0.004																																																																																	
16.4	0.004	0.003	0.003																																																																																	
16.5	0.017	0.213	0.419																																																																																	
16.6	0.016	0.211	0.417																																																																																	
17.0	0.016	0.206	0.407																																																																																	
18.0	0.016	0.195	0.384																																																																																	
22.0	0.013	0.161	0.314																																																																																	
24.0	0.012	0.147	0.288																																																																																	
28.0	0.010	0.127	0.247																																																																																	
32.0	0.007	0.113	0.217																																																																																	
36.0	0.006	0.101	0.193																																																																																	
40.0	0.005	0.092	0.176																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
--	-	-	-																																																																																	
Note: Slanted line shows the range of the rated input voltage.																																																																																				



<p>Model MGW62412</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item</p>	<p>Input Current (by Load Ratio)</p>																																																				
<p>Object</p>	<p>_____</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.016</td><td>0.012</td><td>0.006</td></tr> <tr><td>20</td><td>0.087</td><td>0.067</td><td>0.047</td></tr> <tr><td>40</td><td>0.159</td><td>0.120</td><td>0.083</td></tr> <tr><td>60</td><td>0.230</td><td>0.175</td><td>0.119</td></tr> <tr><td>80</td><td>0.307</td><td>0.230</td><td>0.155</td></tr> <tr><td>100</td><td>0.384</td><td>0.288</td><td>0.193</td></tr> <tr><td>110</td><td>0.419</td><td>0.311</td><td>0.211</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ratio [%]	Input Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.016	0.012	0.006	20	0.087	0.067	0.047	40	0.159	0.120	0.083	60	0.230	0.175	0.119	80	0.307	0.230	0.155	100	0.384	0.288	0.193	110	0.419	0.311	0.211	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Input Current [A]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0	0.016	0.012	0.006																																																		
20	0.087	0.067	0.047																																																		
40	0.159	0.120	0.083																																																		
60	0.230	0.175	0.119																																																		
80	0.307	0.230	0.155																																																		
100	0.384	0.288	0.193																																																		
110	0.419	0.311	0.211																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>1.Graph</p>	<p> —△— Input Volt. 18V - - □ - - Input Volt. 24V - · · ○ · · - Input Volt. 36V </p> <p> Input Current [A] Load Ratio [%] </p>																																																				



<p>Model MGW62412</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
<p>Item</p>	<p>Input Power (by Load Ratio)</p>																																																				
<p>Object</p>	<p>_____</p>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.27</td><td>0.29</td><td>0.21</td></tr> <tr><td>20</td><td>1.56</td><td>1.60</td><td>1.69</td></tr> <tr><td>40</td><td>2.85</td><td>2.89</td><td>2.98</td></tr> <tr><td>60</td><td>4.16</td><td>4.20</td><td>4.27</td></tr> <tr><td>80</td><td>5.48</td><td>5.50</td><td>5.59</td></tr> <tr><td>100</td><td>6.81</td><td>6.82</td><td>6.88</td></tr> <tr><td>110</td><td>7.48</td><td>7.50</td><td>7.57</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Ratio [%]	Input Power [W]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	0.27	0.29	0.21	20	1.56	1.60	1.69	40	2.85	2.89	2.98	60	4.16	4.20	4.27	80	5.48	5.50	5.59	100	6.81	6.82	6.88	110	7.48	7.50	7.57	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Input Power [W]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0	0.27	0.29	0.21																																																		
20	1.56	1.60	1.69																																																		
40	2.85	2.89	2.98																																																		
60	4.16	4.20	4.27																																																		
80	5.48	5.50	5.59																																																		
100	6.81	6.82	6.88																																																		
110	7.48	7.50	7.57																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>1.Graph</p> <p> —△— Input Volt. 18V - - - □ - - - Input Volt. 24V - · - ○ - · - - Input Volt. 36V </p> <p>Input Power [W]</p> <p>Load Ratio [%]</p>																																																					



COSEL																																		
Model	MGW62412																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p> <p>Note: Slanted line shows the range of the rated input voltage.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>17</td><td>86.2</td><td>88.8</td></tr> <tr><td>18</td><td>86.1</td><td>88.7</td></tr> <tr><td>20</td><td>85.8</td><td>88.8</td></tr> <tr><td>24</td><td>84.9</td><td>88.6</td></tr> <tr><td>30</td><td>84.3</td><td>88.5</td></tr> <tr><td>36</td><td>83.0</td><td>87.8</td></tr> <tr><td>40</td><td>81.8</td><td>86.9</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	17	86.2	88.8	18	86.1	88.7	20	85.8	88.8	24	84.9	88.6	30	84.3	88.5	36	83.0	87.8	40	81.8	86.9	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
17	86.2	88.8																																
18	86.1	88.7																																
20	85.8	88.8																																
24	84.9	88.6																																
30	84.3	88.5																																
36	83.0	87.8																																
40	81.8	86.9																																
--	-	-																																
--	-	-																																




Model		MGW62412		Temperature 25°C																																																				
Item		Efficiency (by Load Ratio)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		<p>—△— Input Volt. 18V</p> <p>- - □ - - Input Volt. 24V</p> <p>- · · ○ · · Input Volt. 36V</p>		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>20</td><td>76.9</td><td>74.9</td><td>71.0</td></tr> <tr><td>40</td><td>84.3</td><td>83.6</td><td>80.9</td></tr> <tr><td>60</td><td>86.9</td><td>86.2</td><td>84.7</td></tr> <tr><td>80</td><td>88.1</td><td>87.9</td><td>86.4</td></tr> <tr><td>100</td><td>88.7</td><td>88.6</td><td>87.8</td></tr> <tr><td>110</td><td>88.8</td><td>88.7</td><td>87.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Ratio [%]	Efficiency [%]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0	-	-	-	20	76.9	74.9	71.0	40	84.3	83.6	80.9	60	86.9	86.2	84.7	80	88.1	87.9	86.4	100	88.7	88.6	87.8	110	88.8	88.7	87.7	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Ratio [%]	Efficiency [%]																																																							
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																					
0	-	-	-																																																					
20	76.9	74.9	71.0																																																					
40	84.3	83.6	80.9																																																					
60	86.9	86.2	84.7																																																					
80	88.1	87.9	86.4																																																					
100	88.7	88.6	87.8																																																					
110	88.8	88.7	87.7																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model	MGW62412
Item	Line Regulation
Object	+12V0.25A

Temperature	25°C
Testing Circuitry	Figure A




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	12.136	12.075
18	12.136	12.075
20	12.135	12.075
24	12.133	12.075
30	12.132	12.075
36	12.130	12.075
40	12.130	12.075
--	-	-
--	-	-

-12V: Rated Load Current

Object	-12V0.25A
--------	-----------




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
17	-12.139	-12.076
18	-12.139	-12.076
20	-12.138	-12.076
24	-12.137	-12.076
30	-12.135	-12.076
36	-12.133	-12.076
40	-12.133	-12.076
--	-	-
--	-	-

+12V: Rated Load Current

Note: Slanted line shows the range of the rated input voltage.




Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	12.317	12.309	12.295
0.050	12.192	12.190	12.185
0.100	12.151	12.149	12.145
0.150	12.122	12.120	12.118
0.200	12.097	12.096	12.095
0.250	12.075	12.075	12.075
0.275	12.064	12.064	12.065
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

-12V: Rated Load Current



2.Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]
0.000	-12.324	-12.314	-12.299
0.050	-12.198	-12.195	-12.190
0.100	-12.154	-12.151	-12.148
0.150	-12.124	-12.122	-12.120
0.200	-12.099	-12.098	-12.096
0.250	-12.076	-12.076	-12.076
0.275	-12.065	-12.065	-12.065
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

+12V: Rated Load Current




Model	MGW62412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V0.25A		

Input Volt. 24 V
 -12V:rated load current.
 Cycle 100 ms




Min.Load (0A) ←→
 Load 100% (0.25A)

200 mV/div




4 ms/div




4 ms/div

Min.Load (0A) ←→
 Load 50% (0.125A)

200 mV/div




4 ms/div




4 ms/div

Load 50% (0.125A) ←→
 Load 100% (0.25A)

200 mV/div



4 ms/div



4 ms/div



Model	MGW62412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V0.25A		


Input Volt. 24 V
 +12V:rated load current.
 Cycle 100 ms

$t_1, t_2 = 100 \mu s$




Min.Load (0A) ←→
 Load 100% (0.25A)

200 mV/div




4 ms/div




4 ms/div

Min.Load (0A) ←→
 Load 50% (0.125A)

200 mV/div




4 ms/div




4 ms/div

Load 50% (0.125A) ←→
 Load 100% (0.25A)

200 mV/div



4 ms/div



4 ms/div



<p>Model MGW62412</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
Item	Ripple Voltage (by Load Current)																																							
Object	+12V0.25A																																							
<p>1.Graph</p> <p>—△— Input Volt. 18V - -○- - Input Volt. 36V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.050</td><td>5</td><td>5</td></tr> <tr><td>0.100</td><td>5</td><td>5</td></tr> <tr><td>0.150</td><td>5</td><td>5</td></tr> <tr><td>0.200</td><td>10</td><td>5</td></tr> <tr><td>0.250</td><td>10</td><td>5</td></tr> <tr><td>0.275</td><td>15</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.000	5	5	0.050	5	5	0.100	5	5	0.150	5	5	0.200	10	5	0.250	10	5	0.275	15	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.050	5	5																																						
0.100	5	5																																						
0.150	5	5																																						
0.200	10	5																																						
0.250	10	5																																						
0.275	15	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								



<p>Model MGW62412</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
Item	Ripple Voltage (by Load Current)																																							
Object	-12V0.25A																																							
<p>1.Graph</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.050</td><td>5</td><td>5</td></tr> <tr><td>0.100</td><td>5</td><td>5</td></tr> <tr><td>0.150</td><td>5</td><td>5</td></tr> <tr><td>0.200</td><td>10</td><td>5</td></tr> <tr><td>0.250</td><td>10</td><td>5</td></tr> <tr><td>0.275</td><td>15</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.000	5	5	0.050	5	5	0.100	5	5	0.150	5	5	0.200	10	5	0.250	10	5	0.275	15	5	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.050	5	5																																						
0.100	5	5																																						
0.150	5	5																																						
0.200	10	5																																						
0.250	10	5																																						
0.275	15	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								



<p>Model MGW62412</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object +12V0.25A</p>																																								
<p>1.Graph</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.050</td><td>5</td><td>5</td></tr> <tr><td>0.100</td><td>5</td><td>5</td></tr> <tr><td>0.150</td><td>10</td><td>5</td></tr> <tr><td>0.200</td><td>10</td><td>10</td></tr> <tr><td>0.250</td><td>15</td><td>10</td></tr> <tr><td>0.275</td><td>15</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.000	5	5	0.050	5	5	0.100	5	5	0.150	10	5	0.200	10	10	0.250	15	10	0.275	15	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.050	5	5																																						
0.100	5	5																																						
0.150	10	5																																						
0.200	10	10																																						
0.250	15	10																																						
0.275	15	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								



<p>Model MGW62412</p>		<p>Temperature 25°C Testing Circuitry Figure B</p>																																						
<p>Item Ripple-Noise</p>																																								
<p>Object -12V0.25A</p>																																								
<p>1.Graph</p> <p> —△— Input Volt. 18V -·-○-·- Input Volt. 36V </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 18 [V]</th> <th>Input Volt. 36 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5</td><td>5</td></tr> <tr><td>0.050</td><td>5</td><td>5</td></tr> <tr><td>0.100</td><td>5</td><td>5</td></tr> <tr><td>0.150</td><td>10</td><td>5</td></tr> <tr><td>0.200</td><td>10</td><td>10</td></tr> <tr><td>0.250</td><td>15</td><td>10</td></tr> <tr><td>0.275</td><td>15</td><td>10</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 18 [V]	Input Volt. 36 [V]	0.000	5	5	0.050	5	5	0.100	5	5	0.150	10	5	0.200	10	10	0.250	15	10	0.275	15	10	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 18 [V]	Input Volt. 36 [V]																																						
0.000	5	5																																						
0.050	5	5																																						
0.100	5	5																																						
0.150	10	5																																						
0.200	10	10																																						
0.250	15	10																																						
0.275	15	10																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 100 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>Ripple Noise[mVp-p]</p>																																								
<p>Fig.Complex Ripple Noise Wave Form</p>																																								



COSEL																																								
Model	MGW62412																																							
Item	Ripple Voltage (by Ambient Temp.)	Testing Circuitry Figure B																																						
Object	+12V0.25A																																							
<p>1.Graph</p> <p style="text-align: center;">Input Volt. 24V</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>5</td><td>10</td></tr> <tr><td>-40</td><td>5</td><td>10</td></tr> <tr><td>-20</td><td>5</td><td>10</td></tr> <tr><td>0</td><td>5</td><td>5</td></tr> <tr><td>25</td><td>5</td><td>5</td></tr> <tr><td>80</td><td>5</td><td>5</td></tr> <tr><td>85</td><td>5</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated Load Current</p>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	5	10	-40	5	10	-20	5	10	0	5	5	25	5	5	80	5	5	85	5	5	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	5	10																																						
-40	5	10																																						
-20	5	10																																						
0	5	5																																						
25	5	5																																						
80	5	5																																						
85	5	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
Object	-12V0.25A																																							
<p>1.Graph</p> <p style="text-align: center;">Input Volt. 24V</p> <p>Measured by 100 MHz Oscilloscope. Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-60</td><td>5</td><td>10</td></tr> <tr><td>-40</td><td>5</td><td>10</td></tr> <tr><td>-20</td><td>5</td><td>10</td></tr> <tr><td>0</td><td>5</td><td>5</td></tr> <tr><td>25</td><td>5</td><td>5</td></tr> <tr><td>80</td><td>5</td><td>5</td></tr> <tr><td>85</td><td>5</td><td>5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated Load Current</p>	Ambient Temperature [°C]	Ripple Voltage [mV]		Load 50%	Load 100%	-60	5	10	-40	5	10	-20	5	10	0	5	5	25	5	5	80	5	5	85	5	5	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																							
	Load 50%	Load 100%																																						
-60	5	10																																						
-40	5	10																																						
-20	5	10																																						
0	5	5																																						
25	5	5																																						
80	5	5																																						
85	5	5																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						



<p>Model MGW62412</p>																																																						
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																				
Object	+12V0.25A																																																					
<p>1.Graph</p> <p> —△— Input Volt. 18V - - - □ - - - Input Volt. 24V · · · ○ · · · Input Volt. 36V </p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>12.016</td><td>12.013</td><td>12.037</td></tr> <tr><td>-40</td><td>12.037</td><td>12.037</td><td>12.037</td></tr> <tr><td>-20</td><td>12.055</td><td>12.055</td><td>12.054</td></tr> <tr><td>0</td><td>12.067</td><td>12.067</td><td>12.067</td></tr> <tr><td>25</td><td>12.075</td><td>12.075</td><td>12.075</td></tr> <tr><td>80</td><td>12.075</td><td>12.075</td><td>12.075</td></tr> <tr><td>85</td><td>12.073</td><td>12.074</td><td>12.073</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	12.016	12.013	12.037	-40	12.037	12.037	12.037	-20	12.055	12.055	12.054	0	12.067	12.067	12.067	25	12.075	12.075	12.075	80	12.075	12.075	12.075	85	12.073	12.074	12.073	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
-60	12.016	12.013	12.037																																																			
-40	12.037	12.037	12.037																																																			
-20	12.055	12.055	12.054																																																			
0	12.067	12.067	12.067																																																			
25	12.075	12.075	12.075																																																			
80	12.075	12.075	12.075																																																			
85	12.073	12.074	12.073																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Object	-12V0.25A																																																					
<p>1.Graph</p> <p> —△— Input Volt. 18V - - - □ - - - Input Volt. 24V · · · ○ · · · Input Volt. 36V </p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-60</td><td>-11.990</td><td>-12.010</td><td>-12.012</td></tr> <tr><td>-40</td><td>-12.036</td><td>-12.036</td><td>-12.036</td></tr> <tr><td>-20</td><td>-12.054</td><td>-12.054</td><td>-12.054</td></tr> <tr><td>0</td><td>-12.067</td><td>-12.067</td><td>-12.067</td></tr> <tr><td>25</td><td>-12.076</td><td>-12.076</td><td>-12.076</td></tr> <tr><td>80</td><td>-12.076</td><td>-12.077</td><td>-12.076</td></tr> <tr><td>85</td><td>-12.075</td><td>-12.075</td><td>-12.075</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>		Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-60	-11.990	-12.010	-12.012	-40	-12.036	-12.036	-12.036	-20	-12.054	-12.054	-12.054	0	-12.067	-12.067	-12.067	25	-12.076	-12.076	-12.076	80	-12.076	-12.077	-12.076	85	-12.075	-12.075	-12.075	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																			
-60	-11.990	-12.010	-12.012																																																			
-40	-12.036	-12.036	-12.036																																																			
-20	-12.054	-12.054	-12.054																																																			
0	-12.067	-12.067	-12.067																																																			
25	-12.076	-12.076	-12.076																																																			
80	-12.076	-12.077	-12.076																																																			
85	-12.075	-12.075	-12.075																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																																						



COSEL		Testing Circuitry Figure A
Model	MGW62412	
Item	Output Voltage Accuracy	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 80°C

Input Voltage : 18 - 36V

Load Current (AVR 1) : 0 - 0.25A (AVR 2) : 0 - 0.25A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) =
$$\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Object		+12V0.25A					
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy		
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]	
Maximum Voltage	80	18	0	12.346	±268	±2.2	
Minimum Voltage	80	18	0.25	11.810			

Object		-12V0.25A					
Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy		
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]	
Maximum Voltage	80	18	0	-12.352	±269	±2.2	
Minimum Voltage	80	18	0.25	-11.815			




COSEL																								
Model	MGW62412																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+12V0.25A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.071</td></tr> <tr><td>0.5</td><td>12.074</td></tr> <tr><td>1.0</td><td>12.074</td></tr> <tr><td>2.0</td><td>12.074</td></tr> <tr><td>3.0</td><td>12.074</td></tr> <tr><td>4.0</td><td>12.074</td></tr> <tr><td>5.0</td><td>12.074</td></tr> <tr><td>6.0</td><td>12.074</td></tr> <tr><td>7.0</td><td>12.074</td></tr> <tr><td>8.0</td><td>12.074</td></tr> </tbody> </table> <p>-12V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	12.071	0.5	12.074	1.0	12.074	2.0	12.074	3.0	12.074	4.0	12.074	5.0	12.074	6.0	12.074	7.0	12.074	8.0	12.074
Time since start [H]	Output Voltage [V]																							
0.0	12.071																							
0.5	12.074																							
1.0	12.074																							
2.0	12.074																							
3.0	12.074																							
4.0	12.074																							
5.0	12.074																							
6.0	12.074																							
7.0	12.074																							
8.0	12.074																							
Object	-12V0.25A																							
<p>1.Graph</p> <p style="text-align: center;">Time [H]</p> <p>Input Volt. 24V Load 100%</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.075</td></tr> <tr><td>0.5</td><td>-12.079</td></tr> <tr><td>1.0</td><td>-12.079</td></tr> <tr><td>2.0</td><td>-12.079</td></tr> <tr><td>3.0</td><td>-12.079</td></tr> <tr><td>4.0</td><td>-12.079</td></tr> <tr><td>5.0</td><td>-12.079</td></tr> <tr><td>6.0</td><td>-12.079</td></tr> <tr><td>7.0</td><td>-12.079</td></tr> <tr><td>8.0</td><td>-12.079</td></tr> </tbody> </table> <p>+12V: Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-12.075	0.5	-12.079	1.0	-12.079	2.0	-12.079	3.0	-12.079	4.0	-12.079	5.0	-12.079	6.0	-12.079	7.0	-12.079	8.0	-12.079
Time since start [H]	Output Voltage [V]																							
0.0	-12.075																							
0.5	-12.079																							
1.0	-12.079																							
2.0	-12.079																							
3.0	-12.079																							
4.0	-12.079																							
5.0	-12.079																							
6.0	-12.079																							
7.0	-12.079																							
8.0	-12.079																							



Model	MGW62412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.25A		

1. Graph


Input Volt. 24 V



2. Values

[ms]

Load \ Time	Td	Tr	Ts	Th	Tf
50 %	1.5	0.4	1.9	0.2	3.4
100 %	1.5	0.5	2.0	0.1	1.6






Model	MGW62412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V0.25A		

1. Graph


Input Volt. 24 V



2. Values

[ms]


Load \ Time	Td	Tr	Ts	Th	Tf
50 %	1.5	0.4	1.9	0.2	3.5
100 %	1.5	0.5	2.0	0.1	1.7





Model	MGW62412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.25A


Testing Circuitry Figure A



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.4	15.4
-40	15.1	15.3
-20	15.0	15.1
0	14.9	15.0
25	14.8	15.1
80	14.5	14.6
85	14.3	14.5
--	-	-
--	-	-
--	-	-
--	-	-

Object	-12V0.25A
--------	-----------



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-60	15.5	15.5
-40	15.1	15.3
-20	15.0	15.0
0	14.9	15.0
25	14.8	15.1
80	14.5	14.6
85	14.3	14.5
--	-	-
--	-	-
--	-	-
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



COSEL																																																										
Model	MGW62412	Temperature	25°C																																																							
Item	Overcurrent Protection	Testing Circuitry	Figure A																																																							
Object	+12V0.25A																																																									
<p>1.Graph</p> <p> — Input Volt. 18V — Input Volt. 24V — Input Volt. 36V </p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.43</td><td>0.44</td><td>0.43</td></tr> <tr><td>10.8</td><td>0.46</td><td>0.47</td><td>0.45</td></tr> <tr><td>9.6</td><td>0.53</td><td>0.53</td><td>0.50</td></tr> <tr><td>8.4</td><td>0.60</td><td>0.59</td><td>0.56</td></tr> <tr><td>7.2</td><td>0.68</td><td>0.66</td><td>0.62</td></tr> <tr><td>6.0</td><td>0.75</td><td>0.73</td><td>0.68</td></tr> <tr><td>4.8</td><td>0.83</td><td>0.80</td><td>0.75</td></tr> <tr><td>3.6</td><td>0.92</td><td>0.88</td><td>0.81</td></tr> <tr><td>2.4</td><td>1.01</td><td>0.96</td><td>0.88</td></tr> <tr><td>1.2</td><td>1.09</td><td>1.02</td><td>0.94</td></tr> <tr><td>0.0</td><td>1.10</td><td>1.01</td><td>0.90</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">-12V: Rated Load Current</p>		Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	11.4	0.43	0.44	0.43	10.8	0.46	0.47	0.45	9.6	0.53	0.53	0.50	8.4	0.60	0.59	0.56	7.2	0.68	0.66	0.62	6.0	0.75	0.73	0.68	4.8	0.83	0.80	0.75	3.6	0.92	0.88	0.81	2.4	1.01	0.96	0.88	1.2	1.09	1.02	0.94	0.0	1.10	1.01	0.90	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
11.4	0.43	0.44	0.43																																																							
10.8	0.46	0.47	0.45																																																							
9.6	0.53	0.53	0.50																																																							
8.4	0.60	0.59	0.56																																																							
7.2	0.68	0.66	0.62																																																							
6.0	0.75	0.73	0.68																																																							
4.8	0.83	0.80	0.75																																																							
3.6	0.92	0.88	0.81																																																							
2.4	1.01	0.96	0.88																																																							
1.2	1.09	1.02	0.94																																																							
0.0	1.10	1.01	0.90																																																							
--	-	-	-																																																							
Object	-12V0.25A																																																									
<p>1.Graph</p> <p> — Input Volt. 18V — Input Volt. 24V — Input Volt. 36V </p> <p style="text-align: center;">Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>-11.4</td><td>0.43</td><td>0.44</td><td>0.43</td></tr> <tr><td>-10.8</td><td>0.46</td><td>0.47</td><td>0.45</td></tr> <tr><td>-9.6</td><td>0.53</td><td>0.53</td><td>0.50</td></tr> <tr><td>-8.4</td><td>0.60</td><td>0.59</td><td>0.56</td></tr> <tr><td>-7.2</td><td>0.68</td><td>0.66</td><td>0.62</td></tr> <tr><td>-6.0</td><td>0.75</td><td>0.73</td><td>0.68</td></tr> <tr><td>-4.8</td><td>0.84</td><td>0.80</td><td>0.75</td></tr> <tr><td>-3.6</td><td>0.92</td><td>0.88</td><td>0.81</td></tr> <tr><td>-2.4</td><td>1.02</td><td>0.96</td><td>0.88</td></tr> <tr><td>-1.2</td><td>1.09</td><td>1.04</td><td>0.94</td></tr> <tr><td>0.0</td><td>1.09</td><td>1.00</td><td>0.90</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: center;">+12V: Rated Load Current</p>		Output Voltage [V]	Load Current [A]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	-11.4	0.43	0.44	0.43	-10.8	0.46	0.47	0.45	-9.6	0.53	0.53	0.50	-8.4	0.60	0.59	0.56	-7.2	0.68	0.66	0.62	-6.0	0.75	0.73	0.68	-4.8	0.84	0.80	0.75	-3.6	0.92	0.88	0.81	-2.4	1.02	0.96	0.88	-1.2	1.09	1.04	0.94	0.0	1.09	1.00	0.90	--	-	-	-
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																							
-11.4	0.43	0.44	0.43																																																							
-10.8	0.46	0.47	0.45																																																							
-9.6	0.53	0.53	0.50																																																							
-8.4	0.60	0.59	0.56																																																							
-7.2	0.68	0.66	0.62																																																							
-6.0	0.75	0.73	0.68																																																							
-4.8	0.84	0.80	0.75																																																							
-3.6	0.92	0.88	0.81																																																							
-2.4	1.02	0.96	0.88																																																							
-1.2	1.09	1.04	0.94																																																							
0.0	1.09	1.00	0.90																																																							
--	-	-	-																																																							



<p>Model MGW62412</p>		<p>Temperature 25°C Testing Circuitry Figure A</p>																																																			
Item	Switching Frequency (by Load Current)																																																				
Object	+/-12V0.25A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Frequency [kHz]</th> </tr> <tr> <th>Input Volt. 18[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 36[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>842</td><td>895</td><td>917</td></tr> <tr><td>0.050</td><td>564</td><td>638</td><td>713</td></tr> <tr><td>0.100</td><td>427</td><td>495</td><td>572</td></tr> <tr><td>0.150</td><td>342</td><td>404</td><td>477</td></tr> <tr><td>0.200</td><td>287</td><td>341</td><td>409</td></tr> <tr><td>0.250</td><td>246</td><td>296</td><td>358</td></tr> <tr><td>0.275</td><td>230</td><td>278</td><td>337</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Frequency [kHz]			Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]	0.000	842	895	917	0.050	564	638	713	0.100	427	495	572	0.150	342	404	477	0.200	287	341	409	0.250	246	296	358	0.275	230	278	337	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Frequency [kHz]																																																				
	Input Volt. 18[V]	Input Volt. 24[V]	Input Volt. 36[V]																																																		
0.000	842	895	917																																																		
0.050	564	638	713																																																		
0.100	427	495	572																																																		
0.150	342	404	477																																																		
0.200	287	341	409																																																		
0.250	246	296	358																																																		
0.275	230	278	337																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>1.Graph</p> <p> —△— Input Volt. 18V - - - □ - - - Input Volt. 24V - · - ○ - · - - Input Volt. 36V </p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>-When load current is low, MG operates intermittently, so switching frequency would not become constant.</p>																																																					




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)