

TEST DATA OF MGXW1R52412

Regulated DC Power Supply

February 19, 2018

Approved by : Takayuki Fukuda
Takayuki Fukuda Design Manager

Prepared by : Masumi Kitamura Masumi Kitamura Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Input Voltage)	1
2.Input Current (by Load Ratio)	2
3.Input Power (by Load Ratio)	3
4.Efficiency (by Input Voltage)	4
5.Efficiency (by Load Ratio)	5
6.Line Regulation	6
7.Load Regulation	7
8.Dynamic Load Response	8
9.Ripple Voltage (by Load Current)	10
10.Ripple-Noise	12
11.Ripple Voltage (by Ambient Temperature)	14
12.Ambient Temperature Drift	15
13.Output Voltage Accuracy	16
14.Time Lapse Drift	17
15.Rise and Fall Time	18
16.Minimum Input Voltage for Regulated Output Voltage	20
17.Overcurrent Protection	21
18.Switching frequency (by Load Current)	22
19.Figure of Testing Circuitry	23

(Final Page 23)

COSEL

Model	MGXW1R52412
Item	Input Current (by Input Voltage)
Object	_____



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2.Values


Input Voltage [V]	Input Current [A]		
	Load 0%	Load 50%	Load 100%
0.0	0.000	0.000	0.000
5.0	0.003	0.003	0.003
5.2	0.003	0.003	0.003
5.4	0.003	0.003	0.003
5.5	0.024	0.213	0.327
6.0	0.022	0.174	0.311
9.0	0.016	0.113	0.223
12.0	0.013	0.085	0.164
18.0	0.010	0.058	0.108
24.0	0.008	0.044	0.082
36.0	0.007	0.031	0.056
48.0	0.007	0.025	0.044
60.0	0.007	0.021	0.036
66.0	0.007	0.020	0.034
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	MGXW1R52412																																																																																	
Item	Input Current (by Load Current)																																																																																	
Object	_____																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 6V Input Volt. 12V Input Volt. 24V Input Volt. 48V Input Volt. 60V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Ratio [%]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.022</td> <td>0.013</td> <td>0.008</td> <td>0.007</td> <td>0.007</td> </tr> <tr> <td>20</td> <td>0.082</td> <td>0.042</td> <td>0.023</td> <td>0.014</td> <td>0.013</td> </tr> <tr> <td>40</td> <td>0.144</td> <td>0.071</td> <td>0.037</td> <td>0.021</td> <td>0.018</td> </tr> <tr> <td>60</td> <td>0.208</td> <td>0.101</td> <td>0.052</td> <td>0.029</td> <td>0.024</td> </tr> <tr> <td>80</td> <td>0.279</td> <td>0.132</td> <td>0.067</td> <td>0.036</td> <td>0.030</td> </tr> <tr> <td>100</td> <td>- *</td> <td>0.164</td> <td>0.082</td> <td>0.043</td> <td>0.036</td> </tr> <tr> <td>110</td> <td>- *</td> <td>0.180</td> <td>0.089</td> <td>0.047</td> <td>0.039</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>*: Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>					Load Ratio [%]	Input Current [A]					6[V]	12[V]	24[V]	48[V]	60[V]	0	0.022	0.013	0.008	0.007	0.007	20	0.082	0.042	0.023	0.014	0.013	40	0.144	0.071	0.037	0.021	0.018	60	0.208	0.101	0.052	0.029	0.024	80	0.279	0.132	0.067	0.036	0.030	100	- *	0.164	0.082	0.043	0.036	110	- *	0.180	0.089	0.047	0.039	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Ratio [%]	Input Current [A]																																																																																	
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																													
0	0.022	0.013	0.008	0.007	0.007																																																																													
20	0.082	0.042	0.023	0.014	0.013																																																																													
40	0.144	0.071	0.037	0.021	0.018																																																																													
60	0.208	0.101	0.052	0.029	0.024																																																																													
80	0.279	0.132	0.067	0.036	0.030																																																																													
100	- *	0.164	0.082	0.043	0.036																																																																													
110	- *	0.180	0.089	0.047	0.039																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													
--	-	-	-	-	-																																																																													

COSEL

Model	MGXW1R52412
Item	Input Power (by Load Current)
Object	_____


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Load Ratio [%]	Input Power [W]				
	6[V]	12[V]	24[V]	48[V]	60[V]
0	0.13	0.15	0.20	0.32	0.39
20	0.49	0.50	0.55	0.67	0.75
40	0.86	0.85	0.90	1.02	1.10
60	1.24	1.21	1.25	1.37	1.45
80	1.65	1.58	1.60	1.72	1.80
100	-	1.95	1.96	2.08	2.16
110	-	2.14	2.14	2.25	2.33
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-


※ Maximum output current at minimum input Voltage is 70% of rated load current.
 Refer to instruction manuals for details of input derating.

COSSEL

Model	MGXW1R52412
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
5.5	74.9	74.8
6.0	75.1	75.8
9.0	77.1	79.4
12.0	77.0	80.9
24.0	74.2	80.5
36.0	70.1	78.3
48.0	65.8	75.8
60.0	62.2	73.1
66.0	60.1	71.8

※1: Load 70%

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	MGXW1R52412
Item	Efficiency (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Ratio [%]	Efficiency [%]				
	6[V]	12[V]	24[V]	48[V]	60[V]
0	-	-	-	-	-
20	66.2	64.4	58.0	47.1	41.9
40	73.4	74.5	70.9	62.8	58.3
60	76.3	78.4	76.3	69.4	65.5
80	76.3	80.1	78.8	73.7	70.2
100	-※	81.0	80.9	76.1	73.1
110	-※	81.1	81.0	77.2	74.2
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

※ Maximum output current at minimum input Voltage is 70% of rated load current.
Refer to instruction manuals for details of input derating.

COSEL


Model MGXW1R52412

Item Line Regulation

Object +12V0.065A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph




2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
5.5	12.225	-
6.0	12.216	-
9.0	12.196	12.091
12.0	12.188	12.093
24.0	12.172	12.094
36.0	12.166	12.093
48.0	12.163	12.093
60.0	12.161	12.092
66.0	12.161	12.092

-12V:Rated Load Current

Object -12V0.065A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
5.5	-12.241	-
6.0	-12.238	-
9.0	-12.221	-12.114
12.0	-12.211	-12.116
24.0	-12.194	-12.114
36.0	-12.188	-12.113
48.0	-12.184	-12.112
60.0	-12.182	-12.111
66.0	-12.181	-12.110


+12V:Rated Load Current

Note: Slanted line shows the range of the rated input voltage.

※ Maximum output current at minimum input Voltage is 70% of rated load current.
 Refer to instruction manuals for details of input derating.

COSEL

Model	MGXW1R52412	Temperature 25°C Testing Circuitry Figure A																																																																																		
Item	Load Regulation																																																																																			
Object	+12V0.065A																																																																																			
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —△— Input Volt. 6V - -□-- Input Volt. 12V - -★-- Input Volt. 24V - -○-- Input Volt. 48V - -◇-- Input Volt. 60V 																																																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 6[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 60[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>12.385</td><td>12.391</td><td>12.343</td><td>12.316</td><td>12.311</td></tr> <tr><td>0.013</td><td>12.249</td><td>12.272</td><td>12.244</td><td>12.228</td><td>12.225</td></tr> <tr><td>0.026</td><td>12.171</td><td>12.212</td><td>12.193</td><td>12.182</td><td>12.180</td></tr> <tr><td>0.039</td><td>12.114</td><td>12.167</td><td>12.155</td><td>12.147</td><td>12.146</td></tr> <tr><td>0.052</td><td>12.066</td><td>12.128</td><td>12.123</td><td>12.118</td><td>12.117</td></tr> <tr><td>0.065</td><td>-※</td><td>12.093</td><td>12.094</td><td>12.093</td><td>12.092</td></tr> <tr><td>0.072</td><td>-※</td><td>12.076</td><td>12.080</td><td>12.080</td><td>12.080</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V:Rated Load Current</p>						Load Current [A]	Output Voltage [V]					Input Volt. 6[V]	Input Volt. 12[V]	Input Volt. 24[V]	Input Volt. 48[V]	Input Volt. 60[V]	0.000	12.385	12.391	12.343	12.316	12.311	0.013	12.249	12.272	12.244	12.228	12.225	0.026	12.171	12.212	12.193	12.182	12.180	0.039	12.114	12.167	12.155	12.147	12.146	0.052	12.066	12.128	12.123	12.118	12.117	0.065	-※	12.093	12.094	12.093	12.092	0.072	-※	12.076	12.080	12.080	12.080	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	
Load Current [A]	Output Voltage [V]																																																																																			
	Input Volt. 6[V]	Input Volt. 12[V]	Input Volt. 24[V]	Input Volt. 48[V]	Input Volt. 60[V]																																																																															
0.000	12.385	12.391	12.343	12.316	12.311																																																																															
0.013	12.249	12.272	12.244	12.228	12.225																																																																															
0.026	12.171	12.212	12.193	12.182	12.180																																																																															
0.039	12.114	12.167	12.155	12.147	12.146																																																																															
0.052	12.066	12.128	12.123	12.118	12.117																																																																															
0.065	-※	12.093	12.094	12.093	12.092																																																																															
0.072	-※	12.076	12.080	12.080	12.080																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
Object	-12V0.065A	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 6[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 24[V]</th> <th>Input Volt. 48[V]</th> <th>Input Volt. 60[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>-12.429</td><td>-12.426</td><td>-12.375</td><td>-12.349</td><td>-12.344</td></tr> <tr><td>0.013</td><td>-12.279</td><td>-12.298</td><td>-12.268</td><td>-12.253</td><td>-12.250</td></tr> <tr><td>0.026</td><td>-12.197</td><td>-12.236</td><td>-12.215</td><td>-12.204</td><td>-12.201</td></tr> <tr><td>0.039</td><td>-12.142</td><td>-12.189</td><td>-12.176</td><td>-12.168</td><td>-12.166</td></tr> <tr><td>0.052</td><td>-12.085</td><td>-12.150</td><td>-12.143</td><td>-12.138</td><td>-12.137</td></tr> <tr><td>0.065</td><td>-※</td><td>-12.116</td><td>-12.114</td><td>-12.112</td><td>-12.111</td></tr> <tr><td>0.072</td><td>-※</td><td>-12.100</td><td>-12.101</td><td>-12.100</td><td>-12.099</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V:Rated Load Current</p>						Load Current [A]	Output Voltage [V]					Input Volt. 6[V]	Input Volt. 12[V]	Input Volt. 24[V]	Input Volt. 48[V]	Input Volt. 60[V]	0.000	-12.429	-12.426	-12.375	-12.349	-12.344	0.013	-12.279	-12.298	-12.268	-12.253	-12.250	0.026	-12.197	-12.236	-12.215	-12.204	-12.201	0.039	-12.142	-12.189	-12.176	-12.168	-12.166	0.052	-12.085	-12.150	-12.143	-12.138	-12.137	0.065	-※	-12.116	-12.114	-12.112	-12.111	0.072	-※	-12.100	-12.101	-12.100	-12.099	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																																			
	Input Volt. 6[V]	Input Volt. 12[V]	Input Volt. 24[V]	Input Volt. 48[V]	Input Volt. 60[V]																																																																															
0.000	-12.429	-12.426	-12.375	-12.349	-12.344																																																																															
0.013	-12.279	-12.298	-12.268	-12.253	-12.250																																																																															
0.026	-12.197	-12.236	-12.215	-12.204	-12.201																																																																															
0.039	-12.142	-12.189	-12.176	-12.168	-12.166																																																																															
0.052	-12.085	-12.150	-12.143	-12.138	-12.137																																																																															
0.065	-※	-12.116	-12.114	-12.112	-12.111																																																																															
0.072	-※	-12.100	-12.101	-12.100	-12.099																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
--	-	-	-	-	-																																																																															
<p>Note: Slanted line shows the range of the rated load current.</p> <p>* Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																				

COSEL

COSEL


Model	MGXW1R52412	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	-12V0.065A		

Input Volt. 24 V

+12V:rated load Current

Cycle 100 ms


t1,t2 = 100 μ s

Load Current


Min.Load (0A)↔
 Load 100% (0.065A)

200 mV/div


4 ms/div



Min.Load (0A)↔
 Load 50% (0.0325A)

200 mV/div


4 ms/div



Load 50% (0.0325A)↔
 Load 100% (0.065A)

200 mV/div

4 ms/div



COSEL

Model	MGXW1R52412																																							
Item	Ripple Voltage (by Load Current)	Temperature Testing Circuitry 25°C Figure B																																						
Object	+12V0.065A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The graph shows two curves: one for Input Volt. 6V (solid line with triangle markers) and one for Input Volt. 60V (dashed line with circle markers). The x-axis is Load Current [A] from 0.00 to 0.08. The y-axis is Ripple Voltage [mV] from 0 to 400. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 6V)</th> <th>Ripple Voltage [mV] (Input Volt. 60V)</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>10</td><td>10</td></tr> <tr><td>0.013</td><td>25</td><td>12</td></tr> <tr><td>0.026</td><td>47</td><td>15</td></tr> <tr><td>0.033</td><td>58</td><td>17</td></tr> <tr><td>0.039</td><td>67</td><td>18</td></tr> <tr><td>0.052</td><td>78</td><td>22</td></tr> <tr><td>0.065</td><td>-</td><td>26</td></tr> <tr><td>0.072</td><td>-</td><td>28</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 6V)	Ripple Voltage [mV] (Input Volt. 60V)	0.000	10	10	0.013	25	12	0.026	47	15	0.033	58	17	0.039	67	18	0.052	78	22	0.065	-	26	0.072	-	28	--	-	-	--	-	-	--	-	-			
Load Current [A]	Ripple Voltage [mV] (Input Volt. 6V)	Ripple Voltage [mV] (Input Volt. 60V)																																						
0.000	10	10																																						
0.013	25	12																																						
0.026	47	15																																						
0.033	58	17																																						
0.039	67	18																																						
0.052	78	22																																						
0.065	-	26																																						
0.072	-	28																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 6 [V]</th> <th>Input Volt. 60 [V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>10</td><td>10</td></tr> <tr><td>0.013</td><td>25</td><td>12</td></tr> <tr><td>0.026</td><td>47</td><td>15</td></tr> <tr><td>0.033</td><td>58</td><td>17</td></tr> <tr><td>0.039</td><td>67</td><td>18</td></tr> <tr><td>0.052</td><td>78</td><td>22</td></tr> <tr><td>0.065</td><td>-</td><td>26</td></tr> <tr><td>0.072</td><td>-</td><td>28</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 6 [V]	Input Volt. 60 [V]	0.000	10	10	0.013	25	12	0.026	47	15	0.033	58	17	0.039	67	18	0.052	78	22	0.065	-	26	0.072	-	28	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 6 [V]	Input Volt. 60 [V]																																						
0.000	10	10																																						
0.013	25	12																																						
0.026	47	15																																						
0.033	58	17																																						
0.039	67	18																																						
0.052	78	22																																						
0.065	-	26																																						
0.072	-	28																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
-12V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL

Model	MGXW1R52412																																							
Item	Ripple Voltage (by Load Current)	Temperature Testing Circuitry 25°C Figure B																																						
Object	-12V0.065A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 400 mV, and the X-axis ranges from 0.00 to 0.08 A. Two curves are shown: one for Input Volt. 6V (solid line with open triangles) and one for Input Volt. 60V (dashed line with open circles). Both curves show a slight increase in ripple voltage as load current increases. A slanted line indicates the range of rated load current.</p>																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 6 [V]</th> <th>Input Volt. 60 [V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>10</td> <td>10</td> </tr> <tr> <td>0.013</td> <td>25</td> <td>12</td> </tr> <tr> <td>0.026</td> <td>47</td> <td>15</td> </tr> <tr> <td>0.033</td> <td>58</td> <td>17</td> </tr> <tr> <td>0.039</td> <td>67</td> <td>18</td> </tr> <tr> <td>0.052</td> <td>78</td> <td>22</td> </tr> <tr> <td>0.065</td> <td>-※</td> <td>26</td> </tr> <tr> <td>0.072</td> <td>-※</td> <td>28</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 6 [V]	Input Volt. 60 [V]	0.000	10	10	0.013	25	12	0.026	47	15	0.033	58	17	0.039	67	18	0.052	78	22	0.065	-※	26	0.072	-※	28	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 6 [V]	Input Volt. 60 [V]																																						
0.000	10	10																																						
0.013	25	12																																						
0.026	47	15																																						
0.033	58	17																																						
0.039	67	18																																						
0.052	78	22																																						
0.065	-※	26																																						
0.072	-※	28																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
+12V: Rated Load Current																																								
<p>Measured by 100 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																								
<p>Ripple [mVp-p]</p> <p>Fig.Complex Ripple Wave Form</p>																																								

COSEL


Model MGXW1R52412

Temperature 25°C
Testing Circuitry Figure B

Item Ripple-Noise

Object +12V0.065A

1. Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 6 [V]	Input Volt. 60 [V]
0.000	18	20
0.013	33	20
0.026	55	23
0.033	65	25
0.039	73	21
0.052	83	25
0.065	-	30
0.072	-	31
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current.
Refer to instruction manuals for details of input derating.

Ripple Noise[mVp-p]





Fig.Complex Ripple Noise Wave Form

COSEL

Model	MGXW1R52412
Item	Ripple-Noise
Object	-12V0.065A

Temperature 25°C
Testing Circuitry Figure B

1.Graph



Measured by 100 MHz Oscilloscope.
Ripple-Noise is shown as p-p in the figure below.
Note: Slanted line shows the range of the rated load current.


2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 6 [V]	Input Volt. 60 [V]
0.000	18	20
0.013	33	20
0.026	55	23
0.033	65	25
0.039	73	21
0.052	83	25
0.065	-	30
0.072	-	31
--	-	-
--	-	-
--	-	-

+12V: Rated Load Current

※ Maximum output current at minimum input Voltage is 70% of rated load current.
Refer to instruction manuals for details of input derating.


Ripple Noise[mVp-p]



COSEL

Model	MGXW1R52412
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V0.065A

1.Graph



Testing Circuitry Figure B


2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	28	46
-40	25	42
-20	23	40
0	22	38
25	21	37
50	20	36
85	20	35
90	19	35
--	-	-
--	-	-
--	-	-

-12V: Rated Load Current

Object	-12V0.065A
--------	------------

1.Graph



2.Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Load 50%	Load 100%
-60	28	46
-40	25	42
-20	23	40
0	22	38
25	21	37
50	20	36
85	20	35
90	19	35
--	-	-
--	-	-
--	-	-


+12V: Rated Load Current

Measured by 100 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	MGXW1R52412
Item	Ambient Temperature Drift
Object	+12V0.065A




Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	6[V]	12[V]	24[V]	48[V]	60[V]
-60	12.029	12.031	12.031	12.027	12.026
-40	12.048	12.051	12.051	12.048	12.047
-20	12.065	12.068	12.068	12.066	12.065
0	12.078	12.080	12.082	12.079	12.079
25	12.088	12.090	12.091	12.090	12.089
60	12.093	12.095	12.096	12.096	12.096
70	12.094	12.095	12.097	12.097	12.097
75	12.095	12.096	12.097	12.097	12.097
85	12.094	12.095	12.097	12.097	12.097
90	12.092	12.093	12.095	12.094	12.093
--	-	-	-	-	-

-12V: Rated Load Current



2.Values

Ambient Temperature [°C]	Output Voltage [V]				
	6[V]	12[V]	24[V]	48[V]	60[V]
-60	-12.049	-12.054	-12.054	-12.051	-12.050
-40	-12.069	-12.074	-12.073	-12.070	-12.070
-20	-12.086	-12.091	-12.090	-12.088	-12.086
0	-12.100	-12.104	-12.103	-12.100	-12.099
25	-12.110	-12.114	-12.113	-12.110	-12.109
60	-12.116	-12.119	-12.118	-12.116	-12.114
70	-12.117	-12.120	-12.118	-12.116	-12.115
75	-12.117	-12.120	-12.119	-12.117	-12.115
85	-12.117	-12.119	-12.118	-12.116	-12.115
90	-12.115	-12.116	-12.108	-12.115	-12.113
--	-	-	-	-	-

+12V: Rated Load Current

Note: Slanted line shows the range of the rated ambient temperature.

Note: In case of Input Volt. 6V, Load 70%.
Other case Load 100%.



Model	MGXW1R52412	
Item	Output Voltage Accuracy	Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -40 - 85°C

Input Voltage : 6 - 60V

Load Current (AVR 1) : 0 - 0.065A (AVR 2) : 0 - 0.065A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$



2. Values

Object	+12V0.065A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	85	6	0	12.426	± 330	± 2.8
Minimum Voltage	85	6	0.046 \ddagger	11.767		

Object	-12V0.065A		Output		Output Voltage Accuracy	
Item	Temperature [°C]	Input Voltage[V]	Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	85	6	0	-12.458	± 330	± 2.8
Minimum Voltage	85	6	0.046 \ddagger	-11.799		

\ddagger Maximum output current at minimum input Voltage is 70% of rated load current.
Refer to instruction manuals for details of input derating.


COSEL

Model	MGXW1R52412	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V0.065A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.088</td></tr> <tr><td>0.5</td><td>12.090</td></tr> <tr><td>1.0</td><td>12.090</td></tr> <tr><td>2.0</td><td>12.090</td></tr> <tr><td>3.0</td><td>12.090</td></tr> <tr><td>4.0</td><td>12.090</td></tr> <tr><td>5.0</td><td>12.090</td></tr> <tr><td>6.0</td><td>12.090</td></tr> <tr><td>7.0</td><td>12.090</td></tr> <tr><td>8.0</td><td>12.090</td></tr> </tbody> </table> <p>-12V:Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	12.088	0.5	12.090	1.0	12.090	2.0	12.090	3.0	12.090	4.0	12.090	5.0	12.090	6.0	12.090	7.0	12.090	8.0	12.090
Time since start [H]	Output Voltage [V]																								
0.0	12.088																								
0.5	12.090																								
1.0	12.090																								
2.0	12.090																								
3.0	12.090																								
4.0	12.090																								
5.0	12.090																								
6.0	12.090																								
7.0	12.090																								
8.0	12.090																								
Object			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 24V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-12.110</td></tr> <tr><td>0.5</td><td>-12.112</td></tr> <tr><td>1.0</td><td>-12.112</td></tr> <tr><td>2.0</td><td>-12.112</td></tr> <tr><td>3.0</td><td>-12.112</td></tr> <tr><td>4.0</td><td>-12.112</td></tr> <tr><td>5.0</td><td>-12.112</td></tr> <tr><td>6.0</td><td>-12.112</td></tr> <tr><td>7.0</td><td>-12.112</td></tr> <tr><td>8.0</td><td>-12.112</td></tr> </tbody> </table> <p>+12V:Rated Load Current</p>	Time since start [H]	Output Voltage [V]	0.0	-12.110	0.5	-12.112	1.0	-12.112	2.0	-12.112	3.0	-12.112	4.0	-12.112	5.0	-12.112	6.0	-12.112	7.0	-12.112	8.0	-12.112
Time since start [H]	Output Voltage [V]																								
0.0	-12.110																								
0.5	-12.112																								
1.0	-12.112																								
2.0	-12.112																								
3.0	-12.112																								
4.0	-12.112																								
5.0	-12.112																								
6.0	-12.112																								
7.0	-12.112																								
8.0	-12.112																								

COSEL


Model	MGXW1R52412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+12V0.065A		

1. Graph



2. Values


Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.4	0.8	1.2	0.4	7.1	
100 %		0.4	0.9	1.3	0.3	3.5	



COSSEL


Model	MGXW1R52412	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	-12V0.065A		

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.4	0.8	1.2	0.5	8.5	
100 %		0.4	1.0	1.4	0.3	4.1	




COSEL

Model	MGXW1R52412
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V0.065A

Testing Circuitry Figure A

1.Graph




2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	5.2	4.9
-40	5.0	4.9
-20	5.0	4.9
0	4.9	4.9
25	4.9	4.9
60	4.9	4.8
70	4.9	4.8
75	4.9	4.8
85	4.9	4.8
90	4.9	4.8
--	-	-

Object -12V0.065A

1.Graph



2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 70%
-60	5.2	4.9
-40	5.0	4.9
-20	4.9	4.9
0	4.9	4.9
25	4.9	4.9
60	4.9	4.8
70	4.9	4.8
75	4.9	4.8
85	4.9	4.8
90	4.9	4.8
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	MGXW1R52412	Temperature 25°C Testing Circuitry Figure A																																																																																			
Item	Overcurrent Protection																																																																																				
Object	+12V0.065A																																																																																				
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 6V Input Volt. 12V Input Volt. 24V Input Volt. 48V Input Volt. 60V</p>	2.Values																																																																																			
		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr><td>11.4</td><td>0.077</td><td>0.110</td><td>0.115</td><td>0.117</td><td>0.120</td></tr> <tr><td>10.8</td><td>0.084</td><td>0.121</td><td>0.128</td><td>0.130</td><td>0.132</td></tr> <tr><td>9.6</td><td>0.098</td><td>0.146</td><td>0.156</td><td>0.156</td><td>0.157</td></tr> <tr><td>8.4</td><td>0.116</td><td>0.175</td><td>0.185</td><td>0.182</td><td>0.184</td></tr> <tr><td>7.2</td><td>0.138</td><td>0.206</td><td>0.215</td><td>0.208</td><td>0.210</td></tr> <tr><td>6.0</td><td>0.164</td><td>0.240</td><td>0.246</td><td>0.236</td><td>0.236</td></tr> <tr><td>4.8</td><td>0.194</td><td>0.279</td><td>0.279</td><td>0.264</td><td>0.265</td></tr> <tr><td>3.6</td><td>0.231</td><td>0.321</td><td>0.312</td><td>0.294</td><td>0.294</td></tr> <tr><td>2.4</td><td>0.277</td><td>0.366</td><td>0.348</td><td>0.325</td><td>0.323</td></tr> <tr><td>1.2</td><td>0.331</td><td>0.406</td><td>0.373</td><td>0.344</td><td>0.340</td></tr> <tr><td>0.0</td><td>0.364</td><td>0.389</td><td>0.336</td><td>0.300</td><td>0.295</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>-12V:Rated Load Current</p>	Output Voltage [V]	Load Current [A]					6[V]	12[V]	24[V]	48[V]	60[V]	11.4	0.077	0.110	0.115	0.117	0.120	10.8	0.084	0.121	0.128	0.130	0.132	9.6	0.098	0.146	0.156	0.156	0.157	8.4	0.116	0.175	0.185	0.182	0.184	7.2	0.138	0.206	0.215	0.208	0.210	6.0	0.164	0.240	0.246	0.236	0.236	4.8	0.194	0.279	0.279	0.264	0.265	3.6	0.231	0.321	0.312	0.294	0.294	2.4	0.277	0.366	0.348	0.325	0.323	1.2	0.331	0.406	0.373	0.344	0.340	0.0	0.364	0.389	0.336	0.300	0.295	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																																
11.4	0.077	0.110	0.115	0.117	0.120																																																																																
10.8	0.084	0.121	0.128	0.130	0.132																																																																																
9.6	0.098	0.146	0.156	0.156	0.157																																																																																
8.4	0.116	0.175	0.185	0.182	0.184																																																																																
7.2	0.138	0.206	0.215	0.208	0.210																																																																																
6.0	0.164	0.240	0.246	0.236	0.236																																																																																
4.8	0.194	0.279	0.279	0.264	0.265																																																																																
3.6	0.231	0.321	0.312	0.294	0.294																																																																																
2.4	0.277	0.366	0.348	0.325	0.323																																																																																
1.2	0.331	0.406	0.373	0.344	0.340																																																																																
0.0	0.364	0.389	0.336	0.300	0.295																																																																																
--	-	-	-	-	-																																																																																
Object	-12V0.065A	2.Values																																																																																			
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 6V Input Volt. 12V Input Volt. 24V Input Volt. 48V Input Volt. 60V</p>	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr><td>-11.4</td><td>0.077</td><td>0.109</td><td>0.116</td><td>0.117</td><td>0.121</td></tr> <tr><td>-10.8</td><td>0.084</td><td>0.121</td><td>0.128</td><td>0.130</td><td>0.133</td></tr> <tr><td>-9.6</td><td>0.098</td><td>0.146</td><td>0.155</td><td>0.156</td><td>0.158</td></tr> <tr><td>-8.4</td><td>0.116</td><td>0.176</td><td>0.185</td><td>0.183</td><td>0.184</td></tr> <tr><td>-7.2</td><td>0.139</td><td>0.207</td><td>0.216</td><td>0.208</td><td>0.210</td></tr> <tr><td>-6.0</td><td>0.164</td><td>0.240</td><td>0.246</td><td>0.236</td><td>0.237</td></tr> <tr><td>-4.8</td><td>0.194</td><td>0.279</td><td>0.279</td><td>0.265</td><td>0.265</td></tr> <tr><td>-3.6</td><td>0.231</td><td>0.322</td><td>0.313</td><td>0.294</td><td>0.294</td></tr> <tr><td>-2.4</td><td>0.277</td><td>0.367</td><td>0.349</td><td>0.325</td><td>0.323</td></tr> <tr><td>-1.2</td><td>0.329</td><td>0.407</td><td>0.374</td><td>0.343</td><td>0.340</td></tr> <tr><td>0.0</td><td>0.366</td><td>0.388</td><td>0.336</td><td>0.299</td><td>0.294</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table> <p>+12V:Rated Load Current</p>	Output Voltage [V]	Load Current [A]					6[V]	12[V]	24[V]	48[V]	60[V]	-11.4	0.077	0.109	0.116	0.117	0.121	-10.8	0.084	0.121	0.128	0.130	0.133	-9.6	0.098	0.146	0.155	0.156	0.158	-8.4	0.116	0.176	0.185	0.183	0.184	-7.2	0.139	0.207	0.216	0.208	0.210	-6.0	0.164	0.240	0.246	0.236	0.237	-4.8	0.194	0.279	0.279	0.265	0.265	-3.6	0.231	0.322	0.313	0.294	0.294	-2.4	0.277	0.367	0.349	0.325	0.323	-1.2	0.329	0.407	0.374	0.343	0.340	0.0	0.366	0.388	0.336	0.299	0.294	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																				
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																																
-11.4	0.077	0.109	0.116	0.117	0.121																																																																																
-10.8	0.084	0.121	0.128	0.130	0.133																																																																																
-9.6	0.098	0.146	0.155	0.156	0.158																																																																																
-8.4	0.116	0.176	0.185	0.183	0.184																																																																																
-7.2	0.139	0.207	0.216	0.208	0.210																																																																																
-6.0	0.164	0.240	0.246	0.236	0.237																																																																																
-4.8	0.194	0.279	0.279	0.265	0.265																																																																																
-3.6	0.231	0.322	0.313	0.294	0.294																																																																																
-2.4	0.277	0.367	0.349	0.325	0.323																																																																																
-1.2	0.329	0.407	0.374	0.343	0.340																																																																																
0.0	0.366	0.388	0.336	0.299	0.294																																																																																
--	-	-	-	-	-																																																																																
Note: Slanted line shows the range of the rated load current.		<p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																																			

COSEL

Model	MGXW1R52412																																																																																	
Item	Switching frequency (by Load Current)																																																																																	
Object	+/-12V0.065A																																																																																	
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 6V Input Volt. 12V Input Volt. 24V Input Volt. 48V Input Volt. 60V 																																																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>6[V]</th> <th>12[V]</th> <th>24[V]</th> <th>48[V]</th> <th>60[V]</th> </tr> </thead> <tbody> <tr> <td>0.000</td> <td>210</td> <td>316</td> <td>412</td> <td>479</td> <td>491</td> </tr> <tr> <td>0.013</td> <td>155</td> <td>260</td> <td>361</td> <td>434</td> <td>449</td> </tr> <tr> <td>0.026</td> <td>122</td> <td>221</td> <td>321</td> <td>395</td> <td>412</td> </tr> <tr> <td>0.033</td> <td>109</td> <td>204</td> <td>302</td> <td>377</td> <td>393</td> </tr> <tr> <td>0.039</td> <td>100</td> <td>192</td> <td>288</td> <td>362</td> <td>379</td> </tr> <tr> <td>0.046</td> <td>91</td> <td>179</td> <td>273</td> <td>346</td> <td>364</td> </tr> <tr> <td>0.052</td> <td>84</td> <td>169</td> <td>262</td> <td>334</td> <td>351</td> </tr> <tr> <td>0.055</td> <td>81</td> <td>165</td> <td>256</td> <td>328</td> <td>345</td> </tr> <tr> <td>0.065</td> <td>-</td> <td>151</td> <td>239</td> <td>310</td> <td>327</td> </tr> <tr> <td>0.072</td> <td>-</td> <td>143</td> <td>228</td> <td>299</td> <td>315</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>※ Maximum output current at minimum input Voltage is 70% of rated load current. Refer to instruction manuals for details of input derating.</p>					Load Current [A]	Input Current [A]					6[V]	12[V]	24[V]	48[V]	60[V]	0.000	210	316	412	479	491	0.013	155	260	361	434	449	0.026	122	221	321	395	412	0.033	109	204	302	377	393	0.039	100	192	288	362	379	0.046	91	179	273	346	364	0.052	84	169	262	334	351	0.055	81	165	256	328	345	0.065	-	151	239	310	327	0.072	-	143	228	299	315	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																																	
	6[V]	12[V]	24[V]	48[V]	60[V]																																																																													
0.000	210	316	412	479	491																																																																													
0.013	155	260	361	434	449																																																																													
0.026	122	221	321	395	412																																																																													
0.033	109	204	302	377	393																																																																													
0.039	100	192	288	362	379																																																																													
0.046	91	179	273	346	364																																																																													
0.052	84	169	262	334	351																																																																													
0.055	81	165	256	328	345																																																																													
0.065	-	151	239	310	327																																																																													
0.072	-	143	228	299	315																																																																													
--	-	-	-	-	-																																																																													

Note: Slanted line shows the range of the rated load current.

When load current is low, MG operates intermittently, so switching frequency would not become constant.

COSEL




Figure A

Data Acquisition/Control Unit




Figure B (Ripple and Ripple noise Characteristic)