



Ref. Certif. No.

US-43088-M1-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	DC-DC Converter
Name and address of the applicant	COSEL CO LTD 1-6-43 KAMIAKAE-MACHI TOYAMA-SHI 930-0816 Japan
Name and address of the manufacturer	COSEL CO LTD 1-6-43 KAMIAKAE-MACHI TOYAMA-SHI 930-0816 Japan
Name and address of the factory	COSEL CO LTD 1-6-43 KAMIAKAE-MACHI TOYAMA-SHI 930-0816 Japan
Note: When more than one factory, please report on page 2	<input checked="" type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	Input: 4.5-18 Vdc (12 Vdc typical model), 9-36 Vdc (24 Vdc typical model), 18-76 Vdc (48 Vdc typical model) Output: 3.3, 5, 9, 12, 15 Vdc (Single output model), ±12, ±15 V (Dual output model) <input checked="" type="checkbox"/> Additional Information on page 2
Trademark / Brand (if any)	
Customer's Testing Facility (CTF) Stage used	CTF Stage 2
Model / Type Ref.	MHFS6123R3, MHFS61205, MHFS61209, MHFS61212, MHFS61215 <input checked="" type="checkbox"/> Additional Information on page 2
Additional information (if necessary may also be reported on page 2)	The report was revised to include technical modifications. The risk management requirements of the standard were not addressed National Differences: EU Group Differences, CA, US <input checked="" type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60601-1:2005, IEC 60601-1:2005/AMD1:2012, IEC 60601-1:2005/AMD2:2020
As shown in the Test Report Ref. No. which forms part of this Certificate	E161890-D1068-1/A1/C0-CB issued on 2024-05-15

This CB Test Certificate is issued by the National Certification Body



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-05-21
Original Issue Date: 2023-12-04

Signature:
Mauricio Avila



Ref. Certif. No.

US-43088-M1-UL

Factory(ies):

COSEL CO LTD
TATEYAMA FACTORY, 78 DOGENJI TATEYAMAMACHI NAKANIKAWA-GUN 930-0241
Japan

Additional Model Detail(s):

MHFS6123R3, MHFS61205, MHFS61209, MHFS61212, MHFS61215, MHFS6243R3, MHFS62405, MHFS62409, MHFS62412, MHFS62415, MHFS6483R3, MHFS64805, MHFS64809, MHFS64812, MHFS64815, MHFW61212, MHFW61215, MHFW62412, MHFW62415, MHFW64812, MHFW64815, May be followed by suffix "-#" which can be any number 0 to 9 or any letter A to Z or blank, single number, letter or in the combination of two or more.

Additional Ratings:

<Input rating>

Model MHFS6123R3: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.53 A (0.58 A at 12 Vdc input)
Model MHFS61205: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.63 A (0.61 A at 12 Vdc input)
Model MHFS61209: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.60 A (0.60 A at 12 Vdc input)
Model MHFS61212: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.59 A (0.60 A at 12 Vdc input)
Model MHFS61215: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.59 A (0.60 A at 12 Vdc input)

Model MHFS6243R3: 9 – 36 Vdc (24 Vdc typical), maximum 0.77 A (0.29 A at 24 Vdc input)
Model MHFS62405: 9 – 36 Vdc (24 Vdc typical), maximum 0.82 A (0.31 A at 24 Vdc input)
Model MHFS62409: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)
Model MHFS62412: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)
Model MHFS62415: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)

Model MHFS6483R3: 18 – 76 Vdc (48 Vdc typical), maximum 0.39 A (0.143 A at 48 Vdc input)
Model MHFS64805: 18 – 76 Vdc (48 Vdc typical), maximum 0.41 A (0.153 A at 48 Vdc input)
Model MHFS64809: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.150 A at 48 Vdc input)
Model MHFS64812: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.149 A at 48 Vdc input)
Model MHFS64815: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.149 A at 48 Vdc input)

Model MHFW61212: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.59 A (0.60 A at 12 Vdc input)
Model MHFW61215: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.59 A (0.60 A at 12 Vdc input)

Model MHFW62412: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)
Model MHFW62415: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)

Model MHFW64812: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.149 A at 48 Vdc input)
Model MHFW64815: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.149 A at 48 Vdc input)

<Output rating>

See test report for details.

Additional information (if necessary)



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-05-21

Original Issue Date: 2023-12-04

Signature:

Mauricio Avila



Ref. Certif. No.

US-43088-M1-UL

Additionally evaluated to:

EN 60601-1:2006, EN 60601-1:2006/A1:2013, EN 60601-1:2006/A2:2021, EN 60601-1:2006/A12:2014

Summary of Modifications:

- Update the List of Critical Components table to correct the "Manufacturer" and "Mark(s) of Conformity" of Alternate Potting Compound, Type TIA208R; from "MOMENTIVE PERFORMANCE MATERIALS JAPAN L L C" and "UL (E56745)" to "MOMENTIVE PERFORMANCE MATERIALS (NAN TONG) CO LTD" and "UL (E320603)".

- Changed altitude from "4000m" to "3000m".

- Updated model number to include optional model suffixes.

See CB Test Report for details.

Additional information (if necessary)



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-05-21

Original Issue Date: 2023-12-04

Signature:

Mauricio Avila



Ref. Certif. No.

US-43088-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	DC-DC Converter
Name and address of the applicant	COSEL CO LTD 1-6-43 KAMIAKAE-MACHI TOYAMA-SHI, Toyama, 930-0816 Japan
Name and address of the manufacturer	COSEL CO LTD 1-6-43 KAMIAKAE-MACHI TOYAMA-SHI, Toyama, 930-0816 Japan
Name and address of the factory	COSEL CO LTD 1-6-43 KAMIAKAE-MACHI TOYAMA-SHI, Toyama, 930-0816 Japan
Note: When more than one factory, please report on page 2	<input checked="" type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	Input: 4.5-18 Vdc (12 Vdc typical model), 9-36 Vdc (24 Vdc typical model), 18-76 Vdc (48 Vdc typical model) Output: 3.3, 5, 9, 12, 15 Vdc (Single output model), ±12, ±15 V (Dual output model) <input checked="" type="checkbox"/> Additional Information on page 2
Trademark / Brand (if any)	
Customer's Testing Facility (CTF) Stage used	CTF Stage 2
Model / Type Ref.	MHFW64812, MHFW64815, MHFS61205, MHFS61209, MHFS61212, MHFS61215, MHFS6123R3, MHFS62405, MHFS62409, MHFS62412, MHFS62415, MHFS6243R3, MHFS64805, MHFS64809, MHFS64812, MHFS64815, MHFS6483R3, MHFW61212, MHFW61215, MHFW62412, MHFW62415 <input checked="" type="checkbox"/> Additional Information on page 2
Additional information (if necessary may also be reported on page 2)	Additionally evaluated to: EN 60601-1:2006, EN 60601-1:2006/A1:2013, EN 60601-1:2006/A12:2014, EN 60601-1:2006/A2:2021 The risk management requirements of the standard were not addressed National Differences: EU Group Differences, CA, US <input type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60601-1:2005, IEC 60601-1:2005/AMD1:2012, IEC 60601-1:2005/AMD2:2020
As shown in the Test Report Ref. No. which forms part of this Certificate	E161890-D1068-1/A0/C0-CB issued on 2023-11-28

This CB Test Certificate is issued by the National Certification Body



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-12-04

Signature:

Jolanta M. Wroblewska



Ref. Certif. No.

US-43088-UL

Factory(ies):

COSEL CO LTD
TATEYAMA FACTORY, 78 DOGENJI TATEYAMAMACHI NAKANIKAWA-GUN, Toyama, 930-0241
Japan

Additional Model Detail(s):

MHFx6yz (x = S, W, y = 12, 24 or 48 (for "S" or "W" in suffix x), z = 3R3, 05, 09, 12 or 15 (for "S" in suffix x), z = 12 or 15 (for "W" in suffix x), may be followed by suffix "-#" which can be any number 0 to 9 or any letter A to Z or blank, single number, letter or in the combination of two or more.

Additional Ratings:

<Input rating>

Model MHFS6123R3: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.53 A (0.58 A at 12 Vdc input)
Model MHFS61205: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.63 A (0.61 A at 12 Vdc input)
Model MHFS61209: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.60 A (0.60 A at 12 Vdc input)
Model MHFS61212: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.59 A (0.60 A at 12 Vdc input)
Model MHFS61215: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.59 A (0.60 A at 12 Vdc input)

Model MHFS6243R3: 9 – 36 Vdc (24 Vdc typical), maximum 0.77 A (0.29 A at 24 Vdc input)
Model MHFS62405: 9 – 36 Vdc (24 Vdc typical), maximum 0.82 A (0.31 A at 24 Vdc input)
Model MHFS62409: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)
Model MHFS62412: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)
Model MHFS62415: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)

Model MHFS6483R3: 18 – 76 Vdc (48 Vdc typical), maximum 0.39 A (0.143 A at 48 Vdc input)
Model MHFS64805: 18 – 76 Vdc (48 Vdc typical), maximum 0.41 A (0.153 A at 48 Vdc input)
Model MHFS64809: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.150 A at 48 Vdc input)
Model MHFS64812: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.149 A at 48 Vdc input)
Model MHFS64815: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.149 A at 48 Vdc input)

Model MHFW61212: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.59 A (0.60 A at 12 Vdc input)
Model MHFW61215: 4.5 – 18 Vdc (12 Vdc typical), maximum 1.59 A (0.60 A at 12 Vdc input)

Model MHFW62412: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)
Model MHFW62415: 9 – 36 Vdc (24 Vdc typical), maximum 0.80 A (0.30 A at 24 Vdc input)

Model MHFW64812: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.149 A at 48 Vdc input)
Model MHFW64815: 18 – 76 Vdc (48 Vdc typical), maximum 0.40 A (0.149 A at 48 Vdc input)

<Output rating>

See test report for details.

Additional information (if necessary)



UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
 UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
 UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
 UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-12-04

Signature:

Jolanta M. Wroblewska