

TEST DATA OF MHFS61215

Regulated DC Power Supply
October 26, 2021

Approved by : _____ Kenichi Tsukada

Design Manager

Prepared by : _____ Yoshihiko Saeki

Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Line Regulation	3
4.Load Regulation	4
5.Ripple-Noise	4
6.Dynamic Load Response	5
7.Rise and Fall Time	6
8.Overcurrent Protection	7
9.Ambient Temperature Drift	8
10.Minimum Input Voltage for Regulated Output Voltage	8
11.Switching frequency (by Load Current)	9
12.Figure of Testing Circuitry	10

(Final Page 10)

COSEL

Model	MHFS61215	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Input Current (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 4.5V - -□--- Input Volt. 5V - -*--- Input Volt. 9V - -○--- Input Volt. 12V - -◇--- Input Volt. 18V																																																																														
			2.Values																																																																													
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Input Current [A]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>0.054</td> <td>0.049</td> <td>0.019</td> <td>0.014</td> <td>0.012</td> </tr> <tr> <td>0.08</td> <td>0.343</td> <td>0.310</td> <td>0.177</td> <td>0.139</td> <td>0.110</td> </tr> <tr> <td>0.16</td> <td>0.644</td> <td>0.579</td> <td>0.328</td> <td>0.250</td> <td>0.183</td> </tr> <tr> <td>0.24</td> <td>0.954</td> <td>0.853</td> <td>0.475</td> <td>0.363</td> <td>0.256</td> </tr> <tr> <td>0.32</td> <td>1.275</td> <td>1.140</td> <td>0.624</td> <td>0.473</td> <td>0.331</td> </tr> <tr> <td>0.36</td> <td>1.443</td> <td>1.290</td> <td>0.701</td> <td>0.529</td> <td>0.367</td> </tr> <tr> <td>0.40</td> <td>*1</td> <td>1.437</td> <td>0.777</td> <td>0.585</td> <td>0.404</td> </tr> <tr> <td>0.44</td> <td>*1</td> <td>1.590</td> <td>0.856</td> <td>0.642</td> <td>0.440</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Load Current [A]	Input Current [A]					4.5[V]	5[V]	9[V]	12[V]	18[V]	0.00	0.054	0.049	0.019	0.014	0.012	0.08	0.343	0.310	0.177	0.139	0.110	0.16	0.644	0.579	0.328	0.250	0.183	0.24	0.954	0.853	0.475	0.363	0.256	0.32	1.275	1.140	0.624	0.473	0.331	0.36	1.443	1.290	0.701	0.529	0.367	0.40	*1	1.437	0.777	0.585	0.404	0.44	*1	1.590	0.856	0.642	0.440	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Input Current [A]																																																																															
	4.5[V]	5[V]	9[V]	12[V]	18[V]																																																																											
0.00	0.054	0.049	0.019	0.014	0.012																																																																											
0.08	0.343	0.310	0.177	0.139	0.110																																																																											
0.16	0.644	0.579	0.328	0.250	0.183																																																																											
0.24	0.954	0.853	0.475	0.363	0.256																																																																											
0.32	1.275	1.140	0.624	0.473	0.331																																																																											
0.36	1.443	1.290	0.701	0.529	0.367																																																																											
0.40	*1	1.437	0.777	0.585	0.404																																																																											
0.44	*1	1.590	0.856	0.642	0.440																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
			*1 Maximum output current at 4.5V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																													

Note: Slanted line shows the range of the rated load current.

COSEL


Model	MHFS61215	Temperature Testing Circuitry	25°C Figure A																																																																													
Item	Efficiency (by Load Current)																																																																															
Object	_____																																																																															
1.Graph		—△— Input Volt. 4.5V - -□--- Input Volt. 5V - -*--- Input Volt. 9V - -○--- Input Volt. 12V - -◇--- Input Volt. 18V																																																																														
<p>The graph shows efficiency increasing with load current for all input voltages. A slanted line from approximately (0.1, 60) to (0.4, 40) indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>4.5[V]</th> <th>5[V]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.08</td><td>77.9</td><td>77.7</td><td>75.6</td><td>71.9</td><td>60.6</td></tr> <tr><td>0.16</td><td>82.9</td><td>83.0</td><td>81.4</td><td>80.0</td><td>72.9</td></tr> <tr><td>0.24</td><td>84.0</td><td>84.4</td><td>84.3</td><td>82.6</td><td>78.1</td></tr> <tr><td>0.32</td><td>83.6</td><td>84.1</td><td>85.4</td><td>84.5</td><td>80.7</td></tr> <tr><td>0.36</td><td>83.1</td><td>83.8</td><td>85.6</td><td>85.1</td><td>81.7</td></tr> <tr><td>0.40</td><td>*1</td><td>83.4</td><td>85.7</td><td>85.4</td><td>82.6</td></tr> <tr><td>0.44</td><td>*1</td><td>82.9</td><td>85.7</td><td>85.6</td><td>83.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	4.5[V]	5[V]	9[V]	12[V]	18[V]	0.00	-	-	-	-	-	0.08	77.9	77.7	75.6	71.9	60.6	0.16	82.9	83.0	81.4	80.0	72.9	0.24	84.0	84.4	84.3	82.6	78.1	0.32	83.6	84.1	85.4	84.5	80.7	0.36	83.1	83.8	85.6	85.1	81.7	0.40	*1	83.4	85.7	85.4	82.6	0.44	*1	82.9	85.7	85.6	83.2	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-	2.Values							
Load Current [A]	4.5[V]	5[V]	9[V]	12[V]	18[V]																																																																											
0.00	-	-	-	-	-																																																																											
0.08	77.9	77.7	75.6	71.9	60.6																																																																											
0.16	82.9	83.0	81.4	80.0	72.9																																																																											
0.24	84.0	84.4	84.3	82.6	78.1																																																																											
0.32	83.6	84.1	85.4	84.5	80.7																																																																											
0.36	83.1	83.8	85.6	85.1	81.7																																																																											
0.40	*1	83.4	85.7	85.4	82.6																																																																											
0.44	*1	82.9	85.7	85.6	83.2																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 4.5[V]</th> <th>Input Volt. 5[V]</th> <th>Input Volt. 9[V]</th> <th>Input Volt. 12[V]</th> <th>Input Volt. 18[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.08</td><td>77.9</td><td>77.7</td><td>75.6</td><td>71.9</td><td>60.6</td></tr> <tr><td>0.16</td><td>82.9</td><td>83.0</td><td>81.4</td><td>80.0</td><td>72.9</td></tr> <tr><td>0.24</td><td>84.0</td><td>84.4</td><td>84.3</td><td>82.6</td><td>78.1</td></tr> <tr><td>0.32</td><td>83.6</td><td>84.1</td><td>85.4</td><td>84.5</td><td>80.7</td></tr> <tr><td>0.36</td><td>83.1</td><td>83.8</td><td>85.6</td><td>85.1</td><td>81.7</td></tr> <tr><td>0.40</td><td>*1</td><td>83.4</td><td>85.7</td><td>85.4</td><td>82.6</td></tr> <tr><td>0.44</td><td>*1</td><td>82.9</td><td>85.7</td><td>85.6</td><td>83.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]					Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]	0.00	-	-	-	-	-	0.08	77.9	77.7	75.6	71.9	60.6	0.16	82.9	83.0	81.4	80.0	72.9	0.24	84.0	84.4	84.3	82.6	78.1	0.32	83.6	84.1	85.4	84.5	80.7	0.36	83.1	83.8	85.6	85.1	81.7	0.40	*1	83.4	85.7	85.4	82.6	0.44	*1	82.9	85.7	85.6	83.2	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Efficiency [%]																																																																															
	Input Volt. 4.5[V]	Input Volt. 5[V]	Input Volt. 9[V]	Input Volt. 12[V]	Input Volt. 18[V]																																																																											
0.00	-	-	-	-	-																																																																											
0.08	77.9	77.7	75.6	71.9	60.6																																																																											
0.16	82.9	83.0	81.4	80.0	72.9																																																																											
0.24	84.0	84.4	84.3	82.6	78.1																																																																											
0.32	83.6	84.1	85.4	84.5	80.7																																																																											
0.36	83.1	83.8	85.6	85.1	81.7																																																																											
0.40	*1	83.4	85.7	85.4	82.6																																																																											
0.44	*1	82.9	85.7	85.6	83.2																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
*1 Maximum output current at 4.5V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.																																																																																

Note: Slanted line shows the range of the rated load current.

COSEL

Model	MHFS61215	Temperature	25°C
Item	Line Regulation	Testing Circuitry	Figure A
Object	+15V0.4A		

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
4.3	14.957	*1
4.5	14.957	*1
5.0	14.957	14.964
7.5	14.957	14.964
9.0	14.957	14.964
12.0	14.956	14.964
15.0	14.956	14.963
18.0	14.955	14.962
20.0	14.955	14.962

*1 Maximum output current at 4.5V input
Voltage is 80% of rated load current.
Refer to instruction manuals for details of
input derating.


COSEL

Model	MHFS61215	Temperature	25°C																																																																													
Item	Load Regulation	Testing Circuitry	Figure A																																																																													
Object	+15V0.4A																																																																															
1.Graph	<p>Input Volt. 4.5V Input Volt. 5V Input Volt. 9V Input Volt. 12V Input Volt. 18V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																																																															
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="5">Output Voltage [V]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>14.972</td> <td>14.971</td> <td>14.972</td> <td>14.971</td> <td>14.970</td> </tr> <tr> <td>0.08</td> <td>14.971</td> <td>14.970</td> <td>14.969</td> <td>14.967</td> <td>14.966</td> </tr> <tr> <td>0.16</td> <td>14.970</td> <td>14.970</td> <td>14.968</td> <td>14.967</td> <td>14.964</td> </tr> <tr> <td>0.24</td> <td>14.970</td> <td>14.970</td> <td>14.968</td> <td>14.966</td> <td>14.963</td> </tr> <tr> <td>0.32</td> <td>14.969</td> <td>14.969</td> <td>14.967</td> <td>14.965</td> <td>14.962</td> </tr> <tr> <td>0.36</td> <td>14.969</td> <td>14.969</td> <td>14.966</td> <td>14.965</td> <td>14.962</td> </tr> <tr> <td>0.40</td> <td>*1</td> <td>14.968</td> <td>14.967</td> <td>14.965</td> <td>14.962</td> </tr> <tr> <td>0.44</td> <td>*1</td> <td>14.968</td> <td>14.966</td> <td>14.965</td> <td>14.962</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]					4.5[V]	5[V]	9[V]	12[V]	18[V]	0.00	14.972	14.971	14.972	14.971	14.970	0.08	14.971	14.970	14.969	14.967	14.966	0.16	14.970	14.970	14.968	14.967	14.964	0.24	14.970	14.970	14.968	14.966	14.963	0.32	14.969	14.969	14.967	14.965	14.962	0.36	14.969	14.969	14.966	14.965	14.962	0.40	*1	14.968	14.967	14.965	14.962	0.44	*1	14.968	14.966	14.965	14.962	--	-	-	-	-	-	--	-	-	-	-	-	--	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																																															
	4.5[V]	5[V]	9[V]	12[V]	18[V]																																																																											
0.00	14.972	14.971	14.972	14.971	14.970																																																																											
0.08	14.971	14.970	14.969	14.967	14.966																																																																											
0.16	14.970	14.970	14.968	14.967	14.964																																																																											
0.24	14.970	14.970	14.968	14.966	14.963																																																																											
0.32	14.969	14.969	14.967	14.965	14.962																																																																											
0.36	14.969	14.969	14.966	14.965	14.962																																																																											
0.40	*1	14.968	14.967	14.965	14.962																																																																											
0.44	*1	14.968	14.966	14.965	14.962																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
--	-	-	-	-	-																																																																											
	<p>*1 Maximum output current at 4.5V input Voltage is 80% of rated load current. Refer to instruction manuals for details of input derating.</p>																																																																															
Item	Ripple-Noise	Temperature	25°C																																																																													
Object	+15V0.4A	Testing Circuitry	Figure B																																																																													
1.Graph	<p>Input Voltage 12V Load 100%</p> <p>10[mV/div]</p> <p>1[μs/div]</p>																																																																															

COSEL

Model	MHFS61215	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V0.4A		


Input Volt. 12 V
 Cycle 100 ms

Response. $t_1=t_2=50\mu s$. Typ

Min.Load (0A)↔
 Load 100% (0.4A)

500 mV/div

1 ms/div




1 ms/div

Min.Load (0A)↔
 Load 50% (0.2A)

500 mV/div

1 ms/div




1 ms/div

COSEL

Model	MHFS61215
Item	Rise and Fall Time
Object	+15V0.4A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load	Time	Td	Tr	Ts	Th	Tf	[ms]
50 %		0.4	3.1	3.5	0.2	2.4	
100 %		0.4	3.2	3.6	0.1	0.8	



COSEL

Model	MHFS61215	Temperature Testing Circuitry	25°C Figure A																																																																																			
Item	Overcurrent Protection																																																																																					
Object	+15V0.4A																																																																																					
1.Graph	<p>The graph plots Output Voltage [V] on the Y-axis (0 to 20) against Load Current [A] on the X-axis (0.0 to 1.2). Five curves are shown for different input voltages: 4.5V (black), 5V (blue), 9V (green), 12V (red), and 18V (magenta). All curves show a linear decrease in output voltage as load current increases. A slanted line is drawn from approximately (0.35A, 15.5V) down to (0.85A, 0V), representing the range of rated load current at 4.5V input.</p>																																																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="5">Load Current [A]</th> </tr> <tr> <th>4.5[V]</th> <th>5[V]</th> <th>9[V]</th> <th>12[V]</th> <th>18[V]</th> </tr> </thead> <tbody> <tr><td>14.3</td><td>0.486</td><td>0.498</td><td>0.575</td><td>0.568</td><td>0.543</td></tr> <tr><td>13.5</td><td>0.505</td><td>0.517</td><td>0.589</td><td>0.581</td><td>0.556</td></tr> <tr><td>12.0</td><td>0.544</td><td>0.557</td><td>0.619</td><td>0.608</td><td>0.581</td></tr> <tr><td>10.5</td><td>0.589</td><td>0.601</td><td>0.654</td><td>0.640</td><td>0.606</td></tr> <tr><td>9.0</td><td>0.647</td><td>0.655</td><td>0.690</td><td>0.671</td><td>0.635</td></tr> <tr><td>7.5</td><td>0.696</td><td>0.707</td><td>0.729</td><td>0.704</td><td>0.655</td></tr> <tr><td>6.0</td><td>0.760</td><td>0.768</td><td>0.773</td><td>0.739</td><td>0.685</td></tr> <tr><td>4.5</td><td>0.818</td><td>0.828</td><td>0.818</td><td>0.776</td><td>0.715</td></tr> <tr><td>3.0</td><td>0.882</td><td>0.891</td><td>0.863</td><td>0.814</td><td>0.745</td></tr> <tr><td>1.5</td><td>0.942</td><td>0.948</td><td>0.906</td><td>0.846</td><td>0.769</td></tr> <tr><td>0.0</td><td>0.890</td><td>0.879</td><td>0.779</td><td>0.711</td><td>0.638</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]					4.5[V]	5[V]	9[V]	12[V]	18[V]	14.3	0.486	0.498	0.575	0.568	0.543	13.5	0.505	0.517	0.589	0.581	0.556	12.0	0.544	0.557	0.619	0.608	0.581	10.5	0.589	0.601	0.654	0.640	0.606	9.0	0.647	0.655	0.690	0.671	0.635	7.5	0.696	0.707	0.729	0.704	0.655	6.0	0.760	0.768	0.773	0.739	0.685	4.5	0.818	0.828	0.818	0.776	0.715	3.0	0.882	0.891	0.863	0.814	0.745	1.5	0.942	0.948	0.906	0.846	0.769	0.0	0.890	0.879	0.779	0.711	0.638	--	-	-	-	-	-
Output Voltage [V]	Load Current [A]																																																																																					
	4.5[V]	5[V]	9[V]	12[V]	18[V]																																																																																	
14.3	0.486	0.498	0.575	0.568	0.543																																																																																	
13.5	0.505	0.517	0.589	0.581	0.556																																																																																	
12.0	0.544	0.557	0.619	0.608	0.581																																																																																	
10.5	0.589	0.601	0.654	0.640	0.606																																																																																	
9.0	0.647	0.655	0.690	0.671	0.635																																																																																	
7.5	0.696	0.707	0.729	0.704	0.655																																																																																	
6.0	0.760	0.768	0.773	0.739	0.685																																																																																	
4.5	0.818	0.828	0.818	0.776	0.715																																																																																	
3.0	0.882	0.891	0.863	0.814	0.745																																																																																	
1.5	0.942	0.948	0.906	0.846	0.769																																																																																	
0.0	0.890	0.879	0.779	0.711	0.638																																																																																	
--	-	-	-	-	-																																																																																	
Note:	<p>Slanted line shows the range of the rated load current.</p> <p>Maximum output current at 4.5V input Voltage is 80% of rated load current.</p> <p>Refer to instruction manuals for details of input derating.</p>																																																																																					



Model	MHFS61215	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+15V0.4A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]				
	Input Volt. 4.5V*1	Input Volt. 5V	Input Volt. 9V	Input Volt. 12V	Input Volt. 18V
-40	14.856	14.858	14.859	14.860	14.859
25	14.958	14.960	14.958	14.958	14.957
55	14.976	14.978	14.978	14.977	14.976

*1 Load 80%


Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+15V0.4A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 80%
-40	3.6	3.5
25	3.6	3.6
55	3.5	3.5

COSEL

Model	MHFS61215
Item	Switching frequency (by Load Current)
Object	+15V0.4A



Note: Slanted line shows the range of the rated load current.

When load current is low, MH operates intermittently, so switching frequency would not become constant.

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Switching Frequency [kHz]				
	4.5[V]	5[V]	9[V]	12[V]	18[V]
0.00	1124	1164	1340	1322	1321
0.08	667	711	962	1032	1102
0.16	461	506	738	815	901
0.24	353	394	605	680	770
0.32	283	316	509	586	670
0.36	257	287	473	546	636
0.40	*1	264	438	512	594
0.44	*1	243	412	480	564
--	-	-	-	-	-
--	-	-	-	-	-
--	-	-	-	-	-

*1 Maximum output current at 4.5V input Voltage is 80% of rated load current.
Refer to instruction manuals for details of input derating.

COSEL




Figure A

Data Acquisition/Control Unit




Figure B