

COSEL

TEST DATA OF MMB50A-3
(100V INPUT)

Regulated DC Power Supply

Date : Feb. 15. 1999

Approved by : H. Ishikawa
Design Manager

Prepared by : H. Ishikawa
Design Engineer

コーワセル株式会社
COSEL CO., LTD.



CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency (by Input Voltage)	2
効率(入力電圧特性)	
3. Power Factor (by Input Voltage)	3
力率(入力電圧特性)	
4. Hold-Up Time	4
出力保持時間	
5. Instantaneous Interruption Compensation	6
瞬時停電保障	
6. Load Regulation	8
静的負荷変動	
7. Ripple Voltage (by Load Current)	9
リップル電圧(負荷特性)	
8. Ripple-Noise	11
リップルノイズ	
9. Overcurrent Protection	13
過電流保護	
10. Overvoltage Protection	14
過電圧保護	
11. Inrush Current	15
突入電流	
12. Dynamic Load Response	16
動的負荷変動	
13. Rise and Fall Time	18
立上り、立下がり時間	
14. Ambient Temperature Drift	20
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	21
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	22
リップル電圧(周囲温度特性)	
17. Time Lapse Drift	23
経時ドリフト	
18. Output Voltage Accuracy	24
定電圧精度	
19. Condensation	25
結露特性	
20. Leakage Current	27
漏洩電流	
21. Conducted Emission	28
雑音端子電圧	
22. Figure of Testing Circuitry	29
測定回路図	

(Final Page 30)

COSSEL

Model MMB50A-3

Item Line Regulation 静的入力変動


Object +5.0V 3.00A

Temperature 25°C
Testing Circuitry Figure A

1. Graph

Load 50% □

Load 100% △



2. Values


Input Voltage [V]	Load 50%	Load 100%
	Output Volt. [V]	Output Volt. [V]
75	5.026	5.022
80	5.026	5.023
85	5.026	5.023
90	5.026	5.023
100	5.026	5.023
110	5.026	5.023
120	5.026	5.023
132	5.026	5.023
140	5.026	5.023
—	—	—
—	—	—
—	—	—

Object +24V 1.50A

1. Graph

Load 50% □

Load 100% △



2. Values

Input Voltage [V]	Load 50%	Load 100%
	Output Volt. [V]	Output Volt. [V]
75	23.990	23.986
80	23.990	23.986
85	23.990	23.986
90	23.990	23.987
100	23.990	23.987
110	23.990	23.987
120	23.990	23.987
132	23.990	23.987
140	23.990	23.987
—	—	—
—	—	—
—	—	—

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL


Model	MMB50A-3	Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)																																		
Object																																			
1. Graph	<p style="text-align: center;">-----□----- Load 50% -----△----- Load 100%</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>80</td><td>72.5</td><td>75.0</td></tr> <tr><td>90</td><td>71.0</td><td>75.0</td></tr> <tr><td>100</td><td>69.0</td><td>75.0</td></tr> <tr><td>110</td><td>66.5</td><td>74.5</td></tr> <tr><td>120</td><td>64.5</td><td>74.0</td></tr> <tr><td>130</td><td>63.0</td><td>73.5</td></tr> <tr><td>140</td><td>62.0</td><td>73.0</td></tr> </tbody> </table>		Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	80	72.5	75.0	90	71.0	75.0	100	69.0	75.0	110	66.5	74.5	120	64.5	74.0	130	63.0	73.5	140	62.0	73.0									
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																																	
80	72.5	75.0																																	
90	71.0	75.0																																	
100	69.0	75.0																																	
110	66.5	74.5																																	
120	64.5	74.0																																	
130	63.0	73.5																																	
140	62.0	73.0																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Efficiency [%]</th> <th>Efficiency [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>71.8</td><td>75.4</td></tr> <tr><td>80</td><td>71.8</td><td>75.9</td></tr> <tr><td>85</td><td>71.2</td><td>76.0</td></tr> <tr><td>90</td><td>70.7</td><td>76.1</td></tr> <tr><td>100</td><td>69.2</td><td>76.0</td></tr> <tr><td>110</td><td>67.5</td><td>75.7</td></tr> <tr><td>120</td><td>65.7</td><td>75.1</td></tr> <tr><td>132</td><td>63.5</td><td>74.3</td></tr> <tr><td>140</td><td>62.0</td><td>73.7</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Efficiency [%]	Efficiency [%]	75	71.8	75.4	80	71.8	75.9	85	71.2	76.0	90	70.7	76.1	100	69.2	76.0	110	67.5	75.7	120	65.7	75.1	132	63.5	74.3	140	62.0	73.7
Input Voltage [V]	Load 50%	Load 100%																																	
	Efficiency [%]	Efficiency [%]																																	
75	71.8	75.4																																	
80	71.8	75.9																																	
85	71.2	76.0																																	
90	70.7	76.1																																	
100	69.2	76.0																																	
110	67.5	75.7																																	
120	65.7	75.1																																	
132	63.5	74.3																																	
140	62.0	73.7																																	

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSSEL

Model	MMB50A-3
Item	Power Factor (by Input Voltage) 力率(入力電圧特性)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	load 50%	load 100%
	Power Factor	Power Factor
75	0.60	0.60
80	0.57	0.59
85	0.57	0.58
90	0.56	0.57
100	0.55	0.56
110	0.53	0.54
120	0.52	0.53
132	0.51	0.52
140	0.51	0.52


Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSSEL

Model	MMB50A-3
Item	Hold-Up Time 出力保持時間
Object	+5.0V3A

Temperature 25°C
Testing Circuitry Figure A



2. Values

Input Voltage [V]	Load 50%	Load 100%
	Hold-Up Time [mS]	Hold-Up Time [mS]
75	42	21
80	48	26
85	54	32
90	61	37
100	76	50
110	92	64
120	110	79
132	134	99
140	151	114

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSSEL

Model	MMB50A-3	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+24.0V 1.5A																																		
1. Graph	<p>Y-axis: Hold-Up Time [mS] (logarithmic scale: 1, 10, 100, 1000)</p> <p>X-axis: Input Voltage [V] (linear scale: 0, 80, 90, 100, 110, 120, 130, 140, 150)</p> <p>Legend: Load 50% (△), Load 100% (□)</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Hold-Up Time [mS]</th> <th>Hold-Up Time [mS]</th> </tr> </thead> <tbody> <tr><td>75</td><td>55</td><td>28</td></tr> <tr><td>80</td><td>62</td><td>33</td></tr> <tr><td>85</td><td>70</td><td>39</td></tr> <tr><td>90</td><td>78</td><td>44</td></tr> <tr><td>100</td><td>97</td><td>57</td></tr> <tr><td>110</td><td>117</td><td>71</td></tr> <tr><td>120</td><td>139</td><td>86</td></tr> <tr><td>132</td><td>168</td><td>106</td></tr> <tr><td>140</td><td>189</td><td>121</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Hold-Up Time [mS]	Hold-Up Time [mS]	75	55	28	80	62	33	85	70	39	90	78	44	100	97	57	110	117	71	120	139	86	132	168	106	140	189	121
Input Voltage [V]	Load 50%	Load 100%																																	
	Hold-Up Time [mS]	Hold-Up Time [mS]																																	
75	55	28																																	
80	62	33																																	
85	70	39																																	
90	78	44																																	
100	97	57																																	
110	117	71																																	
120	139	86																																	
132	168	106																																	
140	189	121																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	MMB50A-3	Temperature 25°C Testing Circuitry Figure A																																																				
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																					
Object	+5.0V 3.00A																																																					
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V 																																																					
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>85[V]</th> <th>100[V]</th> <th>132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>0.6</td> <td>70</td> <td>95</td> <td>160</td> </tr> <tr> <td>1.2</td> <td>55</td> <td>78</td> <td>139</td> </tr> <tr> <td>1.8</td> <td>45</td> <td>65</td> <td>123</td> </tr> <tr> <td>2.4</td> <td>35</td> <td>55</td> <td>107</td> </tr> <tr> <td>3.0</td> <td>22</td> <td>44</td> <td>94</td> </tr> <tr> <td>3.3</td> <td>19</td> <td>37</td> <td>86</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Input Volt.	Input Volt.	Input Volt.	85[V]	100[V]	132[V]	0.0	—	—	—	0.6	70	95	160	1.2	55	78	139	1.8	45	65	123	2.4	35	55	107	3.0	22	44	94	3.3	19	37	86	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt.	Input Volt.	Input Volt.																																																			
	85[V]	100[V]	132[V]																																																			
0.0	—	—	—																																																			
0.6	70	95	160																																																			
1.2	55	78	139																																																			
1.8	45	65	123																																																			
2.4	35	55	107																																																			
3.0	22	44	94																																																			
3.3	19	37	86																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
—	—	—	—																																																			
	<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																					

COSEL

Model	MMB50A-3	Temperature Testing Circuitry 25°C Figure A			
Item	Instantaneous Interruption Compensation 瞬時停電保障				
Object	+24.0V 1.50A				
1. Graph					
		△ Input Volt. 85 V	□ Input Volt. 100 V	○ Input Volt. 132 V	
Instantaneous Compensation Time [mS]	10000	1000	100	10	
	1000	100	10	1	
Load Current [A]	0	0.5	1	1.5	2
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated load current.</p>					
<p>瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>					
2. Values					
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]		
	Time [mS]				
0.00	—	—	—		
0.30	111	148	246		
0.60	77	107	189		
0.90	60	85	154		
1.20	46	65	126		
1.50	31	53	104		
1.65	28	46	94		
—	—	—	—		
—	—	—	—		
—	—	—	—		
—	—	—	—		

COSEL

Model	MMB50A-3	Temperature 25°C Testing Circuitry Figure A																																														
Item	Load Regulation 静的負荷変動																																															
Object	+5.0V3.00A																																															
1. Graph	<p>—△— Input Volt. 85V —□— Input Volt. 100V —○— Input Volt. 132V</p>																																															
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>5.030</td><td>5.030</td><td>5.030</td></tr> <tr><td>0.600</td><td>5.029</td><td>5.029</td><td>5.028</td></tr> <tr><td>1.200</td><td>5.027</td><td>5.027</td><td>5.027</td></tr> <tr><td>1.800</td><td>5.026</td><td>5.026</td><td>5.025</td></tr> <tr><td>2.400</td><td>5.024</td><td>5.024</td><td>5.024</td></tr> <tr><td>3.000</td><td>5.023</td><td>5.023</td><td>5.023</td></tr> <tr><td>3.300</td><td>5.022</td><td>5.022</td><td>5.022</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	0.000	5.030	5.030	5.030	0.600	5.029	5.029	5.028	1.200	5.027	5.027	5.027	1.800	5.026	5.026	5.025	2.400	5.024	5.024	5.024	3.000	5.023	5.023	5.023	3.300	5.022	5.022	5.022	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																													
0.000	5.030	5.030	5.030																																													
0.600	5.029	5.029	5.028																																													
1.200	5.027	5.027	5.027																																													
1.800	5.026	5.026	5.025																																													
2.400	5.024	5.024	5.024																																													
3.000	5.023	5.023	5.023																																													
3.300	5.022	5.022	5.022																																													
—	—	—	—																																													
—	—	—	—																																													
—	—	—	—																																													
Object	+24V1.50A	<p>1. Graph</p> <p>—△— Input Volt. 85V —□— Input Volt. 100V —○— Input Volt. 132V</p>																																														
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> </thead> <tbody> <tr><td>0.000</td><td>24.001</td><td>24.002</td><td>24.002</td></tr> <tr><td>0.300</td><td>23.994</td><td>23.994</td><td>23.994</td></tr> <tr><td>0.600</td><td>23.992</td><td>23.992</td><td>23.992</td></tr> <tr><td>0.900</td><td>23.991</td><td>23.990</td><td>23.990</td></tr> <tr><td>1.200</td><td>23.989</td><td>23.989</td><td>23.989</td></tr> <tr><td>1.500</td><td>23.988</td><td>23.988</td><td>23.987</td></tr> <tr><td>1.650</td><td>23.987</td><td>23.987</td><td>23.987</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	0.000	24.001	24.002	24.002	0.300	23.994	23.994	23.994	0.600	23.992	23.992	23.992	0.900	23.991	23.990	23.990	1.200	23.989	23.989	23.989	1.500	23.988	23.988	23.987	1.650	23.987	23.987	23.987	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																													
0.000	24.001	24.002	24.002																																													
0.300	23.994	23.994	23.994																																													
0.600	23.992	23.992	23.992																																													
0.900	23.991	23.990	23.990																																													
1.200	23.989	23.989	23.989																																													
1.500	23.988	23.988	23.987																																													
1.650	23.987	23.987	23.987																																													
—	—	—	—																																													
—	—	—	—																																													
—	—	—	—																																													
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																

Model	MMB50A-3	Temperature Testing Circuitry 25°C Figure A
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)	
Object	+5.0V 3.00A	

1. Graph

Load Current [A]	Input Volt. 85 [V] Ripple Output Volt. [mV]	Input Volt. 132 [V] Ripple Output Volt. [mV]
0.0	5	5
0.6	5	5
1.2	5	5
1.8	5	5
2.4	10	10
3.0	10	10
3.3	10	10
—	—	—
—	—	—
—	—	—
—	—	—

2. Values

Ripple Voltage is shown as p-p in the figure below.



Note: Slanted line shows the range of the rated load current.

リップル電圧は、下図 p - p 値で示される。
(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form
図 リップル波形詳細図

COSSEL

Model	MMB50A-3	Temperature	25°C																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)	Testing Circuitry	Figure A																																						
Object	+24.0V 1.50A																																								
1. Graph																																									
		Input Volt. 85V [mV] □ Input Volt. 132V [mV] △																																							
																																									
		2. Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.3</td><td>5</td><td>5</td></tr> <tr><td>0.6</td><td>5</td><td>5</td></tr> <tr><td>0.9</td><td>5</td><td>5</td></tr> <tr><td>1.2</td><td>10</td><td>10</td></tr> <tr><td>1.5</td><td>10</td><td>10</td></tr> <tr><td>1.7</td><td>10</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.0	5	5	0.3	5	5	0.6	5	5	0.9	5	5	1.2	10	10	1.5	10	10	1.7	10	10	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.0	5	5																																							
0.3	5	5																																							
0.6	5	5																																							
0.9	5	5																																							
1.2	10	10																																							
1.5	10	10																																							
1.7	10	10																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p-p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> 																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	MMB50A-3	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	+5.0V 3.00A																																								
1. Graph	-----□----- Input Volt. 85V [mV] -----△----- Input Volt. 132V	2. Values																																							
			<table border="1"> <thead> <tr> <th>Load current [A]</th> <th>Input Volt. 85 [V] Ripple-Noise [mV]</th> <th>Input Volt. 132 [V] Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>0.6</td><td>20</td><td>20</td></tr> <tr><td>1.2</td><td>20</td><td>20</td></tr> <tr><td>1.8</td><td>20</td><td>20</td></tr> <tr><td>2.4</td><td>20</td><td>20</td></tr> <tr><td>3.0</td><td>20</td><td>20</td></tr> <tr><td>3.3</td><td>20</td><td>20</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load current [A]	Input Volt. 85 [V] Ripple-Noise [mV]	Input Volt. 132 [V] Ripple-Noise [mV]	0.0	20	20	0.6	20	20	1.2	20	20	1.8	20	20	2.4	20	20	3.0	20	20	3.3	20	20	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 85 [V] Ripple-Noise [mV]	Input Volt. 132 [V] Ripple-Noise [mV]																																							
0.0	20	20																																							
0.6	20	20																																							
1.2	20	20																																							
1.8	20	20																																							
2.4	20	20																																							
3.0	20	20																																							
3.3	20	20																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSSEL

Model	MMB50A-3	Temperature Testing Circuitry 25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																							
Object	+24.0V 1.50A																																							
1. Graph	<p>-----□----- Input Volt. 85V [mV]</p> <p>-----△----- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise 85V [mV]</th> <th>Ripple-Noise 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>0.3</td><td>20</td><td>20</td></tr> <tr><td>0.6</td><td>20</td><td>20</td></tr> <tr><td>0.9</td><td>20</td><td>20</td></tr> <tr><td>1.2</td><td>20</td><td>20</td></tr> <tr><td>1.3</td><td>20</td><td>20</td></tr> <tr><td>1.4</td><td>20</td><td>20</td></tr> <tr><td>1.5</td><td>20</td><td>20</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise 85V [mV]	Ripple-Noise 132V [mV]	0.0	20	20	0.3	20	20	0.6	20	20	0.9	20	20	1.2	20	20	1.3	20	20	1.4	20	20	1.5	20	20												
Load Current [A]	Ripple-Noise 85V [mV]	Ripple-Noise 132V [mV]																																						
0.0	20	20																																						
0.3	20	20																																						
0.6	20	20																																						
0.9	20	20																																						
1.2	20	20																																						
1.3	20	20																																						
1.4	20	20																																						
1.5	20	20																																						
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>0.3</td><td>20</td><td>20</td></tr> <tr><td>0.6</td><td>20</td><td>20</td></tr> <tr><td>0.9</td><td>20</td><td>20</td></tr> <tr><td>1.2</td><td>20</td><td>20</td></tr> <tr><td>1.5</td><td>20</td><td>20</td></tr> <tr><td>1.7</td><td>20</td><td>20</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.0	20	20	0.3	20	20	0.6	20	20	0.9	20	20	1.2	20	20	1.5	20	20	1.7	20	20	-	-	-	-	-	-	-	-	-	-	-	-
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																						
	Ripple-Noise [mV]	Ripple-Noise [mV]																																						
0.0	20	20																																						
0.3	20	20																																						
0.6	20	20																																						
0.9	20	20																																						
1.2	20	20																																						
1.5	20	20																																						
1.7	20	20																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
-	-	-																																						
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																								
<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																								

COSSEL

Model	MMB50A-3	Temperature 25°C Testing Circuitry Figure A																																																									
Item	Overcurrent Protection 過電流保護																																																										
Object	+5.0V3.00A																																																										
1. Graph	<p>[V]</p> <p>Output Voltage</p> <p>Load Current [A]</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> <tr> <th>Load Current [A]</th> <th>Load Current [A]</th> <th>Load Current [A]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>4.75</td><td>3.797</td><td>3.815</td><td>3.627</td></tr> <tr><td>4.50</td><td>3.789</td><td>3.799</td><td>3.611</td></tr> <tr><td>4.00</td><td>3.764</td><td>3.751</td><td>3.561</td></tr> <tr><td>3.50</td><td>3.721</td><td>3.693</td><td>3.505</td></tr> <tr><td>3.00</td><td>3.659</td><td>3.620</td><td>3.437</td></tr> <tr><td>2.50</td><td>3.586</td><td>3.542</td><td>3.367</td></tr> <tr><td>2.00</td><td>3.471</td><td>3.427</td><td>3.268</td></tr> <tr><td>1.50</td><td>3.332</td><td>3.292</td><td>3.153</td></tr> <tr><td>1.00</td><td>3.153</td><td>3.125</td><td>3.011</td></tr> <tr><td>0.50</td><td>2.919</td><td>2.907</td><td>2.823</td></tr> <tr><td>0.00</td><td>2.641</td><td>2.648</td><td>2.594</td></tr> </tbody> </table>				Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	5.00	—	—	—	4.75	3.797	3.815	3.627	4.50	3.789	3.799	3.611	4.00	3.764	3.751	3.561	3.50	3.721	3.693	3.505	3.00	3.659	3.620	3.437	2.50	3.586	3.542	3.367	2.00	3.471	3.427	3.268	1.50	3.332	3.292	3.153	1.00	3.153	3.125	3.011	0.50	2.919	2.907	2.823	0.00	2.641	2.648	2.594
Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																								
	Load Current [A]	Load Current [A]	Load Current [A]																																																								
5.00	—	—	—																																																								
4.75	3.797	3.815	3.627																																																								
4.50	3.789	3.799	3.611																																																								
4.00	3.764	3.751	3.561																																																								
3.50	3.721	3.693	3.505																																																								
3.00	3.659	3.620	3.437																																																								
2.50	3.586	3.542	3.367																																																								
2.00	3.471	3.427	3.268																																																								
1.50	3.332	3.292	3.153																																																								
1.00	3.153	3.125	3.011																																																								
0.50	2.919	2.907	2.823																																																								
0.00	2.641	2.648	2.594																																																								
Object	+24V1.50A																																																										
1. Graph	<p>[V]</p> <p>Output Voltage</p> <p>Load Current [A]</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> <tr> <th>Load Current [A]</th> <th>Load Current [A]</th> <th>Load Current [A]</th> </tr> </thead> <tbody> <tr><td>24.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>22.80</td><td>2.207</td><td>2.313</td><td>2.318</td></tr> <tr><td>21.60</td><td>2.202</td><td>2.299</td><td>2.297</td></tr> <tr><td>19.20</td><td>2.171</td><td>2.243</td><td>2.235</td></tr> <tr><td>16.80</td><td>2.122</td><td>2.174</td><td>2.160</td></tr> <tr><td>14.40</td><td>2.052</td><td>2.090</td><td>2.087</td></tr> <tr><td>12.00</td><td>1.977</td><td>1.997</td><td>1.979</td></tr> <tr><td>9.60</td><td>1.859</td><td>1.875</td><td>1.859</td></tr> <tr><td>7.20</td><td>1.722</td><td>1.732</td><td>1.721</td></tr> <tr><td>4.80</td><td>1.550</td><td>1.560</td><td>1.558</td></tr> <tr><td>2.40</td><td>1.344</td><td>1.353</td><td>1.358</td></tr> <tr><td>0.00</td><td>1.420</td><td>1.406</td><td>1.471</td></tr> </tbody> </table>				Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	24.00	—	—	—	22.80	2.207	2.313	2.318	21.60	2.202	2.299	2.297	19.20	2.171	2.243	2.235	16.80	2.122	2.174	2.160	14.40	2.052	2.090	2.087	12.00	1.977	1.997	1.979	9.60	1.859	1.875	1.859	7.20	1.722	1.732	1.721	4.80	1.550	1.560	1.558	2.40	1.344	1.353	1.358	0.00	1.420	1.406	1.471
Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																								
	Load Current [A]	Load Current [A]	Load Current [A]																																																								
24.00	—	—	—																																																								
22.80	2.207	2.313	2.318																																																								
21.60	2.202	2.299	2.297																																																								
19.20	2.171	2.243	2.235																																																								
16.80	2.122	2.174	2.160																																																								
14.40	2.052	2.090	2.087																																																								
12.00	1.977	1.997	1.979																																																								
9.60	1.859	1.875	1.859																																																								
7.20	1.722	1.732	1.721																																																								
4.80	1.550	1.560	1.558																																																								
2.40	1.344	1.353	1.358																																																								
0.00	1.420	1.406	1.471																																																								
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																											

COSEL

Model	MMB50A-3	Testing Circuitry Figure A																																																						
Item	Overvoltage Protection 過電圧保護																																																							
Object	+5.0V 3.00A																																																							
1. Graph																																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>85[V]</th> <th>100[V]</th> <th>132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>6.65</td><td>6.57</td><td>6.56</td> </tr> <tr> <td>-10</td><td>6.57</td><td>6.56</td><td>6.53</td> </tr> <tr> <td>0</td><td>6.52</td><td>6.52</td><td>6.46</td> </tr> <tr> <td>10</td><td>6.47</td><td>6.45</td><td>6.35</td> </tr> <tr> <td>20</td><td>6.43</td><td>6.40</td><td>6.23</td> </tr> <tr> <td>25</td><td>6.40</td><td>6.35</td><td>6.18</td> </tr> <tr> <td>30</td><td>6.35</td><td>6.28</td><td>6.12</td> </tr> <tr> <td>40</td><td>6.25</td><td>6.13</td><td>5.99</td> </tr> <tr> <td>50</td><td>6.15</td><td>5.99</td><td>5.86</td> </tr> <tr> <td>60</td><td>6.10</td><td>5.94</td><td>5.83</td> </tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td> </tr> </tbody> </table>				Ambient Temp. [°C]	Input Volt.	Input Volt.	Input Volt.	85[V]	100[V]	132[V]	-20	6.65	6.57	6.56	-10	6.57	6.56	6.53	0	6.52	6.52	6.46	10	6.47	6.45	6.35	20	6.43	6.40	6.23	25	6.40	6.35	6.18	30	6.35	6.28	6.12	40	6.25	6.13	5.99	50	6.15	5.99	5.86	60	6.10	5.94	5.83	-	-	-	-	
Ambient Temp. [°C]	Input Volt.	Input Volt.	Input Volt.																																																					
	85[V]	100[V]	132[V]																																																					
-20	6.65	6.57	6.56																																																					
-10	6.57	6.56	6.53																																																					
0	6.52	6.52	6.46																																																					
10	6.47	6.45	6.35																																																					
20	6.43	6.40	6.23																																																					
25	6.40	6.35	6.18																																																					
30	6.35	6.28	6.12																																																					
40	6.25	6.13	5.99																																																					
50	6.15	5.99	5.86																																																					
60	6.10	5.94	5.83																																																					
-	-	-	-																																																					
Object	+24V 1.50A	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>85[V]</th> <th>100[V]</th> <th>132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>32.0</td><td>31.9</td><td>31.7</td> </tr> <tr> <td>-10</td><td>32.0</td><td>31.9</td><td>31.7</td> </tr> <tr> <td>0</td><td>31.9</td><td>31.8</td><td>31.6</td> </tr> <tr> <td>10</td><td>31.7</td><td>31.6</td><td>31.3</td> </tr> <tr> <td>20</td><td>31.6</td><td>31.5</td><td>31.2</td> </tr> <tr> <td>25</td><td>31.4</td><td>31.3</td><td>31.0</td> </tr> <tr> <td>30</td><td>31.3</td><td>31.1</td><td>30.7</td> </tr> <tr> <td>40</td><td>31.0</td><td>30.8</td><td>30.2</td> </tr> <tr> <td>50</td><td>30.8</td><td>30.4</td><td>29.6</td> </tr> <tr> <td>60</td><td>30.7</td><td>30.3</td><td>29.5</td> </tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td> </tr> </tbody> </table>				Ambient Temp. [°C]	Input Volt.	Input Volt.	Input Volt.	85[V]	100[V]	132[V]	-20	32.0	31.9	31.7	-10	32.0	31.9	31.7	0	31.9	31.8	31.6	10	31.7	31.6	31.3	20	31.6	31.5	31.2	25	31.4	31.3	31.0	30	31.3	31.1	30.7	40	31.0	30.8	30.2	50	30.8	30.4	29.6	60	30.7	30.3	29.5	-	-	-	-
Ambient Temp. [°C]	Input Volt.	Input Volt.	Input Volt.																																																					
	85[V]	100[V]	132[V]																																																					
-20	32.0	31.9	31.7																																																					
-10	32.0	31.9	31.7																																																					
0	31.9	31.8	31.6																																																					
10	31.7	31.6	31.3																																																					
20	31.6	31.5	31.2																																																					
25	31.4	31.3	31.0																																																					
30	31.3	31.1	30.7																																																					
40	31.0	30.8	30.2																																																					
50	30.8	30.4	29.6																																																					
60	30.7	30.3	29.5																																																					
-	-	-	-																																																					
Note: Slanted line shows the range of the rated ambient temperature. (注)斜線は定格周囲温度範囲を示す。																																																								


COSEL

Model MMB50A-3

Item Inrush Current 突入電流


Temperature 25°C
Testing Circuitry Figure A

Object _____



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current



- ① 15.19 [A]
- ② 3.19 [A]



COSEL


Model	MMB50A-3	Temperature	25°C
Item	Dynamic Load Responce 動的負荷変動	Testing Circuitry	Figure A
Object	+5.0V 3.00A		

Input Volt. 100 V
 Cycle 200 mS



100 mV/div


10 mS/div

COSEL

COSEL


Model	MMB50A-3	Temperature Testing Circuitry	25°C Figure A
Item	Rise and Fall Time 立上り、立下り時間		
Object	+5.0V 3.00A		


1. Graph



2. Values

Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		7.3	9.8	17.0	54.5	47.3	
100 %		7.5	15.0	22.5	31.5	34.8	



COSEL

COSEL


Model	MMB50A-3	Testing Circuitry Figure A																																																		
Item	Ambient Temperature Drift 周囲温度変動																																																			
Object	+5.0V 3.00A																																																			
1. Graph	<p>[V]</p> <p>Output Voltage</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2. Values																																																		
		<table border="1"> <thead> <tr> <th>Temperature [°C]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>5.032</td><td>5.032</td><td>5.032</td> </tr> <tr> <td>-10</td><td>5.032</td><td>5.032</td><td>5.032</td> </tr> <tr> <td>0</td><td>5.029</td><td>5.030</td><td>5.029</td> </tr> <tr> <td>10</td><td>5.027</td><td>5.027</td><td>5.026</td> </tr> <tr> <td>20</td><td>5.024</td><td>5.024</td><td>5.024</td> </tr> <tr> <td>25</td><td>5.023</td><td>5.023</td><td>5.023</td> </tr> <tr> <td>30</td><td>5.022</td><td>5.022</td><td>5.021</td> </tr> <tr> <td>40</td><td>5.017</td><td>5.018</td><td>5.017</td> </tr> <tr> <td>50</td><td>5.014</td><td>5.014</td><td>5.014</td> </tr> <tr> <td>60</td><td>5.010</td><td>5.011</td><td>5.010</td> </tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td> </tr> </tbody> </table>			Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	-20	5.032	5.032	5.032	-10	5.032	5.032	5.032	0	5.029	5.030	5.029	10	5.027	5.027	5.026	20	5.024	5.024	5.024	25	5.023	5.023	5.023	30	5.022	5.022	5.021	40	5.017	5.018	5.017	50	5.014	5.014	5.014	60	5.010	5.011	5.010	—	—	—	—
Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																	
-20	5.032	5.032	5.032																																																	
-10	5.032	5.032	5.032																																																	
0	5.029	5.030	5.029																																																	
10	5.027	5.027	5.026																																																	
20	5.024	5.024	5.024																																																	
25	5.023	5.023	5.023																																																	
30	5.022	5.022	5.021																																																	
40	5.017	5.018	5.017																																																	
50	5.014	5.014	5.014																																																	
60	5.010	5.011	5.010																																																	
—	—	—	—																																																	
Object	+24V 1.50A	2. Values																																																		
1. Graph	<p>[V]</p> <p>Output Voltage</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>																																																			
		<table border="1"> <thead> <tr> <th>Temperature [°C]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>24.016</td><td>24.016</td><td>24.017</td> </tr> <tr> <td>-10</td><td>24.017</td><td>24.017</td><td>24.018</td> </tr> <tr> <td>0</td><td>24.016</td><td>24.016</td><td>24.016</td> </tr> <tr> <td>10</td><td>24.010</td><td>24.010</td><td>24.010</td> </tr> <tr> <td>20</td><td>23.997</td><td>23.997</td><td>23.997</td> </tr> <tr> <td>25</td><td>23.991</td><td>23.991</td><td>23.991</td> </tr> <tr> <td>30</td><td>23.983</td><td>23.983</td><td>23.982</td> </tr> <tr> <td>40</td><td>23.967</td><td>23.967</td><td>23.967</td> </tr> <tr> <td>50</td><td>23.949</td><td>23.948</td><td>23.948</td> </tr> <tr> <td>60</td><td>23.928</td><td>23.928</td><td>23.928</td> </tr> <tr> <td>—</td><td>—</td><td>—</td><td>—</td> </tr> </tbody> </table>			Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	-20	24.016	24.016	24.017	-10	24.017	24.017	24.018	0	24.016	24.016	24.016	10	24.010	24.010	24.010	20	23.997	23.997	23.997	25	23.991	23.991	23.991	30	23.983	23.983	23.982	40	23.967	23.967	23.967	50	23.949	23.948	23.948	60	23.928	23.928	23.928	—	—	—	—
Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																	
-20	24.016	24.016	24.017																																																	
-10	24.017	24.017	24.018																																																	
0	24.016	24.016	24.016																																																	
10	24.010	24.010	24.010																																																	
20	23.997	23.997	23.997																																																	
25	23.991	23.991	23.991																																																	
30	23.983	23.983	23.982																																																	
40	23.967	23.967	23.967																																																	
50	23.949	23.948	23.948																																																	
60	23.928	23.928	23.928																																																	
—	—	—	—																																																	
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注) 斜線は定格周囲温度範囲を示す。</p>																																																				

COSEL

Model	MMB50A-3
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+5.0V 3.00A

Testing Circuitry Figure A

1. Graph




2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-20	32.0	61.0
-10	32.0	61.1
0	32.0	62.1
10	32.0	62.1
20	32.0	63.1
25	32.0	63.1
30	32.0	63.1
40	32.0	64.1
50	32.0	65.1
60	32.0	65.1
—	—	—

Object

+24V 1.50A



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-20	30.0	50.0
-10	30.0	50.0
0	29.0	51.0
10	29.0	51.0
20	29.0	51.0
25	29.0	52.0
30	29.0	52.0
40	30.0	53.0
50	30.0	53.0
60	30.0	54.0
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

COSEL


Model MMB50A-3

Item Ripple Voltage (by Ambient Temp.)
リップル電圧 (周囲温度特性)

Object +5.0V 3.00A

1. Graph

-----□----- Load 50%
 -----△----- Load 100%




Input Volt. 85 V

Object 24V 1.50A

1. Graph

-----□----- Load 50%
 -----△----- Load 100%



Input Volt. 85 V

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	10	20
-10	10	15
0	5	15
10	5	15
20	5	10
25	5	10
30	5	10
40	5	10
50	5	10
60	5	10
—	—	—

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]
-20	10	25
-10	10	20
0	5	15
10	5	15
20	5	10
25	5	10
30	5	10
40	5	10
50	5	10
60	5	10
—	—	—

COSEL

Model	MMB50A-3	Temperature Testing Circuitry	25 °C																						
Item	Time Lapse Drift 経時ドリフト		Figure A																						
Object	+5.0V3.00A																								
1. Graph			2. Values																						
 <p>[V]</p> <p>Output Voltage</p> <p>Time [H]</p> <p>Input Volt. 100.0V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.025</td></tr> <tr><td>0.5</td><td>5.024</td></tr> <tr><td>1.0</td><td>5.024</td></tr> <tr><td>2.0</td><td>5.024</td></tr> <tr><td>3.0</td><td>5.024</td></tr> <tr><td>4.0</td><td>5.024</td></tr> <tr><td>5.0</td><td>5.024</td></tr> <tr><td>6.0</td><td>5.024</td></tr> <tr><td>7.0</td><td>5.023</td></tr> <tr><td>8.0</td><td>5.024</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.025	0.5	5.024	1.0	5.024	2.0	5.024	3.0	5.024	4.0	5.024	5.0	5.024	6.0	5.024	7.0	5.023	8.0	5.024
Time since start [H]	Output Voltage [V]																								
0.0	5.025																								
0.5	5.024																								
1.0	5.024																								
2.0	5.024																								
3.0	5.024																								
4.0	5.024																								
5.0	5.024																								
6.0	5.024																								
7.0	5.023																								
8.0	5.024																								
Object +24V1.50A			2. Values																						
 <p>[V]</p> <p>Output Voltage</p> <p>Time [H]</p> <p>Input Volt. 100.0V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>23.997</td></tr> <tr><td>0.5</td><td>23.985</td></tr> <tr><td>1.0</td><td>23.984</td></tr> <tr><td>2.0</td><td>23.984</td></tr> <tr><td>3.0</td><td>23.984</td></tr> <tr><td>4.0</td><td>23.984</td></tr> <tr><td>5.0</td><td>23.983</td></tr> <tr><td>6.0</td><td>23.983</td></tr> <tr><td>7.0</td><td>23.983</td></tr> <tr><td>8.0</td><td>23.983</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	23.997	0.5	23.985	1.0	23.984	2.0	23.984	3.0	23.984	4.0	23.984	5.0	23.983	6.0	23.983	7.0	23.983	8.0	23.983
Time since start [H]	Output Voltage [V]																								
0.0	23.997																								
0.5	23.985																								
1.0	23.984																								
2.0	23.984																								
3.0	23.984																								
4.0	23.984																								
5.0	23.983																								
6.0	23.983																								
7.0	23.983																								
8.0	23.983																								



Model	MMB50A-3	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 85.0~132.0 V

Load Current (AVR 1) : 0.00~3.00 A

(AVR 2) : 0.00~1.50 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage)/2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85.0~132.0 V

負荷電流 (AVR 1) 0.00~3.00 A

(AVR 2) 0.00~1.50 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値)/2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Object	+5.0V3.00A					
--------	------------	--	--	--	--	--

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	132.0	0.00	5.039		
Minimum Voltage	50	85.0	3.00	5.013	±13	±0.3

Object	+24.0V1.50A					
--------	-------------	--	--	--	--	--

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	132.0	0.00	24.031		
Minimum Voltage	50	85.0	1.50	23.940	±46	±0.2

COSEL

Model	MMB50A-3	Testing Circuitry Figure A
Item	Condensation 結露特性	
Object	+5.0V3A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.085	Input Volt.: 100V, Load Current:3A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:3A
Load Regulation [mV]	7	Input Volt.: 100V, Load Current:0~3A



Model	MMB50A-3	
Item	Condensation 結露特性	Testing Circuitry Figure A
Object	+24.0V 1.5A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	23.987	Input Volt.: 100V, Load Current: 1.5A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current: 1.5A
Load Regulation [mV]	5	Input Volt.: 100V, Load Current: 0.0~1.5A

COSEL

Model	MMB50A-3	Temperature Testing Circuitry	25°C Figure A
Item	Leakage Current 漏洩電流		
Object	—		

1. Results

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
85 [V]	100 [V]	132 [V]	
(A) DENTORI	0.14	0.15	0.20
(B) IEC60950	0.13	0.14	0.19

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt.	Input Volt.	Input Volt.
170 [V]	230 [V]	264 [V]	
(B) IEC60950	—	—	—

COSEL

Model	MMB50A-3	Testing Circuitry Figure D
Item	Conducted Emission 雜音端子電圧	
Object	_____	

1. Graph

Remarks


Input Volt. 120 V

Load 100 %

Note: Slanted line shows the range of Tolerance.

(注)斜線は許容値を示す。

N0	Standards	Standards Complied	Frequency [MHz]	Tolerance [dB/ μ V]
1	FCC class A		0.45~1.6	60
			1.6~30	69.5
2	FCC class B	○	0.45~30	48
3	VCCI class A		0.15~0.5	79
			0.5~30	73
4	VCCI class B		0.15~0.5	66~56
			0.5~5	56
			5~30	60
5	CISPR Pub. 22 class A (EN55022)		0.15~0.5	79
			0.5~30	73
6	CISPR Pub. 22 class B (EN55022)		0.15~0.5	66~56
			0.5~5	56
			5~30	60






Figure A


Data Acquisition/Control Unit
データ集録システム

Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E