



TEST DATA OF MMB50A-4 (100V INPUT)

Regulated DC Power Supply

Date : Feb.12. 1999

Approved by : H. Takashima
Design Manager

Prepared by : H. Ishihara
Design Engineer

コーセル株式会社
COSEL CO., LTD.

CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency (by Input Voltage)	2
効率 (入力電圧特性)	
3. Power Factor (by Input Voltage)	3
力率 (入力電圧特性)	
4. Hold-Up Time	4
出力保持時間	
5. Instantaneous Interruption Compensation	6
瞬時停電保障	
6. Load Regulation	8
静的負荷変動	
7. Ripple Voltage (by Load Current)	9
リップル電圧 (負荷特性)	
8. Ripple-Noise	11
リップルノイズ	
9. Overcurrent Protection	13
過電流保護	
10. Overvoltage Protection	14
過電圧保護	
11. Inrush Current	15
突入電流	
12. Dynamic Load Response	16
動的負荷変動	
13. Rise and Fall Time	18
立上り、立下がり時間	
14. Ambient Temperature Drift	20
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	21
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	22
リップル電圧 (周囲温度特性)	
17. Time Lapse Drift	23
経時ドリフト	
18. Output Voltage Accuracy	24
定電圧精度	
19. Condensation	25
結露特性	
20. Leakage Current	27
漏洩電流	
21. Conducted Emission	28
雑音端子電圧	
22. Figure of Testing Circuitry	29
測定回路図	

(Final Page 30)

COSEL

Model		MMB50A-4																																								
Item		Line Regulation 静的入力変動																																								
Object		+12.0V2.10A																																								
1. Graph		2. Values																																								
<div><div>-----□----- Load 50%</div><div>-----△----- Load 100%</div></div> <div></div>		<table><tr><th>Input Voltage [V]</th><th>Load 50% Output Volt. [V]</th><th>Load 100% Output Volt. [V]</th></tr><tr><td>75</td><td>11.864</td><td>11.862</td></tr><tr><td>80</td><td>11.864</td><td>11.862</td></tr><tr><td>85</td><td>11.865</td><td>11.862</td></tr><tr><td>90</td><td>11.865</td><td>11.862</td></tr><tr><td>100</td><td>11.865</td><td>11.862</td></tr><tr><td>110</td><td>11.865</td><td>11.861</td></tr><tr><td>120</td><td>11.865</td><td>11.862</td></tr><tr><td>132</td><td>11.865</td><td>11.861</td></tr><tr><td>140</td><td>11.865</td><td>11.861</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	75	11.864	11.862	80	11.864	11.862	85	11.865	11.862	90	11.865	11.862	100	11.865	11.862	110	11.865	11.861	120	11.865	11.862	132	11.865	11.861	140	11.865	11.861	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																								
75	11.864	11.862																																								
80	11.864	11.862																																								
85	11.865	11.862																																								
90	11.865	11.862																																								
100	11.865	11.862																																								
110	11.865	11.861																																								
120	11.865	11.862																																								
132	11.865	11.861																																								
140	11.865	11.861																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
Object		+12V2.10A																																								
1. Graph		2. Values																																								
<div><div>-----□----- Load 50%</div><div>-----△----- Load 100%</div></div> <div></div>		<table><tr><th>Input Voltage [V]</th><th>Load 50% Output Volt. [V]</th><th>Load 100% Output Volt. [V]</th></tr><tr><td>75</td><td>12.040</td><td>12.037</td></tr><tr><td>80</td><td>12.040</td><td>12.037</td></tr><tr><td>85</td><td>12.040</td><td>12.037</td></tr><tr><td>90</td><td>12.040</td><td>12.037</td></tr><tr><td>100</td><td>12.041</td><td>12.037</td></tr><tr><td>110</td><td>12.041</td><td>12.037</td></tr><tr><td>120</td><td>12.041</td><td>12.037</td></tr><tr><td>132</td><td>12.041</td><td>12.037</td></tr><tr><td>140</td><td>12.041</td><td>12.037</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td></tr></table>		Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]	75	12.040	12.037	80	12.040	12.037	85	12.040	12.037	90	12.040	12.037	100	12.041	12.037	110	12.041	12.037	120	12.041	12.037	132	12.041	12.037	140	12.041	12.037	—	—	—	—	—	—	—	—	—
Input Voltage [V]	Load 50% Output Volt. [V]	Load 100% Output Volt. [V]																																								
75	12.040	12.037																																								
80	12.040	12.037																																								
85	12.040	12.037																																								
90	12.040	12.037																																								
100	12.041	12.037																																								
110	12.041	12.037																																								
120	12.041	12.037																																								
132	12.041	12.037																																								
140	12.041	12.037																																								
—	—	—																																								
—	—	—																																								
—	—	—																																								
Note: Slanted line shows the range of the rated input voltage.																																										
(注)斜線は定格入力電圧範囲を示す。																																										

COSEL

Model	MMB50A-4	
Item	Efficiency (by Input Voltage) 効率 (入力電圧特性)	Temperature 25°C Testing Circuitry Figure A
Object		

1. Graph

-----□----- Load 50%

-----△----- Load 100%

Efficiency [%]

Input Voltage [V]

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Load 50% Efficiency [%]	Load 100% Efficiency [%]
75	71.4	74.2
80	70.8	75.3
85	70.2	75.4
90	69.9	75.5
100	68.3	75.3
110	66.7	74.8
120	64.8	74.3
132	62.6	73.5
140	60.9	72.9

COSEL

Model		MMB50A-4	
Item	Power Factor (by Input Voltage) 力率 (入力電圧特性)		Temperature 25℃ Testing Circuitry Figure A
Object			

1. Graph

□

load 50%

△

load 100%

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	load 50%	load 100%
	Power Factor	Power Factor
75	0.59	0.62
80	0.58	0.60
85	0.57	0.59
90	0.57	0.58
100	0.55	0.57
110	0.54	0.55
120	0.53	0.54
132	0.52	0.53
140	0.51	0.52

COSEL

Model		MMB50A-4	
Item		Hold-Up Time 出力保持時間	
Object		+12.0V2.1A	

1. Graph

—△—

Load 50%

- -□- -

Load 100%

Hold-Up Time [mS]

1000

100

10

1

0

80

90

100

110

120

130

140

150

Input Voltage [V]

2. Values

Input Voltage [V]	Load 50%	Load 100%
	Hold-Up Time [mS]	Hold-Up Time [mS]
75	51	22
80	57	27
85	65	33
90	72	38
100	89	51
110	108	65
120	128	81
132	154	102
140	173	117

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model		MMB50A-4	
Item		Hold-Up Time 出力保持時間	
Object		+12.0V2.1A	

1. Graph

—△— Load 50%

- -□- - Load 100%

[mS]

Hold-Up Time

Input Voltage [V]

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

2. Values

Input Voltage [V]	Load 50%	Load 100%
	Hold-Up Time [mS]	Hold-Up Time [mS]
75	51	22
80	57	27
85	65	33
90	73	39
100	89	52
110	108	66
120	128	82
132	155	102
140	174	117

COSEL

Model		MMB50A-4	
Item		Instantaneous Interruption Compensation 瞬時停電保障	
Object		+12.0V2.10A	

1. Graph

△

Input Volt. 85 V

□

Input Volt. 100 V

○

Input Volt. 132 V

Instantaneous Compensation Time

[mS]

10000

1000

100

10

1

0

0.5

1

1.5

2

2.5

Load Current

[A]

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note:Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注)斜線は定格負荷電流範囲を示す。

2. Values

Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
	Time [mS]		
0.00	—	—	—
0.40	96	126	206
0.80	71	98	170
1.20	55	79	143
1.60	40	64	122
2.00	30	48	102
2.10	27	46	97
2.31	20	39	88
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

LOVEL

Model	MMB50A-4
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	+12.0V2.10A

1. Graph

△

Input Volt. 85 V

□

Input Volt. 100 V

○

Input Volt. 132 V

[mS]

10000

1000

100

10

1

Instantaneous Compensation Time

0

0.5

1

1.5

2

2.5

Load Current

[A]

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note:Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注)斜線は定格負荷電流範囲を示す。

Temperature

25℃

Testing Circuitry

Figure A

2. Values

Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
	Time [mS]		
0.00	—	—	—
0.40	96	127	207
0.80	71	98	170
1.20	55	79	143
1.60	40	63	121
2.00	29	48	101
2.10	22	45	97
2.31	20	38	86
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model		MMB50A-4																																													
Item		Load Regulation 静的負荷変動																																													
Object		+12.0V2.10A																																													
1. Graph		<div><div><div>—△—</div><div>Input Volt. 85V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>—○—</div><div>Input Volt. 132V</div></div></div> <table><thead><tr><th>Load Current [A]</th><th>Input Volt. 85.0[V] Output Volt. [V]</th><th>Input Volt. 100.0[V] Output Volt. [V]</th><th>Input Volt. 132.0[V] Output Volt. [V]</th></tr></thead><tbody><tr><td>0.000</td><td>11.869</td><td>11.870</td><td>11.870</td></tr><tr><td>0.400</td><td>11.867</td><td>11.867</td><td>11.867</td></tr><tr><td>0.800</td><td>11.865</td><td>11.865</td><td>11.865</td></tr><tr><td>1.200</td><td>11.864</td><td>11.864</td><td>11.864</td></tr><tr><td>1.600</td><td>11.863</td><td>11.863</td><td>11.863</td></tr><tr><td>2.000</td><td>11.862</td><td>11.862</td><td>11.862</td></tr><tr><td>2.100</td><td>11.861</td><td>11.862</td><td>11.862</td></tr><tr><td>2.310</td><td>11.861</td><td>11.861</td><td>11.861</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></tbody></table>		Load Current [A]	Input Volt. 85.0[V] Output Volt. [V]	Input Volt. 100.0[V] Output Volt. [V]	Input Volt. 132.0[V] Output Volt. [V]	0.000	11.869	11.870	11.870	0.400	11.867	11.867	11.867	0.800	11.865	11.865	11.865	1.200	11.864	11.864	11.864	1.600	11.863	11.863	11.863	2.000	11.862	11.862	11.862	2.100	11.861	11.862	11.862	2.310	11.861	11.861	11.861	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85.0[V] Output Volt. [V]	Input Volt. 100.0[V] Output Volt. [V]	Input Volt. 132.0[V] Output Volt. [V]																																												
0.000	11.869	11.870	11.870																																												
0.400	11.867	11.867	11.867																																												
0.800	11.865	11.865	11.865																																												
1.200	11.864	11.864	11.864																																												
1.600	11.863	11.863	11.863																																												
2.000	11.862	11.862	11.862																																												
2.100	11.861	11.862	11.862																																												
2.310	11.861	11.861	11.861																																												
—	—	—	—																																												
—	—	—	—																																												
		2. Values																																													


Object		+12V2.10A																																													
1. Graph		<div><div><div>—△—</div><div>Input Volt. 85V</div></div><div><div>---□---</div><div>Input Volt. 100V</div></div><div><div>—○—</div><div>Input Volt. 132V</div></div></div> <table><thead><tr><th>Load Current [A]</th><th>Input Volt. 85.0[V] Output Volt. [V]</th><th>Input Volt. 100.0[V] Output Volt. [V]</th><th>Input Volt. 132.0[V] Output Volt. [V]</th></tr></thead><tbody><tr><td>0.000</td><td>12.046</td><td>12.046</td><td>12.046</td></tr><tr><td>0.400</td><td>12.043</td><td>12.044</td><td>12.044</td></tr><tr><td>0.800</td><td>12.042</td><td>12.042</td><td>12.042</td></tr><tr><td>1.200</td><td>12.040</td><td>12.040</td><td>12.040</td></tr><tr><td>1.600</td><td>12.039</td><td>12.039</td><td>12.039</td></tr><tr><td>2.000</td><td>12.038</td><td>12.038</td><td>12.038</td></tr><tr><td>2.100</td><td>12.037</td><td>12.037</td><td>12.037</td></tr><tr><td>2.310</td><td>12.037</td><td>12.037</td><td>12.037</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr><tr><td>—</td><td>—</td><td>—</td><td>—</td></tr></tbody></table>		Load Current [A]	Input Volt. 85.0[V] Output Volt. [V]	Input Volt. 100.0[V] Output Volt. [V]	Input Volt. 132.0[V] Output Volt. [V]	0.000	12.046	12.046	12.046	0.400	12.043	12.044	12.044	0.800	12.042	12.042	12.042	1.200	12.040	12.040	12.040	1.600	12.039	12.039	12.039	2.000	12.038	12.038	12.038	2.100	12.037	12.037	12.037	2.310	12.037	12.037	12.037	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85.0[V] Output Volt. [V]	Input Volt. 100.0[V] Output Volt. [V]	Input Volt. 132.0[V] Output Volt. [V]																																												
0.000	12.046	12.046	12.046																																												
0.400	12.043	12.044	12.044																																												
0.800	12.042	12.042	12.042																																												
1.200	12.040	12.040	12.040																																												
1.600	12.039	12.039	12.039																																												
2.000	12.038	12.038	12.038																																												
2.100	12.037	12.037	12.037																																												
2.310	12.037	12.037	12.037																																												
—	—	—	—																																												
—	—	—	—																																												
		2. Values																																													

Load Current		Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]
		Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
0.000		11.869	11.870	11.870
0.400		11.867	11.867	11.867
0.800		11.865	11.865	11.865
1.200		11.864	11.864	11.864
1.600		11.863	11.863	11.863
2.000		11.862	11.862	11.862
2.100		11.861	11.862	11.862
2.310		11.861	11.861	11.861
—		—	—	—
—		—	—	—


Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL



COSEL



COSEL

Model		MMB50A-4	
Item		Ripple-Noise リップルノイズ	
Object		+12.0V2.10A	

1. Graph

-----□-----

Input Volt. 85V

-----△-----

Input Volt. 132V

[mV]

200

180

160

140

120

100

80

60

40

20

0

Ripple-Noise

0

0.5

1

1.5

2

2.5

Load Current

[A]

2. Values

Load current	Input Volt.	Input Volt.
	85 [V]	132 [V]
[A]	Ripple-Noise [mV]	Ripple-Noise [mV]
0.0	20	20
0.4	20	20
0.8	20	20
1.2	20	20
1.6	25	20
2.0	25	20
2.1	30	20
2.3	30	20
—	—	—
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p-p 値で示される。

(注) 斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line

入力商用周期

T2: Due to Switching

スイッチング周期

T2


Ripple-Noise [mVp-p]

T1

Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL



COSEL

Model MMB50A-4		Temperature 25°C Testing Circuitry Figure A																																																					
Item	Overcurrent Protection 過電流保護																																																						
Object	+12.0V 2.10A																																																						
1. Graph <div> <div> <div>Input Volt. 85.0 V</div> <div>Input Volt. 100.0 V</div> <div>Input Volt. 132.0 V</div> </div> </div>		2. Values <table border="1"> <thead> <tr> <th>Output Voltage [V]</th><th>Input Volt. 85.0[V] Load Current [A]</th><th>Input Volt. 100.0[V] Load Current [A]</th><th>Input Volt. 132.0[V] Load Current [A]</th></tr> </thead> <tbody> <tr><td>12.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>11.40</td><td>2.704</td><td>2.814</td><td>2.808</td></tr> <tr><td>10.80</td><td>2.692</td><td>2.787</td><td>2.778</td></tr> <tr><td>9.60</td><td>2.657</td><td>2.733</td><td>2.717</td></tr> <tr><td>8.40</td><td>2.606</td><td>2.667</td><td>2.647</td></tr> <tr><td>7.20</td><td>2.540</td><td>2.589</td><td>2.568</td></tr> <tr><td>6.00</td><td>2.454</td><td>2.495</td><td>2.476</td></tr> <tr><td>4.80</td><td>2.345</td><td>2.381</td><td>2.369</td></tr> <tr><td>3.60</td><td>2.210</td><td>2.246</td><td>2.243</td></tr> <tr><td>2.40</td><td>2.045</td><td>2.083</td><td>2.090</td></tr> <tr><td>1.20</td><td>1.843</td><td>1.881</td><td>1.901</td></tr> <tr><td>0.00</td><td>1.674</td><td>1.710</td><td>1.737</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 85.0[V] Load Current [A]	Input Volt. 100.0[V] Load Current [A]	Input Volt. 132.0[V] Load Current [A]	12.00	—	—	—	11.40	2.704	2.814	2.808	10.80	2.692	2.787	2.778	9.60	2.657	2.733	2.717	8.40	2.606	2.667	2.647	7.20	2.540	2.589	2.568	6.00	2.454	2.495	2.476	4.80	2.345	2.381	2.369	3.60	2.210	2.246	2.243	2.40	2.045	2.083	2.090	1.20	1.843	1.881	1.901	0.00	1.674	1.710	1.737
Output Voltage [V]	Input Volt. 85.0[V] Load Current [A]	Input Volt. 100.0[V] Load Current [A]	Input Volt. 132.0[V] Load Current [A]																																																				
12.00	—	—	—																																																				
11.40	2.704	2.814	2.808																																																				
10.80	2.692	2.787	2.778																																																				
9.60	2.657	2.733	2.717																																																				
8.40	2.606	2.667	2.647																																																				
7.20	2.540	2.589	2.568																																																				
6.00	2.454	2.495	2.476																																																				
4.80	2.345	2.381	2.369																																																				
3.60	2.210	2.246	2.243																																																				
2.40	2.045	2.083	2.090																																																				
1.20	1.843	1.881	1.901																																																				
0.00	1.674	1.710	1.737																																																				
Object +12V 2.10A																																																							
1. Graph <div> <div> <div>Input Volt. 85.0 V</div> <div>Input Volt. 100.0 V</div> <div>Input Volt. 132.0 V</div> </div> </div>		2. Values <table border="1"> <thead> <tr> <th>Output Voltage [V]</th><th>Input Volt. 85.0[V] Load Current [A]</th><th>Input Volt. 100.0[V] Load Current [A]</th><th>Input Volt. 132.0[V] Load Current [A]</th></tr> </thead> <tbody> <tr><td>12.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>11.40</td><td>2.665</td><td>2.769</td><td>2.773</td></tr> <tr><td>10.80</td><td>2.653</td><td>2.743</td><td>2.743</td></tr> <tr><td>9.60</td><td>2.619</td><td>2.692</td><td>2.686</td></tr> <tr><td>8.40</td><td>2.571</td><td>2.630</td><td>2.620</td></tr> <tr><td>7.20</td><td>2.501</td><td>2.548</td><td>2.535</td></tr> <tr><td>6.00</td><td>2.418</td><td>2.458</td><td>2.448</td></tr> <tr><td>4.80</td><td>2.312</td><td>2.349</td><td>2.336</td></tr> <tr><td>3.60</td><td>2.176</td><td>2.210</td><td>2.209</td></tr> <tr><td>2.40</td><td>2.016</td><td>2.049</td><td>2.066</td></tr> <tr><td>1.20</td><td>1.803</td><td>1.853</td><td>1.871</td></tr> <tr><td>0.00</td><td>1.641</td><td>1.680</td><td>1.715</td></tr> </tbody> </table>		Output Voltage [V]	Input Volt. 85.0[V] Load Current [A]	Input Volt. 100.0[V] Load Current [A]	Input Volt. 132.0[V] Load Current [A]	12.00	—	—	—	11.40	2.665	2.769	2.773	10.80	2.653	2.743	2.743	9.60	2.619	2.692	2.686	8.40	2.571	2.630	2.620	7.20	2.501	2.548	2.535	6.00	2.418	2.458	2.448	4.80	2.312	2.349	2.336	3.60	2.176	2.210	2.209	2.40	2.016	2.049	2.066	1.20	1.803	1.853	1.871	0.00	1.641	1.680	1.715
Output Voltage [V]	Input Volt. 85.0[V] Load Current [A]	Input Volt. 100.0[V] Load Current [A]	Input Volt. 132.0[V] Load Current [A]																																																				
12.00	—	—	—																																																				
11.40	2.665	2.769	2.773																																																				
10.80	2.653	2.743	2.743																																																				
9.60	2.619	2.692	2.686																																																				
8.40	2.571	2.630	2.620																																																				
7.20	2.501	2.548	2.535																																																				
6.00	2.418	2.458	2.448																																																				
4.80	2.312	2.349	2.336																																																				
3.60	2.176	2.210	2.209																																																				
2.40	2.016	2.049	2.066																																																				
1.20	1.803	1.853	1.871																																																				
0.00	1.641	1.680	1.715																																																				
Note: Slanted line shows the range of the rated load current. (注)斜線は定格負荷電流範囲を示す。																																																							

COSEL

COSEL

Model	MMB50A-4
Item	Overvoltage Protection 過電圧保護
Object	+12.0V2.10A

1. Graph

△

Input Volt. 85 V

□

Input Volt. 100 V

○

Input Volt. 132 V

[V]

Operating Point

Ambient Temperature [°C]

Testing Circuitry Figure A

2. Values

Ambient Temp.	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
[°C]	Operating Point [V]		
-20	15.52	15.50	15.47
-10	15.49	15.48	15.45
0	15.43	15.41	15.40
10	15.35	15.32	15.29
20	15.28	15.24	15.19
25	15.23	15.19	15.13
30	15.17	15.10	14.98
40	15.06	14.93	14.68
50	14.95	14.75	14.38
60	14.71	14.54	14.18
-	-	-	-

Object

+12V2.10A

1. Graph

△

Input Volt. 85 V

□

Input Volt. 100 V

○

Input Volt. 132 V

[V]

Operating Point

Ambient Temperature [°C]

2. Values


Ambient Temp.	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
[°C]	Operating Point [V]		
-20	15.5	15.5	15.5
-10	15.5	15.5	15.4
0	15.4	15.4	15.4
10	15.3	15.3	15.3
20	15.3	15.2	15.2
25	15.2	15.1	15.1
30	15.2	15.1	15.0
40	15.1	14.9	14.7
50	15.0	14.8	14.4
60	14.8	14.7	14.3
-	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.


(注)斜線は定格周囲温度範囲を示す。

COSEL

Model	MMB50A-4	Temperature 25℃ Testing Circuitry Figure A
Item	Inrush Current 突入電流	
Object		



Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current
 ① 16.70 [A]
 ② 3.61 [A]



COSEL

Model	MMB50A-4	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Response 動的負荷変動	
Object	+12.0V2.10A	



Input Volt. 100 V

Cycle 200 mS

Load Current



Load 0% ↔

Load 100 %



Load 0% ↔

Load 50 %



100 mV/div

10 mS/div

COSEL

Model	MMB50A-4	Temperature 25°C Testing Circuitry Figure A
Item	Dynamic Load Responce 動的負荷変動	
Object	+12.0V2.10A	



Input Volt. 100 V

Cycle 200 mS

Load Current



Load 0% ↔

Load 100 %



Load 0% ↔

Load 50 %



100 mV/div


10 mS/div

COSEL

Model	MMB50A-4	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+12.0V 2.10A		

1. Graph


Input Volt. 85 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	6.6	27.4	34.0	64.0	40.3
100 %	7.0	29.6	36.6	31.9	35.0




COSEL

Model	MMB50A-4	Temperature	25°C
Item	Rise and Fall Time 立上り、立下り時間	Testing Circuitry	Figure A
Object	+12.0V2.10A		

1. Graph


Input Volt. 85 V



2. Values

[mS]

Load \ Time	T d	T r	T s	T h	T f
50 %	6.8	24.2	31.0	63.8	44.4
100 %	7.0	26.2	33.2	32.3	36.4




COSEL

Model MMB50A-4																																																							
Item Ambient Temperature Drift 周囲温度変動		Testing Circuitry Figure A																																																					
Object +12.0V2.10A																																																							
1. Graph <div> <div> <div>△</div> <div>Input Volt. 85.0V</div> </div> <div> <div>□</div> <div>Input Volt. 100.0V</div> </div> <div> <div>○</div> <div>Input Volt. 132.0V</div> </div> </div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		2. Values <table border="1"> <thead> <tr> <th>Temperature</th><th>Input Volt. 85.0[V]</th><th>Input Volt. 100.0[V]</th><th>Input Volt. 132.0[V]</th></tr> <tr> <th>[°C]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr> </thead> <tbody> <tr><td>-20</td><td>11.885</td><td>11.885</td><td>11.885</td></tr> <tr><td>-10</td><td>11.883</td><td>11.883</td><td>11.882</td></tr> <tr><td>0</td><td>11.879</td><td>11.880</td><td>11.879</td></tr> <tr><td>10</td><td>11.874</td><td>11.874</td><td>11.874</td></tr> <tr><td>20</td><td>11.869</td><td>11.868</td><td>11.867</td></tr> <tr><td>25</td><td>11.862</td><td>11.862</td><td>11.862</td></tr> <tr><td>30</td><td>11.857</td><td>11.857</td><td>11.858</td></tr> <tr><td>40</td><td>11.851</td><td>11.852</td><td>11.852</td></tr> <tr><td>50</td><td>11.842</td><td>11.841</td><td>11.841</td></tr> <tr><td>60</td><td>11.834</td><td>11.834</td><td>11.834</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Temperature	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-20	11.885	11.885	11.885	-10	11.883	11.883	11.882	0	11.879	11.880	11.879	10	11.874	11.874	11.874	20	11.869	11.868	11.867	25	11.862	11.862	11.862	30	11.857	11.857	11.858	40	11.851	11.852	11.852	50	11.842	11.841	11.841	60	11.834	11.834	11.834	—	—	—	—
Temperature	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																				
[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-20	11.885	11.885	11.885																																																				
-10	11.883	11.883	11.882																																																				
0	11.879	11.880	11.879																																																				
10	11.874	11.874	11.874																																																				
20	11.869	11.868	11.867																																																				
25	11.862	11.862	11.862																																																				
30	11.857	11.857	11.858																																																				
40	11.851	11.852	11.852																																																				
50	11.842	11.841	11.841																																																				
60	11.834	11.834	11.834																																																				
—	—	—	—																																																				
Object +12V2.10A																																																							
1. Graph <div> <div> <div>△</div> <div>Input Volt. 85.0V</div> </div> <div> <div>□</div> <div>Input Volt. 100.0V</div> </div> <div> <div>○</div> <div>Input Volt. 132.0V</div> </div> </div> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>		2. Values <table border="1"> <thead> <tr> <th>Temperature</th><th>Input Volt. 85.0[V]</th><th>Input Volt. 100.0[V]</th><th>Input Volt. 132.0[V]</th></tr> <tr> <th>[°C]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th><th>Output Volt. [V]</th></tr> </thead> <tbody> <tr><td>-20</td><td>12.057</td><td>12.057</td><td>12.058</td></tr> <tr><td>-10</td><td>12.056</td><td>12.056</td><td>12.056</td></tr> <tr><td>0</td><td>12.051</td><td>12.051</td><td>12.051</td></tr> <tr><td>10</td><td>12.047</td><td>12.047</td><td>12.047</td></tr> <tr><td>20</td><td>12.044</td><td>12.044</td><td>12.044</td></tr> <tr><td>25</td><td>12.040</td><td>12.040</td><td>12.040</td></tr> <tr><td>30</td><td>12.038</td><td>12.037</td><td>12.037</td></tr> <tr><td>40</td><td>12.029</td><td>12.029</td><td>12.029</td></tr> <tr><td>50</td><td>12.013</td><td>12.013</td><td>12.013</td></tr> <tr><td>60</td><td>12.009</td><td>12.008</td><td>12.007</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Temperature	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	-20	12.057	12.057	12.058	-10	12.056	12.056	12.056	0	12.051	12.051	12.051	10	12.047	12.047	12.047	20	12.044	12.044	12.044	25	12.040	12.040	12.040	30	12.038	12.037	12.037	40	12.029	12.029	12.029	50	12.013	12.013	12.013	60	12.009	12.008	12.007	—	—	—	—
Temperature	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																				
[°C]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																				
-20	12.057	12.057	12.058																																																				
-10	12.056	12.056	12.056																																																				
0	12.051	12.051	12.051																																																				
10	12.047	12.047	12.047																																																				
20	12.044	12.044	12.044																																																				
25	12.040	12.040	12.040																																																				
30	12.038	12.037	12.037																																																				
40	12.029	12.029	12.029																																																				
50	12.013	12.013	12.013																																																				
60	12.009	12.008	12.007																																																				
—	—	—	—																																																				
Note: Slanted line shows the range of the rated ambient temperature. (注) 斜線は定格周囲温度範囲を示す。																																																							

COSEL


Model	MMB50A-4
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+12.0V2.10A



Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-20	30.8	57.5
-10	30.9	57.8
0	31.6	58.5
10	31.6	58.5
20	31.7	59.6
25	31.6	59.6
30	31.6	59.5
40	31.4	60.7
50	31.5	60.7
60	32.5	60.7
—	—	—



2. Values

Ambient Temp. [°C]	Load 50% Input Volt. [V]	Load 100% Input Volt. [V]
-20	31.7	59.7
-10	31.7	60.8
0	31.7	61.6
10	31.7	61.5
20	31.6	62.6
25	31.7	62.6
30	32.8	61.8
40	32.6	62.5
50	32.6	64.5
60	32.4	64.5
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

COSEL

Model		MMB50A-4																																				
Item		Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)																																				
Object		+12.0V2.10A																																				
1. Graph		<div> <div>-----□----- Load 50%</div> <div>-----△----- Load 100%</div> </div> <p>Input Volt. 100 V</p>																																				
2. Values		<table> <tr> <th>Ambient Temp. [°C]</th><th>Load 50% Ripple Output Volt. [mV]</th><th>Load 100% Ripple Output Volt. [mV]</th></tr> <tr><td>-20</td><td>10</td><td>25</td></tr> <tr><td>-10</td><td>10</td><td>20</td></tr> <tr><td>0</td><td>5</td><td>15</td></tr> <tr><td>10</td><td>5</td><td>15</td></tr> <tr><td>20</td><td>5</td><td>10</td></tr> <tr><td>25</td><td>5</td><td>10</td></tr> <tr><td>30</td><td>5</td><td>10</td></tr> <tr><td>40</td><td>5</td><td>10</td></tr> <tr><td>50</td><td>5</td><td>10</td></tr> <tr><td>60</td><td>5</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </table>	Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-20	10	25	-10	10	20	0	5	15	10	5	15	20	5	10	25	5	10	30	5	10	40	5	10	50	5	10	60	5	10	—	—	—
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																				
-20	10	25																																				
-10	10	20																																				
0	5	15																																				
10	5	15																																				
20	5	10																																				
25	5	10																																				
30	5	10																																				
40	5	10																																				
50	5	10																																				
60	5	10																																				
—	—	—																																				
Object		+12V2.10A																																				
1. Graph		<div> <div>-----□----- Load 50%</div> <div>-----△----- Load 100%</div> </div> <p>Input Volt. 100 V</p>																																				
2. Values		<table> <tr> <th>Ambient Temp. [°C]</th><th>Load 50% Ripple Output Volt. [mV]</th><th>Load 100% Ripple Output Volt. [mV]</th></tr> <tr><td>-20</td><td>10</td><td>25</td></tr> <tr><td>-10</td><td>10</td><td>20</td></tr> <tr><td>0</td><td>5</td><td>15</td></tr> <tr><td>10</td><td>5</td><td>15</td></tr> <tr><td>20</td><td>5</td><td>10</td></tr> <tr><td>25</td><td>5</td><td>10</td></tr> <tr><td>30</td><td>5</td><td>10</td></tr> <tr><td>40</td><td>5</td><td>10</td></tr> <tr><td>50</td><td>5</td><td>10</td></tr> <tr><td>60</td><td>5</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </table>	Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]	-20	10	25	-10	10	20	0	5	15	10	5	15	20	5	10	25	5	10	30	5	10	40	5	10	50	5	10	60	5	10	—	—	—
Ambient Temp. [°C]	Load 50% Ripple Output Volt. [mV]	Load 100% Ripple Output Volt. [mV]																																				
-20	10	25																																				
-10	10	20																																				
0	5	15																																				
10	5	15																																				
20	5	10																																				
25	5	10																																				
30	5	10																																				
40	5	10																																				
50	5	10																																				
60	5	10																																				
—	—	—																																				
Note: Slanted line shows the range of the rated ambient temperature.																																						
(注) 斜線は定格周囲温度範囲を示す。																																						

COSEL

COSEL	
Model	MMB50A-4
Item	Time Lapse Drift 経時ドリフト
Object	+12.0V2.10A
1. Graph	
<div><div><div>Output Voltage [V]</div><div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></</div></div></div></div>	

COSEL

Model		MMB50A-4		Testing Circuitry Figure A	
Item	Output Voltage Accuracy 定電圧精度				

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 ℃

Input Voltage : 85.0~132.0 V

Load Current (AVR 1) : 0.00~2.10 A

 (AVR 2) : 0.00~2.10 A

* Output Voltage Accuracy = ± (Maximum of Output Voltage - Minimum of Output Voltage) / 2

* Output Voltage Accuracy (Ration) = $\frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 ℃

入力電圧 85.0~132.0 V

負荷電流 (AVR 1) 0.00~2.10 A

 (AVR 2) 0.00~2.10 A

* 定電圧精度(変動値) = ± (出力電圧の最高値 - 出力電圧の最低値) / 2

* 定電圧精度(変動率) = $\frac{\text{変動値}}{\text{定格出力電圧}} \times 100$

Object	+12.0V2.10A					
--------	-------------	--	--	--	--	--

Item	Temperature [℃]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	100.0	0.00	11.889	±24	±0.2
Minimum Voltage	50	132.0	2.10	11.842		

Object	+12V2.10A					
--------	-----------	--	--	--	--	--

Item	Temperature [℃]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	85.0	0.00	12.062	±26	±0.3
Minimum Voltage	50	132.0	2.10	12.011		

-24-

BC-3212

COSEL

LOREL

Model	MMB50A-4														
Item	Condensation 結露特性	Testing Circuitry	Figure A												
Object	+12.0V2.1A														
<div>1. Condensation test</div> <div>Testing procedure is as follows.</div> <div>① Keeping and cooling the unit in a tank at -10℃ for an hour with the input off.</div> <div>② Taking it out of the tank and dewing itself in a room where the temperature is 25℃ and the humidity is 40%RH.</div> <div>③ Testing electrical characteristics of the unit to confirm there be no fault.</div> <div>1. 結露特性試験</div> <div>入力を切った状態で、恒温槽で-10℃に冷却しておき、約1時間後に恒温槽から取り出し、室温25℃、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。</div>															
<div>2. Values</div> <table><tr><td>Item</td><td>Data</td><td>Testing Conditions</td></tr><tr><td>Output Voltage [V]</td><td>11.687</td><td>Input Volt.: 100V, Load Current:2.1A</td></tr><tr><td>Line Regulation [mV]</td><td>1</td><td>Input Volt.: 85~132V, Load Current:2.1A</td></tr><tr><td>Load Regulation [mV]</td><td>5</td><td>Input Volt.: 100V, Load Current:0.0~2.1A</td></tr></table>				Item	Data	Testing Conditions	Output Voltage [V]	11.687	Input Volt.: 100V, Load Current:2.1A	Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:2.1A	Load Regulation [mV]	5	Input Volt.: 100V, Load Current:0.0~2.1A
Item	Data	Testing Conditions													
Output Voltage [V]	11.687	Input Volt.: 100V, Load Current:2.1A													
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:2.1A													
Load Regulation [mV]	5	Input Volt.: 100V, Load Current:0.0~2.1A													

COSEL

Model	MMB50A-4	Temperature	25°C
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure A
Object			

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.13	0.14	0.18
(B) IEC60950	0.12	0.14	0.18

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力 of 両相について測定し、その大きい方を漏洩電流測定値とする。

COSEL

Model	MMB50A-4	Testing Circuitry Figure D
Item	Conducted Emission 雑音端子電圧	
Object		

1. Graph

Remarks



Input Volt. 120 V

Load 100 %

Note: Slanted line shows the range of Tolerance.

(注) 斜線は許容値を示す。

NO	Standards	Standards Complied	Frequency [MHz]	Tolerance [dB/μV]
1	FCC class A		0.45~1.6	60
			1.6~30	69.5
2	FCC class B	○	0.45~30	48
3	VCCI class A		0.15~0.5	79
			0.5~30	73
4	VCCI class B		0.15~0.5	66-56
			0.5~5	56
			5~30	60
5	CISPR Pub. 22 class A (EN55022)		0.15~0.5	79
			0.5~30	73
6	CISPR Pub. 22 class B (EN55022)		0.15~0.5	66-56
			0.5~5	56
			5~30	60







Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E