

COSEL

TEST DATA OF MMB75A-1
(100V INPUT)

Regulated DC Power Supply

Date : June 7, 1999

Approved by : Katsuya Takashima
Design Manager

Prepared by : Katsuomi Ichikawa
Design Engineer

コーセル株式会社
COSEL CO., LTD.



CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency (by Input Voltage)	2
効率(入力電圧特性)	
3. Power Factor (by Input Voltage)	3
力率(入力電圧特性)	
4. Hold-Up Time	4
出力保持時間	
5. Instantaneous Interruption Compensation	6
瞬時停電保障	
6. Load Regulation	8
静的負荷変動	
7. Ripple Voltage (by Load Current)	9
リップル電圧(負荷特性)	
8. Ripple-Noise	11
リップルノイズ	
9. Overcurrent Protection	13
過電流保護	
10. Overvoltage Protection	14
過電圧保護	
11. Inrush Current	15
突入電流	
12. Dynamic Load Responce	16
動的負荷変動	
13. Rise and Fall Time	18
立ち上り、立下がり時間	
14. Ambient Temperature Drift	20
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	21
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	22
リップル電圧(周囲温度特性)	
17. Time Lapse Drift	23
経時ドリフト	
18. Output Voltage Accuracy	24
定電圧精度	
19. Condensation	25
結露特性	
20. Leakage Current	27
漏洩電流	
21. Conducted Emission	28
雑音端子電圧	
22. Figure of Testing Circuitry	29
測定回路図	

(Final Page 30)

COSEL

Model	MMB75A-1	Temperature Testing Circuitry	25°C Figure A																																									
Item	Line Regulation 静的の入力変動																																											
Object	+5.0V 5.00A																																											
1. Graph	<p style="text-align: center;">—□— Load 50% —△— Load 100%</p> <p style="text-align: center;">[V]</p>	2. Values																																										
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>75</td><td>5.071</td><td>5.060</td></tr> <tr><td>80</td><td>5.071</td><td>5.060</td></tr> <tr><td>85</td><td>5.071</td><td>5.060</td></tr> <tr><td>90</td><td>5.071</td><td>5.060</td></tr> <tr><td>100</td><td>5.071</td><td>5.060</td></tr> <tr><td>110</td><td>5.071</td><td>5.060</td></tr> <tr><td>120</td><td>5.071</td><td>5.060</td></tr> <tr><td>132</td><td>5.071</td><td>5.060</td></tr> <tr><td>140</td><td>5.071</td><td>5.060</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	75	5.071	5.060	80	5.071	5.060	85	5.071	5.060	90	5.071	5.060	100	5.071	5.060	110	5.071	5.060	120	5.071	5.060	132	5.071	5.060	140	5.071	5.060	—	—	—	—	—	—	—	—	—	
Input Voltage [V]	Load 50%	Load 100%																																										
	Output Volt. [V]	Output Volt. [V]																																										
75	5.071	5.060																																										
80	5.071	5.060																																										
85	5.071	5.060																																										
90	5.071	5.060																																										
100	5.071	5.060																																										
110	5.071	5.060																																										
120	5.071	5.060																																										
132	5.071	5.060																																										
140	5.071	5.060																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
Object	+12.0V 4.00A	2. Values																																										
1. Graph	<p style="text-align: center;">—□— Load 50% —△— Load 100%</p> <p style="text-align: center;">[V]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>75</td><td>12.052</td><td>12.050</td></tr> <tr><td>80</td><td>12.052</td><td>12.049</td></tr> <tr><td>85</td><td>12.052</td><td>12.049</td></tr> <tr><td>90</td><td>12.052</td><td>12.049</td></tr> <tr><td>100</td><td>12.052</td><td>12.049</td></tr> <tr><td>110</td><td>12.052</td><td>12.049</td></tr> <tr><td>120</td><td>12.052</td><td>12.049</td></tr> <tr><td>132</td><td>12.052</td><td>12.049</td></tr> <tr><td>140</td><td>12.052</td><td>12.049</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	75	12.052	12.050	80	12.052	12.049	85	12.052	12.049	90	12.052	12.049	100	12.052	12.049	110	12.052	12.049	120	12.052	12.049	132	12.052	12.049	140	12.052	12.049	—	—	—	—	—	—	—	—	—	
Input Voltage [V]	Load 50%	Load 100%																																										
	Output Volt. [V]	Output Volt. [V]																																										
75	12.052	12.050																																										
80	12.052	12.049																																										
85	12.052	12.049																																										
90	12.052	12.049																																										
100	12.052	12.049																																										
110	12.052	12.049																																										
120	12.052	12.049																																										
132	12.052	12.049																																										
140	12.052	12.049																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

COSEL

Model	MMB75A-1																																
Item	Efficiency 効率	Temperature 25°C Testing Circuitry Figure A																															
Object	—	—																															
1. Graph	—□— Load 50%	—△— Load 100%																															
<p>The graph plots Efficiency [%] on the y-axis (0 to 86) against Input Voltage [V] on the x-axis (0 to 150). Two sets of data points are shown: Load 50% (squares) and Load 100% (triangles). Both series show a general downward trend as input voltage increases. Two diagonal lines represent the rated input voltage range, which is approximately between 85V and 135V.</p>																																	
2. Values																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Efficiency [%]</th> <th>Efficiency [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>74.9</td><td>75.1</td></tr> <tr><td>80</td><td>74.7</td><td>75.6</td></tr> <tr><td>85</td><td>74.4</td><td>76.1</td></tr> <tr><td>90</td><td>73.9</td><td>76.3</td></tr> <tr><td>100</td><td>73.1</td><td>76.6</td></tr> <tr><td>110</td><td>72.1</td><td>76.6</td></tr> <tr><td>120</td><td>71.1</td><td>76.6</td></tr> <tr><td>132</td><td>69.5</td><td>76.2</td></tr> <tr><td>140</td><td>68.3</td><td>75.8</td></tr> </tbody> </table>		Input Voltage [V]	Load 50%	Load 100%	Efficiency [%]	Efficiency [%]	75	74.9	75.1	80	74.7	75.6	85	74.4	76.1	90	73.9	76.3	100	73.1	76.6	110	72.1	76.6	120	71.1	76.6	132	69.5	76.2	140	68.3	75.8
Input Voltage [V]	Load 50%		Load 100%																														
	Efficiency [%]	Efficiency [%]																															
75	74.9	75.1																															
80	74.7	75.6																															
85	74.4	76.1																															
90	73.9	76.3																															
100	73.1	76.6																															
110	72.1	76.6																															
120	71.1	76.6																															
132	69.5	76.2																															
140	68.3	75.8																															

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	MMB75A-1																																	
Item	Power Factor (by Input Voltage) 力率 (入力電圧特性)	Temperature Testing Circuitry 25°C Figure A																																
Object																																		
1. Graph	<p style="text-align: center;">-----□----- load 50% -----△----- load 100%</p>																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>load 50%</th> <th>load 100%</th> </tr> <tr> <th>Power Factor</th> <th>Power Factor</th> </tr> </thead> <tbody> <tr><td>75</td><td>0.52</td><td>0.57</td></tr> <tr><td>80</td><td>0.50</td><td>0.56</td></tr> <tr><td>85</td><td>0.50</td><td>0.55</td></tr> <tr><td>90</td><td>0.49</td><td>0.54</td></tr> <tr><td>100</td><td>0.47</td><td>0.52</td></tr> <tr><td>110</td><td>0.46</td><td>0.51</td></tr> <tr><td>120</td><td>0.45</td><td>0.49</td></tr> <tr><td>132</td><td>0.44</td><td>0.48</td></tr> <tr><td>140</td><td>0.43</td><td>0.47</td></tr> </tbody> </table>		Input Voltage [V]	load 50%	load 100%	Power Factor	Power Factor	75	0.52	0.57	80	0.50	0.56	85	0.50	0.55	90	0.49	0.54	100	0.47	0.52	110	0.46	0.51	120	0.45	0.49	132	0.44	0.48	140	0.43	0.47
Input Voltage [V]	load 50%	load 100%																																
	Power Factor	Power Factor																																
75	0.52	0.57																																
80	0.50	0.56																																
85	0.50	0.55																																
90	0.49	0.54																																
100	0.47	0.52																																
110	0.46	0.51																																
120	0.45	0.49																																
132	0.44	0.48																																
140	0.43	0.47																																

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	MMB75A-1	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+5.0V 5.00A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Hold-Up Time [ms]</th> <th>Hold-Up Time [ms]</th> </tr> </thead> <tbody> <tr><td>75</td><td>49</td><td>24</td></tr> <tr><td>80</td><td>56</td><td>29</td></tr> <tr><td>85</td><td>62</td><td>35</td></tr> <tr><td>90</td><td>70</td><td>41</td></tr> <tr><td>100</td><td>86</td><td>54</td></tr> <tr><td>110</td><td>104</td><td>69</td></tr> <tr><td>120</td><td>124</td><td>86</td></tr> <tr><td>132</td><td>150</td><td>107</td></tr> <tr><td>140</td><td>168</td><td>123</td></tr> </tbody> </table>	Input Voltage [V]	Load 50%	Load 100%	Hold-Up Time [ms]	Hold-Up Time [ms]	75	49	24	80	56	29	85	62	35	90	70	41	100	86	54	110	104	69	120	124	86	132	150	107	140	168	123
Input Voltage [V]	Load 50%	Load 100%																																	
	Hold-Up Time [ms]	Hold-Up Time [ms]																																	
75	49	24																																	
80	56	29																																	
85	62	35																																	
90	70	41																																	
100	86	54																																	
110	104	69																																	
120	124	86																																	
132	150	107																																	
140	168	123																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	MMB75A-1	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+12.0V 4.00A																																		
1. Graph	<p style="text-align: center;">—△— Load 50% -----□---- Load 100%</p>	2. Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Hold-Up Time [ms]</th> <th>Hold-Up Time [ms]</th> </tr> </thead> <tbody> <tr><td>75</td><td>57</td><td>25</td></tr> <tr><td>80</td><td>65</td><td>30</td></tr> <tr><td>85</td><td>74</td><td>36</td></tr> <tr><td>90</td><td>82</td><td>42</td></tr> <tr><td>100</td><td>102</td><td>56</td></tr> <tr><td>110</td><td>124</td><td>70</td></tr> <tr><td>120</td><td>147</td><td>87</td></tr> <tr><td>132</td><td>178</td><td>109</td></tr> <tr><td>140</td><td>201</td><td>124</td></tr> </tbody> </table>	Input Voltage [V]	Load 50%	Load 100%	Hold-Up Time [ms]	Hold-Up Time [ms]	75	57	25	80	65	30	85	74	36	90	82	42	100	102	56	110	124	70	120	147	87	132	178	109	140	201	124	
Input Voltage [V]	Load 50%	Load 100%																																	
	Hold-Up Time [ms]	Hold-Up Time [ms]																																	
75	57	25																																	
80	65	30																																	
85	74	36																																	
90	82	42																																	
100	102	56																																	
110	124	70																																	
120	147	87																																	
132	178	109																																	
140	201	124																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	MMB75A-1																																																									
Item	Instantaneous Interruption Compensation 瞬時停電保障																																																									
Object	+5.0V 5.00A																																																									
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85V (solid line with triangles) Input Volt. 100V (dashed line with squares) Input Volt. 132V (dash-dot line with circles) <p>Y-axis: Instantaneous Compensation Time [mS]</p> <p>X-axis: Load Current [A]</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>85[V]</th> <th>100[V]</th> <th>132[V]</th> </tr> </thead> <tbody> <tr> <td colspan="4">Time [mS]</td> </tr> <tr> <td>0.0</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>0.8</td> <td>86</td> <td>112</td> <td>187</td> </tr> <tr> <td>1.6</td> <td>69</td> <td>94</td> <td>161</td> </tr> <tr> <td>2.4</td> <td>57</td> <td>79</td> <td>144</td> </tr> <tr> <td>3.2</td> <td>47</td> <td>69</td> <td>127</td> </tr> <tr> <td>4.0</td> <td>38</td> <td>59</td> <td>112</td> </tr> <tr> <td>4.8</td> <td>28</td> <td>48</td> <td>102</td> </tr> <tr> <td>5.0</td> <td>27</td> <td>45</td> <td>95</td> </tr> <tr> <td>5.5</td> <td>20</td> <td>38</td> <td>89</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Input Volt.	Input Volt.	Input Volt.	85[V]	100[V]	132[V]	Time [mS]				0.0	—	—	—	0.8	86	112	187	1.6	69	94	161	2.4	57	79	144	3.2	47	69	127	4.0	38	59	112	4.8	28	48	102	5.0	27	45	95	5.5	20	38	89	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt.	Input Volt.	Input Volt.																																																							
	85[V]	100[V]	132[V]																																																							
Time [mS]																																																										
0.0	—	—	—																																																							
0.8	86	112	187																																																							
1.6	69	94	161																																																							
2.4	57	79	144																																																							
3.2	47	69	127																																																							
4.0	38	59	112																																																							
4.8	28	48	102																																																							
5.0	27	45	95																																																							
5.5	20	38	89																																																							
—	—	—	—																																																							
—	—	—	—																																																							

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	MMB75A-1	Testing Circuitry Figure A		
Item	Instantaneous Interruption Compensation 瞬時停電保障			
Object	+12.0V 4.00A			
1. Graph	<p>Legend: Input Volt. 85V (triangle), Input Volt. 100V (square), Input Volt. 132V (circle)</p>			2. Values
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	Time [mS]
0.0	—	—	—	
0.8	113	152	254	
1.6	80	111	195	
2.4	60	86	157	
3.2	43	65	127	
4.0	29	48	103	
4.4	22	39	90	
—	—	—	—	
—	—	—	—	
—	—	—	—	
—	—	—	—	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	MMB75A-1	Temperature	25°C																																															
Item	Load Regulation 靜的負荷変動	Testing Circuitry	Figure A																																															
Object	+5.0V 5.00A																																																	
1. Graph		2. Values																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.068</td><td>5.069</td><td>5.069</td></tr> <tr><td>0.8</td><td>5.065</td><td>5.065</td><td>5.066</td></tr> <tr><td>1.6</td><td>5.064</td><td>5.064</td><td>5.064</td></tr> <tr><td>2.4</td><td>5.062</td><td>5.062</td><td>5.063</td></tr> <tr><td>3.2</td><td>5.062</td><td>5.062</td><td>5.062</td></tr> <tr><td>4.0</td><td>5.061</td><td>5.061</td><td>5.061</td></tr> <tr><td>4.8</td><td>5.060</td><td>5.060</td><td>5.060</td></tr> <tr><td>5.0</td><td>5.060</td><td>5.060</td><td>5.060</td></tr> <tr><td>5.5</td><td>5.059</td><td>5.059</td><td>5.059</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.0	5.068	5.069	5.069	0.8	5.065	5.065	5.066	1.6	5.064	5.064	5.064	2.4	5.062	5.062	5.063	3.2	5.062	5.062	5.062	4.0	5.061	5.061	5.061	4.8	5.060	5.060	5.060	5.0	5.060	5.060	5.060	5.5	5.059	5.059	5.059	—	—	—	—
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																															
0.0	5.068	5.069	5.069																																															
0.8	5.065	5.065	5.066																																															
1.6	5.064	5.064	5.064																																															
2.4	5.062	5.062	5.063																																															
3.2	5.062	5.062	5.062																																															
4.0	5.061	5.061	5.061																																															
4.8	5.060	5.060	5.060																																															
5.0	5.060	5.060	5.060																																															
5.5	5.059	5.059	5.059																																															
—	—	—	—																																															
Object		2. Values																																																
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.062</td><td>12.062</td><td>12.062</td></tr> <tr><td>0.8</td><td>12.057</td><td>12.056</td><td>12.056</td></tr> <tr><td>1.6</td><td>12.055</td><td>12.055</td><td>12.054</td></tr> <tr><td>2.4</td><td>12.054</td><td>12.054</td><td>12.053</td></tr> <tr><td>3.2</td><td>12.053</td><td>12.052</td><td>12.051</td></tr> <tr><td>4.0</td><td>12.052</td><td>12.051</td><td>12.051</td></tr> <tr><td>4.4</td><td>12.051</td><td>12.050</td><td>12.049</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.0	12.062	12.062	12.062	0.8	12.057	12.056	12.056	1.6	12.055	12.055	12.054	2.4	12.054	12.054	12.053	3.2	12.053	12.052	12.051	4.0	12.052	12.051	12.051	4.4	12.051	12.050	12.049	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																															
0.0	12.062	12.062	12.062																																															
0.8	12.057	12.056	12.056																																															
1.6	12.055	12.055	12.054																																															
2.4	12.054	12.054	12.053																																															
3.2	12.053	12.052	12.051																																															
4.0	12.052	12.051	12.051																																															
4.4	12.051	12.050	12.049																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															
Note: Slanted line shows the range of the rated load current.																																																		
(注)斜線は定格負荷電流範囲を示す。																																																		

COSEL

Model	MMB75A-1	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																								
Object	+5.0V 5.00A																																								
1. Graph		2. Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.8</td><td>5</td><td>5</td></tr> <tr><td>1.6</td><td>5</td><td>5</td></tr> <tr><td>2.4</td><td>5</td><td>5</td></tr> <tr><td>3.2</td><td>5</td><td>5</td></tr> <tr><td>4.0</td><td>10</td><td>10</td></tr> <tr><td>4.8</td><td>10</td><td>10</td></tr> <tr><td>5.0</td><td>10</td><td>10</td></tr> <tr><td>5.5</td><td>15</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.0	5	5	0.8	5	5	1.6	5	5	2.4	5	5	3.2	5	5	4.0	10	10	4.8	10	10	5.0	10	10	5.5	15	10	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.0	5	5																																							
0.8	5	5																																							
1.6	5	5																																							
2.4	5	5																																							
3.2	5	5																																							
4.0	10	10																																							
4.8	10	10																																							
5.0	10	10																																							
5.5	15	10																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>			-9-																																						

COSEL

Model	MMB75A-1	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage(by Load Current) リップル電圧(負荷電流特性)																																								
Object	+12.0V 4.00A	2. Values																																							
1. Graph	<p>-----□----- Input Volt. 85V [mV]</p> <p>-----△----- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Figure 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Volt. 85V [mV] (□)</th> <th>Ripple Output Volt. 132V [mV] (△)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.8</td><td>5</td><td>5</td></tr> <tr><td>1.6</td><td>5</td><td>5</td></tr> <tr><td>2.4</td><td>5</td><td>5</td></tr> <tr><td>3.2</td><td>10</td><td>10</td></tr> <tr><td>4.0</td><td>10</td><td>10</td></tr> <tr><td>4.4</td><td>15</td><td>10</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Volt. 85V [mV] (□)	Ripple Output Volt. 132V [mV] (△)	0.0	5	5	0.8	5	5	1.6	5	5	2.4	5	5	3.2	10	10	4.0	10	10	4.4	15	10														
Load Current [A]	Ripple Output Volt. 85V [mV] (□)	Ripple Output Volt. 132V [mV] (△)																																							
0.0	5	5																																							
0.8	5	5																																							
1.6	5	5																																							
2.4	5	5																																							
3.2	10	10																																							
4.0	10	10																																							
4.4	15	10																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.8</td><td>5</td><td>5</td></tr> <tr><td>1.6</td><td>5</td><td>5</td></tr> <tr><td>2.4</td><td>5</td><td>5</td></tr> <tr><td>3.2</td><td>10</td><td>10</td></tr> <tr><td>4.0</td><td>10</td><td>10</td></tr> <tr><td>4.4</td><td>15</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.0	5	5	0.8	5	5	1.6	5	5	2.4	5	5	3.2	10	10	4.0	10	10	4.4	15	10	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.0	5	5																																							
0.8	5	5																																							
1.6	5	5																																							
2.4	5	5																																							
3.2	10	10																																							
4.0	10	10																																							
4.4	15	10																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
Ripple Voltage is shown as p-p in the figure below.																																									
Note: Slanted line shows the range of the rated load current.																																									
リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。																																									
<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p>																																									
<p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	MMB75A-1	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	+5.0V 5.00A																																								
1. Graph		2. Values																																							
<p>[mV]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>0.8</td><td>20</td><td>20</td></tr> <tr><td>1.6</td><td>20</td><td>20</td></tr> <tr><td>2.4</td><td>20</td><td>20</td></tr> <tr><td>3.2</td><td>20</td><td>20</td></tr> <tr><td>4.0</td><td>20</td><td>20</td></tr> <tr><td>4.8</td><td>25</td><td>25</td></tr> <tr><td>5.0</td><td>25</td><td>25</td></tr> <tr><td>5.50</td><td>25</td><td>25</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.0	20	20	0.8	20	20	1.6	20	20	2.4	20	20	3.2	20	20	4.0	20	20	4.8	25	25	5.0	25	25	5.50	25	25	—	—	—	—	—	—
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple-Noise [mV]	Ripple-Noise [mV]																																							
0.0	20	20																																							
0.8	20	20																																							
1.6	20	20																																							
2.4	20	20																																							
3.2	20	20																																							
4.0	20	20																																							
4.8	25	25																																							
5.0	25	25																																							
5.50	25	25																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise</p> <p>Load Current</p>																																									
<p>(注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>T1: Due to AC Input Line T2: Due to Switching</p> <p>リップルノイズは、下図 p – p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	MMB75A-1	Temperature	25°C																																						
Item	Ripple-Noise リップルノイズ	Testing Circuitry	Figure A																																						
Object	+12.0V 4.00A																																								
1. Graph		2. Values																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15</td><td>20</td></tr> <tr><td>0.8</td><td>20</td><td>20</td></tr> <tr><td>1.6</td><td>20</td><td>20</td></tr> <tr><td>2.4</td><td>20</td><td>25</td></tr> <tr><td>3.2</td><td>25</td><td>30</td></tr> <tr><td>4.0</td><td>30</td><td>30</td></tr> <tr><td>4.4</td><td>40</td><td>40</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.0	15	20	0.8	20	20	1.6	20	20	2.4	20	25	3.2	25	30	4.0	30	30	4.4	40	40	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple-Noise [mV]	Ripple-Noise [mV]																																							
0.0	15	20																																							
0.8	20	20																																							
1.6	20	20																																							
2.4	20	25																																							
3.2	25	30																																							
4.0	30	30																																							
4.4	40	40																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																									
<p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p>																																									
<p>Fig. Complex Ripple Wave Form</p> <p>図 リップル波形詳細図</p>																																									

COSEL


Model	MMB75A-1	Temperature 25°C Testing Circuitry Figure A																																																									
Item	Overcurrent Protection 過電流保護																																																										
Object	+5.0V5.00A																																																										
1. Graph	<p>[V] Input Volt. 85.0 V Input Volt. 100.0 V Input Volt. 132.0 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> <tr> <th>Load Current [A]</th> <th>Load Current [A]</th> <th>Load Current [A]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>6.340</td><td>6.399</td><td>6.464</td></tr> <tr><td>4.75</td><td>6.351</td><td>6.398</td><td>6.443</td></tr> <tr><td>4.50</td><td>6.370</td><td>6.384</td><td>6.399</td></tr> <tr><td>4.00</td><td>6.372</td><td>6.347</td><td>6.318</td></tr> <tr><td>3.50</td><td>6.346</td><td>6.269</td><td>6.193</td></tr> <tr><td>3.00</td><td>6.411</td><td>6.203</td><td>6.078</td></tr> <tr><td>2.50</td><td>6.221</td><td>6.075</td><td>5.944</td></tr> <tr><td>2.00</td><td>6.090</td><td>5.911</td><td>5.755</td></tr> <tr><td>1.50</td><td>5.902</td><td>5.718</td><td>5.523</td></tr> <tr><td>1.00</td><td>5.663</td><td>5.434</td><td>5.220</td></tr> <tr><td>0.50</td><td>5.380</td><td>5.105</td><td>4.860</td></tr> <tr><td>0.00</td><td>5.155</td><td>4.915</td><td>4.550</td></tr> </tbody> </table>				Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	5.00	6.340	6.399	6.464	4.75	6.351	6.398	6.443	4.50	6.370	6.384	6.399	4.00	6.372	6.347	6.318	3.50	6.346	6.269	6.193	3.00	6.411	6.203	6.078	2.50	6.221	6.075	5.944	2.00	6.090	5.911	5.755	1.50	5.902	5.718	5.523	1.00	5.663	5.434	5.220	0.50	5.380	5.105	4.860	0.00	5.155	4.915	4.550
Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																								
	Load Current [A]	Load Current [A]	Load Current [A]																																																								
5.00	6.340	6.399	6.464																																																								
4.75	6.351	6.398	6.443																																																								
4.50	6.370	6.384	6.399																																																								
4.00	6.372	6.347	6.318																																																								
3.50	6.346	6.269	6.193																																																								
3.00	6.411	6.203	6.078																																																								
2.50	6.221	6.075	5.944																																																								
2.00	6.090	5.911	5.755																																																								
1.50	5.902	5.718	5.523																																																								
1.00	5.663	5.434	5.220																																																								
0.50	5.380	5.105	4.860																																																								
0.00	5.155	4.915	4.550																																																								
Object	+12.0V4.00A																																																										
1. Graph	<p>[V] Input Volt. 85.0 V Input Volt. 100.0 V Input Volt. 132.0 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																										
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> <tr> <th>Load Current [A]</th> <th>Load Current [A]</th> <th>Load Current [A]</th> </tr> </thead> <tbody> <tr><td>12.00</td><td>5.104</td><td>5.116</td><td>5.181</td></tr> <tr><td>11.40</td><td>5.091</td><td>5.090</td><td>5.144</td></tr> <tr><td>10.80</td><td>5.073</td><td>5.047</td><td>5.086</td></tr> <tr><td>9.60</td><td>5.014</td><td>4.949</td><td>4.967</td></tr> <tr><td>8.40</td><td>4.926</td><td>4.839</td><td>4.890</td></tr> <tr><td>7.20</td><td>4.808</td><td>4.689</td><td>4.662</td></tr> <tr><td>6.00</td><td>4.644</td><td>4.515</td><td>4.476</td></tr> <tr><td>4.80</td><td>4.446</td><td>4.323</td><td>4.259</td></tr> <tr><td>3.60</td><td>4.197</td><td>4.068</td><td>4.016</td></tr> <tr><td>2.40</td><td>3.888</td><td>3.770</td><td>3.744</td></tr> <tr><td>1.20</td><td>3.478</td><td>3.398</td><td>3.350</td></tr> <tr><td>0.00</td><td>3.512</td><td>3.409</td><td>3.356</td></tr> </tbody> </table>				Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	12.00	5.104	5.116	5.181	11.40	5.091	5.090	5.144	10.80	5.073	5.047	5.086	9.60	5.014	4.949	4.967	8.40	4.926	4.839	4.890	7.20	4.808	4.689	4.662	6.00	4.644	4.515	4.476	4.80	4.446	4.323	4.259	3.60	4.197	4.068	4.016	2.40	3.888	3.770	3.744	1.20	3.478	3.398	3.350	0.00	3.512	3.409	3.356
Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																								
	Load Current [A]	Load Current [A]	Load Current [A]																																																								
12.00	5.104	5.116	5.181																																																								
11.40	5.091	5.090	5.144																																																								
10.80	5.073	5.047	5.086																																																								
9.60	5.014	4.949	4.967																																																								
8.40	4.926	4.839	4.890																																																								
7.20	4.808	4.689	4.662																																																								
6.00	4.644	4.515	4.476																																																								
4.80	4.446	4.323	4.259																																																								
3.60	4.197	4.068	4.016																																																								
2.40	3.888	3.770	3.744																																																								
1.20	3.478	3.398	3.350																																																								
0.00	3.512	3.409	3.356																																																								
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注) 斜線は定格負荷電流範囲を示す。</p>																																																											

COSEL


Model	MMB75A-1	Testing Circuitry Figure A																																																						
Item	Overvoltage Protection 過電圧保護																																																							
Object	+5.0V 5.00A																																																							
1. Graph																																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>85[V]</th> <th>100[V]</th> <th>132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>6.63</td><td>6.63</td><td>6.61</td> </tr> <tr> <td>-10</td><td>6.63</td><td>6.62</td><td>6.61</td> </tr> <tr> <td>0</td><td>6.62</td><td>6.61</td><td>6.60</td> </tr> <tr> <td>10</td><td>6.59</td><td>6.58</td><td>6.54</td> </tr> <tr> <td>20</td><td>6.56</td><td>6.55</td><td>6.49</td> </tr> <tr> <td>25</td><td>6.55</td><td>6.54</td><td>6.46</td> </tr> <tr> <td>30</td><td>6.54</td><td>6.52</td><td>6.43</td> </tr> <tr> <td>40</td><td>6.51</td><td>6.47</td><td>6.37</td> </tr> <tr> <td>50</td><td>6.43</td><td>6.36</td><td>6.25</td> </tr> <tr> <td>60</td><td>6.34</td><td>6.25</td><td>6.12</td> </tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td> </tr> </tbody> </table>				Ambient Temp. [°C]	Input Volt.	Input Volt.	Input Volt.	85[V]	100[V]	132[V]	-20	6.63	6.63	6.61	-10	6.63	6.62	6.61	0	6.62	6.61	6.60	10	6.59	6.58	6.54	20	6.56	6.55	6.49	25	6.55	6.54	6.46	30	6.54	6.52	6.43	40	6.51	6.47	6.37	50	6.43	6.36	6.25	60	6.34	6.25	6.12	-	-	-	-	
Ambient Temp. [°C]	Input Volt.	Input Volt.	Input Volt.																																																					
	85[V]	100[V]	132[V]																																																					
-20	6.63	6.63	6.61																																																					
-10	6.63	6.62	6.61																																																					
0	6.62	6.61	6.60																																																					
10	6.59	6.58	6.54																																																					
20	6.56	6.55	6.49																																																					
25	6.55	6.54	6.46																																																					
30	6.54	6.52	6.43																																																					
40	6.51	6.47	6.37																																																					
50	6.43	6.36	6.25																																																					
60	6.34	6.25	6.12																																																					
-	-	-	-																																																					
Object	+12.0V 4.00A	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Input Volt.</th> <th>Input Volt.</th> <th>Input Volt.</th> </tr> <tr> <th>85[V]</th> <th>100[V]</th> <th>132[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>15.55</td><td>15.56</td><td>15.56</td> </tr> <tr> <td>-10</td><td>15.52</td><td>15.53</td><td>15.51</td> </tr> <tr> <td>0</td><td>15.49</td><td>15.49</td><td>15.45</td> </tr> <tr> <td>10</td><td>15.43</td><td>15.42</td><td>15.37</td> </tr> <tr> <td>20</td><td>15.38</td><td>15.36</td><td>15.31</td> </tr> <tr> <td>25</td><td>15.33</td><td>15.31</td><td>15.25</td> </tr> <tr> <td>30</td><td>15.28</td><td>15.26</td><td>15.17</td> </tr> <tr> <td>40</td><td>15.17</td><td>15.15</td><td>15.01</td> </tr> <tr> <td>50</td><td>15.03</td><td>14.94</td><td>14.78</td> </tr> <tr> <td>60</td><td>14.89</td><td>14.73</td><td>14.55</td> </tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td> </tr> </tbody> </table>				Ambient Temp. [°C]	Input Volt.	Input Volt.	Input Volt.	85[V]	100[V]	132[V]	-20	15.55	15.56	15.56	-10	15.52	15.53	15.51	0	15.49	15.49	15.45	10	15.43	15.42	15.37	20	15.38	15.36	15.31	25	15.33	15.31	15.25	30	15.28	15.26	15.17	40	15.17	15.15	15.01	50	15.03	14.94	14.78	60	14.89	14.73	14.55	-	-	-	-
Ambient Temp. [°C]	Input Volt.	Input Volt.	Input Volt.																																																					
	85[V]	100[V]	132[V]																																																					
-20	15.55	15.56	15.56																																																					
-10	15.52	15.53	15.51																																																					
0	15.49	15.49	15.45																																																					
10	15.43	15.42	15.37																																																					
20	15.38	15.36	15.31																																																					
25	15.33	15.31	15.25																																																					
30	15.28	15.26	15.17																																																					
40	15.17	15.15	15.01																																																					
50	15.03	14.94	14.78																																																					
60	14.89	14.73	14.55																																																					
-	-	-	-																																																					
1. Graph																																																								
2. Values																																																								
Note: Slanted line shows the range of the rated ambient temperature. (注)斜線は定格周囲温度範囲を示す。																																																								


COSEL


Model	MMB75A-1	Temperature Testing Circuitry Figure A
Item	Inrush Current 突入電流	
Object	_____	





Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current
 ① 12.11 [A]
 ② 21.09 [A]




COSEL

COSEL

COSEL


COSEL

COSEL

Model MMB75A-1 Item Ambient Temperature Drift 周囲温度変動 Object +5.0V 5.00A		Testing Circuitry Figure A																																																		
1. Graph		2. Values																																																		
		<table border="1"> <thead> <tr> <th>Temperature [°C]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>5.062</td><td>5.062</td><td>5.062</td></tr> <tr><td>-10</td><td>5.063</td><td>5.063</td><td>5.063</td></tr> <tr><td>0</td><td>5.063</td><td>5.063</td><td>5.063</td></tr> <tr><td>10</td><td>5.062</td><td>5.062</td><td>5.062</td></tr> <tr><td>20</td><td>5.061</td><td>5.061</td><td>5.061</td></tr> <tr><td>25</td><td>5.060</td><td>5.060</td><td>5.060</td></tr> <tr><td>30</td><td>5.059</td><td>5.059</td><td>5.059</td></tr> <tr><td>40</td><td>5.057</td><td>5.057</td><td>5.057</td></tr> <tr><td>50</td><td>5.054</td><td>5.054</td><td>5.054</td></tr> <tr><td>60</td><td>5.052</td><td>5.052</td><td>5.052</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	-20	5.062	5.062	5.062	-10	5.063	5.063	5.063	0	5.063	5.063	5.063	10	5.062	5.062	5.062	20	5.061	5.061	5.061	25	5.060	5.060	5.060	30	5.059	5.059	5.059	40	5.057	5.057	5.057	50	5.054	5.054	5.054	60	5.052	5.052	5.052	—	—	—	—
Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																	
-20	5.062	5.062	5.062																																																	
-10	5.063	5.063	5.063																																																	
0	5.063	5.063	5.063																																																	
10	5.062	5.062	5.062																																																	
20	5.061	5.061	5.061																																																	
25	5.060	5.060	5.060																																																	
30	5.059	5.059	5.059																																																	
40	5.057	5.057	5.057																																																	
50	5.054	5.054	5.054																																																	
60	5.052	5.052	5.052																																																	
—	—	—	—																																																	
Object +12.0V 4.00A		2. Values																																																		
1. Graph		<table border="1"> <thead> <tr> <th>Temperature [°C]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>12.088</td><td>12.088</td><td>12.087</td></tr> <tr><td>-10</td><td>12.084</td><td>12.084</td><td>12.082</td></tr> <tr><td>0</td><td>12.079</td><td>12.080</td><td>12.077</td></tr> <tr><td>10</td><td>12.072</td><td>12.072</td><td>12.070</td></tr> <tr><td>20</td><td>12.064</td><td>12.064</td><td>12.063</td></tr> <tr><td>25</td><td>12.061</td><td>12.061</td><td>12.059</td></tr> <tr><td>30</td><td>12.058</td><td>12.058</td><td>12.057</td></tr> <tr><td>40</td><td>12.047</td><td>12.048</td><td>12.047</td></tr> <tr><td>50</td><td>12.041</td><td>12.040</td><td>12.039</td></tr> <tr><td>60</td><td>12.034</td><td>12.032</td><td>12.032</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	-20	12.088	12.088	12.087	-10	12.084	12.084	12.082	0	12.079	12.080	12.077	10	12.072	12.072	12.070	20	12.064	12.064	12.063	25	12.061	12.061	12.059	30	12.058	12.058	12.057	40	12.047	12.048	12.047	50	12.041	12.040	12.039	60	12.034	12.032	12.032	—	—	—	—
Temperature [°C]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																	
-20	12.088	12.088	12.087																																																	
-10	12.084	12.084	12.082																																																	
0	12.079	12.080	12.077																																																	
10	12.072	12.072	12.070																																																	
20	12.064	12.064	12.063																																																	
25	12.061	12.061	12.059																																																	
30	12.058	12.058	12.057																																																	
40	12.047	12.048	12.047																																																	
50	12.041	12.040	12.039																																																	
60	12.034	12.032	12.032																																																	
—	—	—	—																																																	
Note: Slanted line shows the range of the rated ambient temperature. (注)斜線は定格周囲温度範囲を示す。																																																				

COSEL


Model	MMB75A-1
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+5.0V 5.00A



Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-20	29.6	58.4
-10	29.6	59.5
0	29.6	60.5
10	29.4	60.4
20	30.5	61.5
25	30.6	62.4
30	30.4	62.4
40	30.7	63.3
50	31.5	64.5
60	31.5	65.4
—	—	—



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-20	30.5	58.4
-10	30.5	58.5
0	30.5	59.5
10	31.5	59.6
20	31.6	60.6
25	31.6	60.6
30	31.5	61.4
40	32.5	62.4
50	32.6	63.6
60	32.6	63.5
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


COSEL

Model	MMB75A-1																																								
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)																																								
Object	+5.0V 5.00A																																								
1. Graph	<p>[mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 85 V</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>15</td><td>25</td></tr> <tr><td>-10</td><td>15</td><td>20</td></tr> <tr><td>0</td><td>10</td><td>20</td></tr> <tr><td>10</td><td>10</td><td>15</td></tr> <tr><td>20</td><td>5</td><td>10</td></tr> <tr><td>25</td><td>5</td><td>10</td></tr> <tr><td>30</td><td>5</td><td>10</td></tr> <tr><td>40</td><td>5</td><td>5</td></tr> <tr><td>50</td><td>5</td><td>5</td></tr> <tr><td>60</td><td>5</td><td>5</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temp. [°C]	Load 50%	Load 100%	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	-20	15	25	-10	15	20	0	10	20	10	10	15	20	5	10	25	5	10	30	5	10	40	5	5	50	5	5	60	5	5	—	—	—
Ambient Temp. [°C]	Load 50%	Load 100%																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
-20	15	25																																							
-10	15	20																																							
0	10	20																																							
10	10	15																																							
20	5	10																																							
25	5	10																																							
30	5	10																																							
40	5	5																																							
50	5	5																																							
60	5	5																																							
—	—	—																																							
Object	+12.0V 4.00A																																								
1. Graph	<p>[mV]</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 85 V</p>																																								
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temp. [°C]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>20</td><td>30</td></tr> <tr><td>-10</td><td>15</td><td>25</td></tr> <tr><td>0</td><td>10</td><td>20</td></tr> <tr><td>10</td><td>10</td><td>15</td></tr> <tr><td>20</td><td>5</td><td>15</td></tr> <tr><td>25</td><td>5</td><td>10</td></tr> <tr><td>30</td><td>5</td><td>10</td></tr> <tr><td>40</td><td>5</td><td>5</td></tr> <tr><td>50</td><td>5</td><td>5</td></tr> <tr><td>60</td><td>5</td><td>5</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Ambient Temp. [°C]	Load 50%	Load 100%	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	-20	20	30	-10	15	25	0	10	20	10	10	15	20	5	15	25	5	10	30	5	10	40	5	5	50	5	5	60	5	5	—	—	—
Ambient Temp. [°C]	Load 50%	Load 100%																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
-20	20	30																																							
-10	15	25																																							
0	10	20																																							
10	10	15																																							
20	5	15																																							
25	5	10																																							
30	5	10																																							
40	5	5																																							
50	5	5																																							
60	5	5																																							
—	—	—																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p> <p>(注)斜線は定格周囲温度範囲を示す。</p>																																									

COSEL

Model	MMB75A-1
Item	Time Lapse Drift 経時ドリフト
Object	+5.0V 5.00A

1. Graph




Temperature 25 °C
Testing Circuitry Figure A

2.Values

Time since start [H]	Output Voltage [V]
0.0	5.063
0.5	5.062
1.0	5.062
2.0	5.062
3.0	5.062
4.0	5.062
5.0	5.062
6.0	5.062
7.0	5.062
8.0	5.062

Object	+12.0V 4.00A
--------	--------------

1. Graph



2.Values

Time since start [H]	Output Voltage [V]
0.0	12.062
0.5	12.053
1.0	12.053
2.0	12.053
3.0	12.053
4.0	12.053
5.0	12.053
6.0	12.053
7.0	12.053
8.0	12.053



Model	MMB75A-1	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 85.0~132.0 V

Load Current (AVR 1) : 0.00~5.00 A

(AVR 2) : 0.00~4.00 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{Output Voltage Accuracy (Ration)} = \frac{\text{Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85.0~132.0 V

負荷電流 (AVR 1) 0.00~5.00 A

(AVR 2) 0.00~4.00 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Object	+5.0V 5.00A	
--------	-------------	--

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	132.0	0.00	5.086		
Minimum Voltage	50	100.0	5.00	5.054	±16	±0.4

Object	+12.0V 4.00A	
--------	--------------	--

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	-10	100.0	0.00	12.095		
Minimum Voltage	50	85.0	4.00	12.023	±36	±0.4



Model	MMB75A-1		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	+5.0V 5.00A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.057	Input Volt.: 100V, Load Current:5A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:5A
Load Regulation [mV]	9	Input Volt.: 100V, Load Current:0~5A



Model	MMB75A-1	
Item	Condensation 結露特性	Testing Circuitry Figure A
Object	+12.0V 4.00A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	12.046	Input Volt.: 100V, Load Current:4A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:4A
Load Regulation [mV]	11	Input Volt.: 100V, Load Current:0~4A



Model	MMB75A-1		
Item	Leakage Current 漏洩電流	Testing Circuitry	Figure A
Object	_____		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.17	0.18	0.19
(B) U L	0.14	0.15	0.21
(C) C S A	0.13	0.15	0.21

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 220 [V]	Input Volt. 264 [V]
(D) V D E	—	—	—

COSEL

Model	MMB75A-1
Item	Conducted Emission 雜音端子電圧
Object	_____

Testing Circuitry Figure D

1. Graph

Remarks



Input Volt. 120 V

Load 100 %

Note: Slanted line shows the range of Tolerance.

(注) 斜線は許容値を示す。

No	Standards	Standards Complied	Frequency [MHz]	Tolerance [dB/ μ V]
1	FCC class A		0.45~1.6	60
			1.6~30	69.5
2	FCC class B	○	0.45~30	48
3	VCCI class A		0.15~0.5	79
			0.5~30	73
4	VCCI class B		0.15~0.5	66~56
			0.5~5	56
			5~30	60
5	CISPR Pub. 22 class A (EN55022)		0.15~0.5	79
			0.5~30	73
6	CISPR Pub. 22 class B (EN55022)		0.15~0.5	66~56
			0.5~5	56
			5~30	60






Figure A


Data Acquisition/Control Unit
データ集録システム

Figure B (DENTORI)




Figure B (UL, CSA, VDE)




Figure C




Figure D




Figure E