

COSEL

TEST DATA OF MMC50A-4
(100V INPUT)

Regulated DC Power Supply

Date : July 7, 1999

Approved by : Makoto Takashima
Design Manager

Prepared by : Katsuaki Ishihara
Design Engineer

コーセル株式会社
COSEL CO., LTD.



CONTENTS

1. Line Regulation	1
静的入力変動	
2. Efficiency (by Input Voltage)	3
効率(入力電圧特性)	
3. Power Factor (by Input Voltage)	4
力率(入力電圧特性)	
4. Hold-Up Time	5
出力保持時間	
5. Instantaneous Interruption Compensation	8
瞬時停電保障	
6. Load Regulation	11
静的負荷変動	
7. Ripple Voltage (by Load Current)	13
リップル電圧(負荷特性)	
8. Ripple-Noise	16
リップルノイズ	
9. Overcurrent Protection	19
過電流保護	
10. Overvoltage Protection	21
過電圧保護	
11. Inrush Current	22
突入電流	
12. Dynamic Load Response	23
動的負荷変動	
13. Rise and Fall Time	26
立ち上り、立下がり時間	
14. Ambient Temperature Drift	29
周囲温度変動	
15. Minimum Input Voltage for Regulated Output Voltage	31
最低レギュレーション電圧	
16. Ripple Voltage (by Ambient Temperature)	33
リップル電圧(周囲温度特性)	
17. Time Lapse Drift	35
経時ドリフト	
18. Output Voltage Accuracy	37
定電圧精度	
19. Condensation	38
結露特性	
20. Leakage Current	41
漏洩電流	
21. Conducted Emission	42
雑音端子電圧	
22. Figure of Testing Circuitry	43
測定回路図	


(Final Page 44)

COSEL

Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A																																									
Item	Line Regulation 静的入力変動																																											
Object	+5.0V 7.00A																																											
1. Graph	<p style="text-align: center;">----- □ ----- Load 50% ----- △ ----- Load 100%</p> <p style="text-align: center;">[V]</p>	2. Values																																										
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>75</td><td>5.079</td><td>5.070</td></tr> <tr><td>80</td><td>5.079</td><td>5.070</td></tr> <tr><td>85</td><td>5.079</td><td>5.070</td></tr> <tr><td>90</td><td>5.079</td><td>5.070</td></tr> <tr><td>100</td><td>5.079</td><td>5.070</td></tr> <tr><td>110</td><td>5.079</td><td>5.070</td></tr> <tr><td>120</td><td>5.079</td><td>5.070</td></tr> <tr><td>132</td><td>5.080</td><td>5.070</td></tr> <tr><td>140</td><td>5.080</td><td>5.070</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	75	5.079	5.070	80	5.079	5.070	85	5.079	5.070	90	5.079	5.070	100	5.079	5.070	110	5.079	5.070	120	5.079	5.070	132	5.080	5.070	140	5.080	5.070	—	—	—	—	—	—	—	—	—	
Input Voltage [V]	Load 50%	Load 100%																																										
	Output Volt. [V]	Output Volt. [V]																																										
75	5.079	5.070																																										
80	5.079	5.070																																										
85	5.079	5.070																																										
90	5.079	5.070																																										
100	5.079	5.070																																										
110	5.079	5.070																																										
120	5.079	5.070																																										
132	5.080	5.070																																										
140	5.080	5.070																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
Object	+12.0V 1.00A	2. Values																																										
1. Graph	<p style="text-align: center;">----- □ ----- Load 50% ----- △ ----- Load 100%</p> <p style="text-align: center;">[V]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>75</td><td>11.974</td><td>11.955</td></tr> <tr><td>80</td><td>11.974</td><td>11.954</td></tr> <tr><td>85</td><td>11.974</td><td>11.954</td></tr> <tr><td>90</td><td>11.974</td><td>11.954</td></tr> <tr><td>100</td><td>11.975</td><td>11.954</td></tr> <tr><td>110</td><td>11.975</td><td>11.953</td></tr> <tr><td>120</td><td>11.975</td><td>11.953</td></tr> <tr><td>132</td><td>11.975</td><td>11.953</td></tr> <tr><td>140</td><td>11.975</td><td>11.953</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	75	11.974	11.955	80	11.974	11.954	85	11.974	11.954	90	11.974	11.954	100	11.975	11.954	110	11.975	11.953	120	11.975	11.953	132	11.975	11.953	140	11.975	11.953	—	—	—	—	—	—	—	—	—	
Input Voltage [V]	Load 50%	Load 100%																																										
	Output Volt. [V]	Output Volt. [V]																																										
75	11.974	11.955																																										
80	11.974	11.954																																										
85	11.974	11.954																																										
90	11.974	11.954																																										
100	11.975	11.954																																										
110	11.975	11.953																																										
120	11.975	11.953																																										
132	11.975	11.953																																										
140	11.975	11.953																																										
—	—	—																																										
—	—	—																																										
—	—	—																																										
Note:	Slanted line shows the range of the rated input voltage.																																											
(注)	斜線は定格入力電圧範囲を示す。																																											

COSEL

Model	MMC50A-4	Temperature	25°C																																
Item	Line Regulation 静的入力変動	Testing Circuitry	Figure A																																
Object	-12.0V 0.30A																																		
1. Graph	<p style="text-align: center;">----- □ ----- Load 50% ----- △ ----- Load 100%</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>75</td><td>-11.745</td><td>-11.734</td></tr> <tr><td>80</td><td>-11.747</td><td>-11.732</td></tr> <tr><td>85</td><td>-11.748</td><td>-11.732</td></tr> <tr><td>90</td><td>-11.748</td><td>-11.731</td></tr> <tr><td>100</td><td>-11.748</td><td>-11.731</td></tr> <tr><td>110</td><td>-11.748</td><td>-11.731</td></tr> <tr><td>120</td><td>-11.749</td><td>-11.731</td></tr> <tr><td>132</td><td>-11.749</td><td>-11.731</td></tr> <tr><td>140</td><td>-11.749</td><td>-11.731</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Output Volt. [V]	Output Volt. [V]	75	-11.745	-11.734	80	-11.747	-11.732	85	-11.748	-11.732	90	-11.748	-11.731	100	-11.748	-11.731	110	-11.748	-11.731	120	-11.749	-11.731	132	-11.749	-11.731	140	-11.749	-11.731
Input Voltage [V]	Load 50%	Load 100%																																	
	Output Volt. [V]	Output Volt. [V]																																	
75	-11.745	-11.734																																	
80	-11.747	-11.732																																	
85	-11.748	-11.732																																	
90	-11.748	-11.731																																	
100	-11.748	-11.731																																	
110	-11.748	-11.731																																	
120	-11.749	-11.731																																	
132	-11.749	-11.731																																	
140	-11.749	-11.731																																	
Note:	Slanted line shows the range of the rated input voltage.																																		
(注)	斜線は定格入力電圧範囲を示す。																																		

COSEL

COSEL

Model	MMC50A-4	
Item	Power Factor (by Input Voltage) 力率(入力電圧特性)	Temperature 25°C Testing Circuitry Figure A
Object	_____	
1. Graph		
	load 50% □	load 100% △
	<p>Note: Slanted line shows the range of the rated input voltage.</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>	
2. Values		
Input Voltage [V]	load 50%	load 100%
75	0.56	0.60
80	0.55	0.58
85	0.55	0.57
90	0.54	0.57
100	0.52	0.55
110	0.51	0.53
120	0.50	0.52
132	0.49	0.51
140	0.49	0.50

COSEL

Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+5.0V 7.00A																																		
1. Graph	<p style="text-align: center;">—△— Load 50% ---□--- Load 100%</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Hold-Up Time [mS]</th> <th>Hold-Up Time [mS]</th> </tr> </thead> <tbody> <tr><td>75</td><td>43</td><td>24</td></tr> <tr><td>80</td><td>50</td><td>29</td></tr> <tr><td>85</td><td>58</td><td>34</td></tr> <tr><td>90</td><td>67</td><td>40</td></tr> <tr><td>100</td><td>86</td><td>52</td></tr> <tr><td>110</td><td>108</td><td>66</td></tr> <tr><td>120</td><td>132</td><td>82</td></tr> <tr><td>132</td><td>163</td><td>103</td></tr> <tr><td>140</td><td>186</td><td>118</td></tr> </tbody> </table>			Input Voltage [V]	Load 50%	Load 100%	Hold-Up Time [mS]	Hold-Up Time [mS]	75	43	24	80	50	29	85	58	34	90	67	40	100	86	52	110	108	66	120	132	82	132	163	103	140	186	118
Input Voltage [V]	Load 50%	Load 100%																																	
	Hold-Up Time [mS]	Hold-Up Time [mS]																																	
75	43	24																																	
80	50	29																																	
85	58	34																																	
90	67	40																																	
100	86	52																																	
110	108	66																																	
120	132	82																																	
132	163	103																																	
140	186	118																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A
Item	Hold-Up Time 出力保持時間		
Object	+12.0V 1.00A		
1. Graph	<p>—△— Load 50%</p> <p>- - □ - Load 100%</p>		
2. Values			
Input Voltage [V]	Load 50% [ms]	Load 100% [ms]	
75	36	28	
80	42	33	
85	48	38	
90	54	44	
100	69	57	
110	85	71	
120	102	87	
132	126	107	
140	143	123	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。


COSEL

Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	-12.0V 0.30A																																		
1. Graph	<p style="text-align: center;">—△— Load 50% ---□--- Load 100%</p>	2. Values																																	
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th>Hold-Up Time [ms]</th> <th>Hold-Up Time [ms]</th> </tr> </thead> <tbody> <tr><td>75</td><td>47</td><td>33</td></tr> <tr><td>80</td><td>52</td><td>38</td></tr> <tr><td>85</td><td>57</td><td>43</td></tr> <tr><td>90</td><td>63</td><td>49</td></tr> <tr><td>100</td><td>76</td><td>62</td></tr> <tr><td>110</td><td>91</td><td>76</td></tr> <tr><td>120</td><td>107</td><td>92</td></tr> <tr><td>132</td><td>129</td><td>113</td></tr> <tr><td>140</td><td>145</td><td>128</td></tr> </tbody> </table>	Input Voltage [V]	Load 50%	Load 100%	Hold-Up Time [ms]	Hold-Up Time [ms]	75	47	33	80	52	38	85	57	43	90	63	49	100	76	62	110	91	76	120	107	92	132	129	113	140	145	128
Input Voltage [V]	Load 50%	Load 100%																																	
	Hold-Up Time [ms]	Hold-Up Time [ms]																																	
75	47	33																																	
80	52	38																																	
85	57	43																																	
90	63	49																																	
100	76	62																																	
110	91	76																																	
120	107	92																																	
132	129	113																																	
140	145	128																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p> <p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																			

COSEL

Model	MMC50A-4	Testing Circuitry Figure A		
Item	Instantaneous Interruption Compensation 瞬時停電保障			
Object	+5.0V 7.00A			
1. Graph				
		△ Input Volt. 85V	□ Input Volt. 100V	○ Input Volt. 132V
	[mS]			
	1000			
	100			
	10			
	1			
Instantaneous Compensation Time [mS]				
	1000			
	100			
	10			
	1			
Load Current [A]	0 2 4 6 8 10			
	1000			
	100			
	10			
	1			
Load Current [A]	0 2 4 6 8 10			
2. Values				
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	
	Time [mS]			
0.0	—	—	—	
1.0	80	110	173	
2.0	63	87	153	
3.0	51	69	135	
4.0	42	61	121	
5.0	35	54	109	
6.0	30	48	96	
7.0	26	43	85	
7.7	23	41	72	
—	—	—	—	
—	—	—	—	

Instantaneous Compensation Time



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.


Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	MMC50A-4
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	+12.0V 1.00A



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注) 斜線は定格負荷電流範囲を示す。

Testing Circuitry Figure A

2. Values

Load Current [A]	Input Volt.	Input Volt.	Input Volt.
	85[V]	100[V]	132[V]
	Time [mS]		
0.0	—	—	—
0.2	56	81	145
0.4	48	70	130
0.6	43	64	121
0.8	39	57	113
1.0	36	55	106
1.1	35	53	104
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	MMC50A-4	Testing Circuitry Figure A		
Item	Instantaneous Interruption Compensation 瞬時停電保障			
Object	-12.0V 0.30A			
1. Graph	<p>Legend: Input Volt. 85V (△), Input Volt. 100V (□), Input Volt. 132V (○)</p>			
2. Values	Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
		Time [mS]		
0.00	—	—	—	—
0.06	71	94	147	
0.12	54	72	128	
0.18	47	65	119	
0.24	43	62	114	
0.30	39	57	110	
0.33	39	56	109	
—	—	—	—	
—	—	—	—	
—	—	—	—	
—	—	—	—	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。
(注) 斜線は定格負荷電流範囲を示す。

COSEL

Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A																																																
Item	Load Regulation 靜的負荷変動																																																		
Object	+5.0V 7.00A																																																		
1. Graph	<p>—△— Input Volt. 85 V —□— Input Volt. 100 V —○— Input Volt. 132 V</p>																																																		
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> <tr> <th></th> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.088</td><td>5.088</td><td>5.088</td></tr> <tr><td>1.0</td><td>5.085</td><td>5.085</td><td>5.086</td></tr> <tr><td>2.0</td><td>5.082</td><td>5.083</td><td>5.083</td></tr> <tr><td>3.0</td><td>5.080</td><td>5.080</td><td>5.081</td></tr> <tr><td>4.0</td><td>5.078</td><td>5.078</td><td>5.078</td></tr> <tr><td>5.0</td><td>5.075</td><td>5.075</td><td>5.075</td></tr> <tr><td>6.0</td><td>5.072</td><td>5.073</td><td>5.073</td></tr> <tr><td>7.0</td><td>5.070</td><td>5.070</td><td>5.070</td></tr> <tr><td>7.7</td><td>5.068</td><td>5.068</td><td>5.068</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]		Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.0	5.088	5.088	5.088	1.0	5.085	5.085	5.086	2.0	5.082	5.083	5.083	3.0	5.080	5.080	5.081	4.0	5.078	5.078	5.078	5.0	5.075	5.075	5.075	6.0	5.072	5.073	5.073	7.0	5.070	5.070	5.070	7.7	5.068	5.068	5.068	—	—	—	—
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																
0.0	5.088	5.088	5.088																																																
1.0	5.085	5.085	5.086																																																
2.0	5.082	5.083	5.083																																																
3.0	5.080	5.080	5.081																																																
4.0	5.078	5.078	5.078																																																
5.0	5.075	5.075	5.075																																																
6.0	5.072	5.073	5.073																																																
7.0	5.070	5.070	5.070																																																
7.7	5.068	5.068	5.068																																																
—	—	—	—																																																
Object	+12.0V 1.00A	2. Values																																																	
1. Graph	<p>—△— Input Volt. 85 V —□— Input Volt. 100 V —○— Input Volt. 132 V</p>																																																		
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> <tr> <th></th> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> <th>Output Volt. [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>11.992</td><td>11.993</td><td>11.994</td></tr> <tr><td>0.2</td><td>11.986</td><td>11.986</td><td>11.986</td></tr> <tr><td>0.4</td><td>11.978</td><td>11.978</td><td>11.978</td></tr> <tr><td>0.6</td><td>11.970</td><td>11.971</td><td>11.971</td></tr> <tr><td>0.8</td><td>11.963</td><td>11.963</td><td>11.963</td></tr> <tr><td>1.0</td><td>11.956</td><td>11.956</td><td>11.956</td></tr> <tr><td>1.1</td><td>11.952</td><td>11.952</td><td>11.952</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]		Output Volt. [V]	Output Volt. [V]	Output Volt. [V]	0.0	11.992	11.993	11.994	0.2	11.986	11.986	11.986	0.4	11.978	11.978	11.978	0.6	11.970	11.971	11.971	0.8	11.963	11.963	11.963	1.0	11.956	11.956	11.956	1.1	11.952	11.952	11.952	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]																																																
0.0	11.992	11.993	11.994																																																
0.2	11.986	11.986	11.986																																																
0.4	11.978	11.978	11.978																																																
0.6	11.970	11.971	11.971																																																
0.8	11.963	11.963	11.963																																																
1.0	11.956	11.956	11.956																																																
1.1	11.952	11.952	11.952																																																
—	—	—	—																																																
—	—	—	—																																																
—	—	—	—																																																
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																			

COSEL

Model	MMC50A-4	Temperature Testing Circuitry 25°C Figure A		
Item	Load Regulation 靜的負荷変動			
Object	-12.0V 0.30A			
1. Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 85V Input Volt. 100V Input Volt. 132V 			
2. Values				
Load Current [A]	Input Volt. 85[V] Output Volt. [V]	Input Volt. 100[V] Output Volt. [V]	Input Volt. 132[V] Output Volt. [V]	
0.00	-11.750	-11.753	-11.754	
0.06	-11.749	-11.751	-11.752	
0.12	-11.747	-11.749	-11.750	
0.18	-11.745	-11.746	-11.747	
0.24	-11.741	-11.744	-11.744	
0.30	-11.739	-11.739	-11.741	
0.33	-11.735	-11.736	-11.737	
—	—	—	—	
—	—	—	—	
—	—	—	—	

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSEL

Model	MMC50A-4	Temperature	25°C																																							
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)	Testing Circuitry	Figure A																																							
Object	+5.0V 7.00A																																									
1. Graph	<p style="text-align: center;">-----□----- Input Volt. 85V [mV] -----△----- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Figure 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Volt. 85V [mV]</th> <th>Ripple Output Volt. 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>1.0</td><td>5</td><td>5</td></tr> <tr><td>2.0</td><td>5</td><td>5</td></tr> <tr><td>3.0</td><td>5</td><td>5</td></tr> <tr><td>4.0</td><td>5</td><td>5</td></tr> <tr><td>5.0</td><td>5</td><td>5</td></tr> <tr><td>6.0</td><td>10</td><td>10</td></tr> <tr><td>7.0</td><td>10</td><td>10</td></tr> <tr><td>7.7</td><td>15</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Volt. 85V [mV]	Ripple Output Volt. 132V [mV]	0.0	5	5	1.0	5	5	2.0	5	5	3.0	5	5	4.0	5	5	5.0	5	5	6.0	10	10	7.0	10	10	7.7	15	10	—	—	—	—	—	—			
Load Current [A]	Ripple Output Volt. 85V [mV]	Ripple Output Volt. 132V [mV]																																								
0.0	5	5																																								
1.0	5	5																																								
2.0	5	5																																								
3.0	5	5																																								
4.0	5	5																																								
5.0	5	5																																								
6.0	10	10																																								
7.0	10	10																																								
7.7	15	10																																								
—	—	—																																								
—	—	—																																								
2. Values	<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th></th> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>1.0</td><td>5</td><td>5</td></tr> <tr><td>2.0</td><td>5</td><td>5</td></tr> <tr><td>3.0</td><td>5</td><td>5</td></tr> <tr><td>4.0</td><td>5</td><td>5</td></tr> <tr><td>5.0</td><td>5</td><td>5</td></tr> <tr><td>6.0</td><td>10</td><td>10</td></tr> <tr><td>7.0</td><td>10</td><td>10</td></tr> <tr><td>7.7</td><td>15</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]		Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.0	5	5	1.0	5	5	2.0	5	5	3.0	5	5	4.0	5	5	5.0	5	5	6.0	10	10	7.0	10	10	7.7	15	10	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																								
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																								
0.0	5	5																																								
1.0	5	5																																								
2.0	5	5																																								
3.0	5	5																																								
4.0	5	5																																								
5.0	5	5																																								
6.0	10	10																																								
7.0	10	10																																								
7.7	15	10																																								
—	—	—																																								
—	—	—																																								
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p-p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line 入力商用周期 T2: Due to Switching スイッチング周期</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																										

COSEL

Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A																																				
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)																																						
Object	+12.0V 1.00A																																						
1. Graph			2. Values																																				
			<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85 [V] Ripple Output Volt. [mV]</th> <th>Input Volt. 132 [V] Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5</td><td>5</td></tr> <tr><td>0.2</td><td>5</td><td>5</td></tr> <tr><td>0.4</td><td>5</td><td>5</td></tr> <tr><td>0.6</td><td>5</td><td>5</td></tr> <tr><td>0.8</td><td>10</td><td>10</td></tr> <tr><td>1.0</td><td>10</td><td>10</td></tr> <tr><td>1.1</td><td>10</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 85 [V] Ripple Output Volt. [mV]	Input Volt. 132 [V] Ripple Output Volt. [mV]	0.0	5	5	0.2	5	5	0.4	5	5	0.6	5	5	0.8	10	10	1.0	10	10	1.1	10	10	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V] Ripple Output Volt. [mV]	Input Volt. 132 [V] Ripple Output Volt. [mV]																																					
0.0	5	5																																					
0.2	5	5																																					
0.4	5	5																																					
0.6	5	5																																					
0.8	10	10																																					
1.0	10	10																																					
1.1	10	10																																					
—	—	—																																					
—	—	—																																					
—	—	—																																					
—	—	—																																					
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注) 斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p>																																							
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																							

COSSEL

Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple Voltage (by Load Current) リップル電圧(負荷電流特性)																																								
Object	-12.0V 0.30A																																								
1. Graph	<p style="text-align: center;">□ Input Volt. 85V [mV] △ Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Output Volt. 85V [mV]</th> <th>Ripple Output Volt. 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.06</td><td>5</td><td>5</td></tr> <tr><td>0.12</td><td>5</td><td>5</td></tr> <tr><td>0.18</td><td>5</td><td>5</td></tr> <tr><td>0.24</td><td>5</td><td>5</td></tr> <tr><td>0.30</td><td>10</td><td>10</td></tr> <tr><td>0.33</td><td>10</td><td>10</td></tr> </tbody> </table>			Load Current [A]	Ripple Output Volt. 85V [mV]	Ripple Output Volt. 132V [mV]	0.00	5	5	0.06	5	5	0.12	5	5	0.18	5	5	0.24	5	5	0.30	10	10	0.33	10	10														
Load Current [A]	Ripple Output Volt. 85V [mV]	Ripple Output Volt. 132V [mV]																																							
0.00	5	5																																							
0.06	5	5																																							
0.12	5	5																																							
0.18	5	5																																							
0.24	5	5																																							
0.30	10	10																																							
0.33	10	10																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>5</td><td>5</td></tr> <tr><td>0.06</td><td>5</td><td>5</td></tr> <tr><td>0.12</td><td>5</td><td>5</td></tr> <tr><td>0.18</td><td>5</td><td>5</td></tr> <tr><td>0.24</td><td>5</td><td>5</td></tr> <tr><td>0.30</td><td>10</td><td>10</td></tr> <tr><td>0.33</td><td>10</td><td>10</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	0.00	5	5	0.06	5	5	0.12	5	5	0.18	5	5	0.24	5	5	0.30	10	10	0.33	10	10	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																							
0.00	5	5																																							
0.06	5	5																																							
0.12	5	5																																							
0.18	5	5																																							
0.24	5	5																																							
0.30	10	10																																							
0.33	10	10																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップル電圧は、下図 p - p 値で示される。 (注)斜線は定格負荷電流範囲を示す。</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	MMC50A-4	
Item	Ripple-Noise リップルノイズ	Temperature Testing Circuitry 25°C Figure A
Object	+5.0V 7.00A	
1. Graph		
<p>[mV]</p>		Input Volt. 85V
<p>[mV]</p>		Input Volt. 132V
2. Values		
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]
	Ripple-Noise [mV]	Ripple-Noise [mV]
0.0	15	15
1.0	15	20
2.0	15	20
3.0	15	20
4.0	20	20
5.0	20	20
6.0	25	25
7.0	25	25
7.7	25	25
—	—	—
—	—	—

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

リップルノイズは、下図 p - p 値で示される。

(注)斜線は定格負荷電流範囲を示す。

T1: Due to AC Input Line
入力商用周期
T2: Due to Switching
スイッチング周期




Fig. Complex Ripple Wave Form

図 リップル波形詳細図

COSEL

Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A																																				
Item	Ripple-Noise リップルノイズ																																						
Object	+12.0V 1.00A																																						
1. Graph			2. Values																																				
<p style="text-align: center;">-----□----- Input Volt. 85V [mV] -----△----- Input Volt. 132V</p>			<table border="1"> <thead> <tr> <th>Load current [A]</th> <th>Input Volt. 85 [V] Ripple-Noise [mV]</th> <th>Input Volt. 132 [V] Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>45</td><td>40</td></tr> <tr><td>0.2</td><td>30</td><td>25</td></tr> <tr><td>0.4</td><td>35</td><td>30</td></tr> <tr><td>0.6</td><td>35</td><td>35</td></tr> <tr><td>0.8</td><td>35</td><td>35</td></tr> <tr><td>1.0</td><td>40</td><td>40</td></tr> <tr><td>1.1</td><td>40</td><td>45</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>	Load current [A]	Input Volt. 85 [V] Ripple-Noise [mV]	Input Volt. 132 [V] Ripple-Noise [mV]	0.0	45	40	0.2	30	25	0.4	35	30	0.6	35	35	0.8	35	35	1.0	40	40	1.1	40	45	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 85 [V] Ripple-Noise [mV]	Input Volt. 132 [V] Ripple-Noise [mV]																																					
0.0	45	40																																					
0.2	30	25																																					
0.4	35	30																																					
0.6	35	35																																					
0.8	35	35																																					
1.0	40	40																																					
1.1	40	45																																					
—	—	—																																					
—	—	—																																					
—	—	—																																					
—	—	—																																					
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																							
<p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																							
<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p>																																							
<p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																							


COSEL

Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A																																						
Item	Ripple-Noise リップルノイズ																																								
Object	-12.0V 0.30A																																								
1. Graph	<p>-----□----- Input Volt. 85V [mV]</p> <p>-----△----- Input Volt. 132V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise 85V [mV]</th> <th>Ripple-Noise 132V [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>50</td><td>50</td></tr> <tr><td>0.06</td><td>30</td><td>30</td></tr> <tr><td>0.12</td><td>30</td><td>30</td></tr> <tr><td>0.18</td><td>30</td><td>35</td></tr> <tr><td>0.24</td><td>30</td><td>35</td></tr> <tr><td>0.30</td><td>30</td><td>35</td></tr> <tr><td>0.33</td><td>30</td><td>35</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise 85V [mV]	Ripple-Noise 132V [mV]	0.00	50	50	0.06	30	30	0.12	30	30	0.18	30	35	0.24	30	35	0.30	30	35	0.33	30	35														
Load Current [A]	Ripple-Noise 85V [mV]	Ripple-Noise 132V [mV]																																							
0.00	50	50																																							
0.06	30	30																																							
0.12	30	30																																							
0.18	30	35																																							
0.24	30	35																																							
0.30	30	35																																							
0.33	30	35																																							
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load current [A]</th> <th>Input Volt. 85 [V]</th> <th>Input Volt. 132 [V]</th> </tr> <tr> <th>Ripple-Noise [mV]</th> <th>Ripple-Noise [mV]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>50</td><td>50</td></tr> <tr><td>0.06</td><td>30</td><td>30</td></tr> <tr><td>0.12</td><td>30</td><td>30</td></tr> <tr><td>0.18</td><td>30</td><td>35</td></tr> <tr><td>0.24</td><td>30</td><td>35</td></tr> <tr><td>0.30</td><td>30</td><td>35</td></tr> <tr><td>0.33</td><td>30</td><td>35</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]	Ripple-Noise [mV]	Ripple-Noise [mV]	0.00	50	50	0.06	30	30	0.12	30	30	0.18	30	35	0.24	30	35	0.30	30	35	0.33	30	35	—	—	—	—	—	—	—	—	—	—	—	—
Load current [A]	Input Volt. 85 [V]	Input Volt. 132 [V]																																							
	Ripple-Noise [mV]	Ripple-Noise [mV]																																							
0.00	50	50																																							
0.06	30	30																																							
0.12	30	30																																							
0.18	30	35																																							
0.24	30	35																																							
0.30	30	35																																							
0.33	30	35																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
—	—	—																																							
<p>Ripple-Noise is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p> <p>リップルノイズは、下図 p - p 値で示される。</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																									
<p>T1: Due to AC Input Line 入力商用周期</p> <p>T2: Due to Switching スイッチング周期</p> <p>Fig. Complex Ripple Wave Form 図 リップル波形詳細図</p>																																									

COSEL

Model	MMC50A-4	Temperature 25°C Testing Circuitry Figure A																																																										
Item	Overcurrent Protection 過電流保護																																																											
Object	+5.0V 7.00A																																																											
1. Graph	<p>[V] Input Volt. 85.0 V Input Volt. 100.0 V Input Volt. 132.0 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																											
2. Values	<table border="1"> <thead> <tr> <th>Output Voltage [V]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> <tr> <th>Load Current [A]</th> <th>Load Current [A]</th> <th>Load Current [A]</th> <th>Load Current [A]</th> </tr> </thead> <tbody> <tr><td>5.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>4.75</td><td>10.560</td><td>10.536</td><td>10.251</td></tr> <tr><td>4.50</td><td>10.937</td><td>10.097</td><td>9.836</td></tr> <tr><td>4.00</td><td>10.399</td><td>9.509</td><td>9.390</td></tr> <tr><td>3.50</td><td>9.847</td><td>9.138</td><td>9.167</td></tr> <tr><td>3.00</td><td>9.563</td><td>8.917</td><td>9.101</td></tr> <tr><td>2.50</td><td>9.136</td><td>8.649</td><td>8.990</td></tr> <tr><td>2.00</td><td>8.540</td><td>8.285</td><td>8.809</td></tr> <tr><td>1.50</td><td>7.908</td><td>7.813</td><td>8.577</td></tr> <tr><td>1.00</td><td>7.151</td><td>7.313</td><td>8.277</td></tr> <tr><td>0.50</td><td>6.456</td><td>6.868</td><td>8.081</td></tr> <tr><td>0.00</td><td>6.379</td><td>6.813</td><td>8.097</td></tr> </tbody> </table>				Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	Load Current [A]	5.00	—	—	—	4.75	10.560	10.536	10.251	4.50	10.937	10.097	9.836	4.00	10.399	9.509	9.390	3.50	9.847	9.138	9.167	3.00	9.563	8.917	9.101	2.50	9.136	8.649	8.990	2.00	8.540	8.285	8.809	1.50	7.908	7.813	8.577	1.00	7.151	7.313	8.277	0.50	6.456	6.868	8.081	0.00	6.379	6.813	8.097
Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																									
Load Current [A]	Load Current [A]	Load Current [A]	Load Current [A]																																																									
5.00	—	—	—																																																									
4.75	10.560	10.536	10.251																																																									
4.50	10.937	10.097	9.836																																																									
4.00	10.399	9.509	9.390																																																									
3.50	9.847	9.138	9.167																																																									
3.00	9.563	8.917	9.101																																																									
2.50	9.136	8.649	8.990																																																									
2.00	8.540	8.285	8.809																																																									
1.50	7.908	7.813	8.577																																																									
1.00	7.151	7.313	8.277																																																									
0.50	6.456	6.868	8.081																																																									
0.00	6.379	6.813	8.097																																																									
Object	+12.0V 1.00A																																																											
1. Graph	<p>[V] Input Volt. 85.0 V Input Volt. 100.0 V Input Volt. 132.0 V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																											
2. Values	<table border="1"> <thead> <tr> <th>Output Voltage [V]</th> <th>Input Volt. 85.0[V]</th> <th>Input Volt. 100.0[V]</th> <th>Input Volt. 132.0[V]</th> </tr> <tr> <th>Load Current [A]</th> <th>Load Current [A]</th> <th>Load Current [A]</th> <th>Load Current [A]</th> </tr> </thead> <tbody> <tr><td>12.00</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>11.40</td><td>2.814</td><td>2.482</td><td>2.403</td></tr> <tr><td>10.80</td><td>2.830</td><td>2.505</td><td>2.452</td></tr> <tr><td>9.60</td><td>2.871</td><td>2.574</td><td>2.568</td></tr> <tr><td>8.40</td><td>2.901</td><td>2.630</td><td>2.663</td></tr> <tr><td>7.20</td><td>2.910</td><td>2.668</td><td>2.740</td></tr> <tr><td>6.00</td><td>2.909</td><td>2.685</td><td>2.780</td></tr> <tr><td>4.80</td><td>2.901</td><td>2.694</td><td>2.806</td></tr> <tr><td>3.60</td><td>2.890</td><td>2.697</td><td>2.829</td></tr> <tr><td>2.40</td><td>2.880</td><td>2.701</td><td>2.844</td></tr> <tr><td>1.20</td><td>0.645</td><td>0.631</td><td>0.647</td></tr> <tr><td>0.00</td><td>0.224</td><td>0.218</td><td>0.227</td></tr> </tbody> </table>				Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]	Load Current [A]	Load Current [A]	Load Current [A]	Load Current [A]	12.00	—	—	—	11.40	2.814	2.482	2.403	10.80	2.830	2.505	2.452	9.60	2.871	2.574	2.568	8.40	2.901	2.630	2.663	7.20	2.910	2.668	2.740	6.00	2.909	2.685	2.780	4.80	2.901	2.694	2.806	3.60	2.890	2.697	2.829	2.40	2.880	2.701	2.844	1.20	0.645	0.631	0.647	0.00	0.224	0.218	0.227
Output Voltage [V]	Input Volt. 85.0[V]	Input Volt. 100.0[V]	Input Volt. 132.0[V]																																																									
Load Current [A]	Load Current [A]	Load Current [A]	Load Current [A]																																																									
12.00	—	—	—																																																									
11.40	2.814	2.482	2.403																																																									
10.80	2.830	2.505	2.452																																																									
9.60	2.871	2.574	2.568																																																									
8.40	2.901	2.630	2.663																																																									
7.20	2.910	2.668	2.740																																																									
6.00	2.909	2.685	2.780																																																									
4.80	2.901	2.694	2.806																																																									
3.60	2.890	2.697	2.829																																																									
2.40	2.880	2.701	2.844																																																									
1.20	0.645	0.631	0.647																																																									
0.00	0.224	0.218	0.227																																																									
<p>Note: Slanted line shows the range of the rated load current.</p> <p>(注)斜線は定格負荷電流範囲を示す。</p>																																																												

COSEL

Model	MMC50A-4	Temperature 25°C Testing Circuitry Figure A			
Item	Overcurrent Protection 過電流保護				
Object	-12.0V 0.30A				
1. Graph	[V]				
		Input Volt. 85 V Input Volt. 100 V Input Volt. 132 V			
					
2. Values					
Output Voltage [V]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]		
	Load Current [A]	Load Current [A]	Load Current [A]		
-12.00	—	—	—		
-11.40	1.38	1.29	1.30		
-10.80	1.28	1.22	1.23		
-9.60	1.19	1.15	1.15		
-8.40	1.12	1.09	1.09		
-7.20	1.07	1.04	1.04		
-6.00	0.99	0.96	0.96		
-4.80	0.89	0.86	0.87		
-3.60	0.79	0.77	0.78		
-2.40	0.71	0.70	0.70		
-1.20	0.65	0.63	0.64		
0.00	0.60	0.60	0.60		

Note: Slanted line shows the range of the rated load current.

(注) 斜線は定格負荷電流範囲を示す。

COSEL


Model	MMC50A-4			
Item	Overvoltage Protection 過電圧保護	Testing Circuitry		
Object	+5.0V 7.00A	Figure A		
1. Graph				
			2. Values	
Ambient Temp.	Input Volt. 85 V	Input Volt. 100 V	Input Volt. 132 V	
[°C]	85[V]	100[V]	132[V]	Operating Point [V]
-20	6.31	6.31	6.31	
-10	6.31	6.31	6.31	
0	6.31	6.31	6.31	
10	6.31	6.31	6.24	
20	6.24	6.24	6.24	
25	6.24	6.24	6.24	
30	6.24	6.24	6.24	
40	6.24	6.24	6.24	
50	6.24	6.24	6.24	
60	6.17	6.17	6.17	
—	—	—	—	—

Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。


COSEL


Model	MMC50A-4	Temperature	25°C
Item	Inrush Current 突入電流	Testing Circuitry	Figure A
Object	—	—	—





Input Voltage 100 V
 Frequency 60 Hz
 Load 100 %
 Inrush Current

- ① 28.91 [A]
- ② 4.20 [A]



COSEL


COSEL

COSEL

COSEL


Model	MMC50A-4	Temperature Testing Circuitry	25°C Figure A
Item	Rise and Fall Time 立上り、立下り時間		
Object	+5.0V 7.00A		

1. Graph



2. Values


Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		8.0	16.4	24.4	57.6	43.2	
100 %		8.0	21.4	29.4	33.0	27.4	



COSEL


Model	MMC50A-4	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time 立上り、立下り時間		
Object	+12.0V 1.00A		

1. Graph



2. Values


Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		11.0	12.8	23.8	47.2	52.6	
100 %		11.2	14.4	25.6	37.6	27.0	



COSEL


Model	MMC50A-4	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time 立上り、立下り時間		
Object	-12.0V 0.30A		

1. Graph



2. Values


Load	Time	T _d	T _r	T _s	T _h	T _f	[mS]
50 %		14.0	10.8	24.8	56.4	115.8	
100 %		13.8	11.6	25.4	42.6	55.6	



COSEL

Model	MMC50A-4	Testing Circuitry Figure A		
Item	Ambient Temperature Drift 周囲温度変動			
Object	+5.0V7.00A			
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>	2. Values		
	<p>Input Volt. 85.0V Input Volt. 100.0V Input Volt. 132.0V</p>			
Object	+12.0V1.00A	2. Values		
1. Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p>			
	<p>Input Volt. 85.0V Input Volt. 100.0V Input Volt. 132.0V</p>			
Note:	Slanted line shows the range of the rated ambient temperature.			
(注)	斜線は定格周囲温度範囲を示す。			

COSEL




Testing Circuitry Figure A

2. Values

Temperature [°C]	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
	Output Volt. [V]	Output Volt. [V]	Output Volt. [V]
-20	-11.798	-11.797	-11.798
-10	-11.793	-11.792	-11.792
0	-11.782	-11.782	-11.782
10	-11.769	-11.769	-11.769
20	-11.753	-11.753	-11.753
25	-11.744	-11.743	-11.743
30	-11.733	-11.733	-11.732
40	-11.717	-11.716	-11.716
50	-11.697	-11.697	-11.697
60	-11.677	-11.677	-11.676
—	—	—	—

COSEL

Model	MMC50A-4
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧
Object	+5.0V 7.00A




Testing Circuitry Figure A

2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-20	45.8	54.5
-10	45.6	53.9
0	44.5	53.5
10	44.6	52.6
20	44.6	52.4
25	43.5	52.6
30	43.5	52.4
40	43.6	52.5
50	43.5	51.5
60	43.5	51.3
—	—	—

Object +12.0V 1.00A



2. Values

Ambient Temp. [°C]	Load 50%	Load 100%
	Input Volt. [V]	Input Volt. [V]
-20	49.9	53.6
-10	49.6	52.5
0	49.5	52.5
10	48.6	51.3
20	48.5	51.5
25	48.5	51.5
30	48.5	51.5
40	47.5	51.5
50	47.4	50.6
60	46.7	50.5
—	—	—

Note: Slanted line shows the range of the rated ambient temperature.


(注)斜線は定格周囲温度範囲を示す。

COSEL



Model	MMC50A-4			
Item	Minimum Input Voltage for Regulated Output Voltage 最低レギュレーション電圧			
Object	-12.0 V 0.30 A			
1. Graph				
[V]		Load 50% Load 100%		
Input Voltage [V]				
Ambient Temperature [°C]				
Note: Slanted line shows the range of the rated ambient temperature.				
(注)斜線は定格周囲温度範囲を示す。				
Testing Circuitry Figure A				
2. Values				
Ambient Temp. [°C]	Load 50%	Load 100%		
	Input Volt. [V]	Input Volt. [V]		
-20	51.6	53.6		
-10	51.5	52.5		
0	50.5	51.4		
10	50.4	51.6		
20	50.5	51.4		
25	50.5	51.4		
30	49.5	51.5		
40	49.5	50.5		
50	49.4	50.4		
60	49.5	50.7		
—	—	—		

COSSEL

Model	MMC50A-4																																									
Item	Ripple Voltage (by Ambient Temp.) リップル電圧 (周囲温度特性)	Testing Circuitry Figure A																																								
Object	+5.0V 7.00A																																									
1. Graph																																										
		Load 50% □	Load 100% △																																							
<p>[mV]</p> <p>Ripple Voltage</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100 V</p>																																										
2. Values																																										
<table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th></th> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>10</td><td>25</td></tr> <tr><td>-10</td><td>10</td><td>20</td></tr> <tr><td>0</td><td>10</td><td>15</td></tr> <tr><td>10</td><td>5</td><td>10</td></tr> <tr><td>20</td><td>5</td><td>10</td></tr> <tr><td>25</td><td>5</td><td>10</td></tr> <tr><td>30</td><td>5</td><td>10</td></tr> <tr><td>40</td><td>5</td><td>5</td></tr> <tr><td>50</td><td>5</td><td>5</td></tr> <tr><td>60</td><td>5</td><td>5</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temp. [°C]	Load 50%	Load 100%		Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	-20	10	25	-10	10	20	0	10	15	10	5	10	20	5	10	25	5	10	30	5	10	40	5	5	50	5	5	60	5	5	—	—	—
Ambient Temp. [°C]	Load 50%	Load 100%																																								
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																								
-20	10	25																																								
-10	10	20																																								
0	10	15																																								
10	5	10																																								
20	5	10																																								
25	5	10																																								
30	5	10																																								
40	5	5																																								
50	5	5																																								
60	5	5																																								
—	—	—																																								
1. Graph																																										
		Load 50% □	Load 100% △																																							
<p>[mV]</p> <p>Ripple Voltage</p> <p>Ambient Temperature [°C]</p> <p>Input Volt. 100 V</p>																																										
2. Values																																										
<table border="1"> <thead> <tr> <th>Ambient Temp. [°C]</th> <th>Load 50%</th> <th>Load 100%</th> </tr> <tr> <th></th> <th>Ripple Output Volt. [mV]</th> <th>Ripple Output Volt. [mV]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>10</td><td>15</td></tr> <tr><td>-10</td><td>10</td><td>15</td></tr> <tr><td>0</td><td>5</td><td>10</td></tr> <tr><td>10</td><td>5</td><td>10</td></tr> <tr><td>20</td><td>5</td><td>10</td></tr> <tr><td>25</td><td>5</td><td>10</td></tr> <tr><td>30</td><td>5</td><td>10</td></tr> <tr><td>40</td><td>5</td><td>5</td></tr> <tr><td>50</td><td>5</td><td>5</td></tr> <tr><td>60</td><td>5</td><td>5</td></tr> <tr><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>				Ambient Temp. [°C]	Load 50%	Load 100%		Ripple Output Volt. [mV]	Ripple Output Volt. [mV]	-20	10	15	-10	10	15	0	5	10	10	5	10	20	5	10	25	5	10	30	5	10	40	5	5	50	5	5	60	5	5	—	—	—
Ambient Temp. [°C]	Load 50%	Load 100%																																								
	Ripple Output Volt. [mV]	Ripple Output Volt. [mV]																																								
-20	10	15																																								
-10	10	15																																								
0	5	10																																								
10	5	10																																								
20	5	10																																								
25	5	10																																								
30	5	10																																								
40	5	5																																								
50	5	5																																								
60	5	5																																								
—	—	—																																								
Note: Slanted line shows the range of the rated ambient temperature.																																										
(注)斜線は定格周囲温度範囲を示す。																																										

COSSEL

COSEL

Model	MMC50A-4	Temperature Testing Circuitry	25 °C Figure A																						
Item	Time Lapse Drift 経時ドリフト																								
Object	+5.0V 7.00A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100.0V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.073</td></tr> <tr><td>0.5</td><td>5.071</td></tr> <tr><td>1.0</td><td>5.071</td></tr> <tr><td>2.0</td><td>5.071</td></tr> <tr><td>3.0</td><td>5.071</td></tr> <tr><td>4.0</td><td>5.071</td></tr> <tr><td>5.0</td><td>5.071</td></tr> <tr><td>6.0</td><td>5.071</td></tr> <tr><td>7.0</td><td>5.071</td></tr> <tr><td>8.0</td><td>5.071</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.073	0.5	5.071	1.0	5.071	2.0	5.071	3.0	5.071	4.0	5.071	5.0	5.071	6.0	5.071	7.0	5.071	8.0	5.071
Time since start [H]	Output Voltage [V]																								
0.0	5.073																								
0.5	5.071																								
1.0	5.071																								
2.0	5.071																								
3.0	5.071																								
4.0	5.071																								
5.0	5.071																								
6.0	5.071																								
7.0	5.071																								
8.0	5.071																								
Object +12.0V 1.00A			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100.0V</p> <p>Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>11.970</td></tr> <tr><td>0.5</td><td>11.954</td></tr> <tr><td>1.0</td><td>11.954</td></tr> <tr><td>2.0</td><td>11.955</td></tr> <tr><td>3.0</td><td>11.954</td></tr> <tr><td>4.0</td><td>11.955</td></tr> <tr><td>5.0</td><td>11.954</td></tr> <tr><td>6.0</td><td>11.954</td></tr> <tr><td>7.0</td><td>11.954</td></tr> <tr><td>8.0</td><td>11.954</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	11.970	0.5	11.954	1.0	11.954	2.0	11.955	3.0	11.954	4.0	11.955	5.0	11.954	6.0	11.954	7.0	11.954	8.0	11.954
Time since start [H]	Output Voltage [V]																								
0.0	11.970																								
0.5	11.954																								
1.0	11.954																								
2.0	11.955																								
3.0	11.954																								
4.0	11.955																								
5.0	11.954																								
6.0	11.954																								
7.0	11.954																								
8.0	11.954																								

COSSEL

Model	MMC50A-4	Temperature Testing Circuitry	25 °C Figure A																					
Item	Time Lapse Drift 経時ドリフト																							
Object	-12.0V 0.30A																							
1. Graph			2. Values																					
<p>[V]</p> <table border="1"> <caption>Data points from Figure A graph</caption> <thead> <tr> <th>Time [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-11.762</td></tr> <tr><td>0.5</td><td>-11.732</td></tr> <tr><td>1.0</td><td>-11.732</td></tr> <tr><td>2.0</td><td>-11.732</td></tr> <tr><td>3.0</td><td>-11.732</td></tr> <tr><td>4.0</td><td>-11.732</td></tr> <tr><td>5.0</td><td>-11.732</td></tr> <tr><td>6.0</td><td>-11.732</td></tr> <tr><td>7.0</td><td>-11.732</td></tr> <tr><td>8.0</td><td>-11.732</td></tr> </tbody> </table>			Time [H]	Output Voltage [V]	0.0	-11.762	0.5	-11.732	1.0	-11.732	2.0	-11.732	3.0	-11.732	4.0	-11.732	5.0	-11.732	6.0	-11.732	7.0	-11.732	8.0	-11.732
Time [H]	Output Voltage [V]																							
0.0	-11.762																							
0.5	-11.732																							
1.0	-11.732																							
2.0	-11.732																							
3.0	-11.732																							
4.0	-11.732																							
5.0	-11.732																							
6.0	-11.732																							
7.0	-11.732																							
8.0	-11.732																							
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>																								



Model	MMC50A-4	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	

Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : 0~50 °C

Input Voltage : 85~132 V

Load Current (AVR 1) : 0.75~7.00 A (AVR 2) : 0~1 A (AVR 3) : 0~0.3 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 0~50 °C

入力電圧 85~132 V

負荷電流 (AVR 1) : 0.75~7.00 A (AVR 2) : 0~1 A (AVR 3) : 0~0.3 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

Object	+5.0V7.00A					
Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	0	132	0.75	5.093	±17	±0.4
Minimum Voltage	50	85	7.00	5.060		
Object	+12.0V1.00A					
Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	0	85	0	12.012	±39	±0.4
Minimum Voltage	50	132	1	11.935		
Object	-12.0V0.30A					
Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	0	132	0.0	-11.808	±62	±0.6
Minimum Voltage	50	132	0.3	-11.684		



Model	MMC50A-4	
Item	Condensation 結露特性	Testing Circuitry Figure A
Object	+5.0V 7.00A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	5.069	Input Volt.: 100V, Load Current: 7.00A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current: 7.00A
Load Regulation [mV]	15	Input Volt.: 100V, Load Current: 0.75~7.00A



Model	MMC50A-4	
Item	Condensation 結露特性	Testing Circuitry Figure A
Object	+12.0V 1.00A	

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	11.955	Input Volt.: 100V, Load Current:1A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current:1A
Load Regulation [mV]	35	Input Volt.: 100V, Load Current:0~1A



Model	MMC50A-4		
Item	Condensation 結露特性	Testing Circuitry	Figure A
Object	-12.0V 0.30A		

1. Condensation test

Testing procedure is as follows.

- ① Keeping and cooling the unit in a tank at -10°C for an hour with the input off.
- ② Taking it out of the tank and dewing itself in a room where the temperature is 25°C and the humidity is 40%RH.
- ③ Testing electrical characteristics of the unit to confirm there be no fault.

1. 結露特性試験

入力を切った状態で、恒温槽で-10°Cに冷却しておき、約1時間後に恒温槽から取り出し、室温25°C、湿度40%RHの状態におき結露させ、その電気的特性の測定を行い、異常のないことを確認する。

2. Values

Item	Data	Testing Conditions
Output Voltage [V]	-11.791	Input Volt.: 100V, Load Current: 0.3A
Line Regulation [mV]	1	Input Volt.: 85~132V, Load Current: 0.3A
Load Regulation [mV]	13	Input Volt.: 100V, Load Current: 0.0~0.3A



Model	MMC50A-4	Temperature Testing Circuitry Figure A	25°C
Item	Leakage Current 漏洩電流		
Object	—		

1. Results

Standards	Leakage Current [mA]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
(A) DENTORI	0.24	0.26	0.33
(B) IEC60950	0.22	0.27	0.33

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

交流入力の両相について測定し、その大きい方を漏洩電流測定値とする。

Standards	Leakage Current [mA]		
	Input Volt. 170 [V]	Input Volt. 230 [V]	Input Volt. 264 [V]
(B) IEC60950	—	—	—

COSEL

Model	MMC50A-4	Testing Circuitry Figure D
Item	Conducted Emission 雜音端子電圧	
Object	_____	

1. Graph

Remarks


Input Volt. 120 V

Load 100 %

Note: Slanted line shows the range of Tolerance.

(注)斜線は許容値を示す。

N0	Standards	Standards Complied	Frequency [MHz]	Tolerance [dB/ μ V]
1	FCC class A	○	0.45~1.6	60
			1.6~30	69.5
2	FCC class B		0.45~30	48
3	VCCI class A		0.15~0.5	79
			0.5~30	73
4	VCCI class B		0.15~0.5	66~56
			0.5~5	56
			5~30	60
5	CISPR Pub. 22 class A (EN55022)		0.15~0.5	79
			0.5~30	73
6	CISPR Pub. 22 class B (EN55022)		0.15~0.5	66~56
			0.5~5	56
			5~30	60







Figure B (DENTORI)




Figure B (IEC 60950)




Figure C




Figure D




Figure E