

COSEL

TEST DATA OF NBC-10-□□□

Noise Filter

Oct. 17. 2007

Approved by : Toshio Watanabe
Toshio Watanabe

Watanabe

Design Manager

Prepared by : Tadayuki Noda
Tadayuki Noda


Design Engineer

COSEL CO.,LTD.





CONTENTS


1.Attenuation Characteristics	1
2.Pulse Attenuation Characteristics	4
3.Leakage Current	6
4.Figure of Testing Circuitry	7
(Final Page 8)	

COSEL


COSEL




COSEL

COSEL

COSEL

Model	NBC-10-□□□	Temperature Testing Circuitry	25°C Figure B
Item	Pulse Attenuation Characteristics		
Object	_____		





Model	NBC-10-□□□	Temperature Testing Circuitry Figure C
Item	Leakage Current	
Object	_____	

1. Results

[mA]

Model	Standards	Input Volt.				Note
		100 [V]	125 [V]	230 [V]	250 [V]	
NBC-10-681	UL1283	0.031	0.040	0.082	0.093	
NBC-10-102	UL1283	0.044	0.056	0.110	0.120	
NBC-10-222	UL1283	0.090	0.120	0.230	0.250	
NBC-10-332	UL1283	0.130	0.170	0.340	0.370	
NBC-10-472	UL1283	0.190	0.240	0.480	0.520	

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL




Figure A - 1 Differential mode attenuation measurement




Figure A - 2 Common mode attenuation measurement

COSEL




Figure B Pulse attenuation measurement




Figure C Leakage current measurement (UL1283)