



TEST DATA OF NBM-30-□□□

Noise Filter

Oct. 17. 2007

Approved by : Toshio Watanabe
Toshio Watanabe

Watanabe
Design Manager

Prepared by : Tadayuki Noda
Tadayuki Noda

Noda
Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Attenuation Characteristics	1
2.Pulse Attenuation Characteristics	4
3.Leakage Current	6
4.Figure of Testing Circuitry	7
(Final Page 8)	



COSEL

Model NBM-30-□□□

Temperature 25°C
Testing Circuitry Figure A



Item Attenuation Characteristics


Object _____





COSEL

Model	NBM-30-□□□	Temperature	25°C
Item	Attenuation Characteristics	Testing Circuitry	Figure A
Object	<hr/>		



COSEL

COSEL

COSEL



Model	NBM-30-□□□	Temperature Testing Circuitry	25°C Figure C	
Item	Leakage Current			
Object	_____			

1. Results

[mA]

Model	Standards	Input Volt.				Note
		100 [V]	125 [V]	230 [V]	250 [V]	
NBM-30-000	UL1283	0.002	0.002	0.004	0.005	
NBM-30-101	UL1283	0.006	0.007	0.013	0.015	
NBM-30-221	UL1283	0.011	0.013	0.025	0.028	
NBM-30-331	UL1283	0.015	0.019	0.038	0.042	
NBM-30-471	UL1283	0.023	0.030	0.061	0.069	

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL




Figure A - 1 Differential mode attenuation measurement





Figure A - 2 Common mode attenuation measurement

COSEL



Pulse attenuation measurement





Figure B Pulse attenuation measurement



$$\text{Leakage Current} = \frac{\text{Effective Value of Voltmeter [V]}}{1.5 [\text{k}\Omega]}$$

Figure C Leakage current measurement (UL1283)