

# TEST DATA OF PBA1000F-12

Regulated DC Power Supply  
Mar.30, 2004

Approved by : Kuniaki Nagahara  
Kuniaki Nagahara Design Manager

Prepared by : Kazunari Uotani  
Kazunari Uotani Design Engineer

**COSEL CO.,LTD.**



## CONTENTS


1. Input Current (by Load Current) . . . . .	1
2. Input Power (by Load Current) . . . . .	2
3. Efficiency (by Input Voltage) . . . . .	3
4. Efficiency (by Load Current) . . . . .	4
5. Power Factor (by Input Voltage) . . . . .	5
6. Power Factor (by Load Current) . . . . .	6
7. Inrush Current . . . . .	7
8. Leakage Current . . . . .	8
9. Line Regulation . . . . .	9
10. Load Regulation . . . . .	10
11. Dynamic Load Response . . . . .	11
12. Ripple Voltage (by Load Current) . . . . .	12
13. Ripple-Noise . . . . .	13
14. Ripple Voltage (by Ambient Temperature) . . . . .	14
15. Ambient Temperature Drift . . . . .	15
16. Output Voltage Accuracy . . . . .	16
17. Time Lapse Drift . . . . .	17
18. Rise and Fall Time . . . . .	18
19. Hold-Up Time . . . . .	19
20. Instantaneous Interruption Compensation . . . . .	20
21. Minimum Input Voltage for Regulated Output Voltage . . . . .	21
22. Overcurrent Protection . . . . .	22
23. Ovvoltage Protection . . . . .	23
24. Figure of Testing Circuitry . . . . .	24

(Final Page 24)

**COSEL**

Model	PBA1000F-12																																																					
Item	Input Current (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	—																																																					
1. Graph																																																						
—△— Input Volt. 100V - -□-- Input Volt. 200V - -○-- Input Volt. 230V																																																						
<p>The graph shows a linear relationship between Input Current [A] on the Y-axis (0.0 to 20.0) and Load Current [A] on the X-axis (0 to 100). Three curves are plotted for different input voltages: 100V (solid triangles), 200V (dashed squares), and 230V (dashed circles). A slanted line is drawn through the origin, representing the rated load current range.</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Current [A] (100V)</th> <th>Input Current [A] (200V)</th> <th>Input Current [A] (230V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.318</td><td>0.218</td><td>0.217</td></tr> <tr><td>15.0</td><td>2.654</td><td>1.384</td><td>1.224</td></tr> <tr><td>30.0</td><td>4.690</td><td>2.408</td><td>2.114</td></tr> <tr><td>45.0</td><td>6.810</td><td>3.438</td><td>3.012</td></tr> <tr><td>60.0</td><td>8.980</td><td>4.490</td><td>3.918</td></tr> <tr><td>75.0</td><td>11.200</td><td>5.550</td><td>4.840</td></tr> <tr><td>88.0</td><td>13.000</td><td>6.470</td><td>5.650</td></tr> <tr><td>96.8</td><td>14.560</td><td>7.110</td><td>6.200</td></tr> </tbody> </table>	Load Current [A]	Input Current [A] (100V)	Input Current [A] (200V)	Input Current [A] (230V)	0	0.318	0.218	0.217	15.0	2.654	1.384	1.224	30.0	4.690	2.408	2.114	45.0	6.810	3.438	3.012	60.0	8.980	4.490	3.918	75.0	11.200	5.550	4.840	88.0	13.000	6.470	5.650	96.8	14.560	7.110	6.200																		
Load Current [A]	Input Current [A] (100V)	Input Current [A] (200V)	Input Current [A] (230V)																																																			
0	0.318	0.218	0.217																																																			
15.0	2.654	1.384	1.224																																																			
30.0	4.690	2.408	2.114																																																			
45.0	6.810	3.438	3.012																																																			
60.0	8.980	4.490	3.918																																																			
75.0	11.200	5.550	4.840																																																			
88.0	13.000	6.470	5.650																																																			
96.8	14.560	7.110	6.200																																																			
2. Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.318</td><td>0.218</td><td>0.217</td></tr> <tr><td>15.0</td><td>2.654</td><td>1.384</td><td>1.224</td></tr> <tr><td>30.0</td><td>4.690</td><td>2.408</td><td>2.114</td></tr> <tr><td>45.0</td><td>6.810</td><td>3.438</td><td>3.012</td></tr> <tr><td>60.0</td><td>8.980</td><td>4.490</td><td>3.918</td></tr> <tr><td>75.0</td><td>11.200</td><td>5.550</td><td>4.840</td></tr> <tr><td>88.0</td><td>13.000</td><td>6.470</td><td>5.650</td></tr> <tr><td>96.8</td><td>14.560</td><td>7.110</td><td>6.200</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.318	0.218	0.217	15.0	2.654	1.384	1.224	30.0	4.690	2.408	2.114	45.0	6.810	3.438	3.012	60.0	8.980	4.490	3.918	75.0	11.200	5.550	4.840	88.0	13.000	6.470	5.650	96.8	14.560	7.110	6.200	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.318	0.218	0.217																																																			
15.0	2.654	1.384	1.224																																																			
30.0	4.690	2.408	2.114																																																			
45.0	6.810	3.438	3.012																																																			
60.0	8.980	4.490	3.918																																																			
75.0	11.200	5.550	4.840																																																			
88.0	13.000	6.470	5.650																																																			
96.8	14.560	7.110	6.200																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**


Model	PBA1000F-12																																																					
Item	Input Power (by Load Current)	Temperature	25°C																																																			
Object	Testing Circuitry Figure A																																																					
1.Graph																																																						
—△— Input Volt. 100V - - -□- - Input Volt. 200V - - -○- - Input Volt. 230V			2.Values																																																			
 <p>The graph plots Input Power [W] on the Y-axis (0 to 2000) against Load Current [A] on the X-axis (0 to 100). Three curves are shown for input voltages of 100V, 200V, and 230V. The 100V curve starts at (0,0) and ends at approximately (95, 1450). The 200V curve starts at (0,0) and ends at approximately (95, 1300). The 230V curve starts at (0,0) and ends at approximately (95, 1200). A slanted line is drawn from the origin through the end points of the curves.</p>																																																						
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>24</td> <td>21</td> <td>17</td> </tr> <tr> <td>15.0</td> <td>250</td> <td>246</td> <td>245</td> </tr> <tr> <td>30.0</td> <td>455</td> <td>448</td> <td>448</td> </tr> <tr> <td>45.0</td> <td>665</td> <td>655</td> <td>653</td> </tr> <tr> <td>60.0</td> <td>885</td> <td>866</td> <td>862</td> </tr> <tr> <td>75.0</td> <td>1108</td> <td>1080</td> <td>1076</td> </tr> <tr> <td>88.0</td> <td>1298</td> <td>1267</td> <td>1264</td> </tr> <tr> <td>96.8</td> <td>1435</td> <td>1396</td> <td>1391</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	24	21	17	15.0	250	246	245	30.0	455	448	448	45.0	665	655	653	60.0	885	866	862	75.0	1108	1080	1076	88.0	1298	1267	1264	96.8	1435	1396	1391	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	24	21	17																																																			
15.0	250	246	245																																																			
30.0	455	448	448																																																			
45.0	665	655	653																																																			
60.0	885	866	862																																																			
75.0	1108	1080	1076																																																			
88.0	1298	1267	1264																																																			
96.8	1435	1396	1391																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

**COSEL**

Model	PBA1000F-12	Temperature	25°C																											
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																											
Object	—	2. Values																												
1. Graph	<p>--- □ --- Load 50%</p> <p>— ▲ — Load 100%</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency [Load 50%] [%]</th> <th>Efficiency [Load 100%] [%]</th> </tr> </thead> <tbody> <tr><td>77</td><td>80.6</td><td>79.6</td></tr> <tr><td>85</td><td>81.3</td><td>80.5</td></tr> <tr><td>100</td><td>82.0</td><td>82.0</td></tr> <tr><td>120</td><td>82.1</td><td>82.7</td></tr> <tr><td>200</td><td>83.3</td><td>84.2</td></tr> <tr><td>230</td><td>83.5</td><td>84.5</td></tr> <tr><td>264</td><td>83.8</td><td>84.8</td></tr> <tr><td>280</td><td>85.0</td><td>85.6</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [Load 50%] [%]	Efficiency [Load 100%] [%]	77	80.6	79.6	85	81.3	80.5	100	82.0	82.0	120	82.1	82.7	200	83.3	84.2	230	83.5	84.5	264	83.8	84.8	280	85.0	85.6
Input Voltage [V]	Efficiency [Load 50%] [%]	Efficiency [Load 100%] [%]																												
77	80.6	79.6																												
85	81.3	80.5																												
100	82.0	82.0																												
120	82.1	82.7																												
200	83.3	84.2																												
230	83.5	84.5																												
264	83.8	84.8																												
280	85.0	85.6																												
Efficiency [%]																														
100																														
92																														
84																														
76																														
68																														
60																														
52																														
44																														
50	100	150	200	250	300																									
	Input Voltage [V]																													
Note: Slanted line shows the range of the rated input voltage.																														

# COSEL

Model	PBA1000F-12
Item	Efficiency (by Load Current)
Object	—



Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	-	-	-
15.0	72.8	73.9	74.2
30.0	79.9	81.1	81.1
45.0	82.1	83.4	83.6
60.0	82.3	84.1	84.4
75.0	82.1	84.2	84.5
88.0	82.2	84.2	84.4
96.8	81.8	84.1	84.4
--	-	-	-
--	-	-	-
--	-	-	-

# COSEL




Model	PBA1000F-12	Temperature	25°C																																
Item	Power Factor (by Input Voltage)	Testing Circuitry	Figure A																																
Object	—																																		
1. Graph																																			
<p>Legend: --- □--- Load 50% — ▲— Load 100%</p> <p>Y-axis: Power Factor X-axis: Input Voltage [V]</p>																																			
Note: Slanted line shows the range of the rated input voltage.																																			
2. Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>77</td> <td>0.990</td> <td>0.997</td> </tr> <tr> <td>85</td> <td>0.985</td> <td>0.998</td> </tr> <tr> <td>100</td> <td>0.980</td> <td>0.993</td> </tr> <tr> <td>120</td> <td>0.980</td> <td>0.994</td> </tr> <tr> <td>200</td> <td>0.954</td> <td>0.981</td> </tr> <tr> <td>230</td> <td>0.944</td> <td>0.975</td> </tr> <tr> <td>264</td> <td>0.934</td> <td>0.965</td> </tr> <tr> <td>280</td> <td>0.622</td> <td>0.686</td> </tr> <tr> <td>—</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Power Factor		Load 50%	Load 100%	77	0.990	0.997	85	0.985	0.998	100	0.980	0.993	120	0.980	0.994	200	0.954	0.981	230	0.944	0.975	264	0.934	0.965	280	0.622	0.686	—	-	-
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
77	0.990	0.997																																	
85	0.985	0.998																																	
100	0.980	0.993																																	
120	0.980	0.994																																	
200	0.954	0.981																																	
230	0.944	0.975																																	
264	0.934	0.965																																	
280	0.622	0.686																																	
—	-	-																																	

**COSEL**

Model	PBA1000F-12																																																					
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
Object	—	Testing Circuitry	Figure A																																																			
1.Graph																																																						
<p>—△— Input Volt. 100V      - - -□--- Input Volt. 200V      - - -○--- Input Volt. 230V</p>																																																						
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.763</td><td>0.477</td><td>0.340</td></tr> <tr> <td>15.0</td><td>0.944</td><td>0.891</td><td>0.872</td></tr> <tr> <td>30.0</td><td>0.972</td><td>0.933</td><td>0.924</td></tr> <tr> <td>45.0</td><td>0.981</td><td>0.955</td><td>0.945</td></tr> <tr> <td>60.0</td><td>0.991</td><td>0.968</td><td>0.960</td></tr> <tr> <td>75.0</td><td>0.995</td><td>0.976</td><td>0.970</td></tr> <tr> <td>88.0</td><td>0.998</td><td>0.982</td><td>0.976</td></tr> <tr> <td>96.8</td><td>0.999</td><td>0.984</td><td>0.979</td></tr> <tr> <td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>—</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.763	0.477	0.340	15.0	0.944	0.891	0.872	30.0	0.972	0.933	0.924	45.0	0.981	0.955	0.945	60.0	0.991	0.968	0.960	75.0	0.995	0.976	0.970	88.0	0.998	0.982	0.976	96.8	0.999	0.984	0.979	—	-	-	-	—	-	-	-	—	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.763	0.477	0.340																																																			
15.0	0.944	0.891	0.872																																																			
30.0	0.972	0.933	0.924																																																			
45.0	0.981	0.955	0.945																																																			
60.0	0.991	0.968	0.960																																																			
75.0	0.995	0.976	0.970																																																			
88.0	0.998	0.982	0.976																																																			
96.8	0.999	0.984	0.979																																																			
—	-	-	-																																																			
—	-	-	-																																																			
—	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**

Model	PBA1000F-12	Temperature Testing Circuitry	25°C Figure A
Item	Inrush Current		
Object	—		





Model	PBA1000F-12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

### 1. Results

[mA]

Standards		Input Volt.			Note
		100[V]	200[V]	240[V]	
DEN-AN	Both phases	0.20	0.40	0.42	Operation
	One of phase	0.35	0.73	0.78	stand by
IEC60950	Both phases	0.21	0.40	0.52	Operation
	One of phase	0.36	0.72	0.87	stand by

The value for "One phase" is the reference value only.

### 2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.


# COSEL

Model	PBA1000F-12
Item	Line Regulation
Object	+12V88A

Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph

--- □ --- Load 50%  
— △ — Load 100%





Note: Slanted line shows the range of the rated input voltage.

## 2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
77	12.123	12.125
85	12.124	12.124
100	12.124	12.123
120	12.124	12.123
200	12.124	12.123
230	12.124	12.123
264	12.125	12.123
280	12.125	12.123
-	-	-

**COSEL**


Model	PBA1000F-12	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V88A																																																					
1. Graph																																																						
—△— Input Volt. 100V - - -□--- Input Volt. 200V - - -○--- Input Volt. 230V			2. Values																																																			
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>12.136</td><td>12.137</td><td>12.136</td></tr> <tr> <td>15.0</td><td>12.134</td><td>12.134</td><td>12.133</td></tr> <tr> <td>30.0</td><td>12.134</td><td>12.133</td><td>12.132</td></tr> <tr> <td>45.0</td><td>12.133</td><td>12.133</td><td>12.131</td></tr> <tr> <td>60.0</td><td>12.132</td><td>12.132</td><td>12.130</td></tr> <tr> <td>75.0</td><td>12.131</td><td>12.131</td><td>12.129</td></tr> <tr> <td>88.0</td><td>12.131</td><td>12.130</td><td>12.128</td></tr> <tr> <td>96.8</td><td>12.130</td><td>12.130</td><td>12.128</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	12.136	12.137	12.136	15.0	12.134	12.134	12.133	30.0	12.134	12.133	12.132	45.0	12.133	12.133	12.131	60.0	12.132	12.132	12.130	75.0	12.131	12.131	12.129	88.0	12.131	12.130	12.128	96.8	12.130	12.130	12.128	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	12.136	12.137	12.136																																																			
15.0	12.134	12.134	12.133																																																			
30.0	12.134	12.133	12.132																																																			
45.0	12.133	12.133	12.131																																																			
60.0	12.132	12.132	12.130																																																			
75.0	12.131	12.131	12.129																																																			
88.0	12.131	12.130	12.128																																																			
96.8	12.130	12.130	12.128																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

**COSEL**

**COSEL**

Model	PBA1000F-12
Item	Ripple Voltage (by Load Current)
Object	+12V88A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	10	10
15.0	15	15
30.0	15	15
45.0	15	15
60.0	20	20
75.0	20	20
88.0	25	25
96.8	25	25
--	-	-
--	-	-
--	-	-



T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form

**COSEL**

Model	PBA1000F-12
Item	Ripple-Noise
Object	+12V88A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	20	20
15.0	25	25
30.0	30	30
45.0	40	45
60.0	50	50
75.0	50	50
88.0	55	55
96.8	55	55
--	-	-
--	-	-
--	-	-





Fig. Complex Ripple Wave Form

**COSEL**
**Model** PBA1000F-12

**Item** Ripple Voltage (by Ambient Temp.)


**Object** +12V88A
**1. Graph**

--- □ --- Input Volt. 100V  
 —△— Input Volt. 200V


**Measured by 20 MHz Oscilloscope.**
**Note:** Slanted line shows the range of the rated ambient temperature.

**Testing Circuitry Figure A**
**2. Values**

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	80	80
-20	60	60
0	35	35
25	25	25
50	25	25
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

**COSEL**

## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Output Voltage [V]		
	100[V]	200[V]	230[V]
-30	12.132	12.131	12.131
-20	12.137	12.137	12.137
-10	12.137	12.136	12.136
0	12.135	12.136	12.136
10	12.134	12.134	12.134
25	12.130	12.129	12.129
30	12.130	12.130	12.130
40	12.125	12.123	12.121
50	12.112	12.110	12.109
60	12.096	12.092	12.087
--	-	-	-



Model	PBA1000F-12	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V88A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 88A


\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	264	0	12.149	$\pm 24$	$\pm 0.2$
Minimum Voltage	50	264	88	12.101		

**COSEL**

Model	PBA1000F-12	Temperature Testing Circuitry 25°C Figure A																						
Item	Time Lapse Drift																							
Object	+12V88A																							
1. Graph		2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>		<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.134</td></tr> <tr><td>0.5</td><td>12.118</td></tr> <tr><td>1.0</td><td>12.118</td></tr> <tr><td>2.0</td><td>12.118</td></tr> <tr><td>3.0</td><td>12.118</td></tr> <tr><td>4.0</td><td>12.118</td></tr> <tr><td>5.0</td><td>12.118</td></tr> <tr><td>6.0</td><td>12.118</td></tr> <tr><td>7.0</td><td>12.118</td></tr> <tr><td>8.0</td><td>12.118</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.134	0.5	12.118	1.0	12.118	2.0	12.118	3.0	12.118	4.0	12.118	5.0	12.118	6.0	12.118	7.0	12.118	8.0	12.118
Time since start [H]	Output Voltage [V]																							
0.0	12.134																							
0.5	12.118																							
1.0	12.118																							
2.0	12.118																							
3.0	12.118																							
4.0	12.118																							
5.0	12.118																							
6.0	12.118																							
7.0	12.118																							
8.0	12.118																							
* The characteristic of AC200V is equal.																								

**COSEL**


# COSEL

Model	PBA1000F-12
-------	-------------

| Item | Hold-Up Time |
| Object | +12V88A |

**1. Graph**

---□--- Load 50%  
—△— Load 100%



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C  
Testing Circuitry Figure A

**2. Values**


Input Voltage [V]	Hold-Up Time [mS]	
	Load 50%	Load 100%
77	46	12
85	49	15
100	54	20
120	57	23
200	64	28
230	65	29
264	66	30
280	68	31
--	-	-

**COSEL**

Model	PBA1000F-12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation																																																					
Object	+12V88A																																																					
1.Graph	<p>—△— Input Volt. 100V        - - -□--- Input Volt. 200V        - - ○ --- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [mS]</th> <th>200V [mS]</th> <th>230V [mS]</th> </tr> </thead> <tbody> <tr><td>20</td><td>120</td><td>180</td><td>220</td></tr> <tr><td>30</td><td>40</td><td>60</td><td>80</td></tr> <tr><td>45</td><td>35</td><td>55</td><td>75</td></tr> <tr><td>60</td><td>34</td><td>54</td><td>74</td></tr> <tr><td>75</td><td>25</td><td>35</td><td>45</td></tr> <tr><td>88</td><td>20</td><td>29</td><td>30</td></tr> <tr><td>96.8</td><td>15</td><td>25</td><td>26</td></tr> </tbody> </table>			Load Current [A]	100V [mS]	200V [mS]	230V [mS]	20	120	180	220	30	40	60	80	45	35	55	75	60	34	54	74	75	25	35	45	88	20	29	30	96.8	15	25	26																			
Load Current [A]	100V [mS]	200V [mS]	230V [mS]																																																			
20	120	180	220																																																			
30	40	60	80																																																			
45	35	55	75																																																			
60	34	54	74																																																			
75	25	35	45																																																			
88	20	29	30																																																			
96.8	15	25	26																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>15.0</td><td>116</td><td>178</td><td>194</td></tr> <tr><td>30.0</td><td>35</td><td>78</td><td>87</td></tr> <tr><td>45.0</td><td>35</td><td>41</td><td>50</td></tr> <tr><td>60.0</td><td>34</td><td>37</td><td>43</td></tr> <tr><td>75.0</td><td>25</td><td>35</td><td>36</td></tr> <tr><td>88.0</td><td>20</td><td>29</td><td>30</td></tr> <tr><td>96.8</td><td>15</td><td>25</td><td>26</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	15.0	116	178	194	30.0	35	78	87	45.0	35	41	50	60.0	34	37	43	75.0	25	35	36	88.0	20	29	30	96.8	15	25	26	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Time [mS]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
15.0	116	178	194																																																			
30.0	35	78	87																																																			
45.0	35	41	50																																																			
60.0	34	37	43																																																			
75.0	25	35	36																																																			
88.0	20	29	30																																																			
96.8	15	25	26																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	PBA1000F-12
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V88A

**1. Graph**

Note: Slanted line shows the range of the rated ambient temperature.

**Testing Circuitry Figure A****2. Values**

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	69	69
-20	69	69
-10	69	69
0	69	69
10	69	69
25	69	69
30	69	69
40	69	69
50	69	69
60	69	69
-	-	-

**COSEL**

Model	PBA1000F-12
Item	Overcurrent Protection
Object	+12V88A

1. Graph

Output Voltage [V]

Load Current [A]

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A


## 2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 200[V]
12.0	122.26	122.32
11.4	122.52	122.53
10.8	122.85	122.75
9.6	123.24	123.09
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

**COSEL**

Model	PBA1000F-12
Item	Ovv Protection
Object	+12V88A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 200[V]
-30	15.55	15.44
-20	15.56	15.44
-10	15.61	15.55
0	15.61	15.55
10	15.61	15.55
25	15.61	15.62
30	15.62	15.62
40	15.62	15.61
50	15.62	15.62
60	15.62	15.62
--	-	-




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950 )