



# TEST DATA OF PBA1500F-24

Regulated DC Power Supply  
Jun.10. 2003

Approved by : Takahiro Yoneda  
Design Manager

Prepared by : Takasa Suginoto  
Design Engineer

**COSEL CO.,LTD.**



## CONTENTS

1. Input Current (by Load Current) .....	1
2. Input Power (by Load Current) .....	2
3. Efficiency (by Input Voltage) .....	3
4. Efficiency (by Load Current) .....	4
5. Power Factor (by Input Voltage) .....	5
6. Power Factor (by Load Current) .....	6
7. Inrush Current .....	7
8. Leakage Current .....	8
9. Line Regulation .....	9
10. Load Regulation .....	10
11. Dynamic Load Response .....	11
12. Ripple Voltage (by Load Current) .....	12
13. Ripple-Noise .....	13
14. Ripple Voltage (by Ambient Temperature) .....	14
15. Ambient Temperature Drift .....	15
16. Output Voltage Accuracy .....	16
17. Time Lapse Drift .....	17
18. Rise and Fall Time .....	18
19. Hold-Up Time .....	19
20. Instantaneous Interruption Compensation .....	20
21. Minimum Input Voltage for Regulated Output Voltage .....	21
22. Overcurrent Protection .....	22
23. Overvoltage Protection .....	23
24. Figure of Testing Circuitry .....	24

(Final Page 24)

**COSEL**

Model	PBA1500F-24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object	—																																																					
1. Graph	<p>—▲— Input Volt. 100V        -·□--- Input Volt. 200V        -·○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.268</td><td>0.216</td><td>0.224</td></tr> <tr><td>10</td><td>3.261</td><td>1.725</td><td>1.534</td></tr> <tr><td>20</td><td>5.940</td><td>3.058</td><td>2.706</td></tr> <tr><td>30</td><td>8.600</td><td>4.390</td><td>3.861</td></tr> <tr><td>40</td><td>11.330</td><td>5.720</td><td>5.020</td></tr> <tr><td>50</td><td>14.100</td><td>7.070</td><td>6.190</td></tr> <tr><td>60</td><td>17.000</td><td>8.430</td><td>7.380</td></tr> <tr><td>65</td><td>18.440</td><td>9.120</td><td>7.980</td></tr> <tr><td>70</td><td>19.900</td><td>9.840</td><td>8.650</td></tr> <tr><td>71.5</td><td>20.360</td><td>10.020</td><td>8.760</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0	0.268	0.216	0.224	10	3.261	1.725	1.534	20	5.940	3.058	2.706	30	8.600	4.390	3.861	40	11.330	5.720	5.020	50	14.100	7.070	6.190	60	17.000	8.430	7.380	65	18.440	9.120	7.980	70	19.900	9.840	8.650	71.5	20.360	10.020	8.760							
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																			
0	0.268	0.216	0.224																																																			
10	3.261	1.725	1.534																																																			
20	5.940	3.058	2.706																																																			
30	8.600	4.390	3.861																																																			
40	11.330	5.720	5.020																																																			
50	14.100	7.070	6.190																																																			
60	17.000	8.430	7.380																																																			
65	18.440	9.120	7.980																																																			
70	19.900	9.840	8.650																																																			
71.5	20.360	10.020	8.760																																																			
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.268</td><td>0.216</td><td>0.224</td></tr> <tr><td>10.0</td><td>3.261</td><td>1.725</td><td>1.534</td></tr> <tr><td>20.0</td><td>5.940</td><td>3.058</td><td>2.706</td></tr> <tr><td>30.0</td><td>8.600</td><td>4.390</td><td>3.861</td></tr> <tr><td>40.0</td><td>11.330</td><td>5.720</td><td>5.020</td></tr> <tr><td>50.0</td><td>14.100</td><td>7.070</td><td>6.190</td></tr> <tr><td>60.0</td><td>17.000</td><td>8.430</td><td>7.380</td></tr> <tr><td>65.0</td><td>18.440</td><td>9.120</td><td>7.980</td></tr> <tr><td>70.0</td><td>19.900</td><td>9.840</td><td>8.650</td></tr> <tr><td>71.5</td><td>20.360</td><td>10.020</td><td>8.760</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.268	0.216	0.224	10.0	3.261	1.725	1.534	20.0	5.940	3.058	2.706	30.0	8.600	4.390	3.861	40.0	11.330	5.720	5.020	50.0	14.100	7.070	6.190	60.0	17.000	8.430	7.380	65.0	18.440	9.120	7.980	70.0	19.900	9.840	8.650	71.5	20.360	10.020	8.760	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.268	0.216	0.224																																																			
10.0	3.261	1.725	1.534																																																			
20.0	5.940	3.058	2.706																																																			
30.0	8.600	4.390	3.861																																																			
40.0	11.330	5.720	5.020																																																			
50.0	14.100	7.070	6.190																																																			
60.0	17.000	8.430	7.380																																																			
65.0	18.440	9.120	7.980																																																			
70.0	19.900	9.840	8.650																																																			
71.5	20.360	10.020	8.760																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

**COSEL**


Model	PBA1500F-24	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>Input Power [W]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 200V</li> <li>Input Volt. 230V</li> </ul>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>19</td><td>17</td><td>15</td></tr> <tr><td>10.0</td><td>305</td><td>300</td><td>300</td></tr> <tr><td>20.0</td><td>573</td><td>562</td><td>561</td></tr> <tr><td>30.0</td><td>844</td><td>828</td><td>824</td></tr> <tr><td>40.0</td><td>1117</td><td>1096</td><td>1091</td></tr> <tr><td>50.0</td><td>1399</td><td>1368</td><td>1360</td></tr> <tr><td>60.0</td><td>1692</td><td>1643</td><td>1636</td></tr> <tr><td>65.0</td><td>1839</td><td>1781</td><td>1774</td></tr> <tr><td>70.0</td><td>1984</td><td>1922</td><td>1915</td></tr> <tr><td>71.5</td><td>2031</td><td>1963</td><td>1956</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	19	17	15	10.0	305	300	300	20.0	573	562	561	30.0	844	828	824	40.0	1117	1096	1091	50.0	1399	1368	1360	60.0	1692	1643	1636	65.0	1839	1781	1774	70.0	1984	1922	1915	71.5	2031	1963	1956	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	19	17	15																																																			
10.0	305	300	300																																																			
20.0	573	562	561																																																			
30.0	844	828	824																																																			
40.0	1117	1096	1091																																																			
50.0	1399	1368	1360																																																			
60.0	1692	1643	1636																																																			
65.0	1839	1781	1774																																																			
70.0	1984	1922	1915																																																			
71.5	2031	1963	1956																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

**COSEL**

Model	PBA1500F-24	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object	+24V65A																																		
<b>1. Graph</b>																																			
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line), Load 100% (solid line)</p>																																			
<b>2. Values</b>																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>85.0</td><td>83.9</td></tr> <tr> <td>100</td><td>85.5</td><td>84.9</td></tr> <tr> <td>120</td><td>86.1</td><td>85.9</td></tr> <tr> <td>200</td><td>87.1</td><td>87.6</td></tr> <tr> <td>230</td><td>87.6</td><td>88.0</td></tr> <tr> <td>264</td><td>87.7</td><td>88.3</td></tr> <tr> <td>-</td><td>-</td><td>-</td></tr> <tr> <td>-</td><td>-</td><td>-</td></tr> <tr> <td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	85.0	83.9	100	85.5	84.9	120	86.1	85.9	200	87.1	87.6	230	87.6	88.0	264	87.7	88.3	-	-	-	-	-	-	-	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
85	85.0	83.9																																	
100	85.5	84.9																																	
120	86.1	85.9																																	
200	87.1	87.6																																	
230	87.6	88.0																																	
264	87.7	88.3																																	
-	-	-																																	
-	-	-																																	
-	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

**COSEL**

Model	PBA1500F-24
Item	Efficiency (by Load Current)
Object	_____



Temperature 25°C  
Testing Circuitry Figure A

## 2. Values


Load Current [A]	Efficiency [%]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	-	-	-
10.0	78.3	79.6	79.6
20.0	83.6	85.2	85.4
30.0	85.2	86.9	87.3
40.0	85.9	87.5	87.9
50.0	85.7	87.7	88.2
60.0	85.2	87.7	88.1
65.0	84.9	87.6	88.0
70.0	84.6	87.5	87.8
71.5	84.5	87.4	87.7
-	-	-	-

Note: Slanted line shows the range of the rated load current.

**COSEL**

Model	PBA1500F-24
Item	Power Factor (by Input Voltage)
Object	+24V65A

## 1. Graph




Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
85	0.985	0.998
100	0.983	0.997
120	0.976	0.995
200	0.947	0.976
230	0.932	0.967
264	0.883	0.939
-	-	-
-	-	-
-	-	-

**COSEL**



Model	PBA1500F-24	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>—▲— Input Volt. 100V        - - - ■ - - Input Volt. 200V        - - ○ - - Input Volt. 230V</p> 																																																					
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.705</td><td>0.395</td><td>0.294</td></tr> <tr> <td>10.0</td><td>0.936</td><td>0.870</td><td>0.850</td></tr> <tr> <td>20.0</td><td>0.966</td><td>0.918</td><td>0.900</td></tr> <tr> <td>30.0</td><td>0.983</td><td>0.943</td><td>0.928</td></tr> <tr> <td>40.0</td><td>0.988</td><td>0.958</td><td>0.945</td></tr> <tr> <td>50.0</td><td>0.993</td><td>0.967</td><td>0.955</td></tr> <tr> <td>60.0</td><td>0.997</td><td>0.974</td><td>0.963</td></tr> <tr> <td>65.0</td><td>0.997</td><td>0.976</td><td>0.967</td></tr> <tr> <td>70.0</td><td>0.998</td><td>0.979</td><td>0.970</td></tr> <tr> <td>71.5</td><td>0.998</td><td>0.980</td><td>0.971</td></tr> <tr> <td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.705	0.395	0.294	10.0	0.936	0.870	0.850	20.0	0.966	0.918	0.900	30.0	0.983	0.943	0.928	40.0	0.988	0.958	0.945	50.0	0.993	0.967	0.955	60.0	0.997	0.974	0.963	65.0	0.997	0.976	0.967	70.0	0.998	0.979	0.970	71.5	0.998	0.980	0.971	-	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.705	0.395	0.294																																																			
10.0	0.936	0.870	0.850																																																			
20.0	0.966	0.918	0.900																																																			
30.0	0.983	0.943	0.928																																																			
40.0	0.988	0.958	0.945																																																			
50.0	0.993	0.967	0.955																																																			
60.0	0.997	0.974	0.963																																																			
65.0	0.997	0.976	0.967																																																			
70.0	0.998	0.979	0.970																																																			
71.5	0.998	0.980	0.971																																																			
-	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

**COSEL**

Model PBA1500F-24

Item Inrush Current

Object \_\_\_\_\_

Temperature 25°C  
Testing Circuitry Figure AInput  
Current  
[20A/div]Input Voltage 100 V  
Frequency 60 Hz  
Load 100 %Primary inrush current :  
10.1 A  
Secondary inrush current :  
19.8 AInput  
Voltage  
[100V/div]Input  
Current  
[20A/div]Input Voltage 200 V  
Frequency 60 Hz  
Load 100 %Primary inrush current :  
20.2 A  
Secondary inrush current :  
37.8 AInput  
Voltage  
[200V/div]

Primary inrush current

Secondary inrush current





Model	PBA1500F-24	Temperature 25°C Testing Circuitry Figure B
Item	Leakage Current	
Object	_____	

### 1. Results

Standards		Input Volt.			Note
		100[V]	200[V]	240[V]	
DEN-AN	Both phases	0.31	0.58	0.71	Operation
	One of phase	0.57	1.20	1.36	stand by
IEC60950	Both phases	0.34	0.67	0.81	Operation
	One of phase	0.57	1.15	1.41	stand by

The value for "One phase" is the reference value only.


### 2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

**COSEL**

Model	PBA1500F-24																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+24V65A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>24.079</td><td>24.076</td></tr> <tr> <td>100</td><td>24.078</td><td>24.076</td></tr> <tr> <td>120</td><td>24.078</td><td>24.075</td></tr> <tr> <td>200</td><td>24.078</td><td>24.075</td></tr> <tr> <td>230</td><td>24.077</td><td>24.074</td></tr> <tr> <td>264</td><td>24.077</td><td>24.073</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	24.079	24.076	100	24.078	24.076	120	24.078	24.075	200	24.078	24.075	230	24.077	24.074	264	24.077	24.073	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	24.079	24.076																																
100	24.078	24.076																																
120	24.078	24.075																																
200	24.078	24.075																																
230	24.077	24.074																																
264	24.077	24.073																																
--	-	-																																
--	-	-																																
--	-	-																																

**COSEL**

Model	PBA1500F-24	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Load Regulation																																																						
Object	+24V65A																																																						
1. Graph																																																							
<p>—▲— Input Volt. 100V      - - - □ - - Input Volt. 200V      - - ○ - - Input Volt. 230V</p> 																																																							
2. Values																																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>24.071</td> <td>24.071</td> <td>24.074</td> </tr> <tr> <td>10.0</td> <td>24.070</td> <td>24.071</td> <td>24.073</td> </tr> <tr> <td>20.0</td> <td>24.070</td> <td>24.071</td> <td>24.073</td> </tr> <tr> <td>30.0</td> <td>24.070</td> <td>24.071</td> <td>24.072</td> </tr> <tr> <td>40.0</td> <td>24.069</td> <td>24.071</td> <td>24.072</td> </tr> <tr> <td>50.0</td> <td>24.069</td> <td>24.071</td> <td>24.072</td> </tr> <tr> <td>60.0</td> <td>24.069</td> <td>24.071</td> <td>24.072</td> </tr> <tr> <td>65.0</td> <td>24.069</td> <td>24.071</td> <td>24.072</td> </tr> <tr> <td>70.0</td> <td>24.069</td> <td>24.071</td> <td>24.071</td> </tr> <tr> <td>71.5</td> <td>24.069</td> <td>24.071</td> <td>24.071</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>					Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	24.071	24.071	24.074	10.0	24.070	24.071	24.073	20.0	24.070	24.071	24.073	30.0	24.070	24.071	24.072	40.0	24.069	24.071	24.072	50.0	24.069	24.071	24.072	60.0	24.069	24.071	24.072	65.0	24.069	24.071	24.072	70.0	24.069	24.071	24.071	71.5	24.069	24.071	24.071	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.0	24.071	24.071	24.074																																																				
10.0	24.070	24.071	24.073																																																				
20.0	24.070	24.071	24.073																																																				
30.0	24.070	24.071	24.072																																																				
40.0	24.069	24.071	24.072																																																				
50.0	24.069	24.071	24.072																																																				
60.0	24.069	24.071	24.072																																																				
65.0	24.069	24.071	24.072																																																				
70.0	24.069	24.071	24.071																																																				
71.5	24.069	24.071	24.071																																																				
--	-	-	-																																																				
<p>Note: Slanted line shows the range of the rated load current.</p>																																																							

**COSEL**


**COSEL**

Model PBA1500F-24

Item Ripple Voltage (by Load Current)

Object +24V65A

## 1. Graph



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	10	10
10.0	10	10
20.0	10	10
30.0	10	10
40.0	10	10
50.0	15	15
60.0	15	15
65.0	15	15
70.0	20	20
71.5	20	20
-	-	-


T1: Due to AC Input Line  
T2: Due to Switching

Fig. Complex Ripple Wave Form

**COSEL**

Model	PBA1500F-24	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure A																																						
Object	+24V65A																																								
1. Graph			2. Values																																						
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>20</td><td>20</td></tr> <tr><td>10.0</td><td>20</td><td>20</td></tr> <tr><td>20.0</td><td>30</td><td>30</td></tr> <tr><td>30.0</td><td>30</td><td>30</td></tr> <tr><td>40.0</td><td>40</td><td>40</td></tr> <tr><td>50.0</td><td>50</td><td>50</td></tr> <tr><td>60.0</td><td>50</td><td>50</td></tr> <tr><td>65.0</td><td>50</td><td>50</td></tr> <tr><td>70.0</td><td>60</td><td>60</td></tr> <tr><td>71.5</td><td>60</td><td>60</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	20	20	10.0	20	20	20.0	30	30	30.0	30	30	40.0	40	40	50.0	50	50	60.0	50	50	65.0	50	50	70.0	60	60	71.5	60	60	-	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 100 [V]	Input Volt. 200 [V]																																							
0.0	20	20																																							
10.0	20	20																																							
20.0	30	30																																							
30.0	30	30																																							
40.0	40	40																																							
50.0	50	50																																							
60.0	50	50																																							
65.0	50	50																																							
70.0	60	60																																							
71.5	60	60																																							
-	-	-																																							
<p>Measured by MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<p>Fig. Complex Ripple Wave Form</p>																																									

**COSEL**

<p><b>Model</b> PBA1500F-24</p> <p><b>Item</b> Ripple Voltage (by Ambient Temp.)</p> <p><b>Object</b> +24V70A</p>	<b>Testing Circuitry Figure A</b>																																						
	<b>1. Graph</b>	<b>2. Values</b>																																					
	<p>--- □ --- Input Volt. 100V        —△— Input Volt. 200V</p> <table border="1"> <caption>Data points from Figure A Graph</caption> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV] (100V)</th> <th>Ripple Voltage [mV] (200V)</th> </tr> </thead> <tbody> <tr><td>-30</td><td>60</td><td>60</td></tr> <tr><td>-20</td><td>30</td><td>30</td></tr> <tr><td>-10</td><td>20</td><td>20</td></tr> <tr><td>0</td><td>15</td><td>15</td></tr> <tr><td>10</td><td>15</td><td>15</td></tr> <tr><td>20</td><td>15</td><td>15</td></tr> <tr><td>25</td><td>15</td><td>15</td></tr> <tr><td>30</td><td>15</td><td>15</td></tr> <tr><td>40</td><td>10</td><td>10</td></tr> <tr><td>50</td><td>10</td><td>10</td></tr> <tr><td>60</td><td>10</td><td>10</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV] (100V)	Ripple Voltage [mV] (200V)	-30	60	60	-20	30	30	-10	20	20	0	15	15	10	15	15	20	15	15	25	15	15	30	15	15	40	10	10	50	10	10	60	10	10		
Ambient Temperature [°C]	Ripple Voltage [mV] (100V)	Ripple Voltage [mV] (200V)																																					
-30	60	60																																					
-20	30	30																																					
-10	20	20																																					
0	15	15																																					
10	15	15																																					
20	15	15																																					
25	15	15																																					
30	15	15																																					
40	10	10																																					
50	10	10																																					
60	10	10																																					
<p>Ripple Voltage [mV]</p> <p>Ambient Temperature [°C]</p> <p>Load 100 %</p> <p>Measured by 20 MHz Oscilloscope.</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>60</td><td>60</td></tr> <tr><td>-20</td><td>30</td><td>30</td></tr> <tr><td>-10</td><td>20</td><td>20</td></tr> <tr><td>0</td><td>15</td><td>15</td></tr> <tr><td>10</td><td>15</td><td>15</td></tr> <tr><td>20</td><td>15</td><td>15</td></tr> <tr><td>25</td><td>15</td><td>15</td></tr> <tr><td>30</td><td>15</td><td>15</td></tr> <tr><td>40</td><td>10</td><td>10</td></tr> <tr><td>50</td><td>10</td><td>10</td></tr> <tr><td>60</td><td>10</td><td>10</td></tr> </tbody> </table>	Ambient Temperature [°C]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	-30	60	60	-20	30	30	-10	20	20	0	15	15	10	15	15	20	15	15	25	15	15	30	15	15	40	10	10	50	10	10	60	10	10
Ambient Temperature [°C]	Ripple Voltage [mV]																																						
	Input Volt. 100 [V]	Input Volt. 200 [V]																																					
-30	60	60																																					
-20	30	30																																					
-10	20	20																																					
0	15	15																																					
10	15	15																																					
20	15	15																																					
25	15	15																																					
30	15	15																																					
40	10	10																																					
50	10	10																																					
60	10	10																																					

**COSEL**

Model	PBA1500F-24																																																			
Item	Ambient Temperature Drift																																																			
Object	+24V65A																																																			
1.Graph	Testing Circuitry Figure A																																																			
<p>1. Graph</p> <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 100V</li> <li>Input Volt. 200V</li> <li>Input Volt. 230V</li> </ul>	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>24.154</td><td>24.153</td><td>24.152</td></tr> <tr><td>-20</td><td>24.141</td><td>24.136</td><td>24.135</td></tr> <tr><td>-10</td><td>24.131</td><td>24.126</td><td>24.125</td></tr> <tr><td>0</td><td>24.122</td><td>24.120</td><td>24.119</td></tr> <tr><td>10</td><td>24.122</td><td>24.117</td><td>24.115</td></tr> <tr><td>20</td><td>24.106</td><td>24.104</td><td>24.103</td></tr> <tr><td>25</td><td>24.101</td><td>24.099</td><td>24.098</td></tr> <tr><td>30</td><td>24.094</td><td>24.089</td><td>24.089</td></tr> <tr><td>40</td><td>24.080</td><td>24.077</td><td>24.076</td></tr> <tr><td>50</td><td>24.058</td><td>24.054</td><td>24.052</td></tr> <tr><td>60</td><td>24.021</td><td>24.015</td><td>24.012</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-30	24.154	24.153	24.152	-20	24.141	24.136	24.135	-10	24.131	24.126	24.125	0	24.122	24.120	24.119	10	24.122	24.117	24.115	20	24.106	24.104	24.103	25	24.101	24.099	24.098	30	24.094	24.089	24.089	40	24.080	24.077	24.076	50	24.058	24.054	24.052	60	24.021	24.015	24.012
Ambient Temperature [°C]	Output Voltage [V]																																																			
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																	
-30	24.154	24.153	24.152																																																	
-20	24.141	24.136	24.135																																																	
-10	24.131	24.126	24.125																																																	
0	24.122	24.120	24.119																																																	
10	24.122	24.117	24.115																																																	
20	24.106	24.104	24.103																																																	
25	24.101	24.099	24.098																																																	
30	24.094	24.089	24.089																																																	
40	24.080	24.077	24.076																																																	
50	24.058	24.054	24.052																																																	
60	24.021	24.015	24.012																																																	

Note: Slanted line shows the range of the rated ambient temperature.



Model	PBA1500F-24	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+24V65A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 65A

\* Output Voltage Accuracy =  $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


### 2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	85	65	24.136	±50	±0.2
Minimum Voltage	50	264	65	24.036		

**COSEL**

Model	PBA1500F-24
Item	Time Lapse Drift
Object	+24V70A

## 1. Graph



Input Volt. 100V  
Load 100%


\* The characteristic of AC200V is equal.

Temperature 25°C  
Testing Circuitry Figure A

## 2. Values

Time since start [H]	Output Voltage [V]
0.0	24.104
0.5	24.068
1.0	24.068
2.0	24.068
3.0	24.069
4.0	24.068
5.0	24.070
6.0	24.067
7.0	24.070
8.0	24.067

COSEL



**COSEL**


Model	PBA1500F-24	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+24V65A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>49</td> <td>18</td> </tr> <tr> <td>100</td> <td>52</td> <td>21</td> </tr> <tr> <td>120</td> <td>55</td> <td>24</td> </tr> <tr> <td>200</td> <td>61</td> <td>29</td> </tr> <tr> <td>230</td> <td>61</td> <td>29</td> </tr> <tr> <td>264</td> <td>62</td> <td>30</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	85	49	18	100	52	21	120	55	24	200	61	29	230	61	29	264	62	30	-	-	-	-	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
85	49	18																																	
100	52	21																																	
120	55	24																																	
200	61	29																																	
230	61	29																																	
264	62	30																																	
-	-	-																																	
-	-	-																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

**COSEL**

Model	PBA1500F-24	Temperature	25°C																																								
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																								
Object	+24V65A	2. Values																																									
1. Graph	<p>—△— Input Volt. 100V        - - -□- - Input Volt. 200V        - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>100[V] [ms]</th> <th>200[V] [ms]</th> <th>230[V] [ms]</th> </tr> </thead> <tbody> <tr><td>10</td><td>104</td><td>188</td><td>195</td></tr> <tr><td>20</td><td>30</td><td>80</td><td>96</td></tr> <tr><td>30</td><td>30</td><td>40</td><td>54</td></tr> <tr><td>40</td><td>30</td><td>37</td><td>40</td></tr> <tr><td>50</td><td>30</td><td>32</td><td>38</td></tr> <tr><td>60</td><td>23</td><td>31</td><td>32</td></tr> <tr><td>65</td><td>20</td><td>29</td><td>30</td></tr> <tr><td>70</td><td>19</td><td>27</td><td>27</td></tr> <tr><td>71.5</td><td>19</td><td>26</td><td>26</td></tr> </tbody> </table>			Load Current [A]	100[V] [ms]	200[V] [ms]	230[V] [ms]	10	104	188	195	20	30	80	96	30	30	40	54	40	30	37	40	50	30	32	38	60	23	31	32	65	20	29	30	70	19	27	27	71.5	19	26	26
Load Current [A]	100[V] [ms]	200[V] [ms]	230[V] [ms]																																								
10	104	188	195																																								
20	30	80	96																																								
30	30	40	54																																								
40	30	37	40																																								
50	30	32	38																																								
60	23	31	32																																								
65	20	29	30																																								
70	19	27	27																																								
71.5	19	26	26																																								
Instantaneous Compensation Time [mS]																																											
Load Current [A]																																											
Note: Slanted line shows the range of the rated load current.																																											

**COSEL**

<b>Model</b>	<b>PBA1500F-24</b>
<b>Item</b>	<b>Minimum Input Voltage for Regulated Output Voltage</b>
<b>Object</b>	<b>+24V65A</b>

**1. Graph**

Note: Slanted line shows the range of the rated ambient temperature.


**Testing Circuitry Figure A****2. Values**

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	70	71
-20	70	71
-10	70	71
0	70	71
10	70	71
20	71	71
25	71	71
30	71	71
40	71	71
50	71	71
60	71	71

**COSEL**
**Model** PBA1500F-24

**Item** Overcurrent Protection

**Object** +24V65A

**1. Graph**


Note: Slanted line shows the range of the rated load current.

**Temperature** 25°C  
**Testing Circuitry** Figure A

**2. Values**

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 200[V]
24.0	85.21	109.58
22.8	85.27	109.64
21.6	85.23	109.60
19.2	85.03	109.64
16.8	84.92	109.83
14.4	0.00	0.00
12.0	0.00	0.00
9.6	0.00	0.00
7.2	0.00	0.00
4.8	0.00	0.00
2.4	0.00	0.00
0.0	0.00	0.00

**COSEL**

Model	PBA1500F-24	Testing Circuitry Figure A																																						
Item	Ovvoltage Protection																																							
Object	+24V65A																																							
<b>1. Graph</b>																																								
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Input Volt. 100V</p> <p>Input Volt. 200V</p>																																								
<b>2. Values</b>																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>31.05</td><td>31.05</td></tr> <tr><td>-20</td><td>31.06</td><td>31.05</td></tr> <tr><td>-10</td><td>31.06</td><td>31.06</td></tr> <tr><td>0</td><td>31.05</td><td>31.05</td></tr> <tr><td>10</td><td>31.06</td><td>31.05</td></tr> <tr><td>20</td><td>31.06</td><td>31.05</td></tr> <tr><td>25</td><td>31.17</td><td>31.17</td></tr> <tr><td>30</td><td>31.17</td><td>31.17</td></tr> <tr><td>40</td><td>31.17</td><td>31.17</td></tr> <tr><td>50</td><td>31.17</td><td>31.17</td></tr> <tr><td>60</td><td>31.05</td><td>31.05</td></tr> </tbody> </table>			Ambient Temperature [°C]	Operating Point [V]		Input Volt. 100[V]	Input Volt. 200[V]	-30	31.05	31.05	-20	31.06	31.05	-10	31.06	31.06	0	31.05	31.05	10	31.06	31.05	20	31.06	31.05	25	31.17	31.17	30	31.17	31.17	40	31.17	31.17	50	31.17	31.17	60	31.05	31.05
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 100[V]	Input Volt. 200[V]																																						
-30	31.05	31.05																																						
-20	31.06	31.05																																						
-10	31.06	31.06																																						
0	31.05	31.05																																						
10	31.06	31.05																																						
20	31.06	31.05																																						
25	31.17	31.17																																						
30	31.17	31.17																																						
40	31.17	31.17																																						
50	31.17	31.17																																						
60	31.05	31.05																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								

COSEL




Figure A




Figure B ( DEN-AN )




Figure B ( IEC60950 )