



TEST DATA OF PBA1500F-7R5

Regulated DC Power Supply
May.28. 2003

Approved by : Takahiro Yoneda _____
Design Manager

Prepared by : Tsukasa Sugimoto _____
Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	PBA1500F-7R5		
Item	Input Current (by Load Current)		
Object	_____		
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p>  <p>The graph plots Input Current [A] on the Y-axis (0 to 50) against Load Current [A] on the X-axis (0 to 200). Three curves are shown: a solid line with triangles for 100V, a dashed line with squares for 200V, and a dash-dot line with circles for 230V. All curves start at (0,0) and increase monotonically. A slanted line is drawn through the origin, representing the rated load current range.</p>		
Temperature	25°C		
Testing Circuitry	Figure A		
2.Values			
Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0	0.283	0.216	0.223
40	4.010	2.100	1.864
80	7.470	3.830	3.376
120	11.020	5.590	4.900
160	14.780	7.380	6.470
200	18.620	9.240	8.080
220	20.640	10.180	8.900
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PBA1500F-7R5																																																					
Item	Input Power (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	<p>Input Volt. 100V Input Volt. 200V Input Volt. 230V</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [W]</th> <th>Input Volt. 200V [W]</th> <th>Input Volt. 230V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>20</td><td>16</td><td>14</td></tr> <tr><td>40</td><td>376</td><td>370</td><td>369</td></tr> <tr><td>80</td><td>722</td><td>712</td><td>707</td></tr> <tr><td>120</td><td>1081</td><td>1062</td><td>1056</td></tr> <tr><td>160</td><td>1461</td><td>1423</td><td>1416</td></tr> <tr><td>200</td><td>1854</td><td>1798</td><td>1789</td></tr> <tr><td>220</td><td>2055</td><td>1987</td><td>1980</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Volt. 100V [W]	Input Volt. 200V [W]	Input Volt. 230V [W]	0	20	16	14	40	376	370	369	80	722	712	707	120	1081	1062	1056	160	1461	1423	1416	200	1854	1798	1789	220	2055	1987	1980	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Input Volt. 100V [W]	Input Volt. 200V [W]	Input Volt. 230V [W]																																																			
0	20	16	14																																																			
40	376	370	369																																																			
80	722	712	707																																																			
120	1081	1062	1056																																																			
160	1461	1423	1416																																																			
200	1854	1798	1789																																																			
220	2055	1987	1980																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>20</td><td>16</td><td>14</td></tr> <tr><td>40</td><td>376</td><td>370</td><td>369</td></tr> <tr><td>80</td><td>722</td><td>712</td><td>707</td></tr> <tr><td>120</td><td>1081</td><td>1062</td><td>1056</td></tr> <tr><td>160</td><td>1461</td><td>1423</td><td>1416</td></tr> <tr><td>200</td><td>1854</td><td>1798</td><td>1789</td></tr> <tr><td>220</td><td>2055</td><td>1987</td><td>1980</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	20	16	14	40	376	370	369	80	722	712	707	120	1081	1062	1056	160	1461	1423	1416	200	1854	1798	1789	220	2055	1987	1980	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	20	16	14																																																			
40	376	370	369																																																			
80	722	712	707																																																			
120	1081	1062	1056																																																			
160	1461	1423	1416																																																			
200	1854	1798	1789																																																			
220	2055	1987	1980																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	PBA1500F-7R5																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object																																		
1. Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: ---□--- Load 50% —△— Load 100%</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>83.0</td><td>80.0</td> </tr> <tr> <td>100</td><td>83.4</td><td>81.1</td> </tr> <tr> <td>120</td><td>83.9</td><td>82.1</td> </tr> <tr> <td>200</td><td>85.1</td><td>83.6</td> </tr> <tr> <td>230</td><td>85.4</td><td>84.0</td> </tr> <tr> <td>264</td><td>85.1</td><td>84.2</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	83.0	80.0	100	83.4	81.1	120	83.9	82.1	200	85.1	83.6	230	85.4	84.0	264	85.1	84.2	--	-	-	--	-	-	--	-	-	
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
85	83.0	80.0																																
100	83.4	81.1																																
120	83.9	82.1																																
200	85.1	83.6																																
230	85.4	84.0																																
264	85.1	84.2																																
--	-	-																																
--	-	-																																
--	-	-																																


COSEL


Model	PBA1500F-7R5																																																					
Item	Efficiency (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>40</td><td>79.8</td><td>81.1</td><td>81.3</td></tr> <tr><td>80</td><td>83.2</td><td>84.4</td><td>85.0</td></tr> <tr><td>120</td><td>83.5</td><td>84.9</td><td>85.4</td></tr> <tr><td>160</td><td>82.3</td><td>84.5</td><td>84.9</td></tr> <tr><td>200</td><td>81.1</td><td>83.6</td><td>84.0</td></tr> <tr><td>220</td><td>80.4</td><td>83.2</td><td>83.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	-	-	-	40	79.8	81.1	81.3	80	83.2	84.4	85.0	120	83.5	84.9	85.4	160	82.3	84.5	84.9	200	81.1	83.6	84.0	220	80.4	83.2	83.5	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	-	-	-																																																			
40	79.8	81.1	81.3																																																			
80	83.2	84.4	85.0																																																			
120	83.5	84.9	85.4																																																			
160	82.3	84.5	84.9																																																			
200	81.1	83.6	84.0																																																			
220	80.4	83.2	83.5																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSSEL

Model	PBA1500F-7R5																																
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																															
Object	—	—																															
1.Graph																																	
<p style="text-align: center;">---□--- Load 50% —△— Load 100%</p>																																	
2.Values																																	
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>0.979</td><td>0.997</td></tr> <tr> <td>100</td><td>0.978</td><td>0.996</td></tr> <tr> <td>120</td><td>0.973</td><td>0.990</td></tr> <tr> <td>200</td><td>0.940</td><td>0.971</td></tr> <tr> <td>230</td><td>0.925</td><td>0.962</td></tr> <tr> <td>264</td><td>0.822</td><td>0.925</td></tr> <tr> <td>—</td><td>-</td><td>-</td></tr> <tr> <td>—</td><td>-</td><td>-</td></tr> <tr> <td>—</td><td>-</td><td>-</td></tr> </tbody> </table>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.979	0.997	100	0.978	0.996	120	0.973	0.990	200	0.940	0.971	230	0.925	0.962	264	0.822	0.925	—	-	-	—	-	-	—	-	-
Input Voltage [V]	Power Factor																																
	Load 50%	Load 100%																															
85	0.979	0.997																															
100	0.978	0.996																															
120	0.973	0.990																															
200	0.940	0.971																															
230	0.925	0.962																															
264	0.822	0.925																															
—	-	-																															
—	-	-																															
—	-	-																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	

COSEL

Model	PBA1500F-7R5																																																					
Item	Power Factor (by Load Current)	Temperature	25°C																																																			
Object		Testing Circuitry	Figure A																																																			
1. Graph																																																						
—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V			2. Values																																																			
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.700</td><td>0.372</td><td>0.275</td></tr> <tr><td>40</td><td>0.938</td><td>0.881</td><td>0.862</td></tr> <tr><td>80</td><td>0.969</td><td>0.930</td><td>0.910</td></tr> <tr><td>120</td><td>0.982</td><td>0.950</td><td>0.937</td></tr> <tr><td>160</td><td>0.990</td><td>0.964</td><td>0.952</td></tr> <tr><td>200</td><td>0.996</td><td>0.972</td><td>0.962</td></tr> <tr><td>220</td><td>0.997</td><td>0.976</td><td>0.967</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	0.700	0.372	0.275	40	0.938	0.881	0.862	80	0.969	0.930	0.910	120	0.982	0.950	0.937	160	0.990	0.964	0.952	200	0.996	0.972	0.962	220	0.997	0.976	0.967	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	0.700	0.372	0.275																																																			
40	0.938	0.881	0.862																																																			
80	0.969	0.930	0.910																																																			
120	0.982	0.950	0.937																																																			
160	0.990	0.964	0.952																																																			
200	0.996	0.972	0.962																																																			
220	0.997	0.976	0.967																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL



Model	PBA1500F-7R5	Temperature 25°C Testing Circuitry Figure B
Item	Leakage Current	
Object	_____	

1. Results

[mA]

Standards		Input Volt.			Note
		100[V]	200[V]	240[V]	
DEN-AN	Both phases	0.31	0.58	0.71	Operation
	One of phase	0.57	1.20	1.36	stand by
IEC60950	Both phases	0.34	0.67	0.81	Operation
	One of phase	0.57	1.15	1.41	stand by

The value for "One phase" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.


COSEL

Model	PBA1500F-7R5	Temperature Testing Circuitry 25°C Figure A																																
Item	Line Regulation																																	
Object	+7.5V200A																																	
1.Graph		2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (Dashed Line), Load 100% (Solid Line)</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>7.533</td> <td>7.531</td> </tr> <tr> <td>100</td> <td>7.533</td> <td>7.530</td> </tr> <tr> <td>120</td> <td>7.533</td> <td>7.530</td> </tr> <tr> <td>200</td> <td>7.532</td> <td>7.530</td> </tr> <tr> <td>230</td> <td>7.532</td> <td>7.529</td> </tr> <tr> <td>264</td> <td>7.532</td> <td>7.529</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	7.533	7.531	100	7.533	7.530	120	7.533	7.530	200	7.532	7.530	230	7.532	7.529	264	7.532	7.529	--	-	-	--	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	7.533	7.531																																
100	7.533	7.530																																
120	7.533	7.530																																
200	7.532	7.530																																
230	7.532	7.529																																
264	7.532	7.529																																
--	-	-																																
--	-	-																																
--	-	-																																

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PBA1500F-7R5	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+7.5V200A																																																					
1.Graph	<p>—▲— Input Volt. 100V - - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>7.529</td> <td>7.529</td> <td>7.531</td> </tr> <tr> <td>40</td> <td>7.528</td> <td>7.529</td> <td>7.530</td> </tr> <tr> <td>80</td> <td>7.528</td> <td>7.529</td> <td>7.530</td> </tr> <tr> <td>120</td> <td>7.527</td> <td>7.528</td> <td>7.529</td> </tr> <tr> <td>160</td> <td>7.526</td> <td>7.528</td> <td>7.529</td> </tr> <tr> <td>200</td> <td>7.526</td> <td>7.528</td> <td>7.528</td> </tr> <tr> <td>220</td> <td>7.526</td> <td>7.527</td> <td>7.528</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	7.529	7.529	7.531	40	7.528	7.529	7.530	80	7.528	7.529	7.530	120	7.527	7.528	7.529	160	7.526	7.528	7.529	200	7.526	7.528	7.528	220	7.526	7.527	7.528	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	7.529	7.529	7.531																																																			
40	7.528	7.529	7.530																																																			
80	7.528	7.529	7.530																																																			
120	7.527	7.528	7.529																																																			
160	7.526	7.528	7.529																																																			
200	7.526	7.528	7.528																																																			
220	7.526	7.527	7.528																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

COSEL


Model	PBA1500F-7R5	Temperature	25°C																																						
Item	Ripple Voltage (by Load Current)	Testing Circuitry	Figure A																																						
Object	+7.5V200A																																								
1. Graph																																									
<p>—△— Input Volt. 100V ---○--- Input Volt. 200V</p> <p>Ripple Voltage [mV]</p> <p>Load Current [A]</p>																																									
Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.																																									
<p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p>																																									
Fig. Complex Ripple Wave Form																																									
2. Values		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>10</td><td>10</td></tr> <tr><td>40</td><td>10</td><td>10</td></tr> <tr><td>80</td><td>20</td><td>20</td></tr> <tr><td>120</td><td>20</td><td>20</td></tr> <tr><td>160</td><td>30</td><td>30</td></tr> <tr><td>200</td><td>30</td><td>30</td></tr> <tr><td>220</td><td>35</td><td>35</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0	10	10	40	10	10	80	20	20	120	20	20	160	30	30	200	30	30	220	35	35	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Ripple Voltage [mV]																																								
	Input Volt. 100 [V]	Input Volt. 200 [V]																																							
0	10	10																																							
40	10	10																																							
80	20	20																																							
120	20	20																																							
160	30	30																																							
200	30	30																																							
220	35	35																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							
-	-	-																																							

COSEL

Model	PBA1500F-7R5
Item	Ripple-Noise
Object	+7.5V200A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0	20	20
40	30	30
80	40	40
120	50	50
160	50	50
200	60	60
220	70	70
-	-	-
-	-	-
-	-	-
-	-	-



T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form

Model	PBA1500F-7R5
Item	Ripple Voltage (by Ambient Temp.)
Object	+7.5V200A

1. Graph




Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	100	100
-20	60	60
-10	50	50
0	35	35
10	30	30
20	30	30
25	30	30
30	30	30
40	25	25
50	20	20
60	20	20

COSEL


Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-30	7.540	7.540	7.540
-20	7.542	7.543	7.543
-10	7.542	7.542	7.542
0	7.542	7.542	7.542
10	7.542	7.541	7.541
20	7.540	7.540	7.539
25	7.539	7.538	7.538
30	7.536	7.535	7.535
40	7.532	7.531	7.530
50	7.524	7.522	7.521
60	7.515	7.514	7.511



Model	PBA1500F-7R5	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+7.5V200A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 200A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$


$$\text{* Output Voltage Accuracy (Ratio) } = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-20	264	0	7.546		±18
Minimum Voltage	50	264	200	7.511		±0.2

COSEL

Model	PBA1500F-7R5	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+7.5V200A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>7.536</td></tr> <tr><td>0.5</td><td>7.520</td></tr> <tr><td>1.0</td><td>7.521</td></tr> <tr><td>2.0</td><td>7.521</td></tr> <tr><td>3.0</td><td>7.521</td></tr> <tr><td>4.0</td><td>7.521</td></tr> <tr><td>5.0</td><td>7.521</td></tr> <tr><td>6.0</td><td>7.521</td></tr> <tr><td>7.0</td><td>7.521</td></tr> <tr><td>8.0</td><td>7.521</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	7.536	0.5	7.520	1.0	7.521	2.0	7.521	3.0	7.521	4.0	7.521	5.0	7.521	6.0	7.521	7.0	7.521	8.0	7.521
Time since start [H]	Output Voltage [V]																								
0.0	7.536																								
0.5	7.520																								
1.0	7.521																								
2.0	7.521																								
3.0	7.521																								
4.0	7.521																								
5.0	7.521																								
6.0	7.521																								
7.0	7.521																								
8.0	7.521																								
<p>* The characteristic of AC200V is equal.</p>																									

COSEL

COSEL

Model	PBA1500F-7R5																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+7.5V200A																																	
1. Graph																																		
		2. Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>45</td> <td>15</td> </tr> <tr> <td>100</td> <td>48</td> <td>18</td> </tr> <tr> <td>120</td> <td>51</td> <td>20</td> </tr> <tr> <td>200</td> <td>57</td> <td>25</td> </tr> <tr> <td>230</td> <td>58</td> <td>26</td> </tr> <tr> <td>264</td> <td>59</td> <td>26</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	85	45	15	100	48	18	120	51	20	200	57	25	230	58	26	264	59	26	--	-	-	--	-	-	--	-	-	
Input Voltage [V]	Hold-Up Time [mS]																																	
	Load 50%	Load 100%																																
85	45	15																																
100	48	18																																
120	51	20																																
200	57	25																																
230	58	26																																
264	59	26																																
--	-	-																																
--	-	-																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	PBA1500F-7R5	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+7.5V200A																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [mS]</th> <th>200V [mS]</th> <th>230V [mS]</th> </tr> </thead> <tbody> <tr><td>40</td><td>47</td><td>138</td><td>151</td></tr> <tr><td>80</td><td>30</td><td>44</td><td>61</td></tr> <tr><td>120</td><td>30</td><td>37</td><td>40</td></tr> <tr><td>160</td><td>26</td><td>33</td><td>34</td></tr> <tr><td>200</td><td>18</td><td>23</td><td>26</td></tr> <tr><td>220</td><td>16</td><td>23</td><td>23</td></tr> </tbody> </table>			Load Current [A]	100V [mS]	200V [mS]	230V [mS]	40	47	138	151	80	30	44	61	120	30	37	40	160	26	33	34	200	18	23	26	220	16	23	23																							
Load Current [A]	100V [mS]	200V [mS]	230V [mS]																																																			
40	47	138	151																																																			
80	30	44	61																																																			
120	30	37	40																																																			
160	26	33	34																																																			
200	18	23	26																																																			
220	16	23	23																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [mS]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>40</td><td>47</td><td>138</td><td>151</td></tr> <tr><td>80</td><td>30</td><td>44</td><td>61</td></tr> <tr><td>120</td><td>30</td><td>37</td><td>40</td></tr> <tr><td>160</td><td>26</td><td>33</td><td>34</td></tr> <tr><td>200</td><td>18</td><td>23</td><td>26</td></tr> <tr><td>220</td><td>16</td><td>23</td><td>23</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [mS]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0	-	-	-	40	47	138	151	80	30	44	61	120	30	37	40	160	26	33	34	200	18	23	26	220	16	23	23	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [mS]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0	-	-	-																																																			
40	47	138	151																																																			
80	30	44	61																																																			
120	30	37	40																																																			
160	26	33	34																																																			
200	18	23	26																																																			
220	16	23	23																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PBA1500F-7R5	Testing Circuitry Figure A			
Item	Minimum Input Voltage for Regulated Output Voltage				
Object	+7.5V200A				
1. Graph					
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>---□--- Load 50%</p> <p>—△— Load 100%</p>					
Note: Slanted line shows the range of the rated ambient temperature.					
2. Values					
Ambient Temperature [°C]	Input Voltage [V]				
	Load 50%	Load 100%			
-30	70	71			
-20	70	71			
-10	70	71			
0	70	71			
10	70	71			
20	70	71			
25	70	71			
30	70	71			
40	70	71			
50	70	71			
60	70	71			


COSEL

Model PBA1500F-7R5

Item Overcurrent Protection

Object +7.5V200A

1. Graph



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 200[V]
7.50	247.74	247.86
7.13	253.22	255.04
6.75	254.57	256.23
6.00	256.85	256.61
5.25	0.00	0.00
4.50	0.00	0.00
3.75	0.00	0.00
3.00	0.00	0.00
2.25	0.00	0.00
1.50	0.00	0.00
0.75	0.00	0.00
0.00	0.00	0.00

COSEL

Model	PBA1500F-7R5	Testing Circuitry Figure A																																							
Item	Overvoltage Protection																																								
Object	+7.5V200A	2.Values																																							
1.Graph																																									
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Input Volt. 100V Input Volt. 200V</p>																																									
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr> <td>-30</td> <td>9.64</td> <td>9.64</td> </tr> <tr> <td>-20</td> <td>9.64</td> <td>9.64</td> </tr> <tr> <td>-10</td> <td>9.64</td> <td>9.64</td> </tr> <tr> <td>0</td> <td>9.64</td> <td>9.64</td> </tr> <tr> <td>10</td> <td>9.64</td> <td>9.64</td> </tr> <tr> <td>20</td> <td>9.64</td> <td>9.64</td> </tr> <tr> <td>25</td> <td>9.64</td> <td>9.64</td> </tr> <tr> <td>30</td> <td>9.64</td> <td>9.64</td> </tr> <tr> <td>40</td> <td>9.63</td> <td>9.64</td> </tr> <tr> <td>50</td> <td>9.63</td> <td>9.63</td> </tr> <tr> <td>60</td> <td>9.63</td> <td>9.63</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Operating Point [V]		Input Volt. 100[V]	Input Volt. 200[V]	-30	9.64	9.64	-20	9.64	9.64	-10	9.64	9.64	0	9.64	9.64	10	9.64	9.64	20	9.64	9.64	25	9.64	9.64	30	9.64	9.64	40	9.63	9.64	50	9.63	9.63	60	9.63	9.63
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 100[V]	Input Volt. 200[V]																																							
-30	9.64	9.64																																							
-20	9.64	9.64																																							
-10	9.64	9.64																																							
0	9.64	9.64																																							
10	9.64	9.64																																							
20	9.64	9.64																																							
25	9.64	9.64																																							
30	9.64	9.64																																							
40	9.63	9.64																																							
50	9.63	9.63																																							
60	9.63	9.63																																							

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)