



TEST DATA OF PBA50F-48

Regulated DC Power Supply
Apr.7. 2004

Approved by : Kuniaki Nagahara
Kuniaki Nagahara Design Manager

Prepared by : Koji Todo
Koji Todo Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	PBA50F-48																																																			
Item	Input Current (by Load Current)																																																			
Object	<p>1.Graph</p> <p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>100[V]</th> <th>200[V]</th> <th>230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.052</td><td>0.048</td><td>0.050</td></tr> <tr><td>0.20</td><td>0.153</td><td>0.114</td><td>0.109</td></tr> <tr><td>0.40</td><td>0.264</td><td>0.162</td><td>0.155</td></tr> <tr><td>0.60</td><td>0.369</td><td>0.210</td><td>0.194</td></tr> <tr><td>0.80</td><td>0.475</td><td>0.259</td><td>0.237</td></tr> <tr><td>1.00</td><td>0.583</td><td>0.307</td><td>0.280</td></tr> <tr><td>1.10</td><td>0.637</td><td>0.332</td><td>0.302</td></tr> <tr><td>1.21</td><td>0.698</td><td>0.360</td><td>0.326</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			100[V]	200[V]	230[V]	0.00	0.052	0.048	0.050	0.20	0.153	0.114	0.109	0.40	0.264	0.162	0.155	0.60	0.369	0.210	0.194	0.80	0.475	0.259	0.237	1.00	0.583	0.307	0.280	1.10	0.637	0.332	0.302	1.21	0.698	0.360	0.326	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																			
	100[V]	200[V]	230[V]																																																	
0.00	0.052	0.048	0.050																																																	
0.20	0.153	0.114	0.109																																																	
0.40	0.264	0.162	0.155																																																	
0.60	0.369	0.210	0.194																																																	
0.80	0.475	0.259	0.237																																																	
1.00	0.583	0.307	0.280																																																	
1.10	0.637	0.332	0.302																																																	
1.21	0.698	0.360	0.326																																																	
--	-	-	-																																																	
--	-	-	-																																																	
--	-	-	-																																																	

Note: Slanted line shows the range of the rated load current.


 Temperature 25°C
 Testing Circuitry Figure A

Load Current [A]	Input Current [A]		
	100[V]	200[V]	230[V]
0.00	0.052	0.048	0.050
0.20	0.153	0.114	0.109
0.40	0.264	0.162	0.155
0.60	0.369	0.210	0.194
0.80	0.475	0.259	0.237
1.00	0.583	0.307	0.280
1.10	0.637	0.332	0.302
1.21	0.698	0.360	0.326
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	PBA50F-48	Temperature Testing Circuitry	25°C Figure A																																																		
Item	Input Power (by Load Current)																																																				
Object	<hr/>																																																				
1.Graph	<p>—▲— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (200V)</th> <th>Input Power [W] (230V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3.60</td><td>4.00</td><td>4.00</td></tr> <tr><td>0.20</td><td>14.39</td><td>15.00</td><td>15.00</td></tr> <tr><td>0.40</td><td>25.85</td><td>26.00</td><td>26.00</td></tr> <tr><td>0.60</td><td>36.47</td><td>36.00</td><td>36.00</td></tr> <tr><td>0.80</td><td>47.25</td><td>46.00</td><td>46.00</td></tr> <tr><td>1.00</td><td>58.13</td><td>56.80</td><td>57.00</td></tr> <tr><td>1.10</td><td>63.63</td><td>62.00</td><td>62.00</td></tr> <tr><td>1.21</td><td>69.72</td><td>67.80</td><td>68.00</td></tr> </tbody> </table>		Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)	0.00	3.60	4.00	4.00	0.20	14.39	15.00	15.00	0.40	25.85	26.00	26.00	0.60	36.47	36.00	36.00	0.80	47.25	46.00	46.00	1.00	58.13	56.80	57.00	1.10	63.63	62.00	62.00	1.21	69.72	67.80	68.00															
Load Current [A]	Input Power [W] (100V)	Input Power [W] (200V)	Input Power [W] (230V)																																																		
0.00	3.60	4.00	4.00																																																		
0.20	14.39	15.00	15.00																																																		
0.40	25.85	26.00	26.00																																																		
0.60	36.47	36.00	36.00																																																		
0.80	47.25	46.00	46.00																																																		
1.00	58.13	56.80	57.00																																																		
1.10	63.63	62.00	62.00																																																		
1.21	69.72	67.80	68.00																																																		
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>3.60</td><td>4.00</td><td>4.00</td></tr> <tr><td>0.20</td><td>14.39</td><td>15.00</td><td>15.00</td></tr> <tr><td>0.40</td><td>25.85</td><td>26.00</td><td>26.00</td></tr> <tr><td>0.60</td><td>36.47</td><td>36.00</td><td>36.00</td></tr> <tr><td>0.80</td><td>47.25</td><td>46.00</td><td>46.00</td></tr> <tr><td>1.00</td><td>58.13</td><td>56.80</td><td>57.00</td></tr> <tr><td>1.10</td><td>63.63</td><td>62.00</td><td>62.00</td></tr> <tr><td>1.21</td><td>69.72</td><td>67.80</td><td>68.00</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	3.60	4.00	4.00	0.20	14.39	15.00	15.00	0.40	25.85	26.00	26.00	0.60	36.47	36.00	36.00	0.80	47.25	46.00	46.00	1.00	58.13	56.80	57.00	1.10	63.63	62.00	62.00	1.21	69.72	67.80	68.00	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.00	3.60	4.00	4.00																																																		
0.20	14.39	15.00	15.00																																																		
0.40	25.85	26.00	26.00																																																		
0.60	36.47	36.00	36.00																																																		
0.80	47.25	46.00	46.00																																																		
1.00	58.13	56.80	57.00																																																		
1.10	63.63	62.00	62.00																																																		
1.21	69.72	67.80	68.00																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.

COSEL

Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	76.5	80.6
85	77.4	82.0
100	77.4	83.1
120	77.4	84.0
200	77.4	85.2
230	77.4	85.2
264	77.4	85.2
280	77.4	85.2
-	-	-

COSEL

Model	PBA50F-48
Item	Efficiency (by Load Current)
Object	_____

1. Graph

—△— Input Volt. 100V
 - -□--- Input Volt. 200V
 - -○--- Input Volt. 230V

Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
0.20	65.5	62.9	62.8
0.40	73.8	73.3	73.4
0.60	78.7	79.8	79.7
0.80	81.2	83.4	83.4
1.00	82.6	84.5	84.2
1.10	83.0	85.2	85.2
1.21	83.4	85.7	85.5
-	-	-	-
-	-	-	-
-	-	-	-

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
0.20	65.5	62.9	62.8
0.40	73.8	73.3	73.4
0.60	78.7	79.8	79.7
0.80	81.2	83.4	83.4
1.00	82.6	84.5	84.2
1.10	83.0	85.2	85.2
1.21	83.4	85.7	85.5
-	-	-	-
-	-	-	-
-	-	-	-

COSEL

Model	PBA50F-48	Temperature Testing Circuitry	25°C Figure A																																
Item	Power Factor (by Input Voltage)																																		
Object	_____																																		
1. Graph			2. Values																																
<p>Graph showing Power Factor vs Input Voltage for PBA50F-48 at 25°C. The Y-axis is Power Factor (0.4 to 1.0) and the X-axis is Input Voltage [V] (50 to 300). Two curves are shown: Load 50% (dashed line with open squares) and Load 100% (solid line with solid triangles). Both curves start at 1.0 at 50V and decrease as input voltage increases. A slanted line indicates the rated input voltage range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>0.995</td> <td>0.990</td> </tr> <tr> <td>85</td> <td>0.989</td> <td>0.991</td> </tr> <tr> <td>100</td> <td>0.981</td> <td>0.993</td> </tr> <tr> <td>120</td> <td>0.971</td> <td>0.988</td> </tr> <tr> <td>200</td> <td>0.850</td> <td>0.932</td> </tr> <tr> <td>230</td> <td>0.791</td> <td>0.886</td> </tr> <tr> <td>264</td> <td>0.723</td> <td>0.849</td> </tr> <tr> <td>280</td> <td>0.642</td> <td>0.765</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.995	0.990	85	0.989	0.991	100	0.981	0.993	120	0.971	0.988	200	0.850	0.932	230	0.791	0.886	264	0.723	0.849	280	0.642	0.765	--	-	-
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
75	0.995	0.990																																	
85	0.989	0.991																																	
100	0.981	0.993																																	
120	0.971	0.988																																	
200	0.850	0.932																																	
230	0.791	0.886																																	
264	0.723	0.849																																	
280	0.642	0.765																																	
--	-	-																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model PBA50F-48

Item Power Factor (by Load Current)

Object _____

1. Graph

—△— Input Volt. 100V
 - - -□- - Input Volt. 200V
 - - ○ - - Input Volt. 230V



Note: Slanted line shows the range of the rated load current.




 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Power Factor		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	0.695	0.400	0.364
0.20	0.938	0.652	0.600
0.40	0.973	0.788	0.750
0.60	0.984	0.857	0.800
0.80	0.989	0.906	0.857
1.00	0.992	0.921	0.877
1.10	0.993	0.930	0.886
1.21	0.993	0.936	0.895
-	-	-	-
-	-	-	-
-	-	-	-

COSEL

Model	PBA50F-48	Temperature Testing Circuitry 25°C Figure A
Item	Inrush Current	
Object	_____	





Model	PBA50F-48	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	230 [V]	
DEN-AN	Both phases	0.18	0.30	0.34	Operation
	One of phase	0.22	0.48	0.55	stand by
IEC60950	Both phases	0.18	0.32	0.36	Operation
	One of phase	0.22	0.48	0.55	stand by

The value for "One phase" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.


COSEL

Model	PBA50F-48	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+48V1.1A																																		
1.Graph			2.Values																																
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line), Load 100% (solid line)</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>48.062</td><td>48.063</td></tr> <tr><td>85</td><td>48.062</td><td>48.063</td></tr> <tr><td>100</td><td>48.063</td><td>48.063</td></tr> <tr><td>120</td><td>48.063</td><td>48.063</td></tr> <tr><td>200</td><td>48.064</td><td>48.063</td></tr> <tr><td>230</td><td>48.064</td><td>48.063</td></tr> <tr><td>264</td><td>48.064</td><td>48.062</td></tr> <tr><td>280</td><td>48.064</td><td>48.062</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	48.062	48.063	85	48.062	48.063	100	48.063	48.063	120	48.063	48.063	200	48.064	48.063	230	48.064	48.063	264	48.064	48.062	280	48.064	48.062	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	48.062	48.063																																	
85	48.062	48.063																																	
100	48.063	48.063																																	
120	48.063	48.063																																	
200	48.064	48.063																																	
230	48.064	48.063																																	
264	48.064	48.062																																	
280	48.064	48.062																																	
--	-	-																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PBA50F-48	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+48V1.1A																																																					
1.Graph	<p>—▲— Input Volt. 100V - - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>48.074</td><td>48.074</td><td>48.073</td></tr> <tr><td>0.20</td><td>48.072</td><td>48.071</td><td>48.070</td></tr> <tr><td>0.40</td><td>48.070</td><td>48.070</td><td>48.069</td></tr> <tr><td>0.60</td><td>48.070</td><td>48.070</td><td>48.068</td></tr> <tr><td>0.80</td><td>48.069</td><td>48.069</td><td>48.068</td></tr> <tr><td>1.00</td><td>48.069</td><td>48.069</td><td>48.067</td></tr> <tr><td>1.10</td><td>48.069</td><td>48.068</td><td>48.067</td></tr> <tr><td>1.21</td><td>48.068</td><td>48.068</td><td>48.067</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	48.074	48.074	48.073	0.20	48.072	48.071	48.070	0.40	48.070	48.070	48.069	0.60	48.070	48.070	48.068	0.80	48.069	48.069	48.068	1.00	48.069	48.069	48.067	1.10	48.069	48.068	48.067	1.21	48.068	48.068	48.067	-	-	-	-	-	-	-	-	-	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	48.074	48.074	48.073																																																			
0.20	48.072	48.071	48.070																																																			
0.40	48.070	48.070	48.069																																																			
0.60	48.070	48.070	48.068																																																			
0.80	48.069	48.069	48.068																																																			
1.00	48.069	48.069	48.067																																																			
1.10	48.069	48.068	48.067																																																			
1.21	48.068	48.068	48.067																																																			
-	-	-	-																																																			
-	-	-	-																																																			
-	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

COSEL

Model	PBA50F-48	Temperature Testing Circuitry 25°C Figure A																																			
Item	Ripple Voltage (by Load Current)																																				
Object	+48V1.1A																																				
1. Graph		2. Values																																			
<p>Graph showing Ripple Voltage [mV] vs Load Current [A].</p> <p>Legend:</p> <ul style="list-style-type: none"> —▲— Input Volt. 100V -○- Input Volt. 200V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>10</td><td>10</td></tr> <tr><td>0.20</td><td>45</td><td>45</td></tr> <tr><td>0.40</td><td>50</td><td>50</td></tr> <tr><td>0.60</td><td>50</td><td>50</td></tr> <tr><td>0.80</td><td>50</td><td>50</td></tr> <tr><td>1.00</td><td>50</td><td>50</td></tr> <tr><td>1.10</td><td>50</td><td>50</td></tr> <tr><td>1.21</td><td>50</td><td>50</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	0.00	10	10	0.20	45	45	0.40	50	50	0.60	50	50	0.80	50	50	1.00	50	50	1.10	50	50	1.21	50	50	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																			
0.00	10	10																																			
0.20	45	45																																			
0.40	50	50																																			
0.60	50	50																																			
0.80	50	50																																			
1.00	50	50																																			
1.10	50	50																																			
1.21	50	50																																			
--	-	-																																			
--	-	-																																			
--	-	-																																			
<p>Measured by 20 MHz Oscilloscope.</p> <p>Ripple Voltage is shown as p-p in the figure below.</p> <p>Note: Slanted line shows the range of the rated load current.</p>																																					
<p>T1: Due to AC Input Line</p> <p>T2: Due to Switching</p> <p>Ripple [mVp-p]</p> <p>T1</p> <p>T2</p>																																					
<p>Fig. Complex Ripple Wave Form</p>																																					


COSEL

Model	PBA50F-48	Temperature Testing Circuitry	25°C Figure A																																			
Item	Ripple-Noise																																					
Object	+48V1.1A																																					
1. Graph			2. Values																																			
<table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 100V)</th> <th>Ripple-Noise [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>20</td><td>20</td></tr> <tr><td>0.20</td><td>55</td><td>55</td></tr> <tr><td>0.40</td><td>65</td><td>65</td></tr> <tr><td>0.60</td><td>65</td><td>65</td></tr> <tr><td>0.80</td><td>65</td><td>65</td></tr> <tr><td>1.00</td><td>65</td><td>65</td></tr> <tr><td>1.10</td><td>65</td><td>65</td></tr> <tr><td>1.21</td><td>65</td><td>65</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> <tr><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple-Noise [mV] (Input Volt. 100V)	Ripple-Noise [mV] (Input Volt. 200V)	0.00	20	20	0.20	55	55	0.40	65	65	0.60	65	65	0.80	65	65	1.00	65	65	1.10	65	65	1.21	65	65	-	-	-	-	-	-	-	-	-		
Load Current [A]	Ripple-Noise [mV] (Input Volt. 100V)	Ripple-Noise [mV] (Input Volt. 200V)																																				
0.00	20	20																																				
0.20	55	55																																				
0.40	65	65																																				
0.60	65	65																																				
0.80	65	65																																				
1.00	65	65																																				
1.10	65	65																																				
1.21	65	65																																				
-	-	-																																				
-	-	-																																				
-	-	-																																				
<p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																						
<p>Fig. Complex Ripple Wave Form</p>																																						

COSSEL

Model	PBA50F-48
Item	Ripple Voltage (by Ambient Temp.)
Object	+48V1.1A

1. Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	320	320
-10	140	140
0	100	100
25	50	50
50	40	40
-	-	-
-	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	PBA50F-48	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+48V1.1A																																																						
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <ul style="list-style-type: none"> —○— Input Volt. 100V -□- Input Volt. 200V -△- Input Volt. 230V 																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>48.034</td><td>48.035</td><td>48.035</td></tr> <tr><td>-10</td><td>48.040</td><td>48.040</td><td>48.040</td></tr> <tr><td>0</td><td>48.048</td><td>48.048</td><td>48.048</td></tr> <tr><td>10</td><td>48.062</td><td>48.062</td><td>48.062</td></tr> <tr><td>25</td><td>48.080</td><td>48.080</td><td>48.080</td></tr> <tr><td>30</td><td>48.082</td><td>48.082</td><td>48.082</td></tr> <tr><td>40</td><td>48.080</td><td>48.080</td><td>48.079</td></tr> <tr><td>50</td><td>48.070</td><td>48.070</td><td>48.069</td></tr> <tr><td>60</td><td>48.055</td><td>48.055</td><td>48.054</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>—</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	48.034	48.035	48.035	-10	48.040	48.040	48.040	0	48.048	48.048	48.048	10	48.062	48.062	48.062	25	48.080	48.080	48.080	30	48.082	48.082	48.082	40	48.080	48.080	48.079	50	48.070	48.070	48.069	60	48.055	48.055	48.054	—	-	-	-	—	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
-20	48.034	48.035	48.035																																																				
-10	48.040	48.040	48.040																																																				
0	48.048	48.048	48.048																																																				
10	48.062	48.062	48.062																																																				
25	48.080	48.080	48.080																																																				
30	48.082	48.082	48.082																																																				
40	48.080	48.080	48.079																																																				
50	48.070	48.070	48.069																																																				
60	48.055	48.055	48.054																																																				
—	-	-	-																																																				
—	-	-	-																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						



Model	PBA50F-48	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+48V1.1A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 1.1A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	30	85	0	48.088	±24	±0.1
Minimum Voltage	-10	85	1.1	48.040		

COSSEL

Model	PBA50F-48
Item	Time Lapse Drift
Object	+48V1.1A

1. Graph



Input Volt. 100V


Load 100%

* The characteristic of AC200V is equal.

Temperature 25°C
 Testing Circuitry Figure A

2. Values

Time since start [H]	Output Voltage [V]
0.0	48.070
0.5	48.063
1.0	48.064
2.0	48.064
3.0	48.065
4.0	48.065
5.0	48.065
6.0	48.065
7.0	48.066
8.0	48.066

COSEL

COSEL


Model	PBA50F-48	Temperature Testing Circuitry 25°C Figure A																																
Item	Hold-Up Time																																	
Object	+48V1.1A																																	
1.Graph		2.Values																																
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>39</td><td>15</td></tr> <tr><td>85</td><td>42</td><td>18</td></tr> <tr><td>100</td><td>45</td><td>20</td></tr> <tr><td>120</td><td>47</td><td>22</td></tr> <tr><td>200</td><td>51</td><td>26</td></tr> <tr><td>230</td><td>52</td><td>26</td></tr> <tr><td>264</td><td>53</td><td>27</td></tr> <tr><td>280</td><td>53</td><td>27</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	39	15	85	42	18	100	45	20	120	47	22	200	51	26	230	52	26	264	53	27	280	53	27	--	-	-
Input Voltage [V]	Hold-Up Time [mS]																																	
	Load 50%	Load 100%																																
75	39	15																																
85	42	18																																
100	45	20																																
120	47	22																																
200	51	26																																
230	52	26																																
264	53	27																																
280	53	27																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model PBA50F-48

Item Instantaneous Interruption Compensation

Object +48V1.1A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Load Current [A]	Time [mS]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	-	-	-
0.20	108	134	136
0.40	62	74	72
0.60	40	46	47
0.80	29	37	38
1.00	21	27	29
1.10	20	26	26
1.21	17	22	22
-	-	-	-
-	-	-	-
-	-	-	-

COSEL

Model	PBA50F-48
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+48V1.1A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	50	66
-10	50	66
0	49	65
10	49	65
25	49	65
30	49	65
40	49	65
50	49	65
60	49	66
—	—	—
—	—	—


COSEL

Model PBA50F-48

Item Overcurrent Protection

Object +48V1.1A

1. Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 28.8V to 0V.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 200[V]
48.0	1.16	1.16
45.6	1.44	1.44
43.2	1.45	1.45
38.4	1.48	1.48
33.6	1.52	1.52
28.8	1.53	1.53
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-



		Testing Circuitry Figure A																																							
Model	PBA50F-48																																								
Item	Overvoltage Protection																																								
Object	+48V1.1A																																								
1. Graph		2. Values																																							
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>59.68</td> <td>59.68</td> </tr> <tr> <td>-10</td> <td>60.17</td> <td>60.17</td> </tr> <tr> <td>0</td> <td>60.72</td> <td>60.72</td> </tr> <tr> <td>10</td> <td>61.28</td> <td>61.28</td> </tr> <tr> <td>25</td> <td>62.06</td> <td>62.06</td> </tr> <tr> <td>30</td> <td>62.34</td> <td>62.34</td> </tr> <tr> <td>40</td> <td>62.90</td> <td>62.90</td> </tr> <tr> <td>50</td> <td>63.46</td> <td>63.46</td> </tr> <tr> <td>60</td> <td>63.95</td> <td>63.95</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Ambient Temperature [°C]	Operating Point [V]		Input Volt. 100[V]	Input Volt. 200[V]	-20	59.68	59.68	-10	60.17	60.17	0	60.72	60.72	10	61.28	61.28	25	62.06	62.06	30	62.34	62.34	40	62.90	62.90	50	63.46	63.46	60	63.95	63.95	-	-	-	-	-	-
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 100[V]	Input Volt. 200[V]																																							
-20	59.68	59.68																																							
-10	60.17	60.17																																							
0	60.72	60.72																																							
10	61.28	61.28																																							
25	62.06	62.06																																							
30	62.34	62.34																																							
40	62.90	62.90																																							
50	63.46	63.46																																							
60	63.95	63.95																																							
-	-	-																																							
-	-	-																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																									

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950)