

TEST DATA OF PCA1000F-15

Regulated DC Power Supply
February 20, 2019

Approved by : Koji Todo
Koji Todo Design Manager

Prepared by : Terumasa Araki
Terumasa Araki Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)

COSEL

Model	PCA1000F-15	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Current (by Load Current)																																																					
Object																																																						
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 200V - · ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.236</td><td>0.212</td><td>0.225</td></tr> <tr><td>10.0</td><td>1.802</td><td>0.982</td><td>0.887</td></tr> <tr><td>20.0</td><td>3.422</td><td>1.765</td><td>1.567</td></tr> <tr><td>30.0</td><td>5.060</td><td>2.552</td><td>2.260</td></tr> <tr><td>40.0</td><td>6.710</td><td>3.358</td><td>3.081</td></tr> <tr><td>50.0</td><td>8.390</td><td>4.180</td><td>3.790</td></tr> <tr><td>60.0</td><td>10.110</td><td>5.070</td><td>4.490</td></tr> <tr><td>70.0</td><td>11.860</td><td>5.890</td><td>5.190</td></tr> <tr><td>77.0</td><td>13.090</td><td>6.470</td><td>5.690</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0.0	0.236	0.212	0.225	10.0	1.802	0.982	0.887	20.0	3.422	1.765	1.567	30.0	5.060	2.552	2.260	40.0	6.710	3.358	3.081	50.0	8.390	4.180	3.790	60.0	10.110	5.070	4.490	70.0	11.860	5.890	5.190	77.0	13.090	6.470	5.690	--	-	-	-	--	-	-	-	2.Values				
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																			
0.0	0.236	0.212	0.225																																																			
10.0	1.802	0.982	0.887																																																			
20.0	3.422	1.765	1.567																																																			
30.0	5.060	2.552	2.260																																																			
40.0	6.710	3.358	3.081																																																			
50.0	8.390	4.180	3.790																																																			
60.0	10.110	5.070	4.490																																																			
70.0	11.860	5.890	5.190																																																			
77.0	13.090	6.470	5.690																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.236</td><td>0.212</td><td>0.225</td></tr> <tr><td>10.0</td><td>1.802</td><td>0.982</td><td>0.887</td></tr> <tr><td>20.0</td><td>3.422</td><td>1.765</td><td>1.567</td></tr> <tr><td>30.0</td><td>5.060</td><td>2.552</td><td>2.260</td></tr> <tr><td>40.0</td><td>6.710</td><td>3.358</td><td>3.081</td></tr> <tr><td>50.0</td><td>8.390</td><td>4.180</td><td>3.790</td></tr> <tr><td>60.0</td><td>10.110</td><td>5.070</td><td>4.490</td></tr> <tr><td>70.0</td><td>11.860</td><td>5.890</td><td>5.190</td></tr> <tr><td>77.0</td><td>13.090</td><td>6.470</td><td>5.690</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.236	0.212	0.225	10.0	1.802	0.982	0.887	20.0	3.422	1.765	1.567	30.0	5.060	2.552	2.260	40.0	6.710	3.358	3.081	50.0	8.390	4.180	3.790	60.0	10.110	5.070	4.490	70.0	11.860	5.890	5.190	77.0	13.090	6.470	5.690	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.236	0.212	0.225																																																			
10.0	1.802	0.982	0.887																																																			
20.0	3.422	1.765	1.567																																																			
30.0	5.060	2.552	2.260																																																			
40.0	6.710	3.358	3.081																																																			
50.0	8.390	4.180	3.790																																																			
60.0	10.110	5.070	4.490																																																			
70.0	11.860	5.890	5.190																																																			
77.0	13.090	6.470	5.690																																																			
--	-	-	-																																																			
--	-	-	-																																																			


Note: Slanted line shows the range of the rated load current.

COSEL

Model	PCA1000F-15	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object																																																						
1.Graph	<p>—△— Input Volt. 100V - - □ - - Input Volt. 200V - · ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>10</td><td>88</td><td>85</td><td>85</td></tr> <tr><td>20</td><td>92</td><td>90</td><td>88</td></tr> <tr><td>30</td><td>92</td><td>91</td><td>89</td></tr> <tr><td>40</td><td>92</td><td>91</td><td>89</td></tr> <tr><td>50</td><td>91</td><td>91</td><td>88</td></tr> <tr><td>60</td><td>91</td><td>91</td><td>88</td></tr> <tr><td>70</td><td>91</td><td>91</td><td>88</td></tr> <tr><td>77</td><td>90</td><td>90</td><td>88</td></tr> </tbody> </table>			Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	10	88	85	85	20	92	90	88	30	92	91	89	40	92	91	89	50	91	91	88	60	91	91	88	70	91	91	88	77	90	90	88															
Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																																																			
10	88	85	85																																																			
20	92	90	88																																																			
30	92	91	89																																																			
40	92	91	89																																																			
50	91	91	88																																																			
60	91	91	88																																																			
70	91	91	88																																																			
77	90	90	88																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>10.0</td><td>87.1</td><td>87.9</td><td>86.9</td></tr> <tr><td>20.0</td><td>90.4</td><td>91.8</td><td>91.8</td></tr> <tr><td>30.0</td><td>91.3</td><td>92.8</td><td>92.8</td></tr> <tr><td>40.0</td><td>91.7</td><td>93.3</td><td>92.7</td></tr> <tr><td>50.0</td><td>91.6</td><td>93.3</td><td>93.0</td></tr> <tr><td>60.0</td><td>91.2</td><td>93.0</td><td>93.0</td></tr> <tr><td>70.0</td><td>90.8</td><td>92.9</td><td>93.0</td></tr> <tr><td>77.0</td><td>90.4</td><td>92.7</td><td>92.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	10.0	87.1	87.9	86.9	20.0	90.4	91.8	91.8	30.0	91.3	92.8	92.8	40.0	91.7	93.3	92.7	50.0	91.6	93.3	93.0	60.0	91.2	93.0	93.0	70.0	90.8	92.9	93.0	77.0	90.4	92.7	92.9	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
10.0	87.1	87.9	86.9																																																			
20.0	90.4	91.8	91.8																																																			
30.0	91.3	92.8	92.8																																																			
40.0	91.7	93.3	92.7																																																			
50.0	91.6	93.3	93.0																																																			
60.0	91.2	93.0	93.0																																																			
70.0	90.8	92.9	93.0																																																			
77.0	90.4	92.7	92.9																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PCA1000F-15
Item	Power Factor (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A




2. Values

Load Current [A]	Power Factor		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	0.694	0.286	0.250
10.0	0.981	0.889	0.867
20.0	0.992	0.945	0.928
30.0	0.996	0.971	0.952
40.0	0.997	0.978	0.934
50.0	0.998	0.982	0.946
60.0	0.998	0.976	0.956
70.0	0.998	0.981	0.966
77.0	0.998	0.984	0.971
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PCA1000F-15	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	PCA1000F-15	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure B-1	Both phases	0.11	0.29	0.31	Operation
		One of phases	0.22	0.56	0.59	Stand by
IEC62368-1	Figure B-2	Both phases	0.10	0.28	0.30	Operation
		One of phases	0.22	0.56	0.60	Stand by
IEC60601-1	Figure B-3	Both phases	0.11	0.29	0.31	Operation
		One of phases	0.22	0.57	0.61	Stand by
IEC60601-1	Figure B-4	Both phases	0.11	0.28	0.29	Operation
		One of phases	0.22	0.55	0.57	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PCA1000F-15
Item	Line Regulation
Object	+15V70A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph





2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
80	15.321	-
85	15.322	-
100	15.324	15.315
120	15.324	15.315
200	15.322	15.315
230	15.323	15.315
264	15.324	15.314
280	15.325	15.316
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL



Model	PCA1000F-15	Temperature	25°C
Item	Load Regulation	Testing Circuitry	Figure A
Object	+15V70A		
1.Graph	<p>—△— Input Volt. 100V - - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>		
	<p>Note: Slanted line shows the range of the rated load current.</p>		
Item	Ripple-Noise	Temperature	25°C
Object	+15V70A	Testing Circuitry	Figure C
1.Graph	<p>Input Voltage 200V Load 100%</p>  <p>20[mV/div]</p> <p>4[μs/div]</p>		
		- 7 -	BC-11337

COSEL



Model	PCA1000F-15	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V70A		

Input Volt. 100 V

Cycle 1000 ms



Response. $t_1=t_2=50\mu s$. Typ

Load 0%(0A) \longleftrightarrow
Load 100%(70A)



1[V/div] 2[ms/div] 20[ms/div]

Load 0%(0A) \longleftrightarrow
Load 50%(35A)




1[V/div] 2[ms/div] 20[ms/div]

COSEL

Model	PCA1000F-15	Temperature Testing Circuitry	25°C
Item	Rise and Fall Time		Figure A
Object	+15V70A		


1.Graph



2.Values

[ms]


Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		711.0	9.0	720.0	16.9	8.7
230 V		708.0	9.0	717.0	21.5	8.9





Model	PCA1000F-15
Item	Hold-Up Time
Object	+15V70A

1. Graph



This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
80	31	-
85	31	-
100	31	15
120	31	15
200	40	20
230	40	20
264	40	20
280	42	20
--	-	-

COSEL

Model	PCA1000F-15
Item	Instantaneous Interruption Compensation
Object	+15V70A



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.0	-	-	-
10.0	87	119	114
20.0	53	65	69
30.0	46	55	57
40.0	35	43	43
50.0	26	33	34
60.0	20	26	28
70.0	15	21	21
77.0	14	20	20
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model	PCA1000F-15
Item	Overcurrent Protection
Object	+15V70A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

Hiccup mode activates when the output voltage is from 7.5 to 0V.

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
14.3	79.30	79.22
13.5	79.30	79.22
12.0	79.41	79.21
10.5	79.54	79.26
9.0	79.44	79.32
7.5	79.39	79.45
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-



Model	PCA1000F-15	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+15V70A	

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V
-20	15.231	15.231	15.231
25	15.308	15.308	15.308
40	15.340	15.340	15.340

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+15V70A	

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	73	79
25	74	78
40	74	79

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+15V70A	

1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 230V
-20	19.27	19.27
25	19.26	19.26
40	19.26	19.26






Figure A






Figure B-3 (IEC62368-1 refer to IEC60990 Fig.5)




Figure B-4 (IEC60601-1)




Figure C