



TEST DATA OF PCA600F-15-P2

Regulated DC Power Supply
March 14, 2017

Approved by : Koji Todo _____
Koji Todo Design Manager

Prepared by : Yutaka Tamura _____
Yutaka Tamura Design Engineer

COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Oversupply Protection	23
24.Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model	PCA600F-15-P2																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____																																																					
1.Graph			2.Values																																																			
			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>0.193</td><td>0.147</td><td>0.152</td></tr> <tr> <td>8.0</td><td>1.431</td><td>0.751</td><td>0.673</td></tr> <tr> <td>16.0</td><td>2.706</td><td>1.375</td><td>1.213</td></tr> <tr> <td>24.0</td><td>4.010</td><td>2.012</td><td>1.765</td></tr> <tr> <td>32.0</td><td>5.340</td><td>2.674</td><td>2.345</td></tr> <tr> <td>40.0</td><td>6.680</td><td>3.321</td><td>2.906</td></tr> <tr> <td>43.0</td><td>7.200</td><td>3.560</td><td>3.118</td></tr> <tr> <td>47.3</td><td>7.930</td><td>3.920</td><td>3.422</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.193	0.147	0.152	8.0	1.431	0.751	0.673	16.0	2.706	1.375	1.213	24.0	4.010	2.012	1.765	32.0	5.340	2.674	2.345	40.0	6.680	3.321	2.906	43.0	7.200	3.560	3.118	47.3	7.930	3.920	3.422	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.193	0.147	0.152																																																			
8.0	1.431	0.751	0.673																																																			
16.0	2.706	1.375	1.213																																																			
24.0	4.010	2.012	1.765																																																			
32.0	5.340	2.674	2.345																																																			
40.0	6.680	3.321	2.906																																																			
43.0	7.200	3.560	3.118																																																			
47.3	7.930	3.920	3.422																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL


Model	PCA600F-15-P2	Temperature	25°C																																																			
Item	Input Power (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> —△— Input Volt. 100V - - □ - - Input Volt. 200V - · ○ - - Input Volt. 230V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>13.5</td><td>10.5</td><td>10.3</td></tr> <tr> <td>8.0</td><td>140.7</td><td>138.1</td><td>138.1</td></tr> <tr> <td>16.0</td><td>268.6</td><td>264.7</td><td>264.2</td></tr> <tr> <td>24.0</td><td>399.0</td><td>392.9</td><td>392.0</td></tr> <tr> <td>32.0</td><td>532.0</td><td>523.4</td><td>523.0</td></tr> <tr> <td>40.0</td><td>666.0</td><td>653.1</td><td>652.0</td></tr> <tr> <td>43.0</td><td>717.0</td><td>702.0</td><td>700.0</td></tr> <tr> <td>47.3</td><td>791.0</td><td>773.0</td><td>771.0</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	13.5	10.5	10.3	8.0	140.7	138.1	138.1	16.0	268.6	264.7	264.2	24.0	399.0	392.9	392.0	32.0	532.0	523.4	523.0	40.0	666.0	653.1	652.0	43.0	717.0	702.0	700.0	47.3	791.0	773.0	771.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	13.5	10.5	10.3																																																			
8.0	140.7	138.1	138.1																																																			
16.0	268.6	264.7	264.2																																																			
24.0	399.0	392.9	392.0																																																			
32.0	532.0	523.4	523.0																																																			
40.0	666.0	653.1	652.0																																																			
43.0	717.0	702.0	700.0																																																			
47.3	791.0	773.0	771.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PCA600F-15-P2
Item	Efficiency (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
80	90.0	89.3
85	90.3	89.6
100	90.8	90.9
120	91.3	91.7
200	92.3	92.8
230	92.6	93.1
264	92.6	93.4
280	92.6	93.1
--	-	-

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	PCA600F-15-P2	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	—△— Input Volt. 100V - - □--- Input Volt. 200V - - ○--- Input Volt. 230V																																																					
<p>The graph shows efficiency increasing with load current for all input voltages. The 100V curve is the highest, followed by 230V, and then 200V. A slanted line is drawn through the data points, representing the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>10</td><td>86.1</td><td>87.7</td><td>87.7</td></tr> <tr><td>15</td><td>90.2</td><td>91.5</td><td>91.7</td></tr> <tr><td>20</td><td>91.2</td><td>92.6</td><td>92.8</td></tr> <tr><td>25</td><td>91.2</td><td>92.7</td><td>92.7</td></tr> <tr><td>30</td><td>91.0</td><td>92.8</td><td>93.0</td></tr> <tr><td>35</td><td>90.9</td><td>92.8</td><td>93.1</td></tr> <tr><td>40</td><td>90.6</td><td>92.7</td><td>93.0</td></tr> <tr><td>45</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>50</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	10	86.1	87.7	87.7	15	90.2	91.5	91.7	20	91.2	92.6	92.8	25	91.2	92.7	92.7	30	91.0	92.8	93.0	35	90.9	92.8	93.1	40	90.6	92.7	93.0	45	-	-	-	50	-	-	-												
Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																																																			
10	86.1	87.7	87.7																																																			
15	90.2	91.5	91.7																																																			
20	91.2	92.6	92.8																																																			
25	91.2	92.7	92.7																																																			
30	91.0	92.8	93.0																																																			
35	90.9	92.8	93.1																																																			
40	90.6	92.7	93.0																																																			
45	-	-	-																																																			
50	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8.0</td><td>86.1</td><td>87.7</td><td>87.7</td></tr> <tr><td>16.0</td><td>90.2</td><td>91.5</td><td>91.7</td></tr> <tr><td>24.0</td><td>91.2</td><td>92.6</td><td>92.8</td></tr> <tr><td>32.0</td><td>91.2</td><td>92.7</td><td>92.7</td></tr> <tr><td>40.0</td><td>91.0</td><td>92.8</td><td>93.0</td></tr> <tr><td>43.0</td><td>90.9</td><td>92.8</td><td>93.1</td></tr> <tr><td>47.3</td><td>90.6</td><td>92.7</td><td>93.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	8.0	86.1	87.7	87.7	16.0	90.2	91.5	91.7	24.0	91.2	92.6	92.8	32.0	91.2	92.7	92.7	40.0	91.0	92.8	93.0	43.0	90.9	92.8	93.1	47.3	90.6	92.7	93.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
8.0	86.1	87.7	87.7																																																			
16.0	90.2	91.5	91.7																																																			
24.0	91.2	92.6	92.8																																																			
32.0	91.2	92.7	92.7																																																			
40.0	91.0	92.8	93.0																																																			
43.0	90.9	92.8	93.1																																																			
47.3	90.6	92.7	93.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model	PCA600F-15-P2
Item	Power Factor (by Input Voltage)
Object	_____

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
80	0.998	0.999
85	0.998	0.998
100	0.997	0.999
120	0.994	0.997
200	0.975	0.985
230	0.962	0.978
264	0.939	0.965
280	0.573	0.712
--	-	-




Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PCA600F-15-P2	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object																																																						
1.Graph	<p>—△— Input Volt. 100V - - -□- Input Volt. 200V - - ○- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Power Factor (100V)</th> <th>Power Factor (200V)</th> <th>Power Factor (230V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.70</td><td>0.35</td><td>0.30</td></tr> <tr><td>10</td><td>0.985</td><td>0.920</td><td>0.893</td></tr> <tr><td>20</td><td>0.994</td><td>0.963</td><td>0.948</td></tr> <tr><td>30</td><td>0.995</td><td>0.977</td><td>0.966</td></tr> <tr><td>40</td><td>0.998</td><td>0.979</td><td>0.970</td></tr> <tr><td>47.3</td><td>0.999</td><td>0.987</td><td>0.980</td></tr> </tbody> </table>			Load Current [A]	Power Factor (100V)	Power Factor (200V)	Power Factor (230V)	0	0.70	0.35	0.30	10	0.985	0.920	0.893	20	0.994	0.963	0.948	30	0.995	0.977	0.966	40	0.998	0.979	0.970	47.3	0.999	0.987	0.980																							
Load Current [A]	Power Factor (100V)	Power Factor (200V)	Power Factor (230V)																																																			
0	0.70	0.35	0.30																																																			
10	0.985	0.920	0.893																																																			
20	0.994	0.963	0.948																																																			
30	0.995	0.977	0.966																																																			
40	0.998	0.979	0.970																																																			
47.3	0.999	0.987	0.980																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.702</td><td>0.359</td><td>0.296</td></tr> <tr><td>8.0</td><td>0.985</td><td>0.920</td><td>0.893</td></tr> <tr><td>16.0</td><td>0.994</td><td>0.963</td><td>0.948</td></tr> <tr><td>24.0</td><td>0.995</td><td>0.977</td><td>0.966</td></tr> <tr><td>32.0</td><td>0.998</td><td>0.979</td><td>0.970</td></tr> <tr><td>40.0</td><td>0.999</td><td>0.984</td><td>0.976</td></tr> <tr><td>43.0</td><td>0.999</td><td>0.985</td><td>0.978</td></tr> <tr><td>47.3</td><td>0.999</td><td>0.987</td><td>0.980</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.702	0.359	0.296	8.0	0.985	0.920	0.893	16.0	0.994	0.963	0.948	24.0	0.995	0.977	0.966	32.0	0.998	0.979	0.970	40.0	0.999	0.984	0.976	43.0	0.999	0.985	0.978	47.3	0.999	0.987	0.980	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.702	0.359	0.296																																																			
8.0	0.985	0.920	0.893																																																			
16.0	0.994	0.963	0.948																																																			
24.0	0.995	0.977	0.966																																																			
32.0	0.998	0.979	0.970																																																			
40.0	0.999	0.984	0.976																																																			
43.0	0.999	0.985	0.978																																																			
47.3	0.999	0.987	0.980																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PCA600F-15-P2	Temperature Testing Circuitry Figure A
Item	Inrush Current	
Object	_____	





Model	PCA600F-15-P2	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object	_____		

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure B-1	Both phases	0.13	0.30	0.31	Operation
		One of phases	0.25	0.56	0.58	Stand by
IEC62368-1	Figure B-2	Both phases	0.12	0.29	0.30	Operation
		One of phases	0.25	0.54	0.56	Stand by
	Figure B-3	Both phases	0.12	0.29	0.30	Operation
		One of phases	0.25	0.54	0.57	Stand by
IEC60601-1	Figure B-4	Both phases	0.12	0.29	0.30	Operation
		One of phases	0.24	0.53	0.55	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PCA600F-15-P2																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+15V43A																																	
1.Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>--- □ --- Load 50%</p> <p>— ▲ — Load 100%</p>																																		
Note: Slanted line shows the range of the rated input voltage.																																		
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td><td>15.184</td><td>15.182</td></tr> <tr> <td>85</td><td>15.184</td><td>15.182</td></tr> <tr> <td>100</td><td>15.184</td><td>15.182</td></tr> <tr> <td>120</td><td>15.184</td><td>15.182</td></tr> <tr> <td>200</td><td>15.184</td><td>15.182</td></tr> <tr> <td>230</td><td>15.184</td><td>15.182</td></tr> <tr> <td>264</td><td>15.184</td><td>15.182</td></tr> <tr> <td>280</td><td>15.184</td><td>15.182</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	80	15.184	15.182	85	15.184	15.182	100	15.184	15.182	120	15.184	15.182	200	15.184	15.182	230	15.184	15.182	264	15.184	15.182	280	15.184	15.182	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
80	15.184	15.182																																
85	15.184	15.182																																
100	15.184	15.182																																
120	15.184	15.182																																
200	15.184	15.182																																
230	15.184	15.182																																
264	15.184	15.182																																
280	15.184	15.182																																
--	-	-																																


COSEL

Model	PCA600F-15-P2	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V43A																																																					
1.Graph		2.Values																																																				
<p>The graph plots Output Voltage [V] on the Y-axis (14.80 to 15.50) against Load Current [A] on the X-axis (0 to 50). Three curves are shown for Input Volt. 100V (solid line with triangles), Input Volt. 200V (dashed line with squares), and Input Volt. 230V (dash-dot line with circles). All curves show a slight initial decrease in output voltage as load increases, followed by a sharp drop-off starting around 40A. A slanted line on the right side of the graph indicates the rated load current range.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.185</td><td>15.186</td><td>15.186</td></tr> <tr><td>8.0</td><td>15.185</td><td>15.186</td><td>15.185</td></tr> <tr><td>16.0</td><td>15.184</td><td>15.185</td><td>15.184</td></tr> <tr><td>24.0</td><td>15.184</td><td>15.183</td><td>15.184</td></tr> <tr><td>32.0</td><td>15.182</td><td>15.183</td><td>15.184</td></tr> <tr><td>40.0</td><td>15.182</td><td>15.182</td><td>15.183</td></tr> <tr><td>43.0</td><td>15.181</td><td>15.181</td><td>15.181</td></tr> <tr><td>47.3</td><td>15.181</td><td>15.181</td><td>15.180</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	15.185	15.186	15.186	8.0	15.185	15.186	15.185	16.0	15.184	15.185	15.184	24.0	15.184	15.183	15.184	32.0	15.182	15.183	15.184	40.0	15.182	15.182	15.183	43.0	15.181	15.181	15.181	47.3	15.181	15.181	15.180	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	15.185	15.186	15.186																																																			
8.0	15.185	15.186	15.185																																																			
16.0	15.184	15.185	15.184																																																			
24.0	15.184	15.183	15.184																																																			
32.0	15.182	15.183	15.184																																																			
40.0	15.182	15.182	15.183																																																			
43.0	15.181	15.181	15.181																																																			
47.3	15.181	15.181	15.180																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						


COSEL

Model	PCA600F-15	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+15V43A		

Input Volt. 100 V
 Cycle 1000 ms



Min.Load (0A) →
 Load 50% (21.5A)




COSEL

Model	PCA600F-15-P2
Item	Ripple Voltage (by Load Current)
Object	+15V43A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.0	39	36
8.0	49	36
11.0	115	39
11.9	40	97
16.0	72	70
24.0	71	70
32.0	70	71
40.0	80	81
43.0	80	82
47.3	85	87
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	PCA600F-15-P2	Temperature	25°C
Item	Ripple-Noise	Testing Circuitry	Figure A
Object	+15V43A		

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
0.0	40	37
8.0	50	37
11.0	117	42
11.9	42	100
16.0	74	70
24.0	74	72
32.0	80	86
40.0	95	95
43.0	105	105
47.3	110	110
--	-	-

T1: Due to AC Input Line
T2: Due to Switching





Fig. Complex Ripple Wave Form

COSEL

Model	PCA600F-15-P2
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V43A

Testing Circuitry Figure A

1.Graph



2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
-30	100	100
-20	88	88
-10	83	83
0	80	80
10	80	82
25	75	80
30	72	78
40	72	72
50	72	72
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	PCA600F-15-P2
Item	Ambient Temperature Drift
Object	+15V43A



Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-30	15.168	15.168	15.168
-20	15.175	15.175	15.174
-10	15.180	15.180	15.179
0	15.176	15.176	15.176
10	15.180	15.180	15.180
25	15.182	15.182	15.182
30	15.186	15.186	15.186
40	15.190	15.189	15.190
50	15.181	15.182	15.181
55	15.181	15.182	15.181
--	-	-	-

Note: Slanted line shows the range of the rated ambient temperature.



Model	PCA600F-15-P2	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V43A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 43A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	40	200	0	15.203	± 11	± 0.1
Minimum Voltage	-20	200	43	15.182		

COSEL

Model	PCA600F-15-P2	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+15V43A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 230V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>15.138</td></tr> <tr><td>0.5</td><td>15.147</td></tr> <tr><td>1.0</td><td>15.147</td></tr> <tr><td>2.0</td><td>15.148</td></tr> <tr><td>3.0</td><td>15.148</td></tr> <tr><td>4.0</td><td>15.148</td></tr> <tr><td>5.0</td><td>15.148</td></tr> <tr><td>6.0</td><td>15.148</td></tr> <tr><td>7.0</td><td>15.148</td></tr> <tr><td>8.0</td><td>15.148</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	15.138	0.5	15.147	1.0	15.147	2.0	15.148	3.0	15.148	4.0	15.148	5.0	15.148	6.0	15.148	7.0	15.148	8.0	15.148
Time since start [H]	Output Voltage [V]																								
0.0	15.138																								
0.5	15.147																								
1.0	15.147																								
2.0	15.148																								
3.0	15.148																								
4.0	15.148																								
5.0	15.148																								
6.0	15.148																								
7.0	15.148																								
8.0	15.148																								


* The characteristic of AC100V is equal.

COSEL

Model	PCA600F-15-P2
Item	Rise and Fall Time
Object	+15V43A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		349.5	21.5	371.0	19.0	8.5	
230 V		335.0	21.0	356.0	24.3	8.7	



COSEL

Model	PCA600F-15-P2	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+15V43A																																		
1. Graph		2. Values																																	
		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>80</td><td>36</td><td>18</td> </tr> <tr> <td>85</td><td>36</td><td>18</td> </tr> <tr> <td>100</td><td>36</td><td>18</td> </tr> <tr> <td>120</td><td>36</td><td>18</td> </tr> <tr> <td>200</td><td>46</td><td>23</td> </tr> <tr> <td>230</td><td>46</td><td>23</td> </tr> <tr> <td>264</td><td>46</td><td>23</td> </tr> <tr> <td>280</td><td>46</td><td>23</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	80	36	18	85	36	18	100	36	18	120	36	18	200	46	23	230	46	23	264	46	23	280	46	23	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
80	36	18																																	
85	36	18																																	
100	36	18																																	
120	36	18																																	
200	46	23																																	
230	46	23																																	
264	46	23																																	
280	46	23																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL


Model	PCA600F-15-P2	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+15V43A																																																					
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>8.0</td><td>89</td><td>117</td><td>118</td></tr> <tr> <td>16.0</td><td>49</td><td>63</td><td>63</td></tr> <tr> <td>24.0</td><td>33</td><td>43</td><td>43</td></tr> <tr> <td>32.0</td><td>25</td><td>32</td><td>32</td></tr> <tr> <td>40.0</td><td>20</td><td>26</td><td>26</td></tr> <tr> <td>43.0</td><td>17</td><td>24</td><td>24</td></tr> <tr> <td>47.3</td><td>15</td><td>20</td><td>22</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	8.0	89	117	118	16.0	49	63	63	24.0	33	43	43	32.0	25	32	32	40.0	20	26	26	43.0	17	24	24	47.3	15	20	22	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
8.0	89	117	118																																																			
16.0	49	63	63																																																			
24.0	33	43	43																																																			
32.0	25	32	32																																																			
40.0	20	26	26																																																			
43.0	17	24	24																																																			
47.3	15	20	22																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PCA600F-15-P2
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+15V43A

Testing Circuitry Figure A

1. Graph



2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	74	82
-20	74	82
-10	74	82
0	74	82
10	74	82
25	74	82
30	74	82
40	74	82
50	74	82
55	74	82
--	-	-


Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	PCA600F-15-P2
Item	Overcurrent Protection
Object	+15V43A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

Intermittent operation occurs when the output voltage is from 7.5V to 0V.

2. Values


Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
14.3	49.44	49.15
13.5	49.28	49.31
12.0	49.37	49.11
10.5	49.13	49.16
9.0	49.39	49.23
7.7	49.34	49.37
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	PCA600F-15-P2
Item	Overvoltage Protection
Object	+15V43A

Testing Circuitry Figure A

1.Graph



2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-30	19.28	19.28
-20	19.28	19.28
-10	19.28	19.28
0	19.28	19.28
10	19.28	19.28
20	19.28	19.28
30	19.28	19.28
40	19.28	19.28
50	19.28	19.28
60	19.28	19.28
70	19.28	19.28
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.




Figure A




Figure B-1 (DEN-AN)




Figure B-2 (IEC62368-1 refer to IEC60990 Fig.4)

COSEL




Figure B-3 (IEC62368-1 refer to IEC60990 Fig.5)




Figure B-4 (IEC60601-1)




Figure C