



DATA SHEET		Date	06-Apr-18
Model	PCA600F-48	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	D.Hayashi




Frequency MHz	Line Phase	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/Fail	Remark
		QP	AV	QP	AV	QP	AV		
0.22450	VA	46.4	45.2	62.7	52.7	16.3	7.5	Pass	
0.22426	VB	46.9	45.7	62.7	52.7	15.8	7.0	Pass	
4.53165	VB	42.2	38.9	56.0	46.0	13.8	7.1	Pass	
4.52935	VA	41.5	38.4	56.0	46.0	14.5	7.6	Pass	
27.06110	VB	48.0	42.8	60.0	50.0	12.0	7.2	Pass	
27.16655	VA	47.4	42.5	60.0	50.0	12.6	7.5	Pass	




Frequency MHz	Polarization	Stability	Reading dB(μV)	Limit dB(μV/m)	Margin dB(μV/m)	Pass/Fail	Height cm	Angle deg	Remark
			QP	QP	QP				
55.085	V	Stable	31.0	40.0	9.0	Pass	102	359	
69.102	V	Stable	31.5	40.0	8.5	Pass	101	22	
85.776	V	Stable	31.9	40.0	8.1	Pass	112	41	
189.980	V	Stable	33.4	40.0	6.6	Pass	155	90	
190.919	H	Stable	29.8	40.0	10.2	Pass	109	62	

DATA SHEET		Date	06-Apr-18
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	D.Hayashi

1. Line conduction



2. Radiated emission



Conditions

Test : EMI
Model Name : PCA600F

O Photographs of test set-up

1.LINE CONDUCTION



2.RADIATED EMISSION

