

TEST DATA OF PDA30F-12

Regulated DC Power Supply
November 24, 2023

Approved by : _____ Tetsukazu Okamoto

Design Manager

Prepared by : _____ Takaaki Sekiguchi

Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)

COSEL

Model	PDA30F-12																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____																																																					
1.Graph			2.Values																																																			
<p>The graph shows the relationship between Input Current [A] on the Y-axis (0.0 to 1.0) and Load Current [A] on the X-axis (0 to 3). Three curves are plotted for different input voltages: 100V (solid line with open triangle markers), 200V (dashed line with open square markers), and 230V (dash-dot line with open circle markers). All curves start at (0,0) and increase monotonically. A slanted line is drawn through the origin, representing the rated load current range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.014</td><td>0.021</td><td>0.024</td></tr> <tr> <td>0.40</td><td>0.118</td><td>0.078</td><td>0.073</td></tr> <tr> <td>0.80</td><td>0.210</td><td>0.131</td><td>0.120</td></tr> <tr> <td>1.20</td><td>0.302</td><td>0.182</td><td>0.166</td></tr> <tr> <td>1.60</td><td>0.397</td><td>0.234</td><td>0.212</td></tr> <tr> <td>2.00</td><td>0.492</td><td>0.286</td><td>0.258</td></tr> <tr> <td>2.40</td><td>0.590</td><td>0.339</td><td>0.305</td></tr> <tr> <td>2.50</td><td>0.616</td><td>0.353</td><td>0.318</td></tr> <tr> <td>2.75</td><td>0.678</td><td>0.385</td><td>0.347</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.014	0.021	0.024	0.40	0.118	0.078	0.073	0.80	0.210	0.131	0.120	1.20	0.302	0.182	0.166	1.60	0.397	0.234	0.212	2.00	0.492	0.286	0.258	2.40	0.590	0.339	0.305	2.50	0.616	0.353	0.318	2.75	0.678	0.385	0.347	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.014	0.021	0.024																																																			
0.40	0.118	0.078	0.073																																																			
0.80	0.210	0.131	0.120																																																			
1.20	0.302	0.182	0.166																																																			
1.60	0.397	0.234	0.212																																																			
2.00	0.492	0.286	0.258																																																			
2.40	0.590	0.339	0.305																																																			
2.50	0.616	0.353	0.318																																																			
2.75	0.678	0.385	0.347																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL




Model	PDA30F-12	Temperature	25°C																																														
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																														
Object	_____																																																
1.Graph		2.Values																																															
<p>Graph showing Efficiency [%] vs Load Current [A]. The Y-axis ranges from 50 to 100 in increments of 10. The X-axis ranges from 0 to 3 in increments of 1. Three curves are shown for Input Volt. 100V (solid line with triangles), Input Volt. 200V (dashed line with squares), and Input Volt. 230V (dash-dot line with circles). A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.40</td><td>81.8</td><td>76.1</td><td>74.1</td></tr> <tr><td>0.80</td><td>84.2</td><td>82.4</td><td>81.5</td></tr> <tr><td>1.20</td><td>84.6</td><td>84.7</td><td>84.1</td></tr> <tr><td>1.60</td><td>84.0</td><td>85.5</td><td>85.2</td></tr> <tr><td>2.00</td><td>83.1</td><td>85.5</td><td>85.5</td></tr> <tr><td>2.40</td><td>82.2</td><td>85.3</td><td>85.4</td></tr> <tr><td>2.50</td><td>82.1</td><td>85.3</td><td>85.5</td></tr> <tr><td>2.75</td><td>81.5</td><td>85.5</td><td>85.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.40	81.8	76.1	74.1	0.80	84.2	82.4	81.5	1.20	84.6	84.7	84.1	1.60	84.0	85.5	85.2	2.00	83.1	85.5	85.5	2.40	82.2	85.3	85.4	2.50	82.1	85.3	85.5	2.75	81.5	85.5	85.2	--	-	-	-	--	-	-	-
Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																														
0.00	-	-	-																																														
0.40	81.8	76.1	74.1																																														
0.80	84.2	82.4	81.5																																														
1.20	84.6	84.7	84.1																																														
1.60	84.0	85.5	85.2																																														
2.00	83.1	85.5	85.5																																														
2.40	82.2	85.3	85.4																																														
2.50	82.1	85.3	85.5																																														
2.75	81.5	85.5	85.2																																														
--	-	-	-																																														
--	-	-	-																																														
<p>Note: Slanted line shows the range of the rated load current.</p>																																																	

COSEL

Model	PDA30F-12	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.233</td><td>0.117</td><td>0.105</td></tr> <tr><td>0.40</td><td>0.505</td><td>0.393</td><td>0.375</td></tr> <tr><td>0.80</td><td>0.551</td><td>0.444</td><td>0.426</td></tr> <tr><td>1.20</td><td>0.575</td><td>0.468</td><td>0.448</td></tr> <tr><td>1.60</td><td>0.585</td><td>0.484</td><td>0.465</td></tr> <tr><td>2.00</td><td>0.594</td><td>0.495</td><td>0.477</td></tr> <tr><td>2.40</td><td>0.600</td><td>0.503</td><td>0.485</td></tr> <tr><td>2.50</td><td>0.600</td><td>0.503</td><td>0.485</td></tr> <tr><td>2.75</td><td>0.603</td><td>0.505</td><td>0.489</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.233	0.117	0.105	0.40	0.505	0.393	0.375	0.80	0.551	0.444	0.426	1.20	0.575	0.468	0.448	1.60	0.585	0.484	0.465	2.00	0.594	0.495	0.477	2.40	0.600	0.503	0.485	2.50	0.600	0.503	0.485	2.75	0.603	0.505	0.489	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.233	0.117	0.105																																																			
0.40	0.505	0.393	0.375																																																			
0.80	0.551	0.444	0.426																																																			
1.20	0.575	0.468	0.448																																																			
1.60	0.585	0.484	0.465																																																			
2.00	0.594	0.495	0.477																																																			
2.40	0.600	0.503	0.485																																																			
2.50	0.600	0.503	0.485																																																			
2.75	0.603	0.505	0.489																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	PDA30F-12	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	PDA30F-12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	_____		

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure C-1	Both phases	0.16	0.41	0.43	Operation
		One of phases	0.24	0.60	0.63	Stand by
IEC62368-1	Figure C-2	Both phases	0.16	0.40	0.42	Operation
		One of phases	0.24	0.59	0.62	Stand by
	Figure C-3	Both phases	0.16	0.40	0.42	Operation
		One of phases	0.24	0.59	0.62	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PDA30F-12
Item	Line Regulation
Object	+12V2.5A

 Temperature 25°C
 Testing Circuitry Figure A

1.Graph





2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	12.070	-
90	12.070	12.067
100	12.070	12.067
120	12.070	12.067
200	12.070	12.067
230	12.070	12.067
264	12.070	12.067
280	12.070	12.067
--	-	-

Note: Slanted line shows the range of the rated input voltage.



COSEL

Model	PDA30F-12	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+12V2.5A	2. Values																																																				
1. Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - -○- - Input Volt. 230V</p>  <p>Output Voltage [V]</p> <p>Load Current [A]</p>																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.076</td><td>12.075</td><td>12.075</td></tr> <tr><td>0.40</td><td>12.073</td><td>12.073</td><td>12.073</td></tr> <tr><td>0.80</td><td>12.072</td><td>12.072</td><td>12.072</td></tr> <tr><td>1.20</td><td>12.071</td><td>12.071</td><td>12.071</td></tr> <tr><td>1.60</td><td>12.070</td><td>12.070</td><td>12.070</td></tr> <tr><td>2.00</td><td>12.068</td><td>12.069</td><td>12.068</td></tr> <tr><td>2.40</td><td>12.067</td><td>12.068</td><td>12.067</td></tr> <tr><td>2.50</td><td>12.067</td><td>12.068</td><td>12.067</td></tr> <tr><td>2.75</td><td>12.066</td><td>12.067</td><td>12.066</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr><td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	12.076	12.075	12.075	0.40	12.073	12.073	12.073	0.80	12.072	12.072	12.072	1.20	12.071	12.071	12.071	1.60	12.070	12.070	12.070	2.00	12.068	12.069	12.068	2.40	12.067	12.068	12.067	2.50	12.067	12.068	12.067	2.75	12.066	12.067	12.066	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	12.076	12.075	12.075																																																			
0.40	12.073	12.073	12.073																																																			
0.80	12.072	12.072	12.072																																																			
1.20	12.071	12.071	12.071																																																			
1.60	12.070	12.070	12.070																																																			
2.00	12.068	12.069	12.068																																																			
2.40	12.067	12.068	12.067																																																			
2.50	12.067	12.068	12.067																																																			
2.75	12.066	12.067	12.066																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+12V2.5A	Testing Circuitry	Figure B																																																			
1. Graph	<p>Input Voltage 230V Load 100%</p>  <p>10[mV/div]</p> <p>10[μs/div]</p>																																																					



COSEL

Model	PDA30F-12	Temperature Testing Circuitry	25°C Figure A
Item	Dynamic Load Response		
Object	+12V2.5A		



Input Volt. 230 V
 Cycle 1000 ms

Response. $t_1=t_2=50\mu\text{s}$. Typ



Load 0%(0A) \longleftrightarrow
 Load 100%(2.5A)



Load 50%(1.25A) \longleftrightarrow
 Load 100%(2.5A)




Load 0%(0A) \longleftrightarrow
 Load 50%(1.25A)



COSEL


Model	PDA30F-12	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time		Figure A
Object	+12V2.5A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		55.2	5.1	60.3	26.0	20.3	
230 V		52.8	4.5	57.3	186.0	21.5	



COSEL

Model	PDA30F-12	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+12V2.5A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>41</td> <td>-</td> </tr> <tr> <td>90</td> <td>47</td> <td>19</td> </tr> <tr> <td>100</td> <td>61</td> <td>26</td> </tr> <tr> <td>120</td> <td>93</td> <td>41</td> </tr> <tr> <td>200</td> <td>286</td> <td>136</td> </tr> <tr> <td>230</td> <td>386</td> <td>186</td> </tr> <tr> <td>264</td> <td>517</td> <td>252</td> </tr> <tr> <td>280</td> <td>587</td> <td>287</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	41	-	90	47	19	100	61	26	120	93	41	200	286	136	230	386	186	264	517	252	280	587	287	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	41	-																																	
90	47	19																																	
100	61	26																																	
120	93	41																																	
200	286	136																																	
230	386	186																																	
264	517	252																																	
280	587	287																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL


Model	PDA30F-12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation																																																					
Object	+12V2.5A																																																					
1.Graph	<p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p> <p>Input Volt. 100V Input Volt. 200V Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.40</td><td>205</td><td>866</td><td>1156</td></tr> <tr> <td>0.80</td><td>101</td><td>447</td><td>596</td></tr> <tr> <td>1.20</td><td>64</td><td>301</td><td>406</td></tr> <tr> <td>1.60</td><td>46</td><td>223</td><td>303</td></tr> <tr> <td>2.00</td><td>34</td><td>176</td><td>239</td></tr> <tr> <td>2.40</td><td>27</td><td>144</td><td>196</td></tr> <tr> <td>2.50</td><td>25</td><td>138</td><td>188</td></tr> <tr> <td>2.75</td><td>22</td><td>123</td><td>169</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.40	205	866	1156	0.80	101	447	596	1.20	64	301	406	1.60	46	223	303	2.00	34	176	239	2.40	27	144	196	2.50	25	138	188	2.75	22	123	169	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.40	205	866	1156																																																			
0.80	101	447	596																																																			
1.20	64	301	406																																																			
1.60	46	223	303																																																			
2.00	34	176	239																																																			
2.40	27	144	196																																																			
2.50	25	138	188																																																			
2.75	22	123	169																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PDA30F-12
Item	Overcurrent Protection
Object	+12V2.5A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated load current.

Overcurrent protection is Hiccup mode.

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 100[V]	Input Volt. 230[V]
12.0	3.04	2.99
11.4	-	-
10.8	-	-
9.6	-	-
8.4	-	-
7.2	-	-
6.0	-	-
4.8	-	-
3.6	-	-
2.4	-	-
1.2	-	-
0.0	-	-

COSEL

Model	PDA30F-12	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+12V2.5A	

1.Values

Load 100%

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V
-10	12.018	12.018	12.018
25	12.067	12.068	12.067
55	12.083	12.084	12.083

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+12V2.5A	

1.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-10	33	51
25	32	51
55	32	52

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+12V2.5A	

1.Values

Load 0%

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 230V
-20	16.04	16.04
25	16.47	16.47
55	16.76	16.76

COSEL




Figure A




Figure B

