

TEST DATA OF PDA30F-24

Regulated DC Power Supply
November 24, 2023

Approved by : _____ Tetsukazu Okamoto

Design Manager

Prepared by : _____ Takaaki Sekiguchi

Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)

COSEL

Model	PDA30F-24	Temperature	25°C																																																																																																		
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																																																																		
Object	_____																																																																																																				
1.Graph		2.Values																																																																																																			
<p>The graph plots Input Current [A] on the y-axis (0.0 to 1.0) against Load Current [A] on the x-axis (0.0 to 1.6). Three curves are shown for different input voltages: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves start at (0,0) and increase monotonically. A slanted line is drawn through the data points, representing the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V [A]</th> <th>Input Volt. 200V [A]</th> <th>Input Volt. 230V [A]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.021</td><td>0.025</td><td>0.028</td></tr> <tr><td>0.20</td><td>0.125</td><td>0.081</td><td>0.074</td></tr> <tr><td>0.40</td><td>0.215</td><td>0.133</td><td>0.121</td></tr> <tr><td>0.60</td><td>0.306</td><td>0.184</td><td>0.167</td></tr> <tr><td>0.80</td><td>0.399</td><td>0.235</td><td>0.212</td></tr> <tr><td>1.00</td><td>0.493</td><td>0.287</td><td>0.258</td></tr> <tr><td>1.20</td><td>0.588</td><td>0.339</td><td>0.305</td></tr> <tr><td>1.30</td><td>0.637</td><td>0.366</td><td>0.329</td></tr> <tr><td>1.43</td><td>0.700</td><td>0.401</td><td>0.360</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]	0.00	0.021	0.025	0.028	0.20	0.125	0.081	0.074	0.40	0.215	0.133	0.121	0.60	0.306	0.184	0.167	0.80	0.399	0.235	0.212	1.00	0.493	0.287	0.258	1.20	0.588	0.339	0.305	1.30	0.637	0.366	0.329	1.43	0.700	0.401	0.360	--	-	-	-	--	-	-	-	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.021</td><td>0.025</td><td>0.028</td></tr> <tr><td>0.20</td><td>0.125</td><td>0.081</td><td>0.074</td></tr> <tr><td>0.40</td><td>0.215</td><td>0.133</td><td>0.121</td></tr> <tr><td>0.60</td><td>0.306</td><td>0.184</td><td>0.167</td></tr> <tr><td>0.80</td><td>0.399</td><td>0.235</td><td>0.212</td></tr> <tr><td>1.00</td><td>0.493</td><td>0.287</td><td>0.258</td></tr> <tr><td>1.20</td><td>0.588</td><td>0.339</td><td>0.305</td></tr> <tr><td>1.30</td><td>0.637</td><td>0.366</td><td>0.329</td></tr> <tr><td>1.43</td><td>0.700</td><td>0.401</td><td>0.360</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.021	0.025	0.028	0.20	0.125	0.081	0.074	0.40	0.215	0.133	0.121	0.60	0.306	0.184	0.167	0.80	0.399	0.235	0.212	1.00	0.493	0.287	0.258	1.20	0.588	0.339	0.305	1.30	0.637	0.366	0.329	1.43	0.700	0.401	0.360	--	-	-	-	--	-	-	-
Load Current [A]	Input Volt. 100V [A]	Input Volt. 200V [A]	Input Volt. 230V [A]																																																																																																		
0.00	0.021	0.025	0.028																																																																																																		
0.20	0.125	0.081	0.074																																																																																																		
0.40	0.215	0.133	0.121																																																																																																		
0.60	0.306	0.184	0.167																																																																																																		
0.80	0.399	0.235	0.212																																																																																																		
1.00	0.493	0.287	0.258																																																																																																		
1.20	0.588	0.339	0.305																																																																																																		
1.30	0.637	0.366	0.329																																																																																																		
1.43	0.700	0.401	0.360																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
Load Current [A]	Input Current [A]																																																																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																																																																		
0.00	0.021	0.025	0.028																																																																																																		
0.20	0.125	0.081	0.074																																																																																																		
0.40	0.215	0.133	0.121																																																																																																		
0.60	0.306	0.184	0.167																																																																																																		
0.80	0.399	0.235	0.212																																																																																																		
1.00	0.493	0.287	0.258																																																																																																		
1.20	0.588	0.339	0.305																																																																																																		
1.30	0.637	0.366	0.329																																																																																																		
1.43	0.700	0.401	0.360																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
<p>Note: Slanted line shows the range of the rated load current.</p>																																																																																																					

COSEL




Model	PDA30F-24	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Input Volt. 100V Input Volt. 200V Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.20</td><td>79.6</td><td>77.6</td><td>76.3</td></tr> <tr> <td>0.40</td><td>83.8</td><td>83.5</td><td>82.7</td></tr> <tr> <td>0.60</td><td>84.5</td><td>85.4</td><td>85.0</td></tr> <tr> <td>0.80</td><td>84.6</td><td>86.3</td><td>86.1</td></tr> <tr> <td>1.00</td><td>84.1</td><td>86.5</td><td>86.4</td></tr> <tr> <td>1.20</td><td>83.6</td><td>86.6</td><td>86.5</td></tr> <tr> <td>1.30</td><td>83.5</td><td>86.5</td><td>86.6</td></tr> <tr> <td>1.43</td><td>83.0</td><td>86.4</td><td>86.5</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.20	79.6	77.6	76.3	0.40	83.8	83.5	82.7	0.60	84.5	85.4	85.0	0.80	84.6	86.3	86.1	1.00	84.1	86.5	86.4	1.20	83.6	86.6	86.5	1.30	83.5	86.5	86.6	1.43	83.0	86.4	86.5	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.20	79.6	77.6	76.3																																																			
0.40	83.8	83.5	82.7																																																			
0.60	84.5	85.4	85.0																																																			
0.80	84.6	86.3	86.1																																																			
1.00	84.1	86.5	86.4																																																			
1.20	83.6	86.6	86.5																																																			
1.30	83.5	86.5	86.6																																																			
1.43	83.0	86.4	86.5																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PDA30F-24	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.307</td><td>0.192</td><td>0.179</td></tr> <tr><td>0.20</td><td>0.496</td><td>0.383</td><td>0.370</td></tr> <tr><td>0.40</td><td>0.543</td><td>0.436</td><td>0.421</td></tr> <tr><td>0.60</td><td>0.566</td><td>0.461</td><td>0.444</td></tr> <tr><td>0.80</td><td>0.577</td><td>0.478</td><td>0.460</td></tr> <tr><td>1.00</td><td>0.584</td><td>0.488</td><td>0.471</td></tr> <tr><td>1.20</td><td>0.591</td><td>0.495</td><td>0.478</td></tr> <tr><td>1.30</td><td>0.591</td><td>0.493</td><td>0.479</td></tr> <tr><td>1.43</td><td>0.594</td><td>0.497</td><td>0.480</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.307	0.192	0.179	0.20	0.496	0.383	0.370	0.40	0.543	0.436	0.421	0.60	0.566	0.461	0.444	0.80	0.577	0.478	0.460	1.00	0.584	0.488	0.471	1.20	0.591	0.495	0.478	1.30	0.591	0.493	0.479	1.43	0.594	0.497	0.480	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.307	0.192	0.179																																																			
0.20	0.496	0.383	0.370																																																			
0.40	0.543	0.436	0.421																																																			
0.60	0.566	0.461	0.444																																																			
0.80	0.577	0.478	0.460																																																			
1.00	0.584	0.488	0.471																																																			
1.20	0.591	0.495	0.478																																																			
1.30	0.591	0.493	0.479																																																			
1.43	0.594	0.497	0.480																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note: Slanted line shows the range of the rated load current.																																																						

COSEL

Model	PDA30F-24	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	PDA30F-24	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	_____		

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure C-1	Both phases	0.16	0.41	0.43	Operation
		One of phases	0.24	0.60	0.63	Stand by
IEC62368-1	Figure C-2	Both phases	0.16	0.40	0.42	Operation
		One of phases	0.24	0.59	0.62	Stand by
	Figure C-3	Both phases	0.16	0.40	0.42	Operation
		One of phases	0.24	0.59	0.62	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PDA30F-24
Item	Line Regulation
Object	+24V1.3A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph





2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	24.058	-
90	24.058	24.053
100	24.058	24.053
120	24.058	24.053
200	24.058	24.053
230	24.058	24.053
264	24.058	24.053
280	24.059	24.053
--	-	-

Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	PDA30F-24	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+24V1.3A	2. Values																																																				
1. Graph	<p>—△— Input Volt. 100V - - -□- Input Volt. 200V - - -○- Input Volt. 230V</p> 																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>24.060</td> <td>24.060</td> <td>24.061</td> </tr> <tr> <td>0.20</td> <td>24.058</td> <td>24.058</td> <td>24.058</td> </tr> <tr> <td>0.40</td> <td>24.057</td> <td>24.057</td> <td>24.058</td> </tr> <tr> <td>0.60</td> <td>24.056</td> <td>24.057</td> <td>24.057</td> </tr> <tr> <td>0.80</td> <td>24.055</td> <td>24.056</td> <td>24.056</td> </tr> <tr> <td>1.00</td> <td>24.054</td> <td>24.055</td> <td>24.055</td> </tr> <tr> <td>1.20</td> <td>24.052</td> <td>24.054</td> <td>24.054</td> </tr> <tr> <td>1.30</td> <td>24.052</td> <td>24.053</td> <td>24.054</td> </tr> <tr> <td>1.43</td> <td>24.050</td> <td>24.052</td> <td>24.053</td> </tr> <tr> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> <tr> <td>--</td> <td>--</td> <td>--</td> <td>--</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	24.060	24.060	24.061	0.20	24.058	24.058	24.058	0.40	24.057	24.057	24.058	0.60	24.056	24.057	24.057	0.80	24.055	24.056	24.056	1.00	24.054	24.055	24.055	1.20	24.052	24.054	24.054	1.30	24.052	24.053	24.054	1.43	24.050	24.052	24.053	--	--	--	--	--	--	--	--
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	24.060	24.060	24.061																																																			
0.20	24.058	24.058	24.058																																																			
0.40	24.057	24.057	24.058																																																			
0.60	24.056	24.057	24.057																																																			
0.80	24.055	24.056	24.056																																																			
1.00	24.054	24.055	24.055																																																			
1.20	24.052	24.054	24.054																																																			
1.30	24.052	24.053	24.054																																																			
1.43	24.050	24.052	24.053																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Note:	Slanted line shows the range of the rated load current.																																																					
Item	Ripple-Noise	Temperature	25°C																																																			
Object	+24V1.3A	Testing Circuitry	Figure B																																																			
1. Graph	<p>Input Voltage 230V Load 100%</p> 																																																					

COSEL

Model	PDA30F-24	Temperature Testing Circuitry Figure A	25°C
Item	Dynamic Load Response		
Object	+24V1.3A		

Input Volt. 230 V
 Cycle 1000 ms

Response. $t_1=t_2=50\mu\text{s}$. Typ

Load 0%(0A) \longleftrightarrow
 Load 100%(1.3A)

200[mV/div]

2[ms/div]

10[ms/div]

Load 50%(0.65A) \longleftrightarrow
 Load 100%(1.3A)

200[mV/div]

2[ms/div]

10[ms/div]

Load 0%(0A) \longleftrightarrow
 Load 50%(0.65A)

200[mV/div]


2[ms/div]

10[ms/div]

COSEL


Model	PDA30F-24	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time		Figure A
Object	+24V1.3A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		60.5	13.9	74.4	24.0	37.5	
230 V		57.6	11.8	69.4	181.0	38.0	




COSEL

Model	PDA30F-24
Item	Hold-Up Time
Object	+24V1.3A

 Temperature 25°C
 Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	39	-
90	45	17
100	58	24
120	89	39
200	274	132
230	372	181
264	499	246
280	569	281
--	-	-

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PDA30F-24	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+24V1.3A																																																					
1.Graph	<p>1. Graph</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 100V - - ■ - - Input Volt. 200V - · ○ - - Input Volt. 230V <p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.20</td><td>197</td><td>842</td><td>1126</td></tr> <tr> <td>0.40</td><td>99</td><td>441</td><td>594</td></tr> <tr> <td>0.60</td><td>63</td><td>299</td><td>405</td></tr> <tr> <td>0.80</td><td>45</td><td>224</td><td>305</td></tr> <tr> <td>1.00</td><td>32</td><td>178</td><td>241</td></tr> <tr> <td>1.20</td><td>26</td><td>146</td><td>198</td></tr> <tr> <td>1.30</td><td>23</td><td>132</td><td>182</td></tr> <tr> <td>1.43</td><td>20</td><td>120</td><td>164</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.20	197	842	1126	0.40	99	441	594	0.60	63	299	405	0.80	45	224	305	1.00	32	178	241	1.20	26	146	198	1.30	23	132	182	1.43	20	120	164	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.20	197	842	1126																																																			
0.40	99	441	594																																																			
0.60	63	299	405																																																			
0.80	45	224	305																																																			
1.00	32	178	241																																																			
1.20	26	146	198																																																			
1.30	23	132	182																																																			
1.43	20	120	164																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PDA30F-24																																										
Item	Overcurrent Protection	Temperature 25°C Testing Circuitry Figure A																																									
Object	+24V1.3A																																										
1. Graph																																											
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 230V</p>																																											
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Overcurrent protection is Hiccup mode.</p>																																											
2. Values																																											
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>24.0</td><td>1.55</td><td>1.59</td></tr> <tr><td>22.8</td><td>-</td><td>-</td></tr> <tr><td>21.6</td><td>-</td><td>-</td></tr> <tr><td>19.2</td><td>-</td><td>-</td></tr> <tr><td>16.8</td><td>-</td><td>-</td></tr> <tr><td>14.4</td><td>-</td><td>-</td></tr> <tr><td>12.0</td><td>-</td><td>-</td></tr> <tr><td>9.6</td><td>-</td><td>-</td></tr> <tr><td>7.2</td><td>-</td><td>-</td></tr> <tr><td>4.8</td><td>-</td><td>-</td></tr> <tr><td>2.4</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	24.0	1.55	1.59	22.8	-	-	21.6	-	-	19.2	-	-	16.8	-	-	14.4	-	-	12.0	-	-	9.6	-	-	7.2	-	-	4.8	-	-	2.4	-	-	0.0	-	-
Output Voltage [V]	Load Current [A]																																										
	Input Volt. 100[V]	Input Volt. 230[V]																																									
24.0	1.55	1.59																																									
22.8	-	-																																									
21.6	-	-																																									
19.2	-	-																																									
16.8	-	-																																									
14.4	-	-																																									
12.0	-	-																																									
9.6	-	-																																									
7.2	-	-																																									
4.8	-	-																																									
2.4	-	-																																									
0.0	-	-																																									

COSEL

Model	PDA30F-24	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+24V1.3A	

1.Values

Load 100%

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V
-10	24.057	24.058	24.059
25	24.052	24.053	24.054
55	24.014	24.015	24.016

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+24V1.3A	

1.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-10	39	59
25	39	58
55	38	58

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+24V1.3A	

1.Values

Load 0%

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 230V
-20	32.00	32.00
25	33.17	33.17
55	34.02	34.02

COSEL




Figure A




Figure B

COSEL




Figure C-1 (DEN-AN)




Figure C-2 (IEC62368-1 refer to IEC60990 Fig.4)




Figure C-3 (IEC62368-1 refer to IEC60990 Fig.5)