

TEST DATA OF PDA50F-12

Regulated DC Power Supply
November 21, 2023

Approved by : _____ Tetsukazu Okamoto

Design Manager

Prepared by : _____ Takaaki Sekiguchi

Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 15)

COSEL

Model	PDA50F-12	Temperature	25°C																																																																																																		
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																																																																		
Object	_____																																																																																																				
1.Graph		2.Values																																																																																																			
<p>1. Graph</p> <ul style="list-style-type: none"> — ▲ — Input Volt. 100V - - ■ - - Input Volt. 200V - · ○ - - Input Volt. 230V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.031</td><td>0.058</td><td>0.067</td></tr> <tr><td>0.80</td><td>0.223</td><td>0.152</td><td>0.142</td></tr> <tr><td>1.60</td><td>0.403</td><td>0.250</td><td>0.229</td></tr> <tr><td>2.40</td><td>0.589</td><td>0.349</td><td>0.317</td></tr> <tr><td>3.20</td><td>0.781</td><td>0.451</td><td>0.409</td></tr> <tr><td>4.00</td><td>0.977</td><td>0.556</td><td>0.502</td></tr> <tr><td>4.30</td><td>1.053</td><td>0.599</td><td>0.539</td></tr> <tr><td>4.73</td><td>1.158</td><td>0.657</td><td>0.591</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.031	0.058	0.067	0.80	0.223	0.152	0.142	1.60	0.403	0.250	0.229	2.40	0.589	0.349	0.317	3.20	0.781	0.451	0.409	4.00	0.977	0.556	0.502	4.30	1.053	0.599	0.539	4.73	1.158	0.657	0.591	--	-	-	-	--	-	-	-	--	-	-	-	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.031</td><td>0.058</td><td>0.067</td></tr> <tr><td>0.80</td><td>0.223</td><td>0.152</td><td>0.142</td></tr> <tr><td>1.60</td><td>0.403</td><td>0.250</td><td>0.229</td></tr> <tr><td>2.40</td><td>0.589</td><td>0.349</td><td>0.317</td></tr> <tr><td>3.20</td><td>0.781</td><td>0.451</td><td>0.409</td></tr> <tr><td>4.00</td><td>0.977</td><td>0.556</td><td>0.502</td></tr> <tr><td>4.30</td><td>1.053</td><td>0.599</td><td>0.539</td></tr> <tr><td>4.73</td><td>1.158</td><td>0.657</td><td>0.591</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.031	0.058	0.067	0.80	0.223	0.152	0.142	1.60	0.403	0.250	0.229	2.40	0.589	0.349	0.317	3.20	0.781	0.451	0.409	4.00	0.977	0.556	0.502	4.30	1.053	0.599	0.539	4.73	1.158	0.657	0.591	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																																																																		
0.00	0.031	0.058	0.067																																																																																																		
0.80	0.223	0.152	0.142																																																																																																		
1.60	0.403	0.250	0.229																																																																																																		
2.40	0.589	0.349	0.317																																																																																																		
3.20	0.781	0.451	0.409																																																																																																		
4.00	0.977	0.556	0.502																																																																																																		
4.30	1.053	0.599	0.539																																																																																																		
4.73	1.158	0.657	0.591																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
Load Current [A]	Input Current [A]																																																																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																																																																		
0.00	0.031	0.058	0.067																																																																																																		
0.80	0.223	0.152	0.142																																																																																																		
1.60	0.403	0.250	0.229																																																																																																		
2.40	0.589	0.349	0.317																																																																																																		
3.20	0.781	0.451	0.409																																																																																																		
4.00	0.977	0.556	0.502																																																																																																		
4.30	1.053	0.599	0.539																																																																																																		
4.73	1.158	0.657	0.591																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		
--	-	-	-																																																																																																		

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PDA50F-12	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.80</td><td>83.0</td><td>80.4</td><td>79.3</td></tr> <tr> <td>1.60</td><td>84.5</td><td>84.1</td><td>83.6</td></tr> <tr> <td>2.40</td><td>84.2</td><td>84.9</td><td>84.7</td></tr> <tr> <td>3.20</td><td>83.5</td><td>85.1</td><td>85.1</td></tr> <tr> <td>4.00</td><td>82.6</td><td>85.1</td><td>85.1</td></tr> <tr> <td>4.30</td><td>82.5</td><td>85.0</td><td>85.0</td></tr> <tr> <td>4.73</td><td>81.8</td><td>84.7</td><td>84.8</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.80	83.0	80.4	79.3	1.60	84.5	84.1	83.6	2.40	84.2	84.9	84.7	3.20	83.5	85.1	85.1	4.00	82.6	85.1	85.1	4.30	82.5	85.0	85.0	4.73	81.8	84.7	84.8	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.80	83.0	80.4	79.3																																																			
1.60	84.5	84.1	83.6																																																			
2.40	84.2	84.9	84.7																																																			
3.20	83.5	85.1	85.1																																																			
4.00	82.6	85.1	85.1																																																			
4.30	82.5	85.0	85.0																																																			
4.73	81.8	84.7	84.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					




COSEL

Model	PDA50F-12	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.104</td><td>0.040</td><td>0.036</td></tr> <tr> <td>0.80</td><td>0.530</td><td>0.387</td><td>0.365</td></tr> <tr> <td>1.60</td><td>0.580</td><td>0.461</td><td>0.441</td></tr> <tr> <td>2.40</td><td>0.598</td><td>0.492</td><td>0.473</td></tr> <tr> <td>3.20</td><td>0.603</td><td>0.506</td><td>0.486</td></tr> <tr> <td>4.00</td><td>0.605</td><td>0.514</td><td>0.495</td></tr> <tr> <td>4.30</td><td>0.605</td><td>0.513</td><td>0.495</td></tr> <tr> <td>4.73</td><td>0.607</td><td>0.515</td><td>0.497</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	0.104	0.040	0.036	0.80	0.530	0.387	0.365	1.60	0.580	0.461	0.441	2.40	0.598	0.492	0.473	3.20	0.603	0.506	0.486	4.00	0.605	0.514	0.495	4.30	0.605	0.513	0.495	4.73	0.607	0.515	0.497	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	0.104	0.040	0.036																																																			
0.80	0.530	0.387	0.365																																																			
1.60	0.580	0.461	0.441																																																			
2.40	0.598	0.492	0.473																																																			
3.20	0.603	0.506	0.486																																																			
4.00	0.605	0.514	0.495																																																			
4.30	0.605	0.513	0.495																																																			
4.73	0.607	0.515	0.497																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PDA50F-12	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	PDA50F-12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	_____		

1. Results

[mA]

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	230 [V]	240 [V]	
DEN-AN	Figure C-1	Both phases	0.18	0.47	0.49	Operation
		One of phases	0.26	0.68	0.72	Stand by
IEC62368-1	Figure C-2	Both phases	0.18	0.46	0.48	Operation
		One of phases	0.26	0.67	0.71	Stand by
	Figure C-3	Both phases	0.18	0.46	0.48	Operation
		One of phases	0.26	0.67	0.71	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PDA50F-12																																	
Item	Line Regulation	Temperature 25°C Testing Circuitry Figure A																																
Object	+12V4.3A																																	
1. Graph																																		
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																		
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>12.080</td><td>12.076</td></tr> <tr> <td>90</td><td>12.080</td><td>12.076</td></tr> <tr> <td>100</td><td>12.080</td><td>12.076</td></tr> <tr> <td>120</td><td>12.080</td><td>12.076</td></tr> <tr> <td>200</td><td>12.081</td><td>12.077</td></tr> <tr> <td>230</td><td>12.081</td><td>12.077</td></tr> <tr> <td>264</td><td>12.081</td><td>12.078</td></tr> <tr> <td>280</td><td>12.081</td><td>12.078</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	12.080	12.076	90	12.080	12.076	100	12.080	12.076	120	12.080	12.076	200	12.081	12.077	230	12.081	12.077	264	12.081	12.078	280	12.081	12.078	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	12.080	12.076																																
90	12.080	12.076																																
100	12.080	12.076																																
120	12.080	12.076																																
200	12.081	12.077																																
230	12.081	12.077																																
264	12.081	12.078																																
280	12.081	12.078																																
--	-	-																																

COSEL


Model	PDA50F-12	Temperature	25°C	
Item	Load Regulation	Testing Circuitry	Figure A	
Object	+12V4.3A	2. Values		
1. Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - -○- - Input Volt. 230V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>			
	<p>Note: Slanted line shows the range of the rated load current.</p>			
Item	Ripple-Noise	Temperature	25°C	
Object	+12V4.3A	Testing Circuitry	Figure B	
1. Graph	<p>Input Voltage 230V Load 100%</p> <p>20[mV/div]</p> <p>10[μs/div]</p>			

COSEL

Model	PDA50F-12	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+12V4.3A		

Input Volt. 230 V

Cycle 1000 ms

Load 0%(0A) \longleftrightarrow
Load 100%(4.3A)

200[mV/div]

Response. $t_1=t_2=50\mu s$. Typ

2[ms/div]

10[ms/div]

Load 50%(2.15A) \longleftrightarrow
Load 100%(4.3A)

200[mV/div]

2[ms/div]

10[ms/div]

Load 0%(0A) \longleftrightarrow
Load 50%(2.15A)

200[mV/div]


2[ms/div]

10[ms/div]

COSEL


Model	PDA50F-12	Temperature Testing Circuitry Figure A	25°C
Item	Rise and Fall Time		Figure A
Object	+12V4.3A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		50.1	4.2	54.3	21.0	15.8	
230 V		49.6	4.6	54.2	142.0	16.3	



COSEL

Model	PDA50F-12	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+12V4.3A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>31</td> <td>11</td> </tr> <tr> <td>90</td> <td>35</td> <td>13</td> </tr> <tr> <td>100</td> <td>46</td> <td>21</td> </tr> <tr> <td>120</td> <td>70</td> <td>31</td> </tr> <tr> <td>200</td> <td>217</td> <td>104</td> </tr> <tr> <td>230</td> <td>295</td> <td>142</td> </tr> <tr> <td>264</td> <td>397</td> <td>193</td> </tr> <tr> <td>280</td> <td>451</td> <td>220</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	31	11	90	35	13	100	46	21	120	70	31	200	217	104	230	295	142	264	397	193	280	451	220	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	31	11																																	
90	35	13																																	
100	46	21																																	
120	70	31																																	
200	217	104																																	
230	295	142																																	
264	397	193																																	
280	451	220																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	PDA50F-12	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+12V4.3A																																																					
1.Graph	<p>Graph showing Instantaneous Compensation Time [ms] vs Load Current [A]. The Y-axis is logarithmic from 10 to 10000 ms. The X-axis ranges from 0 to 5 A. Three curves are plotted for Input Voltages: 100V (solid line with open triangles), 200V (dashed line with open squares), and 230V (dash-dot line with open circles). A slanted line indicates the range of the rated load current.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>100[V] [ms]</th> <th>200[V] [ms]</th> <th>230[V] [ms]</th> </tr> </thead> <tbody> <tr><td>0.80</td><td>137</td><td>586</td><td>784</td></tr> <tr><td>1.60</td><td>65</td><td>301</td><td>405</td></tr> <tr><td>2.40</td><td>40</td><td>198</td><td>269</td></tr> <tr><td>3.20</td><td>29</td><td>146</td><td>198</td></tr> <tr><td>4.00</td><td>21</td><td>115</td><td>156</td></tr> <tr><td>4.30</td><td>18</td><td>106</td><td>145</td></tr> <tr><td>4.73</td><td>15</td><td>94</td><td>130</td></tr> </tbody> </table>			Load Current [A]	100[V] [ms]	200[V] [ms]	230[V] [ms]	0.80	137	586	784	1.60	65	301	405	2.40	40	198	269	3.20	29	146	198	4.00	21	115	156	4.30	18	106	145	4.73	15	94	130																			
Load Current [A]	100[V] [ms]	200[V] [ms]	230[V] [ms]																																																			
0.80	137	586	784																																																			
1.60	65	301	405																																																			
2.40	40	198	269																																																			
3.20	29	146	198																																																			
4.00	21	115	156																																																			
4.30	18	106	145																																																			
4.73	15	94	130																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.80</td><td>137</td><td>586</td><td>784</td></tr> <tr><td>1.60</td><td>65</td><td>301</td><td>405</td></tr> <tr><td>2.40</td><td>40</td><td>198</td><td>269</td></tr> <tr><td>3.20</td><td>29</td><td>146</td><td>198</td></tr> <tr><td>4.00</td><td>21</td><td>115</td><td>156</td></tr> <tr><td>4.30</td><td>18</td><td>106</td><td>145</td></tr> <tr><td>4.73</td><td>15</td><td>94</td><td>130</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.80	137	586	784	1.60	65	301	405	2.40	40	198	269	3.20	29	146	198	4.00	21	115	156	4.30	18	106	145	4.73	15	94	130	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
0.80	137	586	784																																																			
1.60	65	301	405																																																			
2.40	40	198	269																																																			
3.20	29	146	198																																																			
4.00	21	115	156																																																			
4.30	18	106	145																																																			
4.73	15	94	130																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PDA50F-12																																										
Item	Overcurrent Protection	Temperature 25°C Testing Circuitry Figure A																																									
Object	+12V4.3A																																										
1. Graph																																											
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 230V</p>																																											
<p>Note: Slanted line shows the range of the rated load current.</p> <p>Overcurrent protection is Hiccup mode.</p>																																											
2. Values																																											
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>5.51</td><td>6.08</td></tr> <tr><td>11.4</td><td>-</td><td>-</td></tr> <tr><td>10.8</td><td>-</td><td>-</td></tr> <tr><td>9.6</td><td>-</td><td>-</td></tr> <tr><td>8.4</td><td>-</td><td>-</td></tr> <tr><td>7.2</td><td>-</td><td>-</td></tr> <tr><td>6.0</td><td>-</td><td>-</td></tr> <tr><td>4.8</td><td>-</td><td>-</td></tr> <tr><td>3.6</td><td>-</td><td>-</td></tr> <tr><td>2.4</td><td>-</td><td>-</td></tr> <tr><td>1.2</td><td>-</td><td>-</td></tr> <tr><td>0.0</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	12.0	5.51	6.08	11.4	-	-	10.8	-	-	9.6	-	-	8.4	-	-	7.2	-	-	6.0	-	-	4.8	-	-	3.6	-	-	2.4	-	-	1.2	-	-	0.0	-	-
Output Voltage [V]	Load Current [A]																																										
	Input Volt. 100[V]	Input Volt. 230[V]																																									
12.0	5.51	6.08																																									
11.4	-	-																																									
10.8	-	-																																									
9.6	-	-																																									
8.4	-	-																																									
7.2	-	-																																									
6.0	-	-																																									
4.8	-	-																																									
3.6	-	-																																									
2.4	-	-																																									
1.2	-	-																																									
0.0	-	-																																									

COSEL

Model	PDA50F-12	
Item	Ambient Temperature Drift	Testing Circuitry Figure A
Object	+12V4.3A	

1.Values

Load 100%

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V
-10	12.042	12.043	12.043
25	12.076	12.077	12.077
50	12.086	12.088	12.088

Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A
Object	+12V4.3A	

1.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-10	35	57
25	35	57
50	35	57

Item	Overvoltage Protection	Testing Circuitry Figure A
Object	+12V4.3A	

1.Values

Load 0%

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 230V
-20	16.04	16.04
25	16.47	16.47
50	16.76	16.76

COSEL




Figure A




Figure B




Figure C-1 (DEN-AN)




Figure C-2 (IEC62368-1 refer to IEC60990 Fig.4)




Figure C-3 (IEC62368-1 refer to IEC60990 Fig.5)