



EXTRA TEST DATA OF PJA100F-12

*Regulated DC Power Supply
Aug 20, 2020*

COSEL CO.,LTD.






CONTENTS

1.Inrush Current (enlargement) 1
2.Dynamic Line Regulation 2
3.Overvoltage Protection (waveform) 3
4.Hiccup cycle (by Overcurrent Protection) 4
5.Power Consumption (by Input Voltage) 5
6.Figure of Testing Circuitry 6

(Final Page 6)






Model		PJA100F-12	Temperature 25°C Testing Circuitry A
Item		Inrush Current (enlargement)	
Object		_____	






Model		PJA100F-12	
Item		Dynamic Line Regulation	
Object		_____	
		Temperature	25°C
		Testing Circuitry	A





Model		PJA100F-12	Temperature	25°C
Item		Over Voltage Protection	Testing Circuitry	A
Object		_____	Input Voltage	: 115V


Output Voltage
[2V/div]



Load : 0%
Oversvoltage protection
value : 15.5V


Time
[40ms/div]

Output Voltage
[2V/div]



Load : 100%
Oversvoltage protection
value : 15.5V


Time
[20ms/div]





Model		PJA100F-12	Temperature	25°C
Item		Hiccup cycle (by Overcurrent Protection)	Testing Circuitry	A
Object		_____	Load	: Short

Output Current
[5A/div]



Input Voltage : 115V


Short-circuit current : 12.8A

ON Time : 44ms

Short circuit period : 333ms

Time
[200ms/div]

Output Current
[5A/div]




Input Voltage : 230V

Short-circuit current : 12.6A

ON Time : 45ms

Short circuit period : 336ms

Time
[200ms/div]





COSEL																	
Model	PJA100F-12-R	Temperature	25°C														
Item	Input voltage - Power consumption	Testing Circuitry	-														
Object	_____	Load :0%															
<p>1.Graph</p> <p>Power consumption [W]</p> <p>Input Voltage [V]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th>Input voltage [V]</th> <th>Power consumption [W]</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>0.01</td> </tr> <tr> <td>100</td> <td>0.02</td> </tr> <tr> <td>115</td> <td>0.03</td> </tr> <tr> <td>200</td> <td>0.12</td> </tr> <tr> <td>230</td> <td>0.17</td> </tr> <tr> <td>264</td> <td>0.23</td> </tr> </tbody> </table>		Input voltage [V]	Power consumption [W]	85	0.01	100	0.02	115	0.03	200	0.12	230	0.17	264	0.23
Input voltage [V]	Power consumption [W]																
85	0.01																
100	0.02																
115	0.03																
200	0.12																
230	0.17																
264	0.23																
<p>Reducing standby power is possible by OFF signal of the remote control.</p>																	




Figure A