



DATA SHEET		Date	03-Aug-18
Model	PJA1500F-12	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Kaku




Frequency MHz	Line Phase	Level dB(μV)		Limit dB(μV)		Margin dB		Pass/Fail	Remark
		QP	AV	QP	AV	QP	AV		
0.19	VA	60.7	56.6	79.0	66.0	18.3	9.4	Pass	
0.19	VB	60.4	56.5	79.0	66.0	18.6	9.5	Pass	
19.77	VB	55.7	49.7	73.0	60.0	17.3	10.3	Pass	
19.99	VA	52.7	43.4	73.0	60.0	20.3	16.6	Pass	



Frequency MHz	Polarization	Stability	Reading dB(μV)	Limit dB(μV/m)	Margin dB(μV/m)	Pass/Fail	Height cm	Angle deg	Remark
			QP	QP	QP				
78.93	V	Stable	37.9	50.0	12.1	Pass	122	54	
186.99	V	Stable	41.3	50.0	8.7	Pass	103	246	
210.42	H	Stable	33.2	50.0	16.8	Pass	157	234	

DATA SHEET		Date	03-Aug-18
Model	Circuit used for measurement	Temp.	25 degreeC
Test	EMI Line conduction & Radiated emission	Humid.	40 %RH
		Tested by	Kaku

1. Line conduction



2. Radiated emission

