



EXTRA TEST DATA OF PJA300F-15

Regulated DC Power Supply
Nov 20, 2021

COSEL CO.,LTD.






CONTENTS

1.Inrush Current (enlargement)	1
2.Dynamic Line Regulation	2
3.Overvoltage Protection (waveform)	3
4.Hiccup cycle (by Overcurrent Protection)	4
5.Power Consumption (by Input Voltage)	5
6.Figure of Testing Circuitry	6

(Final Page 6)




COSEL

Model	PJA300F-15	Temperature	25°C
Item	Inrush Current (enlargement)	Testing Circuitry	A
Object	<hr/>		






COSEL

Model	PJA300F-15	Temperature	25°C
Item	Dynamic Line Regulation	Testing Circuitry	A
Object	<hr/>		






COSEL

Model	PJA300F-15	Temperature	25°C
Item	Over Voltage Protection	Testing Circuitry	A
Object	Input Voltage : 100V		


Output
Voltage
[5V/div]Load : 0%
Overvoltage protection
value : 20.1VTime
[40ms/div]Output
Voltage
[5V/div]Load : 100%
Overvoltage protection
value : 20.1VTime
[20ms/div]

COSEL

Model	PJA300F-15	Temperature	25°C
Item	Hiccup cycle (by Overcurrent Protection)	Testing Circuitry	A
Object	_____	Load	: Short

Output
Current
[10A/div]Output
Current
[10A/div]

COSEL

Model	PJA300F-15-R	Temperature	25°C																												
Item	Input voltage - Power consumption	Testing Circuitry	-																												
Object	_____	Load	: 0%																												
1. Graph			2. Values																												
 <table border="1"> <thead> <tr> <th>Input voltage [V]</th> <th>Power consumption [W]</th> </tr> </thead> <tbody> <tr><td>85</td><td>0.09</td></tr> <tr><td>100</td><td>0.18</td></tr> <tr><td>115</td><td>0.23</td></tr> <tr><td>200</td><td>0.47</td></tr> <tr><td>230</td><td>0.61</td></tr> <tr><td>264</td><td>0.80</td></tr> </tbody> </table>			Input voltage [V]	Power consumption [W]	85	0.09	100	0.18	115	0.23	200	0.47	230	0.61	264	0.80	<table border="1"> <thead> <tr> <th>Input voltage [V]</th> <th>Power consumption [W]</th> </tr> </thead> <tbody> <tr><td>85</td><td>0.09</td></tr> <tr><td>100</td><td>0.18</td></tr> <tr><td>115</td><td>0.23</td></tr> <tr><td>200</td><td>0.47</td></tr> <tr><td>230</td><td>0.61</td></tr> <tr><td>264</td><td>0.80</td></tr> </tbody> </table>	Input voltage [V]	Power consumption [W]	85	0.09	100	0.18	115	0.23	200	0.47	230	0.61	264	0.80
Input voltage [V]	Power consumption [W]																														
85	0.09																														
100	0.18																														
115	0.23																														
200	0.47																														
230	0.61																														
264	0.80																														
Input voltage [V]	Power consumption [W]																														
85	0.09																														
100	0.18																														
115	0.23																														
200	0.47																														
230	0.61																														
264	0.80																														
<p>Reducing standby power is possible by OFF signal of the remote control.</p>																															


COSEL

Figure A