

TEST DATA OF PJA300F-5

Regulated DC Power Supply
August 4, 2017

Approved by : Yukihiro Takehashi
Yukihiro Takehashi Design Manager

Prepared by : Atsushi Nishikawa
Atsushi Nishikawa Design Engineer

COSEL CO.,LTD.



CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 25)



COSEL																																																						
Model	PJA300F-5	Temperature	25°C																																																			
Item	Input Current (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V</p> <p>- -□- - Input Volt. 115V</p> <p>- -○- - Input Volt. 230V</p> <p style="text-align: center;">Input Current [A]</p> <p style="text-align: center;">Load Current [A]</p>	2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.112</td><td>0.105</td><td>0.101</td></tr> <tr><td>8</td><td>0.699</td><td>0.611</td><td>0.349</td></tr> <tr><td>16</td><td>1.170</td><td>1.020</td><td>0.548</td></tr> <tr><td>24</td><td>1.672</td><td>1.461</td><td>0.759</td></tr> <tr><td>32</td><td>2.207</td><td>1.906</td><td>0.978</td></tr> <tr><td>40</td><td>2.742</td><td>2.384</td><td>1.209</td></tr> <tr><td>48</td><td>3.326</td><td>2.873</td><td>1.443</td></tr> <tr><td>50</td><td>3.466</td><td>2.995</td><td>1.502</td></tr> <tr><td>55</td><td>3.825</td><td>3.316</td><td>1.652</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	0.112	0.105	0.101	8	0.699	0.611	0.349	16	1.170	1.020	0.548	24	1.672	1.461	0.759	32	2.207	1.906	0.978	40	2.742	2.384	1.209	48	3.326	2.873	1.443	50	3.466	2.995	1.502	55	3.825	3.316	1.652	--	-	-	-	--	-	-	-	
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0	0.112	0.105	0.101																																																			
8	0.699	0.611	0.349																																																			
16	1.170	1.020	0.548																																																			
24	1.672	1.461	0.759																																																			
32	2.207	1.906	0.978																																																			
40	2.742	2.384	1.209																																																			
48	3.326	2.873	1.443																																																			
50	3.466	2.995	1.502																																																			
55	3.825	3.316	1.652																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																					




<p>Model PJA300F-5</p>		<p>Temperature 25°C</p>																																																				
<p>Item Input Power (by Load Current)</p>		<p>Testing Circuitry Figure A</p>																																																				
<p>Object _____</p>																																																						
<p>1. Graph</p> <p> —△— Input Volt. 100V - - - □ - - - Input Volt. 115V - · - ○ - · - - Input Volt. 230V </p> <p>Input Power [W]</p> <p>Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>8.0</td><td>8.3</td><td>8.3</td></tr> <tr><td>8</td><td>64.7</td><td>64.3</td><td>64.3</td></tr> <tr><td>16</td><td>112.0</td><td>109.7</td><td>109.4</td></tr> <tr><td>24</td><td>162.8</td><td>158.3</td><td>158.1</td></tr> <tr><td>32</td><td>216.7</td><td>209.0</td><td>207.9</td></tr> <tr><td>40</td><td>270.7</td><td>261.1</td><td>260.0</td></tr> <tr><td>48</td><td>329.2</td><td>315.9</td><td>314.4</td></tr> <tr><td>50</td><td>343.3</td><td>329.6</td><td>328.1</td></tr> <tr><td>55</td><td>379.5</td><td>364.9</td><td>362.9</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	8.0	8.3	8.3	8	64.7	64.3	64.3	16	112.0	109.7	109.4	24	162.8	158.3	158.1	32	216.7	209.0	207.9	40	270.7	261.1	260.0	48	329.2	315.9	314.4	50	343.3	329.6	328.1	55	379.5	364.9	362.9	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0	8.0	8.3	8.3																																																			
8	64.7	64.3	64.3																																																			
16	112.0	109.7	109.4																																																			
24	162.8	158.3	158.1																																																			
32	216.7	209.0	207.9																																																			
40	270.7	261.1	260.0																																																			
48	329.2	315.9	314.4																																																			
50	343.3	329.6	328.1																																																			
55	379.5	364.9	362.9																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						



Model	PJA300F-5
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
85	74.0	72.5 ※1
100	75.3	73.8
115	75.4	74.7
200	77.0	76.6
230	77.0	77.0
264	77.3	77.2
280	77.2	77.2
--	-	-
--	-	-

※1: Load 80%

Note: Slanted line shows the range of the rated input voltage.



Model		PJA300F-5		Temperature 25°C																																																				
Item		Efficiency (by Load Current)		Testing Circuitry Figure A																																																				
Object		_____																																																						
1.Graph		—△— Input Volt. 100V - - □ - - Input Volt. 115V - - ○ - - Input Volt. 230V		2.Values																																																				
				<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8</td><td>62.7</td><td>63.1</td><td>63.2</td></tr> <tr><td>16</td><td>72.4</td><td>72.8</td><td>74.1</td></tr> <tr><td>24</td><td>74.7</td><td>75.2</td><td>76.9</td></tr> <tr><td>32</td><td>74.7</td><td>75.7</td><td>77.9</td></tr> <tr><td>40</td><td>74.7</td><td>75.0</td><td>77.8</td></tr> <tr><td>48</td><td>73.6</td><td>74.4</td><td>77.1</td></tr> <tr><td>50</td><td>73.6</td><td>74.3</td><td>77.0</td></tr> <tr><td>55</td><td>73.1</td><td>73.6</td><td>76.5</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	-	-	-	8	62.7	63.1	63.2	16	72.4	72.8	74.1	24	74.7	75.2	76.9	32	74.7	75.7	77.9	40	74.7	75.0	77.8	48	73.6	74.4	77.1	50	73.6	74.3	77.0	55	73.1	73.6	76.5	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																							
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																					
0	-	-	-																																																					
8	62.7	63.1	63.2																																																					
16	72.4	72.8	74.1																																																					
24	74.7	75.2	76.9																																																					
32	74.7	75.7	77.9																																																					
40	74.7	75.0	77.8																																																					
48	73.6	74.4	77.1																																																					
50	73.6	74.3	77.0																																																					
55	73.1	73.6	76.5																																																					
--	-	-	-																																																					
--	-	-	-																																																					
Note: Slanted line shows the range of the rated load current.																																																								






COSEL																																			
Model	PJA300F-5	Temperature	25°C																																
Item	Power Factor (by Input Voltage)	Testing Circuitry	Figure A																																
Object	_____																																		
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>0.980</td> <td>0.993 ※1</td> </tr> <tr> <td>100</td> <td>0.975</td> <td>0.988</td> </tr> <tr> <td>115</td> <td>0.962</td> <td>0.985</td> </tr> <tr> <td>200</td> <td>0.920</td> <td>0.960</td> </tr> <tr> <td>230</td> <td>0.909</td> <td>0.949</td> </tr> <tr> <td>264</td> <td>0.887</td> <td>0.934</td> </tr> <tr> <td>280</td> <td>0.877</td> <td>0.928</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p style="text-align: right;">※1: Load 80%</p>		Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.980	0.993 ※1	100	0.975	0.988	115	0.962	0.985	200	0.920	0.960	230	0.909	0.949	264	0.887	0.934	280	0.877	0.928	--	-	-	--	-	-
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
85	0.980	0.993 ※1																																	
100	0.975	0.988																																	
115	0.962	0.985																																	
200	0.920	0.960																																	
230	0.909	0.949																																	
264	0.887	0.934																																	
280	0.877	0.928																																	
--	-	-																																	
--	-	-																																	
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



COSEL																																																						
Model	PJA300F-5	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
<p>1.Graph</p> <p> \triangle Input Volt. 100V \square Input Volt. 115V \circ Input Volt. 230V </p> <p style="text-align: center;">Load Current [A]</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.718</td><td>0.430</td><td>0.360</td></tr> <tr><td>8</td><td>0.924</td><td>0.831</td><td>0.799</td></tr> <tr><td>16</td><td>0.955</td><td>0.895</td><td>0.868</td></tr> <tr><td>24</td><td>0.972</td><td>0.920</td><td>0.906</td></tr> <tr><td>32</td><td>0.980</td><td>0.939</td><td>0.924</td></tr> <tr><td>40</td><td>0.986</td><td>0.947</td><td>0.934</td></tr> <tr><td>48</td><td>0.988</td><td>0.958</td><td>0.946</td></tr> <tr><td>50</td><td>0.988</td><td>0.960</td><td>0.949</td></tr> <tr><td>55</td><td>0.991</td><td>0.966</td><td>0.955</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	0.718	0.430	0.360	8	0.924	0.831	0.799	16	0.955	0.895	0.868	24	0.972	0.920	0.906	32	0.980	0.939	0.924	40	0.986	0.947	0.934	48	0.988	0.958	0.946	50	0.988	0.960	0.949	55	0.991	0.966	0.955	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0	0.718	0.430	0.360																																																			
8	0.924	0.831	0.799																																																			
16	0.955	0.895	0.868																																																			
24	0.972	0.920	0.906																																																			
32	0.980	0.939	0.924																																																			
40	0.986	0.947	0.934																																																			
48	0.988	0.958	0.946																																																			
50	0.988	0.960	0.949																																																			
55	0.991	0.966	0.955																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						



COSEL			
Model	PJA300F-5	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





COSEL		Temperature 25°C Testing Circuitry Figure B
Model	PJA300F-5	
Item	Leakage Current	
Object	_____	

1.Results

Standards	Testing Circuitry	Measuring Method	Input Volt.			Note
			100 [V]	115 [V]	240 [V]	
DEN-AN	Figure B-1	Both phases	0.13	0.15	0.33	Operation
		One of phases	0.24	0.27	0.60	Stand by
IEC62368-1	Figure B-2	Both phases	0.14	0.16	0.35	Operation
		One of phases	0.25	0.29	0.65	Stand by
	Figure B-3	Both phases	0.14	0.16	0.32	Operation
		One of phases	0.24	0.27	0.59	Stand by

The value for "One of phases" is the reference value only.

2.Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.



Model	PJA300F-5
Item	Line Regulation
Object	+5V50A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	5.073	5.057 ※1
100	5.073	5.057
115	5.073	5.057
200	5.073	5.057
230	5.073	5.057
264	5.073	5.058
280	5.073	5.058
--	-	-
--	-	-

※1: Load 80%

Note: Slanted line shows the range of the rated input voltage.




Model		PJA300F-5		Temperature 25°C																																																				
Item		Load Regulation		Testing Circuitry Figure A																																																				
Object		+5V50A																																																						
1.Graph			2.Values																																																					
<p> —△— Input Volt. 100V - - - □ - - - Input Volt. 115V - · - ○ - · - - Input Volt. 230V </p> <p>Note: Slanted line shows the range of the rated load current.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>5.090</td><td>5.091</td><td>5.090</td></tr> <tr><td>8</td><td>5.084</td><td>5.085</td><td>5.085</td></tr> <tr><td>16</td><td>5.079</td><td>5.080</td><td>5.080</td></tr> <tr><td>24</td><td>5.074</td><td>5.075</td><td>5.075</td></tr> <tr><td>32</td><td>5.069</td><td>5.069</td><td>5.069</td></tr> <tr><td>40</td><td>5.064</td><td>5.064</td><td>5.064</td></tr> <tr><td>48</td><td>5.058</td><td>5.059</td><td>5.059</td></tr> <tr><td>50</td><td>5.057</td><td>5.057</td><td>5.058</td></tr> <tr><td>55</td><td>5.054</td><td>5.054</td><td>5.054</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	5.090	5.091	5.090	8	5.084	5.085	5.085	16	5.079	5.080	5.080	24	5.074	5.075	5.075	32	5.069	5.069	5.069	40	5.064	5.064	5.064	48	5.058	5.059	5.059	50	5.057	5.057	5.058	55	5.054	5.054	5.054	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																							
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																					
0	5.090	5.091	5.090																																																					
8	5.084	5.085	5.085																																																					
16	5.079	5.080	5.080																																																					
24	5.074	5.075	5.075																																																					
32	5.069	5.069	5.069																																																					
40	5.064	5.064	5.064																																																					
48	5.058	5.059	5.059																																																					
50	5.057	5.057	5.058																																																					
55	5.054	5.054	5.054																																																					
--	-	-	-																																																					
--	-	-	-																																																					



Model		PJA300F-5	Temperature		25° C
Item		Dynamic Load Response	Testing Circuitry		Figure A
Object		+5V50A			


Input Volt. 100 V
Cycle 1000 ms

Response. $t_1=t_2=50\mu\text{s}$. Typ




Min. Load (0A) ←→
Load 100% (50A)

200 mV/div




20ms/div




20ms/div

Min. Load (0A) ←→
Load 50% (25A)

200 mV/div



20ms/div



20ms/div



<p>Model PJA300F-5</p>		<p>Temperature 25°C Testing Circuitry Figure C</p>																																						
<p>Item Ripple Voltage (by Load Current)</p>																																								
<p>Object +5V50A</p>																																								
<p>1.Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 100V -·-○-·- Input Volt. 230V</p> </div>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>10</td><td>15</td></tr> <tr><td>8</td><td>10</td><td>15</td></tr> <tr><td>16</td><td>10</td><td>15</td></tr> <tr><td>24</td><td>15</td><td>20</td></tr> <tr><td>32</td><td>15</td><td>20</td></tr> <tr><td>40</td><td>15</td><td>20</td></tr> <tr><td>48</td><td>20</td><td>25</td></tr> <tr><td>50</td><td>20</td><td>25</td></tr> <tr><td>55</td><td>25</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 230 [V]	0	10	15	8	10	15	16	10	15	24	15	20	32	15	20	40	15	20	48	20	25	50	20	25	55	25	30	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 230 [V]																																						
0	10	15																																						
8	10	15																																						
16	10	15																																						
24	15	20																																						
32	15	20																																						
40	15	20																																						
48	20	25																																						
50	20	25																																						
55	25	30																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																								
<div style="text-align: center;"> <p>T1: Due to AC Input Line T2: Due to Switching</p> </div>																																								
<p>Fig. Complex Ripple Wave Form</p>																																								




COSEL																																									
Model	PJA300F-5	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure C																																						
Object	+5V50A																																								
<p>1. Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 100V</p> <p>- -○- - Input Volt. 230V</p> </div> <p style="text-align: center;">Ripple-Noise [mV]</p> <p style="text-align: center;">Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>15</td><td>15</td></tr> <tr><td>8</td><td>15</td><td>15</td></tr> <tr><td>16</td><td>15</td><td>15</td></tr> <tr><td>24</td><td>20</td><td>20</td></tr> <tr><td>32</td><td>20</td><td>20</td></tr> <tr><td>40</td><td>20</td><td>25</td></tr> <tr><td>48</td><td>25</td><td>25</td></tr> <tr><td>50</td><td>25</td><td>30</td></tr> <tr><td>55</td><td>30</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 230 [V]	0	15	15	8	15	15	16	15	15	24	20	20	32	20	20	40	20	25	48	25	25	50	25	30	55	30	30	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 100 [V]	Input Volt. 230 [V]																																							
0	15	15																																							
8	15	15																																							
16	15	15																																							
24	20	20																																							
32	20	20																																							
40	20	25																																							
48	25	25																																							
50	25	30																																							
55	30	30																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																									
<div style="text-align: center;"> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Ripple-Noise [mVp-p]</p> <p style="text-align: center;">T1</p> <p style="text-align: center;">T2</p> </div> <p style="text-align: center;">Fig. Complex Ripple Wave Form</p>																																									



Model	PJA300F-5
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V50A

Testing Circuitry Figure C

1. Graph



2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 230 [V]
-30	90	90
-10	45	45
0	40	40
25	30	30
50	25	25
60	10	10
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-



COSEL																																																					
Model	PJA300F-5																																																				
Item	Ambient Temperature Drift	Testing Circuitry Figure A																																																			
Object	+5V50A																																																				
<p>1. Graph</p> <p> \triangle Input Volt. 100V \square Input Volt. 115V \circ Input Volt. 230V </p> <p style="text-align: center;">Ambient Temperature [°C]</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>5.046</td><td>5.046</td><td>5.047</td></tr> <tr><td>-10</td><td>5.050</td><td>5.050</td><td>5.051</td></tr> <tr><td>0</td><td>5.052</td><td>5.052</td><td>5.053</td></tr> <tr><td>10</td><td>5.054</td><td>5.054</td><td>5.055</td></tr> <tr><td>25</td><td>5.056</td><td>5.056</td><td>5.056</td></tr> <tr><td>50</td><td>5.057</td><td>5.057</td><td>5.057</td></tr> <tr><td>60</td><td>5.057</td><td>5.057</td><td>5.057</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	-30	5.046	5.046	5.047	-10	5.050	5.050	5.051	0	5.052	5.052	5.053	10	5.054	5.054	5.055	25	5.056	5.056	5.056	50	5.057	5.057	5.057	60	5.057	5.057	5.057	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																				
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																		
-30	5.046	5.046	5.047																																																		
-10	5.050	5.050	5.051																																																		
0	5.052	5.052	5.053																																																		
10	5.054	5.054	5.055																																																		
25	5.056	5.056	5.056																																																		
50	5.057	5.057	5.057																																																		
60	5.057	5.057	5.057																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		



COSEL		
Model	PJA300F-5	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+5V50A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 100 - 264V

Load Current : 0 - 50A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

* Output Voltage Accuracy (Ratio) = $\frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	25	115	0	5.091	±21	±0.4
Minimum Voltage	-10	100	50	5.050		




COSEL																								
Model	PJA300F-5																							
Item	Time Lapse Drift	Temperature 25°C Testing Circuitry Figure A																						
Object	+5V50A																							
<p>1. Graph</p> <p style="text-align: center;">Time [H]</p> <p style="text-align: center;">Input Volt. 230V Load 100%</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>5.055</td></tr> <tr><td>0.5</td><td>5.059</td></tr> <tr><td>1.0</td><td>5.060</td></tr> <tr><td>2.0</td><td>5.060</td></tr> <tr><td>3.0</td><td>5.060</td></tr> <tr><td>4.0</td><td>5.061</td></tr> <tr><td>5.0</td><td>5.061</td></tr> <tr><td>6.0</td><td>5.061</td></tr> <tr><td>7.0</td><td>5.061</td></tr> <tr><td>8.0</td><td>5.061</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	5.055	0.5	5.059	1.0	5.060	2.0	5.060	3.0	5.060	4.0	5.061	5.0	5.061	6.0	5.061	7.0	5.061	8.0	5.061
Time since start [H]	Output Voltage [V]																							
0.0	5.055																							
0.5	5.059																							
1.0	5.060																							
2.0	5.060																							
3.0	5.060																							
4.0	5.061																							
5.0	5.061																							
6.0	5.061																							
7.0	5.061																							
8.0	5.061																							
<p>* The characteristic of AC100V is equal.</p>																								




Model	PJA300F-5	Temperature	25°C
Item	Rise and Fall Time	Testing Circuitry	Figure A
Object	+5V50A		

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf
100 V		206.0	2.5	208.5	38.8	2.7
230 V		171.0	2.0	173.0	45.5	2.7





COSEL																																		
Model	PJA300F-5																																	
Item	Hold-Up Time	Temperature 25°C Testing Circuitry Figure A																																
Object	+5V50A																																	
<p>1.Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>85</td><td>78</td><td>38 ※1</td></tr> <tr><td>100</td><td>81</td><td>39</td></tr> <tr><td>115</td><td>84</td><td>40</td></tr> <tr><td>200</td><td>92</td><td>44</td></tr> <tr><td>230</td><td>94</td><td>46</td></tr> <tr><td>264</td><td>96</td><td>48</td></tr> <tr><td>280</td><td>97</td><td>48</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p style="text-align: right;">※1: Load 80%</p>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	78	38 ※1	100	81	39	115	84	40	200	92	44	230	94	46	264	96	48	280	97	48	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																	
	Load 50%	Load 100%																																
85	78	38 ※1																																
100	81	39																																
115	84	40																																
200	92	44																																
230	94	46																																
264	96	48																																
280	97	48																																
--	-	-																																
--	-	-																																
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																		



<p>Model PJA300F-5</p>		<p>Temperature 25°C</p>																																																				
<p>Item Instantaneous Interruption Compensation</p>		<p>Testing Circuitry Figure A</p>																																																				
<p>Object +5V50A</p>																																																						
<p>1. Graph</p> <p> —△— Input Volt. 100V - - - □ - - Input Volt. 115V ···○··· Input Volt. 230V </p> <p>Instantaneous Compensation Time [ms]</p> <p>Load Current [A]</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8</td><td>229</td><td>232</td><td>263</td></tr> <tr><td>16</td><td>121</td><td>122</td><td>146</td></tr> <tr><td>24</td><td>79</td><td>80</td><td>97</td></tr> <tr><td>32</td><td>63</td><td>65</td><td>73</td></tr> <tr><td>40</td><td>48</td><td>48</td><td>57</td></tr> <tr><td>48</td><td>39</td><td>39</td><td>48</td></tr> <tr><td>50</td><td>38</td><td>39</td><td>46</td></tr> <tr><td>55</td><td>34</td><td>35</td><td>40</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	-	-	-	8	229	232	263	16	121	122	146	24	79	80	97	32	63	65	73	40	48	48	57	48	39	39	48	50	38	39	46	55	34	35	40	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0	-	-	-																																																			
8	229	232	263																																																			
16	121	122	146																																																			
24	79	80	97																																																			
32	63	65	73																																																			
40	48	48	57																																																			
48	39	39	48																																																			
50	38	39	46																																																			
55	34	35	40																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						



COSEL																																								
Model	PJA300F-5																																							
Item	Minimum Input Voltage for Regulated Output Voltage	Testing Circuitry Figure A																																						
Object	+5V50A																																							
<p>1. Graph</p> <p style="text-align: right;"> ---□--- Load 50% —△— Load 100% </p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>-30</td><td>36</td><td>53</td></tr> <tr><td>-10</td><td>36</td><td>53</td></tr> <tr><td>0</td><td>36</td><td>53</td></tr> <tr><td>25</td><td>36</td><td>52</td></tr> <tr><td>50</td><td>36</td><td>53</td></tr> <tr><td>60</td><td>36</td><td>53</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-30	36	53	-10	36	53	0	36	53	25	36	52	50	36	53	60	36	53	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-30	36	53																																						
-10	36	53																																						
0	36	53																																						
25	36	52																																						
50	36	53																																						
60	36	53																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								



COSEL																																												
Model	PJA300F-5	Temperature	25°C																																									
Item	Overcurrent Protection	Testing Circuitry	Figure A																																									
Object	+5V50A																																											
<p>1.Graph</p> <div style="text-align: center;"> <p>————— Input Volt. 100V</p> <p>————— Input Volt. 230V</p> </div> <p>Note: Slanted line shows the range of the rated load current.</p>		<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>4.75</td><td>64.32</td><td>63.61</td></tr> <tr><td>4.50</td><td>64.51</td><td>63.86</td></tr> <tr><td>4.00</td><td>64.89</td><td>64.30</td></tr> <tr><td>3.50</td><td>65.27</td><td>64.73</td></tr> <tr><td>3.00</td><td>65.70</td><td>65.20</td></tr> <tr><td>2.50</td><td>66.16</td><td>65.69</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	4.75	64.32	63.61	4.50	64.51	63.86	4.00	64.89	64.30	3.50	65.27	64.73	3.00	65.70	65.20	2.50	66.16	65.69	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																											
	Input Volt. 100[V]	Input Volt. 230[V]																																										
4.75	64.32	63.61																																										
4.50	64.51	63.86																																										
4.00	64.89	64.30																																										
3.50	65.27	64.73																																										
3.00	65.70	65.20																																										
2.50	66.16	65.69																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										
--	-	-																																										



COSEL																																								
Model	PJA300F-5																																							
Item	Overvoltage Protection	Testing Circuitry Figure A																																						
Object	+5V50A																																							
<p>1. Graph</p> <div style="text-align: right;"> <p>—△— Input Volt. 100V</p> <p>---□--- Input Volt. 230V</p> </div> <p style="text-align: center;">Ambient Temperature [°C]</p> <p style="text-align: right;">Load 0%</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>-30</td><td>6.68</td><td>6.67</td></tr> <tr><td>-10</td><td>6.62</td><td>6.67</td></tr> <tr><td>0</td><td>6.67</td><td>6.67</td></tr> <tr><td>10</td><td>6.61</td><td>6.67</td></tr> <tr><td>25</td><td>6.67</td><td>6.67</td></tr> <tr><td>50</td><td>6.67</td><td>6.67</td></tr> <tr><td>60</td><td>6.67</td><td>6.67</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 100[V]	Input Volt. 230[V]	-30	6.68	6.67	-10	6.62	6.67	0	6.67	6.67	10	6.61	6.67	25	6.67	6.67	50	6.67	6.67	60	6.67	6.67	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Operating Point [V]																																							
	Input Volt. 100[V]	Input Volt. 230[V]																																						
-30	6.68	6.67																																						
-10	6.62	6.67																																						
0	6.67	6.67																																						
10	6.61	6.67																																						
25	6.67	6.67																																						
50	6.67	6.67																																						
60	6.67	6.67																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						




Figure A




Figure B-1 (DEN-AN)




Figure B-2 (IEC62368-1 refer to IEC60990 Fig.4)





Figure B-3 (IEC62368-1 refer to IEC60990 Fig.5)



C1= 0.1 μF
(Ceramic capacitor)

C2= 22 μF
(Electrolytic capacitor)

Figure C