



TEST DATA OF PJMA1000F-12

Regulated DC Power Supply
January 25, 2021

Approved by :

A handwritten signature in black ink that reads "Takashi Kajii".

Takashi Kajii

Design Manager

Prepared by :

A handwritten signature in black ink that reads "Ryo Takahashi".

Ryo Takahashi

Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Ovvervoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	PJMA1000F-12
Item	Input Current (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.0	0.144	0.147	0.213
15.0	2.418	2.108	1.155
30.0	4.526	3.924	2.029
45.0	6.710	5.804	2.927
60.0	8.940	7.720	3.843
75.0	11.280	9.670	4.771
84.0	12.760	10.900	5.333
92.4	-	12.070	5.864
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.


COSEL

Model	PJMA1000F-12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Input Power (by Load Current)																																																					
Object																																																						
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 115V - · ○ · - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Power [W] (100V)</th> <th>Input Power [W] (115V)</th> <th>Input Power [W] (230V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>7</td><td>6</td><td>6</td></tr> <tr><td>15.0</td><td>238</td><td>237</td><td>233</td></tr> <tr><td>30.0</td><td>450</td><td>447</td><td>439</td></tr> <tr><td>45.0</td><td>669</td><td>664</td><td>649</td></tr> <tr><td>60.0</td><td>893</td><td>885</td><td>862</td></tr> <tr><td>75.0</td><td>1125</td><td>1111</td><td>1078</td></tr> <tr><td>84.0</td><td>1267</td><td>1250</td><td>1208</td></tr> <tr><td>92.4</td><td>-</td><td>1380</td><td>1330</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W] (100V)	Input Power [W] (115V)	Input Power [W] (230V)	0.0	7	6	6	15.0	238	237	233	30.0	450	447	439	45.0	669	664	649	60.0	893	885	862	75.0	1125	1111	1078	84.0	1267	1250	1208	92.4	-	1380	1330	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Input Power [W] (100V)	Input Power [W] (115V)	Input Power [W] (230V)																																																			
0.0	7	6	6																																																			
15.0	238	237	233																																																			
30.0	450	447	439																																																			
45.0	669	664	649																																																			
60.0	893	885	862																																																			
75.0	1125	1111	1078																																																			
84.0	1267	1250	1208																																																			
92.4	-	1380	1330																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>7</td><td>6</td><td>6</td></tr> <tr><td>15.0</td><td>238</td><td>237</td><td>233</td></tr> <tr><td>30.0</td><td>450</td><td>447</td><td>439</td></tr> <tr><td>45.0</td><td>669</td><td>664</td><td>649</td></tr> <tr><td>60.0</td><td>893</td><td>885</td><td>862</td></tr> <tr><td>75.0</td><td>1125</td><td>1111</td><td>1078</td></tr> <tr><td>84.0</td><td>1267</td><td>1250</td><td>1208</td></tr> <tr><td>92.4</td><td>-</td><td>1380</td><td>1330</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	7	6	6	15.0	238	237	233	30.0	450	447	439	45.0	669	664	649	60.0	893	885	862	75.0	1125	1111	1078	84.0	1267	1250	1208	92.4	-	1380	1330	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	7	6	6																																																			
15.0	238	237	233																																																			
30.0	450	447	439																																																			
45.0	669	664	649																																																			
60.0	893	885	862																																																			
75.0	1125	1111	1078																																																			
84.0	1267	1250	1208																																																			
92.4	-	1380	1330																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PJMA1000F-12
Item	Efficiency (by Input Voltage)
Object	_____

1.Graph



Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
85	81.6	80.6 ※1
100	82.4	81.7 ※2
115	83.0	82.4
170	84.2	84.3
200	84.5	85.0
230	84.8	85.3
264	85.1	85.7
280	85.3	85.9
--	-	-

※1: Load 80%

※2: Load 90%

Note: Slanted line shows the range of the rated input voltage.

COSEL


Model	PJMA1000F-12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>The graph shows efficiency increasing with load current for all input voltages. The 100V curve is the highest, followed by 115V, and then 230V. A vertical slanted line is drawn through the curves at approximately 85A, indicating the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [115V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>77.5</td><td>77.7</td><td>79.0</td></tr> <tr><td>15.0</td><td>81.8</td><td>82.3</td><td>83.8</td></tr> <tr><td>30.0</td><td>82.5</td><td>83.0</td><td>85.0</td></tr> <tr><td>45.0</td><td>82.3</td><td>83.1</td><td>85.3</td></tr> <tr><td>60.0</td><td>81.7</td><td>82.8</td><td>85.3</td></tr> <tr><td>75.0</td><td>81.3</td><td>82.4</td><td>85.3</td></tr> <tr><td>84.0</td><td>-</td><td>82.1</td><td>85.2</td></tr> <tr><td>92.4</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [100V] (%)	Efficiency [115V] (%)	Efficiency [230V] (%)	0.0	77.5	77.7	79.0	15.0	81.8	82.3	83.8	30.0	82.5	83.0	85.0	45.0	82.3	83.1	85.3	60.0	81.7	82.8	85.3	75.0	81.3	82.4	85.3	84.0	-	82.1	85.2	92.4	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Efficiency [100V] (%)	Efficiency [115V] (%)	Efficiency [230V] (%)																																																			
0.0	77.5	77.7	79.0																																																			
15.0	81.8	82.3	83.8																																																			
30.0	82.5	83.0	85.0																																																			
45.0	82.3	83.1	85.3																																																			
60.0	81.7	82.8	85.3																																																			
75.0	81.3	82.4	85.3																																																			
84.0	-	82.1	85.2																																																			
92.4	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>15.0</td><td>77.5</td><td>77.7</td><td>79.0</td></tr> <tr><td>30.0</td><td>81.8</td><td>82.3</td><td>83.8</td></tr> <tr><td>45.0</td><td>82.5</td><td>83.0</td><td>85.0</td></tr> <tr><td>60.0</td><td>82.3</td><td>83.1</td><td>85.3</td></tr> <tr><td>75.0</td><td>81.7</td><td>82.8</td><td>85.3</td></tr> <tr><td>84.0</td><td>81.3</td><td>82.4</td><td>85.3</td></tr> <tr><td>92.4</td><td>-</td><td>82.1</td><td>85.2</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	-	-	-	15.0	77.5	77.7	79.0	30.0	81.8	82.3	83.8	45.0	82.5	83.0	85.0	60.0	82.3	83.1	85.3	75.0	81.7	82.8	85.3	84.0	81.3	82.4	85.3	92.4	-	82.1	85.2	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
15.0	77.5	77.7	79.0																																																			
30.0	81.8	82.3	83.8																																																			
45.0	82.5	83.0	85.0																																																			
60.0	82.3	83.1	85.3																																																			
75.0	81.7	82.8	85.3																																																			
84.0	81.3	82.4	85.3																																																			
92.4	-	82.1	85.2																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PJMA1000F-12
Item	Power Factor (by Input Voltage)
Object	_____

1.Graph


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
85	0.997	0.996 ※1
100	0.996	0.996 ※2
115	0.995	0.996
170	0.982	0.994
200	0.974	0.989
230	0.960	0.985
264	0.936	0.973
280	0.920	0.965
--	-	-

※1: Load 80%

※2: Load 90%




Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PJMA1000F-12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Power Factor (by Load Current)																																																					
Object																																																						
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 115V - · -○- - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Power Factor (100V)</th> <th>Power Factor (115V)</th> <th>Power Factor (230V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.453</td><td>0.375</td><td>0.129</td></tr> <tr><td>15.0</td><td>0.983</td><td>0.978</td><td>0.878</td></tr> <tr><td>30.0</td><td>0.994</td><td>0.992</td><td>0.940</td></tr> <tr><td>45.0</td><td>0.997</td><td>0.995</td><td>0.963</td></tr> <tr><td>60.0</td><td>0.998</td><td>0.997</td><td>0.975</td></tr> <tr><td>75.0</td><td>0.996</td><td>0.998</td><td>0.983</td></tr> <tr><td>84.0</td><td>0.993</td><td>0.997</td><td>0.985</td></tr> <tr><td>92.4</td><td>-</td><td>0.994</td><td>0.987</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor (100V)	Power Factor (115V)	Power Factor (230V)	0.0	0.453	0.375	0.129	15.0	0.983	0.978	0.878	30.0	0.994	0.992	0.940	45.0	0.997	0.995	0.963	60.0	0.998	0.997	0.975	75.0	0.996	0.998	0.983	84.0	0.993	0.997	0.985	92.4	-	0.994	0.987	--	-	-	-	--	-	-	-	--	-	-	-			
Load Current [A]	Power Factor (100V)	Power Factor (115V)	Power Factor (230V)																																																			
0.0	0.453	0.375	0.129																																																			
15.0	0.983	0.978	0.878																																																			
30.0	0.994	0.992	0.940																																																			
45.0	0.997	0.995	0.963																																																			
60.0	0.998	0.997	0.975																																																			
75.0	0.996	0.998	0.983																																																			
84.0	0.993	0.997	0.985																																																			
92.4	-	0.994	0.987																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.453</td><td>0.375</td><td>0.129</td></tr> <tr><td>15.0</td><td>0.983</td><td>0.978</td><td>0.878</td></tr> <tr><td>30.0</td><td>0.994</td><td>0.992</td><td>0.940</td></tr> <tr><td>45.0</td><td>0.997</td><td>0.995</td><td>0.963</td></tr> <tr><td>60.0</td><td>0.998</td><td>0.997</td><td>0.975</td></tr> <tr><td>75.0</td><td>0.996</td><td>0.998</td><td>0.983</td></tr> <tr><td>84.0</td><td>0.993</td><td>0.997</td><td>0.985</td></tr> <tr><td>92.4</td><td>-</td><td>0.994</td><td>0.987</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	0.453	0.375	0.129	15.0	0.983	0.978	0.878	30.0	0.994	0.992	0.940	45.0	0.997	0.995	0.963	60.0	0.998	0.997	0.975	75.0	0.996	0.998	0.983	84.0	0.993	0.997	0.985	92.4	-	0.994	0.987	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	0.453	0.375	0.129																																																			
15.0	0.983	0.978	0.878																																																			
30.0	0.994	0.992	0.940																																																			
45.0	0.997	0.995	0.963																																																			
60.0	0.998	0.997	0.975																																																			
75.0	0.996	0.998	0.983																																																			
84.0	0.993	0.997	0.985																																																			
92.4	-	0.994	0.987																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PJMA1000F-12	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	PJMA1000F-12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	<hr/>		

1. Results

Standards		Input Volt.			Note
		100 [V]	115 [V]	240 [V]	
IEC60601-1	Both phases	0.11	0.10	0.25	Operation
	One of phases	0.18	0.22	0.49	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL


Model	PJMA1000F-12																																	
Item	Line Regulation	Temperature Testing Circuitry 25°C ^{Figure A}																																
Object	+12V84A																																	
1.Graph																																		
<p>The graph plots Output Voltage [V] on the y-axis (11.00 to 13.00) against Input Voltage [V] on the x-axis (50 to 300). Two horizontal lines represent the output voltage at different load levels. A slanted line indicates the range of the rated input voltage. Data points are shown for both 50% and 100% loads.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Output Voltage [V] (Load 50%)</th> <th>Output Voltage [V] (Load 100%)</th> </tr> </thead> <tbody> <tr><td>85</td><td>12.255</td><td>12.253</td></tr> <tr><td>100</td><td>12.255</td><td>12.252</td></tr> <tr><td>115</td><td>12.254</td><td>12.252</td></tr> <tr><td>170</td><td>12.255</td><td>12.252</td></tr> <tr><td>200</td><td>12.254</td><td>12.252</td></tr> <tr><td>230</td><td>12.254</td><td>12.252</td></tr> <tr><td>264</td><td>12.254</td><td>12.252</td></tr> <tr><td>280</td><td>12.254</td><td>12.252</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Output Voltage [V] (Load 50%)	Output Voltage [V] (Load 100%)	85	12.255	12.253	100	12.255	12.252	115	12.254	12.252	170	12.255	12.252	200	12.254	12.252	230	12.254	12.252	264	12.254	12.252	280	12.254	12.252	--	-	-		
Input Voltage [V]	Output Voltage [V] (Load 50%)	Output Voltage [V] (Load 100%)																																
85	12.255	12.253																																
100	12.255	12.252																																
115	12.254	12.252																																
170	12.255	12.252																																
200	12.254	12.252																																
230	12.254	12.252																																
264	12.254	12.252																																
280	12.254	12.252																																
--	-	-																																
2.Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>85</td><td>12.255</td><td>12.253</td></tr> <tr><td>100</td><td>12.255</td><td>12.252</td></tr> <tr><td>115</td><td>12.254</td><td>12.252</td></tr> <tr><td>170</td><td>12.255</td><td>12.252</td></tr> <tr><td>200</td><td>12.254</td><td>12.252</td></tr> <tr><td>230</td><td>12.254</td><td>12.252</td></tr> <tr><td>264</td><td>12.254</td><td>12.252</td></tr> <tr><td>280</td><td>12.254</td><td>12.252</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table> <p>※1 : Load 80% ※2 : Load 90%</p>			Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	12.255	12.253	100	12.255	12.252	115	12.254	12.252	170	12.255	12.252	200	12.254	12.252	230	12.254	12.252	264	12.254	12.252	280	12.254	12.252	--	-	-
Input Voltage [V]	Output Voltage [V]																																	
	Load 50%	Load 100%																																
85	12.255	12.253																																
100	12.255	12.252																																
115	12.254	12.252																																
170	12.255	12.252																																
200	12.254	12.252																																
230	12.254	12.252																																
264	12.254	12.252																																
280	12.254	12.252																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

COSEL

Model	PJMA1000F-12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Load Regulation																																																					
Object	+12V84A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 115V</p> <p>Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>12.263</td> <td>12.262</td> <td>12.263</td> </tr> <tr> <td>15.0</td> <td>12.260</td> <td>12.259</td> <td>12.260</td> </tr> <tr> <td>30.0</td> <td>12.259</td> <td>12.259</td> <td>12.259</td> </tr> <tr> <td>45.0</td> <td>12.258</td> <td>12.258</td> <td>12.258</td> </tr> <tr> <td>60.0</td> <td>12.258</td> <td>12.257</td> <td>12.258</td> </tr> <tr> <td>75.0</td> <td>12.257</td> <td>12.256</td> <td>12.256</td> </tr> <tr> <td>84.0</td> <td>12.256</td> <td>12.256</td> <td>12.256</td> </tr> <tr> <td>92.4</td> <td>-</td> <td>12.255</td> <td>12.255</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	12.263	12.262	12.263	15.0	12.260	12.259	12.260	30.0	12.259	12.259	12.259	45.0	12.258	12.258	12.258	60.0	12.258	12.257	12.258	75.0	12.257	12.256	12.256	84.0	12.256	12.256	12.256	92.4	-	12.255	12.255	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	12.263	12.262	12.263																																																			
15.0	12.260	12.259	12.260																																																			
30.0	12.259	12.259	12.259																																																			
45.0	12.258	12.258	12.258																																																			
60.0	12.258	12.257	12.258																																																			
75.0	12.257	12.256	12.256																																																			
84.0	12.256	12.256	12.256																																																			
92.4	-	12.255	12.255																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

Model	PJMA1000F-12
Item	Dynamic Load Response
Object	+12V84A

Temperature 25°C
Testing Circuitry Figure AInput Volt. 115 V
Cycle 1000 msMin.Load (0A)↔
Load 100% (84A)

500mV/div

20 ms/div

20 ms/div

Min.Load (0A)↔
Load 50% (42A)

500mV/div

20 ms/div


20 ms/div

COSEL

Model	PJMA1000F-12
Item	Ripple Voltage (by Load Current)
Object	+12V84A

Temperature 25°C
Testing Circuitry Figure C

1.Graph




2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0.0	10	40
21.0	45	45
42.0	60	65
63.0	50	60
84.0	65	60
92.4	60	55
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.




COSEL

Model	PJMA1000F-12	Temperature Testing Circuitry	25°C Figure C																																				
Item	Ripple-Noise																																						
Object	+12V84A																																						
1. Graph			2. Values																																				
<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The Y-axis ranges from 0 to 250 mV, and the X-axis ranges from 0 to 100 A. Two curves are plotted: Input Volt. 115V (solid line with open triangles) and Input Volt. 230V (dashed line with open circles). Both curves show an increase in noise with load current, with a sharp vertical rise at approximately 85A.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 115V)</th> <th>Ripple-Noise [mV] (Input Volt. 230V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>40</td><td>40</td></tr> <tr><td>21.0</td><td>45</td><td>50</td></tr> <tr><td>42.0</td><td>60</td><td>65</td></tr> <tr><td>63.0</td><td>60</td><td>60</td></tr> <tr><td>84.0</td><td>65</td><td>70</td></tr> <tr><td>92.4</td><td>70</td><td>70</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Ripple-Noise [mV] (Input Volt. 115V)	Ripple-Noise [mV] (Input Volt. 230V)	0.0	40	40	21.0	45	50	42.0	60	65	63.0	60	60	84.0	65	70	92.4	70	70	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV] (Input Volt. 115V)	Ripple-Noise [mV] (Input Volt. 230V)																																					
0.0	40	40																																					
21.0	45	50																																					
42.0	60	65																																					
63.0	60	60																																					
84.0	65	70																																					
92.4	70	70																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
<p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig. Complex Ripple Wave Form</p>																																							

COSEL

Model	PJMA1000F-12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V84A

1. Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.


Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
-30	135	145
-20	150	135
0	90	90
25	70	65
50	50	60
60	55	55
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	PJMA1000F-12
Item	Ambient Temperature Drift
Object	+12V84A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
-30	12.098	12.098	12.097
-20	12.197	12.196	12.196
-10	12.210	12.209	12.209
0	12.223	12.223	12.224
10	12.236	12.235	12.236
25	12.249	12.249	12.250
30	12.256	12.256	12.256
40	12.263	12.263	12.263
50	12.269	12.269	12.269
60	12.270	12.270	12.271
--	-	-	-

Note: In case of Input Volt. 100V, Load 90%.
Other case Load 100%.



Model	PJMA1000F-12
Item	Output Voltage Accuracy
Object	+12V84A

Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 115 - 264V

Load Current : 0 - 84A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ratio)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$


2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ratio [%]
Maximum Voltage	50	115	0	12.276	±40	±0.3
Minimum Voltage	-20	115	84	12.196		

COSEL

Model	PJMA1000F-12
Item	Time Lapse Drift
Object	+12V84A

1.Graph


 Temperature 25°C
 Testing Circuitry Figure A


2.Values

Time since start [H]	Output Voltage [V]
0.0	12.162
0.5	12.171
1.0	12.171
2.0	12.170
3.0	12.170
4.0	12.170
5.0	12.171
6.0	12.171
7.0	12.171
8.0	12.171

COSEL

Model	PJMA1000F-12	Temperature Testing Circuitry	25°C
Item	Rise and Fall Time		Figure A
Object	+12V84A		


1.Graph



2.Values

[ms]

Input Volt.	Time	Td	Tr	Ts	Th	Tf
115 V		669.5	20.5	690.0	20.4	35.2
230 V		579.0	20.5	599.5	23.2	35.3



COSEL

Model	PJMA1000F-12	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time																																		
Object	+12V84A																																		
1.Graph			2.Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>43</td><td>25 ※1</td> </tr> <tr> <td>100</td><td>45</td><td>22 ※2</td> </tr> <tr> <td>115</td><td>46</td><td>20</td> </tr> <tr> <td>170</td><td>48</td><td>21</td> </tr> <tr> <td>200</td><td>50</td><td>22</td> </tr> <tr> <td>230</td><td>51</td><td>23</td> </tr> <tr> <td>264</td><td>52</td><td>24</td> </tr> <tr> <td>280</td><td>52</td><td>24</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table> <p>※1 : Load 80% ※2 : Load 90%</p>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	43	25 ※1	100	45	22 ※2	115	46	20	170	48	21	200	50	22	230	51	23	264	52	24	280	52	24	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	43	25 ※1																																	
100	45	22 ※2																																	
115	46	20																																	
170	48	21																																	
200	50	22																																	
230	51	23																																	
264	52	24																																	
280	52	24																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			


COSEL

Model	PJMA1000F-12	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Instantaneous Interruption Compensation																																																					
Object	+12V84A																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 115V - · ○ · - Input Volt. 230V</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>15.0</td><td>18</td><td>26</td><td>147</td></tr> <tr> <td>30.0</td><td>17</td><td>22</td><td>71</td></tr> <tr> <td>45.0</td><td>17</td><td>22</td><td>61</td></tr> <tr> <td>60.0</td><td>17</td><td>22</td><td>45</td></tr> <tr> <td>75.0</td><td>17</td><td>22</td><td>36</td></tr> <tr> <td>84.0</td><td>17</td><td>20</td><td>30</td></tr> <tr> <td>92.4</td><td>-</td><td>17</td><td>29</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.0	-	-	-	15.0	18	26	147	30.0	17	22	71	45.0	17	22	61	60.0	17	22	45	75.0	17	22	36	84.0	17	20	30	92.4	-	17	29	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
15.0	18	26	147																																																			
30.0	17	22	71																																																			
45.0	17	22	61																																																			
60.0	17	22	45																																																			
75.0	17	22	36																																																			
84.0	17	20	30																																																			
92.4	-	17	29																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					



Model	PJMA1000F-12
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V84A

1.Graph



Testing Circuitry Figure A


2.Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-30	76	78
-20	76	79
-10	75	79
0	74	79
10	73	79
25	72	78
30	71	79
40	70	79
50	70	79
60	69	80
--	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	PJMA1000F-12
Item	Overcurrent Protection
Object	+12V84A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
11.4	96.20	96.18	96.43
10.8	96.78	96.75	96.99
9.6	98.18	98.19	98.53
8.4	99.63	99.64	100.02
7.2	100.70	100.72	101.11
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	PJMA1000F-12
Item	Oversupply Protection
Object	+12V84A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt.	Input Volt.
115[V]	115[V]	230[V]
-30	15.56	15.44
-20	15.61	15.61
-10	15.61	15.61
0	15.73	15.73
10	15.84	15.84
25	16.02	16.02
30	16.02	16.02
40	16.13	16.13
50	16.25	16.25
60	16.31	16.31
--	-	-

COSEL




Figure A




Figure B (IEC60601-1)


(Ceramic capacitor)
C1= 0.1 μF (Electrolytic capacitor)
C2= 22 μF

Figure C