

TEST DATA OF PJMA300F-24

Regulated DC Power Supply
September 6, 2021

Approved by : Takashi Kajii
Design Manager

Prepared by : Ryo Takahashi
Design Engineer

COSEL CO.,LTD.




CONTENTS

1.Input Current (by Load Current)	1
2.Efficiency (by Load Current)	2
3.Power Factor (by Load Current)	3
4.Inrush Current	4
5.Leakage Current	5
6.Line Regulation	6
7.Load Regulation	7
8.Ripple-Noise	7
9.Dynamic Load Response	8
10.Rise and Fall Time	9
11.Hold-Up Time	10
12.Instantaneous Interruption Compensation	11
13.Overcurrent Protection	12
14.Ambient Temperature Drift	13
15.Minimum Input Voltage for Regulated Output Voltage	13
16.Overvoltage Protection	13
17.Figure of Testing Circuitry	14

(Final Page 14)

COSEL

Model	PJMA300F-24
Item	Input Current (by Load Current)
Object	_____



Temperature 25°C
Testing Circuitry Figure A

2. Values


Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	0.135	0.125	0.114
2.00	0.788	0.689	0.389
4.00	1.336	1.161	0.614
6.00	1.882	1.650	0.845
8.00	2.464	2.123	1.082
10.00	3.027	2.631	1.322
12.00	3.628	3.132	1.563
12.50	3.770	3.257	1.624
13.75	4.135	3.583	1.786
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PJMA300F-24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Efficiency (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>The graph shows efficiency increasing with load current for all input voltages. The 100V curve is the highest, followed by 115V, and then 230V. A slanted line from approximately (3, 67) to (12, 82) indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [115V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>3.0</td><td>67.0</td><td>66.7</td><td>66.7</td></tr> <tr><td>4.0</td><td>78.0</td><td>77.0</td><td>77.0</td></tr> <tr><td>5.0</td><td>80.0</td><td>79.0</td><td>81.0</td></tr> <tr><td>6.0</td><td>81.0</td><td>80.0</td><td>82.0</td></tr> <tr><td>8.0</td><td>82.0</td><td>81.0</td><td>83.0</td></tr> <tr><td>10.0</td><td>82.1</td><td>81.9</td><td>83.0</td></tr> <tr><td>12.0</td><td>81.9</td><td>82.0</td><td>83.0</td></tr> <tr><td>13.75</td><td>82.0</td><td>82.0</td><td>83.0</td></tr> </tbody> </table>			Load Current [A]	Efficiency [100V] (%)	Efficiency [115V] (%)	Efficiency [230V] (%)	3.0	67.0	66.7	66.7	4.0	78.0	77.0	77.0	5.0	80.0	79.0	81.0	6.0	81.0	80.0	82.0	8.0	82.0	81.0	83.0	10.0	82.1	81.9	83.0	12.0	81.9	82.0	83.0	13.75	82.0	82.0	83.0															
Load Current [A]	Efficiency [100V] (%)	Efficiency [115V] (%)	Efficiency [230V] (%)																																																			
3.0	67.0	66.7	66.7																																																			
4.0	78.0	77.0	77.0																																																			
5.0	80.0	79.0	81.0																																																			
6.0	81.0	80.0	82.0																																																			
8.0	82.0	81.0	83.0																																																			
10.0	82.1	81.9	83.0																																																			
12.0	81.9	82.0	83.0																																																			
13.75	82.0	82.0	83.0																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>66.7</td><td>67.0</td><td>67.3</td></tr> <tr><td>4.00</td><td>76.4</td><td>77.0</td><td>78.6</td></tr> <tr><td>6.00</td><td>80.0</td><td>80.1</td><td>82.4</td></tr> <tr><td>8.00</td><td>81.1</td><td>82.2</td><td>84.4</td></tr> <tr><td>10.00</td><td>82.1</td><td>82.5</td><td>85.4</td></tr> <tr><td>12.00</td><td>81.9</td><td>82.9</td><td>85.7</td></tr> <tr><td>12.50</td><td>82.0</td><td>82.9</td><td>85.7</td></tr> <tr><td>13.75</td><td>82.0</td><td>82.7</td><td>85.7</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	2.00	66.7	67.0	67.3	4.00	76.4	77.0	78.6	6.00	80.0	80.1	82.4	8.00	81.1	82.2	84.4	10.00	82.1	82.5	85.4	12.00	81.9	82.9	85.7	12.50	82.0	82.9	85.7	13.75	82.0	82.7	85.7	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
2.00	66.7	67.0	67.3																																																			
4.00	76.4	77.0	78.6																																																			
6.00	80.0	80.1	82.4																																																			
8.00	81.1	82.2	84.4																																																			
10.00	82.1	82.5	85.4																																																			
12.00	81.9	82.9	85.7																																																			
12.50	82.0	82.9	85.7																																																			
13.75	82.0	82.7	85.7																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					




COSEL

Model	PJMA300F-24	Temperature Testing Circuitry	25°C Figure A																																																			
Item	Power Factor (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 115V - ·○--- Input Volt. 230V</p>  <p>The graph plots Power Factor (Y-axis, 0.0 to 1.0) against Load Current [A] (X-axis, 0 to 12). Three curves are shown for different input voltages: 100V (solid line with triangles), 115V (dashed line with squares), and 230V (dash-dot line with circles). All curves show an initial increase in power factor with load current, followed by a slight decrease as the load approaches the rated current. A slanted line on the graph indicates the range of the rated load current.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.725</td><td>0.700</td><td>0.382</td></tr> <tr> <td>2.00</td><td>0.918</td><td>0.909</td><td>0.803</td></tr> <tr> <td>4.00</td><td>0.949</td><td>0.941</td><td>0.871</td></tr> <tr> <td>6.00</td><td>0.963</td><td>0.955</td><td>0.906</td></tr> <tr> <td>8.00</td><td>0.969</td><td>0.965</td><td>0.923</td></tr> <tr> <td>10.00</td><td>0.975</td><td>0.969</td><td>0.932</td></tr> <tr> <td>12.00</td><td>0.979</td><td>0.973</td><td>0.944</td></tr> <tr> <td>12.50</td><td>0.980</td><td>0.974</td><td>0.946</td></tr> <tr> <td>13.75</td><td>0.983</td><td>0.977</td><td>0.947</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.725	0.700	0.382	2.00	0.918	0.909	0.803	4.00	0.949	0.941	0.871	6.00	0.963	0.955	0.906	8.00	0.969	0.965	0.923	10.00	0.975	0.969	0.932	12.00	0.979	0.973	0.944	12.50	0.980	0.974	0.946	13.75	0.983	0.977	0.947	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.725	0.700	0.382																																																			
2.00	0.918	0.909	0.803																																																			
4.00	0.949	0.941	0.871																																																			
6.00	0.963	0.955	0.906																																																			
8.00	0.969	0.965	0.923																																																			
10.00	0.975	0.969	0.932																																																			
12.00	0.979	0.973	0.944																																																			
12.50	0.980	0.974	0.946																																																			
13.75	0.983	0.977	0.947																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PJMA300F-24	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	PJMA300F-24	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure C
Object	<hr/>		

1. Results

Standards		Input Volt.			Note
		115 [V]	230 [V]	240 [V]	
IEC60601-1	Both phases	0.08	0.18	0.18	Operation
	One of phases	0.16	0.33	0.34	Stand by

The value for "One of phases" is the reference value only.


2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PJMA300F-24
Item	Line Regulation
Object	+24V12.5A

1.Graph



Note: Slanted line shows the range of the rated input voltage.



Temperature 25°C
Testing Circuitry Figure A

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	24.307	24.307 ※1
100	24.307	24.307
115	24.307	24.307
200	24.307	24.307
230	24.306	24.307
264	24.306	24.307
280	24.307	24.307
--	-	-
--	-	-

※1: Load 80%



COSEL

Model	PJMA300F-24	Temperature Testing Circuitry	25°C																																																			
Item	Load Regulation		Figure A																																																			
Object	+24V12.5A																																																					
1.Graph	<p>—△— Input Volt. 100V - - - □ - - Input Volt. 115V - · ○ - - Input Volt. 230V</p>  <p>Note: Slanted line shows the range of the rated load current.</p>	2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>24.309</td><td>24.309</td><td>24.309</td></tr> <tr> <td>2.00</td><td>24.306</td><td>24.306</td><td>24.306</td></tr> <tr> <td>4.00</td><td>24.306</td><td>24.306</td><td>24.306</td></tr> <tr> <td>6.00</td><td>24.306</td><td>24.306</td><td>24.306</td></tr> <tr> <td>8.00</td><td>24.306</td><td>24.307</td><td>24.307</td></tr> <tr> <td>10.00</td><td>24.307</td><td>24.307</td><td>24.307</td></tr> <tr> <td>12.00</td><td>24.307</td><td>24.307</td><td>24.308</td></tr> <tr> <td>12.50</td><td>24.308</td><td>24.307</td><td>24.308</td></tr> <tr> <td>13.75</td><td>24.308</td><td>24.307</td><td>24.308</td></tr> <tr> <td>--</td><td>--</td><td>--</td><td>--</td></tr> <tr> <td>--</td><td>--</td><td>--</td><td>--</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	24.309	24.309	24.309	2.00	24.306	24.306	24.306	4.00	24.306	24.306	24.306	6.00	24.306	24.306	24.306	8.00	24.306	24.307	24.307	10.00	24.307	24.307	24.307	12.00	24.307	24.307	24.308	12.50	24.308	24.307	24.308	13.75	24.308	24.307	24.308	--	--	--	--	--	--	--	--	
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	24.309	24.309	24.309																																																			
2.00	24.306	24.306	24.306																																																			
4.00	24.306	24.306	24.306																																																			
6.00	24.306	24.306	24.306																																																			
8.00	24.306	24.307	24.307																																																			
10.00	24.307	24.307	24.307																																																			
12.00	24.307	24.307	24.308																																																			
12.50	24.308	24.307	24.308																																																			
13.75	24.308	24.307	24.308																																																			
--	--	--	--																																																			
--	--	--	--																																																			
Item	Ripple-Noise	Temperature Testing Circuitry	25°C																																																			
Object	+24V12.5A		Figure B																																																			
1.Graph	<p>Input Voltage 115V Load 100%</p> 																																																					

COSEL

Model	PJMA300F-24	Temperature	25°C
Item	Dynamic Load Response	Testing Circuitry	Figure A
Object	+24V12.5A		

Input Volt. 115 V
 Cycle 1000 ms

Response. $t_1=t_2=50\mu\text{s}$. Typ

Load 0%(0A) \longleftrightarrow
 Load 100%(12.5A)

500[mV/div]

20[ms/div]

20[ms/div]

Load 50%(6.25A) \longleftrightarrow
 Load 100%(12.5A)

500[mV/div]

20[ms/div]


20[ms/div]

COSEL

Model	PJMA300F-24
Item	Rise and Fall Time
Object	+24V12.5A

Temperature 25°C
Testing Circuitry Figure A


1.Graph



2.Values

[ms]


Input Volt.	Time	Td	Tr	Ts	Th	Tf
100V		204.0	51.5	255.5	41.3	9.3
230V		169.0	51.0	220.0	47.5	9.2



COSEL

Model	PJMA300F-24
Item	Hold-Up Time
Object	+24V12.5A

1. Graph


 Temperature 25°C
 Testing Circuitry Figure A

2. Values


Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	75	50 ※1
100	77	39
115	80	40
200	87	44
230	89	46
264	92	47
280	93	48
--	-	-
--	-	-

※1: Load 80%

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PJMA300F-24
Item	Instantaneous Interruption Compensation
Object	+24V12.5A


 Temperature 25°C
 Testing Circuitry Figure A


2.Values

Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0.00	-	-	-
2.00	214	221	239
4.00	121	121	137
6.00	80	82	89
8.00	63	64	72
10.00	52	53	57
12.00	43	43	47
12.50	39	40	47
13.75	36	36	39
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.



Model	PJMA300F-24
Item	Overcurrent Protection
Object	+24V12.5A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
22.8	15.77	15.73	15.70
21.6	15.81	15.78	15.75
19.2	15.94	15.90	15.88
16.8	16.05	16.02	16.00
14.4	16.16	16.13	16.10
12.0	16.26	16.23	16.19
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-
--	-	-	-



Model	PJMA300F-24
Item	Ambient Temperature Drift
Object	+24V12.5A

1.Values

Load 100%

Ambient Temperature[°C]	Output Voltage [V]		
	Input Volt. 100V	Input Volt. 115V	Input Volt. 230V
-20	24.290	24.291	24.291
25	24.320	24.320	24.321
50	24.308	24.308	24.307

Item	Minimum Input Voltage for Regulated Output Voltage
Object	+24V12.5A

1.Values

Ambient Temperature[°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	39	57
25	39	57
50	39	58

Item	Overvoltage Protection
Object	+24V12.5A

1.Values

Load 0%

Ambient Temperature[°C]	Operating Point [V]	
	Input Volt. 100V	Input Volt. 230V
-20	30.03	29.97
25	30.91	30.91
50	31.44	31.43

COSEL




Figure A




Figure B




Figure C (IEC60601-1)