

TEST DATA OF PLA150F-12

Regulated DC Power Supply
May 23, 2013

Approved by : Katsumi Ishikawa
Katsumi Ishikawa Design Manager

Prepared by : Naoki Fujita
Naoki Fujita Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 25)

COSEL

Model	PLA150F-12																																																					
Item	Input Current (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	—▲— Input Volt. 100V - - □--- Input Volt. 115V - - ○--- Input Volt. 230V																																																					
<p>The graph shows three curves representing different input voltages. The 100V curve (solid line with triangles) starts at approximately (0, 0.044) and ends at (12, 1.78). The 115V curve (dashed line with squares) starts at approximately (0, 0.042) and ends at (12, 1.55). The 230V curve (dash-dot line with circles) starts at approximately (0, 0.044) and ends at (12, 0.85). A slanted line from the origin to the point (12, 1.78) represents the rated load current range.</p>			2.Values																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.044</td><td>0.042</td><td>0.044</td></tr> <tr> <td>2.00</td><td>0.320</td><td>0.278</td><td>0.171</td></tr> <tr> <td>4.00</td><td>0.591</td><td>0.520</td><td>0.298</td></tr> <tr> <td>6.00</td><td>0.863</td><td>0.760</td><td>0.412</td></tr> <tr> <td>8.00</td><td>1.138</td><td>0.992</td><td>0.528</td></tr> <tr> <td>10.00</td><td>1.428</td><td>1.238</td><td>0.646</td></tr> <tr> <td>12.00</td><td>1.718</td><td>1.483</td><td>0.766</td></tr> <tr> <td>12.50</td><td>1.796</td><td>1.552</td><td>0.797</td></tr> <tr> <td>13.75</td><td>-</td><td>1.710</td><td>0.868</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.044	0.042	0.044	2.00	0.320	0.278	0.171	4.00	0.591	0.520	0.298	6.00	0.863	0.760	0.412	8.00	1.138	0.992	0.528	10.00	1.428	1.238	0.646	12.00	1.718	1.483	0.766	12.50	1.796	1.552	0.797	13.75	-	1.710	0.868	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.044	0.042	0.044																																																			
2.00	0.320	0.278	0.171																																																			
4.00	0.591	0.520	0.298																																																			
6.00	0.863	0.760	0.412																																																			
8.00	1.138	0.992	0.528																																																			
10.00	1.428	1.238	0.646																																																			
12.00	1.718	1.483	0.766																																																			
12.50	1.796	1.552	0.797																																																			
13.75	-	1.710	0.868																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL


Model	PLA150F-12																																																			
Item	Input Power (by Load Current)																																																			
Object	<u> </u>																																																			
1.Graph	<p>Input Power [W]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> —▲— Input Volt. 100V - - □ - - Input Volt. 115V - - ○ - - Input Volt. 230V <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>1.3</td><td>1.3</td><td>1.0</td></tr> <tr><td>2.00</td><td>30.0</td><td>29.7</td><td>31.0</td></tr> <tr><td>4.00</td><td>57.6</td><td>57.6</td><td>57.0</td></tr> <tr><td>6.00</td><td>85.2</td><td>84.3</td><td>84.0</td></tr> <tr><td>8.00</td><td>113.6</td><td>112.4</td><td>112.0</td></tr> <tr><td>10.00</td><td>142.5</td><td>141.1</td><td>139.0</td></tr> <tr><td>12.00</td><td>171.6</td><td>169.8</td><td>167.0</td></tr> <tr><td>12.50</td><td>179.4</td><td>177.6</td><td>174.0</td></tr> <tr><td>13.75</td><td>-</td><td>195.9</td><td>191.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	1.3	1.3	1.0	2.00	30.0	29.7	31.0	4.00	57.6	57.6	57.0	6.00	85.2	84.3	84.0	8.00	113.6	112.4	112.0	10.00	142.5	141.1	139.0	12.00	171.6	169.8	167.0	12.50	179.4	177.6	174.0	13.75	-	195.9	191.0	--	-	-	-	--	-	-	-	Temperature 25°C Testing Circuitry Figure A		
Load Current [A]	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																	
0.00	1.3	1.3	1.0																																																	
2.00	30.0	29.7	31.0																																																	
4.00	57.6	57.6	57.0																																																	
6.00	85.2	84.3	84.0																																																	
8.00	113.6	112.4	112.0																																																	
10.00	142.5	141.1	139.0																																																	
12.00	171.6	169.8	167.0																																																	
12.50	179.4	177.6	174.0																																																	
13.75	-	195.9	191.0																																																	
--	-	-	-																																																	
--	-	-	-																																																	
2.Values																																																				

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PLA150F-12	Temperature Testing Circuitry	25°C Figure A																																
Item	Efficiency (by Input Voltage)																																		
Object	—	2.Values																																	
1.Graph																																			
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>84.2</td> <td>83.2</td> </tr> <tr> <td>100</td> <td>85.1</td> <td>84.0</td> </tr> <tr> <td>115</td> <td>85.6</td> <td>84.5</td> </tr> <tr> <td>200</td> <td>86.3</td> <td>86.4</td> </tr> <tr> <td>230</td> <td>86.7</td> <td>87.1</td> </tr> <tr> <td>264</td> <td>87.1</td> <td>87.0</td> </tr> <tr> <td>280</td> <td>86.1</td> <td>86.9</td> </tr> <tr> <td>—</td> <td>-</td> <td>-</td> </tr> <tr> <td>—</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	84.2	83.2	100	85.1	84.0	115	85.6	84.5	200	86.3	86.4	230	86.7	87.1	264	87.1	87.0	280	86.1	86.9	—	-	-	—	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
85	84.2	83.2																																	
100	85.1	84.0																																	
115	85.6	84.5																																	
200	86.3	86.4																																	
230	86.7	87.1																																	
264	87.1	87.0																																	
280	86.1	86.9																																	
—	-	-																																	
—	-	-																																	
<p>※1: Load 80%</p> <p>※2: Load 90%</p>																																			
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	PLA150F-12																																																					
Item	Efficiency (by Load Current)																																																					
Object	<u> </u>																																																					
1.Graph	—▲— Input Volt. 100V - - □--- Input Volt. 115V - - ○--- Input Volt. 230V																																																					
	 <p>The graph plots Efficiency [%] on the Y-axis (44 to 100) against Load Current [A] on the X-axis (0 to 12). Three data series are shown for different input voltages: 100V (solid line with squares), 115V (dashed line with circles), and 230V (dash-dot line with triangles). All curves show efficiency increasing with load current. A diagonal hatched line represents the rated load current range, which is approximately between 4A and 12A.</p>																																																					
Temperature	25°C																																																					
Testing Circuitry	Figure A																																																					
2.Values																																																						
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>2.00</td> <td>81.0</td> <td>81.1</td> <td>78.5</td> </tr> <tr> <td>4.00</td> <td>84.2</td> <td>85.1</td> <td>83.7</td> </tr> <tr> <td>6.00</td> <td>85.1</td> <td>85.5</td> <td>86.6</td> </tr> <tr> <td>8.00</td> <td>85.4</td> <td>85.8</td> <td>87.2</td> </tr> <tr> <td>10.00</td> <td>84.5</td> <td>85.1</td> <td>87.1</td> </tr> <tr> <td>12.00</td> <td>84.0</td> <td>84.8</td> <td>87.1</td> </tr> <tr> <td>12.50</td> <td>83.7</td> <td>84.5</td> <td>87.1</td> </tr> <tr> <td>13.75</td> <td>-</td> <td>84.5</td> <td>87.0</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	2.00	81.0	81.1	78.5	4.00	84.2	85.1	83.7	6.00	85.1	85.5	86.6	8.00	85.4	85.8	87.2	10.00	84.5	85.1	87.1	12.00	84.0	84.8	87.1	12.50	83.7	84.5	87.1	13.75	-	84.5	87.0	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
2.00	81.0	81.1	78.5																																																			
4.00	84.2	85.1	83.7																																																			
6.00	85.1	85.5	86.6																																																			
8.00	85.4	85.8	87.2																																																			
10.00	84.5	85.1	87.1																																																			
12.00	84.0	84.8	87.1																																																			
12.50	83.7	84.5	87.1																																																			
13.75	-	84.5	87.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PLA150F-12	Temperature Testing Circuitry 25°C Figure A																																
Item	Power Factor (by Input Voltage)																																	
Object	—																																	
1.Graph		2.Values																																
<p>Legend: - - □ - - Load 50% — ▲ — Load 100% </p> <p>Y-axis: Power Factor X-axis: Input Voltage [V]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>0.994</td> <td>0.999 ※1</td> </tr> <tr> <td>100</td> <td>0.991</td> <td>0.999 ※2</td> </tr> <tr> <td>115</td> <td>0.964</td> <td>0.996</td> </tr> <tr> <td>200</td> <td>0.915</td> <td>0.967</td> </tr> <tr> <td>230</td> <td>0.898</td> <td>0.951</td> </tr> <tr> <td>264</td> <td>0.486</td> <td>0.557</td> </tr> <tr> <td>280</td> <td>0.471</td> <td>0.486</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>※1: Load 80% ※2: Load 90%</p>	Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.994	0.999 ※1	100	0.991	0.999 ※2	115	0.964	0.996	200	0.915	0.967	230	0.898	0.951	264	0.486	0.557	280	0.471	0.486	--	-	-	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
85	0.994	0.999 ※1																																
100	0.991	0.999 ※2																																
115	0.964	0.996																																
200	0.915	0.967																																
230	0.898	0.951																																
264	0.486	0.557																																
280	0.471	0.486																																
--	-	-																																
--	-	-																																




Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PLA150F-12																																																					
Item	Power Factor (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																			
Object	_____	_____	_____																																																			
1.Graph	Input Volt. 100V Input Volt. 115V Input Volt. 230V	2.Values	_____																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>			_____																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>0.447</td><td>0.376</td><td>0.115</td></tr> <tr> <td>2.00</td><td>0.938</td><td>0.928</td><td>0.795</td></tr> <tr> <td>4.00</td><td>0.975</td><td>0.962</td><td>0.826</td></tr> <tr> <td>6.00</td><td>0.987</td><td>0.963</td><td>0.884</td></tr> <tr> <td>8.00</td><td>0.997</td><td>0.984</td><td>0.918</td></tr> <tr> <td>10.00</td><td>0.998</td><td>0.991</td><td>0.933</td></tr> <tr> <td>12.00</td><td>0.999</td><td>0.995</td><td>0.949</td></tr> <tr> <td>12.50</td><td>0.999</td><td>0.995</td><td>0.951</td></tr> <tr> <td>13.75</td><td>-</td><td>0.996</td><td>0.955</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	0.447	0.376	0.115	2.00	0.938	0.928	0.795	4.00	0.975	0.962	0.826	6.00	0.987	0.963	0.884	8.00	0.997	0.984	0.918	10.00	0.998	0.991	0.933	12.00	0.999	0.995	0.949	12.50	0.999	0.995	0.951	13.75	-	0.996	0.955	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																			
0.00	0.447	0.376	0.115																																																			
2.00	0.938	0.928	0.795																																																			
4.00	0.975	0.962	0.826																																																			
6.00	0.987	0.963	0.884																																																			
8.00	0.997	0.984	0.918																																																			
10.00	0.998	0.991	0.933																																																			
12.00	0.999	0.995	0.949																																																			
12.50	0.999	0.995	0.951																																																			
13.75	-	0.996	0.955																																																			
--	-	-	-																																																			
--	-	-	-																																																			

COSEL

Model	PLA150F-12	Temperature Testing Circuitry 25°C Figure A
Item	Inrush Current	
Object	—	





Model	PLA150F-12	Temperature Testing Circuitry	25°C Figure B
Item	Leakage Current		
Object			

1. Results

Standards		Input Volt.			Note
		100[V]	115[V]	240[V]	
DEN-AN	Both phases	0.45	0.50	0.65	Operation
	One of phases	0.30	0.35	0.78	Stand by
IEC60950-1	Both phases	0.30	0.31	0.55	Operation
	One of phases	0.27	0.31	0.72	Stand by

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PLA150F-12	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V12.5A																																		
1.Graph		2.Values																																	
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>---□--- Load 50%</p> <p>—△— Load 100%</p>		<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>12.024</td> <td>12.018 ※1</td> </tr> <tr> <td>100</td> <td>12.024</td> <td>12.016 ※2</td> </tr> <tr> <td>115</td> <td>12.024</td> <td>12.014</td> </tr> <tr> <td>200</td> <td>12.024</td> <td>12.014</td> </tr> <tr> <td>230</td> <td>12.024</td> <td>12.014</td> </tr> <tr> <td>264</td> <td>12.024</td> <td>12.014</td> </tr> <tr> <td>280</td> <td>12.024</td> <td>12.014</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>		Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	85	12.024	12.018 ※1	100	12.024	12.016 ※2	115	12.024	12.014	200	12.024	12.014	230	12.024	12.014	264	12.024	12.014	280	12.024	12.014	-	-	-	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
85	12.024	12.018 ※1																																	
100	12.024	12.016 ※2																																	
115	12.024	12.014																																	
200	12.024	12.014																																	
230	12.024	12.014																																	
264	12.024	12.014																																	
280	12.024	12.014																																	
-	-	-																																	
--	-	-																																	
			※1:Load 80%																																
			※2:Load 90%																																
Note: Slanted line shows the range of the rated input voltage.																																			

COSEL


Model	PLA150F-12	Temperature 25°C Testing Circuitry Figure A																																																					
Item	Load Regulation																																																						
Object	+12V12.5A																																																						
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <ul style="list-style-type: none"> —▲— Input Volt. 100V - - □ - - Input Volt. 115V - - ○ - - Input Volt. 230V 																																																						
	2.Values																																																						
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td> <td>12.165</td> <td>12.164</td> <td>12.167</td> </tr> <tr> <td>2.00</td> <td>12.050</td> <td>12.050</td> <td>12.051</td> </tr> <tr> <td>4.00</td> <td>12.028</td> <td>12.028</td> <td>12.029</td> </tr> <tr> <td>6.00</td> <td>12.024</td> <td>12.024</td> <td>12.025</td> </tr> <tr> <td>8.00</td> <td>12.021</td> <td>12.021</td> <td>12.021</td> </tr> <tr> <td>10.00</td> <td>12.018</td> <td>12.018</td> <td>12.018</td> </tr> <tr> <td>12.00</td> <td>12.016</td> <td>12.014</td> <td>12.015</td> </tr> <tr> <td>12.50</td> <td>12.014</td> <td>12.014</td> <td>12.014</td> </tr> <tr> <td>13.75</td> <td>-</td> <td>12.012</td> <td>12.012</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	12.165	12.164	12.167	2.00	12.050	12.050	12.051	4.00	12.028	12.028	12.029	6.00	12.024	12.024	12.025	8.00	12.021	12.021	12.021	10.00	12.018	12.018	12.018	12.00	12.016	12.014	12.015	12.50	12.014	12.014	12.014	13.75	-	12.012	12.012	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																				
0.00	12.165	12.164	12.167																																																				
2.00	12.050	12.050	12.051																																																				
4.00	12.028	12.028	12.029																																																				
6.00	12.024	12.024	12.025																																																				
8.00	12.021	12.021	12.021																																																				
10.00	12.018	12.018	12.018																																																				
12.00	12.016	12.014	12.015																																																				
12.50	12.014	12.014	12.014																																																				
13.75	-	12.012	12.012																																																				
--	-	-	-																																																				
--	-	-	-																																																				
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL


COSEL

Model	PLA150F-12
Item	Ripple Voltage (by Load Current)
Object	+12V12.5A

1.Graph



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure C

2.Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0.00	260	265
2.00	35	35
4.00	35	35
6.00	45	40
8.00	45	40
10.00	45	40
12.00	45	40
12.50	50	40
13.75	55	45
--	-	-
--	-	-


T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form

COSEL

Model	PLA150F-12	Temperature Testing Circuitry	25°C Figure C																																						
Item	Ripple-Noise																																								
Object	+12V12.5A																																								
1.Graph	<p>—△— Input Volt. 115V -·○--- Input Volt. 230V</p>																																								
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 115 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>285</td><td>285</td></tr> <tr><td>2.00</td><td>55</td><td>55</td></tr> <tr><td>4.00</td><td>60</td><td>55</td></tr> <tr><td>6.00</td><td>70</td><td>60</td></tr> <tr><td>8.00</td><td>70</td><td>60</td></tr> <tr><td>10.00</td><td>85</td><td>60</td></tr> <tr><td>12.00</td><td>90</td><td>65</td></tr> <tr><td>12.50</td><td>90</td><td>65</td></tr> <tr><td>13.75</td><td>90</td><td>70</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 115 [V]	Input Volt. 230 [V]	0.00	285	285	2.00	55	55	4.00	60	55	6.00	70	60	8.00	70	60	10.00	85	60	12.00	90	65	12.50	90	65	13.75	90	70	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 115 [V]	Input Volt. 230 [V]																																							
0.00	285	285																																							
2.00	55	55																																							
4.00	60	55																																							
6.00	70	60																																							
8.00	70	60																																							
10.00	85	60																																							
12.00	90	65																																							
12.50	90	65																																							
13.75	90	70																																							
--	-	-																																							
--	-	-																																							
Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.																																									
Fig. Complex Ripple Wave Form																																									


COSEL

Model	PLA150F-12	Testing Circuitry Figure C																																					
Item	Ripple Voltage (by Ambient Temp.)																																						
Object	+12V12.5A																																						
1. Graph		2. Values																																					
<p>Graph showing Ripple Voltage [mV] vs Ambient Temperature [°C] for PLA150F-12 at Load 100%.</p> <p>Legend:</p> <ul style="list-style-type: none"> --- □--- Input Volt. 115V — △— Input Volt. 230V <table border="1"> <thead> <tr> <th>Ambient Temperature [°C]</th> <th>Ripple Voltage [mV] (Input Volt. 115V)</th> <th>Ripple Voltage [mV] (Input Volt. 230V)</th> </tr> </thead> <tbody> <tr><td>-20</td><td>120</td><td>120</td></tr> <tr><td>0</td><td>80</td><td>75</td></tr> <tr><td>20</td><td>50</td><td>40</td></tr> <tr><td>40</td><td>40</td><td>30</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 115V)	Ripple Voltage [mV] (Input Volt. 230V)	-20	120	120	0	80	75	20	50	40	40	40	30																							
Ambient Temperature [°C]	Ripple Voltage [mV] (Input Volt. 115V)	Ripple Voltage [mV] (Input Volt. 230V)																																					
-20	120	120																																					
0	80	75																																					
20	50	40																																					
40	40	30																																					
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 115 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr><td>-20</td><td>120</td><td>120</td></tr> <tr><td>-10</td><td>100</td><td>95</td></tr> <tr><td>0</td><td>80</td><td>75</td></tr> <tr><td>25</td><td>50</td><td>40</td></tr> <tr><td>40</td><td>40</td><td>30</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Ripple Voltage [mV]		Input Volt. 115 [V]	Input Volt. 230 [V]	-20	120	120	-10	100	95	0	80	75	25	50	40	40	40	30	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Ambient Temperature [°C]	Ripple Voltage [mV]																																						
	Input Volt. 115 [V]	Input Volt. 230 [V]																																					
-20	120	120																																					
-10	100	95																																					
0	80	75																																					
25	50	40																																					
40	40	30																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					

Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	PLA150F-12	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+12V12.5A																																																						
1.Graph	<p style="text-align: center;"> —▲— Input Volt. 100V ---□--- Input Volt. 115V ---○--- Input Volt. 230V </p>  <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>12.019</td> <td>12.016</td> <td>12.017</td> </tr> <tr> <td>-10</td> <td>12.020</td> <td>12.018</td> <td>12.018</td> </tr> <tr> <td>0</td> <td>12.021</td> <td>12.019</td> <td>12.019</td> </tr> <tr> <td>10</td> <td>12.021</td> <td>12.018</td> <td>12.018</td> </tr> <tr> <td>20</td> <td>12.018</td> <td>12.016</td> <td>12.016</td> </tr> <tr> <td>25</td> <td>12.016</td> <td>12.014</td> <td>12.014</td> </tr> <tr> <td>30</td> <td>12.015</td> <td>12.012</td> <td>12.012</td> </tr> <tr> <td>40</td> <td>12.011</td> <td>12.008</td> <td>12.008</td> </tr> <tr> <td>45</td> <td>12.009</td> <td>12.006</td> <td>12.006</td> </tr> <tr> <td>50</td> <td>12.006</td> <td>12.003</td> <td>12.003</td> </tr> <tr> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	-20	12.019	12.016	12.017	-10	12.020	12.018	12.018	0	12.021	12.019	12.019	10	12.021	12.018	12.018	20	12.018	12.016	12.016	25	12.016	12.014	12.014	30	12.015	12.012	12.012	40	12.011	12.008	12.008	45	12.009	12.006	12.006	50	12.006	12.003	12.003	-	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																				
-20	12.019	12.016	12.017																																																				
-10	12.020	12.018	12.018																																																				
0	12.021	12.019	12.019																																																				
10	12.021	12.018	12.018																																																				
20	12.018	12.016	12.016																																																				
25	12.016	12.014	12.014																																																				
30	12.015	12.012	12.012																																																				
40	12.011	12.008	12.008																																																				
45	12.009	12.006	12.006																																																				
50	12.006	12.003	12.003																																																				
-	-	-	-																																																				
		<p>Note: In case of Input Volt. 100V, Load 90%.</p> <p>Other case Load 100%.</p>																																																					



Model	PLA150F-12	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V12.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 40°C

Input Voltage : 115 - 264V

Load Current : 3.75 - 12.5A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	0	115	3.75	12.033	±13	±0.1
Minimum Voltage	40	115	12.5	12.008		

COSEL

Model	PLA150F-12	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V12.5A																								
1. Graph																									
<p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 230V Load 100%</p>																									
2. Values																									
<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.014</td></tr> <tr><td>0.5</td><td>12.013</td></tr> <tr><td>1.0</td><td>12.012</td></tr> <tr><td>2.0</td><td>12.012</td></tr> <tr><td>3.0</td><td>12.012</td></tr> <tr><td>4.0</td><td>12.012</td></tr> <tr><td>5.0</td><td>12.012</td></tr> <tr><td>6.0</td><td>12.012</td></tr> <tr><td>7.0</td><td>12.012</td></tr> <tr><td>8.0</td><td>12.012</td></tr> </tbody> </table>				Time since start [H]	Output Voltage [V]	0.0	12.014	0.5	12.013	1.0	12.012	2.0	12.012	3.0	12.012	4.0	12.012	5.0	12.012	6.0	12.012	7.0	12.012	8.0	12.012
Time since start [H]	Output Voltage [V]																								
0.0	12.014																								
0.5	12.013																								
1.0	12.012																								
2.0	12.012																								
3.0	12.012																								
4.0	12.012																								
5.0	12.012																								
6.0	12.012																								
7.0	12.012																								
8.0	12.012																								

* The characteristic of AC115V is equal.

COSEL

Model	PLA150F-12	Temperature Testing Circuitry 25°C Figure A
Item	Rise and Fall Time	
Object	+12V12.5A	

1. Graph

2. Values [ms]

Input Volt.	Time	Td	Tr	Ts	Th	Tf
115 V		479.5	21.0	500.5	32.8	12.5
230 V		462.5	21.0	483.5	39.3	12.8

COSEL

Model	PLA150F-12	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time																																		
Object	+12V12.5A																																		
1. Graph			2. Values																																
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>68</td> <td>43 ※1</td> </tr> <tr> <td>100</td> <td>68</td> <td>38 ※2</td> </tr> <tr> <td>115</td> <td>68</td> <td>33</td> </tr> <tr> <td>200</td> <td>68</td> <td>33</td> </tr> <tr> <td>230</td> <td>80</td> <td>37</td> </tr> <tr> <td>264</td> <td>86</td> <td>42</td> </tr> <tr> <td>280</td> <td>99</td> <td>47</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table> <p>※1: Load 80% ※2: Load 90%</p>	Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	85	68	43 ※1	100	68	38 ※2	115	68	33	200	68	33	230	80	37	264	86	42	280	99	47	--	-	-	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
85	68	43 ※1																																	
100	68	38 ※2																																	
115	68	33																																	
200	68	33																																	
230	80	37																																	
264	86	42																																	
280	99	47																																	
--	-	-																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	PLA150F-12	Temperature Testing Circuitry	25°C Figure A																																																				
Item	Instantaneous Interruption Compensation																																																						
Object	+12V12.5A																																																						
1.Graph	<p>—▲— Input Volt. 100V - - - □ - - Input Volt. 115V - - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>115V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>2.00</td><td>120</td><td>120</td><td>120</td></tr> <tr><td>4.00</td><td>100</td><td>100</td><td>100</td></tr> <tr><td>6.00</td><td>80</td><td>80</td><td>80</td></tr> <tr><td>8.00</td><td>60</td><td>60</td><td>60</td></tr> <tr><td>10.00</td><td>45</td><td>45</td><td>45</td></tr> <tr><td>12.00</td><td>35</td><td>35</td><td>35</td></tr> <tr><td>13.75</td><td>30</td><td>30</td><td>30</td></tr> </tbody> </table>	Load Current [A]	100V [ms]	115V [ms]	230V [ms]	2.00	120	120	120	4.00	100	100	100	6.00	80	80	80	8.00	60	60	60	10.00	45	45	45	12.00	35	35	35	13.75	30	30	30																						
Load Current [A]	100V [ms]	115V [ms]	230V [ms]																																																				
2.00	120	120	120																																																				
4.00	100	100	100																																																				
6.00	80	80	80																																																				
8.00	60	60	60																																																				
10.00	45	45	45																																																				
12.00	35	35	35																																																				
13.75	30	30	30																																																				
2.Values																																																							
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>2.00</td><td>105</td><td>105</td><td>108</td></tr> <tr><td>4.00</td><td>102</td><td>102</td><td>103</td></tr> <tr><td>6.00</td><td>69</td><td>69</td><td>72</td></tr> <tr><td>8.00</td><td>52</td><td>52</td><td>55</td></tr> <tr><td>10.00</td><td>39</td><td>40</td><td>43</td></tr> <tr><td>12.00</td><td>31</td><td>31</td><td>34</td></tr> <tr><td>12.50</td><td>30</td><td>31</td><td>32</td></tr> <tr><td>13.75</td><td>27</td><td>27</td><td>28</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0.00	-	-	-	2.00	105	105	108	4.00	102	102	103	6.00	69	69	72	8.00	52	52	55	10.00	39	40	43	12.00	31	31	34	12.50	30	31	32	13.75	27	27	28	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																						
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																				
0.00	-	-	-																																																				
2.00	105	105	108																																																				
4.00	102	102	103																																																				
6.00	69	69	72																																																				
8.00	52	52	55																																																				
10.00	39	40	43																																																				
12.00	31	31	34																																																				
12.50	30	31	32																																																				
13.75	27	27	28																																																				
--	-	-	-																																																				
--	-	-	-																																																				

Note: Slanted line shows the range of the rated load current.

COSEL


Model	PLA150F-12	Testing Circuitry Figure A																																						
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+12V12.5A																																							
1.Graph																																								
<p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (dashed line) Load 100% (solid line) 																																								
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>42</td> <td>61</td> </tr> <tr> <td>-10</td> <td>43</td> <td>61</td> </tr> <tr> <td>0</td> <td>43</td> <td>61</td> </tr> <tr> <td>10</td> <td>43</td> <td>61</td> </tr> <tr> <td>20</td> <td>43</td> <td>61</td> </tr> <tr> <td>25</td> <td>43</td> <td>61</td> </tr> <tr> <td>30</td> <td>43</td> <td>61</td> </tr> <tr> <td>40</td> <td>44</td> <td>61</td> </tr> <tr> <td>45</td> <td>44</td> <td>61</td> </tr> <tr> <td>50</td> <td>44</td> <td>61</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	42	61	-10	43	61	0	43	61	10	43	61	20	43	61	25	43	61	30	43	61	40	44	61	45	44	61	50	44	61	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-20	42	61																																						
-10	43	61																																						
0	43	61																																						
10	43	61																																						
20	43	61																																						
25	43	61																																						
30	43	61																																						
40	44	61																																						
45	44	61																																						
50	44	61																																						
--	-	-																																						

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	PLA150F-12
Item	Overcurrent Protection
Object	+12V12.5A

1. Graph



Intermittent operation occurs when the output voltage is from 6.8V to 0V.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 115[V]	Input Volt. 230[V]
11.4	16.05	16.55
10.8	16.54	16.60
9.6	16.26	16.79
8.4	16.60	17.16
7.2	17.02	17.58
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

COSEL

Model	PLA150F-12	Testing Circuitry Figure A																																							
Item	Overvoltage Protection																																								
Object	+12V12.5A																																								
1.Graph																																									
<p>Operating Point [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 0%</p> <p>Input Volt. 115V</p> <p>Input Volt. 230V</p>		2.Values																																							
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Operating Point [V]</th> </tr> <tr> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>14.95</td> <td>14.95</td> </tr> <tr> <td>-10</td> <td>14.95</td> <td>14.95</td> </tr> <tr> <td>0</td> <td>14.95</td> <td>14.95</td> </tr> <tr> <td>10</td> <td>14.95</td> <td>14.95</td> </tr> <tr> <td>20</td> <td>14.94</td> <td>14.94</td> </tr> <tr> <td>25</td> <td>14.94</td> <td>14.94</td> </tr> <tr> <td>30</td> <td>14.94</td> <td>14.94</td> </tr> <tr> <td>40</td> <td>14.94</td> <td>14.94</td> </tr> <tr> <td>45</td> <td>14.94</td> <td>14.94</td> </tr> <tr> <td>50</td> <td>14.94</td> <td>14.94</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Ambient Temperature [°C]	Operating Point [V]		Input Volt. 115[V]	Input Volt. 230[V]	-20	14.95	14.95	-10	14.95	14.95	0	14.95	14.95	10	14.95	14.95	20	14.94	14.94	25	14.94	14.94	30	14.94	14.94	40	14.94	14.94	45	14.94	14.94	50	14.94	14.94	--	-	-	
Ambient Temperature [°C]	Operating Point [V]																																								
	Input Volt. 115[V]	Input Volt. 230[V]																																							
-20	14.95	14.95																																							
-10	14.95	14.95																																							
0	14.95	14.95																																							
10	14.95	14.95																																							
20	14.94	14.94																																							
25	14.94	14.94																																							
30	14.94	14.94																																							
40	14.94	14.94																																							
45	14.94	14.94																																							
50	14.94	14.94																																							
--	-	-																																							

COSEL




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)


COSEL

Figure C