

TEST DATA OF PLA600F-12

Regulated DC Power Supply
August 19, 2011

Approved by : Katsumi Ishikawa
Katsumi Ishikawa Design Manager

Prepared by : Shintaro Oki
Shintaro Oki Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24


(Final Page 25)

COSEL

Model PLA600F-12

Item Input Current (by Load Current)

Object



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	0.173	0.174	0.288
8	1.448	1.272	0.737
16	2.522	2.200	1.177
24	3.660	3.178	1.650
32	4.820	4.170	2.129
40	6.020	5.190	2.616
48	7.220	6.220	3.108
50	7.540	6.480	3.230
55	-	7.128	3.553
--	-	-	-
--	-	-	-


Note: Slanted line shows the range of the rated load current.

COSEL

Model PLA600F-12

Item Input Power (by Load Current)

Object _____



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	9.9	9.9	10.0
8	135.0	134.1	132.0
16	243.9	242.4	238.0
24	359.7	357.0	349.0
32	478.0	473.0	460.0
40	597.0	591.0	573.0
48	719.0	711.0	688.0
50	751.0	741.0	716.0
55	-	815.1	787.6
--	-	-	-
--	-	-	-

COSEL

Model	PLA600F-12
Item	Efficiency (by Input Voltage)
Object	—

1.Graph



Temperature 25°C
Testing Circuitry Figure A

2.Values


Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
85	79.5	79.6 ※1
100	80.6	80.5 ※2
115	81.2	81.1
200	82.8	83.4
230	83.3	84.1
264	83.5	84.3
280	83.5	84.5
--	-	-
--	-	-

※1 : Load 80%

※2 : Load 90%

Note: Slanted line shows the range of the rated input voltage.

COSEL



Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	-	-	-
8	71.5	72.0	73.1
16	79.0	79.5	81.0
24	80.5	81.1	82.9
32	80.7	81.5	83.8
40	80.7	81.5	84.1
48	80.4	81.3	84.0
50	80.1	81.2	84.1
55	-	81.0	83.8
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL




Model	PLA600F-12	Temperature	25°C																																
Item	Power Factor (by Input Voltage)	Testing Circuitry	Figure A																																
Object	—	2. Values																																	
1. Graph																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>0.992</td><td>0.995 ※1</td> </tr> <tr> <td>100</td><td>0.985</td><td>0.996 ※2</td> </tr> <tr> <td>115</td><td>0.980</td><td>0.996</td> </tr> <tr> <td>200</td><td>0.941</td><td>0.977</td> </tr> <tr> <td>230</td><td>0.921</td><td>0.964</td> </tr> <tr> <td>264</td><td>0.887</td><td>0.947</td> </tr> <tr> <td>280</td><td>0.833</td><td>0.901</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.992	0.995 ※1	100	0.985	0.996 ※2	115	0.980	0.996	200	0.941	0.977	230	0.921	0.964	264	0.887	0.947	280	0.833	0.901	--	-	-	--	-	-	
Input Voltage [V]	Power Factor																																		
	Load 50%	Load 100%																																	
85	0.992	0.995 ※1																																	
100	0.985	0.996 ※2																																	
115	0.980	0.996																																	
200	0.941	0.977																																	
230	0.921	0.964																																	
264	0.887	0.947																																	
280	0.833	0.901																																	
--	-	-																																	
--	-	-																																	
Note: Slanted line shows the range of the rated input voltage.			※1: Load 80% ※2: Load 90%																																

COSEL

Model	PLA600F-12																																																						
Item	Power Factor (by Load Current)	Temperature Testing Circuitry	25°C Figure A																																																				
Object	_____																																																						
1.Graph	<p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 115V Input Volt. 230V 	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.572</td><td>0.495</td><td>0.152</td></tr> <tr><td>8</td><td>0.932</td><td>0.917</td><td>0.776</td></tr> <tr><td>16</td><td>0.967</td><td>0.958</td><td>0.878</td></tr> <tr><td>24</td><td>0.984</td><td>0.978</td><td>0.918</td></tr> <tr><td>32</td><td>0.992</td><td>0.987</td><td>0.939</td></tr> <tr><td>40</td><td>0.995</td><td>0.992</td><td>0.952</td></tr> <tr><td>48</td><td>0.996</td><td>0.994</td><td>0.962</td></tr> <tr><td>50</td><td>0.997</td><td>0.995</td><td>0.964</td></tr> <tr><td>55</td><td>-</td><td>0.996</td><td>0.965</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	0.572	0.495	0.152	8	0.932	0.917	0.776	16	0.967	0.958	0.878	24	0.984	0.978	0.918	32	0.992	0.987	0.939	40	0.995	0.992	0.952	48	0.996	0.994	0.962	50	0.997	0.995	0.964	55	-	0.996	0.965	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																						
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																				
0	0.572	0.495	0.152																																																				
8	0.932	0.917	0.776																																																				
16	0.967	0.958	0.878																																																				
24	0.984	0.978	0.918																																																				
32	0.992	0.987	0.939																																																				
40	0.995	0.992	0.952																																																				
48	0.996	0.994	0.962																																																				
50	0.997	0.995	0.964																																																				
55	-	0.996	0.965																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

COSEL

Model	PLA600F-12	Temperature Testing Circuitry	25°C Figure A
Item	Inrush Current		
Object	<hr/>		





Model	PLA600F-12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	—		

1. Results

[mA]

Standards		Input Volt.			Note
		100 [V]	115 [V]	240 [V]	
DEN-AN	Both phases	0.31	0.33	0.66	Operation
	One of phases	0.43	0.51	1.10	Stand by
IEC60950-1	Both phases	0.25	0.29	0.64	Operation
	One of phases	0.44	0.50	1.10	Stand by

The value for "One of phases" is the reference value only.


2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PLA600F-12
Item	Line Regulation
Object	+12V50A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	12.092	12.088 ※1
100	12.092	12.086 ※2
115	12.092	12.085
200	12.092	12.085
230	12.092	12.085
264	12.092	12.085
280	12.092	12.085
--	-	-
--	-	-

※1: Load 80%

※2: Load 90%

COSEL




Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	12.100	12.100	12.100
8	12.096	12.097	12.096
16	12.094	12.095	12.094
24	12.092	12.092	12.092
32	12.090	12.090	12.090
40	12.087	12.088	12.088
48	12.085	12.085	12.085
50	12.084	12.085	12.085
55	-	12.083	12.083
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.


COSEL



COSEL

Model	PLA600F-12
Item	Ripple Voltage (by Load Current)
Object	+12V50A

1. Graph



Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure C

2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0	30	30
8	15	15
16	15	15
24	15	15
32	20	20
40	20	20
48	25	25
50	25	25
55	30	30
--	-	-
--	-	-


T1: Due to AC Input Line
T2: Due to Switching


Fig. Complex Ripple Wave Form

COSEL

Model	PLA600F-12	Temperature	25°C																																						
Item	Ripple-Noise	Testing Circuitry	Figure C																																						
Object	+12V50A																																								
1. Graph		2. Values																																							
<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from 0.0 to 60.0 A. Two curves are plotted: one for Input Volt. 115V (solid line with open squares) and one for Input Volt. 230V (dashed line with open circles). Both curves show an increase in Ripple-Noise as Load Current increases, with a slight dip around 10A. A slanted line indicates the rated load current range from 0 to 50A.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 115 [V]</th> <th>Input Volt. 230 [V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>90</td><td>90</td></tr> <tr><td>8</td><td>80</td><td>80</td></tr> <tr><td>16</td><td>85</td><td>85</td></tr> <tr><td>24</td><td>90</td><td>90</td></tr> <tr><td>32</td><td>100</td><td>100</td></tr> <tr><td>40</td><td>110</td><td>110</td></tr> <tr><td>48</td><td>110</td><td>110</td></tr> <tr><td>50</td><td>110</td><td>110</td></tr> <tr><td>55</td><td>120</td><td>120</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple-Noise [mV]		Input Volt. 115 [V]	Input Volt. 230 [V]	0	90	90	8	80	80	16	85	85	24	90	90	32	100	100	40	110	110	48	110	110	50	110	110	55	120	120	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																								
	Input Volt. 115 [V]	Input Volt. 230 [V]																																							
0	90	90																																							
8	80	80																																							
16	85	85																																							
24	90	90																																							
32	100	100																																							
40	110	110																																							
48	110	110																																							
50	110	110																																							
55	120	120																																							
--	-	-																																							
--	-	-																																							
<p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>		<p>Fig. Complex Ripple Wave Form</p> <p>The diagram shows a complex ripple wave form. Two time intervals are indicated: T1, which spans the entire width of the waveform, and T2, which is a smaller segment within T1. The vertical axis is labeled "Ripple-Noise [mVp-p]" and the horizontal axis is labeled "T1" and "T2".</p>																																							

Model	PLA600F-12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V50A

1. Graph



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C


2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
-20	50	50
-10	45	45
0	35	35
10	30	30
20	25	25
25	25	25
30	25	25
40	30	30
50	45	45
--	-	-
--	-	-

Note: In case of Input Volt. 100V, Load 90%.

Other case Load 100%.

COSEL

Model	PLA600F-12	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+12V50A																																																						
1.Graph	<p>—▲— Input Volt. 100V - - - □ - - Input Volt. 115V - - ○ - - Input Volt. 230V</p>  <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p>	2.Values																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>12.084</td><td>12.082</td><td>12.083</td></tr> <tr> <td>-10</td><td>12.084</td><td>12.083</td><td>12.083</td></tr> <tr> <td>0</td><td>12.084</td><td>12.083</td><td>12.083</td></tr> <tr> <td>10</td><td>12.084</td><td>12.083</td><td>12.082</td></tr> <tr> <td>25</td><td>12.083</td><td>12.081</td><td>12.081</td></tr> <tr> <td>30</td><td>12.084</td><td>12.082</td><td>12.082</td></tr> <tr> <td>40</td><td>12.082</td><td>12.081</td><td>12.081</td></tr> <tr> <td>50</td><td>12.078</td><td>12.076</td><td>12.077</td></tr> <tr> <td>60</td><td>12.074</td><td>12.072</td><td>12.073</td></tr> <tr> <td>—</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	-20	12.084	12.082	12.083	-10	12.084	12.083	12.083	0	12.084	12.083	12.083	10	12.084	12.083	12.082	25	12.083	12.081	12.081	30	12.084	12.082	12.082	40	12.082	12.081	12.081	50	12.078	12.076	12.077	60	12.074	12.072	12.073	—	-	-	-	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																				
-20	12.084	12.082	12.083																																																				
-10	12.084	12.083	12.083																																																				
0	12.084	12.083	12.083																																																				
10	12.084	12.083	12.082																																																				
25	12.083	12.081	12.081																																																				
30	12.084	12.082	12.082																																																				
40	12.082	12.081	12.081																																																				
50	12.078	12.076	12.077																																																				
60	12.074	12.072	12.073																																																				
—	-	-	-																																																				
--	-	-	-																																																				
		<p>Note: In case of Input Volt. 100V, Load 90%.</p> <p>Other case Load 100%.</p>																																																					



Model	PLA600F-12	
Item	Output Voltage Accuracy	Testing Circuitry Figure A
Object	+12V50A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 115 - 264V

Load Current : 0 - 50A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	115	0	12.098	± 11	± 0.1
Minimum Voltage	50	264	50	12.076		

coSEL

Model	PLA600F-12	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V50A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 230V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.287</td></tr> <tr><td>0.5</td><td>12.288</td></tr> <tr><td>1.0</td><td>12.288</td></tr> <tr><td>2.0</td><td>12.288</td></tr> <tr><td>* 3.0</td><td>12.288</td></tr> <tr><td>4.0</td><td>12.288</td></tr> <tr><td>5.0</td><td>12.288</td></tr> <tr><td>6.0</td><td>12.288</td></tr> <tr><td>7.0</td><td>12.288</td></tr> <tr><td>8.0</td><td>12.289</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.287	0.5	12.288	1.0	12.288	2.0	12.288	* 3.0	12.288	4.0	12.288	5.0	12.288	6.0	12.288	7.0	12.288	8.0	12.289
Time since start [H]	Output Voltage [V]																								
0.0	12.287																								
0.5	12.288																								
1.0	12.288																								
2.0	12.288																								
* 3.0	12.288																								
4.0	12.288																								
5.0	12.288																								
6.0	12.288																								
7.0	12.288																								
8.0	12.289																								
<p>* The characteristic of AC115V is equal.</p>																									

COSEL


Model PLA600F-12

Item Rise and Fall Time

Object +12V50A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values


Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
115 V		157.5	48.5	206.0	29.0	6.0	
230 V		134.5	46.0	180.5	34.0	6.0	



COSEL

Model	PLA600F-12
Item	Hold-Up Time
Object	+12V50A

1.Graph


 Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	56	34 ※1
100	58	31 ※2
115	59	28
200	67	32
230	69	34
264	71	35
280	70	35
--	-	-
--	-	-

※1: Load 80%

※2: Load 90%

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
 Note: Slanted line shows the range of the rated input voltage.


COSEL

Model	PLA600F-12	Temperature	25°C																																																				
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																				
Object	+12V50A																																																						
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 115V - - ○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>115V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>10</td><td>139</td><td>145</td><td>190</td></tr> <tr><td>20</td><td>81</td><td>80</td><td>90</td></tr> <tr><td>30</td><td>57</td><td>58</td><td>64</td></tr> <tr><td>40</td><td>47</td><td>48</td><td>54</td></tr> <tr><td>50</td><td>37</td><td>38</td><td>44</td></tr> <tr><td>60</td><td>30</td><td>30</td><td>36</td></tr> <tr><td>70</td><td>28</td><td>29</td><td>30</td></tr> <tr><td>80</td><td>-</td><td>26</td><td>27</td></tr> <tr><td>90</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>100</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	100V [ms]	115V [ms]	230V [ms]	10	139	145	190	20	81	80	90	30	57	58	64	40	47	48	54	50	37	38	44	60	30	30	36	70	28	29	30	80	-	26	27	90	-	-	-	100	-	-	-							
Load Current [A]	100V [ms]	115V [ms]	230V [ms]																																																				
10	139	145	190																																																				
20	81	80	90																																																				
30	57	58	64																																																				
40	47	48	54																																																				
50	37	38	44																																																				
60	30	30	36																																																				
70	28	29	30																																																				
80	-	26	27																																																				
90	-	-	-																																																				
100	-	-	-																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>8</td><td>139</td><td>145</td><td>190</td></tr> <tr><td>16</td><td>81</td><td>80</td><td>90</td></tr> <tr><td>24</td><td>57</td><td>58</td><td>64</td></tr> <tr><td>32</td><td>47</td><td>48</td><td>54</td></tr> <tr><td>40</td><td>37</td><td>38</td><td>44</td></tr> <tr><td>48</td><td>30</td><td>30</td><td>36</td></tr> <tr><td>50</td><td>28</td><td>29</td><td>30</td></tr> <tr><td>55</td><td>-</td><td>26</td><td>27</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	-	-	-	8	139	145	190	16	81	80	90	24	57	58	64	32	47	48	54	40	37	38	44	48	30	30	36	50	28	29	30	55	-	26	27	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																						
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																				
0	-	-	-																																																				
8	139	145	190																																																				
16	81	80	90																																																				
24	57	58	64																																																				
32	47	48	54																																																				
40	37	38	44																																																				
48	30	30	36																																																				
50	28	29	30																																																				
55	-	26	27																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

COSEL

Model	PLA600F-12
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+12V50A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A


2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	46	60
-10	46	59
0	46	59
10	46	59
25	46	60
30	46	60
40	47	61
50	47	62
60	47	62
--	-	-
--	-	-

COSEL

Model	PLA600F-12
Item	Overcurrent Protection
Object	+12V50A

1. Graph



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A


2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 115[V]	Input Volt. 230[V]
11.4	57.41	57.44
10.8	57.19	57.62
9.6	58.04	58.04
8.4	58.52	58.49
7.2	58.96	58.85
6.0	59.24	58.52
4.8	59.07	58.84
3.6	59.36	58.81
2.4	59.12	58.75
--	-	-
--	-	-
--	-	-

COSEL

Model	PLA600F-12
Item	Overvoltage Protection
Object	+12V50A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 115[V]	Input Volt. 230[V]
-20	14.21	14.21
-10	14.21	14.21
0	14.21	14.21
10	14.21	14.21
25	14.20	14.21
30	14.20	14.21
40	14.20	14.20
50	14.20	14.20
--	-	-
--	-	-
--	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)




Figure C