

TEST DATA OF PLA600F-5

Regulated DC Power Supply
August 19, 2011

Approved by : Katsumi Ishikawa
Katsumi Ishikawa Design Manager

Prepared by : Shintaro Oki
Shintaro Oki Design Engineer

COSEL CO.,LTD.



CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 25)

COSEL


Model PLA600F-5

Item Input Current (by Load Current)

Object _____

1. Graph

—△— Input Volt. 100V
 - -□--- Input Volt. 115V
 - -○--- Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	0.172	0.180	0.296
15	1.274	1.122	0.652
30	2.110	1.838	1.000
45	3.028	2.638	1.396
60	3.970	3.445	1.782
75	4.930	4.270	2.190
90	6.000	5.180	2.622
100	6.700	5.780	2.904
110	-	6.390	3.194
--	-	-	-
--	-	-	-

COSEL

Model	PLA600F-5																																																
Item	Input Power (by Load Current)																																																
Object	_____																																																
1.Graph	<p>—△— Input Volt. 100V - -□--- Input Volt. 115V - -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [W]</th> <th>115V [W]</th> <th>230V [W]</th> </tr> </thead> <tbody> <tr><td>0</td><td>7.5</td><td>7.2</td><td>7.0</td></tr> <tr><td>15</td><td>114.5</td><td>114.0</td><td>112.0</td></tr> <tr><td>30</td><td>198.3</td><td>197.1</td><td>193.0</td></tr> <tr><td>45</td><td>292.3</td><td>290.3</td><td>284.0</td></tr> <tr><td>60</td><td>388.0</td><td>385.2</td><td>374.0</td></tr> <tr><td>75</td><td>485.0</td><td>482.0</td><td>469.0</td></tr> <tr><td>90</td><td>593.0</td><td>587.0</td><td>569.0</td></tr> <tr><td>100</td><td>664.0</td><td>658.0</td><td>634.0</td></tr> <tr><td>110</td><td>-</td><td>728.0</td><td>703.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	100V [W]	115V [W]	230V [W]	0	7.5	7.2	7.0	15	114.5	114.0	112.0	30	198.3	197.1	193.0	45	292.3	290.3	284.0	60	388.0	385.2	374.0	75	485.0	482.0	469.0	90	593.0	587.0	569.0	100	664.0	658.0	634.0	110	-	728.0	703.0	--	-	-	-	--	-	-	-
Load Current [A]	100V [W]	115V [W]	230V [W]																																														
0	7.5	7.2	7.0																																														
15	114.5	114.0	112.0																																														
30	198.3	197.1	193.0																																														
45	292.3	290.3	284.0																																														
60	388.0	385.2	374.0																																														
75	485.0	482.0	469.0																																														
90	593.0	587.0	569.0																																														
100	664.0	658.0	634.0																																														
110	-	728.0	703.0																																														
--	-	-	-																																														
--	-	-	-																																														

Temperature 25°C
Testing Circuitry Figure A

2.Values

Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	7.5	7.2	7.0
15	114.5	114.0	112.0
30	198.3	197.1	193.0
45	292.3	290.3	284.0
60	388.0	385.2	374.0
75	485.0	482.0	469.0
90	593.0	587.0	569.0
100	664.0	658.0	634.0
110	-	728.0	703.0
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PLA600F-5																																	
Item	Efficiency (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—																																	
1.Graph																																		
<p>Efficiency [%]</p> <p>Input Voltage [V]</p> <p>Legend: Load 50% (dashed line with squares), Load 100% (solid line with triangles)</p>		2.Values																																
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td> <td>76.5</td> <td>75.9 ※1</td> </tr> <tr> <td>100</td> <td>77.3</td> <td>75.8 ※2</td> </tr> <tr> <td>115</td> <td>77.8</td> <td>76.0</td> </tr> <tr> <td>200</td> <td>79.2</td> <td>78.2</td> </tr> <tr> <td>230</td> <td>79.7</td> <td>78.6</td> </tr> <tr> <td>264</td> <td>80.0</td> <td>79.0</td> </tr> <tr> <td>280</td> <td>79.0</td> <td>79.1</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	85	76.5	75.9 ※1	100	77.3	75.8 ※2	115	77.8	76.0	200	79.2	78.2	230	79.7	78.6	264	80.0	79.0	280	79.0	79.1	--	-	-	--	-	-
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
85	76.5	75.9 ※1																																
100	77.3	75.8 ※2																																
115	77.8	76.0																																
200	79.2	78.2																																
230	79.7	78.6																																
264	80.0	79.0																																
280	79.0	79.1																																
--	-	-																																
--	-	-																																
※1: Load 80% ※2: Load 90%																																		
Note: Slanted line shows the range of the rated input voltage.																																		


COSEL

Model PLA600F-5

Item Efficiency (by Load Current)

Object

1. Graph
- △— Input Volt. 100V
 - - □ - - Input Volt. 115V
 - - ○ - - Input Volt. 230V



Note: Slanted line shows the range of the rated load current.

 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	-	-	-
15	65.7	66.0	67.2
30	75.9	76.3	78.0
45	77.1	77.6	79.4
60	77.4	77.9	80.3
75	77.3	77.8	79.9
90	75.8	76.6	79.0
100	75.2	75.9	78.7
110	-	75.4	78.0
--	-	-	-
--	-	-	-

COSEL

Model	PLA600F-5																																	
Item	Power Factor (by Input Voltage)	Temperature 25°C Testing Circuitry Figure A																																
Object	—	—																																
1. Graph																																		
<p>Legend: - - - □ - - - Load 50% — △ — Load 100%</p>																																		
2. Values																																		
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>85</td><td>0.979</td><td>0.991 ※1</td></tr> <tr> <td>100</td><td>0.973</td><td>0.990 ※2</td></tr> <tr> <td>115</td><td>0.964</td><td>0.989</td></tr> <tr> <td>200</td><td>0.919</td><td>0.964</td></tr> <tr> <td>230</td><td>0.895</td><td>0.952</td></tr> <tr> <td>264</td><td>0.867</td><td>0.932</td></tr> <tr> <td>280</td><td>0.834</td><td>0.895</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	85	0.979	0.991 ※1	100	0.973	0.990 ※2	115	0.964	0.989	200	0.919	0.964	230	0.895	0.952	264	0.867	0.932	280	0.834	0.895	--	-	-	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
85	0.979	0.991 ※1																																
100	0.973	0.990 ※2																																
115	0.964	0.989																																
200	0.919	0.964																																
230	0.895	0.952																																
264	0.867	0.932																																
280	0.834	0.895																																
--	-	-																																
--	-	-																																
※1: Load 80% ※2: Load 90%																																		
Note: Slanted line shows the range of the rated input voltage.																																		

COSEL

Model	PLA600F-5																																																			
Item	Power Factor (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																	
Object																																																				
1.Graph	<p style="text-align: center;"> —▲— Input Volt. 100V ---□--- Input Volt. 115V ---○--- Input Volt. 230V </p> <table border="1"> <caption>Data points estimated from Graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Power Factor (100V)</th> <th>Power Factor (115V)</th> <th>Power Factor (230V)</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.436</td><td>0.348</td><td>0.103</td></tr> <tr><td>15</td><td>0.899</td><td>0.884</td><td>0.747</td></tr> <tr><td>30</td><td>0.944</td><td>0.933</td><td>0.839</td></tr> <tr><td>45</td><td>0.966</td><td>0.958</td><td>0.885</td></tr> <tr><td>60</td><td>0.980</td><td>0.973</td><td>0.912</td></tr> <tr><td>75</td><td>0.986</td><td>0.982</td><td>0.931</td></tr> <tr><td>90</td><td>0.990</td><td>0.987</td><td>0.944</td></tr> <tr><td>100</td><td>0.993</td><td>0.991</td><td>0.951</td></tr> <tr><td>110</td><td>-</td><td>0.992</td><td>0.958</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor (100V)	Power Factor (115V)	Power Factor (230V)	0	0.436	0.348	0.103	15	0.899	0.884	0.747	30	0.944	0.933	0.839	45	0.966	0.958	0.885	60	0.980	0.973	0.912	75	0.986	0.982	0.931	90	0.990	0.987	0.944	100	0.993	0.991	0.951	110	-	0.992	0.958	--	-	-	-	--	-	-	-			
Load Current [A]	Power Factor (100V)	Power Factor (115V)	Power Factor (230V)																																																	
0	0.436	0.348	0.103																																																	
15	0.899	0.884	0.747																																																	
30	0.944	0.933	0.839																																																	
45	0.966	0.958	0.885																																																	
60	0.980	0.973	0.912																																																	
75	0.986	0.982	0.931																																																	
90	0.990	0.987	0.944																																																	
100	0.993	0.991	0.951																																																	
110	-	0.992	0.958																																																	
--	-	-	-																																																	
--	-	-	-																																																	
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 115[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.436</td><td>0.348</td><td>0.103</td></tr> <tr><td>15</td><td>0.899</td><td>0.884</td><td>0.747</td></tr> <tr><td>30</td><td>0.944</td><td>0.933</td><td>0.839</td></tr> <tr><td>45</td><td>0.966</td><td>0.958</td><td>0.885</td></tr> <tr><td>60</td><td>0.980</td><td>0.973</td><td>0.912</td></tr> <tr><td>75</td><td>0.986</td><td>0.982</td><td>0.931</td></tr> <tr><td>90</td><td>0.990</td><td>0.987</td><td>0.944</td></tr> <tr><td>100</td><td>0.993</td><td>0.991</td><td>0.951</td></tr> <tr><td>110</td><td>-</td><td>0.992</td><td>0.958</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]	0	0.436	0.348	0.103	15	0.899	0.884	0.747	30	0.944	0.933	0.839	45	0.966	0.958	0.885	60	0.980	0.973	0.912	75	0.986	0.982	0.931	90	0.990	0.987	0.944	100	0.993	0.991	0.951	110	-	0.992	0.958	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																			
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]																																																	
0	0.436	0.348	0.103																																																	
15	0.899	0.884	0.747																																																	
30	0.944	0.933	0.839																																																	
45	0.966	0.958	0.885																																																	
60	0.980	0.973	0.912																																																	
75	0.986	0.982	0.931																																																	
90	0.990	0.987	0.944																																																	
100	0.993	0.991	0.951																																																	
110	-	0.992	0.958																																																	
--	-	-	-																																																	
--	-	-	-																																																	




Note: Slanted line shows the range of the rated load current.

COSEL

Model PLA600F-5

Item Inrush Current

Object

Temperature 25°C
Testing Circuitry Figure A



Model	PLA600F-5	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	—		

1. Results

[mA]

Standards		Input Volt.			Note
		100 [V]	115 [V]	240 [V]	
DEN-AN	Both phases	0.31	0.33	0.66	Operation
	One of phases	0.43	0.51	1.10	Stand by
IEC60950-1	Both phases	0.25	0.29	0.64	Operation
	One of phases	0.44	0.50	1.10	Stand by

The value for "One of phases" is the reference value only.


2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

COSEL

Model	PLA600F-5
Item	Line Regulation
Object	+5V100A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

Temperature 25°C
Testing Circuitry Figure A

2. Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
85	5.034	5.025 ※1
100	5.034	5.022 ※2
115	5.034	5.019
200	5.033	5.019
230	5.033	5.019
264	5.033	5.019
280	5.033	5.019
--	-	-
--	-	-

※1: Load 80%

※2: Load 90%

COSEL


Model	PLA600F-5
Item	Load Regulation
Object	+5V100A

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	5.048	5.048	5.048
15	5.042	5.043	5.043
30	5.039	5.039	5.039
45	5.035	5.035	5.035
60	5.030	5.030	5.031
75	5.027	5.027	5.026
90	5.022	5.022	5.022
100	5.019	5.019	5.019
110	-	5.016	5.016
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.


COSEL

COSEL

Model	PLA600F-5
Item	Ripple Voltage (by Load Current)
Object	+5V100A

Temperature 25°C
Testing Circuitry Figure C

1. Graph



2. Values

Load Current [A]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0	60	60
15	25	25
30	25	25
45	30	30
60	30	30
75	35	35
90	35	35
100	40	40
110	45	45
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Ripple Voltage is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.


T1: Due to AC Input Line
T2: Due to Switching

Fig. Complex Ripple Wave Form

COSEL


Model PLA600F-5

Item Ripple-Noise

Object +5V100A

1. Graph

—△— Input Volt. 115V
 -·○--- Input Volt. 230V



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure C

2. Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
0	80	80
15	55	55
30	60	60
45	60	60
60	65	65
75	80	80
90	90	90
100	100	100
110	105	100
--	-	-
--	-	-


T1: Due to AC Input Line
T2: Due to Switching


Fig. Complex Ripple Wave Form

COSEL

Model	PLA600F-5
Item	Ripple Voltage (by Ambient Temp.)
Object	+5V100A

1.Graph

---□--- Load 50%
—△— Load 100%



Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure C

2.Values


Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 115 [V]	Input Volt. 230 [V]
-30	50	50
-10	50	50
0	50	45
10	45	45
20	40	40
25	40	40
30	40	40
40	40	45
50	45	45
--	-	-
--	-	-

Note: In case of Input Volt. 100V, Load 90%.

Other case Load 100%.

COSEL

Model	PLA600F-5
Item	Ambient Temperature Drift
Object	+5V100A



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
-20	5.015	5.014	5.014
-10	5.013	5.013	5.014
0	5.012	5.012	5.012
10	5.010	5.011	5.011
25	5.009	5.009	5.009
30	5.008	5.009	5.008
40	5.007	5.007	5.008
50	5.007	5.006	5.007
--	-	-	-
--	-	-	-
--	-	-	-

Note: In case of Input Volt. 100V, Load 90%.
Other case Load 100%.



Model	PLA600F-5	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+5V100A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -20 - 50°C

Input Voltage : 115 - 264V

Load Current : 0 - 100A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values


Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	50	115	0	5.046	±20	±0.4
Minimum Voltage	50	115	100	5.006		

COSEL

Model	PLA600F-5
-------	-----------

| Item | Time Lapse Drift |
| Object | +5V100A |

1. Graph



Input Volt. 230V
Load 100%

* The characteristic of AC115V is equal.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Time since start [H]	Output Voltage [V]
0.0	5.140
0.5	5.139
1.0	5.138
2.0	5.138
3.0	5.138
4.0	5.139
5.0	5.139
6.0	5.139
7.0	5.139
8.0	5.139

COSEL


Model PLA600F-5

Item Rise and Fall Time

Object +5V100A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
115 V		158.0	5.0	163.0	31.5	3.5	
230 V		134.5	4.5	139.0	36.7	3.5	




COSEL

Model	PLA600F-5
Item	Hold-Up Time
Object	+5V100A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Hold-Up Time [ms]	
	Load 50%	Load 100%
85	65	39 ※1
100	68	35 ※2
115	69	32
200	76	36
230	78	37
264	79	38
280	78	39
--	-	-
--	-	-


※1: Load 80%

※2: Load 90%

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.
Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PLA600F-5
Item	Instantaneous Interruption Compensation
Object	+5V100A



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A


2. Values

Load Current [A]	Time [ms]		
	Input Volt. 100[V]	Input Volt. 115[V]	Input Volt. 230[V]
0	-	-	-
15	163	165	225
30	89	97	128
45	64	64	87
60	56	56	63
75	43	45	51
90	34	35	40
100	30	31	37
110	-	28	32
--	-	-	-
--	-	-	-

COSEL

Model	PLA600F-5
Item	Minimum Input Voltage for Regulated Output Voltage
Object	+5V100A

1.Graph



Testing Circuitry Figure A

2.Values


Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	51	62
-10	50	61
0	50	61
10	49	61
20	49	61
25	49	61
30	49	61
40	48	61
50	48	61
60	48	61
-	-	-

Note: Slanted line shows the range of the rated ambient temperature.

COSEL

Model	PLA600F-5
Item	Overcurrent Protection
Object	+5V100A

1. Graph



Note: Slanted line shows the range of the rated load current.

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]	
	Input Volt. 115[V]	Input Volt. 230[V]
4.75	111.80	111.53
4.50	112.10	111.66
4.00	113.09	112.86
3.50	114.19	113.85
3.00	115.27	114.88
2.50	116.42	115.97
2.00	116.97	116.35
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-


COSEL

Model PLA600F-5

Item Overvoltage Protection

Object +5V100A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 115[V]	Input Volt. 230[V]
-20	6.61	6.61
-10	6.60	6.60
0	6.60	6.60
10	6.60	6.60
25	6.59	6.59
30	6.59	6.59
40	6.59	6.59
50	6.59	6.59
60	6.59	6.59
--	-	-
--	-	-




Figure A




Figure B (DEN-AN)




Figure B (IEC60950-1)




Figure C