



TEST DATA OF PMA100F-12

Regulated DC Power Supply
June 4, 2010

Approved by : Katsumi Ishikawa
Katsumi Ishikawa Design Manager


Prepared by : Shintaro Oki
Shintaro Oki Design Engineer


COSEL CO.,LTD.

CONTENTS

1.Input Current (by Load Current)	1
2.Input Power (by Load Current)	2
3.Efficiency (by Input Voltage)	3
4.Efficiency (by Load Current)	4
5.Power Factor (by Input Voltage)	5
6.Power Factor (by Load Current)	6
7.Inrush Current	7
8.Leakage Current	8
9.Line Regulation	9
10.Load Regulation	10
11.Dynamic Load Response	11
12.Ripple Voltage (by Load Current)	12
13.Ripple-Noise	13
14.Ripple Voltage (by Ambient Temperature)	14
15.Ambient Temperature Drift	15
16.Output Voltage Accuracy	16
17.Time Lapse Drift	17
18.Rise and Fall Time	18
19.Hold-Up Time	19
20.Instantaneous Interruption Compensation	20
21.Minimum Input Voltage for Regulated Output Voltage	21
22.Overcurrent Protection	22
23.Overvoltage Protection	23
24.Figure of Testing Circuitry	24

(Final Page 24)

Model	PMA100F-12		
Item	Input Current (by Load Current)		
Object	_____		
1.Graph	—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V		
 <p>Note: Slanted line shows the range of the rated load current.</p>			
Temperature	25°C		
Testing Circuitry	Figure A		
2.Values			
Load Current [A]	Input Current [A]		
Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	
0.00	0.095	0.070	0.071
1.50	0.296	0.213	0.233
3.00	0.496	0.302	0.309
4.50	0.702	0.391	0.379
6.00	0.913	0.491	0.454
7.50	1.127	0.591	0.532
8.50	1.271	0.657	0.590
9.35	1.394	0.715	0.640
--	-	-	-
--	-	-	-
--	-	-	-

COSSEL

Temperature 25°C
 Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	5.8	5.3	5.4
1.50	28.0	27.2	27.3
3.00	48.6	47.6	47.5
4.50	69.4	68.8	68.1
6.00	90.8	89.5	88.7
7.50	112.4	110.0	109.5
8.50	126.9	123.8	123.7
9.35	139.3	135.5	135.4
--	-	-	-
--	-	-	-
--	-	-	-

COSEL

Model	PMA100F-12	Temperature	25°C																																
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																																
Object																																			
1. Graph			2. Values																																
<p>The graph plots Efficiency [%] on the y-axis (30 to 86) against Input Voltage [V] on the x-axis (50 to 300). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing from ~78% at 75V to ~80% at 200V, then slightly decreasing to ~79% at 280V. A slanted line indicates the rated input voltage range.</p>			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>77.6</td> <td>79.5</td> </tr> <tr> <td>85</td> <td>78.3</td> <td>80.6</td> </tr> <tr> <td>100</td> <td>79.0</td> <td>82.1</td> </tr> <tr> <td>120</td> <td>79.4</td> <td>82.9</td> </tr> <tr> <td>200</td> <td>79.9</td> <td>84.1</td> </tr> <tr> <td>230</td> <td>80.5</td> <td>84.1</td> </tr> <tr> <td>264</td> <td>80.4</td> <td>84.8</td> </tr> <tr> <td>280</td> <td>80.6</td> <td>84.8</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	77.6	79.5	85	78.3	80.6	100	79.0	82.1	120	79.4	82.9	200	79.9	84.1	230	80.5	84.1	264	80.4	84.8	280	80.6	84.8	--	-	-
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	77.6	79.5																																	
85	78.3	80.6																																	
100	79.0	82.1																																	
120	79.4	82.9																																	
200	79.9	84.1																																	
230	80.5	84.1																																	
264	80.4	84.8																																	
280	80.6	84.8																																	
--	-	-																																	

Note: Slanted line shows the range of the rated input voltage.

COSEL

Model	PMA100F-12	Temperature	25°C																																																			
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																			
Object	<hr/>																																																					
1.Graph	—△— Input Volt. 100V - -□--- Input Volt. 200V - -○--- Input Volt. 230V																																																					
<p>The graph shows efficiency increasing from approximately 65% at 1.5A to 85% at 9.35A. A slanted line marks the rated load current range between approximately 4.5A and 8.5A.</p> <table border="1"> <caption>Data points estimated from Figure A</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>1.50</td><td>65.6</td><td>67.6</td><td>67.3</td></tr> <tr><td>3.00</td><td>75.6</td><td>77.2</td><td>77.3</td></tr> <tr><td>4.50</td><td>79.4</td><td>80.0</td><td>80.8</td></tr> <tr><td>6.00</td><td>80.8</td><td>82.0</td><td>82.7</td></tr> <tr><td>7.50</td><td>81.6</td><td>83.4</td><td>83.8</td></tr> <tr><td>8.50</td><td>82.1</td><td>84.1</td><td>84.1</td></tr> <tr><td>9.35</td><td>82.1</td><td>84.4</td><td>84.4</td></tr> </tbody> </table>			Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	1.50	65.6	67.6	67.3	3.00	75.6	77.2	77.3	4.50	79.4	80.0	80.8	6.00	80.8	82.0	82.7	7.50	81.6	83.4	83.8	8.50	82.1	84.1	84.1	9.35	82.1	84.4	84.4																				
Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																																																			
1.50	65.6	67.6	67.3																																																			
3.00	75.6	77.2	77.3																																																			
4.50	79.4	80.0	80.8																																																			
6.00	80.8	82.0	82.7																																																			
7.50	81.6	83.4	83.8																																																			
8.50	82.1	84.1	84.1																																																			
9.35	82.1	84.4	84.4																																																			
2.Values																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>65.6</td><td>67.6</td><td>67.3</td></tr> <tr><td>3.00</td><td>75.6</td><td>77.2</td><td>77.3</td></tr> <tr><td>4.50</td><td>79.4</td><td>80.0</td><td>80.8</td></tr> <tr><td>6.00</td><td>80.8</td><td>82.0</td><td>82.7</td></tr> <tr><td>7.50</td><td>81.6</td><td>83.4</td><td>83.8</td></tr> <tr><td>8.50</td><td>82.1</td><td>84.1</td><td>84.1</td></tr> <tr><td>9.35</td><td>82.1</td><td>84.4</td><td>84.4</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	1.50	65.6	67.6	67.3	3.00	75.6	77.2	77.3	4.50	79.4	80.0	80.8	6.00	80.8	82.0	82.7	7.50	81.6	83.4	83.8	8.50	82.1	84.1	84.1	9.35	82.1	84.4	84.4	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
1.50	65.6	67.6	67.3																																																			
3.00	75.6	77.2	77.3																																																			
4.50	79.4	80.0	80.8																																																			
6.00	80.8	82.0	82.7																																																			
7.50	81.6	83.4	83.8																																																			
8.50	82.1	84.1	84.1																																																			
9.35	82.1	84.4	84.4																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						


Model	PMA100F-12	Temperature	25°C																															
Item	Power Factor (by Input Voltage)	Testing Circuitry	Figure A																															
Object																																		
1.Graph																																		
<p>---□--- Load 50%</p> <p>—△— Load 100%</p> <p>Power Factor</p> <p>Input Voltage [V]</p>			2.Values																															
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Power Factor</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>0.999</td><td>0.999</td> </tr> <tr> <td>85</td><td>0.997</td><td>0.999</td> </tr> <tr> <td>100</td><td>0.988</td><td>0.998</td> </tr> <tr> <td>120</td><td>0.970</td><td>0.995</td> </tr> <tr> <td>200</td><td>0.868</td><td>0.941</td> </tr> <tr> <td>230</td><td>0.765</td><td>0.911</td> </tr> <tr> <td>264</td><td>0.584</td><td>0.791</td> </tr> <tr> <td>280</td><td>0.536</td><td>0.708</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>			Input Voltage [V]	Power Factor		Load 50%	Load 100%	75	0.999	0.999	85	0.997	0.999	100	0.988	0.998	120	0.970	0.995	200	0.868	0.941	230	0.765	0.911	264	0.584	0.791	280	0.536	0.708	--	-	-
Input Voltage [V]	Power Factor																																	
	Load 50%	Load 100%																																
75	0.999	0.999																																
85	0.997	0.999																																
100	0.988	0.998																																
120	0.970	0.995																																
200	0.868	0.941																																
230	0.765	0.911																																
264	0.584	0.791																																
280	0.536	0.708																																
--	-	-																																
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																		

Model	PMA100F-12
Item	Power Factor (by Load Current)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1.Graph

—△— Input Volt. 100V
---□--- Input Volt. 200V
---○--- Input Volt. 230V






2.Values

Load Current [A]	Power Factor		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	0.608	0.379	0.333
1.50	0.946	0.638	0.509
3.00	0.980	0.788	0.669
4.50	0.987	0.879	0.780
6.00	0.995	0.910	0.848
7.50	0.997	0.931	0.895
8.50	0.998	0.941	0.912
9.35	0.999	0.948	0.920
--	-	-	-
--	-	-	-
--	-	-	-

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PMA100F-12	Temperature	25°C
Item	Inrush Current	Testing Circuitry	Figure A
Object	_____		





Model	PMA100F-12	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	—		

1. Results

Standards		Input Volt.			Note	[mA]
		100 [V]	200 [V]	240 [V]		
IEC60601	Both phases	0.04	0.10	0.16	Operation	
	One of phases	0.09	0.19	0.22	Stand by	

The value for "One of phases" is the reference value only.

2. Condition


Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

Model	PMA100F-12	Temperature	25°C																																
Item	Line Regulation	Testing Circuitry	Figure A																																
Object	+12V8.5A																																		
1.Graph																																			
<p>Output Voltage [V]</p> <p>Input Voltage [V]</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (Dashed line) Load 100% (Solid line) 																																			
Note: Slanted line shows the range of the rated input voltage.																																			
2.Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Output Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>12.269</td> <td>12.264</td> </tr> <tr> <td>85</td> <td>12.269</td> <td>12.264</td> </tr> <tr> <td>100</td> <td>12.269</td> <td>12.264</td> </tr> <tr> <td>120</td> <td>12.269</td> <td>12.263</td> </tr> <tr> <td>200</td> <td>12.269</td> <td>12.264</td> </tr> <tr> <td>230</td> <td>12.269</td> <td>12.264</td> </tr> <tr> <td>264</td> <td>12.269</td> <td>12.264</td> </tr> <tr> <td>280</td> <td>12.269</td> <td>12.263</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Output Voltage [V]		Load 50%	Load 100%	75	12.269	12.264	85	12.269	12.264	100	12.269	12.264	120	12.269	12.263	200	12.269	12.264	230	12.269	12.264	264	12.269	12.264	280	12.269	12.263	--	-	-
Input Voltage [V]	Output Voltage [V]																																		
	Load 50%	Load 100%																																	
75	12.269	12.264																																	
85	12.269	12.264																																	
100	12.269	12.264																																	
120	12.269	12.263																																	
200	12.269	12.264																																	
230	12.269	12.264																																	
264	12.269	12.264																																	
280	12.269	12.263																																	
--	-	-																																	

COSEL

Model	PMA100F-12	Temperature	25°C																																			
Item	Load Regulation	Testing Circuitry	Figure A																																			
Object	+12V8.5A																																					
1.Graph	<p>—△— Input Volt. 100V - - -□--- Input Volt. 200V - - -○--- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (Input 100V)</th> <th>Output Voltage [V] (Input 200V)</th> <th>Output Voltage [V] (Input 230V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>12.277</td><td>12.277</td><td>12.276</td></tr> <tr><td>1.50</td><td>12.274</td><td>12.274</td><td>12.274</td></tr> <tr><td>3.00</td><td>12.272</td><td>12.273</td><td>12.272</td></tr> <tr><td>4.50</td><td>12.270</td><td>12.271</td><td>12.270</td></tr> <tr><td>6.00</td><td>12.268</td><td>12.269</td><td>12.268</td></tr> <tr><td>7.50</td><td>12.267</td><td>12.267</td><td>12.266</td></tr> <tr><td>8.50</td><td>12.265</td><td>12.265</td><td>12.264</td></tr> <tr><td>9.35</td><td>12.264</td><td>12.264</td><td>12.263</td></tr> </tbody> </table>	Load Current [A]	Output Voltage [V] (Input 100V)	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 230V)	0.00	12.277	12.277	12.276	1.50	12.274	12.274	12.274	3.00	12.272	12.273	12.272	4.50	12.270	12.271	12.270	6.00	12.268	12.269	12.268	7.50	12.267	12.267	12.266	8.50	12.265	12.265	12.264	9.35	12.264	12.264	12.263	2.Values
Load Current [A]	Output Voltage [V] (Input 100V)	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 230V)																																			
0.00	12.277	12.277	12.276																																			
1.50	12.274	12.274	12.274																																			
3.00	12.272	12.273	12.272																																			
4.50	12.270	12.271	12.270																																			
6.00	12.268	12.269	12.268																																			
7.50	12.267	12.267	12.266																																			
8.50	12.265	12.265	12.264																																			
9.35	12.264	12.264	12.263																																			
		Load	Output Voltage [V]																																			
		Current	Input Volt. 100[V] Input Volt. 200[V] Input Volt. 230[V]																																			
		[A]																																				
		0.00	12.277 12.277 12.276																																			
		1.50	12.274 12.274 12.274																																			
		3.00	12.272 12.273 12.272																																			
		4.50	12.270 12.271 12.270																																			
		6.00	12.268 12.269 12.268																																			
		7.50	12.267 12.267 12.266																																			
		8.50	12.265 12.265 12.264																																			
		9.35	12.264 12.264 12.263																																			
		--	- - -																																			
		--	- - -																																			
		--	- - -																																			

Note: Slanted line shows the range of the rated load current.

COSEL

COSEL


Model	PMA100F-12																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																						
Object	+12V8.5A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from 0 to 10 A. Two curves are plotted: Input Volt. 100V (solid line with open circles) and Input Volt. 200V (dashed line with open circles). Both curves show a slight increase in ripple voltage as load current increases. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>1.60</td><td>20</td><td>20</td></tr> <tr><td>3.20</td><td>30</td><td>30</td></tr> <tr><td>4.80</td><td>30</td><td>30</td></tr> <tr><td>6.40</td><td>35</td><td>35</td></tr> <tr><td>8.00</td><td>35</td><td>35</td></tr> <tr><td>8.50</td><td>35</td><td>35</td></tr> <tr><td>9.35</td><td>35</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	0.00	15	15	1.60	20	20	3.20	30	30	4.80	30	30	6.40	35	35	8.00	35	35	8.50	35	35	9.35	35	35	--	-	-	--	-	-	--	-	-		
Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																						
0.00	15	15																																						
1.60	20	20																																						
3.20	30	30																																						
4.80	30	30																																						
6.40	35	35																																						
8.00	35	35																																						
8.50	35	35																																						
9.35	35	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>15</td><td>15</td></tr> <tr><td>1.60</td><td>20</td><td>20</td></tr> <tr><td>3.20</td><td>30</td><td>30</td></tr> <tr><td>4.80</td><td>30</td><td>30</td></tr> <tr><td>6.40</td><td>35</td><td>35</td></tr> <tr><td>8.00</td><td>35</td><td>35</td></tr> <tr><td>8.50</td><td>35</td><td>35</td></tr> <tr><td>9.35</td><td>35</td><td>35</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.00	15	15	1.60	20	20	3.20	30	30	4.80	30	30	6.40	35	35	8.00	35	35	8.50	35	35	9.35	35	35	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0.00	15	15																																						
1.60	20	20																																						
3.20	30	30																																						
4.80	30	30																																						
6.40	35	35																																						
8.00	35	35																																						
8.50	35	35																																						
9.35	35	35																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	PMA100F-12
Item	Ripple-Noise
Object	+12V8.5A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



Measured by 20 MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.

2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.00	25	25
1.60	30	35
3.20	35	40
4.80	35	40
6.40	40	45
8.00	45	45
8.50	45	50
9.35	50	50
--	-	-
--	-	-
--	-	-





Fig. Complex Ripple Wave Form

COSEL

Model	PMA100F-12
Item	Ripple Voltage (by Ambient Temp.)
Object	+12V8.5A

1. Graph



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	100	100
-10	55	55
0	50	50
25	35	35
50	30	30
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Model	PMA100F-12	Testing Circuitry Figure A																																																					
Item	Ambient Temperature Drift																																																						
Object	+12V8.5A																																																						
1.Graph	<p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 																																																						
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>12.299</td> <td>12.299</td> <td>12.299</td> </tr> <tr> <td>-10</td> <td>12.301</td> <td>12.301</td> <td>12.301</td> </tr> <tr> <td>0</td> <td>12.297</td> <td>12.297</td> <td>12.297</td> </tr> <tr> <td>10</td> <td>12.295</td> <td>12.295</td> <td>12.295</td> </tr> <tr> <td>20</td> <td>12.290</td> <td>12.290</td> <td>12.289</td> </tr> <tr> <td>25</td> <td>12.287</td> <td>12.286</td> <td>12.286</td> </tr> <tr> <td>30</td> <td>12.282</td> <td>12.282</td> <td>12.282</td> </tr> <tr> <td>40</td> <td>12.276</td> <td>12.275</td> <td>12.275</td> </tr> <tr> <td>50</td> <td>12.267</td> <td>12.267</td> <td>12.267</td> </tr> <tr> <td>60</td> <td>12.264</td> <td>12.264</td> <td>12.263</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	12.299	12.299	12.299	-10	12.301	12.301	12.301	0	12.297	12.297	12.297	10	12.295	12.295	12.295	20	12.290	12.290	12.289	25	12.287	12.286	12.286	30	12.282	12.282	12.282	40	12.276	12.275	12.275	50	12.267	12.267	12.267	60	12.264	12.264	12.263	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
-20	12.299	12.299	12.299																																																				
-10	12.301	12.301	12.301																																																				
0	12.297	12.297	12.297																																																				
10	12.295	12.295	12.295																																																				
20	12.290	12.290	12.289																																																				
25	12.287	12.286	12.286																																																				
30	12.282	12.282	12.282																																																				
40	12.276	12.275	12.275																																																				
50	12.267	12.267	12.267																																																				
60	12.264	12.264	12.263																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated ambient temperature.																																																						



Model	PMA100F-12	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+12V8.5A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 ~ 50°C

Input Voltage : 85 ~ 264V

Load Current : 0 ~ 8.5A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	-10	264	0	12.304	±22	±0.2
Minimum Voltage	50	264	8.5	12.260		

COSEL

Model	PMA100F-12	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+12V8.5A																								
1. Graph			2. Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>12.274</td></tr> <tr><td>0.5</td><td>12.263</td></tr> <tr><td>1.0</td><td>12.263</td></tr> <tr><td>2.0</td><td>12.264</td></tr> <tr><td>3.0</td><td>12.264</td></tr> <tr><td>4.0</td><td>12.264</td></tr> <tr><td>5.0</td><td>12.264</td></tr> <tr><td>6.0</td><td>12.264</td></tr> <tr><td>7.0</td><td>12.264</td></tr> <tr><td>8.0</td><td>12.264</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	12.274	0.5	12.263	1.0	12.263	2.0	12.264	3.0	12.264	4.0	12.264	5.0	12.264	6.0	12.264	7.0	12.264	8.0	12.264
Time since start [H]	Output Voltage [V]																								
0.0	12.274																								
0.5	12.263																								
1.0	12.263																								
2.0	12.264																								
3.0	12.264																								
4.0	12.264																								
5.0	12.264																								
6.0	12.264																								
7.0	12.264																								
8.0	12.264																								


* The characteristic of AC200V is equal.

COSEL

Model	PMA100F-12
Item	Rise and Fall Time
Object	+12V8.5A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		253.5	10.5	264.0	27.5	19.5	
230 V		202.5	10.5	213.0	33.0	19.5	



Model	PMA100F-12	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+12V8.5A																																		
1. Graph																																			
<p>Legend: ---□--- Load 50% —△— Load 100%</p>																																			
2. Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>48</td> <td>19</td> </tr> <tr> <td>85</td> <td>50</td> <td>22</td> </tr> <tr> <td>100</td> <td>53</td> <td>24</td> </tr> <tr> <td>120</td> <td>55</td> <td>26</td> </tr> <tr> <td>200</td> <td>61</td> <td>29</td> </tr> <tr> <td>230</td> <td>63</td> <td>30</td> </tr> <tr> <td>264</td> <td>63</td> <td>32</td> </tr> <tr> <td>280</td> <td>63</td> <td>32</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	48	19	85	50	22	100	53	24	120	55	26	200	61	29	230	63	30	264	63	32	280	63	32	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	48	19																																	
85	50	22																																	
100	53	24																																	
120	55	26																																	
200	61	29																																	
230	63	30																																	
264	63	32																																	
280	63	32																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy. Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	PMA100F-12	Temperature	25°C																																																			
Item	Instantaneous Interruption Compensation	Testing Circuitry	Figure A																																																			
Object	+12V8.5A	2.Values																																																				
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p>																																																					
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>105</td><td>156</td><td>164</td></tr> <tr><td>3.00</td><td>78</td><td>86</td><td>90</td></tr> <tr><td>4.50</td><td>51</td><td>59</td><td>61</td></tr> <tr><td>6.00</td><td>38</td><td>44</td><td>46</td></tr> <tr><td>7.50</td><td>30</td><td>35</td><td>36</td></tr> <tr><td>8.50</td><td>23</td><td>30</td><td>31</td></tr> <tr><td>9.35</td><td>21</td><td>27</td><td>28</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	1.50	105	156	164	3.00	78	86	90	4.50	51	59	61	6.00	38	44	46	7.50	30	35	36	8.50	23	30	31	9.35	21	27	28	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Time [ms]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	-	-	-																																																			
1.50	105	156	164																																																			
3.00	78	86	90																																																			
4.50	51	59	61																																																			
6.00	38	44	46																																																			
7.50	30	35	36																																																			
8.50	23	30	31																																																			
9.35	21	27	28																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

Model	PMA100F-12																																							
Item	Minimum Input Voltage for Regulated Output Voltage																																							
Object	+12V8.5A																																							
1. Graph																																								
<p>--- ■ --- Load 50%</p> <p>— △ — Load 100%</p> <p>Input Voltage [V]</p> <p>Ambient Temperature [°C]</p>																																								
<p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																								
Testing Circuitry Figure A																																								
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>41</td> <td>56</td> </tr> <tr> <td>-10</td> <td>40</td> <td>55</td> </tr> <tr> <td>0</td> <td>40</td> <td>55</td> </tr> <tr> <td>10</td> <td>41</td> <td>55</td> </tr> <tr> <td>20</td> <td>41</td> <td>55</td> </tr> <tr> <td>25</td> <td>41</td> <td>55</td> </tr> <tr> <td>30</td> <td>41</td> <td>55</td> </tr> <tr> <td>40</td> <td>41</td> <td>55</td> </tr> <tr> <td>50</td> <td>41</td> <td>56</td> </tr> <tr> <td>60</td> <td>41</td> <td>56</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	41	56	-10	40	55	0	40	55	10	41	55	20	41	55	25	41	55	30	41	55	40	41	55	50	41	56	60	41	56	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																							
	Load 50%	Load 100%																																						
-20	41	56																																						
-10	40	55																																						
0	40	55																																						
10	41	55																																						
20	41	55																																						
25	41	55																																						
30	41	55																																						
40	41	55																																						
50	41	56																																						
60	41	56																																						
--	-	-																																						

COSEL

Model	PMA100F-12	Temperature	25°C																																												
Item	Overcurrent Protection	Testing Circuitry	Figure A																																												
Object	+12V8.5A																																														
1.Graph		2.Values																																													
<p>Input Volt. 100V Input Volt. 230V</p> <p>Output Voltage [V]</p> <p>Load Current [A]</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>12.0</td><td>10.42</td><td>10.40</td></tr> <tr><td>11.4</td><td>11.02</td><td>10.97</td></tr> <tr><td>10.8</td><td>11.01</td><td>10.97</td></tr> <tr><td>9.6</td><td>10.99</td><td>10.98</td></tr> <tr><td>8.4</td><td>10.86</td><td>10.92</td></tr> <tr><td>7.2</td><td>11.12</td><td>11.07</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	12.0	10.42	10.40	11.4	11.02	10.97	10.8	11.01	10.97	9.6	10.99	10.98	8.4	10.86	10.92	7.2	11.12	11.07	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																														
	Input Volt. 100[V]	Input Volt. 230[V]																																													
12.0	10.42	10.40																																													
11.4	11.02	10.97																																													
10.8	11.01	10.97																																													
9.6	10.99	10.98																																													
8.4	10.86	10.92																																													
7.2	11.12	11.07																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													
--	-	-																																													


Note: Slanted line shows the range of the rated load current.

Model PMA100F-12

Item Overvoltage Protection

Object +12V8.5A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-20	15.83	15.76
-10	15.90	15.90
0	16.04	15.97
10	16.11	16.12
20	16.25	16.18
25	16.24	16.24
30	16.31	16.24
40	16.38	16.38
50	16.53	16.45
60	16.60	16.52
--	-	-




Figure A




Figure B (IEC60601-1)