



TEST DATA OF PMA100F-48

Regulated DC Power Supply
June 4, 2010

Approved by : Katsumi Ishikawa
Katsumi Ishikawa Design Manager

Prepared by : Shintaro Oki
Shintaro Oki Design Engineer


COSEL CO.,LTD.

CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 24)

COSSEL

Model	PMA100F-48		
Item	Input Current (by Load Current)		
Object	_____		
1.Graph	—△— Input Volt. 100V - -□-- Input Volt. 200V - -○--- Input Volt. 230V		
 <p>Note: Slanted line shows the range of the rated load current.</p>			
Temperature	25°C		
Testing Circuitry	Figure A		
2.Values			
Load Current [A]	Input Current [A]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
0.00	0.098	0.083	0.090
0.40	0.312	0.241	0.231
0.80	0.515	0.335	0.312
1.20	0.727	0.416	0.392
1.60	0.938	0.496	0.470
2.00	1.148	0.600	0.546
2.10	1.204	0.625	0.568
2.31	1.319	0.676	0.604
--	-	-	-
--	-	-	-
--	-	-	-

COSSEL

Model	PMA100F-48																																																					
Item	Input Power (by Load Current)																																																					
Object	_____																																																					
1.Graph	<p>Input Volt. 100V Input Volt. 200V Input Volt. 230V</p>																																																					
	<p>2.Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>7.0</td><td>7.0</td><td>7.0</td></tr> <tr><td>0.40</td><td>30.2</td><td>30.0</td><td>29.0</td></tr> <tr><td>0.80</td><td>50.9</td><td>52.0</td><td>52.0</td></tr> <tr><td>1.20</td><td>72.3</td><td>73.0</td><td>72.0</td></tr> <tr><td>1.60</td><td>93.6</td><td>92.0</td><td>92.0</td></tr> <tr><td>2.00</td><td>114.6</td><td>113.0</td><td>113.0</td></tr> <tr><td>2.10</td><td>120.3</td><td>119.0</td><td>119.0</td></tr> <tr><td>2.31</td><td>131.7</td><td>129.0</td><td>128.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	7.0	7.0	7.0	0.40	30.2	30.0	29.0	0.80	50.9	52.0	52.0	1.20	72.3	73.0	72.0	1.60	93.6	92.0	92.0	2.00	114.6	113.0	113.0	2.10	120.3	119.0	119.0	2.31	131.7	129.0	128.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	7.0	7.0	7.0																																																			
0.40	30.2	30.0	29.0																																																			
0.80	50.9	52.0	52.0																																																			
1.20	72.3	73.0	72.0																																																			
1.60	93.6	92.0	92.0																																																			
2.00	114.6	113.0	113.0																																																			
2.10	120.3	119.0	119.0																																																			
2.31	131.7	129.0	128.0																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

Model	PMA100F-48	Temperature	25°C																														
Item	Efficiency (by Input Voltage)	Testing Circuitry	Figure A																														
Object	_____																																
1. Graph			2. Values																														
<p>The graph plots Efficiency [%] on the y-axis (44 to 100) against Input Voltage [V] on the x-axis (50 to 300). Two data series are shown: Load 50% (dashed line with square markers) and Load 100% (solid line with triangle markers). Both series show efficiency increasing slightly with input voltage. A slanted line indicates the rated input voltage range.</p> <table border="1"> <thead> <tr> <th>Input Voltage [V]</th> <th>Efficiency Load 50% [%]</th> <th>Efficiency Load 100% [%]</th> </tr> </thead> <tbody> <tr><td>75</td><td>77.8</td><td>82.1</td></tr> <tr><td>85</td><td>78.4</td><td>83.6</td></tr> <tr><td>100</td><td>78.9</td><td>84.2</td></tr> <tr><td>120</td><td>79.7</td><td>85.5</td></tr> <tr><td>200</td><td>79.5</td><td>86.1</td></tr> <tr><td>230</td><td>78.4</td><td>86.1</td></tr> <tr><td>264</td><td>79.6</td><td>86.5</td></tr> <tr><td>280</td><td>80.8</td><td>86.5</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>				Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]	75	77.8	82.1	85	78.4	83.6	100	78.9	84.2	120	79.7	85.5	200	79.5	86.1	230	78.4	86.1	264	79.6	86.5	280	80.8	86.5	--	-	-
Input Voltage [V]	Efficiency Load 50% [%]	Efficiency Load 100% [%]																															
75	77.8	82.1																															
85	78.4	83.6																															
100	78.9	84.2																															
120	79.7	85.5																															
200	79.5	86.1																															
230	78.4	86.1																															
264	79.6	86.5																															
280	80.8	86.5																															
--	-	-																															
<p>Note: Slanted line shows the range of the rated input voltage.</p>																																	


COSEL

Model	PMA100F-48	Temperature	25°C																																																				
Item	Efficiency (by Load Current)	Testing Circuitry	Figure A																																																				
Object	—	—	—																																																				
1.Graph	<p>—▲— Input Volt. 100V - - - ■ - Input Volt. 200V - - ○ - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Efficiency [100V] (%)</th> <th>Efficiency [200V] (%)</th> <th>Efficiency [230V] (%)</th> </tr> </thead> <tbody> <tr><td>0.40</td><td>65.8</td><td>65.9</td><td>68.3</td></tr> <tr><td>0.80</td><td>76.7</td><td>75.0</td><td>75.0</td></tr> <tr><td>1.20</td><td>80.5</td><td>79.7</td><td>80.8</td></tr> <tr><td>1.60</td><td>82.7</td><td>84.1</td><td>84.0</td></tr> <tr><td>2.00</td><td>84.2</td><td>85.4</td><td>85.4</td></tr> <tr><td>2.10</td><td>84.2</td><td>86.1</td><td>86.1</td></tr> <tr><td>2.31</td><td>84.6</td><td>86.4</td><td>87.0</td></tr> </tbody> </table>				Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)	0.40	65.8	65.9	68.3	0.80	76.7	75.0	75.0	1.20	80.5	79.7	80.8	1.60	82.7	84.1	84.0	2.00	84.2	85.4	85.4	2.10	84.2	86.1	86.1	2.31	84.6	86.4	87.0																			
Load Current [A]	Efficiency [100V] (%)	Efficiency [200V] (%)	Efficiency [230V] (%)																																																				
0.40	65.8	65.9	68.3																																																				
0.80	76.7	75.0	75.0																																																				
1.20	80.5	79.7	80.8																																																				
1.60	82.7	84.1	84.0																																																				
2.00	84.2	85.4	85.4																																																				
2.10	84.2	86.1	86.1																																																				
2.31	84.6	86.4	87.0																																																				
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.40</td><td>65.8</td><td>65.9</td><td>68.3</td></tr> <tr><td>0.80</td><td>76.7</td><td>75.0</td><td>75.0</td></tr> <tr><td>1.20</td><td>80.5</td><td>79.7</td><td>80.8</td></tr> <tr><td>1.60</td><td>82.7</td><td>84.1</td><td>84.0</td></tr> <tr><td>2.00</td><td>84.2</td><td>85.4</td><td>85.4</td></tr> <tr><td>2.10</td><td>84.2</td><td>86.1</td><td>86.1</td></tr> <tr><td>2.31</td><td>84.6</td><td>86.4</td><td>87.0</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.40	65.8	65.9	68.3	0.80	76.7	75.0	75.0	1.20	80.5	79.7	80.8	1.60	82.7	84.1	84.0	2.00	84.2	85.4	85.4	2.10	84.2	86.1	86.1	2.31	84.6	86.4	87.0	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																						
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																				
0.00	-	-	-																																																				
0.40	65.8	65.9	68.3																																																				
0.80	76.7	75.0	75.0																																																				
1.20	80.5	79.7	80.8																																																				
1.60	82.7	84.1	84.0																																																				
2.00	84.2	85.4	85.4																																																				
2.10	84.2	86.1	86.1																																																				
2.31	84.6	86.4	87.0																																																				
--	-	-	-																																																				
--	-	-	-																																																				
--	-	-	-																																																				
Note:	Slanted line shows the range of the rated load current.																																																						

Model	PMA100F-48
Item	Power Factor (by Input Voltage)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
75	0.999	0.999
85	0.998	0.999
100	0.989	0.998
120	0.979	0.992
200	0.831	0.944
230	0.774	0.908
264	0.610	0.824
280	0.548	0.722
--	-	-

Note: Slanted line shows the range of the rated input voltage.




COSEL

Model	PMA100F-48	Temperature Testing Circuitry	25°C Figure A																																		
Item	Power Factor (by Load Current)																																				
Object	_____	2. Values																																			
1. Graph	<p>—△— Input Volt. 100V - - -□- Input Volt. 200V - - ○- Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 100V</th> <th>Input Volt. 200V</th> <th>Input Volt. 230V</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>0.714</td><td>0.412</td><td>0.333</td></tr> <tr><td>0.40</td><td>0.968</td><td>0.625</td><td>0.547</td></tr> <tr><td>0.80</td><td>0.988</td><td>0.776</td><td>0.722</td></tr> <tr><td>1.20</td><td>0.993</td><td>0.880</td><td>0.800</td></tr> <tr><td>1.60</td><td>0.997</td><td>0.929</td><td>0.852</td></tr> <tr><td>2.00</td><td>0.997</td><td>0.942</td><td>0.897</td></tr> <tr><td>2.10</td><td>0.998</td><td>0.952</td><td>0.908</td></tr> <tr><td>2.31</td><td>0.998</td><td>0.956</td><td>0.921</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V	0.00	0.714	0.412	0.333	0.40	0.968	0.625	0.547	0.80	0.988	0.776	0.722	1.20	0.993	0.880	0.800	1.60	0.997	0.929	0.852	2.00	0.997	0.942	0.897	2.10	0.998	0.952	0.908	2.31	0.998	0.956	0.921
Load Current [A]	Input Volt. 100V	Input Volt. 200V	Input Volt. 230V																																		
0.00	0.714	0.412	0.333																																		
0.40	0.968	0.625	0.547																																		
0.80	0.988	0.776	0.722																																		
1.20	0.993	0.880	0.800																																		
1.60	0.997	0.929	0.852																																		
2.00	0.997	0.942	0.897																																		
2.10	0.998	0.952	0.908																																		
2.31	0.998	0.956	0.921																																		

Note: Slanted line shows the range of the rated load current.

COSEL

Model	PMA100F-48	Temperature Testing Circuitry Figure A
Item	Inrush Current	
Object	_____	





Model	PMA100F-48	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	_____		

1. Results

Standards		Input Volt.			Note	[mA]
		100 [V]	200 [V]	240 [V]		
IEC60601	Both phases	0.04	0.10	0.16	Operation	
	One of phases	0.09	0.19	0.22		

The value for "One of phases" is the reference value only.


2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.

Model	PMA100F-48
Item	Line Regulation
Object	+48V2.1A

Temperature 25°C
Testing Circuitry Figure A

1. Graph



Note: Slanted line shows the range of the rated input voltage.

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	48.093	48.101
85	48.094	48.101
100	48.095	48.101
120	48.096	48.102
200	48.097	48.103
230	48.099	48.104
264	48.101	48.105
280	48.101	48.106
--	-	-

Model	PMA100F-48	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+48V2.1A																																																					
1.Graph	<p>—△— Input Volt. 100V - - -□- - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from the graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Output Voltage [V] (Input 100V)</th> <th>Output Voltage [V] (Input 200V)</th> <th>Output Voltage [V] (Input 230V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>48.133</td><td>48.133</td><td>48.133</td></tr> <tr><td>0.40</td><td>48.125</td><td>48.123</td><td>48.125</td></tr> <tr><td>0.80</td><td>48.124</td><td>48.124</td><td>48.124</td></tr> <tr><td>1.20</td><td>48.123</td><td>48.122</td><td>48.123</td></tr> <tr><td>1.60</td><td>48.123</td><td>48.122</td><td>48.122</td></tr> <tr><td>2.00</td><td>48.122</td><td>48.121</td><td>48.122</td></tr> <tr><td>2.10</td><td>48.122</td><td>48.122</td><td>48.122</td></tr> <tr><td>2.31</td><td>48.122</td><td>48.121</td><td>48.121</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V] (Input 100V)	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 230V)	0.00	48.133	48.133	48.133	0.40	48.125	48.123	48.125	0.80	48.124	48.124	48.124	1.20	48.123	48.122	48.123	1.60	48.123	48.122	48.122	2.00	48.122	48.121	48.122	2.10	48.122	48.122	48.122	2.31	48.122	48.121	48.121															
Load Current [A]	Output Voltage [V] (Input 100V)	Output Voltage [V] (Input 200V)	Output Voltage [V] (Input 230V)																																																			
0.00	48.133	48.133	48.133																																																			
0.40	48.125	48.123	48.125																																																			
0.80	48.124	48.124	48.124																																																			
1.20	48.123	48.122	48.123																																																			
1.60	48.123	48.122	48.122																																																			
2.00	48.122	48.121	48.122																																																			
2.10	48.122	48.122	48.122																																																			
2.31	48.122	48.121	48.121																																																			
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>48.133</td><td>48.133</td><td>48.133</td></tr> <tr><td>0.40</td><td>48.125</td><td>48.123</td><td>48.125</td></tr> <tr><td>0.80</td><td>48.124</td><td>48.124</td><td>48.124</td></tr> <tr><td>1.20</td><td>48.123</td><td>48.122</td><td>48.123</td></tr> <tr><td>1.60</td><td>48.123</td><td>48.122</td><td>48.122</td></tr> <tr><td>2.00</td><td>48.122</td><td>48.121</td><td>48.122</td></tr> <tr><td>2.10</td><td>48.122</td><td>48.122</td><td>48.122</td></tr> <tr><td>2.31</td><td>48.122</td><td>48.121</td><td>48.121</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	48.133	48.133	48.133	0.40	48.125	48.123	48.125	0.80	48.124	48.124	48.124	1.20	48.123	48.122	48.123	1.60	48.123	48.122	48.122	2.00	48.122	48.121	48.122	2.10	48.122	48.122	48.122	2.31	48.122	48.121	48.121	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.00	48.133	48.133	48.133																																																			
0.40	48.125	48.123	48.125																																																			
0.80	48.124	48.124	48.124																																																			
1.20	48.123	48.122	48.123																																																			
1.60	48.123	48.122	48.122																																																			
2.00	48.122	48.121	48.122																																																			
2.10	48.122	48.122	48.122																																																			
2.31	48.122	48.121	48.121																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			

Note: Slanted line shows the range of the rated load current.

COSEL

Model PMA100F-48

Item Dynamic Load Response

Object +48V2.1A


Temperature
Testing Circuitry 25°C
Figure AInput Volt. 100 V
Cycle 1000 ms

Response. t1=t2=50us. Typ

Min. Load (0A) ↔
Load 100% (2.1A)


200 mV/div

10 ms/div

Min. Load (0A) ↔
Load 50% (1.05A)

200 mV/div

10 ms/div



COSEL

Model	PMA100F-48																																						
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																					
Object	+48V2.1A																																						
1.Graph																																							
		2.Values																																					
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr> <td>0.00</td><td>15</td><td>15</td></tr> <tr> <td>0.40</td><td>35</td><td>35</td></tr> <tr> <td>0.80</td><td>40</td><td>40</td></tr> <tr> <td>1.20</td><td>40</td><td>40</td></tr> <tr> <td>1.60</td><td>50</td><td>55</td></tr> <tr> <td>2.00</td><td>55</td><td>55</td></tr> <tr> <td>2.10</td><td>55</td><td>55</td></tr> <tr> <td>2.31</td><td>55</td><td>55</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.00	15	15	0.40	35	35	0.80	40	40	1.20	40	40	1.60	50	55	2.00	55	55	2.10	55	55	2.31	55	55	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																						
	Input Volt. 100 [V]	Input Volt. 200 [V]																																					
0.00	15	15																																					
0.40	35	35																																					
0.80	40	40																																					
1.20	40	40																																					
1.60	50	55																																					
2.00	55	55																																					
2.10	55	55																																					
2.31	55	55																																					
--	-	-																																					
--	-	-																																					
--	-	-																																					
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p>																																							
<p>Fig. Complex Ripple Wave Form</p>																																							


COSEL

Model	PMA100F-48																																							
Item	Ripple-Noise	Temperature 25°C Testing Circuitry Figure A																																						
Object	+48V2.1A																																							
1. Graph																																								
<p>Graph showing Ripple-Noise [mV] vs Load Current [A]. The Y-axis ranges from 0 to 200 mV, and the X-axis ranges from 0 to 2.31 A. Two linear plots are shown for Input Voltages 100V and 200V. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple-Noise [mV] (Input Volt. 100V)</th> <th>Ripple-Noise [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>65</td><td>65</td></tr> <tr><td>0.40</td><td>65</td><td>65</td></tr> <tr><td>0.80</td><td>65</td><td>70</td></tr> <tr><td>1.20</td><td>80</td><td>80</td></tr> <tr><td>1.60</td><td>90</td><td>95</td></tr> <tr><td>2.00</td><td>105</td><td>105</td></tr> <tr><td>2.10</td><td>105</td><td>110</td></tr> <tr><td>2.31</td><td>110</td><td>110</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV] (Input Volt. 100V)	Ripple-Noise [mV] (Input Volt. 200V)	0.00	65	65	0.40	65	65	0.80	65	70	1.20	80	80	1.60	90	95	2.00	105	105	2.10	105	110	2.31	110	110	--	-	-	--	-	-	--	-	-		
Load Current [A]	Ripple-Noise [mV] (Input Volt. 100V)	Ripple-Noise [mV] (Input Volt. 200V)																																						
0.00	65	65																																						
0.40	65	65																																						
0.80	65	70																																						
1.20	80	80																																						
1.60	90	95																																						
2.00	105	105																																						
2.10	105	110																																						
2.31	110	110																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
2. Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple-Noise [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>65</td><td>65</td></tr> <tr><td>0.40</td><td>65</td><td>65</td></tr> <tr><td>0.80</td><td>65</td><td>70</td></tr> <tr><td>1.20</td><td>80</td><td>80</td></tr> <tr><td>1.60</td><td>90</td><td>95</td></tr> <tr><td>2.00</td><td>105</td><td>105</td></tr> <tr><td>2.10</td><td>105</td><td>110</td></tr> <tr><td>2.31</td><td>110</td><td>110</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple-Noise [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.00	65	65	0.40	65	65	0.80	65	70	1.20	80	80	1.60	90	95	2.00	105	105	2.10	105	110	2.31	110	110	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple-Noise [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0.00	65	65																																						
0.40	65	65																																						
0.80	65	70																																						
1.20	80	80																																						
1.60	90	95																																						
2.00	105	105																																						
2.10	105	110																																						
2.31	110	110																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple-Noise is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	PMA100F-48
Item	Ripple Voltage (by Ambient Temp.)
Object	+48V2.1A

1. Graph




Measured by 20 MHz Oscilloscope.

Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	215	215
-10	125	125
0	115	115
25	55	55
50	55	55
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Model PMA100F-48 Item Ambient Temperature Drift Object +48V2.1A	Testing Circuitry Figure A																																																					
	1.Graph	—△— Input Volt. 100V	—□— Input Volt. 200V																																																			
		---■--- Input Volt. 230V	—○— Input Volt. 230V																																																			
 <p>Output Voltage [V]</p> <p>Ambient Temperature [°C]</p> <p>Load 100%</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V (solid line with triangle) Input Volt. 200V (dashed line with square) Input Volt. 230V (dash-dot line with circle) <p>Note: Slanted line shows the range of the rated ambient temperature.</p>			2.Values																																																			
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>-20</td> <td>48.100</td> <td>48.102</td> <td>48.101</td> </tr> <tr> <td>-10</td> <td>48.097</td> <td>48.097</td> <td>48.098</td> </tr> <tr> <td>0</td> <td>48.093</td> <td>48.093</td> <td>48.093</td> </tr> <tr> <td>10</td> <td>48.101</td> <td>48.102</td> <td>48.101</td> </tr> <tr> <td>20</td> <td>48.099</td> <td>48.100</td> <td>48.099</td> </tr> <tr> <td>25</td> <td>48.102</td> <td>48.103</td> <td>48.103</td> </tr> <tr> <td>30</td> <td>48.101</td> <td>48.102</td> <td>48.102</td> </tr> <tr> <td>40</td> <td>48.090</td> <td>48.091</td> <td>48.091</td> </tr> <tr> <td>50</td> <td>48.081</td> <td>48.080</td> <td>48.080</td> </tr> <tr> <td>60</td> <td>48.058</td> <td>48.059</td> <td>48.058</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Ambient Temperature [°C]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	-20	48.100	48.102	48.101	-10	48.097	48.097	48.098	0	48.093	48.093	48.093	10	48.101	48.102	48.101	20	48.099	48.100	48.099	25	48.102	48.103	48.103	30	48.101	48.102	48.102	40	48.090	48.091	48.091	50	48.081	48.080	48.080	60	48.058	48.059	48.058	--	-	-	-
Ambient Temperature [°C]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
-20	48.100	48.102	48.101																																																			
-10	48.097	48.097	48.098																																																			
0	48.093	48.093	48.093																																																			
10	48.101	48.102	48.101																																																			
20	48.099	48.100	48.099																																																			
25	48.102	48.103	48.103																																																			
30	48.101	48.102	48.102																																																			
40	48.090	48.091	48.091																																																			
50	48.081	48.080	48.080																																																			
60	48.058	48.059	48.058																																																			
--	-	-	-																																																			



Model	PMA100F-48	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+48V2.1A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 ~ 50°C

Input Voltage : 85 ~ 264V

Load Current : 0 ~ 2.1A


* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	30	200	0	48.109	± 15	± 0.1
Minimum Voltage	50	264	2.1	48.080		

COSEL

Model	PMA100F-48	Temperature	25°C																						
Item	Time Lapse Drift	Testing Circuitry	Figure A																						
Object	+48V2.1A																								
1.Graph			2.Values																						
 <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>			<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>48.064</td></tr> <tr><td>0.5</td><td>48.144</td></tr> <tr><td>1.0</td><td>48.144</td></tr> <tr><td>2.0</td><td>48.144</td></tr> <tr><td>3.0</td><td>48.144</td></tr> <tr><td>4.0</td><td>48.144</td></tr> <tr><td>5.0</td><td>48.144</td></tr> <tr><td>6.0</td><td>48.144</td></tr> <tr><td>7.0</td><td>48.144</td></tr> <tr><td>8.0</td><td>48.144</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	48.064	0.5	48.144	1.0	48.144	2.0	48.144	3.0	48.144	4.0	48.144	5.0	48.144	6.0	48.144	7.0	48.144	8.0	48.144
Time since start [H]	Output Voltage [V]																								
0.0	48.064																								
0.5	48.144																								
1.0	48.144																								
2.0	48.144																								
3.0	48.144																								
4.0	48.144																								
5.0	48.144																								
6.0	48.144																								
7.0	48.144																								
8.0	48.144																								

* The characteristic of AC200V is equal.

COSEL


Model PMA100F-48

Item Rise and Fall Time

Object +48V2.1A


Temperature 25°C
Testing Circuitry Figure A

1. Graph



2. Values

Input Volt.	Time	Td	Tr	Ts	Th	Tf	[ms]
100 V		250.5	21.5	272.0	27.5	57.4	
230 V		204.5	22.0	226.5	32.7	57.4	



Model	PMA100F-48	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+48V2.1A																																		
1. Graph																																			
<p>Y-axis: Hold-Up Time [ms] (logarithmic scale: 1, 10, 100, 1000)</p> <p>X-axis: Input Voltage [V] (linear scale: 50, 100, 150, 200, 250, 300)</p> <p>Legend:</p> <ul style="list-style-type: none"> Load 50% (dashed line with squares) Load 100% (solid line with triangles) 																																			
2. Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>43</td> <td>18</td> </tr> <tr> <td>85</td> <td>46</td> <td>20</td> </tr> <tr> <td>100</td> <td>48</td> <td>22</td> </tr> <tr> <td>120</td> <td>50</td> <td>24</td> </tr> <tr> <td>200</td> <td>55</td> <td>28</td> </tr> <tr> <td>230</td> <td>57</td> <td>29</td> </tr> <tr> <td>264</td> <td>58</td> <td>30</td> </tr> <tr> <td>280</td> <td>58</td> <td>30</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	43	18	85	46	20	100	48	22	120	50	24	200	55	28	230	57	29	264	58	30	280	58	30	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	43	18																																	
85	46	20																																	
100	48	22																																	
120	50	24																																	
200	55	28																																	
230	57	29																																	
264	58	30																																	
280	58	30																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			

COSEL

Model	PMA100F-48	Temperature Testing Circuitry 25°C Figure A																																																			
Item	Instantaneous Interruption Compensation																																																				
Object	+48V2.1A																																																				
1.Graph	<p>—▲— Input Volt. 100V - - - □ - - Input Volt. 200V - - ○ - - Input Volt. 230V</p> <table border="1"> <caption>Data points estimated from Graph 1</caption> <thead> <tr> <th>Load Current [A]</th> <th>100V [ms]</th> <th>200V [ms]</th> <th>230V [ms]</th> </tr> </thead> <tbody> <tr><td>0.40</td><td>82</td><td>136</td><td>139</td></tr> <tr><td>0.80</td><td>66</td><td>73</td><td>76</td></tr> <tr><td>1.20</td><td>42</td><td>49</td><td>51</td></tr> <tr><td>1.60</td><td>31</td><td>37</td><td>38</td></tr> <tr><td>2.00</td><td>22</td><td>29</td><td>30</td></tr> <tr><td>2.10</td><td>22</td><td>28</td><td>29</td></tr> <tr><td>2.31</td><td>20</td><td>25</td><td>26</td></tr> </tbody> </table>	Load Current [A]	100V [ms]	200V [ms]	230V [ms]	0.40	82	136	139	0.80	66	73	76	1.20	42	49	51	1.60	31	37	38	2.00	22	29	30	2.10	22	28	29	2.31	20	25	26																				
Load Current [A]	100V [ms]	200V [ms]	230V [ms]																																																		
0.40	82	136	139																																																		
0.80	66	73	76																																																		
1.20	42	49	51																																																		
1.60	31	37	38																																																		
2.00	22	29	30																																																		
2.10	22	28	29																																																		
2.31	20	25	26																																																		
2.Values																																																					
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Time [ms]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.00</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.40</td><td>82</td><td>136</td><td>139</td></tr> <tr><td>0.80</td><td>66</td><td>73</td><td>76</td></tr> <tr><td>1.20</td><td>42</td><td>49</td><td>51</td></tr> <tr><td>1.60</td><td>31</td><td>37</td><td>38</td></tr> <tr><td>2.00</td><td>22</td><td>29</td><td>30</td></tr> <tr><td>2.10</td><td>22</td><td>28</td><td>29</td></tr> <tr><td>2.31</td><td>20</td><td>25</td><td>26</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>	Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.00	-	-	-	0.40	82	136	139	0.80	66	73	76	1.20	42	49	51	1.60	31	37	38	2.00	22	29	30	2.10	22	28	29	2.31	20	25	26	--	-	-	-	--	-	-	-	--	-	-	-	
Load Current [A]	Time [ms]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.00	-	-	-																																																		
0.40	82	136	139																																																		
0.80	66	73	76																																																		
1.20	42	49	51																																																		
1.60	31	37	38																																																		
2.00	22	29	30																																																		
2.10	22	28	29																																																		
2.31	20	25	26																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		

Note: Slanted line shows the range of the rated load current.


<p>Model PMA100F-48</p> <p>Item Minimum Input Voltage for Regulated Output Voltage</p> <p>Object +48V2.1A</p>	Testing Circuitry Figure A																																						
	1. Graph	2. Values																																					
	<p>Legend:</p> <ul style="list-style-type: none"> ---□--- Load 50% —△— Load 100% <p>Ambient Temperature [°C]</p> <p>Input Voltage [V]</p>	<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>41</td><td>55</td> </tr> <tr> <td>-10</td><td>41</td><td>55</td> </tr> <tr> <td>0</td><td>40</td><td>54</td> </tr> <tr> <td>10</td><td>41</td><td>54</td> </tr> <tr> <td>20</td><td>41</td><td>54</td> </tr> <tr> <td>25</td><td>41</td><td>54</td> </tr> <tr> <td>30</td><td>41</td><td>54</td> </tr> <tr> <td>40</td><td>41</td><td>54</td> </tr> <tr> <td>50</td><td>41</td><td>55</td> </tr> <tr> <td>60</td><td>41</td><td>55</td> </tr> <tr> <td>--</td><td>-</td><td>-</td> </tr> </tbody> </table>	Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	41	55	-10	41	55	0	40	54	10	41	54	20	41	54	25	41	54	30	41	54	40	41	54	50	41	55	60	41	55	--	-
Ambient Temperature [°C]	Input Voltage [V]																																						
	Load 50%	Load 100%																																					
-20	41	55																																					
-10	41	55																																					
0	40	54																																					
10	41	54																																					
20	41	54																																					
25	41	54																																					
30	41	54																																					
40	41	54																																					
50	41	55																																					
60	41	55																																					
--	-	-																																					

Note: Slanted line shows the range of the rated ambient temperature.

Model	PMA100F-48	Temperature Testing Circuitry 25°C Figure A																																												
Item	Overcurrent Protection																																													
Object	+48V2.1A																																													
1.Graph		2.Values																																												
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Note: Slanted line shows the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>48.0</td><td>2.56</td><td>2.56</td></tr> <tr><td>45.6</td><td>2.58</td><td>2.64</td></tr> <tr><td>43.2</td><td>2.66</td><td>2.65</td></tr> <tr><td>38.4</td><td>2.57</td><td>2.62</td></tr> <tr><td>33.6</td><td>2.59</td><td>2.57</td></tr> <tr><td>28.8</td><td>2.64</td><td>2.68</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>	Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	48.0	2.56	2.56	45.6	2.58	2.64	43.2	2.66	2.65	38.4	2.57	2.62	33.6	2.59	2.57	28.8	2.64	2.68	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-	--	-	-
Output Voltage [V]	Load Current [A]																																													
	Input Volt. 100[V]	Input Volt. 230[V]																																												
48.0	2.56	2.56																																												
45.6	2.58	2.64																																												
43.2	2.66	2.65																																												
38.4	2.57	2.62																																												
33.6	2.59	2.57																																												
28.8	2.64	2.68																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												
--	-	-																																												

Model	PMA100F-48
Item	Ovvoltage Protection
Object	+48V2.1A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-20	59.24	59.03
-10	59.73	59.73
0	60.29	60.22
10	60.78	60.71
20	61.27	61.20
25	61.48	61.41
30	61.76	61.69
40	62.32	62.25
50	62.81	62.74
60	63.30	63.23
--	-	-




Figure A




Figure B (IEC60601-1)