

TEST DATA OF PMA30F-15

Regulated DC Power Supply

June 4, 2010

Approved by : Katsumi Ishikawa
Katsumi Ishikawa Design Manager

Prepared by : Tsutomu Okano
Tsutomu Okano Design Engineer

COSEL CO.,LTD.

CONTENTS

1. Input Current (by Load Current)	1
2. Input Power (by Load Current)	2
3. Efficiency (by Input Voltage)	3
4. Efficiency (by Load Current)	4
5. Power Factor (by Input Voltage)	5
6. Power Factor (by Load Current)	6
7. Inrush Current	7
8. Leakage Current	8
9. Line Regulation	9
10. Load Regulation	10
11. Dynamic Load Response	11
12. Ripple Voltage (by Load Current)	12
13. Ripple-Noise	13
14. Ripple Voltage (by Ambient Temperature)	14
15. Ambient Temperature Drift	15
16. Output Voltage Accuracy	16
17. Time Lapse Drift	17
18. Rise and Fall Time	18
19. Hold-Up Time	19
20. Instantaneous Interruption Compensation	20
21. Minimum Input Voltage for Regulated Output Voltage	21
22. Overcurrent Protection	22
23. Overvoltage Protection	23
24. Figure of Testing Circuitry	24

(Final Page 24)

COSEL

Model	PMA30F-15																																																					
Item	Input Current (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	—	—	—																																																			
1.Graph	<p>Input Current [A]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.047</td><td>0.036</td><td>0.036</td></tr> <tr><td>0.4</td><td>0.158</td><td>0.111</td><td>0.103</td></tr> <tr><td>0.8</td><td>0.275</td><td>0.170</td><td>0.154</td></tr> <tr><td>1.2</td><td>0.385</td><td>0.236</td><td>0.216</td></tr> <tr><td>1.6</td><td>0.498</td><td>0.296</td><td>0.270</td></tr> <tr><td>2.0</td><td>0.612</td><td>0.358</td><td>0.325</td></tr> <tr><td>2.2</td><td>0.671</td><td>0.389</td><td>0.353</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.047	0.036	0.036	0.4	0.158	0.111	0.103	0.8	0.275	0.170	0.154	1.2	0.385	0.236	0.216	1.6	0.498	0.296	0.270	2.0	0.612	0.358	0.325	2.2	0.671	0.389	0.353	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Current [A]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.047	0.036	0.036																																																			
0.4	0.158	0.111	0.103																																																			
0.8	0.275	0.170	0.154																																																			
1.2	0.385	0.236	0.216																																																			
1.6	0.498	0.296	0.270																																																			
2.0	0.612	0.358	0.325																																																			
2.2	0.671	0.389	0.353																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL


Model	PMA30F-15																																																					
Item	Input Power (by Load Current)	Temperature 25°C	Testing Circuitry Figure A																																																			
Object	_____	_____	_____																																																			
1.Graph	—△— Input Volt. 100V - -□-- Input Volt. 200V - -○--- Input Volt. 230V																																																					
	<p>The graph plots Input Power [W] on the y-axis (0 to 50) against Load Current [A] on the x-axis (0.0 to 2.0). Three curves are shown for different input voltages: 100V (solid line with triangles), 200V (dashed line with squares), and 230V (dash-dot line with circles). All curves show a linear increase in power with load current. A slanted line is drawn across the graph, starting from approximately (0.0, 2.0) and ending at (2.0, 42.0), representing the rated load current range.</p>																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>2.00</td><td>2.50</td><td>2.90</td></tr> <tr><td>0.4</td><td>8.50</td><td>9.70</td><td>10.00</td></tr> <tr><td>0.8</td><td>16.10</td><td>16.10</td><td>16.20</td></tr> <tr><td>1.2</td><td>23.40</td><td>23.50</td><td>23.90</td></tr> <tr><td>1.6</td><td>31.00</td><td>30.50</td><td>30.80</td></tr> <tr><td>2.0</td><td>38.90</td><td>37.60</td><td>37.80</td></tr> <tr><td>2.2</td><td>43.00</td><td>41.20</td><td>41.40</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Input Power [W]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	2.00	2.50	2.90	0.4	8.50	9.70	10.00	0.8	16.10	16.10	16.20	1.2	23.40	23.50	23.90	1.6	31.00	30.50	30.80	2.0	38.90	37.60	37.80	2.2	43.00	41.20	41.40	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Input Power [W]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	2.00	2.50	2.90																																																			
0.4	8.50	9.70	10.00																																																			
0.8	16.10	16.10	16.20																																																			
1.2	23.40	23.50	23.90																																																			
1.6	31.00	30.50	30.80																																																			
2.0	38.90	37.60	37.80																																																			
2.2	43.00	41.20	41.40																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
	<p>Note: Slanted line shows the range of the rated load current.</p>																																																					

COSEL

Model	PMA30F-15
Item	Efficiency (by Input Voltage)
Object	_____

Temperature 25°C
Testing Circuitry Figure A

1.Graph




Note: Slanted line shows the range of the rated input voltage.

2.Values

Input Voltage [V]	Efficiency [%]	
	Load 50%	Load 100%
75	74.4	72.2
85	75.5	74.9
100	76.3	77.2
120	76.6	78.8
200	74.7	80.1
230	73.6	79.5
264	72.6	78.6
280	71.9	78.0
--	-	-


COSSEL

Model	PMA30F-15																																																					
Item	Efficiency (by Load Current)	Temperature	25°C																																																			
Object	Testing Circuitry Figure A																																																					
1. Graph																																																						
—△— Input Volt. 100V - -□-- Input Volt. 200V - -○--- Input Volt. 230V			2. Values																																																			
 <p>The graph shows efficiency increasing with load current for all input voltages. The 100V curve is the highest, followed by 200V, and then 230V. A slanted line from the top left to the bottom right indicates the rated load current range.</p>																																																						
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>0.4</td><td>70.7</td><td>62.0</td><td>60.1</td></tr> <tr> <td>0.8</td><td>74.7</td><td>74.7</td><td>74.2</td></tr> <tr> <td>1.2</td><td>77.1</td><td>76.8</td><td>75.5</td></tr> <tr> <td>1.6</td><td>77.6</td><td>78.8</td><td>78.1</td></tr> <tr> <td>2.0</td><td>77.2</td><td>80.1</td><td>79.5</td></tr> <tr> <td>2.2</td><td>76.9</td><td>80.2</td><td>79.8</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr> <td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>				Load Current [A]	Efficiency [%]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	0.4	70.7	62.0	60.1	0.8	74.7	74.7	74.2	1.2	77.1	76.8	75.5	1.6	77.6	78.8	78.1	2.0	77.2	80.1	79.5	2.2	76.9	80.2	79.8	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Efficiency [%]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	-	-	-																																																			
0.4	70.7	62.0	60.1																																																			
0.8	74.7	74.7	74.2																																																			
1.2	77.1	76.8	75.5																																																			
1.6	77.6	78.8	78.1																																																			
2.0	77.2	80.1	79.5																																																			
2.2	76.9	80.2	79.8																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model	PMA30F-15
Item	Power Factor (by Input Voltage)
Object	_____

1. Graph



Note: Slanted line shows the range of the rated input voltage.

 Temperature 25°C
 Testing Circuitry Figure A

2. Values

Input Voltage [V]	Power Factor	
	Load 50%	Load 100%
75	0.645	0.686
85	0.620	0.661
100	0.593	0.631
120	0.563	0.600
200	0.487	0.517
230	0.469	0.500
264	0.452	0.481
280	0.447	0.475
--	-	-

COSEL



Model	PMA30F-15	Temperature	25°C																																																			
Item	Power Factor (by Load Current)	Testing Circuitry	Figure A																																																			
Object	_____																																																					
1.Graph		2.Values																																																				
		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Power Factor</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>0.426</td><td>0.347</td><td>0.349</td></tr> <tr><td>0.4</td><td>0.535</td><td>0.435</td><td>0.424</td></tr> <tr><td>0.8</td><td>0.585</td><td>0.472</td><td>0.458</td></tr> <tr><td>1.2</td><td>0.606</td><td>0.499</td><td>0.482</td></tr> <tr><td>1.6</td><td>0.622</td><td>0.514</td><td>0.495</td></tr> <tr><td>2.0</td><td>0.635</td><td>0.525</td><td>0.505</td></tr> <tr><td>2.2</td><td>0.640</td><td>0.529</td><td>0.510</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>		Load Current [A]	Power Factor			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	0.426	0.347	0.349	0.4	0.535	0.435	0.424	0.8	0.585	0.472	0.458	1.2	0.606	0.499	0.482	1.6	0.622	0.514	0.495	2.0	0.635	0.525	0.505	2.2	0.640	0.529	0.510	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Power Factor																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	0.426	0.347	0.349																																																			
0.4	0.535	0.435	0.424																																																			
0.8	0.585	0.472	0.458																																																			
1.2	0.606	0.499	0.482																																																			
1.6	0.622	0.514	0.495																																																			
2.0	0.635	0.525	0.505																																																			
2.2	0.640	0.529	0.510																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
<p>Note: Slanted line shows the range of the rated load current.</p>																																																						

COSEL

Model PMA30F-15

Item Inrush Current

Object _____

Temperature 25°C
Testing Circuitry Figure AInput
Current
[20A/div]Input
Current
[20A/div]

Primary inrush current

Secondary inrush current



Model	PMA30F-15	Temperature	25°C
Item	Leakage Current	Testing Circuitry	Figure B
Object	—————		

1. Results

Standards		Input Volt.			Note
		100 [V]	200 [V]	240 [V]	
IEC60601	Both phases	0.03	0.06	0.08	Operation
	One of phases	0.04	0.10	0.12	Stand by

The value for "One of phases" is the reference value only.

2. Condition

Leakage current value is concluded after measuring both phases of AC input and by choosing the larger one.


Model PMA30F-15

Item Line Regulation

Object +15V2A

1.Graph

---□--- Load 50%
 —△— Load 100%



Note: Slanted line shows the range of the rated input voltage.


Temperature 25°C
 Testing Circuitry Figure A

2.Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	15.004	15.000
85	15.004	15.001
100	15.004	15.002
120	15.005	15.002
200	15.005	15.003
230	15.005	15.003
264	15.005	15.003
280	15.005	15.004
--	-	-

COSEL

Model	PMA30F-15	Temperature	25°C																																																			
Item	Load Regulation	Testing Circuitry	Figure A																																																			
Object	+15V2A																																																					
1.Graph	<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Legend:</p> <ul style="list-style-type: none"> Input Volt. 100V Input Volt. 200V Input Volt. 230V 																																																					
2.Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 200[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>15.007</td> <td>15.008</td> <td>15.008</td> </tr> <tr> <td>0.4</td> <td>15.006</td> <td>15.007</td> <td>15.007</td> </tr> <tr> <td>0.8</td> <td>15.005</td> <td>15.006</td> <td>15.006</td> </tr> <tr> <td>1.2</td> <td>15.004</td> <td>15.005</td> <td>15.005</td> </tr> <tr> <td>1.6</td> <td>15.003</td> <td>15.005</td> <td>15.005</td> </tr> <tr> <td>2.0</td> <td>15.002</td> <td>15.004</td> <td>15.004</td> </tr> <tr> <td>2.2</td> <td>15.002</td> <td>15.003</td> <td>15.003</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	15.007	15.008	15.008	0.4	15.006	15.007	15.007	0.8	15.005	15.006	15.006	1.2	15.004	15.005	15.005	1.6	15.003	15.005	15.005	2.0	15.002	15.004	15.004	2.2	15.002	15.003	15.003	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-	-
Load Current [A]	Output Voltage [V]																																																					
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																			
0.0	15.007	15.008	15.008																																																			
0.4	15.006	15.007	15.007																																																			
0.8	15.005	15.006	15.006																																																			
1.2	15.004	15.005	15.005																																																			
1.6	15.003	15.005	15.005																																																			
2.0	15.002	15.004	15.004																																																			
2.2	15.002	15.003	15.003																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
--	-	-	-																																																			
Note:	Slanted line shows the range of the rated load current.																																																					

COSEL

COSEL


Model	PMA30F-15																																							
Item	Ripple Voltage (by Load Current)	Temperature 25°C Testing Circuitry Figure A																																						
Object	+15V2A																																							
1.Graph																																								
<p>Graph showing Ripple Voltage [mV] vs Load Current [A]. The Y-axis ranges from 0 to 100 mV, and the X-axis ranges from 0 to 2 A. Two curves are plotted: Input Volt. 100V (solid line with triangles) and Input Volt. 200V (dashed line with circles). Both curves show an increase in ripple voltage as load current increases. A slanted line indicates the rated load current range.</p> <table border="1"> <thead> <tr> <th>Load Current [A]</th> <th>Ripple Voltage [mV] (Input Volt. 100V)</th> <th>Ripple Voltage [mV] (Input Volt. 200V)</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.4</td><td>20</td><td>15</td></tr> <tr><td>0.8</td><td>25</td><td>15</td></tr> <tr><td>1.2</td><td>30</td><td>15</td></tr> <tr><td>1.6</td><td>40</td><td>15</td></tr> <tr><td>2.0</td><td>45</td><td>15</td></tr> <tr><td>2.2</td><td>60</td><td>15</td></tr> </tbody> </table>		Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)	0.0	10	10	0.4	20	15	0.8	25	15	1.2	30	15	1.6	40	15	2.0	45	15	2.2	60	15															
Load Current [A]	Ripple Voltage [mV] (Input Volt. 100V)	Ripple Voltage [mV] (Input Volt. 200V)																																						
0.0	10	10																																						
0.4	20	15																																						
0.8	25	15																																						
1.2	30	15																																						
1.6	40	15																																						
2.0	45	15																																						
2.2	60	15																																						
2.Values																																								
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="2">Ripple Voltage [mV]</th> </tr> <tr> <th>Input Volt. 100 [V]</th> <th>Input Volt. 200 [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>10</td><td>10</td></tr> <tr><td>0.4</td><td>20</td><td>15</td></tr> <tr><td>0.8</td><td>25</td><td>15</td></tr> <tr><td>1.2</td><td>30</td><td>15</td></tr> <tr><td>1.6</td><td>40</td><td>15</td></tr> <tr><td>2.0</td><td>45</td><td>15</td></tr> <tr><td>2.2</td><td>60</td><td>15</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Ripple Voltage [mV]		Input Volt. 100 [V]	Input Volt. 200 [V]	0.0	10	10	0.4	20	15	0.8	25	15	1.2	30	15	1.6	40	15	2.0	45	15	2.2	60	15	--	-	-	--	-	-	--	-	-	--	-	-
Load Current [A]	Ripple Voltage [mV]																																							
	Input Volt. 100 [V]	Input Volt. 200 [V]																																						
0.0	10	10																																						
0.4	20	15																																						
0.8	25	15																																						
1.2	30	15																																						
1.6	40	15																																						
2.0	45	15																																						
2.2	60	15																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
--	-	-																																						
<p>Measured by 20 MHz Oscilloscope. Ripple Voltage is shown as p-p in the figure below. Note: Slanted line shows the range of the rated load current.</p> <p>T1: Due to AC Input Line T2: Due to Switching</p> <p>Fig. Complex Ripple Wave Form</p>																																								

COSEL

Model	PMA30F-15
Item	Ripple-Noise
Object	+15V2A

Temperature 25°C
Testing Circuitry Figure A

1.Graph



2.Values

Load Current [A]	Ripple-Noise [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
0.0	15	15
0.4	35	15
0.8	35	15
1.2	40	25
1.6	40	25
2.0	60	30
2.2	60	30
--	-	-
--	-	-
--	-	-
--	-	-

Measured by MHz Oscilloscope.

Ripple-Noise is shown as p-p in the figure below.

Note: Slanted line shows the range of the rated load current.





Fig. Complex Ripple Wave Form

COSEL

Model	PMA30F-15
Item	Ripple Voltage (by Ambient Temp.)
Object	+15V2A

1. Graph



Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Ripple Voltage [mV]	
	Input Volt. 100 [V]	Input Volt. 200 [V]
-30	125	75
-10	80	30
0	80	30
25	45	15
50	40	15
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-
--	-	-

Measured by 20 MHz Oscilloscope.


Note: Slanted line shows the range of the rated ambient temperature.



Model	PMA30F-15
Item	Ambient Temperature Drift
Object	+15V2A

1.Graph

—△— Input Volt. 100V
 - -□--- Input Volt. 200V
 - -○--- Input Volt. 230V



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Output Voltage [V]		
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]
-20	15.011	15.013	15.014
-10	15.011	15.013	15.014
0	15.012	15.014	15.014
10	15.011	15.012	15.012
20	15.014	15.015	15.015
25	15.013	15.015	15.015
30	15.014	15.015	15.015
40	15.012	15.014	15.014
50	15.007	15.008	15.008
60	15.001	15.002	15.002
--	-	-	-



Model	PMA30F-15	Testing Circuitry Figure A
Item	Output Voltage Accuracy	
Object	+15V2A	

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10 - 50°C

Input Voltage : 85 - 264V

Load Current : 0 - 2A

* Output Voltage Accuracy = $\pm(\text{Maximum of Output Voltage} - \text{Minimum of Output Voltage}) / 2$

$$\text{* Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage[V]	Output		Output Voltage Accuracy	
			Current[A]	Voltage[V]	Value [mV]	Ration [%]
Maximum Voltage	20	264	0	15.011	±7	±0.1
Minimum Voltage	50	85	2	14.998		

COSEL


Model PMA30F-15

Item Time Lapse Drift

Object +15V2A

Temperature 25°C
Testing Circuitry Figure A


1. Graph



2. Values

Time since start [H]	Output Voltage [V]
0.0	15.002
0.5	15.002
1.0	15.002
2.0	15.002
3.0	15.002
4.0	15.002
5.0	15.002
6.0	15.002
7.0	15.002
8.0	15.002

* The characteristic of AC100V is equal.

COSEL



Model	PMA30F-15	Temperature	25°C																																
Item	Hold-Up Time	Testing Circuitry	Figure A																																
Object	+15V2A																																		
1. Graph																																			
2. Values																																			
<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [ms]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>23</td> <td>9</td> </tr> <tr> <td>85</td> <td>33</td> <td>14</td> </tr> <tr> <td>100</td> <td>51</td> <td>23</td> </tr> <tr> <td>120</td> <td>79</td> <td>38</td> </tr> <tr> <td>200</td> <td>250</td> <td>126</td> </tr> <tr> <td>230</td> <td>336</td> <td>172</td> </tr> <tr> <td>264</td> <td>451</td> <td>233</td> </tr> <tr> <td>280</td> <td>511</td> <td>265</td> </tr> <tr> <td>--</td> <td>-</td> <td>-</td> </tr> </tbody> </table>				Input Voltage [V]	Hold-Up Time [ms]		Load 50%	Load 100%	75	23	9	85	33	14	100	51	23	120	79	38	200	250	126	230	336	172	264	451	233	280	511	265	--	-	-
Input Voltage [V]	Hold-Up Time [ms]																																		
	Load 50%	Load 100%																																	
75	23	9																																	
85	33	14																																	
100	51	23																																	
120	79	38																																	
200	250	126																																	
230	336	172																																	
264	451	233																																	
280	511	265																																	
--	-	-																																	
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																			



<p>Model PMA30F-15</p> <p>Item Instantaneous Interruption Compensation</p> <p>Object +15V2A</p>	<p>Temperature 25°C Testing Circuitry Figure A</p>																																																				
	<p>2.Values</p>																																																				
	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th><th colspan="3">Time [ms]</th></tr> <tr> <th>Input Volt. 100[V]</th><th>Input Volt. 200[V]</th><th>Input Volt. 230[V]</th></tr> </thead> <tbody> <tr><td>0.0</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>0.4</td><td>123</td><td>464</td><td>648</td></tr> <tr><td>0.8</td><td>65</td><td>264</td><td>364</td></tr> <tr><td>1.2</td><td>43</td><td>213</td><td>281</td></tr> <tr><td>1.6</td><td>30</td><td>162</td><td>212</td></tr> <tr><td>2.0</td><td>22</td><td>129</td><td>164</td></tr> <tr><td>2.2</td><td>21</td><td>114</td><td>137</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> <tr><td>--</td><td>-</td><td>-</td><td>-</td></tr> </tbody> </table>			Load Current [A]	Time [ms]			Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]	0.0	-	-	-	0.4	123	464	648	0.8	65	264	364	1.2	43	213	281	1.6	30	162	212	2.0	22	129	164	2.2	21	114	137	--	-	-	-	--	-	-	-	--	-	-	-	--	-	-
Load Current [A]	Time [ms]																																																				
	Input Volt. 100[V]	Input Volt. 200[V]	Input Volt. 230[V]																																																		
0.0	-	-	-																																																		
0.4	123	464	648																																																		
0.8	65	264	364																																																		
1.2	43	213	281																																																		
1.6	30	162	212																																																		
2.0	22	129	164																																																		
2.2	21	114	137																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
--	-	-	-																																																		
<p>1.Graph</p>																																																					
<p>Note: Slanted line shows the range of the rated load current.</p>																																																					



<table border="1"> <tr> <td>Model</td><td>PMA30F-15</td></tr> <tr> <td>Item</td><td>Minimum Input Voltage for Regulated Output Voltage</td></tr> <tr> <td>Object</td><td>+15V2A</td></tr> </table>	Model	PMA30F-15	Item	Minimum Input Voltage for Regulated Output Voltage	Object	+15V2A	Testing Circuitry Figure A																																
Model	PMA30F-15																																						
Item	Minimum Input Voltage for Regulated Output Voltage																																						
Object	+15V2A																																						
2.Values																																							
<table border="1"> <thead> <tr> <th rowspan="2">Ambient Temperature [°C]</th> <th colspan="2">Input Voltage [V]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>-20</td><td>45</td><td>54</td></tr> <tr> <td>-10</td><td>45</td><td>54</td></tr> <tr> <td>0</td><td>45</td><td>55</td></tr> <tr> <td>10</td><td>45</td><td>55</td></tr> <tr> <td>20</td><td>45</td><td>56</td></tr> <tr> <td>25</td><td>45</td><td>56</td></tr> <tr> <td>30</td><td>45</td><td>57</td></tr> <tr> <td>40</td><td>45</td><td>57</td></tr> <tr> <td>50</td><td>46</td><td>58</td></tr> <tr> <td>60</td><td>46</td><td>59</td></tr> <tr> <td>--</td><td>-</td><td>-</td></tr> </tbody> </table>		Ambient Temperature [°C]	Input Voltage [V]		Load 50%	Load 100%	-20	45	54	-10	45	54	0	45	55	10	45	55	20	45	56	25	45	56	30	45	57	40	45	57	50	46	58	60	46	59	--	-	-
Ambient Temperature [°C]	Input Voltage [V]																																						
	Load 50%	Load 100%																																					
-20	45	54																																					
-10	45	54																																					
0	45	55																																					
10	45	55																																					
20	45	56																																					
25	45	56																																					
30	45	57																																					
40	45	57																																					
50	46	58																																					
60	46	59																																					
--	-	-																																					
<p>1.Graph</p> <p>Note: Slanted line shows the range of the rated ambient temperature.</p>																																							


COSEL

Model	PMA30F-15																																										
Item	Overcurrent Protection	Temperature 25°C Testing Circuitry Figure A																																									
Object	+15V2A																																										
1.Graph																																											
<p>Output Voltage [V]</p> <p>Load Current [A]</p> <p>Input Volt. 100V</p> <p>Input Volt. 230V</p>																																											
<p>Note: Slanted line shows the range of the rated load current.</p>																																											
2.Values																																											
<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="2">Load Current [A]</th> </tr> <tr> <th>Input Volt. 100[V]</th> <th>Input Volt. 230[V]</th> </tr> </thead> <tbody> <tr><td>15.00</td><td>3.90</td><td>5.17</td></tr> <tr><td>14.25</td><td>-</td><td>-</td></tr> <tr><td>13.50</td><td>-</td><td>-</td></tr> <tr><td>12.00</td><td>-</td><td>-</td></tr> <tr><td>10.50</td><td>-</td><td>-</td></tr> <tr><td>9.00</td><td>-</td><td>-</td></tr> <tr><td>7.50</td><td>-</td><td>-</td></tr> <tr><td>6.00</td><td>-</td><td>-</td></tr> <tr><td>4.50</td><td>-</td><td>-</td></tr> <tr><td>3.00</td><td>-</td><td>-</td></tr> <tr><td>1.50</td><td>-</td><td>-</td></tr> <tr><td>0.00</td><td>-</td><td>-</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]		Input Volt. 100[V]	Input Volt. 230[V]	15.00	3.90	5.17	14.25	-	-	13.50	-	-	12.00	-	-	10.50	-	-	9.00	-	-	7.50	-	-	6.00	-	-	4.50	-	-	3.00	-	-	1.50	-	-	0.00	-	-
Output Voltage [V]	Load Current [A]																																										
	Input Volt. 100[V]	Input Volt. 230[V]																																									
15.00	3.90	5.17																																									
14.25	-	-																																									
13.50	-	-																																									
12.00	-	-																																									
10.50	-	-																																									
9.00	-	-																																									
7.50	-	-																																									
6.00	-	-																																									
4.50	-	-																																									
3.00	-	-																																									
1.50	-	-																																									
0.00	-	-																																									

COSEL

Model	PMA30F-15
Item	Ovvoltage Protection
Object	+15V2A

1.Graph



Note: Slanted line shows the range of the rated ambient temperature.

Testing Circuitry Figure A

2.Values

Ambient Temperature [°C]	Operating Point [V]	
	Input Volt. 100[V]	Input Volt. 230[V]
-20	22.89	22.82
-10	23.03	22.96
0	23.10	23.10
10	23.24	23.24
20	23.38	23.38
25	23.45	23.45
30	23.52	23.52
40	23.66	23.59
50	23.80	23.73
60	23.87	23.87
--	-	-

coSEL




Figure A




Figure B (IEC60601-1)