



# TEST DATA OF R100-3

(100V INPUT)

Regulated DC Power Supply

Jan. 24, 2000

Approved by : H. Shibutani  
Design Manager

Prepared by : Jun Uchida  
Design Engineer

コーワセル株式会社

COSEL CO., LTD.




## CONTENTS

1. Line Regulation . . . . .	1
静的入力変動	
2. Input Current (by Load Current) . . . . .	2
入力電流(負荷特性)	
3. Input Power (by Load Current) . . . . .	3
入力電力(負荷特性)	
4. Efficiency (by Input Voltage) . . . . .	4
効率(入力電圧特性)	
5. Efficiency (by Load Current) . . . . .	5
効率(負荷特性)	
6. Hold-Up Time . . . . .	6
出力保持時間	
7. Instantaneous Interruption Compensation . . . . .	7
瞬時停電保護	
8. Load Regulation . . . . .	8
静的負荷変動	
9. Overcurrent Protection . . . . .	9
過電流保護	
10. Inrush Current . . . . .	10
突入電流	
11. Rise and Fall Time . . . . .	11
立ち上り、立ち下り時間	
12. Ambient Temperature Drift . . . . .	12
周囲温度変動	
13. Minimum Input Voltage for Regulated Output Voltage . . . . .	13
最低レギュレーション電圧	
14. Time Lapse Drift . . . . .	14
経時ドリフト	
15. Output Voltage Accuracy . . . . .	15
定電圧精度	
16. Figure of Testing Circuitry . . . . .	16
測定回路図	

(Final Page 17 )

**COSEL**

Model	R100-3
Item	Line Regulation 静的输入变动
Object	+3.0V 20A



Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

Temperature 25°C  
Testing Circuitry Figure A

2. Values

Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	3.078	3.081
80	3.078	3.081
85	3.079	3.081
90	3.079	3.081
100	3.079	3.081
110	3.079	3.081
120	3.079	3.081
132	3.079	3.081
140	3.079	3.081

**COSEL**

Model	R100-3	Temperature Testing Circuitry 25°C Figure A																																																							
Item	Input Current (by Load Current) 入力電流 (負荷特性)																																																								
Object	—																																																								
1. Graph	<p style="text-align: center;">△ Input Volt. 85V □ Input Volt. 100V ○ Input Volt. 132V</p>	2. Values																																																							
<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>0.058</td><td>0.062</td><td>0.070</td></tr> <tr><td>4</td><td>0.462</td><td>0.423</td><td>0.370</td></tr> <tr><td>8</td><td>0.818</td><td>0.735</td><td>0.618</td></tr> <tr><td>12</td><td>1.163</td><td>1.040</td><td>0.861</td></tr> <tr><td>16</td><td>1.511</td><td>1.348</td><td>1.108</td></tr> <tr><td>20</td><td>1.860</td><td>1.654</td><td>1.355</td></tr> <tr><td>22</td><td>2.042</td><td>1.816</td><td>1.486</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Input Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	0.058	0.062	0.070	4	0.462	0.423	0.370	8	0.818	0.735	0.618	12	1.163	1.040	0.861	16	1.511	1.348	1.108	20	1.860	1.654	1.355	22	2.042	1.816	1.486	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Current [A]																																																								
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																						
0	0.058	0.062	0.070																																																						
4	0.462	0.423	0.370																																																						
8	0.818	0.735	0.618																																																						
12	1.163	1.040	0.861																																																						
16	1.511	1.348	1.108																																																						
20	1.860	1.654	1.355																																																						
22	2.042	1.816	1.486																																																						
—	—	—	—																																																						
—	—	—	—																																																						
—	—	—	—																																																						
—	—	—	—																																																						
—	—	—	—																																																						

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

**COSEL**

Model	R100-3	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Input Power (by Load Current) 入力電力 (負荷特性)																																																									
Object	—																																																									
1. Graph		2. Values																																																								
<p>The graph shows the relationship between Input Power (W) and Load Current (A) for three different input voltages: 85V, 100V, and 132V. The power increases linearly with load current for each voltage level. A slanted line on the graph indicates the range of the rated load current.</p>		<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Input Power [W]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>0</td><td>1.67</td><td>2.02</td><td>2.84</td></tr> <tr><td>4</td><td>17.08</td><td>17.77</td><td>19.36</td></tr> <tr><td>8</td><td>32.21</td><td>32.76</td><td>34.30</td></tr> <tr><td>12</td><td>47.81</td><td>48.25</td><td>49.50</td></tr> <tr><td>16</td><td>64.20</td><td>64.48</td><td>65.40</td></tr> <tr><td>20</td><td>81.20</td><td>81.00</td><td>81.60</td></tr> <tr><td>22</td><td>90.00</td><td>89.80</td><td>90.30</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>		Load Current [A]	Input Power [W]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	1.67	2.02	2.84	4	17.08	17.77	19.36	8	32.21	32.76	34.30	12	47.81	48.25	49.50	16	64.20	64.48	65.40	20	81.20	81.00	81.60	22	90.00	89.80	90.30	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Input Power [W]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
0	1.67	2.02	2.84																																																							
4	17.08	17.77	19.36																																																							
8	32.21	32.76	34.30																																																							
12	47.81	48.25	49.50																																																							
16	64.20	64.48	65.40																																																							
20	81.20	81.00	81.60																																																							
22	90.00	89.80	90.30																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

**COSEL**

Model	R100-3	Temperature	25°C																																
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																																
Object																																			
1. Graph	<p>Efficiency [%]</p> <p>Load 50%      Load 100%</p> <p>Input Voltage [V]</p>																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td><td>77.0</td><td>75.0</td></tr> <tr> <td>80</td><td>77.0</td><td>75.4</td></tr> <tr> <td>85</td><td>76.6</td><td>75.7</td></tr> <tr> <td>90</td><td>76.6</td><td>75.9</td></tr> <tr> <td>100</td><td>75.8</td><td>76.0</td></tr> <tr> <td>110</td><td>75.5</td><td>76.1</td></tr> <tr> <td>120</td><td>74.0</td><td>75.8</td></tr> <tr> <td>132</td><td>72.8</td><td>75.5</td></tr> <tr> <td>140</td><td>72.4</td><td>75.2</td></tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	77.0	75.0	80	77.0	75.4	85	76.6	75.7	90	76.6	75.9	100	75.8	76.0	110	75.5	76.1	120	74.0	75.8	132	72.8	75.5	140	72.4	75.2
Input Voltage [V]	Efficiency [%]																																		
	Load 50%	Load 100%																																	
75	77.0	75.0																																	
80	77.0	75.4																																	
85	76.6	75.7																																	
90	76.6	75.9																																	
100	75.8	76.0																																	
110	75.5	76.1																																	
120	74.0	75.8																																	
132	72.8	75.5																																	
140	72.4	75.2																																	

Note: Slanted line shows the range of the rated input voltage.

(注) 斜線は定格入力電圧範囲を示す。

**COSSEL**

Model	R100-3	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Efficiency (by Load Current) 効率(負荷特性)																																																									
Object																																																										
1. Graph	<p>Efficiency [%]</p> <p>Load Current [A]</p> <p>Legend: Input Volt. 85V (△), Input Volt. 100V (□), Input Volt. 132V (○)</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Efficiency [%]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>4</td><td>72.0</td><td>69.2</td><td>63.5</td></tr> <tr><td>8</td><td>76.4</td><td>75.1</td><td>71.8</td></tr> <tr><td>12</td><td>77.1</td><td>76.4</td><td>74.5</td></tr> <tr><td>16</td><td>76.7</td><td>76.4</td><td>75.4</td></tr> <tr><td>20</td><td>75.8</td><td>76.0</td><td>75.4</td></tr> <tr><td>22</td><td>75.3</td><td>75.5</td><td>75.0</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> <tr><td>—</td><td>—</td><td>—</td><td>—</td></tr> </tbody> </table>			Load Current [A]	Efficiency [%]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	4	72.0	69.2	63.5	8	76.4	75.1	71.8	12	77.1	76.4	74.5	16	76.7	76.4	75.4	20	75.8	76.0	75.4	22	75.3	75.5	75.0	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Efficiency [%]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
4	72.0	69.2	63.5																																																							
8	76.4	75.1	71.8																																																							
12	77.1	76.4	74.5																																																							
16	76.7	76.4	75.4																																																							
20	75.8	76.0	75.4																																																							
22	75.3	75.5	75.0																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							
—	—	—	—																																																							

Note: Slanted line shows the range of the rated load current


(注) 斜線は定格負荷電流範囲を示す。

**COSEL**

Model	R100-3	Temperature Testing Circuitry	25°C Figure A																																	
Item	Hold-Up Time 出力保持時間																																			
Object	+3.0V20A																																			
1. Graph		2. Values																																		
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr><td>75</td><td>48</td><td>21</td></tr> <tr><td>80</td><td>61</td><td>28</td></tr> <tr><td>85</td><td>74</td><td>34</td></tr> <tr><td>90</td><td>88</td><td>41</td></tr> <tr><td>100</td><td>119</td><td>57</td></tr> <tr><td>110</td><td>153</td><td>74</td></tr> <tr><td>120</td><td>191</td><td>93</td></tr> <tr><td>132</td><td>240</td><td>117</td></tr> <tr><td>140</td><td>275</td><td>136</td></tr> </tbody> </table>		Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	48	21	80	61	28	85	74	34	90	88	41	100	119	57	110	153	74	120	191	93	132	240	117	140	275	136
Input Voltage [V]	Hold-Up Time [mS]																																			
	Load 50%	Load 100%																																		
75	48	21																																		
80	61	28																																		
85	74	34																																		
90	88	41																																		
100	119	57																																		
110	153	74																																		
120	191	93																																		
132	240	117																																		
140	275	136																																		
<p>This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.</p> <p>Note: Slanted line shows the range of the rated input voltage.</p>																																				
<p>出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。</p> <p>(注)斜線は定格入力電圧範囲を示す。</p>																																				

COSEL

Model	R100-3
Item	Instantaneous Interruption Compensation 瞬時停電保障
Object	+3.0V 20A

Temperature 25°C  
Testing Circuitry Figure A

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.  
Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注) 斜線は定格負荷電流範囲を示す。

## 2. Values

Load Current [A]	Time [mS]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0	—	—	—
4	181	287	551
8	89	139	285
12	56	89	185
16	39	64	135
20	30	48	104
22	26	39	94
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

**COSEL**

Model	R100-3	Temperature Testing Circuitry      25°C Figure A																																																	
Item	Load Regulation 靜的負荷変動																																																		
Object	+3.0V20A																																																		
1. Graph	<p>Legend:</p> <ul style="list-style-type: none"> <li>Input Volt. 85 V</li> <li>Input Volt. 100 V</li> <li>Input Volt. 132 V</li> </ul>																																																		
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>3.082</td> <td>3.082</td> <td>3.082</td> </tr> <tr> <td>4</td> <td>3.081</td> <td>3.081</td> <td>3.080</td> </tr> <tr> <td>8</td> <td>3.080</td> <td>3.080</td> <td>3.080</td> </tr> <tr> <td>12</td> <td>3.079</td> <td>3.080</td> <td>3.079</td> </tr> <tr> <td>16</td> <td>3.078</td> <td>3.078</td> <td>3.078</td> </tr> <tr> <td>20</td> <td>3.077</td> <td>3.077</td> <td>3.077</td> </tr> <tr> <td>22</td> <td>3.077</td> <td>3.077</td> <td>3.077</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>				Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0	3.082	3.082	3.082	4	3.081	3.081	3.080	8	3.080	3.080	3.080	12	3.079	3.080	3.079	16	3.078	3.078	3.078	20	3.077	3.077	3.077	22	3.077	3.077	3.077	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																
0	3.082	3.082	3.082																																																
4	3.081	3.081	3.080																																																
8	3.080	3.080	3.080																																																
12	3.079	3.080	3.079																																																
16	3.078	3.078	3.078																																																
20	3.077	3.077	3.077																																																
22	3.077	3.077	3.077																																																
—	—	—	—																																																
—	—	—	—																																																
—	—	—	—																																																
Note:	Slanted line shows the range of the rated load current.																																																		
(注)	斜線は定格負荷電流範囲を示す。																																																		

**COSEL**

Model	R100-3	Temperature Testing Circuitry	25°C Figure A																																																							
Item	Overcurrent Protection 過電流保護																																																									
Object	+3.0V20A																																																									
1. Graph	<p>[V]      Input Volt. 85 V      Input Volt. 100 V      Input Volt. 132 V</p>																																																									
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Output Voltage [V]</th> <th colspan="3">Load Current [A]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr><td>3.00</td><td>25.45</td><td>25.49</td><td>25.52</td></tr> <tr><td>2.85</td><td>25.46</td><td>25.47</td><td>25.56</td></tr> <tr><td>2.70</td><td>25.46</td><td>25.43</td><td>25.52</td></tr> <tr><td>2.40</td><td>25.42</td><td>25.50</td><td>25.57</td></tr> <tr><td>2.10</td><td>25.47</td><td>25.48</td><td>25.57</td></tr> <tr><td>1.80</td><td>25.50</td><td>25.48</td><td>25.55</td></tr> <tr><td>1.50</td><td>25.56</td><td>25.49</td><td>25.73</td></tr> <tr><td>1.20</td><td>25.63</td><td>25.61</td><td>25.61</td></tr> <tr><td>0.90</td><td>25.58</td><td>25.50</td><td>25.50</td></tr> <tr><td>0.60</td><td>25.47</td><td>25.38</td><td>25.33</td></tr> <tr><td>0.30</td><td>25.27</td><td>25.06</td><td>24.93</td></tr> <tr><td>0.00</td><td>25.04</td><td>24.92</td><td>24.98</td></tr> </tbody> </table>			Output Voltage [V]	Load Current [A]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	3.00	25.45	25.49	25.52	2.85	25.46	25.47	25.56	2.70	25.46	25.43	25.52	2.40	25.42	25.50	25.57	2.10	25.47	25.48	25.57	1.80	25.50	25.48	25.55	1.50	25.56	25.49	25.73	1.20	25.63	25.61	25.61	0.90	25.58	25.50	25.50	0.60	25.47	25.38	25.33	0.30	25.27	25.06	24.93	0.00	25.04	24.92	24.98
Output Voltage [V]	Load Current [A]																																																									
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																																							
3.00	25.45	25.49	25.52																																																							
2.85	25.46	25.47	25.56																																																							
2.70	25.46	25.43	25.52																																																							
2.40	25.42	25.50	25.57																																																							
2.10	25.47	25.48	25.57																																																							
1.80	25.50	25.48	25.55																																																							
1.50	25.56	25.49	25.73																																																							
1.20	25.63	25.61	25.61																																																							
0.90	25.58	25.50	25.50																																																							
0.60	25.47	25.38	25.33																																																							
0.30	25.27	25.06	24.93																																																							
0.00	25.04	24.92	24.98																																																							

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

**COSEL**

Model R100-3

Item Inrush Current 突入電流


Object \_\_\_\_\_

Temperature 25°C  
Testing Circuitry Figure AInput  
Current

[20A/div]

Input  
Voltage

[200V/div]



Input Voltage 100 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 13.44 [A]

② 9.44 [A]





COSEL

Model	R100-3
Item	Rise and Fall Time 立上り、立下り時間
Object	+3.0V20A


Temperature 25°C  
Testing Circuitry Figure A

## 1. Graph




## 2. Values

Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		120.0	0.8	120.8	75.2	3.0	
100 %		120.0	0.8	120.8	34.5	1.5	



**COSEL**

Model	R100-3	Testing Circuitry      Figure A					
Item	Ambient Temperature Drift 周囲温度変動						
Object	+3.0V 20A						
<b>1. Graph</b>							
		—△— Input Volt. 85V -□- Input Volt. 100V ○ Input Volt. 132V					
							
		Output Voltage [V]					
		Ambient Temperature [°C]					
		Load 100%					
Note: Slanted line shows the range of the rated ambient temperature.							
(注)斜線は定格周囲温度範囲を示す。							
2. Values							
Ambient Temperature [°C]	Output Voltage [V]						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]				
-20	3.075	3.075	3.075				
-10	3.076	3.076	3.077				
0	3.078	3.078	3.078				
10	3.079	3.079	3.079				
20	3.080	3.080	3.080				
25	3.081	3.081	3.081				
30	3.081	3.081	3.081				
40	3.082	3.082	3.082				
50	3.083	3.083	3.083				
60	3.084	3.084	3.085				
—	—	—	—				


**COSEL**

Model R100-3

Item Minimum Input Voltage for Regulated Output Voltage  
最低レギュレーション電圧

Object +3.0V20A

## 1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注)斜線は定格周囲温度範囲を示す。

## Testing Circuitry Figure A

## 2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	57	61
-10	56	60
0	55	59
10	54	59
20	54	58
25	53	58
30	53	58
40	53	57
50	53	57
60	53	57
—	—	—

**COSEL**

Model	R100-3	Temperature	25°C																																												
Item	Time Lapse Drift 経時ドリフト	Testing Circuitry	Figure A																																												
Object	+3.0V 20A																																														
1. Graph			2. Values																																												
<p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <table> <tr><td>0</td><td>1</td><td>2</td><td>3</td><td>4</td><td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td></tr> <tr><td>3.150</td><td>3.130</td><td>3.110</td><td>3.090</td><td>3.070</td><td>3.050</td><td>3.030</td><td>0</td><td>0</td><td>0</td><td>0</td></tr> </table> <p>Input Volt. 100V Load 100%</p>			0	1	2	3	4	5	6	7	8	9	10	3.150	3.130	3.110	3.090	3.070	3.050	3.030	0	0	0	0	<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.083</td></tr> <tr><td>0.5</td><td>3.084</td></tr> <tr><td>1.0</td><td>3.084</td></tr> <tr><td>2.0</td><td>3.084</td></tr> <tr><td>3.0</td><td>3.084</td></tr> <tr><td>4.0</td><td>3.084</td></tr> <tr><td>5.0</td><td>3.084</td></tr> <tr><td>6.0</td><td>3.084</td></tr> <tr><td>7.0</td><td>3.084</td></tr> <tr><td>8.0</td><td>3.084</td></tr> </tbody> </table>	Time since start [H]	Output Voltage [V]	0.0	3.083	0.5	3.084	1.0	3.084	2.0	3.084	3.0	3.084	4.0	3.084	5.0	3.084	6.0	3.084	7.0	3.084	8.0	3.084
0	1	2	3	4	5	6	7	8	9	10																																					
3.150	3.130	3.110	3.090	3.070	3.050	3.030	0	0	0	0																																					
Time since start [H]	Output Voltage [V]																																														
0.0	3.083																																														
0.5	3.084																																														
1.0	3.084																																														
2.0	3.084																																														
3.0	3.084																																														
4.0	3.084																																														
5.0	3.084																																														
6.0	3.084																																														
7.0	3.084																																														
8.0	3.084																																														



Model	R100-3	Testing Circuitry Figure A
Item	Output Voltage Accuracy 定電圧精度	
Object	+3.0V20A	

### 1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~20 A

\* Output Voltage Accuracy = ±(Maximum of Output Voltage — Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

### 1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~20 A

\* 定電圧精度(変動値) = ±(出力電圧の最高値—出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

### 2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	50	100	20	3.083		
Minimum Voltage	-10	85	0	3.073	±5	±0.2

COSEL





Figure B (DENTORI)




Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E