



M T B F

(E I A J R C R - 9 1 0 2)

| | |
|-------|---------|
| Model | R150-24 |
|-------|---------|

| No. | P a r t s | | Q'ty of Device | Failure rate [10 ⁻⁶ /H] | R e f e r e n c e |
|--|------------------------|------------|----------------|------------------------------------|-------------------|
| 1 | I C | Monolithic | 2 | 0.0650 | |
| 2 | | Hybrid | 0 | 0.0000 | |
| 3 | T r a n s i s t o r s | | 2 | 0.1001 | |
| 4 | D i o d e s | | 13 | 0.4440 | |
| 5 | LED•Optocouplers | | 3 | 0.1412 | |
| 6 | R e s i s t o r s | | 33 | 0.4998 | |
| 7 | C a p a c i t o r s | | 26 | 0.3804 | |
| 8 | Transformer•Choke Coil | | 21 | 0.1518 | |
| 9 | C o n n e c t o r s | | 239 | 0.1232 | |
| 10 | O t h e r s | | 2 | 0.0230 | |
| Total Failure Rate [10 ⁻⁶ /H] | | | | 1.9285 | |

| | | |
|---------------------|------|---------|
| M T B F | [H] | 519,000 |
| Ambient Temperature | [°C] | — |
| Load Factor | [%] | — |