



TEST DATA OF R15A-3
(100V INPUT)

Regulated DC Power Supply

Jan. 13, 2000

Approved by : H. Shibutani
Design Manager

Prepared by : Jun Aohida
Design Engineer

コーセル株式会社

COSEL CO., LTD.



C O N T E N T S


1. Line Regulation	1
静的入力変動	
2. Input Current (by Load Current)	2
入力電流 (負荷特性)	
3. Input Power (by Load Current)	3
入力電力 (負荷特性)	
4. Efficiency (by Input Voltage)	4
効率 (入力電圧特性)	
5. Efficiency (by Load Current)	5
効率 (負荷特性)	
6. Hold-Up Time	6
出力保持時間	
7. Instantaneous Interruption Compensation	7
瞬時停電保障	
8. Load Regulation	8
静的負荷変動	
9. Overcurrent Protection	9
過電流保護	
10. Inrush Current	10
突入電流	
11. Rise and Fall Time	11
立ち上り、立下り時間	
12. Ambient Temperature Drift	12
周囲温度変動	
13. Minimum Input Voltage for Regulated Output Voltage	13
最低レギュレーション電圧	
14. Time Lapse Drift	14
経時ドリフト	
15. Output Voltage Accuracy	15
定電圧精度	
16. Figure of Testing Circuitry	16
測定回路図	

(Final Page 17)

COSEL

Model	R15A-3
Item	Line Regulation 静的入力変動
Object	+3.0V3A

Temperature 25°C
Testing Circuitry Figure A



2. Values


Input Voltage [V]	Output Voltage [V]	
	Load 50%	Load 100%
75	3.071	3.062
80	3.071	3.063
85	3.071	3.064
90	3.071	3.065
100	3.072	3.066
110	3.072	3.066
120	3.072	3.066
132	3.072	3.067
140	3.072	3.067

Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	R15A-3
Item	Input Current (by Load Current) 入力電流 (負荷特性)
Object	—



Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A


2. Values

Load Current [A]	Input Current [A]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	0.036	0.038	0.041
0.6	0.083	0.080	0.076
1.2	0.128	0.118	0.107
1.8	0.174	0.158	0.137
2.4	0.224	0.200	0.169
3.0	0.275	0.244	0.203
3.3	0.302	0.267	0.220
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	R15A-3
Item	Input Power (by Load Current) 入力電力（負荷特性）
Object	_____

1. Graph



Note: Slanted line shows the range of the rated load current

(注)斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Load Current [A]	Input Power [W]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.0	1.26	1.52	2.08
0.6	3.46	3.71	4.40
1.2	5.71	5.93	6.55
1.8	8.14	8.26	8.74
2.4	10.72	10.76	11.09
3.0	13.45	13.39	13.60
3.3	14.85	14.76	14.89
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

COSEL

Model	R15A-3	Temperature	25°C																															
Item	Efficiency (by Input Voltage) 効率(入力電圧特性)	Testing Circuitry	Figure A																															
Object																																		
1. Graph	<p>Efficiency [%]</p> <p>Input Voltage [V]</p>																																	
<p>2. Values</p> <table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Efficiency [%]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>65.3</td> <td>65.6</td> </tr> <tr> <td>80</td> <td>65.2</td> <td>66.2</td> </tr> <tr> <td>85</td> <td>64.7</td> <td>66.5</td> </tr> <tr> <td>90</td> <td>64.4</td> <td>66.7</td> </tr> <tr> <td>100</td> <td>63.4</td> <td>66.8</td> </tr> <tr> <td>110</td> <td>62.0</td> <td>66.7</td> </tr> <tr> <td>120</td> <td>60.5</td> <td>66.4</td> </tr> <tr> <td>132</td> <td>58.6</td> <td>65.9</td> </tr> <tr> <td>140</td> <td>57.4</td> <td>65.3</td> </tr> </tbody> </table>			Input Voltage [V]	Efficiency [%]		Load 50%	Load 100%	75	65.3	65.6	80	65.2	66.2	85	64.7	66.5	90	64.4	66.7	100	63.4	66.8	110	62.0	66.7	120	60.5	66.4	132	58.6	65.9	140	57.4	65.3
Input Voltage [V]	Efficiency [%]																																	
	Load 50%	Load 100%																																
75	65.3	65.6																																
80	65.2	66.2																																
85	64.7	66.5																																
90	64.4	66.7																																
100	63.4	66.8																																
110	62.0	66.7																																
120	60.5	66.4																																
132	58.6	65.9																																
140	57.4	65.3																																


Note: Slanted line shows the range of the rated input voltage.

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	R15A-3
Item	Efficiency (by Load Current) 効率(負荷特性)
Object	_____

Temperature 25°C
Testing Circuitry Figure A



2. Values

Load Current [A]	Efficiency [%]		
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]
0.6	51.4	48.0	40.6
1.2	62.7	60.4	54.7
1.8	65.9	65.0	61.4
2.4	66.7	66.5	64.5
3.0	66.3	66.7	65.7
3.3	66.1	66.5	66.0
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—

Note: Slanted line shows the range of the rated load current

(注) 斜線は定格負荷電流範囲を示す。

COSSEL

Model	R15A-3	Temperature Testing Circuitry	25°C Figure A																																
Item	Hold-Up Time 出力保持時間																																		
Object	+3.0V3A																																		
1. Graph	<p>Graph showing Hold-Up Time [mS] vs Input Voltage [V]. The Y-axis is logarithmic, ranging from 1 to 1000 mS. The X-axis ranges from 0 to 150 V. Two data series are shown: Load 50% (squares) and Load 100% (triangles). Both series show an increasing trend as input voltage increases. A slanted line indicates the rated input voltage range.</p>	2. Values																																	
2. Values																																			
			<table border="1"> <thead> <tr> <th rowspan="2">Input Voltage [V]</th> <th colspan="2">Hold-Up Time [mS]</th> </tr> <tr> <th>Load 50%</th> <th>Load 100%</th> </tr> </thead> <tbody> <tr> <td>75</td> <td>71</td> <td>26</td> </tr> <tr> <td>80</td> <td>82</td> <td>32</td> </tr> <tr> <td>85</td> <td>93</td> <td>37</td> </tr> <tr> <td>90</td> <td>106</td> <td>43</td> </tr> <tr> <td>100</td> <td>132</td> <td>57</td> </tr> <tr> <td>110</td> <td>161</td> <td>72</td> </tr> <tr> <td>120</td> <td>193</td> <td>88</td> </tr> <tr> <td>132</td> <td>233</td> <td>110</td> </tr> <tr> <td>140</td> <td>262</td> <td>126</td> </tr> </tbody> </table>	Input Voltage [V]	Hold-Up Time [mS]		Load 50%	Load 100%	75	71	26	80	82	32	85	93	37	90	106	43	100	132	57	110	161	72	120	193	88	132	233	110	140	262	126
Input Voltage [V]	Hold-Up Time [mS]																																		
	Load 50%	Load 100%																																	
75	71	26																																	
80	82	32																																	
85	93	37																																	
90	106	43																																	
100	132	57																																	
110	161	72																																	
120	193	88																																	
132	233	110																																	
140	262	126																																	

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated input voltage.

出力保持時間とは、入力電圧断から出力電圧が、定電圧精度の規格範囲を保持しているところまでの時間。

(注)斜線は定格入力電圧範囲を示す。

COSEL

Model	R15A-3	Temperature Testing Circuitry	25°C Figure A																										
Item	Instantaneous Interruption Compensation 瞬時停電保障																												
Object	+3.0V3A	2. Values																											
1. Graph	<p style="text-align: center;"> △ Input Volt. 85 V □ Input Volt. 100 V ○ Input Volt. 132 V </p> <table border="1"> <caption>Data extracted from Figure A graph</caption> <thead> <tr> <th>Load Current [A]</th> <th>Input Volt. 85[V] [ms]</th> <th>Input Volt. 100[V] [ms]</th> <th>Input Volt. 132[V] [ms]</th> </tr> </thead> <tbody> <tr><td>0.6</td><td>201</td><td>276</td><td>459</td></tr> <tr><td>1.2</td><td>111</td><td>157</td><td>276</td></tr> <tr><td>1.8</td><td>72</td><td>104</td><td>190</td></tr> <tr><td>2.4</td><td>48</td><td>73</td><td>139</td></tr> <tr><td>3.0</td><td>31</td><td>51</td><td>104</td></tr> <tr><td>3.3</td><td>22</td><td>39</td><td>90</td></tr> </tbody> </table>	Load Current [A]	Input Volt. 85[V] [ms]	Input Volt. 100[V] [ms]	Input Volt. 132[V] [ms]	0.6	201	276	459	1.2	111	157	276	1.8	72	104	190	2.4	48	73	139	3.0	31	51	104	3.3	22	39	90
Load Current [A]	Input Volt. 85[V] [ms]	Input Volt. 100[V] [ms]	Input Volt. 132[V] [ms]																										
0.6	201	276	459																										
1.2	111	157	276																										
1.8	72	104	190																										
2.4	48	73	139																										
3.0	31	51	104																										
3.3	22	39	90																										
		Load Current [A]	Time [mS]																										
		Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																									
0.0	—	—	—																										
0.6	201	276	459																										
1.2	111	157	276																										
1.8	72	104	190																										
2.4	48	73	139																										
3.0	31	51	104																										
3.3	22	39	90																										
—	—	—	—																										
—	—	—	—																										
—	—	—	—																										
—	—	—	—																										

This duration covers from Shut-off of input voltage to the moment when output voltage descends to the rated range of voltage accuracy.

Note: Slanted line shows the range of the rated load current.

瞬時停電保障時間とは、出力電圧が定電圧精度の規格範囲を保持している瞬時停電時間をいう。

(注) 斜線は定格負荷電流範囲を示す。

COSEL


Model	R15A-3	Temperature	25°C																																															
Item	Load Regulation 靜的負荷変動	Testing Circuitry	Figure A																																															
Object	+3.0V 3A																																																	
1. Graph	<p>—△— Input Volt. 85 V —□— Input Volt. 100 V —○— Input Volt. 132 V</p>																																																	
2. Values	<table border="1"> <thead> <tr> <th rowspan="2">Load Current [A]</th> <th colspan="3">Output Voltage [V]</th> </tr> <tr> <th>Input Volt. 85[V]</th> <th>Input Volt. 100[V]</th> <th>Input Volt. 132[V]</th> </tr> </thead> <tbody> <tr> <td>0.0</td> <td>3.078</td> <td>3.078</td> <td>3.078</td> </tr> <tr> <td>0.6</td> <td>3.075</td> <td>3.075</td> <td>3.075</td> </tr> <tr> <td>1.2</td> <td>3.073</td> <td>3.073</td> <td>3.073</td> </tr> <tr> <td>1.8</td> <td>3.070</td> <td>3.071</td> <td>3.071</td> </tr> <tr> <td>2.4</td> <td>3.068</td> <td>3.068</td> <td>3.069</td> </tr> <tr> <td>3.0</td> <td>3.064</td> <td>3.066</td> <td>3.067</td> </tr> <tr> <td>3.3</td> <td>3.062</td> <td>3.064</td> <td>3.065</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> <tr> <td>—</td> <td>—</td> <td>—</td> <td>—</td> </tr> </tbody> </table>			Load Current [A]	Output Voltage [V]			Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]	0.0	3.078	3.078	3.078	0.6	3.075	3.075	3.075	1.2	3.073	3.073	3.073	1.8	3.070	3.071	3.071	2.4	3.068	3.068	3.069	3.0	3.064	3.066	3.067	3.3	3.062	3.064	3.065	—	—	—	—	—	—	—	—	—	—	—	—
Load Current [A]	Output Voltage [V]																																																	
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]																																															
0.0	3.078	3.078	3.078																																															
0.6	3.075	3.075	3.075																																															
1.2	3.073	3.073	3.073																																															
1.8	3.070	3.071	3.071																																															
2.4	3.068	3.068	3.069																																															
3.0	3.064	3.066	3.067																																															
3.3	3.062	3.064	3.065																																															
—	—	—	—																																															
—	—	—	—																																															
—	—	—	—																																															

Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

COSSEL

Model	R15A-3
Item	Overcurrent Protection 過電流保護
Object	+3.0V3A



Note: Slanted line shows the range of the rated load current.

(注)斜線は定格負荷電流範囲を示す。

Temperature 25°C
Testing Circuitry Figure A

2. Values

Output Voltage [V]	Load Current [A]		
	Input Volt. 85 [V]	Input Volt. 100 [V]	Input Volt. 132 [V]
3.00	4.13	4.46	4.32
2.85	4.10	4.42	4.26
2.70	4.07	4.37	4.21
2.40	3.99	4.26	4.09
2.10	3.90	4.14	3.98
1.80	3.78	3.99	3.83
1.50	3.62	3.81	3.66
1.20	3.43	3.59	3.46
0.90	3.20	3.33	3.23
0.60	2.96	3.06	2.99
0.30	2.65	2.72	2.69
0.00	3.01	3.07	2.92

COSEL

Model R15A-3

Item Inrush Current 突入電流

Object


Temperature 25°C
Testing Circuitry Figure A

Input Current

[20A/div]

Input Voltage

[200V/div]



Input Voltage 100 V


Frequency 60 Hz

Load 100 %

Inrush Current

① 11.25 [A]

② 0.75 [A]




COSEL

Model	R15A-3
Item	Rise and Fall Time 立上り、立下り時間
Object	+3.0V3A


Temperature 25°C
Testing Circuitry Figure A

1. Graph




2. Values

Load	Time	T d	T r	T s	T h	T f	[mS]
50 %		2.8	2.5	5.3	94.0	11.6	
100 %		2.8	3.3	6.0	37.2	18.1	



COSEL

Model	R15A-3	Testing Circuitry Figure A					
Item	Ambient Temperature Drift 周囲温度変動						
Object	+3.0V 3A						
1. Graph							
		Input Volt. 85V Input Volt. 100V Input Volt. 132V					
	[V]						
		Load 100%					
Note: Slanted line shows the range of the rated ambient temperature.							
(注) 斜線は定格周囲温度範囲を示す。							
2. Values							
Ambient Temperature [°C]	Output Voltage [V]						
	Input Volt. 85[V]	Input Volt. 100[V]	Input Volt. 132[V]				
-20	3.057	3.059	3.062				
-10	3.059	3.061	3.063				
0	3.061	3.063	3.064				
10	3.062	3.064	3.065				
20	3.063	3.065	3.066				
25	3.064	3.065	3.066				
30	3.064	3.066	3.067				
40	3.064	3.066	3.067				
50	3.065	3.066	3.067				
60	3.065	3.067	3.068				
—	—	—	—				


COSSEL

Model R15A-3

Item Minimum Input Voltage for Regulated Output Voltage
最低レギュレーション電圧

Object +3.0V 3A

1. Graph



Note: Slanted line shows the range of the rated ambient temperature.

(注) 斜線は定格周囲温度範囲を示す。

Testing Circuitry Figure A

2. Values

Ambient Temperature [°C]	Input Voltage [V]	
	Load 50%	Load 100%
-20	27	50
-10	27	50
0	27	50
10	27	51
20	27	51
25	27	51
30	27	52
40	27	52
50	27	53
60	27	54
—	—	—

COSEL

Model	R15A-3	Temperature Testing Circuitry	25°C Figure A																						
Item	Time Lapse Drift 経時ドリフト																								
Object	+3.0V3A																								
1. Graph																									
<p>[V]</p> <p>Output Voltage [V]</p> <p>Time [H]</p> <p>Input Volt. 100V Load 100%</p>																									
2. Values																									
<table border="1"> <thead> <tr> <th>Time since start [H]</th> <th>Output Voltage [V]</th> </tr> </thead> <tbody> <tr><td>0.0</td><td>3.064</td></tr> <tr><td>0.5</td><td>3.064</td></tr> <tr><td>1.0</td><td>3.064</td></tr> <tr><td>2.0</td><td>3.064</td></tr> <tr><td>3.0</td><td>3.064</td></tr> <tr><td>4.0</td><td>3.064</td></tr> <tr><td>5.0</td><td>3.064</td></tr> <tr><td>6.0</td><td>3.064</td></tr> <tr><td>7.0</td><td>3.064</td></tr> <tr><td>8.0</td><td>3.064</td></tr> </tbody> </table>				Time since start [H]	Output Voltage [V]	0.0	3.064	0.5	3.064	1.0	3.064	2.0	3.064	3.0	3.064	4.0	3.064	5.0	3.064	6.0	3.064	7.0	3.064	8.0	3.064
Time since start [H]	Output Voltage [V]																								
0.0	3.064																								
0.5	3.064																								
1.0	3.064																								
2.0	3.064																								
3.0	3.064																								
4.0	3.064																								
5.0	3.064																								
6.0	3.064																								
7.0	3.064																								
8.0	3.064																								



Model	R15A-3
Item	Output Voltage Accuracy 定電圧精度
Object	+3.0V3A

Testing Circuitry Figure A

1. Output Voltage Accuracy

This is defined as the value of the output voltage, regulation load, ambient temperature and input voltage varied at random in the range as specified below.

Temperature : -10~50 °C

Input Voltage : 85~132 V

Load Current : 0~3 A

* Output Voltage Accuracy = ±(Maximum of Output Voltage - Minimum of Output Voltage) / 2

$$* \text{ Output Voltage Accuracy (Ration)} = \frac{\text{Output Voltage Accuracy}}{\text{Rated Output Voltage}} \times 100$$

1. 定電圧精度

周囲温度、入力電圧、負荷電流を下記仕様内で、任意に変動させたときの出力電圧の変動をいう。

周囲温度 -10~50 °C

入力電圧 85~132 V

負荷電流 0~3 A

* 定電圧精度(変動値) = ±(出力電圧の最高値-出力電圧の最低値) / 2

$$* \text{ 定電圧精度(変動率)} = \frac{\text{変動値}}{\text{定格出力電圧}} \times 100$$

2. Values

Item	Temperature [°C]	Input Voltage [V]	Output Current [A]	Output Voltage [V]	Output Voltage Accuracy [mV]	Output Voltage Accuracy(Ration) [%]
Maximum Voltage	50	132	0	3.079		
Minimum Voltage	-10	85	3	3.059	±10	±0.4

COSEL





Figure B (DENTORI)




Figure B (IEC 60950)

COSEL




Figure C




Figure D




Figure E